On Kernel's Safety in the Spectre Era (And KASLR is Formally Dead)

Davide Davoli, Martin Avanzini, and Tamara Rezk

Inria, Université Côte d'Azur

June 12, 2024

Abstract

The efficacy of address space layout randomization has been formally demonstrated in a sharedmemory model by Abadi et al., contingent on specific assumptions about victim programs. However, modern operating systems, implementing layout randomization in the kernel, diverge from these assumptions and operate on a separate memory model with communication through system calls. In this work, we relax Abadi et al.'s language assumptions while demonstrating that layout randomization offers a comparable safety guarantee in a system with memory separation. However, in practice, speculative execution and side-channels are recognized threats to layout randomization. We show that kernel safety cannot be restored for attackers capable of using side-channels and speculative execution and introduce a new condition, that allows us to formally prove kernel safety in the Spectre era. Our research demonstrates that under this condition, the system remains safe without relying on layout randomization. We also demonstrate that our condition can be sensibly weakened, leading to enforcement mechanisms that can guarantee kernel safety for safe system calls in the Spectre era.

1 Introduction

Memory safety violations on kernel memory can result in serious ramifications for security, such as e.g. arbitrary code execution, privilege escalation, or information leakage. In order to mitigate safety violations, operating systems — such as Linux — employ address space layout randomization [\[19](#page-22-0), [30,](#page-23-0) [47](#page-25-0), [42](#page-24-0), [18,](#page-22-1) [43\]](#page-24-1). This protection measure can prevent attacks that depend on knowledge of specific data or function location, as it introduces randomization of these addresses.

On the one hand, the efficacy of layout randomization has been formally demonstrated in Abadi et al.'s line of work [\[2](#page-21-0), [1,](#page-21-1) [4\]](#page-21-2), as a protective measure within a shared-memory model between the attacker and the victim. These results, however, are contingent on specific assumptions regarding victim programs, notably the absence of pointer arithmetic, introspection, or indirect jumps. These precise constraints shaped a controlled environment where memory safety could be enforced effectively via layout randomization. However, operating systems employing layout randomization on kernel (a.k.a. KASLR in Linux e.g. [\[19](#page-22-0)]) diverge from these assumptions. Notably, they operate on a separate memory model, wherein, kernel code $-$ acting as the victim $-$ resides on kernel memory, while user code — acting as the potential attacker — resides in user space. The interaction between the two occurs through a limited set of functions provided via interfaces or system calls [\[55\]](#page-25-1). In the operating system's realm, system calls may be written in C and assembly code, further deviating from the restricted conditions outlined by Abadi et al. This introduces a distinction not only in the expressiveness of victim code considered but also in the underlying memory model.

Hence, our first research question emerges: can we relax the language assumptions proposed by Abadi et al. [\[2,](#page-21-0) [1](#page-21-1), [4](#page-21-2)] while concurrently demonstrating that layout randomization offers a comparable safety guarantee in a system with memory separation? We affirmatively respond to this question by showcasing that layout randomization probabilistically ensures kernel safety within a classic attacker model, where users of an operating system execute without privileges and victims can feature pointer arithmetic, introspection, and indirect jumps.

On the other hand, in the current state-of-the-art of security, often referred to as the Spectre era, speculative execution and side-channels are well known to be effective vectors for compromising layout randomization [\[24](#page-23-1), [37,](#page-24-2) [25](#page-23-2), [39,](#page-24-3) [34](#page-23-3), [38\]](#page-24-4). Indeed, our first result neglects the impact of speculative execution and side-channels. Recognizing this limitation, our second research question arises: can we restore a similar safety result in the Spectre era?

In this regard, we formally acknowledge that by relying solely on layout randomization it is not possible to restore kernel safety. We then introduce a new condition, called speculative layout noninterference akin to speculative constant-time [\[14](#page-22-2)], which intuitively asserts that victims should not unintentionally leak information on the kernel's layout through side-channels. Our research formally demonstrates that under this assumption, the system is safe, and perhaps surprisingly, without the necessity of layout randomization. Later, we show that speculative layout non-interference is not a necessary requirement, and this motivates us to study how safety can be enforced without requiring that property.

Our third contribution is to show that kernels can be protected even without requiring speculative layout non-interference. Following other similar works [\[57,](#page-25-2) [17](#page-22-3)], we do so by relating safety in the classic execution model to the speculative one. We achieve this result by defining a program transformation by which we enforce safety against speculative attackers on a system that does not conform to this property. This transformation, in turn, requires the system to enjoy a notion of safety that cannot be provided by layout randomization, but that is sensibly weaker than the safety property it enforces. This marks the first formal step toward strengthening kernel safety in the presence of speculative and side-channel vulnerabilities, and the surpassing of layout randomization as a system level protection mechanism.

In summary, our contributions are:

- We formally demonstrate the effectiveness of layout randomization to provide kernel safety for a classic operating system scenario, with system calls offered as interfaces to attackers and different privilege execution modes, as well as kernel and user memory separation.
- We empower attackers in our first scenario to execute side-channel attacks and utilize speculative execution. Demonstrating that kernel safety is not maintained under this more potent attacker model, we subsequently present a sufficient condition to ensure kernel safety.
- We show that it is possible to enforce safety against speculative attackers on a system that enjoys weaker security guarantees by the application of a program transformation.

The paper is structured as follows: in Section [2](#page-2-0) we give an overview of the contributions of this paper, motivated by some concrete examples. In Section [3,](#page-4-0) we introduce our execution model by giving its language and semantics; in Section [4,](#page-8-0) we establish threat models. Section [5](#page-9-0) is devoted to showing that layout randomization is an effective protection measure for attacks that do not rely on speculative execution and side-channel observations. In Section [6](#page-11-0) we first extend the model of Section [3](#page-4-0) to encompass time-channel info leaks and speculative execution, then we show that layout randomization is not a viable protection mechanism in this scenario. In Section [7](#page-17-0) we show that it is feasible to convert any system that is safe against classic attackers into an equivalent system that is safe against speculative attackers. Finally, we consider related work in Section [8,](#page-19-0) and we conclude in Section [9.](#page-20-0)

```
int buf [K+1] [H];
int recv (socket* s, size_t idx) {
  if (valid(s, idx)) return buf [*s][idx];
  return 0;
}
void send (socket* s, size_t idx, int msg) {
  if (valid(s, idx)) {
    buf [*s][idx] = msg;if (buf[K][0] != NULL) (*but [K][0])(s, idx);}
}
```
Figure 1: System Calls vulnerable to memory corruption

2 Motivation

Each year, dozens of vulnerabilities are found in commodity operating systems' kernels, and the majority of them are memory corruption vulnerabilities [\[53\]](#page-25-3). A kernel suffers a memory corruption vulnerability when an unprivileged attacker can trigger it to read or write its memory in an unexpected way, usually, by issuing a sequence of system calls with maliciously crafted arguments. In Figure [1,](#page-2-1) we show a pair of system calls of a hypothetical system that are subject to this kind of vulnerability. The recv and send system calls are meant to implement a simple message passing protocol. The implementation supports up to K sockets, each socket storing up to H messages. A user can send messages by invoking the system call send, and read them with the system call recv. These system calls employ a shared buffer buf that stores messages, together with a hook for a customizable callback buf[K][0]. If specified, this callback is executed after a message is sent. Such a callback may, for instance, signal the receiver that a new message is available.

These system calls are meant to interact only with the memory containing the buffer, the code of the called functions and with the resources that these function in turn access. In the following, we will refer to the set of memory resources that a system call may access rightfully as the *capabilities* of that system call. Depending on the implementation of the valid function, these system calls can suffer from memory corruption vulnerabilities. For instance, if the valid function does not perform any bound checks on the value of idx, these two system calls can be used by the attacker to perform arbitrary read and write operations. In particular, if the attacker supplies an out-of-bounds value for idx to the recv system call, the system call can be used to perform an unrestricted memory read. Similarly, the send system call can be used to overwrite any value of kernel memory and, in particular, to overwrite the function pointer to the callback that is stored within the buffer. This means that the attacker can turn this memory-vulnerability into a control-flow vulnerability, as it can deviate the control flow from its intended paths. When this happens, we talk about violations of control flow integrity (CFI) [\[3\]](#page-21-3).

However, if the system that implements these system calls is protected with layout randomization such as many commodity operating systems $[19, 30, 47, 42, 18, 43]$ $[19, 30, 47, 42, 18, 43]$ $[19, 30, 47, 42, 18, 43]$ $[19, 30, 47, 42, 18, 43]$ $[19, 30, 47, 42, 18, 43]$ $[19, 30, 47, 42, 18, 43]$ $[19, 30, 47, 42, 18, 43]$ $[19, 30, 47, 42, 18, 43]$ — the exploitation of these vulnerabilities is not a straightforward operation. For instance, if an attacker wants to mount a privilege-escalation attack, one of the viable ways is to disable the SMEP protection by running the native_write_cr4 function. When this protection is disabled, the attacker is allowed to run any payload stored in user-space. To this aim, the attacker can use the send system call twice: the first time to run the native_write_cr4 function instead of the callback, and the second time to run the payload. However, in order to do so, the attacker has to first infer the address of native_write_cr4. In the absence of side channel info-leaks, an attacker has to effectively guess this address and, due to layout randomization, the probability of success is low.

This is what we show with our first result (Theorem [1\)](#page-10-0): without side-channel leaks (and speculative execution), if a system is protected with layout randomization, the probability that an unprivileged attacker leads the system to perform an unsafe memory access is very low, provided the address

space is sufficiently large. Of course, the precise probability depends on the concrete randomization scheme. We emphasize that this result is compatible with the large number of kernel attacks that break Linux's kernel layout randomization, e.g. by means of heap overflows ([\[52\]](#page-25-4)). The distribution of Linux's heap addresses lack entropy [\[21\]](#page-23-4), in consequence, the probability of mounting a successful attack are relatively high.

Although it was already well known that layout randomization can provide some security guarantees [\[2](#page-21-0), [1](#page-21-1), [4](#page-21-2)], the novelty of Theorem [1](#page-10-0) lies in showing that these guarantees are valid even if victims can perform pointer arithmetic and indirect jumps.

Despite this positive result, the threat model considered in Theorem [1](#page-10-0) is unrealistic nowadays. In particular, it does not take in account the ability of the attackers to access side-channel info-leaks and to steer speculative execution. There is evidence that, by leveraging similar features, the attackers can leak information on the kernel's layout [\[25,](#page-23-2) [29,](#page-23-5) [34,](#page-23-3) [39,](#page-24-3) [38\]](#page-24-4) and compromise the security guarantees offered by layout randomization [\[24,](#page-23-1) [37\]](#page-24-2).

In particular, if the system under consideration suffers from side-channel info-leaks that involve the layout, an attacker may break the protection offered by randomization. As an illustrative example, suppose the system contains the following system call:

```
int sc\_leak(x) {
  if ((void *) \ x == (void *) \ native.write_cr4)for(int i = 0; i < K; i++);
  return 0;
}
```
By measuring the execution time of the system call, an attacker may deduce information on the location of native_write_cr4. If a call sc_leak(a) takes sufficiently long to execute, the attacker can deduce that the address a corresponds to that of native_write_cr4. Once deduced, the attacker will be effectively able to disable SMEP protection via the vulnerable system call send.

Similar attacks can be mounted by taking advantage of speculative execution: in our example from Figure [1,](#page-2-1) an attacker can make use of the read primitive to probe for readable data without crashing the system. This can be done by supplying to the system call arguments s and idx such that valid(s, idx) returns false — ideally, causing an out of bound access when the return value is fetched from memory. If the attacker manages in mis-training the branch predictor, the access to buf[*s][idx] is performed in transient execution. Depending on the allocation state of the address referenced by buf[*s][idx], two cases arise. If that address does not store any readable data, the memory violation is not raised to the architectural state, because it occurred during transient execution. Most importantly, if that address stores writable data, this operation loads a new line in the system's cache and, as soon as the system detects the mis-prediction, the execution backtracks to the latest safe state. Although this operation does not affect the architectural state, the insertion of a new line in the cache can be detected from user-space. Thus, the attacker can infer that the address referenced by buf[*s][idx] contains readable data, and it can make use of the vulnerabilities of the send and the recv system calls to read or write the content of that memory address. This form of speculative probing is very similar to what happens, for instance, in the BlindSide attack [\[24\]](#page-23-1) that effectively defeats Linux's KASLR.

The reader may observe that these two attacks rely on the attacker's ability to reconstruct the kernel's memory layout by collecting side-channel info-leaks. For this reason, a natural question is whether these attacks can be prevented by imposing that no information of the layouts leaks to the architectural and the micro-architectural state during the execution of system calls. It turns out that this is the case, as we show in Theorem [2.](#page-17-1) In practice, this mitigation is of little help though, as it would effectively rule out all system calls that access memory at runtime.

However, we are able to show that any operating system can be pragmatically turned into another system that is architecturally equivalent to it, but that is not subject to vulnerabilities that are due to transient execution. With this approach, showing that a kernel is safe in the speculative execution model, reduces to showing that the kernel under consideration is safe in the classic execution $Expr \ni E, F ::= v$ values $\vert x \vert$ x register a a a a a array identifier that $\frac{1}{2}$ a a set of $\frac{1}{2}$ a $\frac{1}{2}$ a f procedure identifier that \Box procedure identifier $\text{op}(E_1, \ldots, E_n)$ operation $\ln \left(\frac{1}{2} \right)$::= skip no-op $x := E$ assignment $x := *E$ memory load $\big| * \mathsf{E} := \mathsf{F}$ memory store $\text{real1 F}(E_1, \ldots, E_n)$ procedure call $\text{syscall } s(E_1, \ldots, E_n)$ system call if E then P else Q fi conditional while E do P od while loop Cmd \ni P, Q ::= ϵ | I; P

Figure 2: Syntax of the language.

model. Notably, this holds independently of the technique that is used to show safety in the classic model. Concretely, with this approach, the attack we showed above would be prevented by disallowing the transient execution of the unsafe load operation. In turn, this can be achieved by placing an instruction that stops transient execution before that operation. The efficacy of this technique is shown in Theorem [3.](#page-18-0)

3 The Language

In this section, we introduce the language that we employ throughout the following to study the effectiveness of kernel address space layout randomization.

Syntax and informal semantics. We are considering a simple imperative while language. The address space is explicit, and segregated into user and kernel space. The set Cmd of *commands* is given in Figure [2.](#page-4-1) Memories may store *procedures* and *arrays*, i.e., sequences of *values* $v \in$ Val organized as contiguous regions. The set of values is left abstract, but we assume that it encompasses at least Boolean values Bool \triangleq {true, false}, (memory) addresses Addr, and an undefined value null. Within expressions, $x \in \text{Reg ranges over registers}, a \in \text{Arrld}$ and $f \in \text{Fund over array}$ and procedure *identifiers*, and op ∈ Ops over *operations. Identifiers* $\mathsf{Id} \triangleq \mathsf{Arrd} \oplus \mathsf{Fund}$ are mapped to addresses at runtime, as governed by a layout randomization scheme. The size (length) of an array a is denoted by size(a) and is fixed for simplicity, i.e., we do not model dynamic allocation and deallocation.

A command $P \in \mathbb{C}$ is a sequence of instructions, evaluated in-order. The instruction $x := E$ stores the result of evaluating E within register $x \in \text{Reg}$. To keep the semantics brief, expressions neither read nor write to memory. Specifically, addresses are dereferenced explicitly. To this end, the instruction $x := *E$ performs a memory read from the address given by E, and stores the corresponding value in register x. Dually, the instruction $*E := F$ stores the value of F at the address given by E. The instruction call $F(E_1, \ldots, E_n)$ invokes the procedure residing at address F in memory, supplying arguments E_1, \ldots, E_n . Likewise, syscall $s(E_1, \ldots, E_n)$ invokes a system call $s \in S$ ys with given

arguments. The execution of a system call engages the privileged execution mode and thereby the accessible address space changes. To this end, the address space Addr is partitioned into kernel-space addresses Addr_k , visible in privileged mode, and user-space addresses Addr_k , visible in unprivileged mode. The remaining constructs are standard.

Stores Regarding the address space, we categorize identifiers Id into two distinct sets: kernel-space *identifiers* Id_k and user-space identifiers Id_u . This distinction signifies the intended location of the corresponding objects within the memory address space. We write FunId_k \subseteq Id_k and FunId_u \subseteq Id_u for the kernel-space and user-space procedure idenitifiers; similar for array identifiers. Let $\text{ids}(P) \subseteq \text{Id}$ refer to the set of identifiers literally occurring in P. A *store* is a (well-sorted) mapping $\tau : \mathsf{Id} \to \mathsf{Arr} \cup \mathsf{C}\mathsf{m}\mathsf{d}$, mapping

- 1. procedure identifiers f to their implementation $\tau(f) \in \mathbb{C}$ md; and
- 2. array identifiers a to arrays $\tau(a)$ of size $|\tau(a)| = \text{size}(a)$.

Here, $\text{Arr}^{(n)}$ denotes the set of *arrays* of size n, i.e., finite sequence \vec{v} of values of fixed length n, and Arr the set of arrays of arbitrary size. We write $\tau =_{Id} \tau'$ if τ and τ' coincide on $Id \subseteq \mathsf{Id}$.

Capabilities To model our notion of safety, each system call s is associated at runtime with a fixed set of identifiers that it is meant to access. In the following, we call that set the *capabilities* of s. This set identifies those memory areas that are safe to access, when a certain system call is running.

Systems Let Sys denote a (finite) set of system call identifiers. A system for Sys is a tuple $\sigma =$ (τ, γ, ξ) , consisting of:

- a store τ : Id → Arr ∪ Cmd, relating identifiers to their initial value;
- a system call map γ : Sys \rightarrow Cmd associating system calls to their implementation; and

– a capability map $\xi : Sys \to \mathcal{P}(\mathsf{Id}_k)$ associating system calls with their capabilities.

- To prevent trivial memory safety violations, we impose the following two restrictions:
	- (i) the code $\tau(f)$ associated to user space identifiers $f \in \text{Fund}_u$ is unprivileged, i.e. ids(P) \subseteq Id_u;
	- (ii) the capabilities $\xi(s)$ of a system call s contain at least those identifiers I that s refers to in code, taking procedure calls into account. Concretely, this means that we assume $I \subseteq \xi(s)$, where I is the least set containing identifiers occurring in the body of s ($ids(\gamma(s)) \subseteq I$), and that is closed under procedure calls (i.e., if $f \in I$ then $\text{ids}(\tau(f)) \subseteq I$).

For the sake of simplicity, we also assume that neither kernel-space procedures nor system calls perform system calls themselves. These assumptions, although not substantial, are commonly verified by commodity operating systems.

Observe that by dropping (i) a user-space function may return information on the kernel layout, such as the address of a kernel function to the attacker, making the protection offered by layout randomization vanish. Restriction (ii) relates the capabilities of a system calls to its code, thereby avoiding trivial mis-classifications.

Memories and Layouts A store τ determines the contents of a memory, but not its layout, which is governed by a function $w : \mathsf{Id} \to \mathsf{Addr}$ associating identifiers with their concrete memory addresses. Memories are modeled as functions m : Addr \rightarrow Val ∪ Cmd ∪ {*}, associating addresses with their content. Arrays within τ will be laid out as continuous memory regions; $* \notin$ Val marks that an address is unoccupied in memory. We denote by Mem the set of all memories. In the semantics, we will keep the distinction of procedures from values, thereby modeling a $W^{\dagger}X$ memory protection policy, separating writable from executable memory space.

Let κ_u and κ_k denote the size of user-space and kernel-spaces addresses Addr_u and Addr_k. For simplicity, we assume that $\mathsf{Addr}_u = \{0, \ldots, \kappa_u - 1\}$ and $\mathsf{Addr}_k = \{\kappa_u, \ldots, \kappa_u + \kappa_k - 1\}$, i.e., that user and kernel address spaces are themselves continuous and consecutive regions in memory. Given a store τ , we will always assume that the address space is sufficiently large to hold τ ; that is, $\kappa_b \geq \sum_{\text{id} \in \mathsf{Id}_b} \textsf{size}(\text{id})$ $(b \in \{u, k\})$. Here, by convention size(f) $\triangleq 1$.

A *(memory)* layout is a function $w : \mathsf{Id} \to \mathsf{Addr}$ that describes where objects are placed in memory. As we mentioned, an array a is stored as continuous block at addresses $\underline{w}(\mathsf{a}) \triangleq \{w(\mathsf{a}), \ldots, w(\mathsf{a}) + \}$ size(a) − 1} within memory. For procedure identifiers f, we set $w(f) \triangleq \{w(f)\}\$. We overload this notation to arbitrary sets of identifiers in the obvious way. In particular, $\underline{w}(Arrd)$ and $\underline{w}(Fund)$ refer to the address-spaces of arrays and procedures, under the given layout. We regard only layouts that associate identifiers with non-overlapping blocks $(\underline{w}(\text{id}_1) \cap \underline{w}(\text{id}_2) = \emptyset$ for all $\text{id}_1 \neq \text{id}_2$ and that respect address space separation (\underline{w} (id) \subseteq Addr_b for id \in Id_b, $b \in \{u, k\}$). The set of all such layouts is denoted by Lay. Note that, by the assumptions on κ_u and κ_k , Lay is non-empty.

The application of a *layout* to a *store* results in a memory and is defined in the standard way:

$$
(w \diamond \tau)(p) \triangleq \begin{cases} \text{P} & \text{if } \tau(w^{-1}(p)) = \text{P} \in \text{Cmd}, \\ t & \text{if } w(\texttt{a}) + k = p, \, \tau(\texttt{a}) = \vec{v} \in \text{Arr} \text{ and } \vec{v}[k] = t \\ & \text{for some } \texttt{a} \in \text{Arrld} \text{ and } 0 \leq k < \text{size}(\texttt{a}), \\ * & \text{otherwise}, \end{cases}
$$

where $\vec{v}[k]$ denotes the k-th element of the tuple \vec{v} , indexed starting from 0.

Abstracting from details, we model an address space randomization scheme through a probability distribution over layouts. A specific layout w is established prior to system execution by selecting a memory layout at random. For a given system $\sigma = (\tau, \gamma, \xi)$, this choice then dictates the initial memory configuration $w \circ \tau$. Although the semantics is itself deterministic, computation can be viewed as a probabilistic process. Notably, as instructions are layout-sensitive—such as the result of a memory load operation at a specific address is contingent on whether w positions an object at that address—kernel's safety should be construed as a property that holds in a probabilistic sense.

Operational semantics In the following, we endow our while-language with a small-step operational semantics. Due to the presence of (possible recursive) procedures, configurations make use of a stack of frames. Each such frame records the command under evaluation, the register contents and the execution mode. Formally, configurations are drawn from the following BNF:

A configuration is either of the form (F, m) , where F is a (non-empty) frame stack and m the current memory. A top-frame $\langle P, \rho, b \rangle$ indicates that P is executed with allocated registers, modeled as a mapping ρ : Reg \rightarrow Val, in mode b. In particular, $b = k_s$ indicates that execution proceeds in privileged kernel-mode, triggered by system call s. The annotation of the kernel-mode flag by a system call name facilitates the instrumentation of the semantics. Indeed, every time an access to the memory is made, the semantics checks whether that address is in the capabilities of the system call that is running (if any). If the address can be accessed, the execution proceeds regularly, otherwise it halts in the unsafe state. Finally, an error err signals abnormal termination (for instance, when dereferencing a kernel-space reference in user-space mode or vice versa).

The small step operational semantics takes now the form

$$
w \vdash_{\sigma} C \to D,
$$

$\frac{\llbracket \mathbb{E} \rrbracket^{\mathsf{Addr}}_{\rho, w} = p \quad p \in \underline{w}(\mathsf{Arrld}_b) \quad \boxed{b = \mathbf{k}_s \Rightarrow p \in \underline{w}(\xi(\mathbf{s}))} }{w \vdash_{\sigma} (\langle x \ := \ast \mathbf{E}; \mathbf{P}, \rho, b \rangle : F, m) \rightarrow (\langle \mathbf{P}, \rho[x \leftarrow m(p)], b \rangle : F, m) } [\text{Loap}]$
$\frac{\llbracket\mathbb{E}\rrbracket^{\mathsf{Addr}}_{\rho,w}=p-p\not\in \underline{w}(\mathsf{Arrld}_b)}{w\vdash_\sigma (\langle x\ :=\ \ast\mathbb{E};\mathsf{P},\rho,\mathsf{k}_\mathsf{s}\rangle : F, m)\to \mathsf{err}}[\textsf{LOAD-ERROR}] \quad \frac{\llbracket\mathbb{E}\rrbracket^{\mathsf{Addr}}_{\rho,w}=p-p\in \underline{w}(\mathsf{Arrld}_{\mathsf{k}}) \quad \boxed{p\not\in \underline{w}(\xi(\mathsf{s}))}}{w\vdash_\sigma (\langle x\ :=\ \ast\mathsf{E};\mathsf{P},\rho,\mathsf{k}_$
$\frac{\llbracket \mathbf{E} \rrbracket^{\mathsf{Addr}}_{\rho,w} = p \quad p \in \underline{w}(\mathsf{Arrld}_b) \quad \boxed{b = \mathbf{k}_s \Rightarrow p \in \underline{w}(\xi(\mathbf{s}))}$ $\overline{w \vdash_{\sigma} (\langle \mathbf{*E} := \mathbf{F}; \mathbf{P}, \rho, b \rangle : F, m) \rightarrow (\langle \mathbf{P}, \rho, b \rangle : F, m[p \leftarrow [\mathbf{F}]_{\rho, w}])}$ [STORE]
$\frac{\llbracket \mathbb{E} \rrbracket^{\mathsf{Addr}}_{\rho,w} = p \quad p \notin \underline{w}(\mathsf{Arrld}_b)}{w \vdash_\sigma (\{{*}\mathbb{E}} := \mathbf{F}; \mathtt{P}, \rho, b) : F, m) \rightarrow \mathsf{err}}[\mathtt{STORE-ERROR}] \quad \frac{\llbracket \mathbb{E} \rrbracket^{\mathsf{Addr}}_{\rho,w} = p \quad p \in \underline{w}(\mathsf{Arrld}_k) \quad \boxed{p \notin \underline{w}(\xi(\mathtt{s}))}}{w \vdash_\sigma (\{{*}\mathbb{E}} := \mathbf{F}; \mathtt{P}, \rho, \mathtt{k}_$
$\begin{array}{cc} & \text{[E]}^{\mathsf{Addr}}_{\rho,w} = p & p \in \underline{w}(\mathsf{Funld}_{b}) \quad \boxed{b = \mathtt{k}_{\text{s}} \Rightarrow p \in \underline{w}(\xi(\mathtt{s}))} \\ \hline w \vdash_{\sigma} (\langle \text{call E}(\mathtt{F}_1, \ldots, \mathtt{F}_n); \mathtt{P}, \rho, b \rangle : F, m) \rightarrow (\langle m(p), \rho_0[x_1 \leftarrow [\![\mathtt{F}_1]\!]_{\rho, w}, \ldots, x_n \leftarrow [\![\mathtt{F}_n]\!]_{\rho, w}], b \rangle : \langle \mathtt{P}, \rho, b \rangle : F,$
$\frac{\llbracket \mathbb{E} \rrbracket^{\mathsf{Ador}}_{\rho,w} = p \quad p \notin \underline{w}(\mathsf{FunId}_{\mathsf{k}})}{w \vdash_{\sigma} (\langle \mathsf{call} \ \mathsf{E}(\mathsf{F}_1, \ldots, \mathsf{F}_n); \mathsf{P}, \rho, b) : F, m) \rightarrow \mathsf{err}}^{\lbrack \mathsf{CALLERROR} \rbrack}$
$\frac{\llbracket \mathbb{E} \rrbracket^{\mathsf{Addr}}_{\rho,w} = p \quad p \in \underline{w}(\mathsf{Fundl}_{\mathtt{k}}) \quad \boxed{p \not\in \underline{w}(\xi(\mathtt{s}))} }{w \vdash_{\sigma} (\langle \mathsf{call} \ \mathsf{E}(\mathtt{F}_1, \ldots, \mathtt{F}_n) ; \mathtt{P}, \rho, \mathtt{k}_{\mathtt{s}} \rangle : F, m) \to \mathsf{unsafe}} [\text{CALL-UNSAFE}]$
$w \vdash_{\sigma} (\langle \text{syscall s}(F_1, \ldots, F_n); P, \rho, b \rangle : F, m) \rightarrow (\langle \gamma(s), \rho_0[x_1 \leftarrow [\![F_1]\!]_{\rho, w}, \ldots, x_n \leftarrow [\![F_n]\!]_{\rho, w}], k_s \rangle : \langle P, \rho, b \rangle : F, m)$ ^[SC] $w \vdash_{\sigma} (\langle \epsilon, \rho, b \rangle : \langle P, \rho', b' \rangle : F, m) \rightarrow (\langle P, \rho' [ret \leftarrow \rho (ret)], b' \rangle : F, m)$ ^[Pop]
$w \vdash_{\sigma} (\langle \text{skip}; P, \rho, b \rangle : F, m) \rightarrow (\langle P, \rho, b \rangle : F, m)^{ \text{SKIP} }$
$w \vdash_{\sigma} (\langle x := \mathbf{E}; P, \rho, b \rangle : F, m) \rightarrow (\langle P, \rho[x \leftarrow \mathbb{E}[]_{\rho,w}], b \rangle : F, m)$ ^[Op]
$w \vdash_\sigma (\langle \texttt{if E then P_{true}} \texttt{else P_{false}} \texttt{fi}; \mathtt{Q}, \rho, b \rangle : F, m) \rightarrow (\langle \mathtt{P}_{[\![\mathtt{E}]\!]_{\alpha, m}^{\text{Bool}}}; \mathtt{Q}, \rho, b \rangle : F, m)^{[\![\mathtt{Ir}]\!]}$
$\frac{C_{\text{true}} = (\langle \mathsf{P}; \text{while } \mathsf{E} \text{ do } \mathsf{P} \text{ od}; \mathsf{Q}, \rho, b \rangle : F, m) \quad C_{\text{false}} = (\langle \mathsf{Q}, \rho, b \rangle : F, m)}{w \vdash_{\sigma} (\langle \text{while } \mathsf{E} \text{ do } \mathsf{P} \text{ od}; \mathsf{Q}, \rho, b \rangle : F, m) \rightarrow C_{\llbracket \mathsf{E} \rrbracket_{\rho, \text{col}}^{\text{Bod}}}[\text{WHLE}]}$

Figure 3: Semantics w.r.t. system $\sigma = (\tau, \gamma, \xi)$.

indicating that, w.r.t. system σ , configuration C reduces to D in one step, under layout w. The reduction rules are defined in Figure [3.](#page-7-0) Rules [LOAD] implements a successful memory load $x := *E$. Expression E is evaluated to an address $p = \llbracket \mathbf{E} \rrbracket_{\rho,w}^{\mathsf{Addr}}$, and the register content of x is updated with the value $m(p)$ residing at address p in the memory m. Notice that, the semantics of an expression depends, besides register contents, on the layout w that resolves identifiers to memory addresses. The side-condition $p \in \underline{w}(\text{Arrld}_b)$ enforces that p refers to a value accessible in the current execution mode b (by slight abuse of notation, we disregard the system call label in kernel-mode), otherwise the instruction leads to err (see rule [LOAD-ERROR]). As such, we are modeling unprivileged execution and SMAP protection, preventing respectively the access of kernel-space addresses when in user-mode, and vice versa. The final, boxed, side-condition refers to the safety instrumentation. In kernel-mode, triggered by system call s ($b = k_s$), the rule ensures that p refers to an object within the capabilities of s

 $(p \in \underline{w}(\xi(s)))$. When this condition is violated, unsafe execution is signaled (see rule [LOAD-UNSAFE]). In a similar fashion, the rules for memory writes and procedure calls are defined.

Rule [CALL] deals with procedure calls. It opens a new frame and, by convention, places the n evaluated arguments at registers x_1, \ldots, x_n in an initial register environment ρ_0 . System calls, modeled by rule [[SC](#page-7-5)], follow the same calling convention. Note that in the newly created frame, the execution flag is set to kernel-mode. Once a procedure or system call finished evaluation, rule [[Pop](#page-7-6)] removes the introduced frame from the stack. Note how the rule permits return values through a designated register ret. The remaining rules are standard.

Let us denote by $w \vdash_{\sigma} C \rightarrow^* D$ that configuration C reduces in zero or more steps to configuration D, and by $w \vdash_{\sigma} C \uparrow$ that C diverges. In our semantics, under layout w, any non-diverging computation halts in a terminal configuration of the form $(\langle \epsilon, \rho, b \rangle, w \diamond \tau')$, or abnormally terminates through an error err or through a safety violation unsafe. This motivates the following definition of an evaluation function:

$$
Eval_{\sigma,w}(\mathbf{P}, \rho, b, \tau) \triangleq \begin{cases} \Omega & \text{if } w \vdash_{\sigma} (\langle \mathbf{P}, \rho, b \rangle, w \diamond \tau) \uparrow, \\ (v, \tau') & \text{if } w \vdash_{\sigma} (\langle \mathbf{P}, \rho, b \rangle, w \diamond \tau) \\ & \rightarrow^* (\langle \epsilon, \rho[ret \mapsto v], b \rangle, w \diamond \tau'), \\ \text{err} & \text{if } w \vdash_{\sigma} (\langle \mathbf{P}, \rho, b \rangle, w \diamond \tau) \rightarrow^* \text{err}, \\ \text{unsafe if } w \vdash_{\sigma} (\langle \mathbf{P}, \rho, b \rangle, w \diamond \tau) \rightarrow^* \text{unsafe}. \end{cases}
$$

Note how, in the case of normal termination, we consider the return value as well as the memory contents of the result.

4 Threat Model

In our threat model, attackers are unprivileged user-space programs that execute on a machine supporting two privilege rings: user-mode and kernel-mode. The victim is the host operating system which runs in kernel mode and has exclusive access to its private memory. In particular, the operating system exposes a set of procedures, the system calls, that can be invoked by the attacker and that have access to kernel's memory. The attacker's goal is to trigger a system call to perform an unsafe memory access.

In Section [5,](#page-9-0) attackers are ordinary programs that do not control speculative execution and do not have access to side-channel info-leaks. However, the target machine implements standard mitigations against this kind of attacks. In particular, it supports data execution protection mechanisms (DEP), SMAP [\[16](#page-22-4)] that prevents kernel-mode access to user-space data, and SMEP [\[20](#page-22-5)] that prevents the execution of user-space functions when running in kernel-mode. More precisely, the above-mentioned protection mechanisms are modeled in our semantics by the preconditions of the rules [CALL], [LOAD], [[Store](#page-7-7)] that prevent the system from: (i) overwriting functions, (ii) execute values, (iii) accessing user-space data and functions when the system is in kernel-mode. Most importantly, the system adopts kernel address space layout randomization, that is modeled by sampling the memory layout from a probability distribution.

In Section [6,](#page-11-0) we then consider a stronger threat model where, in addition, attackers have access to side-channel observations and control PHT and STL predictions, related to Spectre v1 and v4 vulnerabilities [\[33\]](#page-23-6). In addition to the above-mentioned mechanisms against speculative attacks, the machine supports PTI [\[32](#page-23-7)] to prevent the speculative access of kernel-space memory from user-space; this is modeled by using the same preconditions of rules [[Call](#page-7-4)], [[Load](#page-7-1)], [[Store](#page-7-7)] for their speculative counterparts, see Section [6.1.1.](#page-11-1)

5 Classic Threat Model

In this section we show how the result of Abadi et. al. [\[2,](#page-21-0) [1,](#page-21-1) [4\]](#page-21-2) scales to the model introduced in Section [3.](#page-4-0) We formalize memory safety as follows:

Definition 1 (Kernel safety). We say that a system $\sigma = (\tau, \gamma, \xi)$ is kernel safe, if for every layout w, unprivileged attacker $P \in \text{Cmd}$, and registers ρ , we have:

$$
\neg \left(w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau \right) \rightarrow^* \text{unsafe} \right)
$$

Thus, safety is broken if an attacker A, executing in unprivileged user mode, is able to trigger a system call in such a way that it accesses, or invokes, a kernel-space object outside its capabilities. The source of such a safety violation can be twofold:

1. Scope extrusion: An obvious reason why kernel-safety may fail is due to apparent communication channels, specifically through the memory and procedure returns. As an illustrative example, consider the two system calls s1 and s2 shown below:

```
void *v();
void s1() { v = \&f; };
void s2() { (*v )(); };
```
A malicious program can use s1 to store the address of f at v, which is a shared capability. A consecutive call to s2 then breaks safety if f is not within the capabilities of s2.

2. Probing: Another counterexample is given by a system call accessing memory based on its input, such as

void $s(a)$ { $(*a)($; };

which directly invokes the procedure stored at the kernel-address a, that is supplied as argument. This system call can potentially be used as a gadget to invoke an arbitrary kernel-space function from user-space. Since an attacker lacks knowledge of the kernel-space layout, such an invocation needs to happen effectively through probing. As any probe of an unused memory address leads to an unrecoverable error,^{[1](#page-9-1)}, the likelihood of an unsafe memory access is, albeit not zero, diminishingly small when the address-space is reasonably large.

To overcome Issue [1,](#page-9-2) we impose a form of (layout) non-interference on system calls.

Definition 2 (Layout non-interference). Given $\sigma = (\tau, \gamma, \xi)$, a system call s is layout non-interfering, if,

$$
Eval_{\sigma, w_1}(\gamma(s), \rho, k_s, \tau') \cong eval_{\sigma, w_2}(\gamma(s), \rho, k_s, \tau')
$$

for all layouts w_1, w_2 , registers ρ and stores $\tau' =_{\text{Fund}} \tau$. Here, the equivalence \cong extends equality by identifying the abnormal termination states err and unsafe. The system σ is non-interfering if all its system calls are.

In effect, layout non-interfering systems do not expose layout information, neither through the memory nor through return values. In particular, observe how non-interference rules out Issue [1,](#page-9-2) as witnessed by two layouts placing f at different addresses in kernel-memory.

Concerning Issue [2,](#page-9-3) it is well known that layout randomization provides in general safety not in an absolute sense, but *probabilistically* $[2, 11, 56]$ $[2, 11, 56]$ $[2, 11, 56]$. Indeed, the chance for a probe to be successful is proportional to the ratio between occupied and free (kernel) memory space. Following Abadi and Plotkin [\[2](#page-21-0)], let μ be a probability distribution of layouts, i.e., a function μ : Lay \rightarrow [0, 1] assigning to each layout $w \in \text{Lay}$ a probability $\mu(w)$ (where $\sum_{w \in \text{Lay}} \mu(w) = 1$). Without loss of generality, we

¹This is not always the case for *user-space* software protected with layout randomization, as some programs (e.g. web servers) may automatically restart after a crash to ensure availability. This behavior can be exploited by attackers to probe the entire memory space of the victim program, thus compromising the protection offered by layout randomization [\[54](#page-25-6)].

assume that the layout of public, i.e. user-space, addresses is fixed. That is, we require for each w_1, w_2 with non-zero probability in μ , that $w_1(id) = w_2(id)$ for all id $\in \mathsf{Id}_n$. For a system call $s \in \mathsf{Sys}$, let id_1^s, \ldots, id_k^s be an enumeration of its capabilities $\xi(s)$. The following probability δ_μ quantifies the chance that accessing an address $p \in \mathsf{Addr}_k$ causes an error (rather than an unsafe access), given that capabilities id_1^s, \ldots, id_h^s are stored at addresses p_1, \ldots, p_h respectively, and that p does not refer to any of the objects within the capabilities of s.

$$
\delta_{\mu} \triangleq \min \{ \Pr_{w \leftarrow \mu} [p \notin \underline{w}(\mathsf{Id}) \mid w(\mathtt{id}_i^{\mathrm{s}}) = p_i, \text{ for } 1 \leq i \leq h] \mid \mathtt{s} \in \mathsf{Sys}, p, p_1, \dots, p_h \in \mathsf{Addr}_{\mathsf{k}} \land p \notin \{p_i, \dots, p_i + \mathsf{size}(\mathtt{id}_i^{\mathrm{s}}) - 1\}, \text{ for } 1 \leq i \leq h \}.
$$

More concretely, δ_{μ} is the probability that, during the execution of a system call s, a fixed kernel address p is not allocated, given that it does not store any object that is the capabilities of that system call. Notably, if an attacker controls the value of p , this is a lower bound to the probability that its guess fails. We arrive now at the main result of this section:

Theorem 1. Let $\sigma = (\tau, \gamma, \xi)$ be layout non-interfering. Then

$$
\mathbb{P}_{w \leftarrow \mu} \ [w \vdash_{\sigma} ((P, \rho, u), w \diamond \tau) \rightarrow^* \text{unsafe}] \leq 1 - \delta_{\mu},
$$

for any unprivileged attacker $P \in \text{Cmd}$, and registers ρ .

The proof of this result is in Appendix [A.1.1.](#page-27-0)

Theorem [1](#page-21-1) extends the results of $[2, 1, 4]$ $[2, 1, 4]$ $[2, 1, 4]$ by showing that layout randomization guarantees kernel safety probabilistically to operating systems; in contrast with $[2, 1, 4]$ $[2, 1, 4]$ $[2, 1, 4]$ $[2, 1, 4]$ $[2, 1, 4]$, this holds even when victim's code contains unsafe programming constructs such as arbitrary pointer arithmetic and indirect jumps. This is achieved by replacing Abadi and Plotkin [\[2\]](#page-21-0)'s restrictions on the syntax of the victims with a weaker dynamic property: layout non-interference. Notice that the strength of the security guarantee provided by Theorem [1](#page-10-0) depends on the distribution of the layouts μ . Therefore, in practice, it is important to determine a randomization scheme that provides a good bound. This can be done quite easily: for instance, if we assume that (i) $\kappa_{\mathbf{k}} \gg \sum_{\mathbf{i} d \in \mathsf{Id}_{\mathbf{k}}} \mathsf{size}(\mathbf{i} d)$ and that (ii) $\theta \triangleq \max_{\mathbf{i} d \in \mathsf{Id}_{\mathbf{k}}} (\mathsf{size}(\mathbf{i} d))$ divides κ_k , we can think of the kernel space address range as divided in $\frac{\kappa_k}{\theta}$ slots, each storing a single object. In this setting, we can define the distribution ν as the uniform distribution of all the layouts that store each *memory object* within a *slot* starting from the beginning of that slot. For this simple scheme, we can estimate the bound δ_{ν} as the ratio between unallocated slots and all the slots that do not store an object that is referenced by the capabilities of a system call:

$$
\delta_{\nu} \geq \min_{s \in \mathsf{Sys}} \frac{\kappa_{\mathsf{k}}/\theta - \mathsf{size}(\mathsf{Id}_{\mathsf{k}})}{\kappa_{\mathsf{k}}/\theta - \mathsf{size}(\xi(s))}.
$$

In particular, the fraction in the right-hand side is the probability that by choosing a slot that is not storing any object referenced by s, we end up with a fully unoccupied slot. Observe that this lower-bound approaches 1 when $\kappa_{\mathbf{k}}$ goes to infinity. The adequacy of this bound is shown in the appendix, Remark [1.](#page-39-0)

Now that we have established that Layout Randomization provides kernel safety in a probabilistic sense, it is worth mentioning how this property relates with other desirable safety properties. In particular, kernel safety encompasses some form of spatial memory safety and of control flow integrity, that are maybe the most sought-after security properties for operating systems, as witnessed by the large number of measures that, together with layout randomization, have been developed for their enforcement [\[45](#page-24-5), [48](#page-25-7), [50](#page-25-8), [58](#page-25-9), [22](#page-23-8), [36](#page-24-6)].

Spatial Memory Safety Although it is difficult to find a common definition of *spatial memory* safety, many of these definitions associate a software component (a program, an instruction, or even a variable) with a fixed memory area, that this component can access rightfully [\[10](#page-22-7), [46,](#page-25-10) [44,](#page-24-7) [7](#page-21-4)]. In this realm, any load or store operation that does not fall within this area is considered a violation of spatial memory safety. Our notion of kernel safety encompasses a form of spatial memory safety: if a system enjoys kernel safety, then no system call can access a memory region that does not appear within its capabilities.

Control Flow Integrity This property requires that the control transfer operations performed by a program can reach only specific targets that are determined statically [\[3\]](#page-21-3). If a system enjoys kernel safety then it also enjoys a weak form of *control flow integrity*. Indeed, our semantics prevents the execution of a function if its address does not belong to the set of capabilities of the current system call. This means that if a system $\sigma = (\tau, \gamma, \xi)$ is kernel safe, we are certain that by executing that system call, the control flow will flow across the procedures that belong to $\xi(s)$.

6 Speculative Threat Model

In this section we establish to which extent a system enjoys kernel safety in presence of speculative attackers. To this aim, in Section [6.1,](#page-11-2) we extend the model of Section [3](#page-4-0) for this new scenario. More precisely, we endow the semantics of Section [3](#page-4-0) with speculative execution and side-channel observations that reveal the accessed addresses and the value of conditional branches [\[10,](#page-22-7) [14,](#page-22-2) [27](#page-23-9), [28\]](#page-23-10). In Section [6.2,](#page-15-0) we refine the notion of kernel safety for this model, by defining speculative kernel safety.

6.1 The Speculative Execution Model

A substantial difference between our model and previous models [\[10](#page-22-7), [14](#page-22-2), [27,](#page-23-9) [28\]](#page-23-10) lies in the possibility to explicitly model attackers. More precisely, an attacker is not given as a mere sequence of microarchitectural directives, but becomes a fully-fledged program that can directly interact with the system. This permits us to naturally extend the notion of kernel safety to the new scenario. Besides, we believe that modeling an attack explicitly can be interesting on its own. Feasibility of an attack is witnessed explicitly through a program. In this setting, for instance, assumptions on the attacker's computational capabilities can be imposed seamlessly.

6.1.1 Victim Language and Semantics

The victims' language remains identical to the classic model. To permit attackers to influence the speculative execution of specific instructions, we assume load and branch instructions are tagged by unique labels $\ell \in L$ bl, We enrich the language with a *fence instruction* found in modern CPUs [\[31\]](#page-23-11):

 $Instr \ni I ::= \cdots |$ fence.

Architecturally, this instruction is a no-op, on the microarchitecture level it commits all buffered writes to memory. Following Barthe et al. [\[10](#page-22-7)], the speculative semantics is instrumented through directives, modeling the choice made by prediction units of the processor. Directives take the form

$$
d \ni \text{Dir} ::= \mathsf{br}_{\ell} b \mid \mathsf{Id}_{\ell} i \mid \mathsf{bt} \mid \mathsf{st},
$$

where $i \in \mathbb{N}$ and $b \in$ Bool. The br_ℓ b directive causes a branch instruction to be evaluated as if the guard resolved to b. The $\mathsf{Id}_\ell i$ causes the load instruction to load the *i*-th most recent value that is associated to an address in a (buffered) memory. The bt directive is used to direct speculations, either backtracking the most recent mis-speculation or committing the microarchitectural state. Finally, the st directive evaluates an instruction without engaging into speculation, in correspondence to the semantics we have given in Section [3.](#page-4-0)

The semantics is also instrumented with observations to model timing side-channel leakage:

$$
C = (\langle x :=_{\ell} * \mathbf{E}; P, \rho, b \rangle : F, \mu m, b_{ms}) \quad \mathbb{E} \mathbb{I}_{\rho,w}^{\text{Adstr}} = p \quad (\mu m)^{i}(p) = (v, f) \quad p \in \underline{w}(\text{Arrld}_{b}) \quad \boxed{b = \mathbf{k}_{s} \Rightarrow p \in \underline{w}(\xi(\mathbf{s}))}
$$
\n
$$
w \vdash_{\sigma} C : S \xrightarrow{\text{mem } p} (\langle P, \rho[x \leftarrow v], b) : F, \mu m, b_{ms} \vee f) : C : S
$$
\n
$$
\frac{[\mathbb{E}]\big|_{\rho,w}^{\text{Adstr}}}{w \vdash_{\sigma} (\langle x :=_{\ell} * \mathbb{E}; P, \rho, b) : F, \mu m, b_{ms}) : S \xrightarrow{\circ} [\mathbb{E}(\mathbf{c}, b_{ms}) : S} [\text{ELAAD-}]
$$
\n
$$
\frac{[\mathbb{E}]\big|_{\rho,w}^{\text{Adstr}}}{w \vdash_{\sigma} (\langle x :=_{\ell} * \mathbb{E}; P, \rho, b) : F, \mu m, b_{ms}) : S \xrightarrow{\text{mem } p} (\mathbb{E}(\mathbf{s}))} [\text{SLOAD-}]
$$
\n
$$
\frac{[\mathbb{E}]\big|_{\rho,w}^{\text{Adstr}}}{w \vdash_{\sigma} (\langle x :=_{\ell} * \mathbb{E}; P, \rho, b, \mathbf{k}_{s}) : F, \mu m, b_{ms}) : S \xrightarrow{\text{mem } p} \text{unsafe}} [\text{UNSAFE}]
$$
\n
$$
\frac{[\mathbb{E}]\big|_{\rho,w}^{\text{Adstr}}}{w \vdash_{\sigma} (\langle x :=_{\ell} * \mathbb{E}; P, \rho, b) : F, \mu m, b_{ms}) : S \xrightarrow{\text{mem } p} (\langle P, \rho[x \leftarrow v], b) : F, \mu m, b_{ms}) : S} [\text{SLOAD-STEP}]
$$
\n
$$
\frac{C = (\langle \text{if } \ell \text{ E then } \mathbb{Q}_{\text{true}} \text{ else } \mathbb{Q}_{\text{false}} \text{ f} \text{ i}; \mathbb{Q}, \rho, b) : F, \mu m, b_{ms} \vee d \neq [\mathbb{E}]\big|_{\rho,w}^{\text{Box
$$

Figure 4: Speculative semantics, excerpt.

$$
o, q \ni \text{Obs} ::= \circ \mid \text{br } b \mid \text{mem } p \mid \text{imp } p \mid \text{bt } b,
$$

where $n \in \mathbb{N}$ b \in Bool, and $p \in$ Addr. We use \circ to label transitions that do not leak observations. The br b observation is caused by branching instructions, with b reflecting the taken branch. The mem p observation is caused by memory access, through loads or stores, and contains the address of the accessed location, thus modeling instruction-cache leaks. Likewise, the $\text{imp } p$ observation is caused by calls to procedures residing at address p in memory. Finally, the $bt\,b$ observation signals a backtracking step during speculative execution. Notice that we leak full addresses on memory accesses, and the value of the branching instructions, i.e. we adopt the baseline leakage model that is widely employed in the literature to model side-channel info-leaks [\[5](#page-21-5), [10](#page-22-7), [14](#page-22-2), [9](#page-22-8)].

A reduction step now takes the form

$$
w \vdash_{\sigma} S \xrightarrow[d]{} S',
$$

indicating that for a given system σ , under layout $w \in \text{Lay}$, the system evolves from state S with directive $d \in \text{Dir}$ to S' in one step, producing the side-channel observation o. The state of a system S is now modeled as a stack of backtrackable configurations. Specifically, configurations follow the following BNF:

 $C, D ::= (F, \mu m, b_{ms}) \mid (err, b_{ms}) \mid$ unsafe

In a configuration $(F, \mu m, b_{ms})$, F is a call-stack as in Section [3,](#page-4-0) μm is a memory equipped with a write buffer μ , and b_{ms} the mis-speculation flag. Buffered memories μ m permit out-of-order, speculative memory operations. Specifically, writing a value v at address p results in a delayed write $[p \mapsto v] \mu m$, and $(\mu m)^k(p)$ yields the kth-last buffered entry v at address p, together with a boolean flag f that it \perp if and only if v is the most recent one associated to address p. This operation is formally described by the following function:

$$
([\![m)^{k}(p) \triangleq m(a), \bot
$$

\n
$$
([\![p \mapsto n] : \mu m)^{0}(p) \triangleq n, \bot
$$

\n
$$
([\![p \mapsto n] : \mu m)^{i+1}(p) \triangleq n', \top
$$

\n
$$
([\![p' \mapsto n] : \mu m)^{i}(p) \triangleq (\mu m)^{i}(p)
$$

\nif $p \neq p'.$

In a configuration, the mis-speculation flag b_{ms} records whether a past step of computation led to a mis-speculation. It is employed when backtracking from a speculative state. As errors are recoverable under mis-speculation, error configurations err carry also a mis-speculation flag. Finally, as in Section [3,](#page-4-0) unsafe indicates a safety violation.

Some illustrative rules of the semantics are given in Figure [4,](#page-12-0) the complete set of rules is relegated to the appendix, see Figures [6](#page-42-0) and [7.](#page-43-0)The rules for a load instruction are very similar to the ones we give in Section [3,](#page-4-0) but attackers can take advantage of the store-to-load dependency speculation by issuing a $\mathsf{Id}_\ell i$ directive. When this happens, the *i*-th most recent value associated to the address $p = [\mathbb{E}]_{\rho,w}^{\mathsf{Addr}}$ is retrieved from the buffered memory, see rule [[SLoad-Load](#page-12-1)]. This value may not correspond to that of the most recent store to the address p , and this is signaled by the flag f that is returned after the buffer lookup. If $f = \top$, this operation may be engaging mis-speculation and, for this reason, the semantics keeps track of the current configuration in the stack. A successful load produces the observation mem p that leaks the address to the attacker. The rules for erroneous and unsafe loads are [[SLoad-Error](#page-12-2)] and [[SLoad-Unsafe](#page-12-3)] and they are analogous to their non-speculative counterparts. In our semantics, every command supports the st directive, which evaluates the configuration without speculating. For instance, the [SLOAD-STEP] rule evaluates the $x := *E$ command by fetching the most recent value from the write buffer, instead of an arbitrary one.

Even branch instructions can be executed speculatively by issuing the directive br d by means of the rule $[IF-BRANCH]$. This causes the evaluation to continue as if the guard resolved to d. This operation leaks which branch is being executed by means of the observation $\mathbf{b}r \, d$. Even in this case, the rule may be mis-speculating; for this reason, the current configuration is book-kept in the stack and the mis-speculation flag is updated.

When the topmost configuration of a stack carries the mis-speculation flag ⊤, the configuration can be is discarded with the rules $[BT_T]$. If it is \perp , the current state is not mis-speculating, so the whole stack of book-kept configurations can be discarded with the rule $[BT_⊥]$.

The [[Fence](#page-12-8)] rule commits all the entries in the write buffer to the memory. Precisely, this operation is defined as follows:

$$
\overline{[m} \triangleq m \qquad \qquad \overline{[p \mapsto v] : \mu m} \triangleq \overline{\mu m} [p \leftarrow v],
$$

where, by $m[p \leftarrow v]$, we denote the memory obtained by updating the value at address p with v. In particular, for consistency, a potentially mis-speculative state must be resolved. This is why this rule requires the mis-speculation flag to be ⊥. This means that, if this configuration is reached when the flag is \top , the semantics must backtrack with the rule $[BT_{\top}]$.

6.1.2 Attacker's Language and Semantics

To give a definition of kernel safety w.r.t. speculative semantics, we endow an attacker with the ability to engage in speculative executions, by issuing directives, and by the ability to read side-channel information. To this end, we extend the instructions from Section [3](#page-4-0) as follows:

$$
\overline{w \vdash_{\sigma} (\langle \text{poisson}(d); \mathbf{A}, \rho, b \rangle : F, m, D, O) \rightarrow (\langle \mathbf{A}, \rho, b \rangle : F, m, d : D, O)}^{\text{[Poisson]}}
$$
\n
$$
\overline{w \vdash_{\sigma} (\langle x := \text{observe}(); \mathbf{A}, \rho, b \rangle : F, m, D, o : O)} \rightarrow (\langle \mathbf{A}, \rho[x \leftarrow o], b) : F, m, D, O)^{\text{[OBSERVE]}}}
$$
\n
$$
\overline{w \vdash_{\sigma} (\langle \text{spec on P}; \mathbf{A}, \rho, b \rangle : F, m, D, O) \rightarrow (\langle P, \rho, b \rangle, m, \bot) \mid (\langle \mathbf{A}, \rho, b \rangle : F, D, O)}^{\text{[SPEC-INT]}}
$$
\n
$$
w \vdash_{\sigma} S \xrightarrow{o} S'
$$
\n
$$
\overline{w \vdash_{\sigma} S \mid (F, d : D, O) \rightarrow S' \mid (F, D, o : O)}^{\text{[SPEC-D]}}
$$
\n
$$
\overline{w \vdash_{\sigma} S \downarrow_{D} w \vdash_{\sigma} S \xrightarrow{\sigma} S'}
$$
\n
$$
\overline{w \vdash_{\sigma} S \mid (F, D, O) \rightarrow S' \mid (F, D, o : O)}^{\text{[SPEC-D]}}
$$
\n
$$
\overline{w \vdash_{\sigma} S \mid (F, D, O) \rightarrow S' \mid (F, D, o : O)}^{\text{[SPEC-S]}} \overline{w \vdash_{\sigma} S \mid (F, D, O) \rightarrow S' \mid (F, D, o : O)}^{\text{[SPEC-D]}}
$$
\n
$$
\overline{w \vdash_{\sigma} (\langle \epsilon, \rho, b \rangle, \mu m, \bot) \mid (\langle \mathbf{A}, \rho', b' \rangle : F, D, O) \rightarrow (\langle \mathbf{A}, \rho', b' \rangle : F, \overline{\mu m}, D, O) \text{[SPEC-TERM]}}
$$
\n
$$
\overline{w \vdash_{\sigma} (\text{err}, \bot) \mid (F, D, O) \rightarrow \text{err}}^{\text{[SPEC-ERROR]}} \overline{w \vdash_{\sigma} \text{unsafe} \mid (F, D, O) \rightarrow \text{unsafe} \mid (S \
$$

Figure 5: Semantics for speculative attackers, excerpt.

Instrument

\n
$$
\begin{array}{ccc}\n\text{Instr } \ni & \text{if } x := \dots \\
\mid & \text{spec on } P & \text{speculation on } \text{victim } P \\
& \text{poison}(d) & \mid & x := \text{observe}() & \text{side-channel observation} \\
\text{SpAdv } \ni & A ::= \epsilon \mid \text{I}; A\n\end{array}
$$

The instruction spec on P is used to execute a victim code P, w.r.t. the speculative semantics defined just above. By using the instruction $poisson(d)$, the attacker is able to to mistrain microarchitectural predictors and to control the speculative execution. Issued directives control the evaluation of victim code under speculative semantics. Dual, the instruction $x := \text{observe}()$ is used to extract side-channel info-leaks, collected during speculative execution of the victim's code. To model this operation, in the following, we assume $\mathsf{Obs} \subseteq \mathsf{Val}$. As an example, the snippet

$$
\begin{aligned}\n\text{poison}(\mathbf{br}_{\ell} \top); \\
\text{spec on if}_{\ell} \mathbf{E} \text{ then } \text{syscall s}(p) \text{ fi}; \\
x &:= \text{observe}() \n\end{aligned} \tag{\dagger}
$$

forces the mis-speculative execution of syscall $s(p)$, independently of the value of E. The register x will hold the final observation leaked through executing the system call.

The attacker's semantics is defined in terms of a relation

$$
w \vdash_{\sigma} C \rightarrow C'.
$$

In essence, the attacker executes under the standard semantics given in Section [3,](#page-4-0) the speculative semantics defined above play a role only when execution of the victim is triggered by the directive spec on P. Consequently, configurations are identical in structure to the ones underlying the standard semantics, but carry however additionally stacks D and O of directives and observations, in order to model the new constructs. In addition, hybrid configurations $S | (F, D, O)$ are used to model the system when executing the victim under speculative semantics. Here S is a stack of speculative configurations concerning the victim, and F the attacker's call stack up to the invocation of speculation. Again, D gives the directives (to be processed) and O the observations (collected from executing victim's code). In summary, configurations are drawn from the following BNF:

$$
C ::= (F, m, D, O) \bigm| S | (F, D, O) \bigm| err \bigm| unsafe
$$

Figure [5](#page-14-0) shows the evaluation rules for the new constructs. Rules [POISON] and [OBSERVE] define the semantics for poisoning and side-channel observations, by pushing and redacting elements of the corresponding stacks. Rule [[Spec-Init](#page-14-3)] deals with the initialization spec on P of speculative execution, starting from the corresponding initial configuration of the victim P in an empty speculation context. A frame for the continuation of the attacker A is pushed on the call stack S. This frame is used to resume execution of the attacker, once the victim has been fully evaluated. The victim itself is evaluated via the speculative semantics through rules [[Spec-D](#page-14-4)]–[[Spec-BT](#page-14-5)]. Note how execution of the victim is directed through the directive stack D (rule [SPEC-D]). Should the current directive be inapplicable, a non-speculative rewrite step (rule [[Spec-S](#page-14-6)]) or backtracking (rule [[Spec-BT](#page-14-5)]) is performed. Here, the premise $w \vdash_{\sigma} S \downarrow_d$ signifies that S is irreducible w.r.t. the directive d. Likewise, $w \vdash_{\sigma} S \downarrow_D$ means that S is irreducible w.r.t. the topmost directive of D , or that D is empty. Note also how side-channel leakage, modeled through observations, is collected in the configuration via these rules. Upon normal termination, resuming of evaluation of the attacker is governed by rule [[Spec-Term](#page-14-7)] in the case of normal termination. Finally, rules [SPEC-ERROR] and [SPEC-UNSAFE] deal with abnormal termination.

We write \rightarrow^* for the multistep reduction relation induced by \rightarrow , i.e, $S \xrightarrow[\epsilon]{\epsilon} S$ and $S \xrightarrow[d:D]{o} S'$ if

$$
S \xrightarrow[d]{o} \cdot \frac{O}{D} \diamond^* S'.
$$

6.2 Speculative Kernel Safety

We are now ready to extend the definition of kernel safety (Definition [1\)](#page-9-4) to the speculative semantics.

Definition 3 (Speculative kernel safety). We say that a system $\sigma = (\tau, \gamma, \xi)$ is speculative kernel safe if for every unprivileged attacker $A \in SpAdv$, every layout w, and register map ρ , we have:

$$
\neg (w \vdash_{\sigma} (\langle A, \rho, u \rangle, w \diamond \tau, \epsilon, \epsilon) \rightarrow^* \textsf{unsafe}).
$$

It is important to note that this safety notion captures violations that occur during transient execution. This is in line with what happens, for instance, for Spectre and Meltdown [\[33,](#page-23-6) [37](#page-24-2)], both exploiting unsafe memory access under transient execution in order to reveal confidential information.

6.3 The Demise of Layout Randomization in the Spectre Era

A direct consequence of Definition [3](#page-15-1) is that every system that is speculative kernel safe is also kernel safe. The inverse, of course, does not hold in general. Most importantly, the probabilistic form of safety provided by layout randomization in Section [5](#page-9-0) does not scale to this extended threat model. This happens because Definition [1](#page-9-4) does not take side-channel leakage into account. As a simple example, gadgets like

if $f = p$ then P else Q fi,

can be exploited by an attacker to infer information about the address of a kernel-space procedure f, through side-channel leakage distinguishing the execution of P and Q. In our model, this is reflected as executing this instruction allows the attacker to observe $\mathsf{b}{\mathsf{r}}$, with b being true precisely when f resides at address p. Secondly, speculative execution undermines a fundamental premise crucially leveraged in Theorem [1](#page-10-0) and, more widely, in the majority of studies demonstrating the efficacy of layout randomization as a defense against attacks (e.g., $[2, 1, 4]$ $[2, 1, 4]$ $[2, 1, 4]$): the notion that an unsuccessful memory probe leads to abnormal termination, thus thwarting the attack. Indeed, within transient executions, memory access violations are recoverable.

This happens, for instance, if the system call s of (t) tries to load the content of the address p form the memory to a register. If p is not allocated, the system performs a memory access violation under transient execution, that does not terminate the execution. Conversely, if p is allocated, its content is loaded into the cache, producing the observation mem p before the execution of the branch and the system call are backtracked. By reading side-channel observations, the attacker can thus distinguish allocated kernel-addresses from those that are not allocated. This last example, in particular, is not at all fictitious: the BlindSide attack [\[24](#page-23-1)] uses the same idea to break Linux's KASLR and locate the position of kernel's executable code and data.

6.4 Speculative Layout Non-Interference

As this revised model significantly enhances the attackers' strength, we will need to implement more stringent countermeasures in order to restore kernel safety. To counter side-channel info-leaks, we can impose a form of side-channel non-interference that is in line with the notion of speculative constanttime from [\[14\]](#page-22-2).

Definition 4 (Speculative layout non-interference). Given $\sigma = (\tau, \gamma, \xi)$, a system call s is *speculative* layout non-interfering, if,

$$
w_1 \vdash_{\sigma} (\langle \gamma(\mathbf{s}), \rho, \mathbf{k_s} \rangle, \mu(w_1 \diamond \tau'), b_{ms}) \xrightarrow{O}^* S_1
$$

implies

$$
w_2 \vdash_{\sigma} (\langle \gamma(s), \rho, \mathbf{k}_s \rangle, \mu(w_2 \diamond \tau'), b_{ms}) \frac{\partial}{\partial \tau} \models^* S_2,
$$

for all layouts w_1, w_2 , configurations over stores $\tau' =_{\text{Fund}} \tau$ coinciding on procedures $(\tau'(\tau) = \tau(\tau))$ for all $f \in \text{Fund}$), directives D, observations O and register map ρ .

Speculative layout non-interference effectively prevents side-channel-related attacks, even during transient executions. Importantly, it ensures the non-leakage of layout information throughout the side-channels by requiring the identity of the two sequences of observations produced by the two reductions. This, however, implies severe restrictions on memory interactions — effectively prohibiting the use of random memory layouts! Unsurprisingly, this form of non-interference directly establishes kernel safety of system calls:

Lemma 1. For every system $\sigma = (\tau, \gamma, \xi)$, if

$$
\kappa_{\tt k} \geq \sum_{\tt id \in \mathsf{Id}_k} \mathsf{size}(\tt id) + 2 \cdot \max_{\tt id \in \mathsf{Id}_k} \mathsf{size}(\tt id),
$$

and if s is speculative layout non-interfering, then

$$
\neg \left(w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, \mu(w \diamond \tau'), b_{ms}) \xrightarrow{O} \rightarrow^* \textsf{unsafe}\right)
$$

for all layouts w and initial configurations over stores τ' coinciding with τ on Funld.

The proof of this lemma is in Appendix [A.2.4.](#page-46-0)

Intuitively, this statement holds because if an invocation of a system call s performs an unsafe memory access when executing under a layout w , the address p of the accessed resource is leaked; but the same address cannot leak if the resource is moved to another location $-$ this is why we impose the condition on the size of the memory. Thus, if a system call is speculative layout non-interfering, it cannot be speculative non-interferent because different memory layouts produce different observations.

In general, it is not always the case that a non-interference property has as consequence memory safety. For instance, being non-interferent with respect to a set of secrets does not prevent a victim program from breaking memory safety. In our case, this property holds because the layouts are not only used as the inputs for a computation, but they also determine where objects are placed in memory.

Theorem 2. Under the assumption $\kappa_k \ge \sum_{i \in [d_k]} size(id) + 2 \cdot max_{id \in [d_k]} size(id)$, if a system σ is speculative layout non-interfering, then it is speculative kernel safe.

This result is demonstrated in Appendix [A.2.4.](#page-46-0)

Observe that the safety guarantee provided by speculative layout non-interference is not probabilistic. Although its effectiveness, layout randomization is unlikely to be restored at the software level without imposing speculative layout non-interference, in presence of this assumption, layout randomization is a redundant protection measure. Also notice that *speculative layout non-interference* is not a necessary condition for speculative kernel safety. For instance, we can take in consideration the following system:

void $f() \{ skip; } \}$; void s() { f (); };

This system does not enjoy speculative non-interference, because by executing s, the address of f leaks, and this address changes under different layouts. However, this system is speculatively safe if we assume that f belongs to the capabilities of s.

7 Enforcement of Speculative Kernel Safety

Although by requiring speculative layout non-interference, we would be able to restore speculative kernel safety, this would impose important limitations on the system. For this reason, we believe it is worth investigating whether *speculative kernel safety* can be enforced without imposing *speculative* layout non-interference.

Nevertheless, directly enforcing speculative kernel safety is non-trivial, because it requires the developers to constantly take in account a large variety of microarchitectural behaviors that their system may run into. On the other hand, in the last decades, plenty of effort has been put in developing safe code in the classic model, [\[45,](#page-24-5) [48](#page-25-7), [50](#page-25-8), [58,](#page-25-9) [22,](#page-23-8) [36](#page-24-6)]. So, our last question is to determine to which extent we can establish a link between kernel safety and speculative kernel safety. Following other works in this direction [\[17,](#page-22-3) [57](#page-25-2)], our main idea is to nullify the gap between kernel safety and speculative kernel safety, by making the latter property a consequence of the former.

This can be achieved by finding a transformation ζ that turns any kernel safe system σ into another system $\zeta(\sigma)$ which is architecturally equivalent to σ but enjoys speculatively kernel safety. The semantic requirement on the transformation ζ is expressed by Definition [5,](#page-17-2) by which we ask that no user-space program may show different behaviors by executing in the two systems.

Definition 5 (Semantics preservation). A system transformation ζ is user-space semantics preserving if, for any system $\sigma = (\tau, \gamma, \xi)$,

$$
Eval_{\zeta(\sigma),w}(\mathbf{P}, \rho, \mathbf{u}, \tau') \simeqEval_{\sigma,w}(\mathbf{P}, \rho, \mathbf{u}, \tau)
$$

for every layout w, unprivileged command P, and registers ρ . Here, τ' is the store underlying $\zeta(\sigma)$. The equivalence is given by $(v, \tau_1) \simeq (v, \tau_2)$ if $\tau_1 =_{\mathsf{Id}_u} \tau_2$, and coincides with equality otherwise.

Notice that in the previous definition we require $\tau_1 =_{\mathsf{Id}_u} \tau_2$ instead of $\tau_1 = \tau_2$ in order to allow the transformation ζ to modify kernel-space procedures.

Thanks to *semantics preservation*, the second requirement on ζ can be fulfilled by asking that the system $\zeta(\sigma)$ can violate speculative kernel safety only if it violates kernel safety, as captured by Definition [6](#page-18-1) below.

Definition 6. We say that ζ *imposes speculative kernel safety* if, for every system σ such that $\zeta(\sigma) = (\tau, \gamma, \xi)$, every buffer μ with $\text{dom}(\mu) \subseteq \underline{w}(\text{Arrld})$ and store $\tau' =_{\text{Fun}} \tau$, if

$$
w \vdash_{\zeta(\sigma)} ((\gamma(\mathbf{s}), \rho, \mathbf{k}_{\mathbf{s}}), \mu(w \diamond \tau'), b_{ms}) \xrightarrow{O} \mathbf{b}^* \text{ unsafe},
$$

then

$$
w \vdash_{\zeta(\sigma)} ((\gamma(\texttt{s}), \rho, \texttt{k}_\texttt{s}), \overline{\mu(w \diamond \tau')}) \rightarrow^* \textsf{unsafe}.
$$

Observe that, by means of this property, we can easily show that if a system $\zeta(\sigma)$ is kernel safe, then it is also speculative kernel safe. Finally, by combining Definition [6](#page-18-1) and Definition [5,](#page-17-2) we obtain the following conclusion:

Proposition 1. If a system σ is kernel-safe, and the transformation ζ (i) imposes speculative kernel safety and (ii) is user-space semantics preserving, then (i) $\zeta(\sigma)$ is speculative kernel safe, and (ii) $\zeta(\sigma)$ is semantically equivalent to σ .

This result states that every kernel safe system can be transformed into another system that is equivalent to it from the user's perspective and enjoys stronger security guarantees. Notice that kernel safety cannot be provided solely by the adoption of layout randomization: by Theorem [1,](#page-10-0) we know that layout randomization provides kernel safety only modulo a small probability of failure.

Just as an example, we observe that a simple transformation that satisfies the requirements of Proposition [1](#page-18-2) can be implemented by placing a fence instruction before all the potentially unsafe operations. This instrumentation stops any ongoing speculation before executing potentially unsafe operations, and prevents their transient execution, yet leaving the program's semantics unaltered at the architectural level. This fencing transformation is expressed by η : Instr \rightarrow P on the level of instructions where, in particular:

$$
\eta(\ast E := F) \triangleq \text{fence}; \ast E := F
$$
\n
$$
\eta(x := \ast E) \triangleq \text{fence}; x := \ast E
$$
\n
$$
\eta(\text{call } E(F_1, \dots, F_k)) \triangleq \text{fence}; \text{call } E(F_1, \dots, F_k)
$$
\n
$$
\eta(\text{while } E \text{ do } P \text{ od}) \triangleq \text{while } E \text{ do } \eta(P) \text{ od}
$$
\n
$$
\eta(\text{if } E \text{ then } P \text{ else } Q \text{ fi}) \triangleq \text{if } E \text{ then } \eta(P) \text{ else } \eta(Q) \text{ fi},
$$

and it is the identity on the remaining instructions. Here, the transformation is extended homomorphically to a transformation $\eta : \mathbb{P} \to \mathbb{P}$. It is lifted to a system σ by systematically applying it to system calls and procedures $\tau(f)$ in kernel-memory $(f \in \text{Fund}_k)$.

Notice that the transformation η , does not stop completely speculation as, for instance, speculation on conditional instructions is still allowed. This is not in contrast with Definition [6](#page-18-1) because even in transient execution, a conditional instruction cannot perform any safety violation. However, as their branches can contain unsafe operations, the transformation visits them.

By observing that η enjoys both the properties in Definitions [5](#page-17-2) and [6,](#page-18-1) we can draw the following conclusion:

Theorem 3. If a system σ is kernel-safe, then $\eta(\sigma)$ is speculative kernel safe, and $\eta(\sigma)$ is semantically equivalent to σ .

This result is proven in Appendix [A.2.5.](#page-54-0)

In addition to η , other program transformations that fit the requirements of Proposition [1](#page-18-2) can be identified: for instance, the variation of η' that places a single fence instruction before sequences of loads — or of stores — is a good choice. Similarly, fence instructions can be omitted before direct calls. Finally, in presence of an external proof that shows that a system call s enjoys speculative kernel safety, the instrumentation may decide to leave that system call unchanged, yet preserving Definition [6.](#page-18-1)

8 Related Work

On Layout Randomization. The first work that provided a formal account of layout randomization was by Abadi and Plotkin [\[2\]](#page-21-0), later extended in [\[1,](#page-21-1) [4\]](#page-21-2). In these works, the authors show that layout randomization prevents, with high probability, malicious programs from accessing the memory of a victim in an execution context with shared address space. We have already discussed this in the body of the paper how these results do not model speculative execution or side-channel observations.

Spatial Memory Safety and Non-Interference Spatial memory safety is typically defined by associating a software component with a memory area and requiring that, at runtime, it only accesses that area [\[10,](#page-22-7) [46,](#page-25-10) [44\]](#page-24-7). Azevedo de Amorim et al. [\[7](#page-21-4)] demonstrated that memory safety can be expressed in terms of non-interference; this property, in turn, stipulates that the final output of a computation is not influenced by secret data that a program must keep confidential [\[23](#page-23-12)]. Both of these properties have been extended to the speculative model. The definition of *speculative memory safety* from [\[10\]](#page-22-7) closely aligns with ours, while speculative non-interference was initially introduced in the context of the Spectector symbolic analyzer [\[27\]](#page-23-9). Spectector's property captures information flows to side-channels that occur with speculative execution but not in sequential execution. In contrast to SPECTECTOR's approach, our definition aligns with *speculative constant-time* [\[14\]](#page-22-2), as it specifically targets information leaks that occur with speculative semantics.

Formal Analysis of Security Properties of Privileged Execution Environments. Barthe et al. [\[9](#page-22-8)] deploy a model with side-channel leaks and privileged execution mode, without specualtive execution. In particular, they are interested in studying the preservation of constant-time in virtualization platforms. They also model privilege-raising procedures hypercalls, similar to our system calls. They show that if one of the hosts is constant-time then the system enjoys a form of non-interference with respect to that host's secret memory. For this reason, although the two models are similar, the purposes of Barthe et al. [\[9](#page-22-8)] and our work are different: in [\[9](#page-22-8)] the victim and the attacker have the same levels of privilege and the role of the hypervisor is to ensure their separation whilst, in our work, the privileged code base is itself the victim.

Attacks to Kernel Layout Randomization Attacks that aim at leaking information on the kernel's layout are very popular and can rely on implementation bugs that reveal information the kernel's layout [\[35,](#page-24-8) [40,](#page-24-9) [15\]](#page-22-9) or on side-channel info-leaks [\[25](#page-23-2), [34,](#page-23-3) [39,](#page-24-3) [38, 38\]](#page-24-4). In particular attacks such as EchoLoad, TagBleed and EntryBleed [\[34](#page-23-3), [39](#page-24-3), [12](#page-22-10)] are successful even in presence of state-of-art mitigations such as Intel's Page Table Isolation (PTI) [\[32\]](#page-23-7). These attacks motivate our decision to take into account side-channel info-leaks. Due to address-space separation between kernel and user space programs, an attacker cannot easily use a pointer to a kernel address to access the victim's memory. So, in general, if the attacker does not control the value of a pointer that is used by the victim, this kind of leak is not harmful.

The Meltdown attack [\[37](#page-24-2)] uses speculative execution to overcome this limitation on operating systems running on Intel processors that do not adopt KAISER [\[26](#page-23-13)] or PTI [\[32](#page-23-7)]. In particular, the hardware can speculatively access an address before checking its permissions. The attack uses this small time window to access kernel memory content and leak it by using a side-channel info-leak gadget. These attacks can also be used to leak information on the layout: by dereferencing pointers under transient execution, the whole kernel's address space can be brute-forced without crashing the system. Due to the adoption of PTI [\[32\]](#page-23-7), this kind of attack is mitigated by removing most of the kernel-space addresses from the page tables of user-space programs. The BlindSide attack [\[24\]](#page-23-1) overcomes this issue by probing directly from kernel-space. Similar attacks can be mounted by triggering different forms of mispredictions [\[8,](#page-21-6) [41](#page-24-10)]. Arm's Pointer Authentication [\[51\]](#page-25-11) is a technique that prevents forging pointers by extending them with an authentication code and raising an error if the code is violated. This can be used to deploy protections similar to layout randomization, but Ravichandran et al. [\[49](#page-25-12)] showed that by leveraging speculative execution, it is possible to brute-force the authentication codes.

Relation Between Security in the Speculative- and Classic-model Blade [\[57\]](#page-25-2) is a protection mechanism which is aimed at preventing speculative data-flows by selectively stopping speculations. The authors show that, with this mechanism, all those program that are constant-time in the sequential model, are constant-time in the speculative model too. This is similar to what we do in Section [7,](#page-17-0) by imposing speculative kernel safety on a system that enjoys kernel safety. ProSpeCT [\[17\]](#page-22-3) is an open-source RISC-V processor that ensures a similar guarantee: each program that is constant-time in the classical model remains constant-time even when executed on that processor. This protection relies on taint-tracking and requires explicit annotations on the security level of programs' data.

Protections against Speculative Data Leaks Commonly, speculative attacks are aimed at leaking its victim's secret data [\[33](#page-23-6), [37,](#page-24-2) [17,](#page-22-3) [57](#page-25-2), [27,](#page-23-9) [28,](#page-23-10) [10](#page-22-7), [14](#page-22-2)]. As a consequence, many of the conventional mitigations against speculative attacks are aimed at preventing secret data from leaking during speculative execution. For instance, Speculative Load Hardening [\[13\]](#page-22-11) is a software protection measure which, in its simplest form, sets each value that is loaded from memory during transient execution to a constant value. By doing so, this mechanism does not prevent these value to be loaded i.e. its application to the kernel would not prevent the attacker from breaking speculative kernel safety. Together with the above-mentioned ProSpeCT, other hardware-level taint-tracking based mechanisms have been deployed to prevent speculative leaks [\[60](#page-26-0), [59](#page-25-13)]. These mechanisms limit the speculative execution of load instructions with different levels of strictness, ranging from completely preventing the execution of these instructions ([\[59\]](#page-25-13), strict propagation and load restriction mode), from just prohibiting the propagation of the loaded value [\[60](#page-26-0)]. Although this approach is promising, the above-mentioned mechanisms do not impose limitations on the speculative execution of indirect branches that may be used by attackers in practice to break speculative kernel safety.

9 Conclusion

We have formally demonstrated that kernel's layout randomization probabilistically ensures kernel safety for a classic model, where an attacker cannot compromise the system via speculative execution or side-channels, and users of an operating system execute without privileges, but victims can feature pointer arithmetic, introspection, and indirect jumps.

We have also shown that the protection offered by layout randomization does not naturally scale against attackers that can control speculative execution and side-channels, and stipulate a sufficient condition to enforce kernel safety in the Spectre era. We also propose mechanisms based on program transformations that provably enforce speculative kernel safety on a system, provided that this system already enjoys kernel safety in the classic model. To the best of our knowledge, our work is the first to formally investigate and provide ways to achieve kernel safety in the presence of speculative and side-channel vulnerabilities.

This work prepares the ground for future developments such as modeling more expressive attacker models, e.g. attackers speculating on the branch target buffer, related to Spectre v2 [\[33\]](#page-23-6), optimizing the instrumentation we presented in Section [7,](#page-17-0) and assessing its overhead on a real operating system.

An orthogonal research direction is to study more fine-grained safety properties instead of (specu*lative)* kernel safety — e.g. by distinguishing violations of CFI from violations of spatial safety, and data integrity from confidentiality, akin to what happens in [\[6\]](#page-21-7). In this direction, it would also be interesting to model a call stack in order to determine whether the safety of kernel's stack can be granted under other, possibly weaker, conditions.

Finally, a valuable future development is to extend our execution model with other features that are often used to undermine operating systems' security, such as dynamic memory allocation and dynamic module loading, with the aim to establish their impact on system's safety in presence of speculative attackers.

Acknowledgments

We are grateful to Gilles Barthe, Márton Bognár, Ugo Dal Lago, Lesly-Ann Daniel, Benjamin Grégoire, Jean-Pierre Lozi, and Frank Piessens for their comments on an early draft of the paper. This work was partially supported through the projects PPS ANR-19-C48-0014 and UCA DS4H ANR-17-EURE-0004, and by the Wallenberg AI, Autonomous Systems and Software Program (WASP) funded by the Knut and Alice Wallenberg Foundation.

References

- [1] Martín Abadi and Jérémy Planul. On layout randomization for arrays and functions. In David Basin and John C. Mitchell, editors, Principles of Security and Trust, pages 167–185, Berlin, Heidelberg, 2013. Springer Berlin Heidelberg. ISBN 978-3-642-36830-1.
- [2] Martín Abadi and Gordon D. Plotkin. On protection by layout randomization. ACM Trans. Inf. Syst. Secur., 15(2), jul 2012. ISSN 1094-9224. doi: 10.1145/2240276.2240279. URL <https://doi.org/10.1145/2240276.2240279>.
- [3] Martín Abadi, Mihai Budiu, Úlfar Erlingsson, and Jay Ligatti. Control-flow integrity. In Proceedings of the 12th ACM Conference on Computer and Communications Security, CCS '05, page 340–353, New York, NY, USA, 2005. Association for Computing Machinery. ISBN 1595932267. doi: 10.1145/1102120.1102165. URL <https://doi.org/10.1145/1102120.1102165>.
- [4] Martín Abadi, Jérémy Planul, and Gordon D. Plotkin. Layout Randomization and Nondeterminism, pages 1–39. Springer International Publishing, Cham, 2014. ISBN 978-3-319-06880-0. doi: 10.1007/978-3-319-06880-0 1. URL https://doi.org/10.1007/978-3-319-06880-0_1.
- [5] Basavesh Ammanaghatta Shivakumar, Gilles Barthe, Benjamin Grégoire, Vincent Laporte, and Swarn Priya. Enforcing fine-grained constant-time policies. In Proceedings of the 2022 ACM SIGSAC Conference on Computer and Communications Security, CCS '22, page 83–96, New York, NY, USA, 2022. Association for Computing Machinery. ISBN 9781450394505. doi: 10. 1145/3548606.3560689. URL <https://doi.org/10.1145/3548606.3560689>.
- [6] Sean Noble Anderson, Roberto Blanco, Leonidas Lampropoulos, Benjamin C. Pierce, and Andrew Tolmach. Formalizing stack safety as a security property. In 2023 IEEE 36th Computer Security Foundations Symposium (CSF), pages 356–371, New York, NY, USA, 2023. IEEE. doi: 10.1109/ CSF57540.2023.00037.
- [7] Arthur Azevedo de Amorim, Cătălin Hritçu, and Benjamin C. Pierce. The meaning of memory safety. In Lujo Bauer and Ralf Küsters, editors, *Principles of Security and Trust*, pages 79–105, Cham, 2018. Springer International Publishing. ISBN 978-3-319-89722-6.
- [8] Enrico Barberis, Pietro Frigo, Marius Muench, Herbert Bos, and Cristiano Giuffrida. Branch history injection: On the effectiveness of hardware mitigations against Cross-Privilege spectrev2 attacks. In 31st USENIX Security Symposium (USENIX Security 22), pages 971– 988, Boston, MA, August 2022. USENIX Association. ISBN 978-1-939133-31-1. URL <https://www.usenix.org/conference/usenixsecurity22/presentation/barberis>.
- [9] Gilles Barthe, Gustavo Betarte, Juan Campo, Carlos Luna, and David Pichardie. System-level non-interference for constant-time cryptography. In Proceedings of the 2014 ACM SIGSAC Conference on Computer and Communications Security, CCS '14, page 1267–1279, New York, NY, USA, 2014. Association for Computing Machinery. ISBN 9781450329576. doi: 10.1145/2660267. 2660283. URL <https://doi.org/10.1145/2660267.2660283>.
- [10] Gilles Barthe, Sunjay Cauligi, Benjamin Grégoire, Adrien Koutsos, Kevin Liao, Tiago Oliveira, Swarn Priya, Tamara Rezk, and Peter Schwabe. High-assurance cryptography in the spectre era. In 2021 IEEE Symposium on Security and Privacy (SP), pages 1884–1901, New York, NY, USA, 2021. IEEE. doi: 10.1109/SP40001.2021.00046.
- [11] Emery D. Berger and Benjamin G. Zorn. Diehard: Probabilistic memory safety for unsafe languages. In Proceedings of the 27th ACM SIGPLAN Conference on Programming Language Design and Implementation, PLDI '06, page 158–168, New York, NY, USA, 2006. Association for Computing Machinery. ISBN 1595933204. doi: 10.1145/1133981.1134000. URL <https://doi.org/10.1145/1133981.1134000>.
- [12] Claudio Canella, Michael Schwarz, Martin Haubenwallner, Martin Schwarzl, and Daniel Gruss. Kaslr: Break it, fix it, repeat. In Proceedings of the 15th ACM Asia Conference on Computer and Communications Security, ASIA CCS '20, page 481–493, New York, NY, USA, 2020. Association for Computing Machinery. ISBN 9781450367509. doi: 10.1145/3320269.3384747. URL <https://doi.org/10.1145/3320269.3384747>.
- [13] Chandler Carruth. Speculative load hardening, Sep 2018. URL <https://llvm.org/docs/SpeculativeLoadHardening.html>.
- [14] Sunjay Cauligi, Craig Disselkoen, Klaus v. Gleissenthall, Dean Tullsen, Deian Stefan, Tamara Rezk, and Gilles Barthe. Constant-time foundations for the new spectre era. In Proceedings of the 41st ACM SIGPLAN Conference on Programming Language Design and Implementation, PLDI 2020, page 913–926, New York, NY, USA, 2020. Association for Computing Machinery. ISBN 9781450376136. doi: 10.1145/3385412.3385970. URL <https://doi.org/10.1145/3385412.3385970>.
- [15] Yueqi Chen, Zhenpeng Lin, and Xinyu Xing. A systematic study of elastic objects in kernel exploitation. In Proceedings of the 2020 ACM SIGSAC Conference on Computer and Communications Security, CCS '20, page 1165–1184, New York, NY, USA, 2020. Association for Computing Machinery. ISBN 9781450370899. doi: 10.1145/3372297.3423353. URL <https://doi.org/10.1145/3372297.3423353>.
- [16] Jonathan Corbet. Supervisor mode access prevention, 2012. URL <https://lwn.net/Articles/517475/>.
- [17] Lesly-Ann Daniel, Marton Bognar, Job Noorman, Sébastien Bardin, Tamara Rezk, and Frank Piessens. ProSpeCT: Provably secure speculation for the Constant-Time policy. In 32nd USENIX Security Symposium (USENIX Security 23), pages 7161–7178, Anaheim, CA, August 2023. USENIX Association. ISBN 978-1-939133-37-3. URL <https://www.usenix.org/conference/usenixsecurity23/presentation/daniel>.
- [18] Theo de Raadt. Openbsd 6.3, Oct 2017. URL <https://www.openbsd.org/33.html>.
- [19] Jake Edge. Kernel address space layout randomization, 2013. URL <https://lwn.net/Articles/569635/>.
- [20] Stephen Fischer. Supervisor mode execution protection, 2011. URL https://www.ncsi.com/nsatc11/presentations/wednesday/emerging_technologies/fischer.pdf.
- [21] Thomas Garnier. Randomizing the linux kernel heap freelists, Sep 2016. URL <https://mxatone.medium.com/randomizing-the-linux-kernel-heap-freelists-b899bb99c767>.
- [22] Xinyang Ge, Nirupama Talele, Mathias Payer, and Trent Jaeger. Fine-grained control-flow integrity for kernel software. In 2016 IEEE European Symposium on Security and Privacy (EuroS&P), pages 179–194, New York, NY, USA, 2016. IEEE. doi: 10.1109/EuroSP.2016.24.
- [23] J. A. Goguen and J. Meseguer. Security policies and security models. In 1982 IEEE Symposium on Security and Privacy, New York, NY, USA, 1982. IEEE. doi: 10.1109/SP.1982.10014.
- [24] Enes Göktas, Kaveh Razavi, Georgios Portokalidis, Herbert Bos, and Cristiano Giuffrida. Speculative probing: Hacking blind in the spectre era. In Proceedings of the 2020 ACM SIGSAC Conference on Computer and Communications Security, CCS '20, page 1871–1885, New York, NY, USA, 2020. Association for Computing Machinery. ISBN 9781450370899. doi: 10.1145/3372297.3417289. URL <https://doi.org/10.1145/3372297.3417289>.
- [25] Daniel Gruss, Clémentine Maurice, Anders Fogh, Moritz Lipp, and Stefan Mangard. Prefetch side-channel attacks: Bypassing smap and kernel aslr. In Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security, CCS '16, page 368–379, New York, NY, USA, 2016. Association for Computing Machinery. ISBN 9781450341394. doi: 10.1145/2976749. 2978356. URL <https://doi.org/10.1145/2976749.2978356>.
- [26] Daniel Gruss, Moritz Lipp, Michael Schwarz, Richard Fellner, Clémentine Maurice, and Stefan Mangard. Kaslr is dead: Long live kaslr. In Eric Bodden, Mathias Payer, and Elias Athanasopoulos, editors, Engineering Secure Software and Systems, pages 161–176, Cham, 2017. Springer International Publishing. ISBN 978-3-319-62105-0.
- [27] Marco Guarnieri, Boris Köpf, José F. Morales, Jan Reineke, and Andrés Sánchez. Spectector: Principled detection of speculative information flows. In 2020 IEEE Symposium on Security and Privacy (SP), pages 1–19, New York, NY, USA, 2020. IEEE. doi: 10.1109/SP40000.2020.00011.
- [28] Marco Guarnieri, Boris Köpf, Jan Reineke, and Pepe Vila. Hardware-software contracts for secure speculation. In 2021 IEEE Symposium on Security and Privacy (SP), pages 1868–1883, New York, NY, USA, 2021. IEEE. doi: 10.1109/SP40001.2021.00036.
- [29] Ralf Hund, Carsten Willems, and Thorsten Holz. Practical timing side channel attacks against kernel space aslr. In 2013 IEEE Symposium on Security and Privacy, pages 191–205, New York, NY, USA, 2013. IEEE. doi: 10.1109/SP.2013.23.
- [30] Apple Inc. Mac os x has you covered, May 2011. URL <http://www.apple.com/macosx/security/>.
- [31] Intel $@64$ and IA-32 Architectures Software Developer's Manual. Intel Corporation, September 2023.
- [32] The kernel development community. Page table isolation (pti), 2023. URL <https://www.kernel.org/doc/html/next/x86/pti.html>.
- [33] Paul Kocher, Jann Horn, Anders Fogh, Daniel Genkin, Daniel Gruss, Werner Haas, Mike Hamburg, Moritz Lipp, Stefan Mangard, Thomas Prescher, Michael Schwarz, and Yuval Yarom. Spectre attacks: Exploiting speculative execution. In 2019 IEEE Symposium on Security and Privacy (SP), pages 1–19, New York, NY, USA, 2019. IEEE. doi: 10.1109/SP.2019.00002.
- [34] Jakob Koschel, Cristiano Giuffrida, Herbert Bos, and Kaveh Razavi. Tagbleed: Breaking kaslr on the isolated kernel address space using tagged tlbs. In 2020 IEEE European Symposium on Security and Privacy (EuroS&P), pages 309–321, New York, NY, USA, 2020. IEEE. doi: 10.1109/EuroSP48549.2020.00027.
- [35] Jakob Koschel, Pietro Borrello, Daniele Cono D'Elia, Herbert Bos, and Cristiano Giuffrida. Uncontained: Uncovering container confusion in the linux kernel. In 32nd USENIX Security Symposium (USENIX Security 23), pages 5055–5072, Anaheim, CA, August 2023. USENIX Association. ISBN 978-1-939133-37-3. URL <https://www.usenix.org/conference/usenixsecurity23/presentation/koschel>.
- [36] Jinku Li, Zhi Wang, Tyler Bletsch, Deepa Srinivasan, Michael Grace, and Xuxian Jiang. Comprehensive and efficient protection of kernel control data. IEEE Transactions on Information Forensics and Security, 6(4):1404–1417, 2011. doi: 10.1109/TIFS.2011.2159712.
- [37] Moritz Lipp, Michael Schwarz, Daniel Gruss, Thomas Prescher, Werner Haas, Anders Fogh, Jann Horn, Stefan Mangard, Paul Kocher, Daniel Genkin, Yuval Yarom, and Mike Hamburg. Meltdown: Reading kernel memory from user space. In 27th USENIX Security Symposium (USENIX Security 18), pages 973–990, Baltimore, MD, August 2018. USENIX Association. ISBN 978-1-939133-04-5. URL <https://www.usenix.org/conference/usenixsecurity18/presentation/lipp>.
- [38] Moritz Lipp, Michael Schwarz, Daniel Gruss, Thomas Prescher, Werner Haas, Anders Fogh, Jann Horn, Stefan Mangard, Paul Kocher, Daniel Genkin, Yuval Yarom, and Mike Hamburg. Meltdown: Reading kernel memory from user space. In 27th USENIX Security Symposium (USENIX Security 18), pages 973–990, Baltimore, MD, August 2018. USENIX Association. ISBN 978-1-939133-04-5. URL <https://www.usenix.org/conference/usenixsecurity18/presentation/lipp>.
- [39] William Liu, Joseph Ravichandran, and Mengjia Yan. Entrybleed: A universal kaslr bypass against kpti on linux. In Proceedings of the 12th International Workshop on Hardware and Architectural Support for Security and Privacy, HASP '23, page 10–18, New York, NY, USA, 2023. Association for Computing Machinery. ISBN 9798400716232. doi: 10.1145/3623652.3623669. URL <https://doi.org/10.1145/3623652.3623669>.
- [40] Ziqin Liu, Zhenpeng Lin, Yueqi Chen, Yuhang Wu, Yalong Zou, Dongliang Mu, and Xinyu Xing. Towards unveiling exploitation potential with multiple error behaviors for kernel bugs. IEEE Transactions on Dependable and Secure Computing, 21(1):1–18, 2023. doi: 10.1109/TDSC.2023. 3246170.
- [41] A. Mambretti, A. Sandulescu, A. Sorniotti, W. Robertson, E. Kirda, and A. Kurmus. Bypassing memory safety mechanisms through speculative control flow hijacks. In 2021 IEEE European Symposium on Security and Privacy (EuroS&P), pages 633–649, Los Alamitos, CA, USA, sep 2021. IEEE Computer Society. doi: 10.1109/EuroSP51992.2021.00048. URL <https://doi.ieeecomputersociety.org/10.1109/EuroSP51992.2021.00048>.
- [42] Tarjei Mandt. Attacking the ios kernel: A look at 'evasi0n', March 2013. URL <https://papers.put.as/papers/ios/2013/NISlecture201303.pdf>.
- [43] Ed Maste. Address space layout randomization (aslr), July 2023. URL <https://wiki.freebsd.org/AddressSpaceLayoutRandomization>.
- [44] Alexandra E. Michael, Anitha Gollamudi, Jay Bosamiya, Evan Johnson, Aidan Denlinger, Craig Disselkoen, Conrad Watt, Bryan Parno, Marco Patrignani, Marco Vassena, and Deian Stefan. Mswasm: Soundly enforcing memory-safe execution of unsafe code. In Proceedings of the 50th ACM SIGACT-SIGPLAN Symposium on Principles of Programming Languages, volume 7 of POPL '23, New York, NY, USA, jan 2023. Association for Computing Machinery. doi: 10.1145/ 3571208. URL <https://doi.org/10.1145/3571208>.
- [45] Jo˜ao Moreira, Sandro Rigo, Michalis Polychronakis, and Vasileios P Kemerlis. Drop the rop fine-grained control-flow integrity for the linux kernel, 2017.
- [46] Santosh Nagarakatte, Jianzhou Zhao, Milo M.K. Martin, and Steve Zdancewic. Softbound: Highly compatible and complete spatial memory safety for c. SIGPLAN Not., 44(6):245–258, jun 2009. ISSN 0362-1340. doi: 10.1145/1543135.1542504. URL <https://doi.org/10.1145/1543135.1542504>.
- [47] Android Open Source Project. Kernel hardening, August 2022. URL <https://source.android.com/docs/core/architecture/kernel/hardening>.
- [48] Liam Proven. Linux 6.1: Rust to hit mainline kernel, October 2022. URL https://www.theregister.com/2022/10/05/rust_kernel_pull_request_pulled/.
- [49] Joseph Ravichandran, Weon Taek Na, Jay Lang, and Mengjia Yan. Pacman: Attacking arm pointer authentication with speculative execution. In Proceedings of the 49th Annual International Symposium on Computer Architecture, ISCA '22, pages 685–698, New York, NY, USA, 2022. Association for Computing Machinery. ISBN 9781450386104. doi: 10.1145/3470496.3527429. URL <https://doi.org/10.1145/3470496.3527429>.
- [50] Elena Reshetova, Hans Liljestrand, Andrew Paverd, and N Asokan. Toward linux kernel memory safety. Software: Practice and Experience, 48(12):2237–2256, 2018.
- [51] Mark Rutland. Armv8. 3 pointer authentication, 2017.
- [52] Michael S and Vitaly Nikolenko. Linux kernel heap feng shui in 2022, May 2022. URL <https://duasynt.com/blog/linux-kernel-heap-feng-shui-2022>.
- [53] SecurityScorecard. Threat overview for linux kernel, November 2022. URL <https://www.cvedetails.com/product/47/Linux-Linux-Kernel.html>.
- [54] Hovav Shacham, Matthew Page, Ben Pfaff, Eu-Jin Goh, Nagendra Modadugu, and Dan Boneh. On the effectiveness of address-space randomization. In Proceedings of the 11th ACM Conference on Computer and Communications Security, CCS '04, page 298–307, New York, NY, USA, 2004. Association for Computing Machinery. ISBN 1581139616. doi: 10.1145/1030083.1030124. URL <https://doi.org/10.1145/1030083.1030124>.
- [55] Andrew S. Tanenbaum and Herbert Bos. Modern Operating Systems. Prentice Hall Press, USA, 4th edition, 2014. ISBN 013359162X.
- [56] PaX Team. Documentation for the pax project, 2003. URL <https://pax.grsecurity.net/docs/>.
- [57] Marco Vassena, Craig Disselkoen, Klaus von Gleissenthall, Sunjay Cauligi, Rami Gökhan Kıcı, Ranjit Jhala, Dean Tullsen, and Deian Stefan. Automatically eliminating speculative leaks from cryptographic code with blade. Proc. ACM Program. Lang., 5(POPL), jan 2021. doi: 10.1145/ 3434330. URL <https://doi.org/10.1145/3434330>.
- [58] Zhi Wang and Xuxian Jiang. Hypersafe: A lightweight approach to provide lifetime hypervisor control-flow integrity. In 2010 IEEE Symposium on Security and Privacy, pages 380–395, New York, NY, USA, 2010. IEEE. doi: 10.1109/SP.2010.30.
- [59] Ofir Weisse, Ian Neal, Kevin Loughlin, Thomas F. Wenisch, and Baris Kasikci. Nda: Preventing speculative execution attacks at their source. In Proceedings of the 52nd Annual IEEE/ACM International Symposium on Microarchitecture, MICRO '52, page 572–586, New York, NY, USA, 2019. Association for Computing Machinery. ISBN 9781450369381. doi: 10.1145/3352460.3358306. URL <https://doi.org/10.1145/3352460.3358306>.

[60] Jiyong Yu, Mengjia Yan, Artem Khyzha, Adam Morrison, Josep Torrellas, and Christopher W. Fletcher. Speculative taint tracking (stt): A comprehensive protection for speculatively accessed data. In Proceedings of the 52nd Annual IEEE/ACM International Symposium on Microarchitecture, MICRO '52, page 954–968, New York, NY, USA, 2019. Association for Computing Machinery. ISBN 9781450369381. doi: 10.1145/3352460.3358274. URL <https://doi.org/10.1145/3352460.3358274>.

A Appendix

A.1 Appendix for Section [5](#page-9-0)

A.1.1 Omitted Proofs and Results

We start by introducing some additional notation that is employed in this section, then we give the proof of Theorem [1;](#page-10-0) finally we prove all the intermediate results this proof relies on.

Semantics' Notation We write $\tau[(a, i) \leftarrow v]$ for the store that is identical to τ except for the array a, that is pointwise equal to $\tau(a)$, but the *i*-th entry, that it is updated to *v*. We use the notation $w \vdash_{\sigma} C \rightarrow^{!} D$ to denote the formula $\exists n'.w \vdash_{\sigma} C \rightarrow^{n} D \wedge D$ is terminal, and the notation $w \vdash_{\sigma} C \to^{!n} D$ to denote the formula $\exists n' \leq n \ldots \vdash_{\sigma} C \to^{n} D \wedge D$ is terminal. We also generalize the definition of the function $Eval_{\sigma,w}(\cdot)$ to take full configurations as arguments, this means that in the following, it will also be used as follows:

$$
Eval_{\sigma,w}((F, w \diamond \tau)) \triangleq \begin{cases} \Omega & \text{if } w \vdash_{\sigma} (F, w \diamond \tau) \uparrow, \\ (v, \tau') & \text{if } w \vdash_{\sigma} (F, w \diamond \tau) \rightarrow^* \\ & (\langle \epsilon, \rho[ret \mapsto v], b \rangle, w \diamond \tau'), \\ \text{err} & \text{if } w \vdash_{\sigma} (F, w \diamond \tau) \rightarrow^* \text{err}, \\ \text{unsafe} & \text{if } w \vdash_{\sigma} (F, w \diamond \tau) \rightarrow^* \text{unsafe}, \end{cases}
$$

and we extend the relation \cong by stating

$$
(v, \tau) \cong (\langle \epsilon, \rho[ret \mapsto v], b \rangle, w \diamond \tau)
$$

holds for every layout w, register map ρ and every flag b, and by taking its symmetric and transitive closure.

User- and Kernel-mode stack We write u(P) as a shorthand for $\text{ids}(P) \subset \text{Id}_n$, the predicate $\text{ids}(F)$ is defined inductively as follows:

$$
\mathbf{u}(\varepsilon) \triangleq \top \quad \mathbf{u}(f : F) \triangleq \mathbf{u}(f) \land \mathbf{u}(F) \quad \mathbf{u}(\langle P, \rho, b \rangle) \triangleq \mathbf{u}(P) \land b = \mathbf{u}.
$$

The predicate k_s is defined analogously: $k(P)$ holds whenever $P \in \text{Cmd}$, and it does not contain any syscall \cdot (\cdot) command and:

$$
\mathbf{k}_{s}(\varepsilon) \triangleq \top \quad \mathbf{k}_{s}(f:F) \triangleq \mathbf{k}_{s}(f) \wedge \mathbf{k}_{s}(F) \quad \mathbf{k}_{s}(\langle P, \rho, b \rangle) \triangleq \mathbf{k}(P) \wedge b = \mathbf{k}_{s}.
$$

We write $k(.)$ as a shorthand for $\exists s \in Sys.k_s(.)$.

Proof of Theorem [1.](#page-10-0) Let $\sigma = (\tau, \gamma, \xi)$ be a system, we want to show that for every unprivileged command P, register map ρ and distribution of layout μ , we have that:

$$
\Pr_{w \leftarrow \mu}\left[w \vdash_\sigma (\langle \mathbf{P}, \rho, \mathbf{u} \rangle, w \diamond \tau) \rightarrow^{!} \mathsf{unsafe}\right] \leq 1 - \delta_\mu.
$$

Assume that the claim does not hold. In particular, it means that:

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau) \rightarrow^! \text{unsafe} \right] > 1 - \delta_{\mu} > 0. \tag{\dagger}
$$

From this assumption, we deduce that there is a layout w' such that:

$$
w' \vdash_{\sigma} (\langle P, \rho, u \rangle, w' \diamond \tau) \rightarrow^{!} \text{ unsafe}, \tag{*}
$$

Which means that $Eval_{\sigma,w'}((\langle P,\rho,u\rangle, w'\diamond \tau)) = \text{unsafe}$; from this observation and Lemma [2](#page-28-0) (that we can apply because that all the system calls in σ are *layout-non-interferent*, and because all the layouts in the support of μ are identical with respect to user-space identifiers), we deduce that:

$$
\forall w \in \mathrm{supp}(\mu).Eval_{\sigma,w}((\langle P, \rho, u \rangle, w \diamond \tau)) \cong \text{unsafe}.
$$

This, in turn, can be rewritten as:

$$
\forall w \in \mathsf{supp}(\mu).Eval_{\sigma,w}((\langle P, \rho, u \rangle, w \diamond \tau)) \in \{\mathsf{unsafe}, \mathsf{err}\},\
$$

and allows us to deduce that

$$
\forall w \in \text{supp}(\mu) . \exists D_w, n_w. w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau) \rightarrow^{!n_w} D_w.
$$

In particular, since the size of the memory is finite, also Lay is finite, so there is a natural number \overline{n} such that $\overline{n} \geq \max_{w \in \text{Lay}} n_w$. Which means that:

$$
\forall w \in \mathrm{supp}(\mu).\exists D_w.w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau) \rightarrow^{!\overline{n}} D_w.
$$

From this assumption and Lemma [3](#page-32-0) applied on the system σ , the bound \overline{n} , the unprivileged attacker P, the initial register map ρ , and the distribution μ , we deduce that one of the two following statement holds:

– There are a register map ρ' and a store $\tau' \sim_{\text{Fun}} \tau$ such that for every $w \in \text{supp}(\mu)$ we have that

$$
w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau) \rightarrow^{!\overline{n}} (\langle \epsilon, \rho, u \rangle, w \diamond \tau'),
$$

 $- \ \Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau) \rightarrow^{!\overline{n}} \textsf{err} \right] \geq \delta_{\mu}.$

We go by cases on these two statements. If the first one holds, we unfold the definition of the notation \rightarrow ^{!n} and we deduce:

$$
\forall w, n. w \vdash_{\sigma} C \to^{!n} D \Rightarrow w \vdash_{\sigma} C \to^{n} D,
$$
 (†)

form this proposition, we can deduce that, for every $w \in \text{supp}(\mu)$ we have that:

$$
w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau) \rightarrow^{!} (\langle \epsilon, \rho', u \rangle, w \diamond \tau'),
$$

which means that

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau) \rightarrow' (\langle \epsilon, \rho', u \rangle, w \diamond \tau') \right] = 1,
$$

but since the final configuration cannot be contemporary unsafe and $(\langle \epsilon, \rho', \mathbf{u} \rangle, w \diamond \tau')$, we conclude that:

$$
\Pr_{w \leftarrow \mu}\left[w \vdash_\sigma (\langle \mathtt{P}, \rho, \mathtt{u} \rangle, w \diamond \tau) \rightarrow^! \mathtt{unsafe}\right] \leq \\ 1 - \Pr_{w \leftarrow \mu}\left[w \vdash_\sigma (\langle \mathtt{P}, \rho, \mathtt{u} \rangle, w \diamond \tau) \rightarrow^! (\langle \epsilon, \rho', \mathtt{u} \rangle, w \diamond \tau')\right] = 0.
$$

This shows the claim. If the second proposition holds, form (‡) we also deduce that:

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau) \rightarrow^! \text{err} \right] \geq \Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau) \rightarrow^! \overline{n} \text{err} \right] \geq \delta_{\mu}.
$$

We also observe that:

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_\sigma (\langle \mathbf{P}, \rho, \mathbf{u} \rangle, w \diamond \tau) \rightarrow^! \text{unsafe} \right] \leq 1 - \Pr_{w \leftarrow \mu} \left[w \vdash_\sigma (\langle \mathbf{P}, \rho, \mathbf{u} \rangle, w \diamond \tau) \rightarrow^! \text{err} \right] \leq 1 - \delta_\mu.
$$

This is another contradiction because we were assuming (†).

Lemma 2 (Preservation of layout-non-interference). If all the system calls of a system σ are layoutnon-interferent, then the whole system is layout-non-interferent with respect to unprivileged attackers in the following sense: for every unprivileged attacker P, register map ρ , pair of layouts w_1, w_2 such that \forall id \in $\mathsf{Id}_u \cdot w_1$ (id) = w_2 (id) and configuration C_1 we have that:

$$
w_1 \vdash_{\sigma} (\langle P, \rho, \mathbf{u} \rangle, w_1 \diamond \tau) \rightarrow^{!} C_1 \Rightarrow \mathit{Eval}_{\sigma, w_2}((\langle P, \rho, \mathbf{u} \rangle, w_2 \diamond \tau)) \cong C_1
$$

Proof. In order to make the induction work, we show a slightly stronger statement, namely, we substitute the quantification over P and ρ with a quantification over a non-empty stack F such that $\mathfrak{u}(F)$, and we rewrite the claim in a more convenient shape, where all the meta-variables that are not quantified explicitly are quantified universally.

$$
\forall n. \forall \tau' \sim_{\text{Fun}} \tau. (w_1 \vdash_{\sigma} (F, w_1 \diamond \tau') \rightarrow^n C_1 \wedge w_1 \vdash_{\sigma} C_1 \not\rightarrow) \Rightarrow \text{Eval}_{\sigma, w_2}((F, w_2 \diamond \tau')) \cong C_1
$$
 (C')

We start by showing that the claim (C) holds, and that we show that it entails that of the statement. In the proof we will extensively use the assumption on the layouts

$$
\forall \text{id} \in \text{Id}_{\mathbf{u}}. w_1(\text{id}) = w_2(\text{id}),\tag{\dagger}
$$

For this reason, we fix it on top and name it (†). The proof goes by induction on n.

- Case 0. We assume

$$
w_1 \vdash_{\sigma} (F, w_1 \diamond \tau') \rightarrow^0 C_1 \wedge w_1 \vdash_{\sigma} C_1 \nrightarrow
$$

Which means that $C_1 = (F, w_1 \circ \tau')$. From this observation, and because C_1 is terminal, we deduce that $F = \langle \epsilon, \rho', \mathbf{u} \rangle$. By introspection of the semantics, this also shows that

$$
w_2 \vdash_{\sigma} (F, w_2 \diamond \tau') \not\rightarrow,
$$

so we conclude that $Eval_{\sigma,w_2}((F, w_2 \diamond \tau'))$ is equal to $(\rho'(ret), \tau') \cong C_1$.

- CASE $n + 1$. We first go by cases on F in order to refuse the case where $F = \varepsilon$ because this, in turn would contradict the assumption

$$
w_1 \vdash_{\sigma} (F, w_1 \diamond \tau') \rightarrow^{n+1} C_1 \wedge w_1 \vdash_{\sigma} C_1 \nrightarrow (H)
$$

and can be shown by introspection on the semantics. So, in the following, we assume that $F =$ $\langle P, \rho, u \rangle : F'$, and we proceed by going by cases on P. Observe that the induction hypothesis coincides, syntactically, with(C').

- Case ϵ . Absurd.
- CASE $x := E$; Q. In this case, we rewrite the first part of (H) as follows:

$$
w_1 \vdash_{\sigma} (\langle x := \mathbf{E}; \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_1 \diamond \tau') \to (\langle \mathbf{Q}, \rho[x \leftarrow [\![\mathbf{E}]\!]_{\rho, w_1}], \mathbf{u} \rangle : F', w_1 \diamond \tau') \to^n C_1
$$

observe that $\mathbf{u}(\langle \mathbf{Q}, \rho[x \leftarrow [\mathbb{E}]_{\rho,w_1}], \mathbf{u} \rangle : F'$, so we can apply the IH and conclude that

$$
Eval_{\sigma, w_2}((\langle \mathbf{Q}, \rho[x \leftarrow [\![\mathbf{E}]\!]_{\rho, w_1}], \mathbf{u}) : F', w_2 \diamond \tau')) \cong C_1
$$

This means that, in order to conclude the proof, it suffices to observe that

$$
w_2 \vdash_{\sigma} (\langle x:=\mathbf{E};\mathbf{Q},\rho,\mathbf{u}\rangle : F',w_2 \diamond \tau') \to (\langle \mathbf{Q},\rho[x \leftarrow [\![\mathbf{E}]\!]_{\rho,w_1}],\mathbf{u}\rangle : F',w_2 \diamond \tau'),
$$

which, in turn, boils down in showing that $[\![\mathbf{E}]\!]_{\rho,w_1} = [\![\mathbf{E}]\!]_{\rho,w_2}$. Observe that from the definition of $u(F)$, we have that $x := E$; Q is an unprivileged command, so, in particular the identifiers within E are in Id_u , so the equality of the semantics of the expressions is a consequence of Remark [2,](#page-40-0) and of the premise \forall id ∈ $\mathsf{Id}_{\mathbf{u}}$. w_1 (id) = w_2 (id).

- Case skip; Q. Analogous to the case of assignments.

- CASE if E then P_⊥ else P_⊤ fi; Q. Analogous to the case of assignments.
- Case while E do P od; Q. Analogous to the case of assignments.
- CASE $*E := F$; Q. In this case, we start by observing that $[\![E]\!]_{\rho,w_1} = [\![E]\!]_{\rho,w_2}$ for the same reasons of the case on assignments. This also means that $[\mathbb{E}]\rho^{\mathsf{Addr}}_{\rho,w_1} = [\mathbb{E}]\rho^{\mathsf{Addr}}_{\rho,w_2}$. Call this address p. For the same reasons, we also know that $[\![\mathbf{F}]\!]_{\rho,w_1} = [\![\mathbf{F}]\!]_{\rho,w_2}$, and we call this value v. From the assumption (†) we deduce that $w_1(\text{Arrld}_u) = w_2(\text{Arrld}_u)$, and we name that set P. We apply the excluded middle principle (EM) on $p \in P$.
	- CASE $p \in P$. In this case, the rule [STORE] can be applied to both the configurations

$$
(\langle\ast\mathtt{E}:=\mathtt{F};{\mathtt{Q}},\rho,\mathtt{u}\rangle:F',w_1\diamond\tau')
$$

and

$$
(\langle\ast \texttt{E}:=\texttt{F};\texttt{Q},\rho,\texttt{u}\rangle:F',w_2\diamond \tau')
$$

under the layouts w_1 and w_2 , obtaining respectively:

$$
(\langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_1 \diamond \tau'[p \leftarrow v])
$$

and

$$
(\langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_2 \diamond \tau'[p \leftarrow v]).
$$

from the assumption $p \in \underline{w}_1(\mathsf{Arrld}_u)$ and the definition of \underline{w}_1 , we deduce that there is a \in ArrId_u and $0 \le i \le$ size(a) such that $w_1(a) + i = p$. From (†), we also deduce that $w_2(a) + i = p$, so we can apply Remark [3](#page-40-1) in order to show that

$$
w_1 \diamond \tau'[p \leftarrow v] = w_1 \diamond \tau'[(a, i) \leftarrow v]
$$

and that

$$
w_2 \diamond \tau'[p \leftarrow v] = w_1 \diamond \tau'[(a, i) \leftarrow v].
$$

Finally, we observe that $u(\langle \mathbf{Q}, \rho, u \rangle : F')$ holds and that

$$
\tau'[(\mathbf{a},i) \leftarrow v] \sim_{\mathsf{Fund}} \tau' \sim_{\mathsf{Fund}} \tau
$$

holds as well, so we can apply the IH, and conclude the proof of this sub-derivation.

- CASE $p \notin P$. In this case, from (†), we deduce that $p \in \underline{w}_2(\text{Arrld}_u)$, so we observe that the rule [[Store-Error](#page-7-8)] can be applied to show both

$$
w_1 \vdash_{\sigma} (\langle \ast \mathbf{E} := \mathbf{F}; \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_1 \diamond \tau') \to \text{err},
$$

and

$$
w_2 \vdash_{\sigma} (\langle \ast \mathbf{E} := \mathbf{F}; \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_2 \diamond \tau') \to \text{err}.
$$

This shows the claim.

- CASE $x := *E$; Q. Analogous to the case of memory store operations.
- CASE call $E(F_1, \ldots, F_k)$; Q. This case is also very similar to that of memory loads, but requires some non-trivial observations. Even in this case, we start by defining p as $\llbracket \mathbf{E} \rrbracket_{\rho,w_1}^{\mathsf{Addr}}$ and observing that it is also equal to $[\mathbb{E}]_{\rho,w_2}^{\mathsf{Addr}}$. Similarly, we introduce the values v_1,\ldots,v_k that respectively correspond to the semantics of F_1, \ldots, F_k evaluated under ρ and both the layouts w_1, w_2 . Then we observe that, because of (†), $w_1(\text{Fund}_u) = w_2(\text{Fund}_u)$, so we call this set P_{Fund_u} , and we apply the EM principle on $p \in P_{\mathsf{Fund}_u}$.
	- CASE $p \in P_{\text{Fund}_u}$. In this case, there is $f \in \text{Fund}_u$ such that $w_1(f) = p$, and we can deduce $p = w_2(f)$ from \dagger . From these conclusions, and the definition of \diamond , we deduce that $w_1 \diamond \tau'(p) =$ $\tau'(\texttt{f}) = \tau(\texttt{f})$, (the last step comes from the assumption $\tau' \sim_{\text{Fund}} \tau$), and similarly for $w_1 \circ \tau'(p)$. Since $p \in P_{\mathsf{Fund}_u}$, we deduce that

$$
w_1 \vdash_{\sigma} (\langle \text{call } E(F_1, \ldots, F_k); \text{Q}, \rho, u \rangle : F', w_1 \diamond \tau') \rightarrow (\langle \tau(f), \rho'_0, u \rangle : \langle \text{Q}, \rho, u \rangle : F', w_1 \diamond \tau'),
$$

and

$$
w_2 \vdash_{\sigma} (\langle \text{call } E(F_1, \ldots, F_k); \textbf{Q}, \rho, \textbf{u} \rangle : F', w_2 \diamond \tau') \rightarrow (\langle \tau(f), \rho_0', \textbf{u} \rangle : \langle \textbf{Q}, \rho, \textbf{u} \rangle : F', w_2 \diamond \tau'),
$$

where $\rho'_0 = \rho_0[x_1,\ldots,x_k \leftarrow v_1,\ldots,v_k]$. Finally, we observe that, from the assumption on τ , we know that $\tau(f)$ is an unprivileged program. So, in particular,

$$
\mathtt{u}(\langle \tau(\mathtt{f}), \rho_0', \mathtt{u} \rangle : \langle \mathtt{Q}, \rho, \mathtt{u} \rangle : F')
$$

holds. This allows us to apply the IH and conclude the proof.

- CASE $p \notin P_{\text{Fund}_u}$. Analogous to the corresponding case for memory store operations.

- CASE syscall $s(E_1, \ldots, E_k)$; Q. This is maybe the most interesting case of this proof. We start by introducing the values v_1, \ldots, v_k that respectively correspond to the semantics of F_1, \ldots, F_k evaluated under ρ and both the layouts w_1, w_2 ; this is shown in the same way we show $[\mathbb{E}]_{w_1,\rho} =$ $[\![\mathtt{E}]\!]_{w_2,\rho}$ in the case of assignments. By introspection of the rule [[SC](#page-7-5)], we deduce that both the following statements hold:

$$
w_1 \vdash_{\sigma} (\langle \texttt{syscall s}(F_1, \ldots, F_k); \texttt{Q}, \rho, \texttt{u} \rangle : F', w_1 \diamond \tau') \to (\langle \gamma(s), \rho'_0, k_s \rangle : \langle \texttt{Q}, \rho, \texttt{u} \rangle : F', w_1 \diamond \tau'),
$$

and

$$
w_2 \vdash_{\sigma} (\langle \texttt{syscall s}(F_1, \ldots, F_k); \mathtt{Q}, \rho, \mathtt{u} \rangle : F', w_2 \diamond \tau') \to (\langle \gamma(\mathtt{s}), \rho_0', \mathtt{k}_\mathtt{s} \rangle : \langle \mathtt{Q}, \rho, \mathtt{u} \rangle : F', w_2 \diamond \tau'),
$$

where $\rho'_0 = \rho_0[x_1, \ldots, x_k \leftarrow v_1, \ldots, v_k]$. Unfortunately, we cannot apply the IH on the configuration

$$
(\langle \gamma(\mathbf{s}), \rho_0', \mathbf{k}_\mathbf{s}\rangle : \langle \mathbf{Q}, \rho, \mathbf{u}\rangle : F', w_1 \diamond \tau')
$$

because $\mathbf{u}(\langle \gamma(s), \rho_0', \mathbf{k}_s \rangle : \langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F')$ does not hold. However, we can go by cases on

$$
\mathit{Eval}_{\sigma, w_1}(\gamma(s), \rho_0', k_s, \tau')
$$

- Case Ω. From Lemma [7,](#page-41-0) we deduce that

$$
Eval_{\sigma, w_1}((\langle \gamma(s), \rho'_0, k_s \rangle : \langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_1 \diamond \tau')) = \Omega,
$$

which is absurd because we were assuming

$$
w_1 \vdash_{\sigma} (\langle \gamma(s), \rho'_0, \mathbf{k}_s \rangle : \langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_1 \diamond \tau') \rightarrow^{n+1} C_1 \wedge w_1 \vdash_{\sigma} C_1 \not\rightarrow.
$$

- CASE unsafe. From the *layout-non-intreference property* Definition [2,](#page-9-5) we deduce that

$$
\mathit{Eval}_{\sigma, w_2}(\gamma(s), \rho_0', k_s, \tau') \in \{\mathsf{err}, \mathsf{unsafe}\}
$$

we take err as an example. This means that

$$
\exists h.w_2 \vdash_{\sigma} (\langle \gamma(s), \rho'_0, k_s \rangle, w_2 \diamond \tau') \rightarrow^h \textsf{err}.
$$

From Lemma [7](#page-41-0) applied on the reduction with w_1 , we deduce that the initial configuration reaches the final configuration unsafe, so it must be the case where C_1 = unsafe. By applying the same lemma to the reduction with w_2 , we deduce that

$$
w_2 \vdash_\sigma (\langle \gamma(\texttt{s}), \rho_0', b \rangle : \langle \mathtt{Q}, \rho, \mathtt{u} \rangle : F', w_2 \diamond \tau') \rightarrow^! \textsf{err}.
$$

We conclude by observing that unsafe ≅ err. The case with unsafe is analogous.

- Case err. Analogous to the previous case.

- CASE (v, m) . We start by observing that $m = w_1 \diamond \tau''$ for some τ'' because of Remark [4;](#page-40-2) form the layout-non-interference property Definition [2,](#page-9-5) we deduce that

$$
Eval_{\sigma, w_2}(\gamma(s), \rho_0', \mathbf{k}_s, \tau') = (v, \tau'');
$$

by applying two times Lemma [7,](#page-41-0) we deduce that:

$$
w_1 \vdash_{\sigma} (\langle \text{syscall s}(F_1, \ldots, F_k); \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_1 \diamond \tau') \to (\langle \gamma(s), \rho'_0, k_s \rangle : \langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_1 \diamond \tau') \to (\langle \mathbf{Q}, \rho[ret \leftarrow v], \mathbf{u} \rangle : F', w_1 \diamond \tau'')
$$

and

$$
w_2 \vdash_{\sigma} (\langle \text{syscall s}(F_1, \ldots, F_k); \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_2 \diamond \tau') \to (\langle \gamma(s), \rho'_0, k_s \rangle : \langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_2 \diamond \tau') \to (\langle \mathbf{Q}, \rho[ret \leftarrow v], \mathbf{u} \rangle : F', w_2 \diamond \tau'')
$$

Then, we observe that we are assuming

$$
w_1 \vdash_{\sigma} (\langle \text{syscall s}(F_1, \ldots, F_k); \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_1 \diamond \tau') \rightarrow^{n+1} C_1,
$$

and C_1 is terminal, so it must be the case where $w_1 \vdash_{\sigma} (\langle \mathbf{Q}, \rho[ret \leftarrow v], \mathbf{u} \rangle : F', w_1 \diamond \tau'') \rightarrow C_1$. In particular, this requires less than n steps. From the assumption $u(F)$, we also deduce $u(F')$, and $u(\langle \mathbf{Q}, \rho[ret \leftarrow v], \mathbf{u} \rangle : F')$ and from Remark [4](#page-40-2) we conclude that $\tau'' \sim_{\text{Fund}} \tau' \sim_{\text{Fund}} \tau$, so we can apply the IH to

$$
(\langle \mathbf{Q}, \rho[ret \leftarrow v], \mathbf{u} \rangle : F', w_1 \diamond \tau'')
$$

and deduce that

$$
Eval_{\sigma, w_2}((\langle \epsilon, \rho', b_2 \rangle : F', w_2 \diamond \tau'')) \cong C_1,
$$

which concludes the proof.

Now that (C') has been established, it suffices to observe that the claim of the theorem is a particular case of (C) where instead of a general τ' we chose τ , and instead of a general stack we chose $(\langle P, \rho, u \rangle, w_1 \diamond \tau)$, and finally, instead of a generic number of steps, we chose exactly the number of steps that this configuration employs to reach the terminal configuration C_1 . □

Lemma 3 (Main Lemma). For every layout non-leaking system $\sigma = (\tau, \gamma, \xi)$, every $n \in \mathbb{N}$, unprivileged program P, register map ρ , and distribution μ , if

$$
\forall w \in \mathrm{supp}(\mu) . \exists D_w . w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau) \rightarrow^{!n} D_w,
$$

and

$$
\forall \mathrm{id} \in \mathrm{Id}_{\mathrm{u}}.\forall w_1, w_2 \in \mathrm{supp}(\mu).w_1(\mathrm{id}) = w_2(\mathrm{id}),
$$

one of the two following statements holds:

- There are a register map ρ' and a store $\tau' \sim_{\text{Fun}} \tau$ such that for every $w \in \text{supp}(\mu)$ we have that

$$
w \vdash_{\sigma} (\langle P, \rho, \mathbf{u} \rangle, w \diamond \tau) \rightarrow^{!n} (\langle \epsilon, \rho', \mathbf{u} \rangle, w \diamond \tau'),
$$

$$
- \Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau) \rightarrow^{!n} \text{err} \right] \geq \delta_{\mu}.
$$

Proof. In order to ease the induction, we show a slightly stronger statement, namely, we substitute the quantification over P and ρ with a quantification over a non-empty stack F such that $u(F)$, we quantify over a general $\tau' \sim_{\text{Fund}} \tau$ instead of τ , and we rewrite the claim in a more convenient shape, where all the meta-variables that are not quantified explicitly are quantified globally and universally. The resulting claim is: if $\forall w \in \text{supp}(\mu) . \exists D_w . w \vdash_{\sigma} (F, w \diamond \tau') \rightarrow^{!n} D_w$, then:

- $\exists \rho', \tau'' \sim_{\mathsf{Funld}} \tau'.\forall w \in \mathsf{supp}(\mu).w \vdash_\sigma (F, w \diamond \tau') \to^{!n}$ $(\langle \epsilon, \rho', \mathbf{u} \rangle, w \diamond \tau''),$ or
- $-\left|\Pr_{w \leftarrow \mu}\left[w \vdash_{\sigma} (F, w \diamond \tau') \rightarrow^{!n} \textsf{err}\right]\right| \geq \delta_{\mu}.$

We call this auxiliary claim C' and we go by induction on n .

- Case 0. in this case, we assume

$$
\forall w \in \text{supp}(\nu) . \exists D_w. w \vdash_{\sigma} (F, w \diamond \tau') \rightarrow^{!0} D_w,
$$

and, from this premise, we deduce that $(F, w \circ \tau')$ is terminal, so from the definition of the notation $\rightarrow^!,$ u(F) and the assumption on the size of F, we deduce that $F = \langle \epsilon, \rho, \mathbf{u} \rangle : \epsilon$, so the claim holds trivially by choosing the register map ρ and the store τ' .

- CASE $n + 1$. In this case, we start by assuming

$$
\forall w \in \text{supp}(\mu) . \exists D_w . w \vdash_{\sigma} (F, w \diamond \tau') \rightarrow^{!n+1} D_w \tag{H}
$$

and we go by cases on F; the case where $F = \varepsilon$ because this, in turn, would contradict the assumption (H) because $(\varepsilon, w \diamond \tau')$ would be a terminal configuration. So, in the following, we assume that $F = \langle P, \rho, u \rangle : F'$, and we proceed by going by cases on P. Observe that the induction hypothesis coincides, syntactically, with (C') .

- CASE $x := E; Q$. In this case, we start by observing that there is a value v such that for every layout $w \in \text{supp}(\mu)$, we have that $[\![\mathbb{E}]\!]_{\rho,w} = v$. More precisely, this comes from Remark [2](#page-40-0) because we assumed that for every id \in Id_u , and every $w_1, w_2 \in \mathsf{supp}(\mu)$, it holds that $w_1(\text{id}) = w_2(\text{id})$ and, in particular, this holds for those identifiers that appear in E and that belong to Id_u by assumption. From (H) we deduce that for every $w \in \text{supp}(\nu)$:

$$
w \vdash_\sigma (\langle x := \mathbf{E}; \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w \diamond \tau') \rightarrow (\langle \mathbf{Q}, \rho[x \leftarrow v], \mathbf{u} \rangle : F', w \diamond \tau') \qquad \qquad (*)
$$

observe that $u(\langle \mathbf{Q}, \rho[x \leftarrow v], \mathbf{u} \rangle : F'$, so we can apply the IH to this stack and τ' and conclude that one among (A) and (B) below holds.

$$
\exists \rho', \tau'' \sim_{\text{Fund}} \tau'.\forall w \in \text{supp}(w).w \vdash_{\sigma} (\langle \mathbf{Q}, \rho[x \leftarrow v], \mathbf{u} \rangle : F', w \diamond \tau') \rightarrow^{!n} (\langle \epsilon, \rho', \mathbf{u} \rangle, w \diamond \tau'') \tag{A}
$$

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle \mathbf{Q}, \rho [x \leftarrow v], \mathbf{u} \rangle : F', w \diamond \tau') \rightarrow^{!n} \text{err} \right] \ge \delta_{\mu}.
$$
 (B)

We go by cases on this disjunction.

- CASE A. In this case, we introduce ρ' and τ'' from the IH, we assume τ'' ∼Funld τ', we fix a layout $w \in \mathsf{supp}(\mu)$ and from $(*)$ and (A) , we conclude

$$
w \vdash_\sigma (\langle x := \mathtt{E}; \mathtt{Q}, \rho, \mathtt{u} \rangle : F', w \diamond \tau') \rightarrow^{n+1} (\langle \epsilon, \rho', \mathtt{u} \rangle, w \diamond \tau'')
$$

Due to the generality of w (inside $\text{supp}(\mu)$), we can introduce the universal quantification over the elements of that set. This concludes the proof.

- CASE B. We call E the set of all the layouts $\overline{w} \in \mathsf{supp}(\mu)$ such that

$$
\overline{w} \vdash_\sigma (\langle \mathtt{Q}, \rho[x \leftarrow v], \mathtt{u} \rangle : F', w \diamond \tau') \rightarrow^{!n} \mathtt{err}
$$

Observe that we can apply the assumption (∗) to each of these layouts. This shows that

$$
\forall \overline{w} \in E. \overline{w} \vdash_{\sigma} (\langle x:=\text{E};\text{Q},\rho,\text{u}\rangle : F', \overline{w} \diamond \tau') \rightarrow^{!n+1} \text{err}.
$$

From (B), we know that the probability associated to this set is bigger than δ_{μ} and this shows the claim.

- CASE ϵ . Analogous to the case above.
- Case skip; Q. Analogous to the case of assignments.
- CASE if E then P⊥ else P⊤ fi; Q. Analogous to the case of assignments.

- Case while E do P od; Q. Analogous to the case of assignments.

- CASE $*E := F; Q$. In this case, we start by observing that there is a value v_E such that for every $w \in \text{supp}(\mu)$, we have that $\mathbb{E}\|_{\rho,w} = v_E$. This comes from Remark [2,](#page-40-0) because we assume that $u(*E := F; Q)$, which means that all the identifiers within E belong to Id_u , and because we assume that all the layouts in the support of μ store these interpret these identifiers in the same way. From the same reason, there is a unique value v_F such that for every $w \in \text{supp}(\mu)$, we have that $[\![\mathbf{F}]\!]_{\rho,w} = v_{\mathbf{F}}$. This also means that there is a unique $p \in \mathsf{Addr}$ that is equal to v^{Addr} . For the same reason again, we can deduce that there is a unique set of addresses P_{Artld_i} such that for every $w \in \mathsf{supp}(\mu)$, we have that $\underline{w}(\text{Arrld}_u) = P_{\text{Arrld}_u}$. Finally, we observe that, because of the assumptions on the set of layouts Lay, $P_{\text{Arrld}_u} \subseteq \text{Addr}_u$. We go by cases (EM) on $p \in P_{\text{Arrld}_u}$.

- CASE $p \in P_{\text{Arrld}_u}$. The rule [STORE] can be applied to each configuration

$$
(\langle\ast\mathtt{E}:=\mathtt{F};{\mathtt{Q}},\rho,\mathtt{u}\rangle:F',w\diamond\tau')
$$

for every $w \in \text{supp}(\mu)$, obtaining:

$$
(\langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w \diamond \tau'[p \leftarrow v_{\mathbf{E}}]);
$$

from the assumption $p \in \underline{w}(\text{Arrld}_u)$ and the definition of \underline{w} , we deduce that there is a $\in \text{Arrld}_u$ and $0 \le i \le \text{size}(a)$ such that $w(a) + i = p$ and that for every other layout $\overline{w} \in \text{supp}(\mu)$ it must hold that $\overline{w}(a) + i = p$, so we can apply Remark [3](#page-40-1) in order to show that

$$
\forall w \in \text{supp}(\mu). w \diamond \tau'[p \leftarrow v_{\mathbb{E}}] = w \diamond \tau'[(a, i) \leftarrow v_{\mathbb{E}}].
$$

Finally, we observe that $u(\langle \mathbf{Q}, \rho, u \rangle : F')$ holds and that

$$
\tau'[(\mathsf{a},i) \leftarrow v_{\mathrm{E}}] \sim_{\mathsf{Fund}} \tau' \sim_{\mathsf{Fund}} \tau
$$

holds as well, so we can apply the IH and conclude the proof of this sub-derivation as we did in the case of assignments.

- CASE $p \notin P_{\text{Arrld}_u}$. In this case, from (†), we deduce that $p \in \underline{w}_2(\text{Arrld}_u)$, so we observe that the rule [[Store-Error](#page-7-8)] can be applied to show both

$$
w_1 \vdash_{\sigma} (\langle \ast \mathbf{E} := \mathbf{F}; \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_1 \diamond \tau') \to \text{err},
$$

and

$$
w_2 \vdash_{\sigma} (\langle \ast \mathbf{E} := \mathbf{F}; \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w_2 \diamond \tau') \to \textsf{err}.
$$

This shows the claim.

- CASE $x := *E; 0$. Analogous to the case of memory store operations.
- CASE call $E(F_1, \ldots, F_k); Q$. This case is also very similar to that of memory loads, but requires some considerations on the stacks of the target configurations. We start observing that there is a unique address p such that for every $w \in \text{supp}(\mu)$, we have that $[\![\mathbf{E}]\!]_{\rho,w}^{\text{Addr}} = p$. Similarly, we introduce the values v_1, \ldots, v_k that respectively correspond to the semantics of F_1, \ldots, F_k evaluated under ρ and every the layouts $w \in \text{supp}(\mu)$. Then we observe that there is a set P_{Fund_n} such that $\forall w \in \mathsf{supp}(\mu)$, we have that $\underline{w}(\mathsf{Fund}_u) = P_{\mathsf{Fund}_u}$. The proof continues by applying the EM principle on $p \in P_{\mathsf{Fund}_u}$.
	- CASE $p \in P_{\mathsf{Fund}_u}$. In this case, there is a unique $f \in \mathsf{Fund}_u$ such that for every $w \in \mathsf{supp}(\mu)$, we have $w(f) = p$ and from this observation, and the definition of \diamond , we deduce that for every $w \in \mathsf{supp}(\mu)$ $w \diamond \tau'(p) = \tau'(f) = \tau(f)$, (the last step comes from the assumption $\tau' \sim_{\mathsf{Fund}} \tau$). Since $p \in P_{\mathsf{Fund}_u}$, we deduce that

$$
\forall p \in P_{\mathsf{Fundd}_{\mathtt{u}}} . w \vdash_{\sigma} (\langle \mathsf{call}\ \mathtt{E}(\mathtt{F}_1, \ldots, \mathtt{F}_k) ; \mathtt{Q}, \rho, \mathtt{u} \rangle : F', w \diamond \tau') \rightarrow \\ (\langle \tau(f), \rho'_0, \mathtt{u} \rangle : \langle \mathtt{Q}, \rho, \mathtt{u} \rangle : F', w \diamond \tau'),
$$

where $\rho'_0 = \rho_0[x_1,\ldots,x_k \leftarrow v_1,\ldots,v_k]$. Finally, we observe that $\mathbf{u}(\langle \tau(f), \rho'_0, \mathbf{u} \rangle : \langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F')$ holds because we require that τ associates unprivileged commands to identifiers in FunId_u. This allows us to apply the IH. The proof continues as in the case of assignments.

- CASE $p \notin P_{\text{Fund}_u}$. Analogous to the corresponding case for memory store operations.

- CASE syscall $s(E_1, \ldots, E_k)$; Q. We start by introducing the values v_1, \ldots, v_k that respectively correspond to the semantics of F_1, \ldots, F_k evaluated under ρ and all the layouts $w \in \text{supp}(\mu)$. By introspection of the rule [[SC](#page-7-5)], we deduce that for every $w \in \text{supp}(\mu)$, we have that:

$$
w \vdash_{\sigma} (\langle \text{syscall s}(F_1, \ldots, F_k); \mathbb{Q}, \rho, u \rangle : F', w \diamond \tau') \to (\langle \gamma(s), \rho'_0, k_s \rangle : \langle \mathbb{Q}, \rho, u \rangle : F', w \diamond \tau'), \quad (\dagger)
$$

where $\rho'_0 = \rho_0[x_1, \ldots, x_k \leftarrow v_1, \ldots, v_k]$. Unfortunately, we cannot apply the IH on the configuration

$$
(\langle \gamma(\mathbf{s}), \rho_0', \mathbf{k}_{\mathbf{s}} \rangle : \langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w \diamond \tau')
$$

because $u(\langle \gamma(s), \rho_0', k_s \rangle : \langle \mathbf{Q}, \rho, u \rangle : F')$ does not hold. However, we can apply Lemma [4](#page-35-0) to obtain that one of the following statements holds:

$$
\exists \overline{\rho}, \overline{\tau} \sim_{\mathsf{Fund}} \tau'.\forall w \in \mathsf{Lay}.w \vdash_{\sigma} (\langle \gamma(s), \rho_0', \mathbf{k}_s \rangle, w \diamond \tau') \rightarrow^{!} (\langle \epsilon, \overline{\rho}, \mathbf{k}_s \rangle, w \diamond \tau''),
$$
 (A)

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle \gamma(s), \rho_0', \mathbf{k}_s \rangle, w \diamond \tau') \rightarrow^! \text{err} \right] \ge \delta_{\mu},\tag{B}
$$

$$
\forall w \in \text{Lay}.Eval_{\sigma,w}((\langle \gamma(s), \rho_0', \mathbf{k}_s \rangle, w \diamond \tau')) = \Omega.
$$
 (C)

- CASE A. From (A) and Lemma [7,](#page-41-0) we can conclude that there are a register map $\bar{\rho}$, a store $\bar{\tau}$ such that for every $w \in \text{supp}(\mu) \subseteq \text{Lay}$, we have:

$$
w \vdash_\sigma (\langle \gamma(s), \rho_0', \mathbf{k}_s \rangle : \langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w \diamond \tau') \rightarrow^{!} (\langle \mathbf{Q}, \rho[ret \leftarrow \overline{\rho}(ret)], \mathbf{u} \rangle : F', w \diamond \overline{\tau}).
$$

We also observe that $\tau \sim_{\text{Funld}} \tau'$ for Remark [4.](#page-40-2) By composing this observation with (†), we conclude that

$$
w \vdash_\sigma (\langle \texttt{syscall s}(F_1, \ldots, F_k); \mathtt{Q}, \rho, \mathtt{u}\rangle : F', w \diamond \tau') \rightarrow^! (\langle \mathtt{Q}, \rho[ret \leftarrow \overline{\rho}(ret)], \mathtt{u}\rangle : F', w \diamond \overline{\tau})
$$

holds as well. From (H) we also deduce that the number of steps must be smaller than $n + 1$, and from (†), we deduce that it must be greater than 1. This means that the IH can be applied on $(\langle \mathbf{Q}, \rho[ret \leftarrow \overline{\rho}(ret)], \mathbf{u} \rangle : F', w \diamond \overline{\tau})$, the proof is then similar to the analogous case for assignments.

- CASE B. We call E the set of all the layouts $\overline{w} \in \mathsf{supp}(\mu)$ such that

$$
\overline{w}\vdash_\sigma(\langle \gamma(\texttt{s}),\rho_0',\texttt{k}_\texttt{s}\rangle,\overline{w} \diamond \tau') \to^!\textsf{err}
$$

Observe that we can apply the assumption (†) to each of these layouts. This shows that for every $\overline{w} \in E$ we have:

$$
\overline{w} \vdash_\sigma (\langle \texttt{syscall s}(F_1, \ldots, F_k); \mathtt{Q}, \rho, \mathtt{u} \rangle : F', \overline{w} \diamond \tau') \to^{!} \textsf{err}.
$$

From (B), we know that the probability measure associated to the set is bigger than δ_{μ} and from (H) we deduce that

$$
\overline{w} \vdash_{\sigma} (\langle \texttt{syscall s}(F_1, \ldots, F_k); \mathbf{Q}, \rho, u, : \rangle F', \overline{w} \diamond \tau') \rightarrow^{!n+1} \textsf{err}.
$$

holds; this shows the claim.

- CASE C. Let $w \in \text{Lay}$ be any layout. From Lemma [7,](#page-41-0) we deduce that

$$
\mathit{Eval}_{\sigma, w}((\langle \gamma(s), \rho_0', \mathbf{k_s}\rangle : \langle \mathbf{Q}, \rho, \mathbf{u}\rangle : \mathit{F}', w \diamond \tau')) = \Omega,
$$

which is absurd because we were assuming (H).

The main claim is a particular case of C' where F is $\langle P, \rho, u \rangle$, and τ' is τ .

Lemma 4. For every layout non-leaking system $\sigma = (\tau, \gamma, \xi)$, unprivileged program P, register map ρ, store τ ′ ∼FunId τ, and distribution µ such that

$$
\forall \texttt{id} \in \mathsf{Id}_{\mathtt{u}}.\forall w_1,w_2 \in \mathsf{supp}(\mu).w_1(\mathtt{id})=w_2(\mathtt{id}),
$$

one of the following statements holds:

(A) There are a value \overline{v} and a store $\overline{\tau} \sim_{\text{Funld}} \tau$ such that for every layout $w \in \text{Lay}$, we have:

$$
\exists \overline{\rho}. w \vdash_{\sigma} (\langle \gamma(s), \rho, \mathbf{k}_s \rangle, w \diamond \tau') \rightarrow^{!} (\langle \epsilon, \overline{\rho}[ret \leftarrow v], \mathbf{k}_s \rangle, w \diamond \tau''),
$$

- (B) $Pr_{w \leftarrow \mu} [w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau') \rightarrow' err] \geq \delta_{\mu}$
- (C) For every layout $w \in \textsf{Lay}$, we have that:

$$
Eval_{\sigma,w}((\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau')) = \Omega.
$$

Proof. We start by fixing all the universally quantified variable in the statement with the same metavariable we used there. We also fix some $\overline{w} \in \text{Lay}$, and we go by cases on

$$
Eval_{\sigma,\overline{w}}((\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau')).
$$

- CASE (v, τ'') . In this case, due to the *layout-non-interference* property, we conclude that (A) holds for $\overline{v} = v$ and $\overline{\tau} = \tau''$, and because Remark [4](#page-40-2) shows that $\tau'' \sim_{\text{Fund}} \tau' \sim_{\text{Fund}} \tau$.
- CASE unsafe. In this case, from the *layout-non-interference* property, we deduce that for every $w \in \text{Lay}$

$$
Eval_{\sigma,w}((\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau')) \in \{err, \text{unsafe}\}.
$$

This also means that for every $w \in \text{Lay}$, we have that

$$
\exists n_w.w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau') \rightarrow^{n_w} D \in \{\text{err}, \text{unsafe}\},\
$$

and since the set Lay is finite, there is a number \overline{n} such that

$$
\forall w \in \text{Lay}.w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau') \rightarrow^{!\overline{n}} D \in \{\text{err}, \text{unsafe}\}. \tag{\dagger}
$$

We can conclude that

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle \gamma(s), \rho, \mathbf{k}_s \rangle, w \diamond \tau') \rightarrow^{!\overline{n}} \textsf{err} \right] \geq \delta_{\mu}
$$

by fixing an enumeration id_0, \ldots, id_h of the identifiers in the capabilities of s and by observing that the probability we wrote above is given by the summation over $p_1, \ldots, p_h \in \mathsf{Addr}_k$ of

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau') \rightarrow^{! \overline{n}} \text{err} \middle| \forall 1 \leq i \leq h \ldots (id_i) = p_i \right] \tag{*}
$$

multiplied by

$$
\Pr_{w \leftarrow \mu}[w(\text{id}_1) = p_1, \dots, w(\text{id}_h) = p_h]
$$

From (†) and Lemma [5,](#page-37-0) we deduce that for every choice of $p_1, \ldots, p_h \in \mathsf{Addr}_k$, the probability (*) is bounded by δ_{μ} so that their convex combination is again bounded by this value. Then, we observe that

$$
w \vdash_\sigma (\langle \gamma(s), \rho, \mathbf{k}_\mathbf{s}\rangle, w \diamond \tau') \to^{!\overline{n}} \mathsf{err}
$$

implies

$$
w \vdash_\sigma (\langle \gamma(\mathtt{s}), \rho, \mathtt{k}_\mathtt{s} \rangle, w \diamond \tau') \rightarrow^! \mathtt{err}
$$

for the definition of $\rightarrow^{!m}$, and this means that

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau') \rightarrow^! \text{err} \right]
$$

is greater than

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau') \rightarrow^{! \overline{n}} \text{err} \right]
$$

and this shows the claim.

- CASE Ω. In this case, due to the *layout-non-interference* property, we conclude that (C) holds.

Lemma 5. For every layout non-leaking system $\sigma = (\tau, \gamma, \xi)$ every system call s, sequence of addresses p_1, \ldots, p_h where $h = \text{size}(\xi(s))$ unprivileged program P, register map ρ , and store $\tau' \sim_{\text{Fund}} \tau$, and distribution μ such that

$$
\forall \texttt{id} \in \mathsf{Id}_{\mathbf{u}}.\forall w_1, w_2 \in \mathsf{supp}(\mu).w_1(\texttt{id}) = w_2(\texttt{id}),
$$

said $\xi(s) = \{\text{id}_1, \ldots, \text{id}_h\}$, one of the following statements holds:

(A) There are a non-empty stack \overline{F} such that $\mathbf{k}_s(\overline{F})$, and $\mathsf{ids}(\overline{F}) \subseteq \xi(s)$, there is also a store $\overline{\tau} \sim_{\mathsf{Fund}} \tau'$ such that for every layout w, if for every $1 \leq i \leq h$, $w(\text{id}_i) = p_i$ then

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau') \rightarrow^{n} (F, w \diamond \overline{\tau}).
$$

(B) The value of

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau') \rightarrow^{!n} \text{err} \middle| \forall 1 \leq i \leq h \cdot w(\text{id}_i) = p_i \right]
$$

is greater than δ_{μ} .

(C) If $\xi(s) = {\text{id}_1, \dots, \text{id}_h}$, there are a register map $\overline{\rho}$ and a store $\overline{\tau} \sim_{\text{Funld}} \tau'$ such that for every layout w, if for every $1 \leq i \leq h$, $w(\text{id}_i) = p_i$ then

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho, \mathbf{k}_{s} \rangle, w \diamond \tau') \rightarrow^{!n} (\langle \epsilon, \overline{\rho}, \mathbf{k}_{s} \rangle, w \diamond \overline{\tau}).
$$

Proof. We go by induction on n.

- Case 0. In this case, we conclude that (A)or (C) hold trivially, depending on $\gamma \neq \epsilon$ or not.
- CASE $n + 1$. We start by applying the IH to the initial configuration. Three cases arise:
	- CASE A. In this case, we start by fixing the system σ , a system call s, an initial configuration $(\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau')$ together with the sequences of indexes and addresses, respectively id_1, \ldots, id_h and p_1, \ldots, p_h . The IH tells that there are a stack F such that $k_s(F)$ and a store $\tau'' \sim_f \tau$ such that for every layout that satisfies the premise $\forall 1 \leq i \leq h.w(\mathrm{id}_i) = p_i$, we have

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau') \rightarrow^{n} (F, w \diamond \tau'').
$$

Because of the non-emptiness of F, we assume that $F = \langle P, \rho', k_{s} \rangle : F'$. From the IH, we also know that $k_s(F)$ (H1) and that $\text{ids}(F) \subseteq \xi(s)$ (H2). We go by cases on P.

- CASE $x := \mathbf{E}$; Q. In this case, we start by observing that there is a value v such that for each of the layouts we are quantifying over, we have that $\llbracket \mathbb{E} \rrbracket_{\rho,w} = v$. More precisely, this comes from Remark [2](#page-40-0) because we assumed that for every id $\in \xi(s)$, and every w_1, w_2 such layouts, it holds that $w_1(\text{id}) = w_2(\text{id})$ and, in particular, this holds for those identifiers that appear in E and that belong to $\mathsf{Id}_{\mathbf{u}}$ by the definition of ξ . For all these layouts, we have:

$$
w \vdash_{\sigma} (\langle x := \mathbf{E}; \mathbf{Q}, \rho', \mathbf{k}_{s} \rangle : F', w \diamond \tau'') \to (\langle \mathbf{Q}, \rho'[x \leftarrow v], \mathbf{k} \rangle : F', w \diamond \tau'').
$$
 (*)

From (H1) we deduce that $k_s(\langle \mathbf{Q}, \rho' [x \leftarrow v], \mathbf{k} \rangle : F'$, and from (H2) we deduce that

$$
ids(\langle \mathbf{Q}, \rho' [x \leftarrow v], \mathbf{k} \rangle : F') \subseteq \xi(\mathbf{s})
$$

so we conclude that (A) holds if $\mathbb{Q} \neq \epsilon$ or F' is non-empty, otherwise (C) holds.

- CASE ϵ . Analogous to the case above.
- Case skip; Q. Analogous to the case of assignments.
- CASE if E then P_{\perp} else P_{\top} fi; Q. Analogous to the case of assignments.
- Case while E do P od; Q. Analogous to the case of assignments.

□

- CASE $*E := F$; Q. In this case, we start by observing that there is a value v_E such that for each layout w that satisfies the premise, we have that $\mathbb{E}\|_{\rho,w} = v_{\mathbb{E}}$. This comes from Remark [2,](#page-40-0) (H2) and the definition of ξ , which ensures that all the identifiers within these two expressions are in $\xi(\mathbf{s})$. From the same reason, there is a unique value v_F such that for each of these layouts, we have that $[\mathbb{E}]_{\rho',w} = v_{\mathbb{F}}$. This also means that there is a unique $p \in \mathsf{Addr}$ that is equal to v^{Addr} that this instruction attempts to write at. Finally, we observe that there is a unique set P such that for every of those lay that satisfy the assumption w, we have $P = w(\xi(s))$ all the addresses We go by cases (EM) on $p \in P$.
	- CASE $p \in P$. In this case, for each layout w that we are covering with our quantification, it happens that $\underline{w}(\text{id}_i) \ni p$. If id_i is a function identifier, we have

$$
w \vdash_{\sigma} (\langle \ast \mathbf{E} := \mathbf{F}; \mathbf{Q}, \rho', \mathbf{k}_{\mathrm{s}} \rangle : F', w \diamond \tau'') \to \text{err}.
$$

And this shows that (B) holds with probability 1. Otherwise, there is are an array a and a unique index j such that for each of thee layouts, we have $w(a)+j = p$ and a and j are unique — if this was not the case, then it would not be true that these layouts store id_1, \ldots, id_h respectively at p_i, \ldots, p_h . So with each of those layouts w that satisfy the premise the rule [[Store](#page-7-7)] can be applied and shows

$$
w \vdash_{\sigma} (\langle *E := F; \mathbf{Q}, \rho', k_{\mathrm{s}} \rangle : F', w \diamond \tau'') \to (\langle \mathbf{Q}, \rho', k_{\mathrm{s}} \rangle : F', w \diamond \tau''[p \leftarrow v_{\mathrm{F}}]).
$$

Then, we can apply Remark [3](#page-40-1) to show that

$$
w \vdash_\sigma (\langle \ast \mathbf{E}:=\mathbf{F};\mathbf{Q},\rho',\mathbf{k}_\mathrm{s}\rangle: F',w\diamond \tau'') \to (\langle \mathbf{Q},\rho',\mathbf{k}_\mathrm{s}\rangle: F',w\diamond \tau''[(\mathrm{a},j)\leftarrow v_\mathrm{F}]).
$$

By observing the uniqueness of the target configuration modulo w, that $k_s(\langle \mathbf{Q}, \rho', \mathbf{k}_s \rangle : F')$ hold and that $\textsf{ids}(\langle \mathbf{Q}, \rho', \mathbf{k}_s \rangle : F') \subseteq \xi(s)$ because of (H1) and (H2) respectively, we conclude that claim (A) holds if $\mathbb{Q} \neq \epsilon$ or F' is non-empty, otherwise (C) holds.

- CASE $p \notin P$. In this case, by introspection of the semantics, we observe that only rules [LOAD-ERROR] and [LOAD-UNSAFE]. In particular, the rule [LOAD-ERROR] can apply only to those layouts w such that $p \notin \underline{w}(\mathsf{Arrld}_k)$, and we observe that $p \notin \underline{w}(\mathsf{Id}_k) \Rightarrow p \notin \underline{w}(\mathsf{Arrld}_k)$. In particular, if $p \notin \text{Addr}_k$, then due to the restriction we (globally) impose on the set of layouts, it cannot be that $p \in w(\text{Arrld}_k)$, so the rule [LOAD-ERROR] applies independently of the layout and (B) holds with probability 1. For this reason, in the following, we can assume $p \in \text{Addr}_k$, in this case, we can also observe that:

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle \texttt{*E} := \texttt{F}; \texttt{Q}, \rho', \texttt{k}_s \rangle : F', w \diamond \tau'') \rightarrow \texttt{err} \middle| \forall 1 \leq i \leq h.w(\texttt{id}_i) = p_i \right]
$$

is greater than

$$
\Pr_{w \leftarrow \mu} \left[p \notin \underline{w}(\mathsf{Arrld_k}) \mid \forall 1 \leq i \leq h.w(\mathtt{id}_i) = p_i \right]
$$

which, in turn, is greater than

$$
\Pr_{w \leftarrow \mu} \left[p \notin \underline{w}(\mathsf{Id}_{\mathsf{k}}) \mid \forall 1 \leq i \leq h.w(\mathtt{id}_i) = p_i \right]
$$

which is greater than δ_{μ} by definition. This shows that (B) holds.

- CASE $x := *E; Q$. Analogous to the case of memory store operations.
- CASE call $E(F_1, \ldots, F_k)$; Q. We start observing that there is a unique address p such that for every w that satisfies the precondition, we have that $[\mathbb{E}]_{\rho,w}^{\mathsf{Addr}} = p$. Similarly, we introduce the values v_1, \ldots, v_k that respectively correspond to the semantics of F_1, \ldots, F_k evaluated under ρ and every the layout that satisfies the precondition. Then we observe that there is a set P such that for each of the layouts we are taking in account, it holds that $\underline{w}(\xi(s)) = P$. The proof continues by applying the EM principle on $p \in P$.
- CASE $p \in P$. In this case, there is a unique id_i such that for every layout w that satisfies the precondition, we have $\underline{w}(\text{id}_i) \ni p$. We apply the EM principle on $id_i = f$
	- CASE i $d_j = f$. In this case, from the definition of \diamond , we deduce that for each of these layouts $w \circ \tau'(p) = \tau''(f) = \tau(f)$, (the last step comes from the assumption $\tau'' \sim_{\text{Fund}} \tau$). Since $p \in P$, we deduce that independently of the specific layout, if we have the preconditions, it holds that

$$
w \vdash_{\sigma} (\langle \text{call } E(F_1, \ldots, F_k); \mathbf{Q}, \rho, k_{s} \rangle : F', w \diamond \tau'') \rightarrow (\langle \tau(f), \rho'_0, k_{s} \rangle : \langle \mathbf{Q}, \rho, k_{s} \rangle : F', w \diamond \tau''),
$$

where $\rho'_0 = \rho_0[x_1, \ldots, x_k \leftarrow v_1, \ldots, v_k]$. Finally, we observe that

$$
\mathbf{k}_\mathrm{s}\big(\langle\tau(f),\rho_0',\mathbf{k}_\mathrm{s}\rangle:\langle\mathbf{Q},\rho,\mathbf{k}_\mathrm{s}\rangle:F'\big)
$$

holds. In particular $\tau(f)$ does contain syscall $\cdot(\cdot)$ for the definition of system, and for the same definition, ξ contains all the identifiers within F_1, \ldots, F_k , so it must be that $\mathsf{ids}(\tau(f)) \in \mathsf{ids}(\langle \tau(f), \rho_0', \mathbf{k}_s \rangle : \langle \mathbf{Q}, \rho, \mathbf{k}_s \rangle : F')$. This shows that (A) holds.

- CASE id_j = a. In this case, since the set of array identifiers and that of functions are disjoint, we conclude that for every layout w that satisfies the preconditions, we have that $p \notin \underline{w}$ (FunId_k). This means that for each of these layouts, we can show:

$$
w \vdash_{\sigma} (\langle \text{call } E(\mathbf{F}_1, \ldots, \mathbf{F}_k); \mathbf{Q}, \rho, \mathbf{k}_{\mathrm{s}} \rangle : F', w \diamond \tau'') \rightarrow \text{err},
$$

and this means that (B) holds with probability 1.

- CASE $p \notin P$. Analogous to the corresponding case for memory store operations.
- CASE syscall $E(F_1, \ldots, F_k); Q$. This is absurd because system calls cannot call, and this is a consequence of the IH, more precisely of (H1).

- CASE B. From the definition of $\rightarrow^{!n}$, we observe that if

$$
w \vdash_\sigma (\langle \gamma(s), \rho, \mathbf{k}_\mathbf{s}\rangle, w \diamond \tau') \to^{!n} \mathsf{err}
$$

then

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho, \mathbf{k}_{s} \rangle, w \diamond \tau') \rightarrow^{!n+1} \text{err}.
$$

This shows that

$$
\Pr_{i \leftarrow \mu} \left[w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau') \rightarrow^{!n+1} \text{err} \middle| \forall 1 \leq i \leq h.w(\text{id}_i) = p_i \right]
$$

is greater than the probability

 \boldsymbol{u}

$$
\Pr_{w \leftarrow \mu} \left[w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, w \diamond \tau') \rightarrow^{!n} \text{err} \middle| \forall 1 \leq i \leq h \cdot w(\text{id}_i) = p_i \right],
$$

and this shows the claim.

- Case C. Similar to the case above.

口

Remark 1.

$$
\delta_{\nu} \geq \min_{s \in \mathsf{Sys}} \frac{\kappa_{\mathbf{k}}/\theta - \mathsf{size}(\mathsf{Id}_{\mathbf{k}})}{\kappa_{\mathbf{k}}/\theta - \mathsf{size}(\xi(s))}
$$

Proof. We want to show that every q that belongs to

$$
\{ \Pr_{w \leftarrow \nu} [p \notin \underline{w}(\mathsf{Id}) \mid w(\mathtt{id}_i^{\mathtt{s}}) = p_i, \text{ for } 1 \leq i \leq h] \mid \mathtt{s} \in \mathsf{Sys}, p, p_1, \dots, p_h \in \mathsf{Addr}_{\mathtt{k}} \land
$$
\n
$$
p \notin \{p_i, \dots, p_i + \mathsf{size}(\mathtt{id}_i^{\mathtt{s}}) - 1\}, \text{ for } 1 \leq i \leq h \}.
$$

is greater than δ_{ν} . To do that, we fix a system call $s \in \mathsf{Sys}$ and $p, p_1, \ldots, p_h \in \mathsf{Addr}_k$, such that

$$
q = \Pr_{w \leftarrow \nu} [p \notin \underline{w}(\mathsf{Id}) \mid w(\mathtt{id}_i^{\mathtt{s}}) = p_i, \text{ for } 1 \leq i \leq h]
$$

and that

$$
p \notin \{p_i, \dots, p_i + \text{size}(\text{id}_i^s) - 1\}, \text{ for } 1 \le i \le h
$$
 (†)

 \Box

Since the probability is defined, p_1, \ldots, p_h are the starting addresses of the slots $s_1, \ldots s_h$ in which the capabilities $\xi(s)$ of s are allocated. Now assume that p belongs to one of those slots. From (†) we deduce that p must not be allocated, so the bound holds trivially because $q = 1$. Otherwise, p belongs to another slot s, observe that (5) above corresponds to the probability that the smallest address of s is unoccupied. This value, in turn, is smaller than the probability that p itself is not occupied, which is q. 口

Technical observations

Remark 2. For every set of identifiers $\{id_1, \ldots, id_h\} \subseteq \mathsf{Id}$, set of addresses $\{p_i, \ldots, p_h\}$, set of layouts

$$
W \subseteq \{w \in \text{Lay} \mid \forall 1 \leq i \leq h.w(\text{id}_i) = p_i\}
$$

and expression E, and register map ρ there is a value $v \in$ Val such that

$$
\forall w \in W[\![\mathtt{E}]\!]_{\rho,w} = v
$$

Proof. By cases on the size of W: if it is 0 or 1, the claim is trivial, otherwise, we pick $w_1, w_2 \in W$, and we show by induction on the syntax of the expression that they evaluate the same. So, we define v as $[\mathbb{E}]_{\rho,w_1}$, and we assume that there is a layout \overline{w} where E evaluates differently. This contradicts the claim we just showed. □

Remark 3. For every address $p \in$ Addr, array $a \in$ Arr, store τ and $0 \leq i <$ size(a), if $p = w(a) + i$, then

$$
(w \diamond \tau)[p \leftarrow v] = w \diamond (\tau[(p, i) \leftarrow v]).
$$

Proof. By definition.

Remark 4. For every layout $w \in \text{Lay}$, pair of configurations $(F, w \diamond \tau)$ and (F', m) such that $w \vdash_{\sigma}$ $(F, w \diamond \tau) \rightarrow^* (F', m)$, we have that $m = w \diamond \tau'$ for some $\tau' \sim_{\text{Fund}} \tau$.

Proof. The proof goes by induction on the length of the reduction. The base case follows from reflexivity of \sim _{FunId}, the inductive case follows from introspection of the semantics; the only nontrivial case is that of the [STORE] rule: in that case the premise $p \in \underline{w}(\text{Arrld}_b)$ ensures the existence of a pair (a, i) such that $0 \leq i <$ size(a) and the observation is a consequence of Remark [3.](#page-40-1) □

Lemma 6. For every layout $w \in \text{Lay}$, configuration $(\langle P, \rho, b \rangle, m)$ and non-empty stack $f : F, n \in \mathbb{N}$, and configuration C:

 $- if w \vdash_{\sigma} (\langle P, \rho, b \rangle, w \diamond \tau) \rightarrow^{n} (F', m'), then:$

$$
w \vdash_{\sigma} (\langle P, \rho, b \rangle : f : F, m) \rightarrow^{n} (F' : f : F, m')
$$

– if $w \vdash_{\sigma} (\langle P, \rho, b \rangle, w \diamond \tau) \rightarrow^n$ err, then:

$$
w \vdash_{\sigma} (\langle P, \rho, b \rangle : f : F, m) \rightarrow^{n} \text{err}
$$

 $-$ if $w \vdash_{\sigma} (\langle P, \rho, b \rangle, w \diamond \tau) \rightarrow^n$ unsafe, then:

$$
w \vdash_\sigma (\langle \mathtt{P}, \rho, b \rangle : f : F, m) \rightarrow^n \mathtt{unsafe}
$$

Proof. By induction on n . The base case is trivial, the inductive case follows by applying the IH and then by going by cases on the IH. □

Lemma 7. For every layout $w \in \text{Lay}$, configuration $(\langle P, \rho, b \rangle, w \diamond \tau)$ and non-empty stack $\langle \mathbf{Q}, \rho', b \rangle : F$, $n \in \mathbb{N}$, and configuration C:

 $-$ if $Eval_{\sigma,w}((\langle P,\rho,b\rangle, w \diamond \tau)) = v, \tau'$, then:

$$
w \vdash_{\sigma} (\langle P, \rho, b \rangle : \langle Q, \rho', b \rangle : F, w \diamond \tau) \rightarrow^* (\langle Q, \rho'[ret \leftarrow v], b \rangle : F, w \diamond \tau')
$$

 $-$ if $Eval_{\sigma,w}((\langle P, \rho, b \rangle, w \diamond \tau)) =$ err, then:

$$
w \vdash_\sigma (\langle \mathbf{P}, \rho, b \rangle : \langle \mathbf{Q}, \rho', b \rangle : F, w \diamond \tau) \rightarrow^* \mathsf{err}
$$

 $-$ if $Eval_{\sigma,w}((\langle P, \rho, b \rangle, w \diamond \tau)) = \text{unsafe}, then:$

$$
w \vdash_\sigma (\langle \mathbf{P}, \rho, b \rangle : \langle \mathbf{Q}, \rho', b \rangle : F, w \diamond \tau) \rightarrow^* \mathsf{unsafe}
$$

 $-$ if $Eval_{\sigma,w}((\langle P,\rho,b\rangle, w \diamond \tau)) = \Omega$, then:

$$
Eval_{\sigma,w}((\langle P, \rho, b \rangle : \langle Q, \rho', b \rangle : F, w \diamond \tau)) = \Omega
$$

Proof. The first three cases are trivial rewriting of the definitions, the most interesting is the last one. By expanding the definition of $Eval_{\sigma,w}(\cdot)$, we obtain that $Eval_{\sigma,w}((\langle P, \rho, b \rangle, w \diamond \tau)) = \Omega$ is equivalent to stating for every n ,

$$
w \vdash_{\sigma} (\langle P, \rho, b \rangle, w \diamond \tau) \rightarrow^{n} D
$$

has as consequence that there is D' such that $w \vdash_{\sigma} D \to D'$. We go by cases on D, and we exclude unsafe and err. So it must be the case where $D = (\langle P', \rho'', b' \rangle : F', w \diamond \tau'')$ and $P' \neq \epsilon$, then we apply Lemma [6](#page-40-3) to show that

$$
w \vdash_{\sigma} (\langle P, \rho, b \rangle : \langle Q, \rho', b \rangle : F, w \diamond \tau) \rightarrow^n (\langle P', \rho'', b' \rangle : F' : \langle Q, \rho', b \rangle : F, w \diamond \tau'').
$$

Finally we go by cases on the rules for proving the transition $w \vdash_{\sigma} D \to D'$ in order to verify that all of these rules apply to both the target configurations. This shows that for all n , if

$$
(\langle P, \rho, b \rangle : \langle Q, \rho', b \rangle : F, w \diamond \tau)
$$

reduces *n* steps, then it also reduces $n + 1$ steps.

A.2 Appendix for Section [6](#page-11-0)

A.2.1 Speculative Semantics of Cmd

The speculative semantics of Cmd is in Figures [6](#page-42-0) and [7.](#page-43-0)

A.2.2 Semantics of SpAdv

The semantics of SpAdv is in Figures [8](#page-44-0) to [10.](#page-46-1)

A.2.3 Buffered Memories

Buffered memories have already been defined in Section [6.](#page-11-0) In this section we just give the formal definitions of their lookup and flushing operations following [\[10\]](#page-22-7). The operation of lookup a value from a buffered memory is defined as follows:

$$
(m)^{k}(p) \triangleq m(a), \perp
$$

\n
$$
([p \mapsto n] : \mu m)^{0}(p) \triangleq n, \perp
$$

\n
$$
([p \mapsto n] : \mu m)^{i+1}(p) \triangleq n', \perp
$$

\n
$$
([p' \mapsto n] : \mu m)^{i}(p) \triangleq (\mu m)^{i}(p)
$$

\nif $p \neq p'$

$$
\frac{\left[\mathbb{E}\right]_{\rho,w}^{\text{Adof}}=p\quad (\mu m)^{0}(p)=v,\perp\quad p\in \underline{w}(\text{Artd}_{b})\quad \boxed{b=\mathbb{R}_{a}\Rightarrow p\in \underline{w}(\xi(\mathbb{s}))}\right]}{w+_{\sigma}(\langle x:=_{\ell}*E;P,\rho,b):F,\mu m,b_{\text{max}}):S\stackrel{\text{memp}}{=}p\cdot((P,\rho|x\leftarrow v),b):F,\mu m,b_{\text{max}}):S\stackrel{\text{memp}}{=}S\cdot(\mathbb{R}_{a}\land\mathbb{R}_{a}\land\mathbb{R}_{a})\cdot S\cdot(\mathbb{R}_{a}\land\mathbb{R}_{a}\land\mathbb{R}_{a})\cdot S\cdot(\mathbb{R}_{a}\land\mathbb{R}_{a}\land\mathbb{R}_{a})\cdot S\cdot(\mathbb{R}_{a}\land\mathbb{R}_{a}\land\mathbb{R}_{a})\cdot S\cdot(\mathbb{R}_{a}\land\mathbb{R}_{a}\land\mathbb{R}_{a})\cdot S\cdot(\mathbb{R}_{a}\land\mathbb{R}_{a}\land\mathbb{R}_{a}\land\mathbb{R}_{a})\cdot S\cdot(\mathbb{R}_{a}\land\mathbb{R}_{a}\land\mathbb{R}_{a})\cdot S\cdot(\mathbb{R}_{a}\land\mathbb{
$$

$$
\frac{1}{w \vdash_{\sigma} (\langle x := E; P, \rho, b \rangle : F, \mu m, b_{ms}) : S \xrightarrow{\sigma} (\langle P, \rho[x \leftarrow [E]]_{\rho, w}], b \rangle : F, \mu m, b_{ms}) : S} [\text{SSKIP}]
$$
\n
$$
\frac{1}{w \vdash_{\sigma} (\langle \text{skip}; P, \rho, b \rangle : F, \mu m, b_{ms}) : S \xrightarrow{\sigma} (\langle P, \rho, b \rangle : F, \mu m, b_{ms}) : S} [\text{SSKIP}]
$$
\n
$$
\frac{1}{w \vdash_{\sigma} (\langle \text{skip}; \text{while} \rho E \text{ do } Q \text{ od}; P, \rho, b) : F, \mu m, b_{ms}) \cdot C_{\text{false}} = (\langle P, \rho, b \rangle : F, \mu m, b_{ms})}{w \vdash_{\sigma} (\langle \text{while} \rho E \text{ do } Q \text{ od}; P, \rho, b) : F, \mu m, b_{ms}) \cdot S \xrightarrow{\text{tr}} \sigma} C_{d} : S
$$
\n
$$
\frac{C_{\text{true}} = (\langle Q; \text{while} \rho E \text{ do } Q \text{ od}; P, \rho, b) : F, \mu m, b_{ms} \rangle : S \xrightarrow{\text{tr}} \sigma \cdot C_{d} : S}
$$
\n
$$
\frac{C_{\text{true}} = (\langle Q; \text{while} \rho E \text{ do } Q \text{ od}; P, \rho, b) : F, \mu m, b_{ms} \rangle \cdot (d \neq [E]]_{\rho, w}^{\text{Bool}}) \cdot C_{\text{false}} = (\langle P, \rho, b \rangle : F, \mu m, b_{ms} \rangle \cdot (d \neq [E]]_{\rho, w}^{\text{Bool}}) [\text{SLOOP-BRANCII}]
$$
\n
$$
\frac{1}{w \vdash_{\sigma} (\langle \text{tri}_{\theta} E \text{ do } Q \text{ od}; P, \rho, b) : F, \mu m, b_{ms}) : S \xrightarrow{\text{trd}} \sigma \cdot (\langle \text{while} \rho E \text{ do } Q \text{ od}; P, \rho, b) : F, \mu m, b_{ms}) : S} [\text{SIP-BRANCII}]
$$
\n
$$
\frac{C = (\langle \text{tr} \rho E \text{ then } P_{\text{true}} \text{ else } P_{\text{false}} \text{
$$

Figure 7: Speculative rules for \mathtt{Cmd} and a system $\sigma=(\tau,\gamma,\xi),$ Part II.

and a function for flushing buffers:

$$
\frac{\overline{m} \triangleq m}{[p \mapsto n] : \mu m \triangleq \overline{\mu m} [p \leftarrow n].}
$$

This function commits all the pending stores to the main memory. The domain of a buffered memory is defined as follows: $\text{dom}(\epsilon) = \emptyset$, $\text{dom}([p \mapsto v]\mu) = \{p\} \cup \text{dom}(\mu)$.

Remark 5. if $(\mu m)^i(p) = v, \perp$, then $(\mu m)^0(p) = v, \perp$.

Proof. the claim is:

$$
\forall \mu m. \forall i. \forall v. (\mu m)^{i}(p) = v, \bot \rightarrow (\mu m)^{0}(p) = v, \bot
$$

0

By induction on the length of the buffer.

- CASE $\epsilon.$ The claim comes from the definition of lookup.

- CASE $[p' \mapsto \overline{v}] : \mu$. The IH says:

$$
\forall i, v. (\mu m)^{i}(p) = v, \perp \rightarrow (\mu m)^{i}(p) = (\mu m)^{0}(p)
$$

and the claim is:

$$
\forall i, v. (((p' \mapsto \overline{v}]: \mu, m))^i(p) = v, \bot \Rightarrow (([p' \mapsto \overline{v}]: \mu, m))^i(p) = (([p' \mapsto \overline{v}]: \mu, m))^0(p)
$$

By cases on i .

$$
\overline{w \vdash_{\sigma} (\langle \text{poisson}(d); \mathbf{A}, \rho, b \rangle : F, m, D, O) \rightarrow (\langle \mathbf{A}, \rho, b \rangle : F, m, d : D, O)}^{\text{[POSON]}}
$$
\n
$$
\overline{w \vdash_{\sigma} (\langle x := \text{observe}(); \mathbf{A}, \rho, b \rangle : F, m, D, o : O)} \rightarrow (\langle \mathbf{A}, \rho[x \leftarrow o], b) : F, m, D, O)^{\text{[OBSERVE]}}
$$
\n
$$
\overline{w \vdash_{\sigma} (\langle x := \text{observe}(); \mathbf{A}, \rho, b \rangle : F, m, D, e)} \rightarrow (\langle \mathbf{A}, \rho[x \leftarrow \text{null}], b \rangle : F, m, D, e)^{\text{[OBSERVE-END]}}
$$
\n
$$
\overline{w \vdash_{\sigma} (\langle \text{spec on P}; \mathbf{A}, \rho, b \rangle : F, m, D, O)} \rightarrow (\langle \mathbf{P}, \rho, b \rangle, m, \bot) | (\langle \mathbf{A}, \rho, b \rangle : F, D, O)^{\text{[SPEC-INT]}}
$$
\n
$$
w \vdash_{\sigma} S \xrightarrow{a} S'
$$
\n
$$
w \vdash_{\sigma} S \xrightarrow{b} w \vdash_{\sigma} S \xrightarrow{b} s'
$$
\n
$$
w \vdash_{\sigma} S \xrightarrow{b} w \vdash_{\sigma} S \xrightarrow{b} S'
$$
\n
$$
\overline{w \vdash_{\sigma} S} \xrightarrow{w \vdash_{\sigma} S \xrightarrow{b} S'}
$$
\n
$$
\overline{w \vdash_{\sigma} S} \xrightarrow{w \vdash_{\sigma} S \xrightarrow{b} S'}
$$
\n
$$
\overline{w \vdash_{\sigma} (\langle \epsilon, \rho, b \rangle, \mu m, \bot) | (\langle \mathbf{A}, \rho', b' \rangle : F, D, O
$$

Figure 8: Semantics of the non-standard constructs of \texttt{SpAdv} for the system $\sigma = (\tau, \gamma, \xi)$.

- Case 0. The claim is:

$$
\forall v. ([p' \mapsto \overline{v}]: \mu m)^0(p) = v, \bot \Rightarrow ([p' \mapsto \overline{v}]: \mu m)^0(p) = ([p' \mapsto \overline{v}]: \mu m)^0(p)
$$

Observe that the conclusion is trivial.

- CASE $i + 1$. The claim is:

$$
\forall i. \forall v. ([p' \mapsto \overline{v}]: \mu m)^{i+1}(p) = v, \bot \Rightarrow ([p' \mapsto \overline{v}]: \mu m)^{i+1}(p) = ([p' \mapsto \overline{v}]: \mu m)^0(p)
$$

Fix *i*, *v*, assume $([p' \mapsto \overline{v}]: \mu m)^{i+1}(p) = v, \perp$, call this assumption (H). The claim becomes:

$$
([p' \mapsto \overline{v}]: \mu m)^0(p) = ([p' \mapsto \overline{v}]: \mu m)^0(p)
$$

Observe that it must be the case where $p' \neq p$, otherwise from (H) and the definition of lookup, we obtain $\bot = \top$. With this assumption, from (H) we deduce $(\mu m)^{i+1}(p) = v, \bot$, and we can rewrite the claim as follows:

$$
(\mu m)^{i+1}(p) = (\mu m)^0(p)
$$

The claim is a consequence of the IH.

Remark 6. For every buffered memory μ m, and every address p we have that $(\mu m)^0(p) = \overline{\mu m}(p)$.

JEK Addr ρ,w = p p ∈ w(ArrIdb) b = k^s ⇒ p ∈ w(ξ(s)) w ⊢^σ (hx := *E; P, ρ, bi : F, m, D, O) (hP, ρ[x ← m(p)], bi : F, m, D, O) -ALoad JEK Addr ρ,w = p p ∈ w(ArrIdb) b = k^s ⇒ p ∈ w(ξ(s)) w ⊢^σ (h*E := F; P, ρ, bi : F, m, D, O) (hP, ρ, bi : F, m[p ← JFKρ,w], D, O) -AStore JEK Addr ρ,w = p p ∈ w(ArrId^k) p 6∈ w(ξ(s)) w ⊢^σ (hx := *E; P, ρ, ksi : F, m, D, O) unsafe -ALoad-Unsafe JEK Addr ρ,w = p p ∈ w(ArrId^k) p 6∈ w(ξ(s)) w ⊢^σ (h*E := F; P, ρ, ksi : F, m, D, O) unsafe -AStore-Unsafe JEK Addr ρ,w = p p /∈ w(ArrIdb) w ⊢^σ (hx := *E; P, ρ, bi : F, m, D, O) err -ALoad-Error JEK Addr ρ,w = p p /∈ w(ArrIdb) w ⊢^σ (h*E := F; P, ρ, bi : F, m, D, O) err -AStore-Error w ⊢^σ (hskip; P, ρ, bi : F, m, D, O) (hP, ρ, bi : F, m, D, O) -ASkip w ⊢^σ (hfence; P, ρ, bi : F, m, D, O) (hP, ρ, bi : F, m, D, O) -AFence w ⊢^σ (hx := E; P, ρ, bi : F, m, D, O) (hP, ρ[x ← JEKρ,w], bi : F, m, D, O) -AOp w ⊢^σ (hif E then Ptrue else Pfalse fi; Q, ρ, bi : F, m, D, O) (hPJE^K Bool ρ,w ; Q, ρ, bi : F, m, D, O) -AIf Ctrue = (hP; while E do P od; Q, ρ, bi : F, m, D, O) Cfalse = (hQ, ρ, bi : F, m, D, O) w ⊢^σ (hwhile E do P od; Q, ρ, bi : F, m, D, O) CJE^K Bool ρ,w -AWhile

Figure 9: Semantics of standard construct of SpAdv for the system $\sigma=(\tau,\gamma,\xi),$ part I.

$$
\boxed{\mathbb{E}^{\text{Add}r}_{\rho,w} = p \quad p \in \underline{w}(\text{Fund}_b) \quad b = \mathbf{k}_s \Rightarrow p \in \underline{w}(\xi(s))\n\boxed{b = \mathbf{k}_s \Rightarrow p \in \underline{w}(\xi(s))}\n\boxed{w \vdash_{\sigma} (\langle \text{call } E(\mathbf{F}_1, \ldots, \mathbf{F}_n); \mathbf{P}, \rho, b) : F, m, D, O) \rightarrow (\langle m(p), \rho_0[x_1 \leftarrow [\mathbf{F}_1]_{\rho,w}, \ldots, x_n \leftarrow [\mathbf{F}_n]_{\rho,w}], b) : \langle \mathbf{P}, \rho, b \rangle : F, m)}\n\boxed{\mathbb{E}^{\text{Add}r}_{\rho,w} = p \quad p \in \underline{w}(\text{Fund}_\mathbf{k}) \quad p \notin \underline{w}(\xi(s))\n\boxed{p \in \underline{w}(\xi(s))}\n\boxed{w \vdash_{\sigma} (\langle \text{call } E(\mathbf{F}_1, \ldots, \mathbf{F}_n); \mathbf{P}, \rho, \mathbf{k}_s) : F, m, D, O) \rightarrow \text{unsafe}}\n\boxed{\text{ACALL-UNSAFE}}
$$
\n
$$
\boxed{\mathbb{E}^{\text{Add}r}_{\rho,w} = p \quad p \notin \underline{w}(\text{Fund}_b)\n\boxed{p \in \underline{w}(\text{Fund}_b)\n\boxed{p \in \underline{w}(\text{Fund}_b)\n\boxed{p \in \underline{w}(\text{Small } S(\mathbf{F}_1, \ldots, \mathbf{F}_n); \mathbf{P}, \rho, b) : F, m, D, O) \rightarrow \text{err}}\n\boxed{\text{ACALL-ERron}}
$$
\n
$$
\boxed{w \vdash_{\sigma} (\langle \text{syscall } S(\mathbf{F}_1, \ldots, \mathbf{F}_n); \mathbf{P}, \rho, b) : F, m, D, O) \rightarrow (\langle \gamma(s), \rho_0[x_1 \leftarrow [\mathbf{F}_1]_{\rho,w}, \ldots, x_n \leftarrow [\mathbf{F}_n]_{\rho,w}], \mathbf{k}_s) : \langle \mathbf{P}, \rho, b \rangle : F, m, D, O)}\n\boxed{\text{APOP}}
$$

Figure 10: Semantics of standard construct of SpAdv for the system $\sigma = (\tau, \gamma, \xi)$, part II.

Proof. The proof goes by induction on μ . If it is empty, then the claim is a trivial consequence of the definition of lookup. Otherwise, the claim is:

$$
([p' \mapsto v] : \mu m)^0(p) = \overline{[p' \mapsto v] : \mu m}(p),
$$

that rewrites as follows:

$$
([p' \mapsto v] : \mu m)^0(p) = \overline{\mu m}[p' \leftarrow v](p).
$$

If $p = p'$, the claim is a consequence of the definition of lookup and memory update. Otherwise, it is a consequence of the IH. \Box

Remark 7. For every buffered memory $\mu(w \diamond \tau)$ if $\text{dom}(\mu) \subseteq w(\text{Arrld})$, then we have that: $\overline{\mu(w \diamond \tau)} =$ $w \diamond \tau'$ for some $\tau' \sim_{\mathsf{Fund}} \tau$.

Proof. The proof is by induction on the length of the buffer. If it is 0, then the claim is trivial. Otherwise, it is a consequence of Remark [3.](#page-40-1) 口

A.2.4 Omitted Proofs and Results

In the following we will assume, without lack of generality that all the memories m within a configuration that is reached during the evaluation of a configuration whose memory is $w \circ \tau$ is such that $m = w \diamond \tau'$ for some $\tau' \sim_{\text{Fund}} \tau$. This is justified by Remarks [8](#page-56-0) and [9.](#page-56-1)

Proof of Lemma [1.](#page-16-0) Assume that a system call s of a system $\sigma = (\gamma, \tau, \xi)$ is not speculative kernel safe; this means that for some *n* layout w, register map ρ , buffered memory $(\mu, w \circ \tau')$ with $\tau' \sim_{\text{Fund}} \tau$, sequence of directives D, sequence of observations O , and mis-speculation flag b_{ms} we have that:

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho, \mathbf{k}_s \rangle, w \diamond \tau', b_{ms}) \xrightarrow{O}^n \mathbf{unsafe}.
$$

By introspection on the rules, we deduce that the rule applied must be one among [[SLoad-Unsafe](#page-42-1)], [[SStore-Unsafe](#page-42-2)], [[SCall-Unsafe](#page-42-3)]. In all these cases, the rightmost observation within O must be memp for some address $p \in w(\mathsf{Id}_k)$. More precisely, p belongs to $w(\mathsf{Fund}_k)$ if the rule was $[\text{SCALL-UNSAFE}]$ and to $\underline{w}(\text{Arrld}_k)$ otherwise. In the following we just show this last case. From the definition of $\underline{w}(\text{ArrId}_k)$, we deduce that there are $a \in \text{ArrId}_k$ and $0 \leq i <$ size(a) such that $w(a) + i = p$. Our goal now, is to show that there is a layout w' such that $p \notin \underline{w}'(|d_k)$, which means that p is not allocated in w'. To build w', we go by cases on $p' = w(a)$.

- CASE κ_u . In this case, the array is stored at the beginning of the kernel-space address space. From the assumption on the size of this address space, there are at least $2 \cdot \max_{i \in [d_k]} \text{size}(id) > \text{size}(a)$ free addresses in the set $\{\kappa_u + \text{size}(a), \ldots, \kappa_u + \kappa_k - 1\}$, so the array can be moved in this space, leaving the address p not allocated. We call w' one such layout.
- CASE $\kappa_{\mathbf{k}}$ 1 size(a). Analogous to the case above.
- CASE $\kappa_u < p' < \kappa_k 1$ size(a). Due to the pigeonhole principle, in at least one of the address spaces $\{\kappa_{\mathbf{u}}, \ldots, p'-1\}$ and $\{p'+\textsf{size}(\mathbf{a}), \ldots, \kappa_{\mathbf{k}}-1 \textsf{size}(\mathbf{a})\}$ there are at least $\max_{\mathbf{i} \in \mathsf{Id}_{\mathbf{k}}} \textsf{size}(\mathbf{i} \in \mathsf{Id}) > \textsf{size}(\mathbf{a})$ not allocated address, this means that a can be moved to one of these sub-spaces, leaving free the gap $w(a), \ldots, w(a) + i$ and in particular p. We call w' one such layout.

From the speculative side-channel layout-non-interference assumption, we deduce that there is S' such that

$$
w' \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, \mu w' \diamond \tau', b_{ms}) \xrightarrow{O} {n \atop D} S',
$$

Observe that, in particular, this transition produces the sequence of observations O. By applying Remark [10,](#page-56-2) we deduce that mem p does not appear in O , but this is absurd, because we showed that the rightmost observation of O was exactly mem p . □

Proof of Theorem [2.](#page-17-1) We fix a system $\sigma = (\tau, \gamma, \xi)$ and go by contraposition. We assume that there are an unprivileged command $A \in \text{SpAdv}$, an initial register map ρ , a number of steps n and a layout such that:

$$
w \vdash_{\sigma} (\langle \mathtt{A}, \rho, \mathtt{u} \rangle, w \diamond \tau, \epsilon, \epsilon) \mathbin{{\to}^{n}} \mathtt{unsafe}.
$$

We first observe that $n \neq 0$, and by introspection of the rules of the semantics, we observe that the last rule must be one among [ALOAD-UNSAFE], [ASTORE-UNSAFE], [ACALL-UNSAFE] and

[[Spec-Unsafe](#page-44-1)]. We go by cases on these rules; in particular, the proof in the case of the first three rules is analogous, so we take the case of the rule $|ALOAD-UNSAFE|$ as an example.

- CASE [ALOAD-UNSAFE]. By introspection of the rule, we deduce that there is a configuration

$$
(\langle x \; := \; *E, \rho', k_s \rangle : F, m, D, O)
$$

such that

$$
w \vdash_{\sigma} (\langle \mathtt{A}, \rho, \mathtt{u} \rangle, w \diamond \tau, \epsilon, \epsilon) \rightarrow^n (\langle x \ := \ast \mathtt{E}, \rho', \mathtt{k}_\mathtt{s} \rangle : F, m, D, O) \rightarrow \mathtt{unsafe}.
$$

With an application of Lemma [8,](#page-48-0) we deduce that there is a configuration

$$
(\langle \gamma(s), \rho_0[x_1,\ldots,x_k \leftarrow v_1,\ldots,v_k], k_s \rangle, m', D', O'),
$$

a prefix F' of F and $n' \in \mathbb{N}$ such that:

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho_0[x_1, \ldots, x_k \leftarrow v_1, \ldots, v_k], \mathbf{k}_s \rangle, m', D', O') \rightarrow^{n'} (\langle x \rangle := * \mathbf{E}, \rho', \mathbf{k}_s \rangle : F', m, D, O)
$$

In the following, we write $\tau' \sim_{\text{Fund}} \tau$, instead of m' as a consequence of Remark [9.](#page-56-1) By introspection of the rule [ALOAD-UNSAFE] we deduce that:

$$
- \quad \ \ \mathbb{E} \, \mathbb{E}_{\rho',w} \in \underline{w}(\mathsf{Arrld}_{\mathtt{k}}).
$$

$$
-\;[\![\mathtt{E}]\!]_{\rho',w}\notin \underline{w}(\xi(\mathtt{s})).
$$

and this allows us to conclude that the same rule applies to

$$
(\langle x := *E, \rho', k_{s} \rangle : F', m, D, O),
$$

thus showing that

$$
(\langle \gamma(s), \rho_0[x_1, \ldots, x_k \leftarrow v_1, \ldots, v_k], k_s \rangle, w \diamond \tau', D', O')
$$

Reduces in n steps to unsafe. With an application of Lemma [9,](#page-49-0) we deduce that also the speculative configuration

 $(\langle \gamma(s), \rho_0[x_1, \ldots, x_k \leftarrow v_1, \ldots, v_k], k_s \rangle, w \diamond \tau', \perp)$

reduces in $n' + 1$ $n' + 1$ steps to unsafe using the sequence of directives $st^{n'+1}$ and this contradicts Lemma 1 applied to the system call s.

- Case [[Spec-Unsafe](#page-44-1)]. By introspection of the rule, we deduce that there is a hybrid configuration

$$
\mathsf{unsafe}\,|\,(\langle \mathtt{A},\rho,b \rangle : F, D, O)
$$

such that

$$
w \vdash_{\sigma} \mathsf{unsafe} \, | \, (\langle \mathtt{A}, \rho, b \rangle : F, D, O) \rightarrow \mathsf{unsafe}
$$

and

$$
w \vdash_\sigma (\langle \mathtt{A}, \rho, \mathtt{u} \rangle, w \diamond \tau, \epsilon, \epsilon) \mathbin{\rightarrow}^n \mathtt{unsafe} \, | \, (\langle \mathtt{A}, \rho, b \rangle : F, D, O)
$$

With an application of Remark [13,](#page-58-0) we deduce that there is a configuration

$$
(\langle P, \rho', u \rangle, w \diamond \tau', \bot),
$$

with τ' ~Fund τ , a sequence of directives D', a sequence of observations O' and a natural number $n' \leq n$ such that:

$$
w \vdash_{\sigma} (\langle \mathtt{P}, \rho', \mathtt{u} \rangle, w \diamond \tau', \bot) \xrightarrow[D'] {O'}^{n'} \text{ unsafe}.
$$

Because of Lemma [14](#page-61-0) we can assume without lack of generality that D' does not contain any bt directive. From Lemma [10,](#page-51-0) we deduce that there is configuration

$$
(\langle \gamma(s), \rho'', \mathbf{k}_s \rangle, w \diamond \tau', b),
$$

a sequence of directives D'' , a sequence of observations O'' and a store τ'' such that:

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho'', \mathbf{k}_s \rangle, w \diamond \tau'', b) \xrightarrow{O''} \substack{n'' \text{ unsafe.}}
$$

but this is in contradiction with Lemma [1](#page-16-0) applied to s.

Lemma 8. For every system $\sigma = (\tau, \gamma, \xi)$, natural number n, configurations

$$
C=(\langle \mathtt{A},\overline{\rho},\mathtt{u}\rangle,\overline{m},\overline{D},\overline{O})
$$

and

 $(\langle P, \rho, k_s \rangle : F_k : F_u, m, D, O)$

where A is unprivileged, $\kappa(F_k)$ and $\mu(F_u)$, such that

$$
w \vdash_{\sigma} C \rightarrow^n (\langle P, \rho, k_{s} \rangle : F_{k} : F_{u}, m, D, O),
$$

there is a third configuration

$$
(\langle \gamma({\bf s}),\rho', {\bf k_s}\rangle, m', D,O),
$$

a natural number n ′ such that

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho', k_s \rangle, m', D, O) \rightarrow^{n'} (\langle P, \rho, k_s \rangle : F_k, m, D, O).
$$

Proof. The proof goes by induction on n . The base case holds for vacuity of the premise The inductive case goes by cases on the rule that has been used to show the last transition. All the rules that do have as target a non-terminal classic configuration except for [[APop](#page-46-3)] and [[ASC](#page-46-4)] share a similar behavior is the same, so we just show the case of loads:

- Case [[ALoad](#page-45-2)]. In this case, the assumption is that

$$
w \vdash_\sigma C \twoheadrightarrow^n (\langle x \ := \ * \mathsf{E}; \mathsf{P}, \rho'', b \rangle : F, m, D, O) \twoheadrightarrow (\langle \mathsf{P}, \rho''[x \leftarrow [\![\mathsf{E}]\!]_{\rho'',w}], \mathtt{k}_\mathtt{s} \rangle : F_\mathtt{k} : F_\mathtt{u}, m, D, O)
$$

by introspection of the rule, we deduce $\rho = \rho''[x \leftarrow \llbracket \mathbf{E} \rrbracket_{\rho'',w}]$ and that flag of the source configuration is equal to that of the target one it must be k_s as well, so we can apply the IH. This shows that there is a configuration

$$
(\langle \gamma(\mathbf{s}), \rho', \mathbf{k_s} \rangle, m', D, O)
$$

a natural number n' such that

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho', \mathbf{k}_s \rangle, m', D, O) \rightarrow^{n'} (\langle x \ := \ast \mathbf{E}; \mathbf{P}, \rho'', \mathbf{k}_s \rangle : F_{\mathbf{k}}, m, D, O).
$$

Then we observe that the rule [ALOAD] can be applied to the configuration

$$
(\langle x \; := * \mathbf{E}; \mathbf{P}, \rho'', \mathbf{k}_{\mathrm{s}} \rangle : F_{\mathbf{k}}, m, D, O)
$$

to show the transition to

$$
(\langle \mathbf{P}, \rho''[x \leftarrow [\![\mathbf{E}]\!]_{\rho'',w}], \mathbf{k}_\mathrm{s}\rangle : F_\mathbf{k}, m, D, O)
$$

and this shows the claim.

- Case [[ASC](#page-46-4)]. In this case, the assumption is that

$$
w \vdash_{\sigma} C \rightarrow^n (\langle \text{syscall s}(E_1, \ldots, E_k); P, \rho'', b \rangle : F, m, D, O) \rightarrow \langle (\langle \gamma(s), \rho, k_s \rangle : \langle P, \rho'', b \rangle : F_k : F_u, m, D, O) \rangle
$$

From Remark [11,](#page-57-0) we deduce that $u(F)$ and $b = u$. This shows that the claim holds, in particular $F_{\mathbf{k}} = \varepsilon$, $F_{\mathbf{u}} = F$, and it is easy to verify that

$$
w \vdash_{\sigma} (\langle \text{syscall s}(E_1, \ldots, E_k); P, \rho'', b \rangle, m, D, O) \rightarrow (\langle \gamma(s), \rho, k_s \rangle : \langle P, \rho'', b \rangle, m, D, O)
$$

holds.

- Case [[APop](#page-46-3)]. In this case, the assumption is that

$$
w \vdash_\sigma C \multimap^n (\langle \mathbf{Q}, \rho'', b \rangle : \langle \mathbf{P}, \rho, \mathbf{k}_s \rangle : F, m, D, O) \multimap (\langle \mathbf{P}, \rho'[ret \leftarrow \rho''(ret)], \mathbf{k}_s \rangle : F, m, D, O),
$$

With an application of Remark [11,](#page-57-0) we rewrite F as $F_k : F_u$, and we deduce that $b = k_s$, so we can apply the IH. It shows that there is a configuration

$$
(\langle \gamma(s), \rho', \mathtt{k}_s \rangle, m', D, O)
$$

a natural number n' such that

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho', \mathbf{k}_s \rangle, m', D, O) \rightarrow^{n'} (\langle \mathbf{Q}, \rho'', b \rangle : \langle \mathbf{P}, \rho, \mathbf{k}_s \rangle : F_{\mathbf{k}}, m, D, O).
$$

To conclude the proof it suffices to verify that

$$
w \vdash_{\sigma} (\langle \mathbf{Q}, \rho'', b \rangle : \langle \mathbf{P}, \rho, \mathbf{k}_{s} \rangle : F_{\mathbf{k}}, m, D, O) \rightarrow (\langle \mathbf{P}, \rho'[ret \leftarrow \rho''(ret)], \mathbf{k}_{s} \rangle : \langle \mathbf{P}, \rho, \mathbf{k}_{s} \rangle : F_{\mathbf{k}}, m, D, O).
$$

Lemma 9. For every system $\sigma = (\overline{\tau}, \gamma, \xi)$, store $\tau \sim_{\text{Funld}} \overline{\tau}$), configuration $(\langle P, \rho, u \rangle, w \diamond \tau, D, O)$, $n \in \mathbb{N}$, and every configuration $(F, w \diamond \tau, D, O)$ if

$$
w \vdash_{\sigma} (\langle P, \rho, k_{s} \rangle, w \diamond \tau, D, O) \rightarrow^{n} (F, w \diamond \tau', D, O),
$$

then $\mathbf{k}_s(F)$ and there is a buffered memory $\mu(w \diamond \tau'')$ and a sequence of observations O such that

$$
w \vdash_{\sigma} (\langle P, \rho, k_{s} \rangle, w \diamond \tau, \bot) \xrightarrow{\Theta} {n \choose s t^{n}} (F, \mu(w \diamond \tau''), \bot)
$$

and $\overline{\mu(w \diamond \tau'')} = w \diamond \tau'.$

Proof. We go by induction on n .

- Case 0. Trivial.
- CASE $n + 1$. In this case, the premise is:

$$
w \vdash_\sigma (\langle \mathtt{P}, \rho, \mathtt{k}_\mathtt{s} \rangle, w \diamond \tau, D, O) \multimap^n (\langle \mathtt{P}', \rho', \mathit{b}' \rangle : F', w \diamond \tau'', D, O) \multimap (F, w \diamond \tau', D, O)
$$

We can apply The IH to the first n steps. This shows that there are μ and O

$$
w \vdash_\sigma (\langle \mathtt{P}, \rho, \mathtt{k}_\mathtt{s} \rangle, w \diamond \tau, \bot) \xrightarrow[\mathtt{st}^n]{O} \mathsf{n} \ (\langle \mathtt{P}', \rho', \mathtt{k}_\mathtt{s} \rangle : F', \mu(w \diamond \omega), \bot)
$$

such that $\overline{\mu(w \diamond \omega)} = w \diamond \tau''$ and $k_s(\langle P', \rho', k_s \rangle : F')$. We are required to show that

$$
w \vdash_\sigma (\langle \mathtt{P}', \rho', \mathtt{k_s}\rangle : F', \mu(w \diamond \omega), \bot) \xrightarrow[\mathtt{st}]{o} (F, \mu'(w \diamond \omega'), \bot),
$$

that $\overline{\mu'(w \diamond \omega')} = w \diamond \tau'$, and that $k_s(F)$ holds. The proof cases on the $\rightarrow \infty$ relation; many of the cases are similar with the others, so we just show the most important ones, also note that, in particular, cases [[Poison](#page-44-2)], [[Observe](#page-44-3)], [[Spec-Term](#page-44-4)], [[Spec-Error](#page-44-5)], and [[Spec-Unsafe](#page-44-1)] can be omitted because of the IH.

- Case [[AFence](#page-45-3)]. In this case, the assumption rewrites as follows:

$$
w \vdash_\sigma (\langle \texttt{fence}; \mathbf{Q}, \rho, \mathbf{k}_\mathrm{s}\rangle : F', w \diamond \tau'', D, O) \mathop{\rightarrow} (\langle \mathbf{Q}, \rho, \mathbf{k}_\mathrm{s}\rangle : F', w \diamond \tau'', D, O)
$$

and the goal is to show that there is an observation o , a buffer μ' and a store ω' such that:

$$
w \vdash_{\sigma} (\langle x \; := \; *E; \mathbf{Q}, \rho, \mathbf{k}_{s} \rangle : F', \mu(w \diamond \omega), \bot) \xrightarrow[\text{st}]{o} (\langle \mathbf{Q}, \rho, \mathbf{k}_{s} \rangle : F', \mu'(w \diamond \omega'), \bot)
$$

and $\overline{\mu'(w \diamond \omega)} = w \diamond \tau''$. By applying the rule [FENCE], suitable buffers and stores for the target configuration are $\mu' = \epsilon$ and $\omega' = \mu(w \diamond \omega)$, and the transition produces the observation \circ ; we need to observe that $w \circ \tau'' = \overline{\mu(w \circ \omega)}$, that is a consequence of the IH and of the definition of $\overline{\cdot}$ on memories. Finally, we must observe that $k_s(\langle \mathbf{Q}, \rho, \mathbf{k}_s : F' \rangle)$, but this is a direct consequence of the IH, and of the fact that Q is a sub-term of $x := *E; Q$.

- Case [[ALoad](#page-45-2)]. In this case, the assumption rewrites as follows:

$$
w \vdash_{\sigma} (\langle x \; := * \mathbf{E}; \mathbf{Q}, \rho, \mathbf{k}_{\mathrm{s}} \rangle : F', w \diamond \tau'', D, O) \rightarrow (\langle \mathbf{Q}, \rho[x \leftarrow w \diamond \tau''([\![\mathbf{E}]\!]_{\rho,w}^{\mathsf{Addr}})], \mathbf{k}_{\mathrm{s}} \rangle : F', w \diamond \tau'', D, O)
$$

and the goal is to show that there is an observation o and a buffer μ' such that:

$$
w \vdash_{\sigma} (\langle x \; := *E; \mathbf{Q}, \rho, \mathbf{k}_{\mathrm{s}} \rangle : F', \mu(w \diamond \omega), \bot) \xrightarrow[\text{st}]{\sigma} (\langle \mathbf{Q}, \rho[x \leftarrow w \diamond \tau''([\![\mathbf{E}]\!]_{\rho,w}^{\mathsf{Addr}})], \mathbf{k}_{\mathrm{s}} \rangle : F', \mu'(w \diamond \omega'), \bot)
$$

and $\overline{\mu'(w \diamond \omega)} = w \diamond \tau''$. We choose $\mu' = \mu$ and $\omega = \omega'$ and the equality is a consequence of the IH. The only rule that can apply is [[SLoad-Step](#page-42-4)]; with this choice the observation produced is mem $\llbracket \mathbf{E} \rrbracket_{\rho,w}^{\mathsf{Addr}}$; we need to observe that $w \diamond \tau''(\llbracket \mathbf{E} \rrbracket_{\rho,w}^{\mathsf{Addr}}) = (\mu'(w \diamond \omega))^0(\llbracket \mathbf{E} \rrbracket_{\rho,w}^{\mathsf{Addr}})$, that is a consequence of Remark [6.](#page-44-6) Finally, we must observe that

$$
\mathbf{k}_{\mathrm{s}}(\langle \mathbf{Q}, \rho[x \leftarrow w \diamond \tau''([\![\mathbf{E}]\!]_{\rho,w}^{\mathsf{Addr}})], \mathbf{k}_{\mathrm{s}}\rangle : F'),
$$

but this is a direct consequence of the IH, and of the fact that Q is a sub-term of $x := *E$; Q. - Case [[AStore](#page-45-4)]. In this case, the assumption rewrites as follows:

$$
w \vdash_\sigma (\langle \ast \mathbf{E}:=\mathbf{F};{\tt Q},\rho,\mathbf{k}_\mathrm{s}\rangle : F',w\diamond \tau'',D,O) \rightarrow (\langle {\tt Q},\rho,\mathbf{k}_\mathrm{s}\rangle : F',w\diamond \tau''[\llbracket \mathbf{E} \rrbracket^{\mathsf{Addr}}_{\rho,w} \leftarrow \llbracket \mathbf{F} \rrbracket_{\rho,w}],D,O)
$$

and the goal is to show that there is an observation o and a buffer μ' such that:

$$
w \vdash_\sigma (\langle \ast x := \mathtt{E}; \mathtt{Q}, \rho, \mathtt{k}_\mathtt{s} \rangle : F', \mu(w \diamond \omega), \bot) \xrightarrow[\mathtt{st}]{o} (\langle \mathtt{Q}, \rho, \mathtt{k}_\mathtt{s} \rangle : F', \mu'(w \diamond \omega), \bot)
$$

and $\overline{\mu'(w \circ \omega)} = w \circ \tau''[[\mathbb{E}]_{\rho,w}^{\text{Addr}} \leftarrow [\mathbb{F}]_{\rho,w}].$ We observe that the rule [SSTORE] applies and produces a target configuration that matches the one we are looking for, in particular, the buffer it produces is

$$
[\llbracket \mathbf{E} \rrbracket^{\mathsf{Addr}}_{\rho,w} \mapsto \llbracket \mathbf{F} \rrbracket_{\rho,w}] : \mu.
$$

We observe that the conclusion

$$
\overline{[\![\mathbb E]\!]_{\rho,w}^{\mathsf{Addr}}\mapsto [\![\mathbf F]\!]_{\rho,w}]:\mu(w\diamond\omega)}=w\diamond\tau''[\![\mathbb E]\!]_{\rho,w}^{\mathsf{Addr}}\leftarrow[\![\mathbf F]\!]_{\rho,w}]
$$

comes from the rewriting of the function $\overline{\cdot}$ and form the assumption $\overline{\mu(w \diamond \omega)} = w \diamond \tau''$.

- Case [[ACall](#page-46-5)]. In this case, we observe that this rule and [[SCall](#page-42-6)] share the same premises, so also the second one can be applied. By introspection of these rules, we deduce that said $P' = \text{call } F(E_1, \ldots, E_k); Q$, the target configurations are respectively

$$
(\langle w \diamond \tau''(\llbracket \mathbf{F} \rrbracket_{\rho',w}), \rho_0', \mathbf{k}_\mathrm{s}\rangle : \langle \mathbf{Q}, \rho', \mathbf{k}_\mathrm{s}\rangle : F', w \diamond \tau'', D, O)
$$

and

$$
(\langle w \diamond \tau''(\llbracket \mathbf{F} \rrbracket_{\rho',w}), \rho_0', \mathbf{k}_s \rangle : \langle \mathbf{Q}, \rho', \mathbf{k}_s \rangle : F', \mu(w \diamond \omega), \bot),
$$

where $\rho'_0 = \rho_0[x_1,\ldots,x_k \leftarrow [\![\mathbf{E}_1]\!] \rho', w, \ldots, \mathbf{E}_k \rho', w]$. For this reason, the conclusion on the buffered memory is a consequence of the IH, and we can deduce

$$
\mathbf{k}_{\mathrm{s}}(\langle w\diamond \tau''(\llbracket \mathbf{F} \rrbracket_{\rho',w}),\rho'_0,\mathbf{k}_{\mathrm{s}}\rangle:\langle \mathbf{Q},\rho',\mathbf{k}_{\mathrm{s}}\rangle:F')
$$

from the IH and the premises of the rule [ACALL], which guarantee $[\![\mathbf{F}]\!]_{\rho',w} \in \underline{w}(\mathsf{Funld}_k)$; this, in turn, has as consequence that there is $f \in \text{Fund}_k$ such that $w(f) = \llbracket F \rrbracket_{\rho',w}$. Thus, by definition of $\cdot \diamond \cdot$, we conclude that

$$
w \diamond \tau''(\llbracket \mathbf{F} \rrbracket_{\rho',w}) = \omega(\mathbf{f}) = \overline{\tau}(\mathbf{f}).
$$

For this reason, it suffices to observe that $k_s(\overline{\tau}(f))$ holds by definition of system.

Lemma 10. For every system $\sigma = (\tau, \gamma, \xi)$, configuration

 $(\langle P, \rho, u \rangle, (\mu m), \perp)$

such that $u(P)$ speculative stack $S = (\langle P, \rho', k_{s} \rangle : F', (\mu m)', b_{ms}) : S'$, sequence of directives D without bt directives, sequence of observations O and layout w such that

$$
w \vdash_{\sigma} (\langle P, \rho, u \rangle, (\mu m), \bot) \xrightarrow{O} {n} S,
$$

there is a configuration $(\langle \gamma(s), \rho_0[x_0, \ldots, x_h \leftarrow v_1, \ldots, v_h], k_s \rangle : F'', (\mu m)'', b_{ms})$ a sequence of directives D', a sequence of observations O', and a natural number $n' \leq n$ such that:

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho'', \mathbf{k}_s \rangle, (\mu m)'', b_{ms}'') \xrightarrow{O'} n'(\langle P, \rho', \mathbf{k}_s \rangle : \overline{F}, (\mu m)', b_{ms}') : \overline{S},
$$

for some \overline{S} , where in particular \overline{F} is a prefix of F' such that $\mathbf{k}_{s}(\langle P,\rho',\mathbf{k}_{s}\rangle : \overline{F})$ and there is a stack F'' such that $u(F'')$ and $F' = \overline{F} : F''$.

Proof. By induction on n .

- Case 0. Holds by vacuity of the premise.
- CASE $n + 1$. The premise rewrites as

$$
w \vdash_{\sigma} (\langle P, \rho, u \rangle, (\mu m), \bot) \xrightarrow{O} {n \atop D} T \xrightarrow{o} S.
$$

We go by cases on the rule that has been applied to show the last transition. Most of these cases are similar to the others; for this reason, we just show some of the most interesting ones. In particular, since D does not contain any bt directive, we can assume without lack of generality that the rules for backtracking are not employed.

□

- Case [[SOp](#page-43-2)]. In this case we can assume that

$$
T = (\langle x := \mathbf{E}; \mathbf{Q}, \rho'''', b \rangle : F'''', (\mu m)''', b_{ms}''': T'.
$$
 (†)

By introspection of the rule, we deduce that the flag of the target configuration is equal to that of the source configuration, so we deduce $b = k_s$, this also means that we can apply the IH on the first n steps and deduce that

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho'', \mathbf{k}_s \rangle, (\mu m)'', b_{ms}'') \xrightarrow{O'} n'(\langle x := \mathbf{E}; \mathbf{Q}, \rho'''', b \rangle : \overline{F}''', (\mu m)''', b_{ms}'') : \overline{T}',
$$

 \overline{F}'''' is a suffix of F''' such that $\mathbf{k}_s(\overline{F}''')$ and there is a stack G such that $\mathbf{u}(G)$ and $F''' = \overline{F}'''$: G. Then, we observe that

$$
w \vdash_{\sigma} (\langle x := \mathbf{E}; \mathbf{Q}, \rho''', b \rangle : \overline{F}''', (\mu m)''', b_{ms}'') : \overline{T}' \xrightarrow[\text{st}]{\circ} (\langle \mathbf{Q}, \rho'''[x \leftarrow [\![\mathbf{F}]\!]_{\rho'''}, w], b \rangle : \overline{F}'''', (\mu m)''', b_{ms}''') : \overline{T}',
$$

and that:

$$
w \vdash_{\sigma} (\langle x := \mathbf{E}; \mathbf{Q}, \rho''', b \rangle : F''', (\mu m)''', b_{ms}''') : T' \xrightarrow[\text{st}]{\circ} (\langle \mathbf{Q}, \rho'''[x \leftarrow [\![\mathbf{F}]\!]_{\rho'''}, w], b \rangle : F'''', (\mu m)''', b_{ms}''') : T',
$$

The conclusions that we are required to show are a direct consequence of the IH, and of the observation that $k_s(x := E; Q)$ has as consequence $k_s(Q)$.

- Case [[SLoad](#page-42-7)]. In this case we can assume that

$$
T = (\langle x :=_{\ell} * \mathbf{E}; \mathbf{Q}, \rho''', b \rangle : F''', (\mu m)''', b''''_{ms}) : T'.
$$
 (†)

By introspection of the rule, we deduce that the execution mode flag of the target configuration is equal to that of the source configuration, so we deduce $b = k_s$, this also means that we can apply the IH on the first n steps and deduce that

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho'', \mathbf{k}_s \rangle, (\mu m)'', b_{ms}'') \xrightarrow{O'} n'(\langle x \ :=_{\ell} \ast \mathbf{E}; \mathbf{Q}, \rho'''', b \rangle : \overline{F}''', (\mu m)''', b_{ms}'') : \overline{T}',
$$

 \overline{F}'''' is a suffix of F''' such that $\mathbf{k}_s(\overline{F}''')$ and there is a stack G such that $\mathbf{u}(G)$ and $F''' = \overline{F}'''$: G. Then, we call p the value of $\llbracket \mathbf{E} \rrbracket_{\rho''',w}^{\mathsf{Addr}}$ and (v, b) the pair that is returned by $((\mu m)''')^i(p)$. Then, we observe that

$$
w \vdash_{\sigma} (\langle x \ ::=_{\ell} * \mathbf{E}; \mathbf{Q}, \rho''', b \rangle : F''', (\mu m)''', b_{ms}''': T' \frac{\text{mem } p}{\text{1d}_{\ell} i} \rangle
$$

$$
(\langle \mathbf{Q}, \rho'''[x \leftarrow v], b \rangle : F''', (\mu m)''', b_{ms}''' \vee b) :
$$

$$
(\langle x \ ::=_{\ell} * \mathbf{E}; \mathbf{Q}, \rho''', b \rangle : F''', (\mu m)''', b_{ms}''': T',
$$

and that:

$$
w \vdash_{\sigma} (\langle x \; :=_{\ell} * \mathbf{E}; \mathbf{Q}, \rho''', b \rangle : \overline{F}''', (\mu m)''', b_{ms}'') : \overline{T}' \xrightarrow{\text{mem } p} \langle \langle \mathbf{Q}, \rho'''[x \leftarrow v], b \rangle : \overline{F}''', (\mu m)''', b_{ms}''' \vee b) : \\ (\langle x \; :=_{\ell} * \mathbf{E}; \mathbf{Q}, \rho'''', b \rangle : \overline{F}''', (\mu m)''', b_{ms}'''': \overline{T}',
$$

The conclusions that we are required to show are a direct consequence of the IH and of the observation that and of the observation that $k_s(x := *E; Q)$ has as consequence $k_s(Q)$.

- CASE [SCALL]. In this case we can assume that T is

$$
(\langle \text{call } E(\mathbf{F}_1,\ldots,\mathbf{F}_k); \mathbf{Q}, \rho^{\prime\prime\prime},b\rangle : F^{\prime\prime\prime},(\mu m)^{\prime\prime\prime},b_{ms}^{\prime\prime\prime}):T^{\prime}.
$$

By introspection of the rule, and by knowing that the execution flag of the target configuration is k_s , we deduce that this must be the case also for the source configuration, so $b = k_s$, this also means that we can apply the IH on the first n steps and deduce that

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho'', \mathbf{k}_s \rangle, (\mu m)'', b_{ms}'') \xrightarrow{O'} n'(\langle \text{call } E(\mathbf{F}_1, \ldots, \mathbf{F}_k); \mathbf{Q}, \rho''', b \rangle : \overline{F}''', (\mu m)''', b_{ms}''') : \overline{T}',
$$

 \overline{F}'''' is a suffix of F''' such that $\mathbf{k}_s(\overline{F}''')$ and there is a stack G such that $\mathbf{u}(G)$ and $F''' = \overline{F}'''$: G. Then, we call p the value of $[\mathbb{E}]_{\rho''',w}^{\mathsf{Addr}}$ and we observe that form the premise of the rule and the definition of w, we can deduce that there is $f \in \text{Fund}_b$ such that $w(f) = p$. From this observation, and Remark [9,](#page-56-1) we deduce that $(\mu m)''' = \mu' w \diamond \tau'$ for a $\tau' \sim_{\text{Funld}} \tau$ So, from the definition of $\cdot \diamond \cdot$ and these observations we conclude that the executed procedure is exactly $\tau(f)$. We also call $\bar{\rho}$ the register map that is obtained by evaluating the semantics of the arguments in $\rho^{\prime\prime\prime}$ and updating the argument registers of ρ_0 with these values. Then, by introspection of the rule, we observe that

$$
w \vdash_{\sigma} (\langle \text{call } E(F_1, \ldots, F_k); \mathbf{Q}, \rho''', b \rangle : F'''', (\mu m)''', b_{ms}'') : T' \frac{\text{imp } p}{\text{st}} \rangle (\langle \tau(f), \overline{\rho}, b \rangle : \langle \mathbf{Q}, \rho'''', b \rangle : F'''', (\mu m)''', b_{ms}''') : T',
$$

and that also:

$$
w \vdash_{\sigma} (\langle \text{call } E(F_1, \ldots, F_k); \mathbf{Q}, \rho''', b \rangle : \overline{F}''', (\mu m)''', b_{ms}'') : \overline{T}' \xrightarrow{\text{imp } p} \uplus (\langle \tau(f), \overline{\rho}, b \rangle : \langle \mathbf{Q}, \rho'''', b \rangle : \overline{F}''', (\mu m)''', b_{ms}''') : \overline{T}'.
$$

can be shown. The conclusions that we are required to show are a direct consequence of the IH, and of the observation that $k_s(\tau(f))$ holds by definition of τ because $f \in \text{Fund}_k$. - CASE [[SSC](#page-42-8)]. In this case we can assume that T is

$$
(\langle \text{syscall } t(\mathbf{F}_1,\ldots,\mathbf{F}_k) ; \mathbf{Q}, \rho''' , b \rangle : F''', (\mu m)''', b'''_{ms}) : T'.
$$

By introspection of the rule and the target configuration, we deduce that $t = s$; and that S has the following shape:

$$
(\langle \gamma(\mathbf{s}), \rho_0', \mathbf{k_s}\rangle : \langle \mathbf{Q}, \rho''', b\rangle : F''', (\mu m)''', b_{ms}''') : T'.
$$

where ρ'_0 is obtained by updating the argument registers of ρ_0 with the evaluation of E_1, \ldots, E_k . To show the claim, it suffices to set $n' = 0$, $D' = \epsilon$, $\overline{C} = \epsilon$, $\overline{F} = \epsilon$, $F'' = F'$, and the observation $\mathbf{k}_{s}(\langle \gamma(s), \rho'_{0}, \mathbf{k}_{s} \rangle)$ holds for definition of γ , while $\mathbf{u}(\langle \mathbf{Q}, \rho''', b \rangle : F''')$ is a consequence of Remark [12.](#page-57-1) In particular, we can refuse the assumption that $op = \mathbf{k}_t$, because in such case we could not have a system call invocation as a command. Then, from the invariant on the composition on the stack, we deduce u (syscall $s(E_1, \ldots, E_k); Q$).

- CASE [SPOP]. In this case we can assume that T is

$$
(\langle \epsilon, \rho''', b \rangle : F''', (\mu m)''', b_{ms}''') : T'.
$$

And by introspection of the rule, we deduce that

$$
F''' = \langle P, \rho'[ret \leftarrow v], \mathbf{k}_{s} \rangle : F'
$$

for some v; from this observation and Remark [12,](#page-57-1) we deduce that $b = \mathbf{k}_s$, so we can apply the IH to the first n steps and obtain that

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho'', \mathbf{k}_s \rangle, (\mu m)'', b_{ms}'') \xrightarrow{\mathcal{O}'} n'(\langle \epsilon, \rho''', b \rangle : \overline{F}''', (\mu m)''', b_{ms}'') : \overline{T}',
$$

 \overline{F}'''' is a suffix of F''' such that $\mathbf{k}_s(\overline{F}''')$ and there is a stack G such that $\mathbf{u}(G)$ and $F''' = \overline{F}'''$: G. This shows that, in particular, the first frame of \overline{F}'''' must also be $\langle P, \rho'[ret \leftarrow v], k_{s}\rangle$. Otherwise, it either would not be a prefix of F''' or its concatenation with G (observe that $\mathfrak{u}(G)$) would not be F''' . Thanks to this observation, by introspection of the rule, we observe that

$$
w \vdash_{\sigma} (\langle \epsilon, \rho''', b \rangle : F''' , (\mu m)''' , b_{ms}''') : T' \xrightarrow{\circ} (\langle P, \rho', k_{s} \rangle : F', (\mu m)''', b_{ms}''') : T',
$$

and that also:

$$
w \vdash_{\sigma} (\langle \epsilon, \rho''', b \rangle : \overline{F}''', (\mu m)''', b_{ms}'') : \overline{T}' \xrightarrow[\text{st}]{\circ} (\langle P, \rho', k_{s} \rangle : F', (\mu m)''', b_{ms}'') : T',
$$

This concludes the proof.

A.2.5 On the fencing transformation

Proof of Theorem [3.](#page-18-0) This result is a direct consequence of Lemmas [11](#page-54-1) and [12](#page-54-2) and of Proposition [1.](#page-18-2) \Box

We extend the semantics of fig. [3](#page-7-0) by giving the following semantics to the fence instruction:

$$
w \vdash_{\sigma} (\langle \text{fence}; P, \rho, b \rangle : F, m) \rightarrow (\langle P, \rho, b \rangle : F, m)
$$
^[FENCE]

In addition, in order to facilitate the proof of the forthcoming results, we introduce the predicate of η -well-formedness. Given a system $\sigma = (\tau, \gamma, \xi)$, such predicate is defined as follows:

$$
\frac{\forall f \in \text{FunId}_{k}.\exists P.\tau'(f) = \eta(P) \quad \tau \sim_{\text{FunId}} \tau'}{\sigma \vdash \text{fwf}_{w,s}(\tau')}
$$
\n
$$
\frac{\sigma \vdash \text{fwf}_{w,s}(F) \quad \exists P'.P = \eta(P')}{\sigma \vdash \text{fwf}_{w,s}(\langle P, \rho, k_{s} \rangle : F)}
$$
\n
$$
\overline{\sigma \vdash \text{fwf}_{w,s}(\varepsilon)} \quad \overline{\sigma \vdash \text{fwf}_{w,s}(\text{err})} \quad \overline{\sigma \vdash \text{fwf}_{w,s}(\text{unsafe})}
$$
\n
$$
\frac{\sigma \vdash \text{fwf}_{w,s}(\tau') \quad \sigma \vdash \text{fwf}_{w,s}(F) \quad \text{dom}(\mu) \subseteq \underline{w}(\text{Arrld}_{k})}{\sigma \vdash \text{fwf}_{w,s}((F, \mu(w \diamond \tau'), b_{ms}))}
$$
\n
$$
\frac{\sigma \vdash \text{fwf}_{w,s}(C)}{\sigma \vdash \text{fwf}_{w,s}(C : S)} \quad \overline{\sigma \vdash \text{fwf}_{w,s}(\epsilon)}
$$

Lemma 11. The semantics of every system σ is equivalent to that of $\eta(\sigma)$.

Proof. Direct consequence of Lemma [15.](#page-62-0)

Lemma 12. The transformation η imposes speculative kernel safety.

Proof. We assume that there is a system $\sigma = (\tau, \gamma, \varphi)$, a system call s a register map ρ buffer μ , an array store $\tau' \sim_{\text{Fun}} \tau$, and a natural number *n* such that

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho, \mathbf{k}_s \rangle, \mu(w \diamond \tau'), b_{ms}) \xrightarrow{O}^n \mathbf{u} \mathbf{n} \mathbf{s} \mathbf{a} \mathbf{f} \mathbf{e}.
$$

for a sequence of directives D (that we assume free of b t because of Lemma [14\)](#page-61-0) producing a set of observations O. By case analysis on n, we refuse the case where $n = 0$, because that would mean

$$
(\langle \gamma(s), \rho, k_s \rangle, \mu(w \diamond \tau'), b_{ms}) = \text{unsafe}.
$$

 \Box

For this reason, in the following, we assume that $n > 0$. By case analysis on the proof relation, we deduce that the rule that has been used to show the last transition must be one among [ALOAD-UNSAFE]. [[AStore-Unsafe](#page-45-1)] and [[ACall-Unsafe](#page-46-2)]. We just show the case for [[ALoad-Unsafe](#page-45-0)], in the other cases it is analogous. This means that

$$
w \vdash_\sigma (\langle \gamma(s), \rho, \mathbf{k}_s \rangle, \mu(w \diamond \tau'), b_{ms}) \xrightarrow[D']{}^{n-1}(\langle x \ := \ * \mathbf{E}; \mathbf{Q}, \rho', \mathbf{k}_s \rangle : F, \mu'(w \diamond \tau''), b_{ms}') : S \xrightarrow[\text{st}]{\text{mem } p} \text{unsafe}.
$$

Observe that $n > 1$: otherwise, if $n = 1$, we would have $x := *E, Q = \gamma(s)$, but from $\sigma \in \mathsf{im}(\eta)$, we deduce that there is a system $\sigma' = (\tau'', \gamma', \xi')$ such that $\eta(\sigma') = \sigma$. This, in particular, would mean that $\gamma(s) = \eta(\gamma'(s))$, so there is a command $P \in \text{Cmd}$ such that $\gamma(s) = \eta(\gamma'(P))$ but, by induction on the syntax of the command, we observe that this is not possible. However, from Remark [12,](#page-57-1) we deduce that P cannot contain system calls, so we can apply Lemma [16,](#page-64-0) we deduce that there must be a stack of configurations

$$
(\langle P, \rho'', k_s \rangle : F'', \mu''(w \diamond \tau'''), b''_{ms}) : S'
$$

such that:

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, \mu(w \diamond \tau'), b_{ms}) \xrightarrow{O''} {}^{n-2}
$$

$$
(\langle P, \rho'', k_s \rangle : F'', \mu''(w \diamond \tau'''), b''_{ms}) : S' \xrightarrow{o} {}_{d} \diamond
$$

$$
(\langle x := *E; \mathbf{Q}, \rho', k_s \rangle : F, \mu'(w \diamond \tau''), b''_{ms}) : S \xrightarrow{\text{mem } p} \text{unsafe.}
$$

and, in particular, $\sigma \vdash \text{fwf}_{w,s}(\langle P, \rho'', k_s \rangle : F'')$. From this observation, we deduce that $P = \eta(\mathbf{Q})$ for some $Q \in \mathsf{Cmd}$ and that $\sigma \vdash \mathsf{fwf}_{w,s}(F'')$ holds. For these reasons, going by cases on Q and the rule that has been used to show the last transition (knowing that $d \neq$ bt by assumption), we can rewrite the reduction above, that rewrites as follows:

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho, k_{s} \rangle, \mu(w \diamond \tau'), b_{ms}) \xrightarrow{\mathcal{O}''} {}^{n-2}
$$

$$
(\langle \text{fence}; x \rangle := *E; \mathbf{Q}, \rho'', k_{s} \rangle, \mu''(w \diamond \tau'''), b_{ms}'') : S \xrightarrow{o}{}_{d}
$$

$$
(\langle x \rangle := *E; \mathbf{Q}, \rho', k_{s} \rangle : F, \overline{\mu''(w \diamond \tau''')}, \bot) : S \xrightarrow{\text{mem } p} \text{unsafe}.
$$

In particular, none of the rules except for [[AFence](#page-45-3)] can have been used. This also means that $b'_{ms} = b''_{ms} = \perp$ because no bt directive can have been employed. From Lemma [13,](#page-60-0) we deduce that there is n' such that:

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho, \mathbf{k}_s \rangle, \mu(w \diamond \tau'), b_{ms}) \xrightarrow[\text{str}'']{}^{n'}(\langle x \ := \ * \mathbf{E}; \mathbf{Q}, \rho', \mathbf{k}_s \rangle : F, \overline{\mu''(w \diamond \tau''')}, \bot) : S \xrightarrow[\text{st}]{\text{mem } p} \text{unsafe}.
$$

Finally, we apply Lemma [17](#page-66-0) that shows:

$$
w \vdash_{\sigma} (\langle \gamma(s), \rho, k_s \rangle, \overline{\mu(w \diamond \tau')}) \rightarrow^{n'} (\langle x \ := \ast E; \mathbf{Q}, \rho', k_s \rangle : F, \overline{\mu''(w \diamond \tau''')}).
$$

Finally, by assumption we know that the rule [SLOAD-UNSAFE] has been applied to show the transition in the speculative semantics. By introspection of that rule, we conclude that its premises are also verified by the configuration

$$
(\langle x\> := \ast \mathbf{E}; \mathbf{Q}, \rho', \mathbf{k}_\mathrm{s}\rangle : F, \overline{\mu''(w\diamond \tau''')});
$$

this shows that [LOAD-UNSAFE] applies, i.e.

$$
w \vdash_{\sigma} (\langle x \; := \text{ *E}; \text{Q}, \rho', \text{k}_s \rangle : F, \overline{\mu''(w \diamond \tau''')}) \rightarrow^{n'} \text{unsafe},
$$

and this shows $CBU(\sigma)$.

Technical Observations In order to show the analogous result but for the speculative semantics, we define the judgment $\sigma \vdash \textsf{wf}_{\sigma}(\cdot)$. For a system $\sigma = (\tau, \gamma, \xi)$, it is defined as follows:

$$
\begin{array}{c}\n\overline{\sigma \vdash \textsf{wf}_{\sigma}((\textsf{err}, \bot))} \quad \overline{\sigma \vdash \textsf{wf}_{\sigma}(\textsf{unsafe})} \quad \overline{\sigma \vdash \textsf{wf}_{\sigma}(\epsilon)} \\
\overline{\sigma \vdash \textsf{wf}_{\sigma}(S) \quad \textsf{dom}(\mu) \subseteq w(\textsf{Arrld}) \quad m = w \diamond \tau' \quad \tau' \sim_{\textsf{Fund}} \tau} \\
\sigma \vdash \textsf{wf}_{\sigma}((F, \mu m, b_{ms}): S)\n\end{array}
$$

Remark 8. For every system $\sigma = (\tau, \gamma, \xi)$, layout $w \in \text{Lay}$, pair of configurations S and S', sequences of directives D and of observations O, if $\sigma \vdash \textsf{wf}_{\sigma}(S)$ and $w \vdash_{\sigma} (\langle P, \rho, u \rangle, w \diamond \tau, \bot) \stackrel{O}{\to} *S$, then we have $\sigma \vdash \mathsf{wf}_{\sigma}(S)$.

Proof. The proof goes by induction on the number of steps.

- Case 0. Trivial.
- CASE $n + 1$. The claim is still a direct consequence of the IH, and in most of the cases the proof is straightforward. The most interesting cases are those for stores and fences. In the first case,the premise of the rule insures that the address where we write is part of the memory of an array. In the second case, it is a consequence of Remark [7.](#page-46-6)

Remark 9. For every system $\sigma = (\tau, \gamma, \xi)$, layout $w \in \text{Lay}$, pair of configurations $(F, w \circ \tau, D, O)$ and (F', m, D', O') such that $w \vdash_{\sigma} (F, w \circ \tau, D, O) \rightarrow^* (F', m, D', O')$, we have that $m = w \circ \tau'$ for some $τ'$ ~Funld $τ$.

Proof. To show this result we need to show, in conjunction with it, that if

$$
w \vdash_{\sigma} (F, w \diamond \tau, D, O) \rightarrow^* (S, F, D', O')
$$

then $\sigma \vdash \mathsf{wf}_{\sigma}(S)$ The proof goes by induction on the number of steps.

- Case 0. Trivial.
- CASE $n + 1$. The proof goes by cases on the rule that has been applied to show the last transition. The cases for the ordinary rules are simple. For this reason we just focus on those for the hybrid configuration.
	- Case [[Spec-Init](#page-44-7)]. In this case, we can verify that the speculative frame of the target configuration enjoys $\sigma \vdash \mathsf{wf}_{\sigma}(\cdot)$ simply by introspection of the target configuration and because of the IH.
	- Case [[Spec-D](#page-44-8)], [[Spec-S](#page-44-9)], [[Spec-BT](#page-44-10)]. The claim is a consequence of the IH and of Remark [8.](#page-56-0)
	- Case [[Spec-Term](#page-44-4)]. The claim is a consequence of the IH, and of Remark [7](#page-46-6) which ensures that the memory that is extracted form the speculative stack enjoys the desired property.

 \Box

Remark 10. For every pair of speculative stacks S, S' , system $\sigma = (\tau, \gamma, \xi)$, $n \in \mathbb{N}$, sequence of directives D, address p and layout w such that $p \notin \underline{w}(\mathsf{Id})$, if:

$$
w \vdash_\sigma S \xrightarrow{O} \nolimits^n S',
$$

then O does not contain the observation memp.

Proof. The proof goes by induction on n.

- Case 0. Trivial
- CASE $n + 1$. We apply the IH, and we go by cases on the rule that has been used to show the last transition. For those rules that do not produce a transition like mem p' , the claim is trivial. The rules that can produce a similar transition are [SLOAD-STEP], [SLOAD], [SLOAD-UNSAFE], [[SStore](#page-42-5)], [[SStore-Unsafe](#page-42-2)], [[SCall](#page-42-6)],

[SCALL-UNSAFE]. All these rules require in their premises that $p' \in \underline{w}(\text{Arrld}_k)$, $p' \in \underline{w}(\text{Fund}_k)$, $p' \in \underline{w}(\text{Arrld}_u)$, or that $p' \in \underline{w}(\text{FunId}_u)$, but since $p \notin \underline{w}(\text{Id})$, we deduce that p does not belong to any of these sets, so it must be that $p' \neq p$.

Remark 11. For every system $\sigma = (\tau, \gamma, \xi)$, every store $\tau \sim_{\text{Fun}} \tau'$, configuration

$$
C = (\langle P, \rho, u \rangle, w \diamond \tau', O, D),
$$

configuration $(F', w \circ \tau'', O, D)$, and hybrid configuration $(S, (F', O, D))$ that are reachable in n step from C, there are a pair of stacks $F_{\mathbf{k}}$, $F_{\mathbf{u}}$ such that $F' = F_{\mathbf{k}} : F_{\mathbf{u}}$, $\mathbf{k}(F_{\mathbf{k}})$ and $\mathbf{u}(F_{\mathbf{u}})$.

Proof. By induction on n . The base case is trivial, the inductive one comes by cases on the rule that is applied. Most of these rules are relatively simple. We just show the most interesting cases:

- Case [[APop](#page-46-3)]. The target configuration carries a stack which is a suffix of the one in the source configuration, so the conclusion is a trivial consequence of the IH.
- Case [[ASC](#page-46-4)]. We first apply the IH, which shows that:

$$
w \vdash_{\sigma} (\langle P, \rho, u \rangle : F, w \diamond \tau, O, D) \rightarrow^n (\langle \text{syscall s}(E_1, \ldots, E_k); Q, \rho', b \rangle F', w \diamond \tau, O, D)
$$

and that $\langle \text{syscall s}(E_1, \ldots, E_k), \rho', b \rangle F'$ is a concatenation of a pair of stacks F_k, F_u such that $k(F_k)$ and $u(F_u)$. Since the current command is a system call, F_k must be empty and b must be u. Observe that

$$
w \vdash_{\sigma} (\langle \text{syscall s}(E_1, \ldots, E_k); Q, \rho', u \rangle F', w \diamond \tau, O, D) \rightarrow (\langle \gamma(s), \rho'', k_s \rangle : \langle Q, \rho', u \rangle F', w \diamond \tau, O, D)
$$

for a suitable ρ'' . The claim just requires verifying that the target configuration above satisfies the premises. In particular that $k(\langle \gamma(s), \rho'', k_s \rangle)$ holds because $\gamma(s)$ cannot contain system call invocations for the definition of system.

- Case [[ACall](#page-46-5)]. This case is analogous to the previous one, but instead of setting the flag to k in the new frame, the rule copies it from the topmost frame of the source configuration, and this does not break the invariant. In particular, we observe that the target configuration of the rule looks like the following one:

$$
\langle \langle w \diamond \tau''(p), \rho_0[x_1 \leftarrow [\![\mathbf{F}_1]\!]_{\rho,w}, \ldots, x_n \leftarrow [\![\mathbf{F}_n]\!]_{\rho,w}], b \rangle : \langle P, \rho, b \rangle : F, w \diamond \tau'' \rangle.
$$

From Remark [8,](#page-56-0) we deduce that $\tau'' \sim_{\text{Fund}} \tau$, this means that $w \circ \tau''(p)$, because from the premises of the rule, we know that $p \in \underline{w}(\text{Fun}[b])$, which means that there is a function $f \in \text{Fun}[b]$ such that $w(f) = p$. From this observation and the definition of $\cdot \diamond \cdot$, we deduce that $w \diamond \tau''(p) = \tau(f)$. So, we go by cases on b. If it is u, the body of the function is unprivileged, and this shows $w \circ \tau''(p)$, analogously, if it is k, we observe that, this program is in Cmd and does not have any syscall \cdot (\cdot) instruction inside. This shows $k_s(\tau(f))$, as required.

- Case [[Spec-Init](#page-44-7)]. Observe that this rule simply copies the stack from the source configuration to the target configuration, and removes the executed command from the topmost frame; the conclusion is a consequence of the IH.

 \Box

口

In order to show a similar result, but for speculative execution, we strengthen the predicate $\sigma \vdash$ $\mathsf{wf}_{\sigma}(\cdot)$ into $\sigma \vdash \mathsf{swf}_{w}(\cdot)$ that is defined as follows:

$$
\begin{array}{ccc}\n\hline\n\sigma \vdash \mathsf{swf}_{w}((\mathsf{err}, \bot)) & \sigma \vdash \mathsf{swf}_{w}(\mathsf{unsafe}) & \sigma \vdash \mathsf{swf}_{w}(\epsilon) \\
\hline\n\sigma \vdash \mathsf{wf}_{\sigma}((F, \mu m, b_{ms}) : S) & \sigma \vdash \mathsf{swf}_{w}(S) & F = F_{\mathsf{k}} : F_{\mathsf{u}} & \mathsf{k}_{\mathsf{s}}(F_{\mathsf{k}}) & \mathsf{u}(F_{\mathsf{u}}) \\
\hline\n\sigma \vdash \mathsf{swf}_{w}((F, \mu m, b_{ms}) : S)\n\end{array}
$$

Remark 12. For every system $\sigma = (\tau, \gamma, \xi)$, every stack S such that $\sigma \vdash \textsf{swf}_{w}(S)$, stack S', such that $w \vdash_{\sigma} S \xrightarrow{O} \overline{D}^n S'$, we have $\sigma \vdash \mathsf{swf}_w(S')$.

Proof. By induction on n . The base case is trivial, the inductive one comes by cases on the rule that is applied. Thanks to Remark [8,](#page-56-0) we can just focus in showing the additional requirements on the stack. Most of these rules are relatively simple. We just show the most interesting cases:

- Case [[SPop](#page-42-9)]. The target configuration carries a frame-stack which is a suffix of the one in the source configuration, so the conclusion is a trivial consequence of the IH.
- CASE [ACALL]. We apply the IH, and we rewrite the configuration reached after n steps as follows:

$$
(\langle \text{call } E(E_1,\ldots,E_k); \mathbf{Q}, \rho, b \rangle : F, \mu' w \diamond \tau, b_{ms}) : S''
$$

we know by IH that it enjoys $\sigma \vdash \mathsf{swf}_{w}(\cdot)$, and we observe that the target configuration looks like the following one:

$$
(\langle \text{call } E(E_1,\ldots,E_k); \mathbf{Q}, \rho', b \rangle : \langle \mathbf{Q}, \rho, \mathbf{k} \rangle : F, \mu' w \diamond \tau, b_{ms}) : S''
$$

for some ρ_0 . From the premises of the rule, we know that $p \in \underline{w}(\text{Fund}_b)$, which means that there is a function $f \in \text{Fund}_b$ such that $w(f) = p$. From this observation and the definition of $\cdot \diamond \cdot$, we deduce that $w \circ \tau''(p) = \tau(f)$. So, we go by cases on b. If it is u, the body of the function is unprivileged, and this shows $w \circ \tau''(p)$, analogously, if it is k, we observe that, this program is in Cmd and does not have any syscall \cdot (\cdot) instruction inside. This shows $k_s(\tau(f))$, as required

- CASE [[ASC](#page-46-4)]. We first apply the IH, which shows that the configuration reached after n steps enjoys $\sigma \vdash \mathsf{swf}_{w}(\cdot),$ namely:

$$
\sigma \vdash \mathsf{swf}_{w}((\langle \mathsf{syscall} \; \mathsf{s}(\mathtt{E}_1, \ldots, \mathtt{E}_k); \mathtt{Q}, \rho, \mathtt{u} \rangle : F, \mu' w \diamond \tau, b_{ms}) : S'')
$$

form this observation, we deduce that

$$
\mathtt{u}(\langle \mathtt{syscall}~ \mathtt{s}(\mathtt{E}_1, \ldots, \mathtt{E}_k) ; \mathtt{Q}, \rho, \mathtt{u} \rangle : F)
$$

must hold. The claim comes from introspection of the rule, and from the definition of γ .

 \Box

Remark 13. For every system $\sigma = (\tau, \gamma, \xi)$, natural number n, layout w, and every configuration $(\langle A, \rho, u \rangle, w \diamond \tau, \epsilon, \epsilon)$ where A is unprivileged, and stack of directives D and stack of observations O, if

$$
w \vdash_\sigma (\langle \mathtt{A}, \rho, \mathtt{u} \rangle, w \diamond \tau, \epsilon, \epsilon) \multimap^n (S, F, D, O)
$$

then there is $n' \leq n$ and a configuration $(\langle P', \rho', u \rangle, w \diamond \tau', \bot)$ with $u(P')$, a sequence of directives D' and a sequence of observations O′ such that

$$
w \vdash_\sigma (\langle \mathtt{P}', \rho', \mathtt{u} \rangle, w \diamond \tau', \bot) \xrightarrow[D']{}^{n'} S.
$$

Proof. The proof goes by induction on n .

- Case 0. Follows from vacuity of the premise.
- CASE $n + 1$. The premise is:

$$
w \vdash_{\sigma} (\langle A, \rho, u \rangle, w \diamond \tau, \epsilon, \epsilon) \rightarrow^{n} D \rightarrow (S, F, D, O)
$$

We go by cases on the rule that has been applied to show the last transition.

- Case [[Spec-Init](#page-44-7)]. We observe that

$$
D = (\langle \text{spec on P''}; \mathbf{Q}, \rho'', b \rangle, w \diamond \tau'')
$$

and the claim follows by introspection of the rule. $u(P'')$ comes from the definition of the language and, in particular, $b = u$ comes from Remark [11:](#page-57-0) it cannot be that $b = k_s$ because, otherwise, we could not have spec on P'; Q as command.

- Case [[Spec-S](#page-44-9)]. The IH provides

$$
w \vdash_\sigma (\langle \mathtt{P}', \rho', \mathtt{u} \rangle, w \diamond \tau', \bot) \xrightarrow[D']{}^{n'} S.
$$

from the premise of the rule, we conclude

$$
w \vdash_{\sigma} S \xrightarrow[\text{st}]{} S'
$$

and this concludes the proof. The other cases are analogous.

Remark 14. If

$$
w \vdash_\sigma C \xrightarrow{O}^n S
$$

and $S = D : S'$ and S' not empty, then there are $n' \leq n, D', O'$ such that:

$$
w \vdash_{\sigma} C \xrightarrow{O'} n' S'
$$

Proof. By induction on S and then on n .

- CASE ϵ . Absurd.

- CASE $D : S'$. The IH tells that for every m, there are $m' \leq m, D', O'$ such that:

$$
w \vdash_{\sigma} C \xrightarrow{O'} m' S'
$$
 (IHS)

we go by induction on n .

- CASE 0. From the premise we can deduce $\epsilon = S'$, which is absurd.
- CASE $n + 1$. We go by cases on the directive used for the last step:
- Case st. The claim is a consequence of the IH on n.
- CASE ld *i*, br *b*. The witness we need to introduce is *n* step transition $w \vdash_{\sigma} C \xrightarrow{O} n D : S'.$
- Case bt. We go by cases on the rule that has been applied. It must be one of $[BT_T], [BT_T]$. We will just show the result for the case of ordinary configurations. The proof with error configurations is analogous.
	- CASE [BT⊤]. In this case, we go by cases on the $n + 1$ -th target stack. It cannot be empty. If it has one element, the claim holds for vacuity of the premise, if it has more than one element, then we can apply the IH on S.
	- CASE [BT_\perp]. The claim holds for vacuity of the premise: the $n + 1$ -th target stack has just one element.

 \Box

Remark 15. For every n, initial configuration $C = (\langle P, \rho, u \rangle, m, \perp),$ if:

$$
w \vdash_{\sigma} C \xrightarrow{O} {n \choose D} \, n \, D,
$$

and D has a mis-speculation flag (D \neq unsafe) then the mis-speculation-flag of D must be \perp .

Proof. The proof is by induction, and the base case is trivial. In the inductive case, we go by cases on the directive of the last transition:

- Case st. By introspection of this fragment of the semantics, we deduce that the number of stacks in the *n*-th and in the $n+1$ -th target configurations is the same, so in particular the *n*-th target stack must have one entry only. For this reason we can apply the IH and deduce that the mis-speculation flag of the n-th target configuration \perp . Then we observe that for all these rules, the flag is always copied from the source configuration to the target one, so we conclude.

口

- CASE Id i , br b. For all the rules that match these directives, the claim hold for vacuity of the premise: the $n + 1$ -th target configuration stack has height greater than 1. The only exception is [[SLoad-Error](#page-42-10)]. In this case, the proof is analogous to the case of the same but with st directive, which has already taken in account in the previous step.
- CASE bt. We go by cases on the rule that has been applied. It must be one of $[BT_T], [BT_⊥].$ We will just show the result for the ordinary configurations, the case for errors is analogous.
	- Case [[Bt](#page-43-4)⊥]. In this case, the claim follows directly from the definition of the rule.
	- CASE [BT⊤]. Call S_n the n-th target configuration stack. Observe that its height cannot be neither 0 nor 1. In the first case there would be no next transition, in the other case, we would get for the IH that its mis-speculation flag is unset, which is in contradiction with the assumption on the applied rule. Observe that if its height is greater than 2, then the height of the $n + 1$ -th target stack is greater than 1, so the claim holds for vacuity of the premise. Finally, if its height is exactly 2, then it must be in the shape $D_n : D'_n$. From Remark [14,](#page-59-0) we deduce that there is a sequence of transitions from C to D'_n whose length is $n' \leq n$. By applying the IH on this sequence, we can show that D'_n has mis-speculation flag unset. We conclude observing that the $n+1$ -th target configuration stack is exactly D'_n .

Lemma 13. For every n initial configuration C , if:

$$
w \vdash_\sigma C \xrightarrow{O} {^n} D : S
$$

and the mis-speculation flag of D is \perp , then there are \overline{O} and $n' \leq n$ such that :

$$
w \vdash_\sigma C \xrightarrow[\text{st}^{n'}]{}^{n'} D
$$

Proof. The proof is by induction on n. The base case is trivial. For the inductive case, we go by cases on the directive of the $n + 1$ -th transition. The premise tells us that:

$$
w \vdash_{\sigma} C \xrightarrow{O} {n \choose D} : S \xrightarrow{o} D' : S'
$$

and we know that the mis-speculation flag of D' is \bot . We must show that there are \overline{O}' and $n'' \leq n+1$ such that :

$$
w \vdash_{\sigma} D \xrightarrow{\overline{O}}^{n''} D'
$$

- CASE st. Observe that the mis-speculation flag of D must be \perp , because no rules for the directive st changes it. For this reason we can apply the IH. This shows that:

$$
w \vdash_{\sigma} C \xrightarrow{\overline{O}}^{n'} D
$$

We examine all the rules matching the transition

$$
w \vdash_\sigma D : S \xrightarrow[d]{o} D' : S'
$$

and we observe that the premises these rules do not depend on S , but they depend on D only, so if one of these rules is applied to show the transition above, it can be applied only on the transition of the claim. By introspection of all these rules, we observe that the configuration they produce is exactly D'' .

口

- CASE Id i. There are two rules that match this directive and our premises, namely [SLOAD-ERROR] and $[SLOAD]$. We show just the case of the second one. The first one can be reduced for the same rule with the st directive. If this rule is applied, we can rewrite

$$
w \vdash_{\sigma} D : S \xrightarrow[d]{o} D' : S'
$$

as follows

$$
w \vdash_{\sigma} (\langle x :=_{\ell} * \mathbf{E}; P, \rho, b \rangle : F, \mu m, b_{ms}) : S \xrightarrow{\text{mem } p} \langle \langle P, \rho [x \leftarrow v], b \rangle : F, \mu m, b_{ms} \vee b' \rangle : \langle \langle x :=_{\ell} * \mathbf{E}; P, \rho, b \rangle : F, \mu m, b_{ms} \rangle : S \rangle
$$
\n
$$
(\langle x :_{\ell} * \mathbf{E}; P, \rho, b \rangle : F, \mu m, b_{ms} \rangle : S \rangle) \leq \langle \langle x :_{\ell} * \mathbf{E}; P, \rho, b \rangle : F, \mu m, b_{ms} \rangle : S \rangle
$$

From the premises of the rule, we deduce:

- $\llbracket \texttt{E} \rrbracket^{\textsf{Addr}}_{\rho,w} = p$
- $\ (\mu m)^i(p) = v, b'$
- $p \in \underline{w}(\text{Arrld}_b)$
- $b = k_{s} \Rightarrow p \in \underline{w}(\xi(s))$

In particular, from the main premise of the claim, we deduce that b' cannot be ⊤. This means that $(\mu m)^i(p) = v, \perp$. Our goal is to show

$$
w \vdash_{\sigma} (\langle x \ :=_{\ell} \ast \mathsf{E}; \mathsf{P}, \rho, b \rangle : F, \mu m, b_{ms}) \xrightarrow[\text{st}]{\text{mem } p} (\langle \mathsf{P}, \rho[x \leftarrow v], b \rangle : F, \mu m, b_{ms} \vee b')
$$

To do so, we can observe that, if we show that $(\mu m)^0(p) = v, \perp$, then premises of the rule [[SLoad-Step](#page-42-4)] are matched, and thus the proof is concluded. This is a consequence of Remark [5.](#page-43-5) - CASE br b. Analogous to the case above.

- Case bt. If the rule which has been applied is $[B_T_{\perp}]$, the claim is a direct consequence of the IH. Otherwise, the rule applied is $[BT_T]$. We go by cases on the height of D : S. If it is 0, we reached a contradiction, if its height is 1, then the topmost configuration must have mis-speculation flag unset for Remark [15,](#page-59-1) ad this contradicts the assumption on the applied rule, which requires it to be set to ⊤. If the height is greater, we deduce that $D : S = D : D' : S$ and that the mis-speculation flag of D' is \perp by introspection of the rule and by the main assumption of this claim. We apply Remark [14](#page-59-0) on the *n*-step reduction from C to D : D' : S in order to show that there are $n' \leq n$ and a n'-long reduction from C to $D' : S'$. For the IH, there is a $n'' \leq n'$ step reduction from C to D' which employs only the directive st. Which is our claim.

Lemma 14. For every system $\sigma = (\tau, \gamma, \xi)$, speculative configuration $C = (\langle P, \rho, b \rangle, m, \bot)$ non-empty speculative stack S , sequence of directives D and sequence of observations O , if:

 \Box

$$
w \vdash_\sigma C \xrightarrow{O}^n S
$$

then there are $n' \leq n$, D', O' such that

$$
w \vdash_{\sigma} C \xrightarrow{O'} n' S.
$$

and D' does not contain any bt directive.

Proof. By induction on n . - Case 0. Trivial.

- CASE $n + 1$. The premise tells

$$
w \vdash_{\sigma} C \xrightarrow{O} \frac{n}{D} S' \xrightarrow{o} S
$$

The IH shows that there are $n' \leq n$, D' without bt directives and O' such that:

$$
w \vdash_{\sigma} C \xrightarrow{O'} n' S'.
$$

We are required to show that if

$$
w \vdash_{\sigma} S' \xrightarrow{o} S, \tag{\dagger}
$$

then there is $n'' \leq n+1$, D'' and O' such that

$$
w \vdash_{\sigma} C \xrightarrow{O''} {}^{n''}S'.
$$

where in particular D'' does not contain bt directives. We go by cases on the directive d that is used in (†).

- CASE $d \neq$ bt. In these cases, the claim holds if we take $D'' = D' : d, O'' = O' : o$ and $n'' = n' + 1$.
- CASE $d = \mathsf{bt}$. The applied rule can either be $[\mathsf{BT}_{\mathsf{T}}]$, or $[\mathsf{BT}_{\mathsf{T}}]$. We just take in exam the case of ordinary configurations:
	- $-$ CASE [BT⊤]. In this case, we conclude that $S' = D : S''$ by introspection of the rule, we deduce that the mis-speculation flag of the topmost configuration of S' is \top , so we apply Remark [15](#page-59-1) to deduce that $S'' \neq \epsilon$ (otherwise we could not have the flag set to ⊤). Thanks to this observation, we can use Remark [14](#page-59-0) to show that there is a sequence of transitions from S to S'' whose length is $n' \leq n$. The conclusion is a consequence of the application of the IH on this intermediate result. This concludes the sub-derivation.
	- CASE [BT⊥]. In this case, we use Lemma [13](#page-60-0) to show that there is a sequence of transitions from C to C containing only the directive st , which is stronger than the claim we need.

□

For sake of simplicity, we define the relation \precsim as follows:

$$
\frac{\tau \sim_{\mathsf{Id}_{\mathsf{u}} \cup \mathsf{Arrld}_k \tau' \quad \forall \mathtt{f} \in \mathsf{FunId}_k . \tau'(\mathtt{f}) = \eta(\tau(\mathtt{f}))}{\tau \precsim \tau'}
$$
\n
$$
\frac{F \precsim F' \quad \mathsf{P}' = \eta(\mathsf{P})}{\langle \mathsf{P}, \rho, \mathsf{k}_\mathsf{s} \rangle : F \precsim \langle \mathsf{P}', \rho, \mathsf{k}_\mathsf{s} \rangle : F'} \quad \frac{F \precsim F'}{\langle \mathsf{P}, \rho, \mathsf{u} \rangle : F \precsim \langle \mathsf{P}, \rho, \mathsf{u} \rangle : F'}{\text{err} \precsim \text{err} \precsim \text{ern} \quad \frac{\tau \precsim \tau' \quad F \precsim F'}{\langle F, w \diamond \tau \rangle \precsim (F', w \diamond \tau)}
$$

Lemma 15. For every system σ , configurations C and D such that $C \precsim D$, if

$$
\sigma \vdash_w C \to C',
$$

then

$$
\eta(\sigma) \vdash_w D \to^* D',
$$

for some D' such that $C' \precsim D'$.

Proof. The proof goes first by cases on C to refuse the cases where it is err or unsafe. After that we can assume that $C = (\langle P, \rho, b \rangle : F, w \diamond \tau)$, and we go by cases on b.

- Case u. We can assume that

$$
C = (\langle P, \rho, u \rangle : F, w \diamond \tau)
$$

and

$$
D = (\langle P, \rho, u \rangle : F', w \diamond \tau').
$$

with $F \precsim F'$ and $\tau \precsim \tau'$. The proof goes by cases on the rule that has been applied to P - Case [[Op](#page-7-9)]. The assumption is

$$
\sigma \vdash_w (\langle x := \mathtt{E}; \mathtt{Q}, \rho, \mathtt{u} \rangle : F, w \diamond \tau) \rightarrow (\langle \mathtt{Q}, \rho[x \leftarrow \llbracket \mathtt{E} \rrbracket_{\rho, w}], \mathtt{u} \rangle : F, w \diamond \tau),
$$

and by applying the same rule to D , we obtain

$$
\eta(\sigma) \vdash_w (\langle x := \mathtt{E}; \mathtt{Q}, \rho, \mathtt{u} \rangle : F', w \diamond \tau') \to (\langle \mathtt{Q}, \rho[x \leftarrow \llbracket \mathtt{E} \rrbracket_{\rho, w}], \mathtt{u} \rangle : F', w \diamond \tau')
$$

and this shows the claim.

- Case [[Skip](#page-7-10)]. Analogous to the previous one.
- Case [[Fence](#page-54-3)]. Analogous to the case of assignments.
- Case [[Pop](#page-7-6)]. Analogous to the case of assignments.
- Case [[If](#page-7-11)]. Analogous to the case of assignments.
- Case [[While](#page-7-12)]. Analogous to the case of assignments.
- Case [[Store](#page-7-7)]. The assumption is

$$
\sigma \vdash_w (\langle *E := F; \mathbf{Q}, \rho, \mathbf{u} \rangle : F, w \diamond \tau) \to (\langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F, w \diamond \tau[p \leftarrow v]),
$$

where $v = \llbracket \mathbf{F} \rrbracket_{\rho,w}$ and $p = \llbracket \mathbf{E} \rrbracket_{\rho,w}^{\mathsf{Addr}}$. Observe that $p \in \underline{w}(\mathsf{Arrld}_{u})$. Which means that there is a pair (a, i) such that $w(a) + i = p$ and $a \in \text{Arrld}_u$. So, in particular, we have that $w \circ \tau[p \leftarrow v] =$ $w \diamond \tau[(a, i) \leftarrow v]$ because of Remark [3.](#page-40-1) We also deduce that by applying the same rule to D, we obtain

$$
\sigma \vdash_w (\langle *E := F; \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w \diamond \tau') \to (\langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w \diamond \tau'[(\mathbf{a}, i) \leftarrow v]),
$$

and to show the claim, we just need to observe $\tau[(a, i) \leftarrow v] \precsim \tau'[(a, i) \leftarrow v]$, which is a consequence of the assumption $a \in ArrId_u$.

- Case [[Load](#page-7-1)]. Analogous to the previous case
- Case [[Call](#page-7-4)]. The assumption is

$$
\sigma \vdash_w (\langle \text{call } E(\mathtt{F}_1, \ldots, \mathtt{F}_k) ; \mathtt{Q}, \rho, \mathtt{u} \rangle : F, w \diamond \tau) \rightarrow (\langle w \diamond \tau([\![\mathtt{E}]\!]_{\rho, w}), \rho_0', \mathtt{u} \rangle : (\langle \mathtt{Q}, \rho, \mathtt{u} \rangle : F, w \diamond \tau)),
$$

where ρ_0' is a shorthand for

$$
\rho_0[x_1,\ldots,x_k \leftarrow [\![\mathtt{F}_1]\!]_{\rho,w},\ldots,[\![\mathtt{F}_1]\!]_{\rho,w}]
$$

and from the premise of the rule, we obtain that there is $f \in \text{Fund}_u$ such that $[\mathbb{E}]_{\rho,w} = w(f)$. Thus, from the definition of $w \circ \tau$, we deduce that $w \circ \tau = \tau(f) = \tau'(f)$ for the definition of the \lesssim relation. Thanks to these observations, we can show that the application of the same rule to D gives rule to D , we obtain

$$
\eta(\sigma) \vdash_w (\langle \text{call } E(F_1, \ldots, F_k); \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w \diamond \tau') \rightarrow (\langle w \diamond \tau([\![\mathbf{E}]\!]_{\rho, w}), \rho_0', \mathbf{u} \rangle : (\langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w \diamond \tau')),
$$

and this shows the claim.

- Case [[SC](#page-7-5)]. The assumption is

$$
\sigma \vdash_w (\langle \texttt{syscall s}(F_1, \ldots, F_k); \texttt{Q}, \rho, u \rangle : F, w \diamond \tau) \rightarrow (\langle \gamma(s), \rho_0', k_s \rangle : (\langle \texttt{Q}, \rho, u \rangle : F, w \diamond \tau)),
$$

where ρ_0' is a shorthand for

$$
\rho_0[x_1,\ldots,x_k \leftarrow [\![\mathbf{F}_1]\!]_{\rho,w},\ldots,[\![\mathbf{F}_1]\!]_{\rho,w}]
$$

By applying the same rule to the configuration D , we obtain

 $\eta(\sigma) \vdash_w (\langle \texttt{syscall s}(F_1, \ldots, F_k); \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w \diamond \tau') \rightarrow (\langle \eta(\gamma)(\texttt{s}), \rho'_0, \texttt{k}_\texttt{s} \rangle : (\langle \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w \diamond \tau')),$

to conclude, we just need to observe that

$$
\langle \gamma(s), \rho_0', k_s \rangle \precsim \langle \eta(\gamma)(s), \rho_0', k_s \rangle.
$$

- Case [[Store-Error](#page-7-8)]. The assumption is

$$
\sigma \vdash_w (\langle *E := \texttt{F}; \texttt{Q}, \rho, \texttt{u} \rangle : F, w \diamond \tau) \to \textsf{err},
$$

We call $p = \llbracket \mathbf{E} \rrbracket_{\rho,w}^{\mathsf{Addr}}$, and from the premises of the rule, we deduce that $p \notin \underline{w}(\mathsf{Arrld}_{u})$. This suffices to show

$$
\sigma \vdash_w (\langle *E := F; \mathbf{Q}, \rho, \mathbf{u} \rangle : F', w \diamond \tau') \to \text{err}
$$

and to show the claim.

- CASE k_s . Under this assumption, most of the cases are analogous to the corresponding ones for user-mode execution. Even in this case, we go by induction on the rules. We just show some among the most important cases:

- Case [[Op](#page-7-9)]. The assumption is

$$
\sigma \vdash_w (\langle x := \mathbf{E}; \mathbf{Q}, \rho, \mathbf{k}_s \rangle : F, w \diamond \tau) \rightarrow (\langle \mathbf{Q}, \rho[x \leftarrow [\![\mathbf{E}]\!]_{\rho,w}], \mathbf{k}_s \rangle : F, w \diamond \tau),
$$

from the assumption D , we deduce that is

$$
(\langle x := \mathsf{E}; \eta(\mathsf{Q}), \rho, \mathsf{k}_s \rangle : F', w \diamond \tau')
$$

so the same rule can be applied on D to show:

$$
\eta(\sigma) \vdash_w (\langle x := \mathtt{E}; \mathtt{Q}, \rho, \mathtt{k_s} \rangle : F', w \diamond \tau') \rightarrow (\langle \eta(\mathtt{Q}), \rho[x \leftarrow [\![\mathtt{E}]\!]_{\rho, w}], \mathtt{k_s} \rangle : F', w \diamond \tau')
$$

and the claim comes from the observation that the command of the target configuration is exactly $\eta(\mathsf{Q})$.

- Case [[Call](#page-7-4)]. The assumption is

$$
\sigma \vdash_w (\langle \text{call } E(F_1, \ldots, F_k); \mathbf{Q}, \rho, k_s \rangle : F, w \diamond \tau) \rightarrow (\langle w \diamond \tau([\![\mathbf{E}]\!]_{\rho, w}), \rho_0', k_s \rangle : (\langle \mathbf{Q}, \rho, k_s \rangle : F, w \diamond \tau)),
$$

where ρ_0' is a shorthand for

$$
\rho_0[x_1,\ldots,x_k \leftarrow [\![\mathbf{F}_1]\!]_{\rho,w},\ldots,[\![\mathbf{F}_1]\!]_{\rho,w}]
$$

and from the premise of the rule, we obtain that there is $f \in \text{Fund}_k$ such that $\mathbb{E}\|_{o,w} = w(f)$. Thus, from the definition of $w \diamond \tau$, we deduce that $w \diamond \tau = \tau(f)$. We observe that D is:

$$
(\langle \text{fence}; \text{call } E(F_1, \ldots, F_k); \eta(\textbf{Q}), \rho, k_s \rangle : F', w \diamond \tau')
$$

Thanks to these observations, we can show that the application of the [[Fence](#page-54-3)] rule and of the [CALL] rule to D show:

$$
\begin{aligned} \eta(\sigma) \vdash_w (\langle \text{call } E(F_1, \ldots, F_k); \mathbf{Q}, \rho, \mathbf{k}_s \rangle : F', w \diamond \tau') \rightarrow^2 \\ & (\langle w \diamond \tau'([\![\mathbf{E}]\!]_{\rho, w}), \rho_0', \mathbf{k}_s \rangle : (\langle \eta(\mathbf{Q}), \rho, \mathbf{k}_s \rangle : F', w \diamond \tau')), \end{aligned}
$$

To conclude, we must observe that $w \circ \tau'([\![\mathbf{E}]\!]_{\rho,w}) = \eta(\tau(\mathbf{f})).$ This is a consequence of the assumptions $[\![\mathbf{E}]\!]_{\rho,w} = w(f), \; f \in \mathsf{FunId}_{\mathbf{k}} \text{ and } \tau \precsim \tau'.$

Lemma 16. For every stack of speculative configurations S layout w, system $\sigma \in \text{im}(\eta)$ such that $\sigma \vdash \text{\rm twf}_{w,s}(S)$, bt-free sequence of directives $d: D$, sequence of observations $o: O$, and S' such that $\neg(\sigma \vdash \textsf{fwf}_{w,s}(S'))$, there is a stack S'' such that

$$
(w \vdash_{\sigma} S \xrightarrow[D:d]{O : o} {}^n S') \Rightarrow (w \vdash_{\sigma} S \xrightarrow[D]{O} {}^{n-1} S'')
$$

and $\sigma \vdash \text{\rm twf}_{w,s}(S'')$.

Proof. By cases on n.

- Case 0. Absurd.

- CASE $n + 1$. In this case, we assume that

$$
(w \vdash_{\sigma} S \xrightarrow{O : o}_{D:d} {}^{n+1}S')
$$

and $\neg(\sigma \vdash \text{fwf}_{w,s}(S'))$. We need to show that

$$
(w \vdash_{\sigma} S \xrightarrow{O} {n} S'')
$$

for some S'' such that $\sigma \vdash f w f_{w,s}(S'')$. Assume that the claim does not hold, i.e. that $\neg \sigma \vdash$ $fwf_{w,s}(S'')$. If $n=0$, that stack is exactly S, but this is absurd, so we can assume that $n>0$, however, in this case we would have a contradiction of Remark [16](#page-65-0) for the configuration that is reached after $n-1$ steps because none of the two following configuration satisfies $\sigma \vdash \text{fwf}_{w,s}(\cdot)$. \Box

Remark 16. For every stack of speculative configurations S every layout w, every system $\sigma \in \text{im}(\eta)$ such that $\sigma \vdash \text{fw}(S)$, and every system-call s, one of the three following cases holds: – w ⊢^σ S↓

$$
\neg \ \forall d \neq \text{bt}.\forall o.w \vdash_{\sigma} S \xrightarrow{o} S' \Rightarrow \sigma \vdash \text{fwf}_{w,s}(S')
$$

$$
\neg \ \forall d_1, d_2 \neq \text{bt}.\forall o_1, o_2.w \vdash_{\sigma} S \xrightarrow{o_1: o_2} {}^{2}S' \Rightarrow \sigma \vdash \text{fwf}_{w,s}(S')
$$

Proof. The proof goes by cases on the proof of the predicate σ ⊢ $fwr_{w,s}(\cdot)$. Many of the cases are trivial. The most interesting ones are when the stack of configurations is not-empty, i.e. it is like $(\langle \eta(P), \rho, k_{s} \rangle : F, \mu(w \diamond \tau'), b_{ms}) : S$. The proof goes by cases on P. Observe that from, we can avoid the case of system calls.

- CASE ϵ . Observe that if $F = \epsilon$, the first claim holds, otherwise:

$$
w \vdash_{\sigma} (\langle \eta(\epsilon), \rho, \mathbf{k}_{s} \rangle : \langle \mathbf{Q}, \rho', \mathbf{k}_{s} \rangle : F', \mu(w \diamond \tau'), b_{ms}) : S^{\circ}_{\mathsf{st}} \diamond
$$

$$
(\langle \mathbf{Q}, \rho'[ret \leftarrow \rho(ret)], \mathbf{k}_{s} \rangle : F', \mu(w \diamond \tau'), b_{ms}) : S^{\circ}
$$

and the claim is a consequence of the premise of the proof-rule for $\sigma \vdash \text{fwf}_{w,s}(\cdot)$.

- CASE $x := *F; Q$. Observe that one rule among [SLOAD-STEP], [SLOAD], [SLOAD-UNSAFE], and [[SLoad-Error](#page-42-10)] must apply. If one of the last two rules applies, the claim is trivial. Otherwise, the stack looks like:

$$
(\langle \eta(x^* := *F; \mathbf{Q}), \rho, k_s \rangle : F', \mu(w \diamond \tau'), b_{ms}) : S
$$

And if $b_{ms} = \top$, the first claim holds, because, without backtracking, this configuration cannot reduce further. So we can assume that $b_{ms} = \perp$ Otherwise, we just show the case for the [SLOAD] rule:

$$
w \vdash_{\sigma} (\langle \eta(x := *F; \mathbf{Q}), \rho, \mathbf{k}_{s} \rangle : F', \mu(w \diamond \tau'), b_{ms}) : S \xrightarrow{\text{c:mem } p} 2
$$

$$
(\langle \eta(\mathbf{Q}), \rho[x \leftarrow v], \mathbf{k}_{s} \rangle : F', \mu(w \diamond \tau'), b_{ms} \vee b') : (\langle x := *F; \eta(\mathbf{Q}), \rho, \mathbf{k}_{s} \rangle : F', \overline{\mu(w \diamond \tau')}, b_{ms}) : S
$$

where $p = \mathbb{F}_{\rho,w}^{\text{Addr}}$, $v = (\mu(w \diamond \tau'))^i(p)$. Observe that in particular, the fence instruction that precedes the assignment has flushed the memory. For this reason, in order to show the claim, we just need to verify that:

$$
\sigma \vdash \texttt{fwf}_{w,\texttt{s}}((\langle \eta(\texttt{Q}), \rho, \texttt{k}_\texttt{s} \rangle : F', \overline{\mu(w \diamond \tau')}, b_{ms} \vee b'))
$$

which is almost entirely consequence of the premise of the proof-rule for $\sigma \vdash \text{fwf}_{w,s}(\cdot)$. In particular, since the domain of μ does not contain any function address, the result is a consequence of Remark [7,](#page-46-6) which ensures that the resulting memory is $w \diamond \tau''$ and $\tau'' \sim_{\text{Fund}} \tau' \sim_{\text{Fund}} \tau$.

- CASE $*E := F$; Q. Observe that one rule among [SSTORE],

[[SStore-Unsafe](#page-42-2)], and [[SStore-Error](#page-42-11)] must apply. If one of the last two rules applies, the claim is trivial. Otherwise, the stack looks like:

$$
(\langle \eta(*\mathtt{E}:=\mathtt{F};\mathtt{Q}),\rho,\mathtt{k}_\mathtt{s}\rangle:F',\mu(w\diamond\tau'),b_{ms}):S
$$

We just show the case for the [SSTORE] rule:

$$
w \vdash_{\sigma} (\langle \eta (* \mathbf{E} := \mathbf{F}; \mathbf{Q}), \rho, \mathbf{k}_{s} \rangle : F', \mu(w \diamond \tau'), b_{ms}) : S \xrightarrow{\text{c:mem } p} \text{S} \xrightarrow{\text{c:form } p} (\langle \eta(\mathbf{Q}), \rho, \mathbf{k}_{s} \rangle : F', [p \mapsto v] \overline{\mu(w \diamond \tau')}, b_{ms} \vee b') : S
$$

where $p = \llbracket \mathbf{F} \rrbracket_{\rho,w}^{\mathsf{Addr}}, v = \llbracket \mathbf{F} \rrbracket_{\rho,w}.$ Observe that the claim requires to verify just that

$$
\sigma \vdash \texttt{fwf}_{w,s}((\langle \eta(\mathtt{Q}), \rho, \mathtt{k}_s \rangle : F', [p \mapsto v] \overline{\mu(w \diamond \tau')}, b_{ms} \vee b'))
$$

which is almost completely a consequence of the premise of the proof-rule for $\sigma \vdash \text{fwf}_{w,s}(\cdot)$. In particular, as in the case above, we observe that we just need to observe that $\overline{\mu(w \diamond \tau')}$ is such that $\sigma \vdash \textsf{fwf}_{w,s}(\overline{\mu(w \diamond \tau')})$ and from the premise of the rule [SSTORE], we deduce that $p \in \textsf{Arrld}_k$, that shows that the new buffer satisfies the desired conditions.

- CASE call $E(F_1, \ldots, F_k)$; Q. Observe that either [SCALL], [SCALL-UNSAFE], or [SCALL-ERROR] must apply. If one of the last two rules applies, the claim is trivial. Otherwise, The proof proceeds as in the previous cases, but the important observation is that:

$$
w \vdash_{\sigma} (\langle \eta(*\mathbf{E} := \mathbf{F}; \mathbf{Q}), \rho, \mathbf{k}_{s} \rangle : F', \mu(w \diamond \tau'), b_{ms}) : S \xrightarrow{\text{c:mem } p} \frac{\langle \mathbf{F} \rangle}{\text{st:st}} \times \frac{\langle \mathbf{F} \rangle}{\langle \mu(w \diamond \tau') \rangle} \times \frac{\langle \mathbf{F} \rangle}{\langle \mu(w \diamond
$$

where $p = \llbracket \mathbf{F} \rrbracket_{\rho,w}^{\mathsf{Addr}}, v = \llbracket \mathbf{F} \rrbracket_{\rho,w}.$ And we must ensure that the loaded program (namely $\overline{\mu(w \diamond \tau')}(p)$) is equal to $\eta(\overline{P}')$ for some command. From the premise of the rule [SCALL] that has been applied, we deduce that $p \in \underline{w}(\text{Fund}_k)$ means that there is a function in Fund_k such that $w(f) = p$. From Remark [7,](#page-46-6) we deduce that $\overline{\mu(w \diamond \tau')} = w \diamond \tau''$ for some $\tau'' \sim_{\text{Fund}} \tau' \sim_{\text{Fund}} \tau$. By definition of $\cdot \diamond \cdot$, this also means that $\overline{w \diamond \tau''}(p) = \tau(p)$ that satisfies the requirement by hypothesis on σ . \Box

Lemma 17. For every pair of configurations

$$
C = \left(\langle \mathbf{P}_1, \rho_1, \mathbf{k}_\mathrm{s} \rangle : F_1, \mu_1 m_1, b_{ms1} \right) :
$$

and

$$
D = (\langle P_2, \rho_2, \mathbf{k}_s \rangle : F_2, \mu_2 m_2, b_{ms2}),
$$

and stack if

$$
w \vdash_\sigma (\langle \mathtt{P}_1, \rho_1, \mathtt{k} \rangle [\mathtt{s}] : F_1, \mu_1 m_1, b_{ms1}) \xrightarrow[\mathtt{st}]{o} (\langle \mathtt{P}_2, \rho_2, \mathtt{k} \rangle [\mathtt{s}] : F_2, \mu_2 m_2, b_{ms2})
$$

for some observation o, then

$$
w \vdash_{\sigma} (\langle P_1, \rho_1, \mathbf{k} \rangle [s] : F_1), \overline{\mu_1 m_1} \to (\langle P_2, \rho_2, \mathbf{k} \rangle [s] : F_2), \overline{\mu_2 m_2}
$$

Proof. The proof goes by cases on the transition relation. Most of the cases are trivial. The most interesting ones are those which interact with memory.

- Case [[AFence](#page-45-3)]. We rewrite the assumption as follows:

$$
w \vdash_\sigma (\langle \texttt{fence}; \texttt{P}, \rho_1, \texttt{k}_\texttt{s} \rangle : F_1, \mu_1 m_1, b_{ms1}) \xrightarrow[\texttt{st}]{o} (\langle \texttt{P}, \rho_1, \texttt{k}_\texttt{s} \rangle : F_1, \overline{\mu_1 m_1}, b_{ms1})
$$

The claim is

$$
w \vdash_{\sigma} (\langle \text{fence}; \text{P}, \rho_1, \text{k}\rangle[\text{s}] : F_1), \overline{\mu_1 m_1} \to (\langle \text{P}_1, \rho_1, \text{k}\rangle[\text{s}] : F_1), \overline{\mu_1 m_1}
$$

that is trivial.

- Case [[AStore](#page-45-4)]. We rewrite the assumption as follows:

$$
w \vdash_\sigma (\langle \ast \mathbf{E}:=\mathbf{F};\mathbf{P},\rho_1,\mathbf{k}\rangle[\mathbf{s}]:F_1,\mu_1m_1,b_{ms1}) \xrightarrow[\mathbf{st}]{o} (\langle \mathbf{P},\rho_1,\mathbf{k}\rangle[\mathbf{s}]:F_1,[p \mapsto v]:\mu_1m_1,b_{ms1}).
$$

Where $p = \llbracket \mathbf{E} \rrbracket_{\rho_1,w}^{\text{Addr}}$ and $v = \llbracket \mathbf{F} \rrbracket_{\rho_1,w}$. To show the claim is suffices to observe that

$$
w \vdash_\sigma (\langle \ast \mathbf{E}:=\mathbf{F};\mathbf{P},\rho_1,\mathbf{k}\rangle[\mathbf{s}]:F_1),\overline{\mu_1m_1}\to (\langle \mathbf{P}_1,\rho_1,\mathbf{k}\rangle[\mathbf{s}]:F_1,\overline{\mu_1m_1}[p\leftarrow v])
$$

and that $[p \mapsto v] : \mu_1 m_1 = \overline{\mu_1 m_1} [p \leftarrow v]$ that is a consequence of the definition of \cdot . - CASE [ALOAD]. We rewrite the assumption as follows:

$$
w \vdash_\sigma (\langle x \; := \; \ast \mathbf{E}; \mathbf{P}, \rho_1, \mathbf{k} \rangle [\mathbf{s}] : F_1, \mu_1 m_1, b_{ms1}) \xrightarrow[\mathbf{st}]{} (\langle \mathbf{P}, \rho_1[x \leftarrow v], \mathbf{k} \rangle [\mathbf{s}] : F_1, \mu_1 m_1, b_{ms1}).
$$

Where $v = (\mu_1 m_1)^0([\mathbb{E}]\substack{\text{Addr}}_{\rho_1,w})$. To show the claim is suffices to apply Remark [6.](#page-44-6)