# Multimodal Table Understanding

Mingyu Zheng<sup>1,2\*†</sup>, Xinwei Feng<sup>3\*</sup>, Qingyi Si<sup>1,2\*</sup>, Qiaoqiao She<sup>3</sup>, Zheng Lin<sup>1,2‡</sup>, Wenbin Jiang<sup>4</sup>, Weiping Wang<sup>1</sup>

<sup>1</sup>Institute of Information Engineering, Chinese Academy of Sciences, Beijing, China <sup>2</sup>School of Cyber Security, University of Chinese Academy of Sciences, Beijing, China

<sup>3</sup>Baidu Inc, Beijing, China

<sup>4</sup>School of Artificial Intelligence, Beijing Normal University, Beijing, China

{zhengmingyu, siqingyi, linzheng, wangweiping}@iie.ac.cn

{fengxinwei, sheqiaoqiao}@baidu.com

{jiangwenbin}@bnu.edu.cn

# Abstract

Although great progress has been made by previous table understanding methods including recent approaches based on large language models (LLMs), they rely heavily on the premise that given tables must be converted into a certain text sequence (such as Markdown or HTML) to serve as model input. However, it is difficult to access such high-quality textual table representations in some real-world scenarios, and table images are much more accessible. Therefore, how to directly understand tables using intuitive visual information is a crucial and urgent challenge for developing more practical applications. In this paper, we propose a new problem, multimodal table understanding, where the model needs to generate correct responses to various tablerelated requests based on the given table image. To facilitate both the model training and evaluation, we construct a large-scale dataset named MMTab, which covers a wide spectrum of table images, instructions and tasks. On this basis, we develop Table-LLaVA, a generalist tabular multimodal large language model (MLLM), which significantly outperforms recent open-source MLLM baselines on 23 benchmarks under held-in and held-out settings. The code and data is available at https: //github.com/SpursGoZmy/Table-LLaVA.

#### 1 Introduction

Tables are widely used to store and present data across various fields, e.g., financial analysis, scientific research and government reports (Lautert et al., 2013; Shigarov, 2023). To make the most of the abundant tabular data, the table understanding (TU) technique has been proposed to automatically understand tables and perform table-based tasks, such as question answering (Pasupat and Liang,




Figure 1: An overall performance comparison of Table-LLaVA 7B and existing MLLMs on various multimodal table understanding benchmarks. Table-LLaVA outperforms recent open-source MLLMs and is even competitive with the powerful GPT-4V on most tasks.

2015) and text generation (Parikh et al., 2020). As a technique that could significantly elevate work efficiency in different industries, it has attracted ever-increasing research interest in recent years.

Though considerable efforts have been dedicated to the table understanding problem (Herzig et al., 2020; Liu et al., 2022), most previous models can only fulfill very limited tasks until the emergence of large language models (LLMs) (Brown et al., 2020; Chowdhery et al., 2022). With the help of powerful LLMs, we are getting closer to the vision that a versatile model can perform a variety of table-based tasks. However, existing table-oriented LLMs (Zhang et al., 2023b; Li et al., 2023c; Zha et al., 2023) rely heavily on the prerequisite that all given tables must be converted into a certain text sequence (like Markdown or HTML) to be input to LLMs. Under some practical scenarios like scanned documents and webpage screenshots, it

<sup>\*</sup> Indicates equal contribution.

<sup>&</sup>lt;sup>†</sup>This work was done during an internship at Baidu Inc.

<sup>&</sup>lt;sup>‡</sup> Corresponding author: Zheng Lin.

is difficult to obtain such high-quality textual table representations, and yet table images are more accessible. Moreover, humans can directly understand two-dimensional tables using the intuitive visual information, whereas LLMs can only interpret tables in a one-directional textual perspective, which may increase the difficulty of comprehending diverse table structures and colored table elements. In summary, for the sake of convenience and intuitiveness, it is a crucial and urgent challenge to explore how to directly digest tables using visual information.

To promote the advancement of table understanding and its real-world applications, we propose the multimodal table understanding problem, where the model is required to generate correct responses to different table-related requests (e.g., questions) in an end-to-end fashion based on the table image. Despite the fact that recent multimodal large language models (MLLMs) have demonstrated excellent capabilities in many multimodal tasks, they cannot be directly extended to the proposed task. As shown in Figure 1, the performance of popular MLLMs like MiniGPT-4 (Zhu et al., 2023) and BLIP2 (Li et al., 2023b) is close to zero on most tasks, revealing their weakness in understanding tabular data. More importantly, there is a lack of a comprehensive dataset that can support both the development and evaluation of generalist MLLMs towards multimodal table understanding.

To address the above issue, we construct **MMTab**, the first open-source large-scale dataset for multimodal table understanding problem, based on 14 publicly available table datasets of 8 domains. We carefully design scripts to convert original textual tables in these datasets into table images highlighting a broad coverage of table structures and styles, and transform all task-specific samples into multimodal instruction-tuning samples with a unified format of <table image, input request, output response>. The resulting dataset contains (1) 150K table recognition samples on 97K table images for pre-training (named MMTab-pre). (2) 232K samples of 14 table-based tasks on 82K table images for instruction tuning (named MMTabinstruct). (3) 49K test samples on 23K table images composing 17 held-in and 7 held-out benchmarks (named MMTab-eval). During the dataset construction, data augmentations at multiple levels (e.g., table-level, task-level) were adopted to further improve the data diversity, and we also introduce multimodal table structure understanding tasks that

have been overlooked in previous studies.

Based on the curated dataset, we develop a versatile tabular MLLM named **Table-LLaVA** with an enhanced two-stage training paradigm. In the first stage, we pre-train LLaVA-1.5 (Liu et al., 2023a) with an extra table recognition task on the MMTabpre, which requires the model to generate textual sequences (like HTML) given table images. This stage aligns the structures and elements within table images to textual modality and thus enhances the comprehension of the basic table structure and content. In the second stage, we continue to instructiontuning the model with diverse table-based downstream tasks on the MMTab-instruct, which endows the model with the multimodal instructionfollowing ability for table-related requests.

We compare Table-LLaVA with a series of opensource (M)LLMs and closed-source GPT-4V. Experimental results show that Table-LLaVA beats strong MLLM baselines on 17 held-in and 6 heldout benchmarks, and is even competitive with the powerful GPT-4V on 14 benchmarks with a subset of test samples. Extensive ablation experiments are conducted to reveal the contributions of different training data (e.g., the influence of table recognition pre-training data). We also explore the mutual influence between model's capacity for tabular tasks and non-tabular tasks. We hope this work could establish a strong base for future research on the multimodal table understanding problem and facilitate the progress of more general MLLMs.

We conclude our contributions as follows:

1) We make the first systematic exploration of the multimodal table understanding problem, which is complementary to the traditional text-only problem setting.

2) Accordingly, we construct and release a largescale dataset MM-Tab which covers diverse tables and data for different tasks, including a series of novel table structure understanding tasks.

3) We develop a versatile tabular MLLM Table-LLaVA, which significantly outperforms a range of strong MLLM baselines under both held-in and held-out settings (Figure 1).

# 2 Related Work

#### 2.1 Table Understanding

The table understanding (TU) problem concentrates on how to automatically extract, transform and interpret essential information from tabular data, and it has attracted significant attention in the past years (Bonfitto et al., 2021; Shigarov, 2023). Many tasks fall under the umbrella of table understanding problem, e.g., Table Question Answering (TQA) (Nan et al., 2022; Zheng et al., 2023), Table Fact Verification (TFV) (Chen et al., 2020) and Table-to-Text (T2T) generation (Cheng et al., 2022).

Different approaches have been proposed to solve specific TU tasks, ranging from early rulebased systems (Gatterbauer et al., 2007) to later tabular language models (TaLMs) (Liu et al., 2022; Chen et al., 2023a; Dong et al., 2022), which are pre-trained from general language models like BERT (Devlin et al., 2019) with extra large-scale table corpus. Nevertheless, these methods can only support limited TU tasks and handle tables of specific types. Recently, the emerging LLMs have opened up new possibilities for utilizing one single model to fulfill multiple table tasks. Researchers have attempted to enhance the TU ability of existing LLMs with different strategies such as prompt engineering (Chen, 2023; Sui et al., 2023), instruction tuning (Zhang et al., 2023b; Li et al., 2023c; Liu et al., 2023c) and combining external tools (Lu et al., 2023a; Li et al., 2023a). The resulting tabular LLMs like TableLlama (Zhang et al., 2023b) and TableGPT (Li et al., 2023c) can possess better TU ability and respond to wide-ranging table-related requests. However, previous TU approaches including tabular LLMs are unable to directly understand table images, which limits the potential application scenarios of TU technique.

#### 2.2 Multimodal Large Language Models

With LLMs experiencing rapid advancements, recent studies have tried to endow the purely texutal LLMs with understanding and perception capabilities of other modalities such as image and video, leading to the emergence of MLLMs (Alayrac et al., 2022; Li et al., 2022). Flamingo (Alayrac et al., 2022) proposes a gated cross-attention mechanism between vision encoder and LLM, which is trained on billions of image-text pairs to align vision and language modalities. BLIP2 (Li et al., 2023b) introduces a Q-Former with learnable query vectors to abstract the visual information from vision encoder into features of a fixed number. LLaVA (Liu et al., 2023b) uses a linear layer as a simpler cross-modal connector and achieve powerful performance with better data efficiency.

Though previous MLLMs demonstrated remarkable performance on multiple multimodal tasks (Liu et al., 2023d; Yu et al., 2023), their ability to digest table images and perform downstream tasks has not been thoroughly investigated. In this work, we build the first large-scale multimodal table understanding dataset and develop Table-LLaVA, a versatile tabular MLLM for diverse table-based tasks. To stimulate future endeavours on this problem, we also provide a comprehensive benchmark and fully evaluate the table understanding ability of existing models. More recently, researchers also tried to develop MLLMs like Vary (Wei et al., 2023) and Monkey (Li et al., 2023d) to understand document pictures with enhanced visual encoders, e.g., scaling up the vision vocabulary and image resolution. These models focus on the unified visual understanding of different document images and can be further improved with the proposed dataset.

#### **3** MMTab Dataset

#### 3.1 Data Collection

As shown in Table 1, with a pursuit of diverse table structures, tasks, and domains, we collect samples from 14 public table datasets of 8 domains (the first 14 rows in Table 1), covering 9 representative academic tasks. The detailed definition of each task can be found in Table 6. The original tables in these datasets are stored in divergent textual formats such as HTML or Markdown. We carefully design Python scripts with external packages like html2image to convert textual tables into highquality table images. The task-specific input and output texts are transformed into the instructionfollowing format with pre-defined instruction templates. To minimize errors during answering parsing, we also add extra instructions, requiring models to output the final answer in the JSON format. As shown in the Figure 2, the rendered table images and processed input-output pairs constitute the final multimodal instruction-tuning samples with a unified format of <table image, input request, output response>. We adhere to the original dataset partitioning and select 11 datasets for training and held-in evaluation. 3 small-scale datasets with non-overlapping domains are used for held-out evaluation. The overview of sample construction process is depicted in Figure 3.

#### 3.2 Data Augmentations

Previous works have shown that the diversity of instruction-following data is crucial to the capa-




Figure 2: MMTab contains diversified table images and instruction following data, covering a wide range of tabular tasks (see Table 1). More dataset examples are shown in Figure 5-7 in Appendix A.1.




Figure 3: The overview of sample construction process.

bility of the resulting instruction-following models (Zhou et al., 2023; Si et al., 2023; Li et al., 2023c). To create more data diversity and avoid over-fitting in the model training, we perform additional data augmentations at multiple levels.

**Table-level augmentations.** Real-world tables often have varied structures and styles. An ideal table understanding model should be able to process divergent tables like a human reader. Since our dataset already includes diverse table structures from academic datasets, we separately design scripts to render table images with three different styles: Web-page (70.8%), Excel (19.4%) and Markdown (9.8%). Fine-grained adjustments such as font type and cell colors are also considered.

**Instruction-level augmentations.** In practical scenarios, user instructions for the same task are

likely to vary from user to user. To improve models' robustness towards such variations, we resort to GPT-4 to generate new instruction templates and descriptions about JSON output format in a fewshot fashion based on several manually annotated demonstrations. Generated instruction templates with grammar mistakes or deviation from the original task are filtered out. When we construct input requests of each dataset, we randomly select an instruction template and an output format description from the candidate pool, and then combine them with the task-specific input such as table-related questions to produce the final input request. This combination strategy can bring more diversity of input requests. Using the TABMWP as an example, we show instruction templates and Python code for building input requests in Figure 8.

**Task-level augmentations.** Though the collected 14 public datasets highlight 9 academic tabular tasks (e.g., Flat TQA and Cell Description) which demand table-based reasoning capabilities, it is still a question whether existing MLLMs are truly aware of the basic table structures. Prior study has found that, despite achieving great performance on downstream tasks, tabular LLMs may still exhibit poor capacity for perceiving table structures (Sui et al., 2023). To further strengthen the fundamental table structure understanding ability of MLLMs, 6 table structure understanding tasks (the 6 rows with 'Structure Understanding' task category in Table 1) are devised, e.g., table size detection (TSD) task.

For each task, we use the above-mentioned method to generate input requests and design scripts to automatically extract the final answer from the textual tables in collected datasets. Finally, 8K training samples, 1K or 1.25K evaluation samples were constructed for each structure understanding task. Except above strategies, we also combine single-turn samples of the same table to compose 37K multi-turn conversation samples. At last, we obtain 232K samples on 82K table images for instruction-tuning (named **MMTab-instruct**), and 45K held-in and 4K held-out test samples on 23K table images for evaluation (named **MMTab-eval**).

Inspired by existing MLLMs which align textual descriptions with input images through image-text pre-training, we introduce the table recognition task as an important pre-training task for multimodal table understanding. In this task, MLLMs learn to generate a textual table representation such as an HTML sequence given the table image, which helps aligning structure and text information in the table image with the ground-truth. We additionally collect 20K table images from the ToTTo (Parikh et al., 2020) training split and merge them with table images in the MMTab-instruct to construct sufficient pre-training data. Based on these table images and their original textual tables, we write scripts to construct table representations of three formats (HTML, Markdown and Latex), and then build instruction-following samples in the same way of MMTab-instruct. The resulting pre-training data contains 150K table recognition samples (HTML: 96K, Markdown: 27K, Latex: 27K) on 97K table images, which is denoted as MMTab-pre. More details about MMTab are given in Appendix A.

# 3.3 Dataset Analysis

**MMTab** offers the following advantages: (1) Large volume of data. It contains 150K samples for pretraining, 232K samples for instruction-tuning, 45K samples and 4K samples for held-in and held-out evaluation, respectively. (2) Including tables of diverse structures, styles and domains. It includes 105K table images covering a broad range of structures (e.g., simple tables with flat structures as well as complex tables with merged cells and hierarchical headers), divergent styles (i.e., Web page, Excel, and Markdown tables) and multiple domains (e.g., Wikipedia and financial reports). (3) Encompassing a wide range of tabular tasks. In addition to 9 academic tasks which mainly evaluate the advanced table-based reasoning ability, MMTab also




Figure 4: The two-stage training tasks and evaluation of Table-LLaVA. The red font represents our contribution.

comprises 6 tasks aimed at assessing models' basic understanding of table structures. The broad coverage of tables and tasks can not only improve the generalization of the resulting model, but also provide a comprehensive testbed for MLLM research.

# 4 Table-LLaVA

After constructing the MMTab dataset, we endeavor to fully leverage this data to promote models' multimodal table understanding ability. Inspired by the widely adopted training paradigm of previous MLLMs (Li et al., 2023b; Liu et al., 2023b; Zhu et al., 2023), we devise an enhanced two-stage training procedure and choose LLaVA-1.5 (Liu et al., 2023a) as the backbone to develop a versatile tabular MLLM named Table-LLaVA. The whole training process is illustrated in the Figure 4.

#### 4.1 Model Architecture

Following LLaVA-1.5, the proposed Table-LLaVA consists of three modules: a pre-trained ViT model (Radford et al., 2021) as the visual encoder, a two-layer MLP as the vision-language connector and a Vicuna model (Chiang et al., 2023) as the backbone LLM. The ViT model encodes the input image into visual features, which are then projected into the word embedding space of LLM by the MLP connector. The Vicuna takes as input the concatenation of processed visual features and embedded textual features to generate responses.

## 4.2 Model Training

**Pre-training.** As depicted in the top-left region of Fig. 4, the vision-language connector is first

MMTab	Task Category	Task Name	Dataset	Table Style	Domain	Held-in	# Ta	ables	# Sa	nples	Avg. Length
WIWI Iab	Task Category	Task Ivallie	Dataset	Table Style	Domain	meiu-m	Train	Test	Train	Test	(input/output)
		Flat TQA	WTQ (2015)	W	Wikipedia	Yes	1.6K	0.4K	17K	4K	45.9/10.4
	Table	Free-form TQA	FeTaQA (2022)	W	Wikipedia	Yes	8K	2K	8K	2K	32.3/18.69
	Question	Hierarchical TQA	HiTab (2022)	Е	Wikipedia goverment reports	Yes	3K	0.5K	8K	1.5K	63.5/12.6
			AIT-QA (2021)	Е	Airline	No	-	0.1K	-	0.5K	41.8/10.2
	(TQA)	Multi-choice TQA	TabMCQ (2016)	М	science exams	No	-	0.05K	-	1K	47.9/13.2
		Tabular	TABMWP (2023b)	W	math exams	Yes	30K	7K	30K	7K	54.2/51.9
		Numerical Reasoning			Yes	1.7K	0.2K	5.9K	0.7K	40.1/16.5	
	Table Fact		TabFact (2020)	E, M	Wikipedia	Yes	9K	1K	31K	6.8K	49.9/18.3
MMTab-	Verification (TFV)	TFV	InfoTabs (2020)	W	Wikipedia	Yes	1.9K	0.6K	18K	5.4K	54.2/18.6
instruct	vernication (TFV)		PubHealthTab (2022)	W	public health	No	-	0.3K	-	1.9K	71.9/18.4
mstruct	Table to	Cell Description	ToTTo (2020)	W	Wikipedia	Yes	15K	7.7K	15K	7.7K	31.1/14.8
	Text	Cen Description	HiTab_T2T (2022)	Е	Wikipedia goverment reports	Yes	3K	1.5K	3K	1.5K	39.1/14.7
	(T2T)	Game Summary	Rotowire (2017)	Е	NBA games	Yes	3.4K	0.3K	3.4K	0.3K	27.6/291.7
		Biography Generation	WikiBIO (2016)	Е	Wikipedia	Yes	4.9K	1K	4.9K	1K	18.1/84.2
		Table Size Detection	TSD	W, E, M	-	Yes	8K	1.25K	8K	1.25K	30.1/17.9
	Table	Table Cell Extraction	TCE	W, E, M	-	Yes	8K	1.25K	8K	1.25K	51.6/19.9
	Structure	Table Cell Locating	TCL	W, E, M	-	Yes	8K	1.25K	8K	1.25K	72.5/45.6
	Understanding	Merged Cell Detection	MCD	W, E, M	-	Yes	8K	1K	8K	1K	57.49/28.2
	(TSU)	Row&Column Extraction	RCE	W, E, M	-	Yes	8K	1.25K	8K	1.25K	45.6/55.1
		Table Recognition	TR	W, E, M	-	Yes	8K	1K	8K	1K	16.3/389.2
		82K	-	232K	-	66.1/66.9					
MMTab-eval			Total				-	23K	-	49K	46.3/32.6
MMTab-pre	Table	Recognition	TR	W, E, M	-	-	97K	-	150K	-	16.4/397.5

Table 1: Breakdown statistics of the constructed **MMTab** dataset. W, E and M represents Web page, Excel, and Markdown tables, respectively. Task descriptions are shown in Table 6 in Appendix A.1. For TSD, TCE, TCL, RCE datasets, their test samples contains 1K held-in and 0.25K held-out evaluation samples.

pre-trained with an extra table recognition task on the MMTab-pre dataset, where the model is required to output a textual table representation (e.g., an HTML string) which encompasses both the table structure and table content. This process aims at aligning the visual features of diversified table images with the ground-truth textual table representations, which endows the model with augmented table structure perceiving and OCR ability and thus lays the foundation of more advanced tabular tasks.

Instruction fine-tuning. In the second stage, the pre-trained vision-language connector and the LLM are jointly fine-tuned with instruction following data of multimodal table tasks in MMTabinstruct and traditional multimodal tasks. While a plethora of multimodal instruction following datasets have been previously constructed (Liu et al., 2023b; Lyu et al., 2023; Xu et al., 2023), none of them have adequately solved the multimodal table understanding problem. The proposed MMTab-instruct contributes to addressing this gap and we use it to endow the model with the advanced ability to perform downstream table tasks. We also include the original pre-training and fine-tuning data of LLaVA-1.5 during the training process to improve the generalization of the resulting model and we analyze their influence in the ablation study.

## **5** Experiments

#### 5.1 Experimental Setup

Baselines. We consider baselines of three genres: (1) Open-source MLLMs including BLIP (Li et al., 2022), OFA-Huge (Wang et al., 2022), BLIP2 (Li et al., 2023b), MiniGPT-4 (Zhu et al., 2023), Qwen-VL (Bai et al., 2023), InternLM-XComposer (Zhang et al., 2023a), mPLUG-Owl (Ye et al., 2023a) and mPLUG-Owl2 (Ye et al., 2023b), LLaVA-1.5 (Liu et al., 2023a), Varytoy (Wei et al., 2024) and Monkey (Li et al., 2023d). (2) Open-source LLMs including Llama2 (Touvron et al., 2023) and its counterpart TableLlama (Zhang et al., 2023b), which uses LongLoRA (Chen et al., 2023c) to instruction-tune LLama2 on a series of textual tabular tasks. (3) The GPT-4V with low and high image resolution. Considering the high cost of GPT-4V, we randomly select 100 or 200 samples from each benchmark to compare Table-LLaVA with GPT-4V. To enable LLMs to digest table images, we consider an ideal scenario where LLMs are provided with oracle table sequences to explore the performance upper bound, and a more practical scenario where available table sequences are recognized from images by a competitive OCR engine (PaddleOCR, 2024). For all methods, the zero-shot setting was adopted during evaluation.

				Quest	ion Ans	wering		Fact Ve	rification		Text Generation			
Method	LLM	Res.	TABMWP	WTQ	HiTab	TAT-QA	FeTaQA	TabFact	InfoTabs	тотто	HiTab_T2T	Rotowire	WikiBIO	
			Acc.	Acc.	Acc.	Acc.	BLEU	Acc.	Acc.	BLEU	BLEU	BLEU	BLEU	
MLLM														
BLIP	385M	384	3.94	1.24	0.12	0.13	0.02	0.17	0.22	0	0.18	0.04	0.02	
OFA-Huge	930M	-	0	0.06	0.07	0	0.07	0.26	0.11	0.20	0.15	0	0	
BLIP2	Flan-T5 3B	224	3.34	2.01	1.52	2.20	2.34	18.62	27.53	4.3	2.63	1.08	0.72	
MiniGPT-4	Vicuna 7B	224	0.22	0.90	0.20	0.13	0.39	0	0.10	0.20	0.11	1.26	0.33	
Qwen-VL	Qwen 7B	448	3.30	0.09	0.06	0.13	0.45	1.12	0.65	0.80	0.18	0	0	
InternLM-XComposer	InternLM 7B	224	0.06	0.05	0.12	0.26	2.62	1.19	1.11	7.10	3.25	0.43	1.52	
mPLUG-Owl	Llama 7B	224	1.76	0.62	0.25	0.13	7.42	7.46	5.53	3.50	1.75	1.96	1.37	
mPLUG-Owl2	Llama-2 7B	448	6.83	0.67	0.13	0.39	11.91	8.21	26.19	5.30	2.11	1.23	2.16	
LLaVA v1.5	Vicuna-1.5 7B	336	6.05	1.24	2.03	2.97	8.24	18.9	28.31	6.40	2.07	1.92	2.34	
Vary-toy	Qwen 1.8B	1024	4.42	7.96	3.42	8.81	2.44	6.33	6.98	0.70	0.27	0.46	0.37	
Monkey	Qwen 7B	896	13.26	$19.07^\dagger$	6.41	12.31	3.41	$22.56^{\dagger}$	22.11	3.50	1.12	0.03	2.77	
LLM														
Llama2+Oracle	Llama-2 7B	-	17.88	4.26	1.21	3.62	5.54	4.21	7.55	6.20	1.84	4.67	1.33	
Llama2+OCR	Llama-2 7B	-	16.35	3.91	0.77	5.27	5.15	4.32	7.17	-	1.56	3.90	1.28	
TableLlama+Oracle	Llama-2 7B	-	12.98	31.63 <sup>‡</sup>	$64.71^\ddagger$	2.84	39.05 <sup>‡</sup>	82.55 <sup>‡</sup>	2.85	$20.77^{\ddagger}$	0.19	0.13	0.39	
TableLlama+OCR	Llama-2 7B	-	11.09	12.49	$13.51^\dagger$	2.72	$25.44^{\dagger}$	$44.54^{\dagger}$	2.18	-	0.12	0.13	0.31	
Ours														
Table-LLaVA 7B	Vicuna-1.5 7B	336	57.78	18.43	10.09	12.82	25.60	59.85	65.26	23.00	9.74	10.46	9.68	
Table-LLaVA 13B	Vicuna-1.5 13B	336	59.77	20.41	10.85	15.67	28.03	65.00	66.91	24.10	10.40	8.83	9.67	

Table 2: Evaluation results on 11 held-in academic tabular benchmarks. '+*Oracle*' and '+OCR' represents that the ground truth or OCR-extracted textual table representations are provided to LLMs, respectively. We only report model performance in the ideal '+*Oracle*' setting and compare with models in the more practical '+OCR' setting.  $\dagger$  indicates the model has been trained on the corresponding dataset,  $\ddagger$  denotes results from original papers.

Implementation details can be found in App. B.

Evaluation metrics. For TQA, TFV, and T2T benchmarks, we use accuracy or BLEU (Papineni et al., 2002). For TSD, we compute accuracy for predicted row and column numbers separately. For TCE and TCL, we compute accuracy at cell-level. For MCD, we use cell-level F1. For RCE, we compute cell-level F1 for extracted rows and columns, respectively. For table recognition (TR) task, we follow Zhong et al. (2020) and use the Tree-Edit-Distance-based Similarity (TEDS) score, which is based on the tree structure of HTML table sequence and can measure both the structure similarity and the cell content similarity between the prediction and the ground truth. The score is normalized between 0 and 1, where 1 means perfect matching. For TR testing samples whose target sequences are in the Markdown or Latex format, we convert the predicted sequences into the HTML format to compute their TEDS scores.

#### 5.2 Results and Analysis

**Public academic tabular benchmark results.** *Performance of open-source MLLMs.* As we can see from the MLLM rows in Table 2, early MLLMs (e.g., MiniGPT-4, BLIP) exhibited minimal proficiency in multimodal table understanding due to the lack of tabular training data, but recent MLLMs (e.g., LLaVA-1.5 and Monkey) have yielded better capacity for comprehending table images, which can be attributed to their improvements on the OCR and text-rich scenarios. Especially, among existing MLLMs, Monkey performs the best in most question answering tasks and fact verification tasks because of the training on relevant table datasets (i.e., WTQ and TabFact).

Performance of LLMs. As shown in Table 2, TableLlama+OCR performs better than Llama2+OCR on several tasks (e.g., HiTab, Fe-TaQA, TabFact) through fine-tuning on the corresponding training data, but this also damages its generalization ability on unseen tasks (e.g., InfoTabs and TABMWP). Compared to Llama2+OCR, Llama2+Oracle does not achieve notable improvements, indicating that its bottleneck is the ability to understand tables and follow related instructions, rather than the table recognition ability. On the contrary, TableLlama+Oracle consistently outperforms TableLlama+OCR in all tasks, because it has been instruction-tuned on large-scale tabular data, which leads to better table understanding and instruction-following ability. Thus, the provided oracle table sequences break the bottleneck of the OCR engine's table recognition capability, resulting in significant improvements.

Comparison between Table-LLaVA and existing models. Compared to previous open-source MLLMs and LLMs+OCR, Table-LLaVA 7B and

Method	LLM	Res.	TS	SD	TCE	TCL	MCD	R	CE		TR	
Wiethou	LLM	Res.	Row	Col.	Acc.	Acc.	F1	Row	Col.	HTML	Markdown	Latex
			Acc.	Acc.	Acc.	Acc.	1.1	F1	F1	TEDS	TEDS	TEDS
MLLM												
BLIP	385M	384	0	0.10	0.76	0	0	0	0	0	0.18	0
OFA-Huge	930M	-	0	0.10	0.26	0	0	0	0	0	0.16	0
BLIP2	Flan-T5 3B	224	0.20	0.30	0.15	0	0	0.06	0	0	0.25	0
MiniGPT-4	Vicuna 7B	224	0.40	0.40	0	0	0	0	0	0	0.34	0
Qwen-VL	Qwen 7B	448	0	0	0.03	0.03	0.38	0	0	0	2.51	0
InternLM-XComposer	InternLM 7B	224	0.90	3.00	0.89	0.28	0.14	0.28	0.25	13.33	2.61	1.34
mPLUG-Owl	Llama 7B	224	1.20	3.90	0.13	0.16	0.34	2.04	1.38	15.31	7.36	3.13
mPLUG-Owl2	Llama-2 7B	448	0.50	3.50	0.51	0.17	0.45	3.49	2.38	15.71	6.67	4.43
LLaVA v1.5	Vicuna-1.5 7B	336	0.80	2.50	0.22	0.62	1.26	1.66	4.13	12.88	10.74	1.55
Vary-toy	Qwen 1.8B	1024	1.30	2.20	1.96	0.73	0.52	2.01	2.38	10.13	12.72	11.67
Monkey	Qwen 7B	896	0.80	0.60	1.46	1.31	0.67	3.89	4.53	21.96	13.29	4.54
LLM												
Llama2+Oracle	Llama-2 7B	-	1.70	3.60	0.62	0.17	-	9.36	18.03	-	-	-
Llama2+OCR	Llama-2 7B	-	1.30	3.40	0.35	0.15	-	8.15	10.45	-	-	-
TableLlama+Oracle	Llama-2 7B	-	5.30	4.40	9.35	0.82	-	4.34	5.26	-	-	-
TableLlama+OCR	Llama-2 7B	-	3.90	3.70	3.95	0.65	-	2.82	2.39	-	-	-
Ours												
Table-LLaVA 7B	Vicuna-1.5 7B	336	33.10	33.20	19.45	29.31	17.14	31.43	37.93	50.24	44.82	46.11
Table-LLaVA 13B	Vicuna-1.5 13B	336	34.40	27.60	19.53	29.68	16.52	31.07	41.49	51.44	46.00	46.50

Table 3: Evaluation results on 6 held-in table structure understanding benchmarks. For all evaluation metrics, higher values indicate better performance. HTML, Markdown and Latex represents the format of target textual table representations in the table recognition (TR) task, and TEDS is its evaluation metric. See Section 5.1 for the details.

13B both surpass them with large margins, demonstrating the effectiveness of our methods and the value of MMTab dataset. One exception is the accuracy of TableLlama+OCR on HiTab, which maybe because table images in this benchmark are relatively large, leading to information loss when resizing them into desired resolutions of Table-LLaVA (i.e.,  $336 \times 336$ ). We believe there is great potential for using more powerful MLLMs to perform diverse multimodal table understanding tasks.

**Table structure understanding benchmark results.** Table structure understanding is a fundamental ability for fulfilling more advanced tabular tasks. As can been found in Table 3, both previous MLLMs and LLMs failed to generalize well on these relatively simple tabular benchmarks that are almost trivial for humans. What's more, their performance is even worse than that on more challenging academic benchmarks in Table 2. This shows that these powerful (M)LLMs may rely on some superficial correlations (Geirhos et al., 2020) to perform downstream tabular tasks that require complex reasoning, and they actually lack the important ability to perceive basic table structures.

**Held-out tabular benchmark results.** Table 10 reports model performance on 7 held-out bench-

marks whose data do not appear in the model training. We can find that previous open-source models excel at different benchmarks respectively, and no model can consistently outperform others on all these tasks. By contrast, Table-LLaVA achieves best performance on most benchmarks, except for the accuracy of Vary-toy on AIT-QA, which is because AIT-QA contains large tables extracted from annual reports of airline companies and Vary-toy might have seen similar tables in its training data of company document images. Besides, Vary-toy supports higher input image resolution (1024), which is more friendly for large tables.

**Comparison with GPT-4V.** The average performance of Table-LLaVA and GPT-4V on five types of benchmarks is shown in the upper part of Table 4. GPT-4V achieves remarkable results under both low ( $512 \times 512$ ) and high ( $768 \times 2000$ ) image resolution. The average performance of Table-LLaVA 7B ( $336 \times 336$ ) is better than GPT-4V with low resolution ( $512 \times 512$ ) on four types of benchmarks, while GPT-4V surpasses Table-LLaVA in the held-out scenario, indicating its strong generalization ability. As can be seen from detailed benchmark performance in Table 8, Table 9 and Table 10, Table-LLaVA achieves better or competitive results with GPT-4V on 14 out of 24 benchmarks. Besides,

Method	TQA	TFV	T2T	TSU	Held-out
GPT-4V (On a subset	of test s	amples)			
Low Resolution	24.15	52.00	2.42	28.11	30.40
High Resolution	35.91	55.55	3.05	31.16	44.49
Ours (On a subset of	test sam	ples)			
Table-LLaVA 7B	24.55	65.25	9.49	34.24	23.16
Table-LLaVA 13B	26.63	64.50	9.12	34.36	24.71
Table-LLaVA 13B	26.95	65.96	13.25	34.42	25.62
Table-LLaVA 7B	24.94	62.56	13.22	34.27	24.46
w/o LLaVA-pre	24.06	61.45	12.40	31.18	21.50
$\bigtriangleup$	-0.88	-1.11	-0.82	-3.09	-2.96
w/o MMTab-pre	23.45	60.32	12.26	29.55	21.73
$\bigtriangleup$	-1.49	-2.24	-0.97	-4.73	-2.72
w/o LLaVA-instruct	24.98	61.85	12.87	33.98	23.90
$\bigtriangleup$	+0.04	-0.71	-0.36	-0.29	-0.56
w/o MMTab-instruct	2.82	20.57	4.08	5.68	3.02
$\bigtriangleup$	-22.12	-41.99	-9.14	-28.60	-21.43
w/o TSU-instruct	24.34	62.28	12.39	5.99	13.24
$\bigtriangleup$	-0.60	-0.28	-0.83	-28.28	-11.22
w successively IFT	24.76	61.99	13.06	33.89	23.85
$\bigtriangleup$	-0.18	-0.57	-0.16	-0.38	-0.61

Table 4: Upper: Comparison with GPT-4V. Lower: Ablation experiment results. We report average performance over benchmarks under five types, respectively.  $\triangle$  stands for the performance gap between Table-LLaVA 7B and its variants. 'TSU-instruct' stands for 6 table structure understanding datasets in MMTabinstruct. 'successively IFT' represents that 'LLaVAinstruct' and 'MMTab-instruct' are used to fine-tune the model in a sequential order rather than mixed together.

GPT-4V can obtain significant improvements from high image resolution, which helps the model comprehend fine-grained table elements and structures in large tables. We also analyze the influence of input image resolution on the performance of Table-LLaVA in Appendix C.1.

Ablation study. We conduct sufficient ablation experiments to validate the effectiveness of our proposed dataset and training strategy. We divide the ablation study into three parts: (1) Ablation of pretraining. As shown in Table 4, both 'w/o LLaVApre' and 'w/o MMTab-pre' cause negative effects, and the latter results in a larger decline. This is because both LLaVA-pre and MMTab-pre help align visual and textual modalities, while MMTab-pre is more suitable for multimodal alignment of table understanding. (2) Ablation of instruction fine-tuning. 'w/o LLaVA-instruct' causes a slight performance decrease, indicating that though LLaVA-instruct has different image domains and task settings from MMTab, it has benefits for the multimodal table understanding due to the enhancement of instructionfollowing ability. 'w/o MMTab-instruct' leads to a significant performance drop on all types of tasks, resulting in extremely poor performance (e.g., 3.02 on held-out benchmarks). This further confirms that our constructed data can supplement the missing table understanding capability of the current MLLMs. If the table structure understanding data in MMTab-instruct is removed (i.e., 'w/o TSUinstruct'), we can find that, although it does not cause obvious performance damage to traditional academic tasks like TQA and TFV, it has a huge negative impact on TSU and Held-out tasks. This indicates that the proposed TSU datasets also help with model generalization. (3) Ablation of training strategies. We compare models instruction-tuned with LLaVA-pre and MMTab-pre in sequence ('w successfully IFT') or mixed together. We find that 'w successfully IFT' has slightly weaker performance, which suggests that mixed data is more conducive to model performance.

The influence of MMTab on non-tabular tasks. Table 7 lists performance of Table-LLaVA and its backbone LLaVA-1.5 on two non-tabular benchmarks: TextVQA (Singh et al., 2019) and LLaVA-Bench (In-the-Wild) (Liu et al., 2023b). Table-LLaVA beats LLaVA-1.5 in most cases under both model sizes, which demonstrates that MMTab actually has positive impact on the performance of non-tabular tasks. Combing this with ablation of non-tabular training data, we can find that there are mutual benefits between model's capacity for tabular tasks and non-tabular tasks, which shows that table understanding is one fundamental and necessary ability of MLLM and it deserves more investigations. More results and analysis such as case study are shown in Appendix C.

## 6 Conclusion

This paper proposes a novel multimodal table understanding problem, together with a largescale open-source dataset MMTab, which covers a broad range of table structures and tabular tasks. This dataset provides a comprehensive testbed for MLLM research with held-in and held-out multimodal tabular benchmarks. On the basis of MMTab, we empower LLaVA 1.5 to be a generalist tabular MLLM Table-LLaVA. Experimental results show that Table-LLaVA significantly outperforms existing MLLMs on multiple benchmarks, and is even on par with the powerful GPT-4V. In conclusion, the contributions of this paper lie at promoting the research on multimodal table understanding from the task, dataset and model perspectives.

# 7 Limitations

Though this work makes the first comprehensive exploration towards the multimodal table understanding problem, there are certain limitations that can be left to the follow-ups. First, the proposed dataset mainly focus on the single table in English. The multi-table scenario together with broader language coverage have not yet been considered. Second, MMTab is based on real-world tables from carefully selected table datasets and it contains diverse high-quality table images rendered by automatic scripts. Nevertheless, table images in the wild can be low-quality. For instance, blurred, handwritten or incomplete table images. To further bridge the gap between the academic research and the real application scenarios, more diversified table images from the wild could be collected in the future, and their corresponding instruction following data needs to be constructed. We believe this could significantly promote the applications of MLLMbased table understanding systems. In the end, though the proposed Table-LLaVA demonstrates great performance on a wide range of table-based tasks, the resolution of input images is relatively low and may limit the upper bound of its capacity. Luckily, with the emergence of MLLMs which possess higher input image resolution (e.g., Monkey (Li et al., 2023d), LLaVA-Next (Liu et al., 2024)), we can use MMTab to develop more powerful tabular MLLM in the future research.

### 8 Ethical Considerations

The proposed MMTab dataset is constructed based on the academic datasets like WTQ and TabFact, which are free and open datasets for research use with licenses like MIT License<sup>1</sup> or CC-BY-SA-4.0 License<sup>2</sup>. We write Python scripts to render textual table sequences (like HTML) in these datasets to obtain table images, and build multimodal instruction-following data based on original samples. The resulting dataset MMTab is also a free and open resource for the community to study the multimodal table understanding problem. Thus, the authors foresee no ethical concerns with the research in this paper.

#### References

- Mubashara Akhtar, Oana Cocarascu, and Elena Simperl. 2022. PubHealthTab: A public health table-based dataset for evidence-based fact checking. In *Findings of the Association for Computational Linguistics: NAACL 2022*, pages 1–16, Seattle, United States. Association for Computational Linguistics.
- Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, et al. 2022. Flamingo: a visual language model for few-shot learning. *Advances in Neural Information Processing Systems*, 35:23716–23736.
- Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. 2023. Qwen-vl: A versatile visionlanguage model for understanding, localization, text reading, and beyond.
- Sara Bonfitto, Elena Casiraghi, and Marco Mesiti. 2021. Table understanding approaches for extracting knowledge from heterogeneous tables. *Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery*, 11(4):e1407.
- Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. Language models are few-shot learners.
- Pei Chen, Soumajyoti Sarkar, Leonard Lausen, Balasubramaniam Srinivasan, Sheng Zha, Ruihong Huang, and George Karypis. 2023a. Hytrel: Hypergraphenhanced tabular data representation learning. In *Thirty-seventh Conference on Neural Information Processing Systems*.
- Wenhu Chen. 2023. Large language models are few(1)shot table reasoners. In *Findings of the Association for Computational Linguistics: EACL 2023*, pages 1120–1130, Dubrovnik, Croatia. Association for Computational Linguistics.
- Wenhu Chen, Xueguang Ma, Xinyi Wang, and William W. Cohen. 2023b. Program of thoughts prompting: Disentangling computation from reasoning for numerical reasoning tasks.
- Wenhu Chen, Hongmin Wang, Jianshu Chen, Yunkai Zhang, Hong Wang, Shiyang Li, Xiyou Zhou, and William Yang Wang. 2020. Tabfact: A large-scale dataset for table-based fact verification.
- Yukang Chen, Shengju Qian, Haotian Tang, Xin Lai, Zhijian Liu, Song Han, and Jiaya Jia. 2023c. Longlora: Efficient fine-tuning of long-context large language models.

<sup>&</sup>lt;sup>1</sup>https://opensource.org/license/mit/

<sup>&</sup>lt;sup>2</sup>https://creativecommons.org/licenses/by-sa/4.0/deed.en

- Zhoujun Cheng, Haoyu Dong, Zhiruo Wang, Ran Jia, Jiaqi Guo, Yan Gao, Shi Han, Jian-Guang Lou, and Dongmei Zhang. 2022. HiTab: A hierarchical table dataset for question answering and natural language generation. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics* (Volume 1: Long Papers), pages 1094–1110, Dublin, Ireland. Association for Computational Linguistics.
- Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E. Gonzalez, Ion Stoica, and Eric P. Xing. 2023. Vicuna: An opensource chatbot impressing gpt-4 with 90%\* chatgpt quality.
- Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. 2022. Palm: Scaling language modeling with pathways.
- Tri Dao, Daniel Y. Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. 2022. FlashAttention: Fast and memory-efficient exact attention with IO-awareness. In Advances in Neural Information Processing Systems (NeurIPS).
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding.
- Haoyu Dong, Zhoujun Cheng, Xinyi He, Mengyu Zhou, Anda Zhou, Fan Zhou, Ao Liu, Shi Han, and Dongmei Zhang. 2022. Table pre-training: A survey on model architectures, pre-training objectives, and downstream tasks.
- Wolfgang Gatterbauer, Paul Bohunsky, Marcus Herzog, Bernhard Krüpl, and Bernhard Pollak. 2007. Towards domain-independent information extraction from web tables. In *Proceedings of the 16th international conference on World Wide Web*, pages 71–80.
- Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel,

Matthias Bethge, and Felix A. Wichmann. 2020. Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11):665–673.

- Vivek Gupta, Maitrey Mehta, Pegah Nokhiz, and Vivek Srikumar. 2020. INFOTABS: Inference on tables as semi-structured data. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pages 2309–2324, Online. Association for Computational Linguistics.
- Jonathan Herzig, Pawel Krzysztof Nowak, Thomas Müller, Francesco Piccinno, and Julian Eisenschlos. 2020. TaPas: Weakly supervised table parsing via pre-training. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pages 4320–4333, Online. Association for Computational Linguistics.
- Sujay Kumar Jauhar, Peter Turney, and Eduard Hovy. 2016. Tabmcq: A dataset of general knowledge tables and multiple-choice questions.
- Yannis Katsis, Saneem Chemmengath, Vishwajeet Kumar, Samarth Bharadwaj, Mustafa Canim, Michael Glass, Alfio Gliozzo, Feifei Pan, Jaydeep Sen, Karthik Sankaranarayanan, and Soumen Chakrabarti. 2021. Ait-qa: Question answering dataset over complex tables in the airline industry.
- Larissa R. Lautert, Marcelo M. Scheidt, and Carina F. Dorneles. 2013. Web table taxonomy and formalization. SIGMOD Rec., 42(3):28–33.
- Rémi Lebret, David Grangier, and Michael Auli. 2016. Neural text generation from structured data with application to the biography domain. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 1203–1213, Austin, Texas. Association for Computational Linguistics.
- Hongxin Li, Jingran Su, Yuntao Chen, Qing Li, and Zhaoxiang Zhang. 2023a. Sheetcopilot: Bringing software productivity to the next level through large language models. In *Thirty-seventh Conference on Neural Information Processing Systems*.
- Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. 2023b. Blip-2: Bootstrapping language-image pretraining with frozen image encoders and large language models.
- Junnan Li, Dongxu Li, Caiming Xiong, and Steven Hoi. 2022. Blip: Bootstrapping language-image pretraining for unified vision-language understanding and generation. In *ICML*.
- Peng Li, Yeye He, Dror Yashar, Weiwei Cui, Song Ge, Haidong Zhang, Danielle Rifinski Fainman, Dongmei Zhang, and Surajit Chaudhuri. 2023c. Table-gpt: Table-tuned gpt for diverse table tasks.
- Zhang Li, Biao Yang, Qiang Liu, Zhiyin Ma, Shuo Zhang, Jingxu Yang, Yabo Sun, Yuliang Liu, and Xiang Bai. 2023d. Monkey: Image resolution and text label are important things for large multi-modal models. arXiv preprint arXiv:2311.06607.

- Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. 2023a. Improved baselines with visual instruction tuning.
- Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. 2024. Llavanext: Improved reasoning, ocr, and world knowledge.
- Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023b. Visual instruction tuning. In *NeurIPS*.
- Qian Liu, Bei Chen, Jiaqi Guo, Morteza Ziyadi, Zeqi Lin, Weizhu Chen, and Jian-Guang Lou. 2022. TAPEX: Table pre-training via learning a neural SQL executor. In *International Conference on Learning Representations*.
- Qian Liu, Fan Zhou, Zhengbao Jiang, Longxu Dou, and Min Lin. 2023c. From zero to hero: Examining the power of symbolic tasks in instruction tuning.
- Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, Kai Chen, and Dahua Lin. 2023d. Mmbench: Is your multi-modal model an all-around player?
- Pan Lu, Baolin Peng, Hao Cheng, Michel Galley, Kai-Wei Chang, Ying Nian Wu, Song-Chun Zhu, and Jianfeng Gao. 2023a. Chameleon: Plug-and-play compositional reasoning with large language models. In *The 37th Conference on Neural Information Processing Systems (NeurIPS).*
- Pan Lu, Liang Qiu, Kai-Wei Chang, Ying Nian Wu, Song-Chun Zhu, Tanmay Rajpurohit, Peter Clark, and Ashwin Kalyan. 2023b. Dynamic prompt learning via policy gradient for semi-structured mathematical reasoning. In *International Conference on Learning Representations (ICLR)*.
- Chenyang Lyu, Minghao Wu, Longyue Wang, Xinting Huang, Bingshuai Liu, Zefeng Du, Shuming Shi, and Zhaopeng Tu. 2023. Macaw-Ilm: Multi-modal language modeling with image, audio, video, and text integration. *arXiv preprint arXiv:2306.09093*.
- Linyong Nan, Chiachun Hsieh, Ziming Mao, Xi Victoria Lin, Neha Verma, Rui Zhang, Wojciech Kryściński, Hailey Schoelkopf, Riley Kong, Xiangru Tang, Mutethia Mutuma, Ben Rosand, Isabel Trindade, Renusree Bandaru, Jacob Cunningham, Caiming Xiong, and Dragomir Radev. 2022. Fetaqa: Freeform table question answering. *Transactions of the Association for Computational Linguistics*, 10:35–49.
- PaddleOCR. 2024. table recognition model from ppstructure. https://github.com/PaddlePaddle/ PaddleOCR/tree/release/2.7/ppstructure/ table. Accessed on: 2024-02-14.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the* 40th Annual Meeting on Association for Computational Linguistics, ACL '02, page 311–318, USA. Association for Computational Linguistics.

- Ankur Parikh, Xuezhi Wang, Sebastian Gehrmann, Manaal Faruqui, Bhuwan Dhingra, Diyi Yang, and Dipanjan Das. 2020. ToTTo: A controlled table-to-text generation dataset. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1173–1186, Online. Association for Computational Linguistics.
- Panupong Pasupat and Percy Liang. 2015. Compositional semantic parsing on semi-structured tables. In Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), pages 1470–1480, Beijing, China. Association for Computational Linguistics.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. 2021. Learning transferable visual models from natural language supervision.
- Alexey Shigarov. 2023. Table understanding: Problem overview. WIREs Data Mining and Knowledge Discovery, 13(1):e1482.
- Qingyi Si, Tong Wang, Zheng Lin, Xu Zhang, Yanan Cao, and Weiping Wang. 2023. An empirical study of instruction-tuning large language models in chinese.
- Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. 2019. Towards vqa models that can read. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 8317–8326.
- Yuan Sui, Mengyu Zhou, Mingjie Zhou, Shi Han, and Dongmei Zhang. 2023. Gpt4table: Can large language models understand structured table data? a benchmark and empirical study.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas

Scialom. 2023. Llama 2: Open foundation and finetuned chat models.

- Peng Wang, An Yang, Rui Men, Junyang Lin, Shuai Bai, Zhikang Li, Jianxin Ma, Chang Zhou, Jingren Zhou, and Hongxia Yang. 2022. Ofa: Unifying architectures, tasks, and modalities through a simple sequence-to-sequence learning framework. *CoRR*, abs/2202.03052.
- Haoran Wei, Lingyu Kong, Jinyue Chen, Liang Zhao, Zheng Ge, Jinrong Yang, Jianjian Sun, Chunrui Han, and Xiangyu Zhang. 2023. Vary: Scaling up the vision vocabulary for large vision-language models.
- Haoran Wei, Lingyu Kong, Jinyue Chen, Liang Zhao, Zheng Ge, En Yu, Jianjian Sun, Chunrui Han, and Xiangyu Zhang. 2024. Small language model meets with reinforced vision vocabulary. *arXiv preprint arXiv:2401.12503*.
- Sam Wiseman, Stuart Shieber, and Alexander Rush. 2017. Challenges in data-to-document generation. In Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, pages 2253–2263, Copenhagen, Denmark. Association for Computational Linguistics.
- Zhiyang Xu, Ying Shen, and Lifu Huang. 2023. Multiinstruct: Improving multi-modal zero-shot learning via instruction tuning.
- Qinghao Ye, Haiyang Xu, Guohai Xu, Jiabo Ye, Ming Yan, Yiyang Zhou, Junyang Wang, Anwen Hu, Pengcheng Shi, Yaya Shi, Chenliang Li, Yuanhong Xu, Hehong Chen, Junfeng Tian, Qian Qi, Ji Zhang, and Fei Huang. 2023a. mplug-owl: Modularization empowers large language models with multimodality.
- Qinghao Ye, Haiyang Xu, Jiabo Ye, Ming Yan, Anwen Hu, Haowei Liu, Qi Qian, Ji Zhang, Fei Huang, and Jingren Zhou. 2023b. mplug-owl2: Revolutionizing multi-modal large language model with modality collaboration.
- Weihao Yu, Zhengyuan Yang, Linjie Li, Jianfeng Wang, Kevin Lin, Zicheng Liu, Xinchao Wang, and Lijuan Wang. 2023. Mm-vet: Evaluating large multimodal models for integrated capabilities.
- Liangyu Zha, Junlin Zhou, Liyao Li, Rui Wang, Qingyi Huang, Saisai Yang, Jing Yuan, Changbao Su, Xiang Li, Aofeng Su, Tao Zhang, Chen Zhou, Kaizhe Shou, Miao Wang, Wufang Zhu, Guoshan Lu, Chao Ye, Yali Ye, Wentao Ye, Yiming Zhang, Xinglong Deng, Jie Xu, Haobo Wang, Gang Chen, and Junbo Zhao. 2023. Tablegpt: Towards unifying tables, nature language and commands into one gpt.
- Pan Zhang, Xiaoyi Dong, Bin Wang, Yuhang Cao, Chao Xu, Linke Ouyang, Zhiyuan Zhao, Haodong Duan, Songyang Zhang, Shuangrui Ding, Wenwei Zhang, Hang Yan, Xinyue Zhang, Wei Li, Jingwen Li, Kai Chen, Conghui He, Xingcheng Zhang, Yu Qiao,

Dahua Lin, and Jiaqi Wang. 2023a. Internlmxcomposer: A vision-language large model for advanced text-image comprehension and composition.

- Tianshu Zhang, Xiang Yue, Yifei Li, and Huan Sun. 2023b. Tablellama: Towards open large generalist models for tables.
- Mingyu Zheng, Yang Hao, Wenbin Jiang, Zheng Lin, Yajuan Lyu, QiaoQiao She, and Weiping Wang. 2023. IM-TQA: A Chinese table question answering dataset with implicit and multi-type table structures. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 5074–5094, Toronto, Canada. Association for Computational Linguistics.
- Xu Zhong, Elaheh ShafieiBavani, and Antonio Jimeno Yepes. 2020. Image-based table recognition: data, model, and evaluation.
- Chunting Zhou, Pengfei Liu, Puxin Xu, Srini Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma, Avia Efrat, Ping Yu, Lili Yu, Susan Zhang, Gargi Ghosh, Mike Lewis, Luke Zettlemoyer, and Omer Levy. 2023. Lima: Less is more for alignment.
- Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. 2023. Minigpt-4: Enhancing vision-language understanding with advanced large language models.
- Fengbin Zhu, Wenqiang Lei, Youcheng Huang, Chao Wang, Shuo Zhang, Jiancheng Lv, Fuli Feng, and Tat-Seng Chua. 2021. TAT-QA: A question answering benchmark on a hybrid of tabular and textual content in finance. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), pages 3277–3287, Online. Association for Computational Linguistics.

#### A More Details about MMTab

# A.1 Task Descriptions and More Dataset Examples

Detailed description and evaluation metric of each task are given in Table 6, and more dataset examples are illustrated in Figure 5, 6, 7. When we collect tables from TabMCQ dataset, we filter extremely long tables more than 50 rows. For the hybrid-QA dataset TAT-QA, we only preserve samples whose questions can be answered with the table information. For the ToTTo dataset, its training set contains 35K tables and we randomly select 15K tables for MMTab-instruct in order to reduce the cost of transforming HTML tables into images.

Except augmentation strategies mentioned in Section 3.2, we also perform additional data augmentations including: (1) "response-level augmentations", where we synthesize chain-of-thoughts using annotated intermediate computational procedures in the original datasets and use them to augment the final answer. (2) "conversation-level augmentations", where we randomly choose samples of the same table to compose multi-turn conversation samples.

Hyperparameter	Pre-train	Fine-tune				
tertation total	MMTab-pre (150K),	MMTab-instruct (232K),				
training data	LLaVA-pre (558K)	LLaVA-instruct (665K)				
batch size	256	128				
max length		2560				
learning rate (lr)	1e-3	2e-5				
lr schedule	cosine decay					
warmup ratio	0.03					
weight decay	0					
optimizer	A	damW				
epoch		1				
Deepspeed Stage	2	3				
machine	one machine	with 8 80GB A800				
training time	32 hours	26 hours				
(w/o flash-attention)	52 10018	20 nours				

Table 5: Hyperparameter setting and training details of Table-LLaVA.

# A.2 Instruction Templates

The diversity of the instruction-following data has a significant impact on the performance of the resulting model. As discussed in the Section 3.2, we utilize in-context learning to ask GPT-4 to generate new instruction templates and create more diversity of input request. When we build input requests of each dataset, we randomly choose an instruction template and an output format description from the candidate pool, and then combine them with the task-specific input such as the question to produce the final input request. Figure 8 shows the Python code for this combination process, together with all instruction templates and JSON output format descriptions for the TABMWP dataset. Previous textual instruction-following datasets for tabular tasks such as TableInstruct (Zhang et al., 2023b) usually adopt one fixed instruction template for each dataset. By contrast, we construct at least 20 instruction templates for each dataset while considering their respective characteristics.

### **B** Implementation Details

Following LLaVA-1.5 (Liu et al., 2023a), we use the well-trained CLIP-ViT-L-336px (Radford et al., 2021) as the visual encoder and input images are resized to  $336 \times 336$ . We develop two Table-LLaVA models with Vicuna-1.5 7B and 13B as the backbone LLM, and we denote the resulting models as Table-LLaVA 7B and Table-LLaVA 13B, respectively. We follow the original hyper-parameter setting of LLaVA-1.5 except that We increased the max sequence length from 2048 to 2560 to accommodate longer text sequences. The training hyperparameters for both the pre-training and the visual instruction tuning are listed in Table 5. In this paper, all experiments including baseline experiments were conducted on a single machine with 8 80GB A800. Without using flash-attention (Dao et al., 2022), the pre-training process and the instructiontuning takes about 32 hours and 26 hours for one epoch, respectively. Unless otherwise specified, we evaluate performance of baseline models on our benchmarks with the official implementations. As mentioned in the Section 3.1, we add extra instructions to the input request which require models to output the final answer in the JSON format, and we write Python scripts with regular expressions to extract the final answer for a fair comparion. Some baselines like Monkey cannot follow instructions to output the answer in the desired JSON format, which may only output a short answer due to the overfitting of their training data. Thus, we relaxed requirements and specifically designed answer extraction scripts to calculate their accuracy. For ToTTo benchmark, since the ground-truth of testing samples have not been open-sourced, we submit the output results of different models to the official website to get evaluation results.

MMTab	Task Category	Task Name	Dataset	Task Description	Metric
		Flat TQA	WTO	TQA based on tables which usually possesses a flat	A a a una a u († )
l		(F TQA)	WTQ	structure with the first row as the sole column header.	Accuracy(†)
		Error forms TO A	E-T-04	TQA with a free-form text answer rather than a	
	Question	Free-form TQA	FeTaQA	short text span copied from the table.	BLEU(↑)
i	Answering	Hierarchical TQA	HiTab	TQA based on tables which usually possesses	Accuracy(↑)
i		(H TQA)	AIT-QA	AIT-QA hierachical headers and merged cells.	
l		Multi-choice TQA	TabMCQ	TQA with multi-choice questions.	Accuracy( <sup>†</sup> )
		Tabular	TABMWP	TQA requiring mathematical reasoning operations such as	Accuracy( <sup>†</sup> )
		Numerical Reasoning	TAT-QA	finding the largest number or do math computations.	Accuracy( <sup>†</sup> )
			TabFact	Given a table as evidence and a statement, the	Accuracy( <sup>†</sup> )
MMTab-	Fact		InfoTabs	task is to distinguish whether the given	Accuracy( <sup>†</sup> )
instruct	Verification	Fact Verification	PubHealthTab	statement is entailed or refuted by the table.	Accuracy( <sup>†</sup> )
				Generate a one-sentence description for the	DI FILIA
	_	Cell Description ToTTo highlighted table cells.		highlighted table cells.	BLEU(↑)
	Text			Generate a one-sentence description for the	
	Generation	Generation		highlighted table cells using the provided	BLEU(†)
				operators such as SUM, DIVISION.	
1		Given a table recording box- and line-scores			
		Game Summary	Rotowire	of an NBA game, the task is to generate a	BLEU(†)
				detail game summary which is sourced from rotowire.com.	
		Biography Generation	WikiBIO	Given a table containing information of a person, the task is to generate a biography	BLEU(†)
				to introduce this person.	
		<b>T</b> 11 (2) <b>D</b> 1	map	Determine the row number and column	Accuracy at row
		Table Size Detection	TSD	number of the given table.	or column level(↑
	~			Given a group of (row_id, column_id), the task	
	Structure	Table Cell Extraction	TCE	is to extract the corresponding table cells.	Accuracy( <sup>†</sup> )
	Understanding			Given a group of cells, the task is to find	
		Table Cell Locating	TCL	positions of these cells in the table and return	Accuracy( <sup>†</sup> )
		-		their position in theformat of (row_id, column_id).	
				Determine whether the table contains	
		Merged Cell Detection	MCD	merged cells and return postions of top-left	F1(†)
		, i i i i i i i i i i i i i i i i i i i		and bottom-right cells in the merged regions.	
l		<b>D</b> 0.01 <b>D</b> 1	DOD	Given a group of row_id or column_id, the task is to extract the	F1 at row
l		Row&Column Extraction	RCE	corresponding table cells in the target rows or target columns.	or column level(↑
		Table Recognition	TR	Given a table image, the task is to return a textual representation	
		0			$TEDS(\uparrow)$
MMTab-		e Recognition	TR for pre-training	of the table in the format of HTML, Markdown or Latex Same	1220(1)

Table 6: Detailed description of each task and their evaluation metrics.

Models	TextVQA	LLaVA-Bench (in-the-wild)								
woucis	IEXTVQA	Conversation	Detail	Complex	Overall					
		Conversation	description	reasoning	Overall					
LLaVA v1.5 7B	58.2*	54.3	49.6	72.4	61.4					
Table-LLaVA 7B	59.2	58.3	50.9	73.2	63.2					
LLaVA v1.5 13B	61.3*	72.0	53.8	72.0	67.5					
Table-LLaVA 13B	61.9	72.0	53.7	77.1	69.6					

Table 7: Comparison of Table-LLaVA and its backbone on non-tabular tasks. \* indicates results are from the original LLaVA-1.5 paper.

# C More Experimental Results and Analysis

# C.1 Influence of Input Image Resolution

To shed more light on the influence of image resolution on multimodal table understanding, we divide test samples into 5 groups by their image resolution and evaluate model performance on different groups. The results, illustrated in Figure 9, demonstrate that image resolution has a great impact on model performance. The model performance gradually degenerates with the increasing image resolution, which reveals that it is necessary to enlarge the input image solution of MLLMs in order to process extremely large table images.

# C.2 Influence of MMTab on Non-tabular Tasks

We compare Table-LLaVA with its backbone LLaVA-1.5 on two non-tabular benchmarks: TextVQA (Singh et al., 2019), a VQA benchmark requiring the understanding of image texts, and LLaVA-Bench (In-the-Wild) (Liu et al., 2023b), a recent general benchmark for MLLMs including 3 task categories (conversation, detail description and complex reasoning). The results are listed in the Table 7. Table-LLaVA beats LLaVA-1.5 in most cases under both model sizes, which demonstrates that tabular training data has positive impact on the performance on non-tabular tasks.

# C.3 Influence of OCR Success Rate on LLM Performance

We compute the cell-level OCR success rates on 4 benchmarks and show the performance of textual




Figure 5: More dataset examples.

				Quest	ion Ans	wering		Fact Ve	rification		Text Ge	neration	
Method	LLM	Res.	TABMWP	WTQ	HiTab	TAT-QA	FeTaQA	TabFact	InfoTabs	ТоТТо	HiTab_T2T	Rotowire	WikiBIO
			Acc.	Acc.	Acc.	Acc.	BLEU	Acc.	Acc.	BLEU	BLEU	BLEU	BLEU
Ours (on all test samples)													
Table-LLaVA 7B	Vicuna-1.5 7B	336	57.78	18.43	10.09	12.82	25.60	59.85	65.26	23.00	9.74	10.46	9.68
Table-LLaVA 13B	Vicuna-1.5 13B	336	59.77	20.41	10.85	15.67	28.03	65.00	66.91	24.10	10.40	8.83	9.67
GPT-4V (on a subse	t of test samples	)											
Low Resolution	GPT-4	512	60.00	22.50	9.50	19.50	9.26	45.50	58.50	-	1.85	3.89	1.55
High Resolution	GPT-4	768*2000	60.50	48.00	27.50	32.50	11.04	45.50	65.60	-	2.98	4.23	1.94
Ours (on a subset of	f test samples)												
Table-LLaVA 7B	Vicuna-1.5 7B	336	57.00	18.00	7.50	11.00	29.23	63.50	67.00	-	9.34	10.08	9.04
Table-LLaVA 13B	Vicuna-1.5 13B	336	60.00	21.50	8.00	14.00	29.63	59.50	69.50	-	9.53	9.00	8.84

Table 8: Comparison between GPT-4V and Table-LLaVA on 11 held-in public academic tabular benchmarks. Note that we randomly select a subset of testing samples for each tasks due to the high cost of GPT-4V and we also evaluate Table-LLaVA on the same subset.

LLMs in Table 11. As shown in the table, OCR success rates vary a lot among 4 benchmarks, ranging from 11.05% to 75.35%. Intuitively, table images with large sizes (i.e. large Ave. Cell Numer) pose greater challenge to OCR engines and thus often lead to low OCR success rates. With OCR success rate decreasing, the performance gap of TableLlama between '+Oracle' and '+OCR' settings significantly increases, which reveals the importance of correct table recognition results. Moreover, compared with TableLlama, the performance gap of Llama2 between two settings is much more lower and less significant, which shows its bottleneck is the ability to understand and follow table-related instructions, rather than OCR results.

By manually inspecting the OCR results, we find that typical error types include (1) character-level mistakes, e.g., missing the first or last letter, (2) cell-level mistakes, e.g., missing whole cells, mistakenly splitting text in one cell into two cells, very wrong cell text especially for cells with long and intensive text, (3) row or column level mistakes, e.g., missing rows or inserting non-existing rows. (4) structure-level mistakes, e.g., falsely recognizing a merged cell as a non-merged cell or vice versa.

#### C.4 Case Study

We conduct a side-by-side qualitative analysis to compare Table-LLaVA with other (M)LLMs on different benchmarks, as illustrated in Figure 10-16. The results demonstrate that Table-LLaVA can handle a series of table tasks and possesses better multimodal table understanding ability than existing open-source MLLMs. For instance, as can be seen in Figure 10, Table-LLaVA provides both the intermediate reasoning steps and the correct final answer for the math word problem based on table image, whereas other MLLMs including GPT-4V fail to give the correct answer. The proposed MMTab dataset can be directly utilized in the training process of future MLLMs to boost their multimodal table understanding ability.

Method	LLM	Res.	TS	SD	TCE	TCL	MCD	R	CE		TR	
Methou		ксз.	Row	Col.	Acc.	1	F1	Row	Col.	HTML	Markdown	Latex
			Acc.	Acc.	Acc.	Acc.	1.1	F1	F1	TEDS	TEDS	TEDS
Ours (on all test samples)												
Table-LLaVA 7B	Vicuna-1.5 7B	336	33.10	33.20	19.45	29.31	17.14	31.43	37.93	50.24	44.82	46.11
Table-LLaVA 13B	Vicuna-1.5 13B	336	34.40	27.60	19.53	29.68	16.52	31.07	41.49	51.44	46.00	46.50
GPT-4V (on a subse	t of test samples)											
Low Resolution	GPT-4	512	6.00	24.00	3.57	14.41	2.12	30.32	56.86	41.55	45.74	34.46
High Resolution	GPT-4	768*2000	12.50	46.00	9.75	23.38	3.50	26.44	43.17	48.58	60.58	37.66
Ours (on a subset of	f test samples)											
Table-LLaVA 7B	Vicuna-1.5 7B	336	32.00	30.50	17.72	30.45	18.44	29.55	40.40	51.66	40.74	50.94
Table-LLaVA 13B	Vicuna-1.5 13B	336	34.50	26.00	18.41	30.54	15.88	29.87	42.88	52.03	41.65	51.85


Table 9: Comparison between GPT-4V and Table-LLaVA on 6 held-in table structure understanding benchmarks.


Method	AIT-QA	PubHealthTab	TabMCQ	,	ГSD	TCE	TCL	RCE		
Methou	Acc	Acc	Acc	Row Acc.	Col Acc.	Acc.	Acc.	Row F1.	Col. F1.	
Previous Best	Vary-toy	Monkey	Monkey	LLaVA-1.5	mPLUG-Owl2	Monkey	LLaVA-1.5	Monkey	LLama2+OCR	
	9.39	18.89	17.89	2.40	3.60	0.76	0.93	4.29	4.54	
Ours										
Table-LLaVA 7B	5.48	51.03	44.51	25.20	16.40	11.28	26.10	21.97	18.14	
Table-LLaVA 13B	6.06	48.46	51.51	31.60	14.80	11.38	26.17	21.94	18.67	
GPT-4V (on a subs	et of test so	umples)								
Low Resolution	19.00	59.50	66.00	8.00	15.00	10.29	17.73	27.69	50.36	
High Resolution	62.50	67.00	66.00	19.00	38.00	14.36	27.91	48.52	57.14	
Ours (on a subset of	of test samp	oles)								
Table-LLaVA 7B	5.00	52.50	43.50	22.00	16.00	12.73	26.27	16.57	13.91	
Table-LLaVA 13B	6.50	53.50	45.50	30.00	15.00	11.92	25.45	20.77	13.78	

Table 10: Evaluation results on 7 held-out tabular benchmarks.

OCR Accuracy	TABMWP	TabFact	WTQ	HiTab
Cell-level OCR Accuracy (%)	75.35	51.48	27.09	11.05
Table Size				
Ave. Row Number	6.45	14.40	26.4	23.38
Ave. Col Number	2.19	6.23	6.2	8.17
Ave. Cell Number (Row*Col)	14.13	83.71	163.68	191.01
Image Resolution (px)				
Ave. Width*Height	269*190	2354*875	1996*1137	3194*870
Methods				
Llama2+Oracle	17.88	4.32	4.26	1.21
Llama2+OCR	16.35	4.21	3.91	0.77
Gap between Oracle and OCR	1.53	0.11	0.35	0.44
TableLlama+Oracle	12.98	82.55	31.63	64.71
TableLlama+OCR	11.09	44.54	12.49	13.51
Gap between Oracle and OCR	1.89	38.01	19.14	51.20

Table 11: LLM performance on benchmarks with different OCR success rates.





Task	Table im:	ages of differ	ent types	Input requests of different tasks ( <mark>task description, required output format, task-related input</mark> )	Output responses (final answer, chain-of-thoughts)
		As of D	ecember 31,		
		2017	2018 2019		
Numerical	Employ	vees			
Reasoning			11,651 11,328	Analyze the table and respond to the question that follows. Present the final answer as JSON in the format {"answer": [ <a answer="" list="" of="" strin<="" th=""><th>Based on the given table: (798+784+833) / 3 = 805</th></a>	Based on the given table: (798+784+833) / 3 = 805
	Technic		7,494 7,416	[ss]]. What is the average number of Administrative Staff employed?	(798+784+853)7 5 = 805 Therefore, the answer is {"answer": ["805"]}.
	Administrative :		784 833	(8-1)	
		Total 20,076	19,929 19,577		
		Bruce Lee			
	Chinese name	李小龍 (tradition	al)		
	Chinese name	李小龙 (simplifie	ed)		
	Years active			Based on the shown table, determine if it upholds or disproves the fol	
	Spouse(s)	Linda Emery (m. 1		lowing claim. If the claim may or may not be true, it should be consid	Based on the table information, we can not determine whether the
Fact Verification	Children	Brandon Lee (son) Shannon Lee (daug	hter) (born 1969)	ered 'not enough evidence'. Your final answer should be in the JSON structure, formatted as {"answer": " <your answer="">"}.</your>	claim is true or false. Thus, the answer is {"answer": "not enough evidence"}.
	Parents	Lee Hoi-chuen (fat Grace Ho (mother)	(1907–1996)	Bruce Lee was the oldest in his family.	
	Siblings	Phoebe Lee (sister) Agnes Lee (sister) Peter Lee (brother) Robert Lee (brother)			
	Taylor Gabriel				
Cell Description		36 621 17.3 70 1 4 28 241 8.6 56 0 0	Avg         Lng         TO         FUMI         Lost           0         2.5         8         0         0         0           0         0.5         0.0         1         1           51         12.8         27         1         0         0           60         0.1         15         0         0         0           51         12.8         27         1         0         0           60         0.1         15         0         0         0           51         0.8         20         0         1         1	Using the table regarding 'Taylor Gabriel' and its associated metadata, compose a one-sentence description of the data emphasized in the hig hlighted table cells.	Gabriel finished the 2018 season with 67 catches for 688 yards and two receiving touchdowns.






Figure 8: Exemplary instruction templates, JSON output format descriptions, and the Python Code for constructing the input requests. Taking the TABMWP dataset as an example.




Figure 9: Break-down experimental results of Table-LLaVA 7B by different input image resolution. We divide test samples into 5 groups according to their image resolution, e.g., '512' represents the input image resolution is smaller than  $512 \times 512$  but larger than  $336 \times 336$ . For TSD, MCD, RCE and TR, we report averaged results.




Figure 10: Case study on the TABMWP and WTQ benchmark. For the TABMWP benchmark, the model needs to conduct multi-step reasoning to obtain the final answer.

( <b>O</b> )	club	season 1966-67	division second division	league apps goal	fac s apps ତ	goals		total number	male 1,242,600	female 1,352,000		
	carlisle united	1966-67 1967-68 1968-69	second division second division second division	1 0 27 0 4 0	0	8 8	Ŭ	mean age	38.6 % dis	39.4 ribution		
	total cardiff city	1966-67 1967-68	32 second division second division	0 0 5 0 9 1	8 0 8	2 0 8		age group 0 to 24 25 to 44	22.5 41.7	19.8 44.4		
	barnsley	1970-71 1971-72 1972-73	total third division third division fourth division	14 1 43 3 42 0 40 4	0 4 3 2	0 0 0		45 to 64 65 or older immigration category economic class	29.0 6.8	27.2 8.6		
	grimsby town port vale	1973-74 1974-75 career tot	total third division third division al	125 7 29 2 24 2 224 12	9 4 2 15	0 0 0		principal applicant dependant family class refugee class	26.2 23.5 28.9	12.2 33.7 37.4 12.7		
•	ensuing quest appearances?R list of answ "ontario"]}.	ion:how eturn the er string	about 'statistics many goals dic result as JSON [s>]}, e.g., {";	sharp score in the formation	e in 125 t {"answe	league r": [ <a< th=""><th></th><th>Given the excel table landing file cohort, by and source world region answer in the JSON answer strings&gt;]} such</th><th>sex, age group, im 1', answer the follo structure, using th</th><th>migration cate wing question e format {"a</th><th>egory, landing year, h briefly. Provide an nswer": [<a list="" of<="" th=""><th></th></a></th></a<>		Given the excel table landing file cohort, by and source world region answer in the JSON answer strings>]} such	sex, age group, im 1', answer the follo structure, using th	migration cate wing question e format {"a	egory, landing year, h briefly. Provide an nswer": [ <a list="" of<="" th=""><th></th></a>	
	{"ar ("answer": ["6"	nswer": ["		nation, the	final ans	ver is		of male immigrants did Using the information i	the family class ac		"answer": ["28.9"]}.	(
6 0		nswer": ["		nation, the	final ansv	ver is		of male immigrants did Using the information i {"answer": {"28.9"}}	the family class ac		"answer": ["28.9"]},	
20	("answer": ["6" 121.28 {"answer": [["f	nswer": [" ]]] Tield hous nplex", 1	7.0"]}. e", 10, 36], ["sta , 10], ["score bc	dium", 4, 17]	["scorebo	ard", 1,	A	of male immigrants did Using the information i	the family class ac		"answer": ["28.9"]},	
20	("answer": ["6" 121.28 {"answer": [["f 2], ["sports con 10]], "league le	ield houss nplex", 1 ague": [1	7.0"]}. e", 10, 36], ["sta , 10], ["score bc	dium", 4, 17] ard", 1, 10],	["scorebo ["score bo	ard", 1, ard", 1,		of male immigrants did Using the information i ["answer": ["28.9"]] [2.7 ] 33.7 ["answer": [9.5, 3.7, 3]	the family class ac	ne answer is <b>{</b> 3, 4.3, 4.3, 4.3, 4.3	1, 4.3, 4.3]}	

Figure 11: Case study on the HiTab benchmark, where the model is required to comprehend hierarchical tables with merged cells.




Figure 12: Case study on the InfoTab and TAT-QA benchmarks. Common table structures usually have the first row as column header, but table structures in IntoTab are quite different, where the first column contains row headers. Diverse table structures in MMTab pose unique challenge to existing MLLMs.



Figure 13: Case study on the ToTTo and TSD benchmarks. Though facing a relatively small and simple table, existing powerful MLLMs may fail to determine the row number and column number of the table. The basic ability to understand diverse table structures has been overlooked by previous MLLM study and the proposed MMTab alleviates this problem.




Figure 14: Case study on the TCE and TCL benchmarks, where the model is required to extract the target cell content or find the target cell location based on the table image. This task is trivial for human readers yet is challenging for existing MLLMs, which reveals the gap between current MLLMs and the human-level table understanding ability.

1 2 3		opponent	result	attendance	week   date   result   opponent   attendance   new york yankees   33 - 28 239,366 38 - 23
	september 10, 2001	new york giants	w 31 - 20	75735	
	september 23, 2001	arizona cardinals	w 38 - 17	50913	231,549 arizona cardinals   39 - 21 47,050 baltimore ravens   14 - 7 14,281 kansas city
	september 30 , 2001	baltimore ravens	1 20 - 13	75082	chiefs   17 - 14 29,341 seattle seahawks   28 - 17 52,417 san francisco giants   26 - 21
4 5	october 7, 2001	kansas city chiefs	w 20 - 6	75037	33,624 philadelphia phillies   5 - 3 10,286 new york patriots   21 - 7 63,020 oakland
6	october 14, 2001 october 21, 2001	seattle seahawks san diego chargers	1 34 - 21 1 27 - 10	61837 67521	raiders   17 - 14 26,198 san diego chargers   16 - 10 21,963 washington redskins   20 - 14
7	october 28, 2001	new england patriots	w 31 - 20	74750	70,964 dallas cowboys   24 - 13 60,041 st. louis rams   29 - 17 58,018 seattle seahawks
8	november 5 , 2001	oakland raiders	138 - 28	62637	27 - 19 57,980 san francisco 49ers   29 - 17 57,867 cleveland browns   29 - 19 57,025 san
9	november 11 , 2001	san diego chargers	w 26 - 16	74951	diego chargers   29 - 19 56,905 kansas city chiefs   29 - 19 56,817 cleveland browns   29 -
10	november 18, 2001	washington redskins	117 - 10	74622	
11	november 22, 2001	dallas cowboys	w 26 - 24	64104	18 56,905 seattle seahawks   29 - 17 56,817 san francisco 49ers   29 - 17 56,817
12	december 2, 2001	miami dolphins	121 - 10	73938	philadelphia phillies   29 - 17 56,817 san diego chargers   20 - 19 57,025 philadelphia
13	december 9, 2001	seattle seahawks	w 20 - 7	74524	phillies
14	december 16 , 2001	kansas city chiefs	126 - 23	77778	
16	december 30, 2001 january 6, 2002	oakland raiders indianapolis colts	w 23 - 17 1 29 - 10	75582 56192	
-  1 se  2 se	ptember 23 , 2001   ar	v york giants   w 31 - 2 izona cardinals   w 38	- 17   50913		multiple N are reported.]           (begin (tabular) { }           week & date & [multicolumn[3][c]] (opponent) & [multicolumn[2][c][result] & attendance              & attendance              & & & & & & & & & & & & & & & & & & &
-   1   se   2   se   3   se   4   oo   5   oo   6   oo   7   oo   8   no   9   no	ptember 9, 2001   nev ptember 23, 2001   ar ptember 30, 2001   br tober 7, 2001   kansa: tober 14, 2001   san c tober 28, 2001   new ovember 5, 2001   oak ovember 11, 2001   sa	v york giants   w 31 - 2	- 17   50913   12   75032   3   75037     61837   0   76521   - 20   71250   62637   5 - 21   74651	I	\begin [tabular] {]       week & date & [multicolumn[3] {c] [opponent] & [multicolumn[2] [c] [result] & attendance \\       & & & & & & & & & & & & & & &
-   1   se   2   se   3   se   4   oo   5   oo   6   oo   7   oo   8   no   9   no   10   1	prember 9, 2001   nev prember 23, 2001   are prember 23, 2001   are tober 7, 2001   kansa tober 14, 2001   sant tober 23, 2001   san tober 28, 2001	v york giants   w 31 - 2 izona cardinals   w 38 altimore ravens   1 20 - 1 s city chiefs   w 20 - 13 leseahawks   1 34 - 21 liego chargers   1 37 - 1 england patriots   w 31 land raiders   1 38 - 28 n diego chargers   w 2 2	- 17   50913   12   75032   3   75037     61837   0   76521   - 20   71250   62637   5 - 21   74651 17 - 10   7182	I	Wegin (tabular) {]         week & date & multicolumn[3] [c] (opponent) & multicolumn[2] [c] [result) & attendance \\             & & & & & & & & & & & &
-  1 se  2 se  3 se  4 oo  5 oo  6 oo  7 oo  8 no  9 no  10 1  11 1	ptember 3, 2001   nev ptember 3, 2001   av ptember 30, 2001   ba tober 7, 2001   kaat tober 21, 2001   saat tober 21, 2001   saat tober 28, 2001   new yvember 5, 2001   oak yvember 11, 2001   sa tovember 12, 2001   v	v york giants   w 31 - 2 izona cardinals   w 38 litimore ravens   1 20 - s city chiefs   w 20 - 13 le seahawks   1 34 - 21 liego chargers   1 27 - 1 england patriots   w 31 land raiders   1 38 - 28 n diego chargers   w 26 vashington redskins   1	- 17   50913   12   75032   8   75037   61837   0   76521   1 - 20   71250 62637   5 - 21   74651 17 - 10   7182 24   64104	I	Wegin (tabular) {]         wmalticolumn[3] [c] {opponent}         wmalticolumn[2] [c] {result}           & attendance \\         & attendance \\         & attendance \\           & & & & & & & & & & & & & & & & & & &
-   1   se   2   se   3   se   4   oo   5   oo   6   oo   7   oo   8   no   9   no   10   1   11   1   12	ptember 9, 2001   nev ptember 30, 2001   av ptember 30, 2001   at ptember 30, 2001   st tober 7, 2001   san t tober 21, 2001   san t tober 28, 2001   new yvember 5, 2001   oak yvember 18, 2001   so tovember 22, 2001   d tovember 25, 2001   t	v york giants   w 31 - 2 izona cardinals   w 38 litimore ravens   120 - 1 liego chargers   124 - 1 liego chargers   127 - 1 england patricts   w 31 land raiders   138 - 28 u diego chargers   w 22 vashington redskins     allas cowboys   w 26 - inami dolphins   121 -	- 17   50913   12   75032   8   75037   61837   0   76521   1 - 20   71250 62637   5 - 21   74651 17 - 10   7182 24   64104   10   73938	I	Wegin (tabular) {]         week & date & multicolumn[3] [c] (opponent) & multicolumn[2] [c] [result) & attendance \\             & & & & & & & & & & & &
-   1   se   2   se   3   se   4   oc   5   oc   6   oc   7   oc   8   nc   9   nc   10   1     11   1   11   1   13   c	ptember 9, 2001   nev ptember 30, 2001   av ptember 30, 2001   av itober 7, 2001   kansa itober 14, 2001   seatt itober 21, 2001   soat itober 28, 2001   oak wember 5, 2001   oak wember 11, 2001   sa itovember 22, 2001   d ivovember 22, 2001   d ivovember 22, 2001   d ivovember 29, 2001   se	v york giants   w 31 - 2 izona cardinals   w 38 ltimore ravens   120 - 1 is city chiefs   w 20 - 1 ile seahawks   134 - 21 liego chargers   127 - 1 land raiders   138 - 28 n diego chargers   w 26 usahington redskins   lallas cowboys   w 26 - niami dolphins   121 - tile seahawks   w 20 -	- 17   50913   12   75032   175037   61837   0   76521   - 20   71250   62637   5 - 21   74651   17 - 10   7182   24   64104   10   73938   7   74751	I	Wegin (tabular) {]         wmalticolumn[3] [c] {opponent}         wmalticolumn[2] [c] {result}           & attendance \\         & attendance \\         & attendance \\           & & & & & & & & & & & & & & & & & & &
-   1   se   2   se   3   se   4   oc   5   oc   6   oc   7   oc   8   nc   9   nc   10   1   11   1   12     13   c   14   c	prember 9 . 2001   nex prember 3 . 2001   arx prember 30 . 2001   arx tober 7 . 2001   sans tober 14 . 2001   sans tober 21 . 2001   san tober 28 . 2001   san tober 28 . 2001   san voember 18 . 2001   sa november 25 . 2001   n november 25 . 2001   n lecember 6 . 2001   s	v york giants   w 31 - 2 izona cardinals   w 38 litimore ravens   120 - 1 liego chargers   127 - 1 england patriots   w 31 land raiders   138 - 28 vashington redskins   1 lands cowboys   w 26 - niami dolphins   121 - litlas cowboys   w 26 - niami dolphins   121 -	- 17   50913   12   75032   1   75037   61837   0   76521   - 20   71250   62637   5 - 21   74651   17 - 10   7182   24   64104   10   73938   7   74751   - 23   77778	I	Wegin (tabular) {]         wmalticolumn[3] [c] {opponent}         wmalticolumn[2] [c] {result}           & attendance \\         & attendance \\         & attendance \\           & & & & & & & & & & & & & & & & & & &
-   1   sc   2   sc   3   sc   4   oc   5   oc   6   oc   7   oc   8   nc   9   nc   10   1   11   1   12     13   (   14   oc	implember 2, 2001   nev           pptember 30, 2001   nev           pptember 30, 2001   bit           tober 7, 2001   sans           tober 7, 2001   sans           tober 21, 2001   sans           tober 22, 2001   sans           tober 23, 2001   sans           tober 24, 2001   sans           tober 24, 2001   sans           tober 25, 2001   oak           towember 22, 2001   das           towember 25, 2001   sans           towember 25, 2001   sans           toecember 25, 2001   sans           toecember 25, 2001   sans           toecember 25, 2001   sans           toecember 26, 2001   sans           toecember 16, 2001   sans	v york giants   w 31 - 2 izona cardinals   w 38 ltimore ravens   120 - 1 is city chiefs   w 20 - 1 ile seahawks   134 - 21 liego chargers   127 - 1 land raiders   138 - 28 n diego chargers   w 26 usahington redskins   lallas cowboys   w 26 - niami dolphins   121 - tile seahawks   w 20 -	- 17   50913   12   75032   3   75037   61837   0   76521   - 20   71250   62637   5 - 21   74651   17 - 10   7182   24   64104   10   73938   7   74751   - 23   77778   17   74258	I	\begin[tabular]]         \begin[tabular]]           \begin[tabular]]         \begin[tabular]]           & & & & & & & & & & & & & & & & & & &

Figure 15: Case study on the TR (table recognition) benchmark. Though Table-LLaVA generate the markdown sequence with correct table structure, its OCR ability is restricted by the input resolution and needs to be enlarged. In the future work, the proposed MMTab dataset can be combined with MLLMs with stronger OCR ability and larger input image resolution like Monkey and LLaVA-Next to build more powerful tabular MLLMs.

Hours of babysitting       Month     Hours       Normbor     50       December     57       January     36       February     68       March     61       April     45       May     55       June     54	<b>2</b>	The range of the numbers is from 50 to 54 hours. To solve this problem, we need to find the average hours of babysitting for each month. We can do this by dividing the total hours of babysitting by the number of months in the year. Here are the steps: 1. Find the total hours of babysitting: "markdown Total hours of babysitting = 555
Table title: Hours of babysitting Math word problem: Carson looked at his calendar to figure out how much time he spent babysitting each month. What is the range of the numbers? Solve the above problem based on the table information. Let's think step by step. The final result should be presented in the JSON format of ("answer": " <your answer="">"). Read the numbers from the table. 50, 57, 36, 68, 61, 45, 55, 54 First, find the greatest number. The greatest number is 68. Next, find the least number. The least number is 36. Subtract the least number from the greatest number: 68 - 36 - 32 The range is 32. Thus, the final answer is ("answer": "32").</your>		2. Divide the total hours by the number of months in the year: "markdown Number of months = 365 Hours per month = Total hours of babysitting / Number of months = 555 / 365 = 0.1894229999999997 3. Convert the result from seconds to hours: "makefile Total hours of babysitting in hours = 0.1894929999999997 \\* 60 + 0.1894929999999999 3. 4. Print the answer in the desired format: "makefile Total hours of babysitting in hours = 8.309999999999999
<ul> <li>To find the range of the numbers, we need to identify the maximum and minimum values from the given data and then subtract the minimum value from the maximum value (the highest number of hours).</li> <li>Find the maximum value (the highest number of hours).</li> <li>Calculate the difference between the maximum and minimum values.</li> <li>Let's identify the values from the table:</li> <li>Maximum value (highest number of babysiting hours): 61 (March) Minimum value (lowest number of babysiting hours): 36 (February) Now, let's calculate the range:</li> <li>Range = Maximum value - Minimum value</li> <li>Range = 1 - 36</li> <li>Range = 25</li> <li>Therefore, the range of the numbers is 25 hours.</li> <li>The final result in JSON format is:</li> </ul>	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	So the answer is "8.30999999999999". Based on the table information, the range of the numbers is 36 to 54. So, the answer is ["answer": "36 to 54"] ("answer": "45] <55.0>, <68.0>

Figure 16: Case study on the TABMWP benchmark. In this case, the model needs to conduct table-based mathematical reasoning such as finding the largest number in the table or do math computations. Moreover, more external tools like Python Interpreter (Chen et al., 2023b) could be integrated with Table-LLaVA to build MLLM-based table agents.