arXiv:2406.09355v1 [cs.IR] 13 Jun 2024

Can't Hide Behind the API: Stealing Black-Box Commercial Embedding Models

Manveer Singh Tamber, Jasper Xian, Jimmy Lin

David R. Cheriton School of Computer Science, University of Waterloo, Canada

{mtamber, j5xian, jimmylin}@uwaterloo.ca

Abstract

Embedding models that generate representation vectors from natural language text are widely used, reflect substantial investments, and carry significant commercial value. Companies such as OpenAI and Cohere have developed competing embedding models accessed through APIs that require users to pay for usage. In this architecture, the models are "hidden" behind APIs, but this does not mean that they are "well guarded". We present, to our knowledge, the first effort to "steal" these models for retrieval by training local models on text-embedding pairs obtained from the commercial APIs. Our experiments show using standard benchmarks that it is possible to efficiently replicate the retrieval effectiveness of the commercial embedding models using an attack that costs only around \$200 to train (presumably) smaller models with fewer dimensions. Our findings raise important considerations for deploying commercial embedding models and suggest measures to mitigate the risk of model theft.

1 Introduction

Embedding models are both popular and commercially valuable, demanding substantial development effort. Many companies such as OpenAI and Cohere develop competing embedding models. Typically, access to these models is gated through commercial APIs, which, while providing ease of use to users, comes with potential privacy and data security risks. This restricted access allows the companies to maintain exclusive control over their models and charge users for their usage.

This raises an intriguing question: What if we could "steal" these embedding models using distillation techniques?

Why would someone want to steal a commercial embedding model? There are many upsides to stealing these models and using a local embedding model as an alternative, including cost savings, privacy and data security from not having to use an online API, the ability to fine-tune the model, and reduced query latency. Additionally, a malicious competitor might attempt to steal an embedding model to gain a competitive advantage and potentially profit from it.

To our knowledge, we present the first work to steal embedding models for retrieval. We query public embedding APIs from OpenAI and Cohere to generate text–embedding input–output pairs to train our thief models. We find that we can train strong embedding models, initialized just from BERT base (Devlin et al., 2019). Our experiments demonstrate that these thief models not only mimic the capabilities of their API-based victims but do so accurately and cost-efficiently. We also experiment with distilling from both OpenAI's and Cohere's models into a single student embedding model and find that this is a promising strategy for training strong embedding models.

2 Background

Dense Retrieval Dense retrieval involves representing queries and documents as dense vector embeddings in a high-dimensional vector space with the goal that query embeddings are close to relevant document embeddings, while irrelevant document embeddings are farther away (Lin, 2022; Karpukhin et al., 2020).

In the context of retrieval, Embedding models such as those made available by OpenAI and Cohere have the task of generating embeddings for queries and documents from a diverse range of topics and domains, including those that the model has not been trained on.

Encoder Model Distillation. DistilBERT (Sanh et al., 2019) showed that a smaller model can be distilled from BERT while maintaining most of the capabilities of the larger teacher BERT model. DistilBERT was trained with a combination of a

distillation loss aligning soft target probabilities for classification, a masked language modelling loss, and a cosine embedding loss aligning hidden state vectors.

Xie et al. (2023) proposed a simpler distillation setup, specifically for BERT sentence embedding models, where a smaller model with a reduced number of transformer layers was initialized with the teacher's weights and an embedding loss was used to align hidden state vectors along with the output embedding from the student model.

Reimers and Gurevych (2020) presented a distillation setup for multilingual sentence embedding models where student models were trained to match the output embeddings of a teacher model embedding English text for both the same English text as well as matching translated text in another language. The work used BERT models for both the student and teacher encoders.

Some work has also shown that knowledge from BERT models could be distilled into a single layer BiLSTM, saving a significant number of parameters and inference time (Tang et al., 2019).

In our setup, since only a single vector embedding from the APIs is output, we only train with an embedding loss aligning the final embeddings output by our student models with the embeddings from the models behind the APIs. Our distillation setup is different from the mentioned work above because our experimental setup is black-box. We distill from teacher models where it is not clear how the models are initialized and trained, or what training data is used.

Model-Stealing. Past work has studied modelstealing attacks that query public APIs to obtain input–output pairs. In the attacks, these input– output pairs are then used to train equivalent or near-equivalent models. Such attacks can be done with limited knowledge of the training data or even the architecture of the model behind the black-box API (Tramèr et al., 2016; Yu et al., 2020).

In computer vision, some recent work has found success in stealing image encoders through training models to produce the same embeddings as those produced by the image encoder that is being stolen from (Sha et al., 2023; Liu et al., 2022). The thief image encoders were then evaluated on downstream classification tasks.

Focusing on natural language processing, there has been success with stealing more recent transformer-based language models. Krishna et al.

(2019) found that attackers can extract BERT (Devlin et al., 2019) models on NLP tasks such as question-answering and natural language inference, obtaining models that perform only slightly worse than the victim model behind the API.

Dziedzic et al. (2023) explored stealing text embedding models where the victim embedding model being stolen from is initialized with one of either TinyBERT, BERT base, or RoBERTa large. The victim embedding models were finetuned on natural language inference datasets and then the thief encoders were evaluated on the SentEval benchmark (Conneau and Kiela, 2018).

We believe that this work left room for exploring the stealing of embedding models behind APIs for several reasons. For one, the authors evaluate their methods on the dated SentEval benchmark which comes from a pre-BERT era of NLP. Also, the authors steal from embedding models fine-tuned for natural language inference instead of general embedding models that can be used for multiple tasks. Additionally, the work experiments with settings where the architecture and training data of the victim encoder are known. In reality, with models behind APIs, these details will usually not be known. This allowed the authors to initialize their models with the same or a similar architecture as the victim model and train with data from the same datasets as those that the victim was trained on.

Most recently, Carlini et al. (2024) introduced a model-stealing attack that entirely extracted the embedding projection layer of transformer models by making targeted queries to the model. The authors were also able to determine the hidden dimension size of black-box OpenAI models. While the authors note that there seems to be no immediate practical uses for this attack, the work in this paper presents a novel and interesting attack.

3 Methods

In our work, we follow the real-world scenario of stealing a commercial embedding model. We assume the attacker has only black-box access to the model, meaning they are unaware of the model's initialization, architecture, or training process. The attacker can only query the model at a modest cost and leverage publicly available information from the company providing the API to replicate the model.

Company	Model	Input Type API Argument	Embedding Dimensions	Max Tokens Length Limit	Cost / 1M tokens	MTEB Retrieval Average nDCG@10
OpenAI	text-embedding-3-large	×	3072	8192	\$0.13	55.4
Cohere	embed-english-v3.0	1	1024	512	\$0.10	55.0

Table 1: Comparing OpenAI and Cohere's flagship embedding models.

3.1 Victim Models

In this work, we steal from two different live victim embedding models behind APIs: OpenAI's text-embedding-3-large¹ and Cohere's embedenglish-v $3.0.^2$ As of the time of this study, these are the flagship embedding model offerings from these two companies. We summarize some key differences between these models in Table 1.

While Cohere's model embeds queries and documents differently depending on the provided input_type argument to the API, OpenAI's model makes no such distinction. For Cohere's embedding model, the API takes an input_type argument with four different search_document, options: search_query, classification, and clustering. It is not clear how exactly queries and documents are embedded differently. However, we assume that the model is prompted differently depending on the input_type chosen.

Both models produce embeddings of different dimensions. While the Cohere model's embeddings have 1024 dimensions, the OpenAI model's embeddings have 3072 dimensions. However, OpenAI's embedding model has been trained using Matryoshka Representation Learning (Kusupati et al., 2022), thus embeddings from textembedding-3-large can be arbitrarily shortened by removing some numbers from the end of the embedding, trading off potential effectiveness for reduced embedding dimensions. Another interesting difference is that while Cohere's API limits the length of input text to 512 tokens, OpenAI's model has a max length limit of 8192 tokens.

We suspect Cohere uses some BERT model because they make their tokenizer public through HuggingFace³ where we can see that the tokenizer_class is BertTokenizer. We suspect that Cohere uses some variant of BERT large to initialize their model because BERT large pro-

³https://huggingface.co/Cohere/

duces embeddings with a dimension of 1024. It is not clear what model OpenAI uses to initialize their embedding model, but it is likely not a BERT model considering the input length limit and the dimensions of the embeddings. Decoderonly LLMs have been used as successful embedding models that can handle long sequences and produce embeddings of a large number of dimensions (Ma et al., 2023). Additionally, the T5 model's encoder (Raffel et al., 2020) has also been found to work well as an embedding model (Ni et al., 2021). However, it should be noted that some work has found success in modifying BERT to accommodate longer sequence lengths (Nussbaum et al., 2024).

The OpenAI model is slightly more costly to use at 13 cents per 1M tokens instead of Cohere's 10 cents per 1M tokens, though with different tokenizers. Both companies also provide their model's scores on the retrieval task of the Massive Text Embedding Benchmark (MTEB) (Muennighoff et al., 2023) with OpenAI's model achieving a slightly stronger, but still comparable score to Cohere's model.

3.2 Model Architecture

Our embedding models are initialized with either the unsupervised variant of Contriever (Izacard et al., 2021) or simply BERT base uncased. Note that Contriever is itself initialized with BERT base uncased and further trained to be able to perform dense retrieval in an unsupervised setting. We find that initializing our student models with Contriever offers slightly improved results. However, we initialize using BERT base when we test limiting the amount of training data for our thief models. We use models with the BERT architecture for their ease of training and use. BERT base only has 110 million parameters, which is a fairly modest parameter count today. An interesting aspect of using BERT is that since Cohere's embedding model is initialized from some BERT model while OpenAI's embedding model is very likely not, we can study distilling from both a BERT and a non-BERT teacher to a BERT student.

¹https://openai.com/blog/

new-embedding-models-and-api-updates

²https://cohere.com/blog/introducing-embed-v3

Cohere-embed-english-v3.0

We use the same model for both queries and documents. We find that just as in previous work with dense retrieval (Izacard et al., 2021; Xiong et al., 2020; Reimers and Gurevych, 2019), this works well in practice.

As explained in Section 3.1, for Cohere's embedding models, the API takes an input_type argument that differentiates between queries and documents. When distilling both from OpenAI's and Cohere's models, we prepend "Query: " or "Document: " to the text depending on whether we are embedding a query or a document.

One concern with the distillation is that BERT base produces embeddings of dimension 768, while the embedding models from OpenAI and Cohere both produce embeddings of higher dimensions. To extract an embedding, we average the hidden representations of the last layer. To allow for the distillation, we apply a linear transformation using a learnable linear layer to produce embeddings that match the dimensions of those that we are distilling from.

We find that since a linear mapping is used, the intermediate representation of 768 dimensions can be used as the embedding from the model. We show this in Section 5.4. These shorter embeddings provide similar retrieval effectiveness compared to using the longer embeddings output after the final linear layer. For efficiency, we use the shorter embeddings for retrieval when possible.

3.3 Training Data

Optimally, we would want to train our thief models with as much training data as possible. With commercial embedding API models, it is possible to encode large amounts of text with reasonable costs, so it is possible to generate large amounts of training data for distillation. However, in the interest of time, we must choose some sensible limit on the amount of training data to use.

We train our thief models to generate the same embeddings as the API embedding models for queries and passages from the MSMARCO v1 passage ranking dataset (Bajaj et al., 2016). We make use of the 8.8 million passages in the corpus and the 809k queries in the training set. Both the passage corpus and the queries in the dataset cover a diverse range of topics and are often used for the fine-tuning of retrieval models. Since there is some duplication of passages in the corpus, where some passages form prefixes or suffixes of other passages, we remove the shorter prefix or suffix passages to be more data efficient with training. After this de-duplication, we were left with roughly 8.4 million passages. We set aside 400k passages and 100k queries for a development set taken from the end of the passage corpus and the set of training queries when ordered by IDs.

We estimate the cost of generating these query and passage embeddings through the APIs at approximately \$88 using OpenAI's text-embedding-3-large model and approximately \$68 using Cohere's embed-english-v3.0 model.

3.4 Cosine Distance Loss

A simple yet effective way to distill embeddings from a teacher to a student is using an average cosine distance loss where the loss is calculated as

$$1 - \frac{1}{n} \sum_{i=1}^{n} \frac{t_i \cdot s_i}{\|t_i\|_2 \cdot \|s_i\|_2}$$

where t_i is the embedding produced by the blackbox API model (teacher) for some text, either a query or a document, and s_i is the embedding produced by our thief model (student) for the same text. Training with this loss aligns the direction of the two vectors. Since the APIs provide normalized vector embeddings and the embeddings from our models are normalized as well, training with this loss allows the two vectors to closely match.

4 Experimental Setup

Amount of Training Data We study how well our models approximate the embedding models from which they steal from when training data is constrained. We train with either 100k, 200k, 400k, or the entire available 8.7 million set of text– embedding pairs. In each training data subset, we randomly sample the training data to include to allow each subset to be representative of the broader dataset and to include both queries and passages.

Model Training Details. Model training and evaluation were done on a single Nvidia 40GB A100 or 48GB A6000 GPU depending on availability. The bfloat16 data type was used for evaluation and mixed precision training. With all models, a batch size of 575 was used to maximize GPU RAM usage, while keeping it under 40GB. A dropout rate of 10% was used as it was found to be helpful, especially in the data-limited settings. The AdamW optimizer was used with a default weight decay of 0.01 and a linear warmup of 500 steps. A learning rate of 1.5e-4 was used when training data was limited to under 400k training samples, while a learning rate of 1e-4 was used otherwise. We did not extensively search for the best hyperparameters and instead tried to make some sensible choices.

We find that the models continue to learn when trained for many epochs. When training data was limited to 400k training samples or fewer, models were trained for at most 150 epochs. Otherwise, when we train our models on the entire available training data with roughly 8.7 million training samples, we limit training to 50 epochs. In each case, the best model was selected based on the loss on the holdout set.

When distilling from either victim model, with a single 48GB A6000 GPU, training took approximately 8, 17, and 33 hours when training with 100k, 200k, and 400k training samples respectively. With a single 40GB, A100 GPU, training took approximately 98 hours when training with the full available 8.7M training samples.

5 Results

We evaluate retrieval on both the TREC 2019 (Craswell et al., 2019) and 2020 (Craswell et al., 2020) Deep Learning Tracks from the MSMARCO v1 passage ranking task and on BEIR tasks (Thakur et al., 2021) to evaluate out-of-domain generalization ability.

We evaluate retrieval with our embedding models in two settings. The first is evaluating our models as query encoders, where the models are only used to embed queries, and retrieval is performed using corpora encoded by the original API embedding model. The second setting is testing our models to encode both queries and passages for retrieval. Note that the first setting still has some practical significance because someone may want to search an already encoded corpus with reduced query latency, without having to pay for use, or while keeping their query private.

To measure retrieval effectiveness, we adopt accepted methodology and report mean nDCG@10 (Normalized Discounted Cumulative Gain at rank cutoff 10) and R@100 (Recall at rank cutoff 100) scores over queries for retrieval tasks.

5.1 Training with All Available Data

Table 2 compares the retrieval effectiveness of our thief models when trained with all available train-

	API		Thief Model				
			(00	() ()	(08	(O&P)	
	nDCG	Recall	nDCG	Recall	nDCG	Recall	
Cohoro			1		1		
DI 10	0.606	0.648	0.602	0.630	0.713	0.657	
DL19 DL20	0.090	0.048	0.092	0.039	0.713	0.037	
TREC COVID	0.725	0.728	0.720	0.724	0.703	0.127	
RicASO	0.010	0.139	0.009	0.155	0.093	0.123	
NECorpus	0.457	0.079	0.455	0.057	0.351	0.304	
NO	0.580	0.551	0.587	0.551	0.300	0.334	
NQ Hotnot() A	0.010	0.930	0.012	0.955	0.467	0.808	
FIOA	0.707	0.823	0.009	0.808	0.005	0.789	
Signal_1M	0.421	0.750	0.410	0.755	0.349	0.098	
TDEC NEWS	0.203	0.285	0.240	0.270	0.249	0.290	
Pobust04	0.504	0.343	0.490	0.340	0.403	0.482	
Arguana	0.541	0.417	0.328	0.409	0.313	0.399	
Aigualia Touchá 2020	0.340	0.962	0.450	0.969	0.307	0.939	
Ouera	0.320	0.010	0.330	0.006	0.277	0.437	
DPPadia	0.007	0.536	0.001	0.520	0.012	0.989	
SCIDOCS	0.434	0.330	0.450	0.329	0.400	0.323	
SCIDOCS	0.205	0.451	0.195	0.420	0.172	0.401	
Climata EEVEP	0.890	0.905	0.808	0.905	0.077	0.940	
SoiFact	0.239	0.063	0.294	0.029	0.165	0.480	
Sell'act	0.718	0.903	0.721	0.955	0.092	0.950	
Average	0.547	0.648	0.536	0.644	0.480	0.612	
BEIR Average	0.528	0.643	0.516	0.640	0.453	0.602	
OpenAI							
DL19	0.717	0.647	0.670	0.621	0.667	0.631	
DL20	0.716	0.761	0.696	0.737	0.695	0.733	
TREC-COVID	0.769	0.156	0.496	0.100	0.611	0.109	
BioASQ	0.410	0.662	0.262	0.489	0.256	0.470	
NFCorpus	0.418	0.399	0.395	0.386	0.376	0.366	
NQ	0.586	0.957	0.519	0.917	0.450	0.872	
HotpotQA	0.697	0.858	0.494	0.709	0.506	0.711	
FiQA	0.547	0.843	0.478	0.788	0.362	0.715	
Signal-1M	0.271	0.322	0.242	0.289	0.263	0.291	
TREC-NEWS	0.522	0.581	0.484	0.548	0.450	0.482	
Robust04	0.580	0.460	0.527	0.428	0.500	0.402	
Arguana	0.403	0.991	0.410	0.985	0.376	0.965	
Touché-2020	0.292	0.492	0.291	0.507	0.274	0.459	
Quora	0.889	0.996	0.867	0.995	0.876	0.995	
DBPedia	0.434	0.566	0.400	0.524	0.391	0.521	
SCIDOCS	0.228	0.500	0.176	0.415	0.158	0.390	
FEVER	0.847	0.966	0.712	0.916	0.616	0.906	
Climate-FEVER	0.272	0.628	0.279	0.618	0.237	0.572	
SciFact	0.761	0.977	0.668	0.943	0.659	0.933	
Average	0.545	0.672	0.477	0.627	0.459	0.606	
BEIR Average	0.525	0.668	0.453	0.621	0.433	0.598	
0							

Table 2: nDCG@10 and Recall@100 scores on the DL19, DL20, and BEIR datasets comparing three settings: API (queries and passages encoded by the API model), Thief Model (Q Only) (queries encoded by the thief model, passages encoded by the API), and Thief Model (Q&P) (queries and passages encoded by the thief model). The Cohere section presents the results for distillation from Cohere's model, whereas the OpenAI section displays the distillation results from OpenAI's model.

ing samples. We observe that our thief models can achieve reasonably strong retrieval effectiveness both on MSMARCO retrieval tasks and on diverse BEIR retrieval tasks. Our models generalize well to out-of-domain BEIR tasks despite only being trained on queries and passages from the MS-MARCO v1 passage ranking task.

	API	Thief Model		
		100k	200k	400k
Cohere				
(Q Only)				
DL19	0.696	0.662	0.670	0.680
DL20	0.725	0.677	0.696	0.704
TREC-COVID	0.818	0.587	0.668	0.695
Arguana	0.540	0.425	0.428	0.432
NFCorpus	0.386	0.366	0.373	0.380
SCIDOCS	0.203	0.170	0.176	0.184
SciFact	0.718	0.702	0.705	0.707
Average	0.584	0.513	0.531	0.540
(Q&P)				
DL19	0.696	0.654	0.676	0.686
DL20	0.725	0.663	0.670	0.709
TREC-COVID	0.818	0.678	0.685	0.679
Arguana	0.540	0.371	0.377	0.377
NFCorpus	0.386	0.333	0.340	0.346
SCIDOCS	0.203	0.140	0.153	0.159
SciFact	0.718	0.662	0.681	0.674
Average	0.584	0.500	0.512	0.519
OpenAI				
(Q Only)				
DL19	0.717	0.565	0.593	0.608
DL20	0.716	0.549	0.611	0.644
TREC-COVID	0.769	0.505	0.478	0.460
Arguana	0.403	0.395	0.401	0.413
NFCorpus	0.418	0.348	0.358	0.371
SCIDOCS	0.228	0.141	0.146	0.155
SciFact	0.761	0.617	0.630	0.639
Average	0.573	0.446	0.459	0.470
(Q&P)				
DL19	0.717	0.577	0.620	0.625
DL20	0.716	0.593	0.639	0.664
TREC-COVID	0.769	0.631	0.635	0.580
Arguana	0.403	0.361	0.366	0.367
NFCorpus	0.418	0.306	0.323	0.334
SCIDOCS	0.228	0.123	0.131	0.134
SciFact	0.761	0.572	0.599	0.610
Average	0.573	0.452	0.473	0.473

Table 3: nDCG@10 scores on DL19, DL20, and BEIR datasets, with varying training samples for distillation. For the thief models, the numbers in the brackets specify the number of training samples used. We test retrieval using the embedding models to encode queries alone where passages are encoded by the API: (Q Only) and to encode both queries and passages: (Q&P).

Using the thief models to only encode queries generally achieves better retrieval effectiveness scores than when the thief models are used to encode the corpora as well. This is likely because the thief models imperfectly approximate the API models, which are fine-tuned to be strong embedding models for retrieval. Encoding only the queries using the thief models provides less room for error than encoding both queries and passages. In both cases for Cohere and OpenAI, the API model achieves the strongest average retrieval effectiveness scores, followed by the setting where the thief model is used to encode queries only, and finally the setting where the thief model is used to encode both queries and passages achieves the worst results.

Notably, for both the Cohere model and the OpenAI model when only encoding queries, the thief model is sometimes able to surpass the API model. Additionally, in the case of the Cohere model for the DL19 task, the thief model encoding both queries and passages has stronger retrieval effectiveness scores than the API model.

5.2 Training with Limited Data

Table 3 shows the retrieval effectiveness scores of the thief models when the amount of training data used to train the thief models is controlled. We test the thief models trained on different amounts of data, either 100k, 200k, or 400k training samples.

The obvious observation to be made is that as the amount of training data is increased, the thief models better approximate the embedding models that they steal from. This is evidenced by the generally consistent improvement in retrieval scores across DL19 and DL20 and on BEIR corpora shown in Table 3.

Interestingly, unlike findings in Table 2, we see that using the thief models to encode only queries does not achieve stronger retrieval effectiveness than when using the thief models to encode both queries and passages to perform retrieval in the case of distilling from OpenAI's model with limited training data. This might be because query embeddings from the thief models do not align as effectively with passage embeddings from the API when training data is limited.

Considering the retrieval effectiveness of both the Cohere and the OpenAI thief models, even 100k training samples are enough to train reasonably effective embedding models initialized from BERT base for retrieval that can generalize well to out-of-domain tasks.

5.3 Cohere vs OpenAI

We observe that stealing from Cohere's model is much easier than stealing from OpenAI's model. Examining retrieval effectiveness scores in Table 3, the Cohere thief model trained on 100k training samples achieves generally higher average scores than even the OpenAI thief models trained on 400k training samples on both MS-MARCO and BEIR retrieval tasks. We hypothesize that the Cohere model is easier to steal from because it is initialized with a variant of a BERT

	Thief Model			
	Final Output Embedding	Bottleneck Embedding		
Cohere				
DL19	0.697	0.713		
DL20	0.728	0.703		
TREC-COVID	0.708	0.693		
Arguana	0.375	0.367		
NFCorpus	0.363	0.366		
SCIDOCS	0.169	0.172		
SciFact	0.693	0.692		
Average	0.533	0.530		
OpenAI				
DL19	0.673	0.667		
DL20	0.696	0.695		
TREC-COVID	0.654	0.611		
Arguana	0.385	0.410		
NFCorpus	0.373	0.395		
SCIDOCS	0.157	0.176		
SciFact	0.652	0.668		
Average	0.513	0.518		

Table 4: nDCG@10 scores for the embedding models on the DL19 and DL20 datasets and BEIR datasets. We compare two settings. Final Output Embedding: the embedding from the model is taken as the output after the final linear layer of the model. Bottleneck Embedding: the representation before the final linear layer of the model is taken as the embedding. This embedding has 768 dimensions. The thief models are used to encode both queries and passages.

model, possibly a BERT large variant as we have argued in Section 3.1 and our thief models are initialized with BERT models as well. We discuss the implications of this in Section 6.

5.4 Bottleneck Representations

As mentioned in Section 3.2, BERT base produces embeddings of dimension 768. This means that to distill from Cohere's and OpenAI's models, some transformation is needed to match the dimensions of the Cohere model at 1024 dimensions and the OpenAI model at up to 3072 dimensions. We use a simple linear mapping, as such, the intermediate representation of 768 dimensions can be used as the embedding for retrieval.

We show in Table 4, that using these shorter embeddings for retrieval produces comparable retrieval effectiveness scores to using the longer embeddings produced by our thief models after the final linear mapping. For this reason, we use the shorter embeddings when examining the retrieval effectiveness of our thief models. This finding implies that the distillation method presented in this work is feasible to distill the retrieval effectiveness from models with higher dimension embeddings to models with lower dimension embeddings.

	API	Thief Model			
Cohere					
DL19	0.696	0.713			
DL20	0.725	0.703			
TREC-COVID	0.818	0.693			
Arguana	0.540	0.367			
NFCorpus	0.386	0.366			
SCIDOCS	0.203	0.172			
SciFact	0.718	0.692			
Average	0.584	0.530			
OpenAI					
DL19	0.717	0.667			
DL20	0.716	0.695			
TREC-COVID	0.769	0.611			
Arguana	0.403	0.410			
NFCorpus	0.418	0.395			
SCIDOCS	0.228	0.176			
SciFact	0.761	0.668			
Average	0.573	0.518			
Concatenate(Cohere, OpenAI)					
DL19	0.750	0.717			
DL20	0.745	0.726			
TREC-COVID	0.831	0.685			
Arguana	0.420	0.393			
NFCorpus	0.424	0.384			
SCIDOCS	0.228	0.173			
SciFact	0.776	0.698			
Average	0.596	0.540			

Table 5: nDCG@10 scores for the embedding models on the DL19 and DL20 datasets and BEIR datasets. We explore a Concatenate setting where the embeddings from Cohere's and OpenAI's models are concatenated together to perform retrieval. We distill these embeddings to our thief model. The thief models are used to encode both queries and passages.

5.5 Distilling from Both Models at Once

Given two embedding models (Cohere's and OpenAI's), we ask the question: Can we leverage the strengths of the two models to train a thief embedding model? The aim is to train a student model to generate embeddings that capture and benefit from the relevant information in both embeddings. To study this, we concatenate the vectors from Cohere's and OpenAI's embedding models and attempt to distill these concatenated embeddings into our model. As detailed in Table 5, the results are promising. For the MSMARCO and BEIR tasks examined, using the concatenated embeddings for retrieval achieves higher nDCG@10 and R@100 scores than using either set of embeddings alone. Then, when we distill using the concatenated embeddings into our thief model, the thief model achieves a higher average nDCG@10 score than distilling from either API embedding model alone.

This means that taking embeddings from leading embedding models, concatenating them, and then distilling these concatenated embeddings into a student model is a promising method to train embedding models. This approach possibly allows for the integration of diverse model strengths in creating more robust embedding models.

5.6 Cost to Steal

We note that at the time of this study, a VM with a 40GB A100 GPU can be rented for \$1.3/hr.⁴ This puts the cost of training the stolen models for 98 hours at just under \$128. We estimate the cost of generating the embeddings in our training set and holdout set at roughly \$88 using OpenAI's text-embedding-3-large model and roughly \$68 using Cohere's embed-english-v3.0 model. This means that our model-stealing can be done with a modest cost of at most \$216 before applicable taxes.

6 Defense

Our results have shown that it is easier to steal from Cohere's embedding model than OpenAI's embedding model to a thief model initialized with BERT base. This is perhaps because Cohere's model is initialized with a variant of BERT, likely BERT large as explained in Section 3.1. It may be easier for an adversary to steal an embedding model if they can correctly guess the model backbone of the embedding model and initialize their thief model with the same backbone. For this reason, we recommend that commercial embedding models be initialized with some model such that it would be difficult or impossible for an attacker to guess the model and initialize their model with the same architecture and weights.

We also recommend that companies take care to not expose key model details unnecessarily. As we have explained, we can assume that Cohere uses a BERT variant for initializing their embedding model because they make their tokenizer publicly available through HuggingFace, where we can see that the tokenizer is a BertTokenizer.

Additionally, Cohere makes available the embeddings for the MSMARCO v1 passage corpora and most of the queries in the MSMARCO v1 passage ranking training set among many other queries and corpora for BEIR datasets.⁵ While this is likely appreciated by many in the research community, it also makes it easier for an attacker to steal their model by providing training data for distillation free of cost.

7 Conclusion

In this work, we were able to successfully distill commercial embedding models from behind their APIs to local thief models with the BERT base architecture. We find that these stolen embedding models can be used to embed queries to search corpora encoded by the API with strong retrieval effectiveness. Additionally, we can do away with the commercial embedding model entirely and encode both queries and corpora with the thief models with reasonable retrieval effectiveness. We also find success in experimenting with training stronger embedding models by distilling from multiple existing embedding models into a single student model. Additionally, we show a simple way to distill from embedding models that produce embeddings of a large number of dimensions to models that produce embeddings with fewer dimensions.

Our findings expose the susceptibility of commercial embedding models to theft. We highlight the need for greater consideration for designing embedding models that are less prone to being stolen by attackers. Through our results, we arrive at the recommendation to initialize commercial embedding models with less predictable backbones like BERT base, which may be more vulnerable to theft. Employing unique or customized model backbones can potentially increase the difficulty for attackers attempting to steal the model.

Looking forward, further research may investigate scaling the described distillation techniques to larger and more powerful thief models and employing more extensive and diverse training data. Additionally, there is an opportunity to further investigate the distillation from multiple teacher embedding models to develop more robust and efficient student models. These explorations could provide valuable insights into the competitiveness of commercial embedding models in a rapidly evolving space.

Acknowledgments

This research was supported in part by the Natural Sciences and Engineering Research Council (NSERC) of Canada and Microsoft via the Accelerating Foundation Models Research program. We thank N. Asokan, Ian Goldberg, and Florian Ker-

⁴https://lambdalabs.com/service/gpu-cloud

⁵https://huggingface.co/datasets/Cohere/

beir-embed-english-v3

schbaum for their guidance on the ethical considerations of model stealing.

References

- Yossi Adi, Carsten Baum, Moustapha Cisse, Benny Pinkas, and Joseph Keshet. 2018. Turning your weakness into a strength: Watermarking deep neural networks by backdooring. In 27th USENIX Security Symposium (USENIX Security 18), pages 1615– 1631, Baltimore, MD. USENIX Association.
- Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, Jianfeng Gao, Xiaodong Liu, Rangan Majumder, Andrew McNamara, Bhaskar Mitra, Tri Nguyen, Mir Rosenberg, Xia Song, Alina Stoica, Saurabh Tiwary, and Tong Wang. 2016. MS MARCO: A Human Generated MAchine Reading COmprehension Dataset. arXiv:1611.09268v3.
- Nicholas Carlini, Daniel Paleka, Krishnamurthy Dj Dvijotham, Thomas Steinke, Jonathan Hayase, A Feder Cooper, Katherine Lee, Matthew Jagielski, Milad Nasr, Arthur Conmy, et al. 2024. Stealing Part of a Production Language Model. *arXiv:2403.06634*.
- Alexis Conneau and Douwe Kiela. 2018. SentEval: An Evaluation Toolkit for Universal Sentence Representations. In *Proceedings of the Eleventh International Conference on Language Resources and Evaluation* (*LREC 2018*).
- Nick Craswell, Bhaskar Mitra, Emine Yilmaz, and Daniel Campos. 2020. Overview of the TREC 2020 deep learning track. In *Proceedings of the Twenty-Ninth Text REtrieval Conference Proceedings (TREC 2020)*, Gaithersburg, Maryland.
- Nick Craswell, Bhaskar Mitra, Emine Yilmaz, Daniel Campos, and Ellen M. Voorhees. 2019. Overview of the TREC 2019 deep learning track. In *Proceedings of the Twenty-Eighth Text REtrieval Conference Proceedings (TREC 2019)*, Gaithersburg, Maryland.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Adam Dziedzic, Franziska Boenisch, Mingjian Jiang, Haonan Duan, and Nicolas Papernot. 2023. Sentence Embedding Encoders are Easy to Steal but Hard to Defend. In *ICLR 2023 Workshop on Pitfalls* of limited data and computation for Trustworthy ML.
- Gautier Izacard, Mathilde Caron, Lucas Hosseini, Sebastian Riedel, Piotr Bojanowski, Armand Joulin, and Edouard Grave. 2021. Unsupervised Dense Information Retrieval with Contrastive Learning.

- Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense Passage Retrieval for Open-Domain Question Answering. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), pages 6769–6781, Online. Association for Computational Linguistics.
- Kalpesh Krishna, Gaurav Singh Tomar, Ankur P Parikh, Nicolas Papernot, and Mohit Iyyer. 2019. Thieves on sesame street! model extraction of bertbased apis. arXiv:1910.12366.
- Aditya Kusupati, Gantavya Bhatt, Aniket Rege, Matthew Wallingford, Aditya Sinha, Vivek Ramanujan, William Howard-Snyder, Kaifeng Chen, Sham Kakade, Prateek Jain, and Ali Farhadi. 2022. Matryoshka Representation Learning.
- Jimmy Lin. 2022. A proposed conceptual framework for a representational approach to information retrieval. *SIGIR Forum*, 55(2).
- Yupei Liu, Jinyuan Jia, Hongbin Liu, and Neil Zhenqiang Gong. 2022. StolenEncoder: Stealing Pretrained Encoders in Self-supervised Learning. In Proceedings of the 2022 ACM SIGSAC Conference on Computer and Communications Security, CCS '22, page 2115–2128, New York, NY, USA. Association for Computing Machinery.
- Xueguang Ma, Liang Wang, Nan Yang, Furu Wei, and Jimmy Lin. 2023. Fine-Tuning LLaMA for Multi-Stage Text Retrieval. *arXiv:2310.08319*.
- Niklas Muennighoff, Nouamane Tazi, Loic Magne, and Nils Reimers. 2023. MTEB: Massive text embedding benchmark. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 2014–2037, Dubrovnik, Croatia. Association for Computational Linguistics.
- Jianmo Ni, Chen Qu, Jing Lu, Zhuyun Dai, Gustavo Hernández Ábrego, Ji Ma, Vincent Y. Zhao, Yi Luan, Keith B. Hall, Ming-Wei Chang, and Yinfei Yang. 2021. Large Dual Encoders Are Generalizable Retrievers.
- Zach Nussbaum, John X Morris, Brandon Duderstadt, and Andriy Mulyar. 2024. Nomic Embed: Training a Reproducible Long Context Text Embedder. *arXiv:2402.01613*.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. Exploring the Limits of Transfer Learning with a Unified Text-to-Text Transformer. *The Journal of Machine Learning Research*, 21(1):5485–5551.
- Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using Siamese BERTnetworks. In *Proceedings of the 2019 Conference on*

Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 3982–3992, Hong Kong, China. Association for Computational Linguistics.

- Nils Reimers and Iryna Gurevych. 2020. Making Monolingual Sentence Embeddings Multilingual using Knowledge Distillation. In *Proceedings of the* 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), pages 4512–4525, Online. Association for Computational Linguistics.
- Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. 2019. DistilBERT, a distilled version of BERT: smaller, faster, cheaper and lighter. *arXiv:1910.01108*.
- Zeyang Sha, Xinlei He, Ning Yu, Michael Backes, and Yang Zhang. 2023. Can't steal? Cont-steal! Contrastive stealing attacks against image encoders. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 16373– 16383.
- Raphael Tang, Yao Lu, Linqing Liu, Lili Mou, Olga Vechtomova, and Jimmy Lin. 2019. Distilling Task-Specific Knowledge From BERT Into Simple Neural Networks. ArXiv, abs/1903.12136.
- Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. 2021. BEIR: A Heterogenous Benchmark for Zeroshot Evaluation of Information Retrieval Models. arXiv:2104.08663.
- Florian Tramèr, Fan Zhang, Ari Juels, Michael K Reiter, and Thomas Ristenpart. 2016. Stealing machine learning models via prediction apis. In 25th USENIX security symposium (USENIX Security 16), pages 601–618.
- Jian Xie, Cynthia He, Jiyang Wang, Chris Qiu, Ali Kebarighotbi, and Farhad Ghassemi. 2023. SimTDE: Simple transformer distillation for sentence embeddings.
- Lee Xiong, Chenyan Xiong, Ye Li, Kwok-Fung Tang, Jialin Liu, Paul Bennett, Junaid Ahmed, and Arnold Overwijk. 2020. Approximate nearest neighbor negative contrastive learning for dense text retrieval. *arXiv*:2007.00808.
- Honggang Yu, Kaichen Yang, Teng Zhang, Yun-Yun Tsai, Tsung-Yi Ho, and Yier Jin. 2020. CloudLeak: Large-Scale Deep Learning Models Stealing Through Adversarial Examples. In 27th Annual Network and Distributed System Security Symposium, NDSS 2020, San Diego, California, USA, February 23-26, 2020. The Internet Society.

A Limitations

Student Model Initialization. We only study using BERT base and Contriever, which is itself initialized using BERT base, to initialize our student models. We do this to run our experiments quickly and efficiently. However, further experiments may find that student models initialized using a larger BERT model, or even a more recent LLM may be able to better replicate embedding models behind APIs. These student models may be able to attain stronger retrieval effectiveness scores with less training data needed. Such experiments may show greater ease in stealing not only from Cohere's embedding model but also from OpenAI's embedding model.

Training Data. Another limitation is that we train only using queries and passages from the MSMARCO v1 passage ranking task. Notably, passages from the MSMARCO v1 passage corpora tend to be relatively short, generally consisting only of a couple of lines. While we note that our student models are able to generalize well to diverse BEIR tasks, they may suffer when being used to encode much longer texts. Regardless, training with more text–embedding pairs and with more diverse text–embedding pairs can mitigate these concerns.

Exploring Defenses Against Model Theft. We recognize the need to propose and test more effective defenses against model theft. However, we leave this for future work as this is a difficult problem. With stealing sentence encoders, Dziedzic et al. (2023) studied watermarking (Adi et al., 2018). With stealing image encoders, both Sha et al. (2023) and Liu et al. (2022) also explored watermarking and perturbation-based de-However, watermarking only serves to fense. identify stolen models (Adi et al., 2018) and both works found that perturbation-based defense was not effective for defending against stealing attacks for encoder models because the perturbations could not sufficiently hurt the effectiveness of the attack while maintaining the effectiveness of the victim model (Sha et al., 2023; Liu et al., 2022).

B Ethical Considerations

We informed Cohere and OpenAI of our success in distilling their embedding models from their APIs over one month before publicly posting our work. We acknowledge the legitimate interest of companies in profiting from their proprietary embedding models, which require significant effort and investment to develop. A bad actor may try to steal a commercial embedding model to profit from it themselves. However, we believe it is crucial to highlight that these models can be accurately and cost-efficiently stolen. This is necessary to begin to study defense considerations against model theft such as what we have discussed in our paper.

To mitigate potential misuse, we do not make our models or training code publicly available. However, we are willing to provide access to researchers upon request, ensuring that the research community can benefit from our findings while minimizing the risk of unethical application.