BREAKING THE ATTENTION BOTTLENECK

GLOBAL CONTEXT AS STATIC ATTENTION REPLACEMENT IN DECODERS

Kalle Johannes Hilsenbek

s2kahils@uni-trier.de

June 18, 2024

ABSTRACT

Attention-based transformers have become the standard architecture in many deep learning fields, primarily due to their ability to model long-range dependencies and handle variable-length input sequences. However, the attention mechanism with its quadratic complexity is a significant bottleneck in the transformer architecture. This algorithm is only uni-directional in the decoder and converges to a static pattern in over-parametrized decoder-only models. I address this issue by developing a generative function as attention or activation replacement. It still has the auto-regressive character by comparing each token with the previous one. In my test setting with nanoGPT this yields a smaller loss while having a smaller model. The loss further drops by incorporating an average context vector. This concept of attention replacement is distributed under the GNU AGPL v3 license at https://gitlab.com/Bachstelze/causal_generation.

Keywords linear attention, transformer, decoder, generative language modeling, GPT

1 Introduction

The advent of attention-based transformer models has catalyzed transformative advancements in the fields of natural language processing, video, and audio processing. Since their introduction, these models have consistently pushed the boundaries of what is achievable in machine learning and artificial intelligence. The work on the Transformer architecture by Vaswani et al. [2023] laid the foundation for a new era in which attention mechanisms enable models to process and understand complex sequential data with an improved accuracy.

One-directional attention models, such as GPTBrown et al. [2020], are commonly employed for instruction-following tasks, highlighting the significance of model scaling in the development of decoder-only architectures. However, this increase of the decoder size leads to computational demands, a "lost-inthe-middle"-effect of accessible input informations Liu et al. [2023] and an informationless redundant attention pattern (see figure 1 on the right) Hilsenbek et al. [2024]. Hence, instruction-tuned GPTs only store information in the fully connected linear feed-forward layers. They model information mostly linear Hernandez et al. [2024]Razzhigaev et al. [2024] and represent abstract concepts linearly Park et al. [2023]. Therefore, instruction GPTs can be seen as advanced multi-layer perceptrons and generative key-value memories Geva et al. [2021]. The paper "Transformers are Multi-State RNNs" proposes that transformers can be viewed as a type of recurrent neural network (RNN) with multiple states Oren et al. [2024]. Traditionally, transformers and RNNs are seen as distinct architectures. Transformers rely on self-attention mechanisms to handle dependencies between input tokens, while RNNs auto-regressive process sequences step-by-step. However, transformers can be interpreted as multi-state RNNs, where each layer in a transformer manages a set of hidden states, much like an RNN but with multiple-state representations.

Layer 31, Head 31	
<\$>	<\$>
Gener	Gener
ate	ate
a	a
positive	positive
review	review
for	for
a	a
place	place

Figure 1: This attention pattern is repeated in all heads of instruction-tuned GPTs. Each token has a uniform distribution over all previous tokens as a consistent auto-regressive activation. While the quadratic complexity of attention is clobbered by large tech companies with a destructive amount of resources, it poses significant challenges for the broader research community. Therefore, the resource-intensive nature of these models has prompted the exploration of more efficient transformer variants. For example, "Your Transformer is Secretly Linear" reveals a novel linear characteristic in transformer decoders, suggesting that their operation may be more linear than previously assumed. This study introduces a cosine-similarity-based regularization to reduce layer linearity, improving performance metrics on benchmarks like Tiny Stories and SuperGLUE Razzhigaev et al. [2024]. In contrast, "Not All Language Model Features Are Linear" argues that certain features of language models resist linear simplification, highlighting the need for a nuanced approach to optimization Engels et al. [2024].

In this paper, I try to explore the limitations and challenges associated with current transformer models, particularly focusing on the "attention bottleneck". This bottleneck arises from the quadratic complexity of the attention mechanism, which can hinder the scalability and efficiency of transformer models when processing long sequences. I will examine simple techniques aimed at breaking this bottleneck, paving the way for more efficient and scalable transformer-based solutions. By addressing these challenges, I aim to contribute to the ongoing evolution of transformer models, ensuring their accessibility and efficacy within the open-source community.

2 Related work

In the field of language modeling, linear attention mechanisms have been developed to address quadratic complexity and keep the dynamic parameterized behaviorWu et al. [2021]Katharopoulos et al. [2020]Schlag et al. [2021]Zhai et al. [2021]Nguyen et al. [2022]Arora et al. [2023]Lee et al. [2024] Peng et al. [2023]Peng et al. [2024]. These methods aim to make attention computation more efficient in terms of both memory and computational resources, allowing transformers to handle longer sequences effectively Buckman and Gelada [2024]. E.g. by representing keys and queries with kernel feature maps, it enables the use of associative properties to simplify the computation Shen et al. [2022]. New approaches have further optimized the computation by employing kernel tricks for different memory components within GPUs to enhance execution speed and efficiency Qin et al. [2024]Sun et al. [2024]. Furthermore, a linear transformation by an unparameterized Fourier Transform can encode language with a reduction in accuracy Lee-Thorp et al. [2022]. There are many more attempts to optimize attention besides its linearization Tay et al. [2022]Hosseini and Hosseini [2024]Munkhdalai et al. [2024]. E.g. FlashAttention is introduced as a new standard method to compute attention exactly and efficiently. The method is designed to address the inefficiencies in memory and operations from the input to the output that are common in traditional attention mechanisms Dao et al. [2022].

There are also parameter-free attention approaches with convolutional neural nets (CNN) in vision processing Körber [2022] Shi et al. [2023] Yang et al. [2021] Guo et al. [2022] Wan et al. [2023]. While they don't explicitly delve into language modeling, the concepts of parameter-free attention mechanisms have relevant implications for this domain. Similar to how they aim to simplify attention in CNNs, parameter-free attention mechanisms in language models can reduce the computational load and memory requirements. This makes training and inference more efficient, particularly beneficial for large-scale and resource-intensive language models.

3 Method

In this section, I describe the cross-entropy loss divergence as a measurement between the standard attention and my concept of recurrence and global context as static attention replacement in nanoGPT. A small setting is used with a block size of 64, a batch size of 12, 4 layers, an embedding size of 128, no dropout, and 4 heads for attention. The only difference to the hyperparameters in the ReadMe is the longer iteration and learning rate decay iteration number of 5000 instead of 2000 to see that the results also hold for a longer trainingKarpathy [2023]. The small nanoGPT configuration has a number of 0.8 million parameters. Those parameters accumulate from 802,944 decayed parameter tensors and 1,152 non-decayed parameter tensors. This amount is reduced to 0.6 million without the attention parameters of the key, value, and query matrices. The quarter smaller size comes from the total 606,336 parameters of decayed parameter tensors in my static attention approach. A comparison of the different concepts is made by distinguishing the loss curve of the training on the tiny Shakespeare dataset Karpathy [2015].

This Shakespeare dataset is so small that the middle model size of nanoGPT overfits with 10.65 million number of parameters. The middle-sized setting has 6 layers, 6 attention heads, an embedding size of 384, batch size of 64 and also a learning-rate of 1e-3. My concept is also applied in this middle-sized setting to evaluate its performance in an over-parameterized setting.

4 Results

The auto-regressive attention can be replaced by static functions without parameters by mimicking its equal distribution over the previous tokens (see figure 1 in the introduction). This can achieved by returning the maximum value of all dimensions of the current token and its precursor. The first token remains unchanged by this vector manipulation. Such a simple concept already achieves a smaller loss value with a smaller model size at once, while reducing the computational cost. This finding is significant at the start of the training and aligns with the further process (see figure 2). Causal attention has a validation loss of 1.692, whereas my approach has a difference of 0.054 with a loss of 1.638 in the end. Minimizing with the previous token yields a nearly identical loss of 1.635. Training fluctuation could be a plausible explanation for the tiny loss difference between maximization and minimization with the previous token.



Figure 2: The training and validation loss curve of the standard attention and recurrent maximization as well as minimization.

The integration of an average context vector as reference yields an even further improvement of the auto-regressive maximization loss down to 1.557 respectively to 1.555 for the minimization. This drop of around 0.135 from the standard attention loss is attained by the additional averaging of all input vectors and an additional comparison of all tokens to this reference vector. Calculating the mean between vectors seems to signal a complementary signal to the maximization or minimization. Only calculating the mean with the previous token performs between the standard attention and the discrete auto-regressive optimization (see figure 3).



Figure 3: The validation loss curve of the standard attention and recurrent methods with an average context.

In the over-parameterized setting the validation loss curve of the standard attention increases after a fast drop of the validation the loss to a local optimum. This can be mitigated by reducing the batch size from 64 to 16, which yields a slightly better validation loss for attention (see figure 4) that is continuously decreasing. Replacing the attention module with my recursive function shows a similar over-fitting behaviour (see the curve of "causal_min" in figure 4). This over-fitting can be avoided by leveraging my generative function as activation in the fully-connected feedforward

network. This complementary approach stabilized and improves the training even with the bigger batch size of 64 (see the "causal_context_attention"curve in figure 4). Though the activation replacement increases the computational cost from 500ms to around 575ms per iteration and the 2.5GB GPU-RAM to 3.6GB. This increase is caused by the 4 times up-scaling of the inner dimension of the perceptron. The replaced GELU function is activated before the down-scaling the normal embedding size. Leaving the inner dimension unchanged reduces the cost of the generative activation to 2.2GB GPU-RAM and an iteration time of 325ms while having similar results to the upscaled version (see the "causal_context_simple_inner_attention"-curve in figure 4). My generative activation can also be placed before the first linear computation to keep the larger inner dimensions with the GELU-activation.



Figure 4: The validation loss curve of the standard attention and recurrent methods with an average context in the middle Shakespeare setting of nanoGPT.

5 Disussion

In "Multilayer feedforward networks are universal approximators" it is demonstrated that perceptrons can approximate any continuous functionHornik et al. [1989]Cybenko [1989]. This result is often referred to as the Universal Approximation Theorem and it could also describe the generative pretrained transformers. The feedforward neural network seems to be the crucial component within the GPT architecture by considering the static help function of attention in decoders.¹ Therefore it should be possible to apply all of the Universal Approximation Theorem to decoder-only models. Attention can be seen as an activation function for the perceptron Neo et al. [2024]. Non-linear activation functions (like static attention) enable the network to approximate complex functions. The generative power comes with such non-linearity and model size.

An open question is the combination of the different algorithm variants at many possible positions and furthermore the integration of my concept into other architectures like encoder-decoder models or plain MLPs Bengio et al. [2003]. Moreover, the context vector could be gated with external resources, e.g. for nearest neighbor speculative decodingLi et al. [2024]. This could enhance the model's ability to incorporate external knowledge dynamically, improving its overall contextual understanding and decision-making capabilities while keeping a low computational complexity.

6 Conclusion

In this paper, I presented an efficient attention replacement for the decoder module that addresses some of the key challenges faced by traditional attention mechanisms. My proposed method can significantly reduce the computational complexity and resource requirements while maintaining or even improving the language modeling. The amount of operations is linear with the sequence length and increases by a logarithmic factor with the self context vector. The complexity can be brought down to O(1) and O(log(n)) for the averaging over all tokens in parallel. This makes it particularly suitable for deployment in environments with limited computational resources and hopefully helps to reduce the destructive impact on our nature.

By leveraging a generative help function, my approach not only simplifies the model architecture but also enhances interpretability and transparency. This aligns with the growing demand for explainable AI systems that can provide

¹There is a discussion in BertViz about this redundant pattern: https://github.com/jessevig/bertviz/issues/128

insights into their decision-making processes. The empirical results demonstrate so far that my method achieves competitive modeling, which still has to be proven in standard settings on downstream tasks.

I am pleased to distribute this work under the GNU affero general public lisence version 3 ("GNU AGPL v3 license") at https://gitlab.com/Bachstelze/causal_generation to ensure that the research community can freely access, combine and build upon my findings. This open-access approach fosters collaboration and innovation, encouraging a development, which is aligned with humanistic values.

References

- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need, 2023.
- Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners, 2020.
- Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts, 2023.
- Kalle Hilsenbek, Hyunjun Park, Gerti Sana, and Phillip Schmitz. Explainable attention in instruction-tuned models, 2024.
- Evan Hernandez, Arnab Sen Sharma, Tal Haklay, Kevin Meng, Martin Wattenberg, Jacob Andreas, Yonatan Belinkov, and David Bau. Linearity of relation decoding in transformer language models, 2024.
- Anton Razzhigaev, Matvey Mikhalchuk, Elizaveta Goncharova, Nikolai Gerasimenko, Ivan Oseledets, Denis Dimitrov, and Andrey Kuznetsov. Your transformer is secretly linear, 2024.
- Kiho Park, Yo Joong Choe, and Victor Veitch. The linear representation hypothesis and the geometry of large language models, 2023.
- Mor Geva, Roei Schuster, Jonathan Berant, and Omer Levy. Transformer feed-forward layers are key-value memories, 2021.
- Matanel Oren, Michael Hassid, Yossi Adi, and Roy Schwartz. Transformers are multi-state rnns, 2024.
- Joshua Engels, Isaac Liao, Eric J. Michaud, Wes Gurnee, and Max Tegmark. Not all language model features are linear, 2024.
- Chuhan Wu, Fangzhao Wu, Tao Qi, Yongfeng Huang, and Xing Xie. Fastformer: Additive attention can be all you need, 2021.
- Angelos Katharopoulos, Apoorv Vyas, Nikolaos Pappas, and François Fleuret. Transformers are rnns: Fast autoregressive transformers with linear attention, 2020.
- Imanol Schlag, Kazuki Irie, and Jürgen Schmidhuber. Linear transformers are secretly fast weight programmers, 2021.
- Shuangfei Zhai, Walter Talbott, Nitish Srivastava, Chen Huang, Hanlin Goh, Ruixiang Zhang, and Josh Susskind. An attention free transformer, 2021.
- Tan Nguyen, Richard G. Baraniuk, Robert M. Kirby, Stanley J. Osher, and Bao Wang. Momentum transformer: Closing the performance gap between self-attention and its linearization, 2022.
- Simran Arora, Sabri Eyuboglu, Aman Timalsina, Isys Johnson, Michael Poli, James Zou, Atri Rudra, and Christopher Ré. Zoology: Measuring and improving recall in efficient language models, 2023.
- Heejun Lee, Jina Kim, Jeffrey Willette, and Sung Ju Hwang. SEA: Sparse linear attention with estimated attention mask. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=JbcwfmYrob.
- Bo Peng, Eric Alcaide, Quentin Anthony, Alon Albalak, Samuel Arcadinho, Stella Biderman, Huanqi Cao, Xin Cheng, Michael Chung, Matteo Grella, Kranthi Kiran GV, Xuzheng He, Haowen Hou, Jiaju Lin, Przemyslaw Kazienko, Jan Kocon, Jiaming Kong, Bartlomiej Koptyra, Hayden Lau, Krishna Sri Ipsit Mantri, Ferdinand Mom, Atsushi Saito, Guangyu Song, Xiangru Tang, Bolun Wang, Johan S. Wind, Stanislaw Wozniak, Ruichong Zhang, Zhenyuan Zhang, Qihang Zhao, Peng Zhou, Qinghua Zhou, Jian Zhu, and Rui-Jie Zhu. Rwkv: Reinventing rnns for the transformer era, 2023.

Bo Peng, Daniel Goldstein, Quentin Anthony, Alon Albalak, Eric Alcaide, Stella Biderman, Eugene Cheah, Xingjian Du, Teddy Ferdinan, Haowen Hou, Przemysław Kazienko, Kranthi Kiran GV, Jan Kocoń, Bartłomiej Koptyra, Satyapriya Krishna, Ronald McClelland Jr. au2, Niklas Muennighoff, Fares Obeid, Atsushi Saito, Guangyu Song, Haoqin Tu, Stanisław Woźniak, Ruichong Zhang, Bingchen Zhao, Qihang Zhao, Peng Zhou, Jian Zhu, and Rui-Jie Zhu. Eagle and finch: Rwkv with matrix-valued states and dynamic recurrence, 2024.

Jacob Buckman and Carles Gelada. Linear Transformers Are Faster After All, 2024.

- Zhuoran Shen, Mingyuan Zhang, Haiyu Zhao, Shuai Yi, and Hongsheng Li. Efficient attention: Attention with linear complexities, 2024.
- Krzysztof Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Davis, Afroz Mohiuddin, Lukasz Kaiser, David Belanger, Lucy Colwell, and Adrian Weller. Rethinking attention with performers, 2022.
- Zhen Qin, Weigao Sun, Dong Li, Xuyang Shen, Weixuan Sun, and Yiran Zhong. Lightning attention-2: A free lunch for handling unlimited sequence lengths in large language models, 2024.
- Weigao Sun, Zhen Qin, Dong Li, Xuyang Shen, Yu Qiao, and Yiran Zhong. Linear attention sequence parallelism, 2024.
- James Lee-Thorp, Joshua Ainslie, Ilya Eckstein, and Santiago Ontanon. Fnet: Mixing tokens with fourier transforms, 2022.
- Yi Tay, Mostafa Dehghani, Dara Bahri, and Donald Metzler. Efficient transformers: A survey, 2022.
- Mehran Hosseini and Peyman Hosseini. You need to pay better attention: Rethinking the mathematics of attention mechanism, 2024.
- Tsendsuren Munkhdalai, Manaal Faruqui, and Siddharth Gopal. Leave no context behind: Efficient infinite context transformers with infini-attention, 2024.
- Tri Dao, Daniel Y. Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. Flashattention: Fast and memory-efficient exact attention with io-awareness, 2022.
- Nils Körber. Parameter-free average attention improves convolutional neural network performance (almost) free of charge, 2022.
- Yuxuan Shi, Lingxiao Yang, Wangpeng An, Xiantong Zhen, and Liuqing Wang. Parameter-free channel attention for image classification and super-resolution, 2023.
- Lingxiao Yang, Ru-Yuan Zhang, Lida Li, and Xiaohua Xie. Simam: A simple, parameter-free attention module for convolutional neural networks. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 11863–11874. PMLR, 18–24 Jul 2021. URL http://proceedings.mlr.press/v139/yang210.html.
- Ziyu Guo, Renrui Zhang, Longtian Qiu, Xianzheng Ma, Xupeng Miao, Xuming He, and Bin Cui. Calip: Zero-shot enhancement of clip with parameter-free attention, 2022.
- Cheng Wan, Hongyuan Yu, Zhiqi Li, Yihang Chen, Yajun Zou, Yuqing Liu, Xuanwu Yin, and Kunlong Zuo. Swift parameter-free attention network for efficient super-resolution, 2023.
- Andrej Karpathy. nanogpt: The simplest, fastest repository for training/finetuning medium-sized gpts. https://github.com/karpathy/nanoGPT, 2023. Commit on Feb 27, 2024.
- Andrej Karpathy. char-rnn. https://github.com/karpathy/char-rnn, 2015.
- Kurt Hornik, Maxwell Stinchcombe, and Halbert White. Multilayer feedforward networks are universal approximators. *Neural Networks*, 2(5):359–366, 1989. ISSN 0893-6080. doi:https://doi.org/10.1016/0893-6080(89)90020-8. URL https://www.sciencedirect.com/science/article/pii/0893608089900208.
- George Cybenko. Approximation by superpositions of a sigmoidal function. math cont sig syst (mcss) 2:303-314. *Mathematics of Control, Signals, and Systems*, 2:303–314, 12 1989. doi:10.1007/BF02551274.
- Clement Neo, Shay B. Cohen, and Fazl Barez. Interpreting context look-ups in transformers: Investigating attention-mlp interactions, 2024.
- Yoshua Bengio, Réjean Ducharme, Pascal Vincent, and Christian Janvin. A neural probabilistic language model. J. Mach. Learn. Res., 3(null):1137–1155, mar 2003. ISSN 1532-4435.
- Minghan Li, Xilun Chen, Ari Holtzman, Beidi Chen, Jimmy Lin, Wen tau Yih, and Xi Victoria Lin. Nearest neighbor speculative decoding for llm generation and attribution, 2024.