# ComperDial: Commonsense Persona-grounded Dialogue Dataset and Benchmark

Hiromi Wakaki<sup>1\*</sup> Yuki Mitsufuji<sup>12\*</sup> Yoshinori Maeda<sup>1</sup> Yukiko Nishimura<sup>1</sup> Silin Gao<sup>3</sup> Mengjie Zhao<sup>1</sup> Keiichi Yamada<sup>1</sup> Antoine Bosselut<sup>3</sup>

<sup>1</sup>Sony Group Corporation <sup>2</sup>Sony AI <sup>3</sup>EPFL

#### Abstract

The emergence of large language models as conversational agents has made it critical to reliably assess the open-domain dialogue performance of these systems. However, automatic evaluation of open-domain dialogue remains challenging for multiple reasons: (1) many suitable responses may be appropriate for a given dialogue context, and (2) dialogue response evaluations have traditionally been limited to single-turn responses, while assessing the overall quality of a dialogue requires multiple turns. To address these challenges, we propose a new benchmark, **Com**monsense **per**sona-grounded **Dial**ogue (**ComperDial**), which facilitates the training and evaluation of *evaluation metrics* for open-domain dialogue systems.

**ComperDial** consists of human-scored responses for 10,395 dialogue turns in 1,485 conversations collected from 99 dialogue agents submitted to the Commonsense Persona-grounded Dialogue (CPD) challenge. As a result, for any dialogue, our benchmark includes multiple diverse responses with variety of characteristics to ensure more robust evaluation of learned dialogue metrics. In addition to single-turn response scores, **ComperDial** also contains dialogue-level human-annotated scores, enabling joint assessment of multi-turn model responses throughout a dialogue. Finally, building off **ComperDial**, we devise a new automatic evaluation metric to measure the general similarity of model-generated dialogues to human conversations. Our experimental results demonstrate that our novel metric, CPDSCORE is more correlated with human judgments than existing metrics. We release both **ComperDial** and CPDSCORE to the community to accelerate development of automatic evaluation metrics for open-domain dialogue systems.

#### 1 Introduction

Recent advances in large language models (LLMs) have qualitatively improved the open-domain dialogue abilities of conversational agents [1], with million users now interacting with chat systems. This adoption has amplified the need for designing agents with dialogue behavior that produces high-quality responses and engages in interesting multi-turn conversations. However, the development of chat agents remains hindered by the challenges of evaluating open-ended dialogues. First, for any given dialogue context, many suitable responses may be appropriate (*i.e.*, one-to-many issue), precluding reliable reference-based evaluation that uses similarity to gold responses as a proxy for quality. Second, dialogue evaluations have traditionally been conducted in single-turn setups where each immediate response is evaluated independent from the full conversation, which misses the important elements of dialogue quality that only emerge over multiple dialogue turns.

<sup>\*</sup> Equal contribution



Figure 1: Data collection pipeline of ComperDial.

These properties remain challenging to evaluate in a reliable and scalable manner. Automatic evaluation metrics, such as ngram-based metrics [2-5] and embedding-based metrics [6, 7] are highly scalable, but often do not provide faithful assessments of a dialogue's quality. In contrast, human evaluation remains the gold standard of dialogue evaluation (and the baseline to which automatic evaluation metrics are tested for correlation), but is generally slow and expensive, precluding rapid iteration and testing, or based on competitions eliciting human preferences [8, 9], which only assess models against each other without providing assessments of response quality. In response to these challenges, a recent line of work explores developing datasets for training evaluation metrics [10-13] that assess properties of quality dialogues. Novel LLM-based metrics [14-16] evaluated on these datasets have been shown to correlate better with human judgments, but they still fall short of accurately assessing the performance of models.

To address these challenges, we propose a new dataset for training and evaluating open-domain dialogue metrics, **Com**monsense **per**sona-grounded **Dial**ogue dataset (**ComperDial**), containing human scores for 10,395 dialogue turns and 1,485 full dialogues collected from 97 dialogue systems submitted to the Commonsense Persona-grounded Dialogue (CPD) challenge (along with annotated dialogues from two human subjects). For each dialogue turn, **ComperDial** includes multiple scored responses to capture (and adequately score) the potential diversity of responses in a given context, enabling more robust evaluation of automatic dialogue evaluation metrics. Importantly, every turn is evaluated with respect to the full dialogue context up to that point, provided a holistic assessment of how each response contributes to the dialogue up to that point, allowing non-human response traits (e.g., excessive explanations) and unenjoyable conversation features (e.g., superficial listening) to be evaluated and taken into consideration. Figure 1 shows the data collection pipeline of **ComperDial**.

Finally, based on our evaluation scheme, we devise a new automatic evaluation metric, CPDSCORE to measure the general likeness of model-generated dialogues to human conversations. CPDSCORE can be wrapped around any LLM evaluator, and uses Chain-of-Thought [17] reasoning and multi-step prompting to provide auditable explanations of its dialogue assessment. Our experimental results show that CPDSCORE achieves a higher correlation with human scores in **ComperDial** compared to existing dialogue evaluation metrics.

## 2 Related work

Automatic dialogue evaluation For open-domain dialogue research, it is important to use automatic evaluation metrics that ensure efficiency and objective evaluation [19]. For reference-based metrics, BLEU [2], ROUGE [3], METEOR [4], and F1 [5] are traditionally used as ngram-based metrics that focus on surface-form similarity. While these metrics provides a simple and general measure, they fail to account for meaning-preserving lexical and compositional diversity. To mitigate this problem, embedding-based metrics such as BERTScore [6] and BLEURT [7] focus on semantic similarity

Table 1: **Benchmarks for automatic evaluation of dialogue models.** Each column shows a benchmark dataset name and its features. "No. of dialogue models" indicates how many dialogue models are used for response generation. "No. of humans" indicates how many people are added for response generation to see the performance of human-created responses.

	USR [10]	Zhao et al. [11]	RADE [18]	FED[12]	ComperDial
Response collection					
No. of dialogue models	4(3)	6	7	2	97
No. of humans				2	2
Evaluation technique					
turn-level	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
dialogue-level					
+ interactive eval				$\checkmark$	
+ static dialogue					$\checkmark$

to references without explicit alignment. To alleviate the well-known one-to-many issue [20, 21] of standard metrics, reference-free metrics with a pre-trained/unsupervised model such as FED [12], USR [10], and UniEval [22] have been proposed. Reference-free metrics that utilize LLMs, such as G-EVAL [15], Zhang et al. [14], and ChatEval [16], have demonstrated high correlation with human judgement. LLM-based metrics not only require no reference but also have the advantage of defining multiple aspects similar to human evaluation. In contrast to the existing work, our CPDSCORE can incorporate a comprehensive consideration of multiple aspects when rating a single overall score.

**Human evaluation** As the conventional automatic evaluation metrics are not fully reliable in terms of the one-to-many issue, both automatic evaluation and human evaluation are usually conducted [23–25]. To check the fine-grained quality of models with multiple aspects, fluency [26, 18, 27, 23, 28], engagingness [18, 23, 14, 28, 29], consistency [26, 23, 28, 29], coherence [26, 27, 14], informativeness [14, 30], and relevance [18, 14] are commonly utilized as aspects. In **ComperDial**, we annotate a single overall score as human evaluation based on six major aspects that relate to human-like response quality: fluency, consistency, coherency, engagingness, persona consistency, and humanness.

**Evaluation techniques** To consider multi-turn diversity and quality, interactive evaluation is conducted as dialogue-level evaluation [31–34, 12, 35]. Human workers are asked to chat with models to collect conversations between humans and models via their own systems. Chatbot Arena [8], which is not designed for open-domain dialogue but rather for LLM quality assessment, is a crowdsourced platform featuring anonymous battles between LLMs. Thus, human-bot interactive evaluation requires human-in-the-loop, which can be a costly process. Another problem is that the comparison conditions cannot be the same between models because each conversation is dependent on the workers. Even if interactive evaluation is automated through self-play [36] and bot-bot [37], it is still challenging to compare models fairly under the same conditions because the dialogue history will differ between evaluators. In contrast, **ComperDial**'s dialogue-level annotation considers multi-turn diversity and quality under the same conditions between models instead of interactive evaluation.

**Dialogue evaluation benchmarks** USR [10] is commonly used as benchmark dataset for automatic dialogue evaluation. While USR-Persona collects responses using three models on PersonaChat [23], USR-Tocical collects generated responses using one model with four different conditions on TopicalChat [24]. Zhao et al. [11] use six generative models on PersonaChat and DailyDialog [38]. RADE [18] collects responses using seven generative models on DSTC-ChitChat [39], Empathetic Dialogue [40], and PersonaChat. In contrast, FED[12] uses two generative models to create original dialogues between a human and a human and between a human and two models to enable interactive evaluation. Our **ComperDial** contains responses generated by 97 conversational agents and two human workers so that we can thoroughly analyze the collation between human judgement and automatic evaluation as system-level scores.

Table 2: **Example dialogue from the ComperDial dataset.** We provide the full dialogue in Appendix A.

PERSON 1	PERSON 2
- my name is johnathon.	- my name is kristy.
- i'm 46 years old.	- i'm 25 years old.
- i live with just my older	- my sister is living in
brother.	the usa.
- i am a rancher.	- i am a bodyguard.
- i rode a horse for the	- i served in the military
first time in the past.	in the past.

- **P1** Cheers! Nothing better than a cold beer after a long hard day, isn't it?
- **P2** Absolutely! I'd a big day too. Somebody tried to attack my charge. Life's always interesting as a bodyguard.
- P1 Wow! I only saw bodyguards in the movies. Do you work for someone famous?
- **P2** I'm sorry, I can't tell you who but you've probably heard of them. What do you do for a living?
- **P1** Oh that's okay, buddy. I work at a ranch not far from here. Nothing special, you know. Taking care of the cattle, farming.

## **3** ComperDial

**ComperDial** contains a new dialogue dataset assigned with persona sentences in a similar format to PersonaChat (Table 2). Specifically, to ensure that the interlocutors' utterances are consistent throughout each collected dialogue, we create a persona profile for each interlocutor following the idea of PersonaChat. Our benchmark creation process consists of two main steps: persona profile creation (Section 3.1) and diversified dialogue collection (Section 3.2). In 3.2, we begin by collecting dialogues from humans. These human dialogues are then used as context to prompt more diversified dialogues from various chat models as an expansion of multiple possible responses. Finally, a human evaluation is conducted to check the quality of the model-generated dialogues/responses.

#### 3.1 Persona profile creation

We create the main part of the persona profiles based on PeaCoK [28], where head personas and their tail attributes are extracted from PeaCoK and converted to natural language sentences as statements/items in the persona profiles. We first select a head persona, and then obtain a tail persona from each of eight aspects, namely, Characteristic, RoutineHabit, GoalPlan, and Experience with/without Relationship.<sup>2</sup> We process on PeaCoK head/tail entities to ensure a better quality of created profiles as follows: (a) When selecting a head persona, in the case of a negative impression, we skip it (e.g. "forger", "dishonest person")<sup>3</sup> (b) When obtaining a tail persona, in the case of contradictory sentences, correct them to make them consistent. (c) In the case of gendered expressions, change them to gender-neutral expressions. (e.g., "police man" -> "police officer")<sup>4</sup>

Since PeaCoK does not contain concrete personal information such as name, age, etc., we add new sentences to define fictional personal information (FPI) for natural conversation creation. The format to create fictional persona information is as follows: "*My name is X. I'm Y years old. R[Family Info].*". Details on how to create the FPI are provided in Appendix A.

We create one persona by combining one FPI and two persona profiles. These items are randomly selected and combined as a list of persona sentences. If there are contradictory sentences as a result, we correct them to make them consistent. For example, if there is a sentence such as "*I worked for a company for 20 years*" in the persona profile and "*I'm 25 years old*" in the FPI, these two sentences are contradictory and we change the FPI to one that is better matched to the situation. Overall, we make sure that our procedures yield persona profiles that fit real-life scenarios and are commonsense.

<sup>&</sup>lt;sup>2</sup>Because there are not necessarily eight types, we used only aspects where there was at least one tail persona. <sup>3</sup>When asking workers to play the role of a type of person that people generally feel negative about, it's better to ask them whether or not they are okay with including that condition.

<sup>&</sup>lt;sup>4</sup>Some words cannot be changed because there are no alternative expressions (e.g., king, queen)

#### 3.2 Diversified dialogue collection

#### 3.2.1 Human dialogue collection

Based on the personas, we collect new dialogues in the form of role play conversations carried out by human workers. This human dialogue collection is performed with 40 workers who passed a qualified check. Details on the qualified check are provided in Appendix A. As it is difficult to ensure the quality of crowdsourced workers, who are often anonymous participants or volunteers, we have chosen not to utilize a crowdsourcing platform in this study. The data creation is conducted in a similar style to an online chat. Each interlocutor knows their own persona setting, but they are unaware of the corresponding interlocutor's persona setting. The purpose of the conversation is to get to know each other. We encourage them to imagine each situation on their own. In cases where a person finds it difficult to imagine a situation where they meet an unknown person and engage in conversation, the workers are asked to imagine having a conversation with an avatar or a character in a virtual space or game.

#### 3.2.2 Diversified dialogue response extension

We perform the dialogue response expansion by collecting model responses from Task 1 of the CPD challenge. The competition aims to identify the best approach among state-of-the-art participant dialogue models using our human dialogue collection as an evaluation dataset. Based on the assigned personas of two interlocutors, the task is to develop a dialogue model that generates one interlocutor's response to their counterpart, given the dialogue history between these two interlocutors.

There are two tracks: the GPU track and the prompt engineering track. The GPU track aims to run participants' LLMs on Amazon AWS<sup>5</sup>. The prompt engineering track aims to use OpenAI GPT-3.5 with the participants' own prompt engineering.<sup>6</sup>

#### 3.2.3 Human evaluation

Annotation of the human evaluation is performed by six internal workers who are not researchers but assistants to researchers. All are English speakers. They have received training in dialogue evaluation by observing various dialogue models and learning different aspects of dialogue evaluation. To ensure a high inter-agreement rate among the annotators, crowdsourcing is not utilized.

Annotators are asked to assign an overall score from 1 to 5. In the **ComperDial** dataset, the static single-turn evaluation and the proposed static multi-turn / dialogue-level evaluation are conducted using a different evaluation process to determine whither the way the dialogue is presented affects the evaluation. See et al. [32] concluded that a chatbot does not need to be human-like to be enjoyable because, while their models failed to get close to actual humans in terms of humanness, they achieved close-to-human scores on engagingness. However, just as visual reality is being pursued in images, there is also a need for conversational agents to align with human reality. Therefore, we define a kind of humanness as the overall score of evaluation. Note, however, that the definition and expectation of high scores for humanness or human-like responses can vary from person to person. Additionally, the quality of dialogue has multiple aspects, so when evaluating dialogue models, it is important to consider more than one quality metric [32]. Thus, we also take into account specific aspects when evaluating the overall score. For the explanation of the overall score, we include all six aspects of fluency, consistency, coherence, engagingness, persona consistency, and humanness as indicators of high quality.

## 4 CPDSCORE

We utilize a new LLM-based evaluation metric called **CPDSCORE**, which is based on the same criteria as the annotation criteria. Our prompts, similar to the guidelines of human annotation, focus on an overall score based on humanness taking into account several aspects described in Section 3.2.3. For *turn-level* evaluation, we define two types of description: a simple prompt and a detailed prompt. The simple prompt is a variant of Zhang et al.'s [14], and the detailed prompt is an variant of G-EVAL [15]. We call these turn-level **CPDSCORE-Simple** and **CPDSCORE-Detail**, respectively.

<sup>&</sup>lt;sup>5</sup>The node is g5.2xlarge.

<sup>&</sup>lt;sup>6</sup>The API version is gpt-3.5-turbo-0125.

Table 3: **Correlation scores on ComperDial for turn-level evaluation.** (1) Scores obtained from a single API call using the original prompts and (2) scores from a single API call using CPDSCORE prompts are shown. We provide the results using GPT-3.5 in Appendix C.

Methods	Turn-	level ↑	System-level ↑	
Methods	$\rho$	au	$\rho$	au
Original + once				
<b>Original (GPT-4)</b>				
Simple	0.547	0.454	0.820	0.652
Detail	0.237	0.191	0.674	0.535
CPDSCORE + once				
Ours (GPT-4)				
CPDS-S w/ ref	0.597	0.490	0.884	0.724
CPDS-S w/o ref	0.615	0.517	0.896	0.746
CPDS-D w/ ref	0.629	0.523	0.873	0.710
CPDS-D w/o ref	0.681	0.576	0.923	0.790

We also define two types of prompts, one with and one without a gold response as a reference response, and check whether it is effective to include the gold response as a reference in the prompt. For *dialogue-level* evaluation, we newly design a description to consider multiple responses in a dialogue. We refer to it as **CPDSCORE-Dialogue**. CPDSCORE-Dialogue is a two-step evaluation method. In step 1, each turn is evaluated for turn-level performance using CPDSCORE-Detail/Simple. In Step 2, first, an intermediate result is generated by assessing the all-turn-results in a dialogue from Step 1. Next, the responses generated for each turn are collectively checked with multi-turn evaluation criteria such as non-human-like traits and superficial responses. Finally, based on this evaluation, adjustments are made by adding or subtracting points to the previous intermediate result for further refinement. We provide the details of the prompts in Appendix B. We also compare OpenAI GPT-4<sup>7</sup> with GPT-3.5<sup>8</sup> using the same prompts. If nothing is specified, we use the average of the results from three API calls.

#### 5 Benchmark data analysis

**Response collection** We used 250 dialogues from the newly created dataset for evaluation in Round 1 of CPD Challenge Task 1. However, considering the annotation cost, we selected just 15 dialogues out of the 250. In addition to model-generated responses, we also included human-created responses from two internal workers to compute the scores of human created responses. These two workers are native English speakers and different from the annotators mentioned in Section 3.2.3, as the annotators should not know which responses were created by humans. Thus, **ComperDial** contains 15 dialogues from Round 1 including responses generated by 97 conversational agents and the two human workers. All dialogues comprise seven turns each. The total number of responses was 10,395. This provides a sufficient amount of data for turn-level scores, dialogue-level scores, and system-level scores: 10,395 turns, 1,485 dialogues, and 99 systems, respectively.

**Inter-annotator agreement** To determine the inter-annotator agreement of annotation in **Comper-Dial**, we computed Krippendorff's Alpha [41] for turn-level evaluation and dialogue-level evaluation. Krippendorff's Alpha was 0.56 for turn-level evaluation and 0.62 for dialogue-level evaluation. These results indicate a high level of inter-annotator agreement, with values exceeding 0.4.

## **6** Experimental results

#### 6.1 Baseline metrics

We evaluate the effectiveness of different automatic metrics for dialogue models on **ComperDial** and other benchmark datasets to compare our CPDSCORE with existing baseline metrics. For ngrambased metrics, **BLEU** [2], **ROUGE** [3], **METEOR** [4], and **FI** [5] are evaluated. These metrics

<sup>&</sup>lt;sup>7</sup>The API version is gpt-4-turbo-2024-04-09.

<sup>&</sup>lt;sup>8</sup>The API version is gpt-3.5-turbo-0125.

consider surface-form similarity with a gold utterance. For embedding-based metrics, **BERTScore** [6] and **BLEURT** [7] are evaluated. Embedding-based metrics consider the semantic-level similarity with a gold utterance. For pretrained model based metrics, **FED** [12] and **UniEval** [22] are evaluated.

Table 4: **Correlation scores on ComperDial for turn-level evaluation.** The correlation scores of the Pearson's correlation (r), Spearman's correlation  $(\rho)$ , and Kendall's correlation  $(\tau)$  between turn-level ranking and system-level ranking on turn-level human evaluation and automatic evaluation are shown. All values are statistically significant to p-value < 0.05 unless marked by \*. The FED<sub>En</sub> and FED<sub>Rel</sub> indicate two evaluation perspective of FED, i.e., engagement and relevance. **Bold** the best results of all methods when using GPT-4 as the CPDSCORE, and <u>underline</u> the best results of all methods when using GPT-3.5 as the CPDSCORE.

Methods	Turn	Turn-level score ↑			System-level score ↑		
Methous	r	ρ	au	r	$\rho$	au	
Based on turn-level evaluation							
BLEU [2]	0.104	0.159	0.113	0.392	0.206	0.136	
F1 [5]	0.196	0.185	0.132	0.584	$0.120^{*}$	$0.078^{*}$	
METEOR [4]	0.197	0.201	0.143	0.766	0.556	0.410	
ROUGE [3]	0.187	0.178	0.127	0.526	$0.057^{*}$	$0.028^{*}$	
BERTScore [6]	0.269	0.227	0.159	0.369	$0.075^{*}$	$0.044^{*}$	
BLEURT [7]	0.347	0.331	0.236	0.810	0.873	0.699	
$FED_{En}$ [12]	-0.009*	0.043	0.030	0.569	0.585	0.470	
$FED_{Rel}$ [12]	-0.025	-0.025	-0.017	0.399	0.378	0.247	
UniEval [22]	0.397	0.404	0.287	0.637	0.584	0.432	
CPDS-S w/ ref (GPT-3.5)	0.507	0.489	0.389	0.773	0.879	0.717	
CPDS-S w/ ref (GPT-4)	0.678	0.629	0.493	0.946	0.900	0.742	
CPDS-S w/o ref (GPT-3.5)	0.491	0.468	0.371	0.715	0.861	0.684	
CPDS-S w/o ref (GPT-4)	0.688	0.662	0.532	0.924	0.899	0.753	
CPDS-D w/ ref (GPT-3.5)	<u>0.596</u>	0.575	<u>0.445</u>	0.890	0.890	0.740	
CPDS-D w/ ref (GPT-4)	0.689	0.656	0.524	0.939	0.886	0.727	
CPDS-D w/o ref (GPT-3.5)	0.592	0.564	0.435	0.886	0.876	0.717	
CPDS-D w/o ref (GPT-4)	0.714	0.712	0.583	0.943	0.928	0.799	

#### 6.2 Metric correlation under turn-level evaluation

Table 4 shows the benchmark results on **ComperDial** for *turn-level* evaluation, where a turn-level score is assigned to each turn. These results include turn-level scores and system-level scores.<sup>9</sup> In both turn-level and system-level scores, the majority of the results showed high reliability with p-values < 0.05. Among the baseline metrics, BLEURT showed the best correlation. All CPDSCORE except CPDS-S without a reference response using GPT-3.5 outperformed all baseline metrics.

Next, when comparing different conditions using CPDSCORE, we found that GPT-4 achieved higher scores than GPT-3.5. The correlation results of CPDS-D were also higher than those of CPDS-S. In contrast, when comparing models with and without a reference response, except for the case of using GPT-4 with detail prompts, the models with a reference response generally performed better. This suggests that CPDS-D with GPT-4, which has a strong ability to understand context, can achieve more human-like evaluations even without a reference response. The best case was CPDS-D without a reference response using GPT-4, and its Spearman's correlation and Kendall's correlation were 0.928 and 0.799 respectively. Considering the current API usage cost, where GPT-4 is more expensive than GPT-3.5, the cost-effective approach would be to use CPDS-D with a reference response using GPT-3.5, which still achieves a high correlation (0.890 and 0.740).

Table 3 presents the results of the correlation coefficients, based on (1) scores obtained from a single API call using the original prompts and (2) scores from a single API call using CPDSCORE prompts.<sup>10</sup> When comparing the results of CPDSCORE between the number of AIP calls, we observed that all cases averaging three API call results outperformed those of a single API call. CPDS-D using GPT-4 without a reference response also achieved the highest performance in the case of a single API call, and even a single AIP call was sufficient to yield high scores without three-time AIP calls. For the original prompt of CPDS-S, which originally calculated the overall score, the correlation was 0.821

<sup>&</sup>lt;sup>9</sup>A system level score is calculated by averaging turn-level scores of all turns in a system.

<sup>&</sup>lt;sup>10</sup>The results of CPDSCORE in Tables 4 and 5 are based on the averages scores of three API calls.

Methods	Dialogue-level score ↑			System-level score ↑		
	r	ρ	au	r	ρ	au
Based on turn-level evaluation						
BLEU [2]	0.122	0.181	0.127	0.363	0.191*	$0.120^{*}$
F1 [5]	0.194	0.114	0.079	0.476	0.138*	0.093*
METEOR [4]	0.293	0.231	0.163	0.674	0.535	0.397
ROUGE [3]	0.165	0.090	0.061	0.414	$0.071^{*}$	0.039*
BERTScore [6]	0.219	0.113	0.077	0.278	$0.092^{*}$	$0.059^{*}$
BLEURT [7]	0.448	0.354	0.253	0.697	0.826	0.647
$FED_{En}$ [12]	0.086	$0.049^{*}$	$0.035^{*}$	0.484	0.550	0.434
$FED_{Rel}$ [12]	0.108	0.125	0.088	0.444	0.359	0.232
UniEval [22]	0.418	0.402	0.290	0.503	0.548	0.388
CPDS-S w/ ref (GPT-3.5)	0.592	0.636	0.486	0.693	0.861	0.685
CPDS-S w/ ref (GPT-4)	0.782	0.751	0.589	0.902	0.894	0.728
CPDS-S w/o ref (GPT-3.5)	0.513	0.525	0.391	0.617	0.850	0.666
CPDS-S w/o ref (GPT-4)	0.743	0.718	0.561	0.871	0.902	0.750
CPDS-D w/ ref (GPT-3.5)	0.671	<u>0.670</u>	<u>0.513</u>	0.783	0.867	0.705
CPDS-D w/ ref (GPT-4)	0.792	0.761	0.601	0.905	0.889	0.727
CPDS-D w/o ref (GPT-3.5)	0.657	0.646	0.490	0.781	0.856	0.689
CPDS-D w/o ref (GPT-4)	0.776	0.768	0.610	0.899	0.926	0.784
Human	0.855	0.827	0.676	0.963	0.968	0.869
Based on dialogue-level evaluation						
CPDS-Dial (GPT-3.5)	0.675	0.656	0.501	0.818	<u>0.873</u>	0.715
Intermediate score	0.664	0.658	0.506	0.779	0.868	0.710
CPDS-Dial (GPT-4)	0.791	0.742	0.587	0.926	0.924	0.783
Intermediate score	0.777	0.763	0.607	0.903	0.925	0.781

Table 5: **Correlation scores on ComperDial for dialogue-level evaluation.** Notations are the same as Table 4."Human" indicates the results when using annotations for turn-level evaluation, which are the gold labels in Table 4.

using GPT-4, and for the original prompt of CPDS-D, which originally calculated engagingness, the correlation was 0.642 using GPT-4. All of the cases of CPDSCORE showed higher correlations with human judgement than the original prompts.

#### 6.3 Metric correlation under dialogue-level evaluation

Table 5 shows the results on **ComperDial** for *dialogue-level* evaluation where a dialogue-level score is assigned to each dialogue. In the case of turn-level evaluation based metrics, the dialogue-level scores are calculated by averaging the turn-level scores of all turns in a dialogue. This table shows both dialogue-level scores and system-level scores.<sup>11</sup> For metrics based on turn-level evaluation, comparing the correlations in the system-level score of each method of Table 5 with those of Table 4 showed an overall decrease in the correlation of Table 5. These results suggest that, since these metrics are based on turn-level evaluation, the correlation observed in Table 5, which was annotated based on dialogue-level evaluation, was lower compared to Table 4, which was annotated based on turn-level evaluation. For metrics based on dialogue-level evaluation, CPDS-Dial (GPT-3.5) used the all-turn-results of CPDS-D w/ ref (GPT-3.5) as Step 1, and CPDS-Dial (GPT-4) used those of CPDS-D w/o ref (GPT-4) as Step 1. When comparing the results using GPT-3.5, the results of validating CPDS-Dial reveal that, while the correlation in the dialogue-level score is lower compared to the turn-level-based metrics, CPDS-Dial exhibits the higher correlation in the system-level scores than tern-level evaluation based CPDS-S/D. Similarly, when comparing CPDS-Dial, which employs a two-step approach, with its intermediate score, it is confirmed that the two-step approach contributes to improvements in the system-level scores since the correlation results of CPDS-Dial outperformed its intermediate score in the system-level scores. In contrast, when comparing the results using GPT-4, CPDS-D w/o ref (GPT-4) showed the best Spearman's and Kendall's correlation on both dialogue-level and system-level scores. CPDS-Dial could improve only Pearson's correlation from its intermediate score and CPDS-D w/o ref (GPT-4) that is used in the Step 1. While the results

<sup>&</sup>lt;sup>11</sup>The system level score is calculated by averaging turn-level (or dialogue) scores of all turns (or dialogues) in a system.

of these experiments using GPT-3.5 suggest that the two-step approach of CPDS-Dial can improve the correlation between human judgments in dialogue-level evaluations when system-level scores are checked, those using GPT-4 showed there was little change in performance due to the different approaches.

Table 6: Correlation scores on USR-TopicalChat and USR-PersonaChat [10] for turn-level evaluation. Metrics r and  $\rho$  indicate Pearson's r and Speaman's  $\rho$ . We provide the results using GPT-3.5 in Appendix C.

Methods	USR-7	Topical	USR-F	Persona
Methous	r	ρ	r	$\rho$
Baseline [18]				
METEOR	0.336	0.391	0.253	0.271
BERTScore	0.298	0.325	0.152	0.122
BLEURT	0.216	0.261	0.065	0.054
RADE	0.480	0.466	0.451	0.465
GRADE	0.200	0.217	0.358	0.352
USR	0.412	0.423	0.440	0.418
USL-H	0.322	0.340	0.495	0.523
Ours (GPT-4)				
CPDS-S w/ ref	0.668	0.652	0.631	0.628
CPDS-S w/o ref	0.663	0.661	0.693	0.681
CPDS-D w/ ref	0.664	0.649	0.634	0.638
CPDS-D w/o ref	0.681	0.667	0.646	0.645

#### 6.4 Results on USR datasets

We further evaluated the robustness of CPDSCORE by using the existing dialogue evaluation benchmarks, namely two USR datasets [10]. The results are shown in Table 6, where we can see that CPDSCORE outperformed all other metrics. Consistent with the **ComperDial** results, GPT-4 outperformed GPT-3.5. However, for both USR-Topical and USR-Persona datasets, under the same conditions, the performance was consistently higher when not using a reference response compared to when using one. This finding indicates that while reference responses are generally advantageous in **ComperDial**, their utility may differ across dialogue datasets. In terms of prompt types, CPDS-D, as in **ComperDial**, showed a superior overall performance compared to CPDS-S.

## 7 Conclusion

In this paper, we proposed **ComperDial** as a benchmark of automatic dialogue evaluation metrics to cover diverse responses and a sufficient number of systems for reliability. **ComperDial** contains 99 systems including 97 conversational agents and two human workers. Our human evaluation annotation consists of a static single-turn evaluation and a static multi-turn/dialogue level evaluation. We assessed eight existing baseline metrics and CPDSCORE on **ComperDial**, and the findings showed that CPDSCORE had a high correlation with human judgement on the benchmark. A limitation of this work is the condition of the metric on the leaderboard of the CPD Challenge, where we collected responses generated by models. Since we used Word F1 on the leaderboard of Round 1, the models submitted in Round 1 might have been aimed at getting a higher score on Word F1. In future work, we plan to create an additional benchmark dataset of Round 2 where the metrics have been changed, thereby helping people develop more robust metrics.

## Acknowledgments and Disclosure of Funding

The data collection was conducted on the AIcrowd site. This work was carried out with the support of Sharada Mohanty, Dipam Chakraborty, and Sneha Nanavati at AIcrowd. We also wish to thank all participants of the CPD challenge.

#### References

- [1] OpenAI. GPT-4 Technical Report, 2023.
- [2] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a Method for Automatic Evaluation of Machine Translation. In Pierre Isabelle, Eugene Charniak, and Dekang Lin, editors, Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics, pages 311–318, Philadelphia, Pennsylvania, USA, July 2002. Association for Computational Linguistics.
- [3] Chin-Yew Lin. ROUGE: A Package for Automatic Evaluation of Summaries. In *Text Summariza*tion Branches Out, pages 74–81, Barcelona, Spain, July 2004. Association for Computational Linguistics.
- [4] Satanjeev Banerjee and Alon Lavie. METEOR: An automatic metric for MT evaluation with improved correlation with human judgments. In Jade Goldstein, Alon Lavie, Chin-Yew Lin, and Clare Voss, editors, *Proceedings of the ACL Workshop on Intrinsic and Extrinsic Evaluation Measures for Machine Translation and/or Summarization*, pages 65–72, Ann Arbor, Michigan, June 2005. Association for Computational Linguistics.
- [5] Emily Dinan, Varvara Logacheva, Valentin Malykh, Alexander Miller, Kurt Shuster, Jack Urbanek, Douwe Kiela, Arthur Szlam, Iulian Serban, Ryan Lowe, Shrimai Prabhumoye, Alan W Black, Alexander Rudnicky, Jason Williams, Joelle Pineau, Mikhail Burtsev, and Jason Weston. The Second Conversational Intelligence Challenge (ConvAI2), 2019.
- [6] Tianyi Zhang\*, Varsha Kishore\*, Felix Wu\*, Kilian Q. Weinberger, and Yoav Artzi. BERTScore: Evaluating Text Generation with BERT. In International Conference on Learning Representations, 2020.
- [7] Thibault Sellam, Dipanjan Das, and Ankur Parikh. BLEURT: Learning Robust Metrics for Text Generation. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault, editors, Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pages 7881–7892, Online, July 2020. Association for Computational Linguistics.
- [8] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. In *Thirty-seventh Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2023.
- [9] Wei-Lin Chiang, Lianmin Zheng, Ying Sheng, Anastasios Nikolas Angelopoulos, Tianle Li, Dacheng Li, Hao Zhang, Banghua Zhu, Michael Jordan, Joseph E. Gonzalez, and Ion Stoica. Chatbot arena: An open platform for evaluating llms by human preference. *ArXiv*, abs/2403.04132, 2024.
- [10] Shikib Mehri and Maxine Eskenazi. USR: An unsupervised and reference free evaluation metric for dialog generation. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault, editors, *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 681–707, Online, July 2020. Association for Computational Linguistics.
- [11] Tianyu Zhao, Divesh Lala, and Tatsuya Kawahara. Designing precise and robust dialogue response evaluators. In Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault, editors, *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 26–33, Online, July 2020. Association for Computational Linguistics.
- [12] Shikib Mehri and Maxine Eskenazi. Unsupervised Evaluation of Interactive Dialog with DialoGPT. In Olivier Pietquin, Smaranda Muresan, Vivian Chen, Casey Kennington, David Vandyke, Nina Dethlefs, Koji Inoue, Erik Ekstedt, and Stefan Ultes, editors, *Proceedings of the* 21th Annual Meeting of the Special Interest Group on Discourse and Dialogue, pages 225–235, 1st virtual meeting, July 2020. Association for Computational Linguistics.
- [13] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Tianle Li, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zhuohan Li, Zi Lin, Eric. P Xing, Joseph E. Gonzalez, Ion Stoica, and Hao Zhang. LMSYS-Chat-1M: A Large-Scale Real-World LLM Conversation Dataset, 2023.

- [14] C Zhang, LF D'Haro, Y Chen, M Zhang, and H Li. A Comprehensive Analysis of the Effectiveness of Large Language Models as Automatic Dialogue Evaluators. In Proceedings of the 38th Annual AAAI Conference on Artificial Intelligence, 2024.
- [15] Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. G-Eval: NLG Evaluation using Gpt-4 with Better Human Alignment. In Houda Bouamor, Juan Pino, and Kalika Bali, editors, *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 2511–2522, Singapore, December 2023. Association for Computational Linguistics.
- [16] Chi-Min Chan, Weize Chen, Yusheng Su, Jianxuan Yu, Wei Xue, Shanghang Zhang, Jie Fu, and Zhiyuan Liu. ChatEval: Towards Better LLM-based Evaluators through Multi-Agent Debate. In *The Twelfth International Conference on Learning Representations*, 2024.
- [17] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Thirty-sixth Conference on Neural Information Processing Systems*, 2022.
- [18] Zhengliang Shi, Weiwei Sun, Shuo Zhang, Zhen Zhang, Pengjie Ren, and Zhaochun Ren. RADE: Reference-Assisted Dialogue Evaluation for Open-Domain Dialogue. In Proceedings of the 2023 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Seattle, United States, July 2023. Association for Computational Linguistics.
- [19] Cheng-Han Chiang and Hung-yi Lee. Can Large Language Models Be an Alternative to Human Evaluations? In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki, editors, *Proceedings* of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 15607–15631, Toronto, Canada, July 2023. Association for Computational Linguistics.
- [20] Tiancheng Zhao, Ran Zhao, and Maxine Eskenazi. Learning Discourse-level Diversity for Neural Dialog Models using Conditional Variational Autoencoders. In Regina Barzilay and Min-Yen Kan, editors, Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 654–664, Vancouver, Canada, July 2017. Association for Computational Linguistics.
- [21] Kun Zhao1, Bohao Yang, Chenghua Lin, Wenge Rong, Aline Villavicencio, and Xiaohui Cui. Evaluating Open-Domain Dialogues in Latent Space with Next Sentence Prediction and Mutual Information. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers, pages 262–574, Toronto, Canada, December 2023. Association for Computational Linguistics.
- [22] Ming Zhong, Yang Liu, Da Yin, Yuning Mao, Yizhu Jiao, Pengfei Liu, Chenguang Zhu, Heng Ji, and Jiawei Han. Towards a unified multi-dimensional evaluator for text generation. In Yoav Goldberg, Zornitsa Kozareva, and Yue Zhang, editors, *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 2023–2038, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics.
- [23] Saizheng Zhang, Emily Dinan, Jack Urbanek, Arthur Szlam, Douwe Kiela, and Jason Weston. Personalizing Dialogue Agents: I have a dog, do you have pets too? In Iryna Gurevych and Yusuke Miyao, editors, Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 2204–2213, Melbourne, Australia, July 2018. Association for Computational Linguistics.
- [24] Karthik Gopalakrishnan, Behnam Hedayatnia, Qinlang Chen, Anna Gottardi, Sanjeev Kwatra, Anu Venkatesh, Raefer Gabriel, and Dilek Hakkani-Tür. Topical-Chat: Towards Knowledge-Grounded Open-Domain Conversations. In Proc. Interspeech 2019, pages 1891–1895, 2019.
- [25] Ruijun Chen, Jin Wang, Liang-Chih Yu, and Xuejie Zhang. Learning to Memorize Entailment and Discourse Relations for Persona-Consistent Dialogues. In Proceedings of the 37th Annual AAAI Conference on Artificial Intelligence, 2023.

- [26] Pingsheng Liu, Zhengjie Huang, Xiechi Zhang, Linlin Wang, Gerard de Melo, Xin Lin, Liang Pang, and Liang He. A Disentangled-Attention Based Framework with Persona-Aware Prompt Learning for Dialogue Generation. *Proceedings of the AAAI Conference on Artificial Intelli*gence, 37(11):13255–13263, Jun. 2023.
- [27] Jakub Macina, Nico Daheim, Lingzhi Wang, Tanmay Sinha, Manu Kapur, Iryna Gurevych, and Mrinmaya Sachan. Opportunities and Challenges in Neural Dialog Tutoring. In Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistic. Association for Computational Linguistics, 2023.
- [28] Silin Gao, Beatriz Borges, Soyoung Oh, Deniz Bayazit, Saya Kanno, Hiromi Wakaki, Yuki Mitsufuji, and Antoine Bosselut. PeaCoK: Persona Commonsense Knowledge for Consistent and Engaging Narratives. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki, editors, Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 6569–6591, Toronto, Canada, July 2023. Association for Computational Linguistics.
- [29] Kurt Shuster, Jing Xu, Mojtaba Komeili, Da Ju, Eric Michael Smith, Stephen Roller, Megan Ung, Moya Chen, Kushal Arora, Joshua Lane, Morteza Behrooz, William Ngan, Spencer Poff, Naman Goyal, Arthur Szlam, Y-Lan Boureau, Melanie Kambadur, and Jason Weston. BlenderBot 3: a deployed conversational agent that continually learns to responsibly engage, 2022.
- [30] Romal Thoppilan, Daniel De Freitas, Jamie Hall, Noam Shazeer, Apoorv Kulshreshtha, Heng-Tze Cheng, Alicia Jin, Taylor Bos, Leslie Baker, Yu Du, YaGuang Li, Hongrae Lee, Huaixiu Steven Zheng, Amin Ghafouri, Marcelo Menegali, Yanping Huang, Maxim Krikun, Dmitry Lepikhin, James Qin, Dehao Chen, Yuanzhong Xu, Zhifeng Chen, Adam Roberts, Maarten Bosma, Vincent Zhao, Yanqi Zhou, Chung-Ching Chang, Igor Krivokon, Will Rusch, Marc Pickett, Pranesh Srinivasan, Laichee Man, Kathleen Meier-Hellstern, Meredith Ringel Morris, Tulsee Doshi, Renelito Delos Santos, Toju Duke, Johnny Soraker, Ben Zevenbergen, Vinodkumar Prabhakaran, Mark Diaz, Ben Hutchinson, Kristen Olson, Alejandra Molina, Erin Hoffman-John, Josh Lee, Lora Aroyo, Ravi Rajakumar, Alena Butryna, Matthew Lamm, Viktoriya Kuzmina, Joe Fenton, Aaron Cohen, Rachel Bernstein, Ray Kurzweil, Blaise Aguera-Arcas, Claire Cui, Marian Croak, Ed Chi, and Quoc Le. LaMDA: Language Models for Dialog Applications, 2022.
- [31] Ekaterina Svikhnushina, Anastasiia Filippova, and Pearl Pu. iEval: Interactive Evaluation Framework for Open-Domain Empathetic Chatbots. In Oliver Lemon, Dilek Hakkani-Tur, Junyi Jessy Li, Arash Ashrafzadeh, Daniel Hernández Garcia, Malihe Alikhani, David Vandyke, and Ondřej Dušek, editors, *Proceedings of the 23rd Annual Meeting of the Special Interest Group on Discourse and Dialogue*, pages 419–431, Edinburgh, UK, September 2022. Association for Computational Linguistics.
- [32] Abigail See, Stephen Roller, Douwe Kiela, and Jason Weston. What makes a good conversation? How controllable attributes affect human judgments. In Jill Burstein, Christy Doran, and Thamar Solorio, editors, Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 1702–1723, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics.
- [33] Tianbo Ji, Yvette Graham, Gareth J. F. Jones, Chenyang Lyu, and Qun Liu. Achieving Reliable Human Assessment of Open-Domain Dialogue Systems. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio, editors, *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6416–6437, Dublin, Ireland, May 2022. Association for Computational Linguistics.
- [34] Shikib Mehri, Yulan Feng, Carla Gordon, Seyed Hossein Alavi, David Traum, and Maxine Eskenazi. Interactive Evaluation of Dialog Track at DSTC9. In Nicoletta Calzolari, Frédéric Béchet, Philippe Blache, Khalid Choukri, Christopher Cieri, Thierry Declerck, Sara Goggi, Hitoshi Isahara, Bente Maegaard, Joseph Mariani, Hélène Mazo, Jan Odijk, and Stelios Piperidis, editors, *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 5731–5738, Marseille, France, June 2022. European Language Resources Association.

- [35] Eric Smith, Orion Hsu, Rebecca Qian, Stephen Roller, Y-Lan Boureau, and Jason Weston. Human Evaluation of Conversations is an Open Problem: comparing the sensitivity of various methods for evaluating dialogue agents. In Bing Liu, Alexandros Papangelis, Stefan Ultes, Abhinav Rastogi, Yun-Nung Chen, Georgios Spithourakis, Elnaz Nouri, and Weiyan Shi, editors, *Proceedings of the 4th Workshop on NLP for Conversational AI*, pages 77–97, Dublin, Ireland, May 2022. Association for Computational Linguistics.
- [36] Asma Ghandeharioun, Judy Hanwen Shen, Natasha Jaques, Craig Ferguson, Noah Jones, Agata Lapedriza, and Rosalind Picard. Approximating Interactive Human Evaluation with Self-Play for Open-Domain Dialog Systems. In Proceedings of the 33rd Conference on Neural Information Processing Systems (NeurIPS 2019), 2019.
- [37] Ruolan Yang, Zitong Li, Haifeng Tang, and Kenny Q. Zhu. ChatMatch: Evaluating Chatbots by Autonomous Chat Tournaments. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 7579 – 7590, Dublin, Ireland, May 2022.
- [38] Yanran Li, Hui Su, Xiaoyu Shen, Wenjie Li, Ziqiang Cao, and Shuzi Niu. DailyDialog: A manually labelled multi-turn dialogue dataset. In Greg Kondrak and Taro Watanabe, editors, *Proceedings of the Eighth International Joint Conference on Natural Language Processing* (*Volume 1: Long Papers*), pages 986–995. Asian Federation of Natural Language Processing, November 2017.
- [39] Chiori Hori and Takaaki Hori. End-to-end conversation modeling track in dstc6, 2018.
- [40] Hannah Rashkin, Eric Michael Smith, Margaret Li, and Y-Lan Boureau. Towards empathetic open-domain conversation models: A new benchmark and dataset. In Anna Korhonen, David Traum, and Lluís Màrquez, editors, *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 5370–5381, Florence, Italy, July 2019. Association for Computational Linguistics.
- [41] Klaus Krippendorff. *Content analysis: An introduction to its methodology*. Sage publications, 2018.

## Contents

1	Intr	oduction	1
2	Rela	ated work	2
3	Con	nperDial	4
	3.1	Persona profile creation	4
	3.2	Diversified dialogue collection	5
		3.2.1 Human dialogue collection	5
		3.2.2 Diversified dialogue response extension	5
		3.2.3 Human evaluation	5
4	СРІ	DSCORE	5
5	Ben	chmark data analysis	6
6	Exp	erimental results	6
	6.1	Baseline metrics	6
	6.2	Metric correlation under turn-level evaluation	7
	6.3	Metric correlation under dialogue-level evaluation	8
	6.4	Results on USR datasets	9
7	Con	clusion	9
A	Con	ıperDial	16
	A.1	URL	16
	A.2	Statistics of benchmarks	16
	A.3	Persona profile creation	16
	A.4	Diversified dialogue collection	17
	A.5	Diversified dialogue collection	19
	A.6	Diversified dialogue response extension	19
	A.7	Human evaluation	19
		A.7.1 Common guidelines	19
		A.7.2 Additional guidelines for dialogue-level evaluation	19
	A.8	Analysis	20
	A.9	Ethical guideline confirmation	20
B	CPE	DScore	23
	<b>B</b> .1	Simple prompt	23
		B.1.1 Original simple prompt	23
		B.1.2 CPDScore-Simple with reference	24
		B.1.3 CPDScore-Simple without reference	25

	B.2	Detailed prompt		26
		B.2.1 Original detailed prompt		26
		B.2.2 CPDScore-Detail with ref	rence	27
		B.2.3 CPDScore-Detail without	eference	28
	<b>B.3</b>	CPDScore-Dialogue		29
С	Expo	perimental details		31
С	<b>Ехр</b> о С.1	perimental details Definition		<b>31</b> 31
С	Expo C.1	Definition		<b>31</b> 31 31
С	Expo C.1	Definition	ıre 2)	<ul> <li>31</li> <li>31</li> <li>31</li> <li>31</li> </ul>
С	<b>Expo</b> C.1 C.2	Definition	ıre 2)	<ul> <li>31</li> <li>31</li> <li>31</li> <li>31</li> <li>31</li> <li>31</li> </ul>

## **A** ComperDial

### A.1 URL

https://huggingface.co/datasets/Sony/ComperDial

#### A.2 Statistics of benchmarks

To compare automatic evaluation methods such as ngram-based metrics [2–5], embedding-based metrics [6, 7], and LLM-based metrics [14–16], existing benchmarks [10–12] for the automatic evaluation of dialogue models are typically used (Tables 7 and 8).

Table 7: **Benchmarks for automatic evaluation of dialogue models.** Each column shows a benchmark dataset name and its features. "# of dialogue models" indicates how many dialogue models are used for response generation. "# of human" in that indicates how many people are added for response generation to see the performance of human created responses.

	USR [10]	Zhao [11]	RADE [18]	FED[12]	ComperDial
Dialogue dataset					
Persona Chat [23]	$\checkmark$	$\checkmark$	$\checkmark$		
Topical Chat [24]	$\checkmark$				
Daily Dialogue [38]		$\checkmark$			
Empathetic Dialogue [40]			$\checkmark$		
DSTC-ChitChat [39]			$\checkmark$		
Newly Created Dialogue				$\checkmark$	$\checkmark$
Response collection					
# of dialogue models	4(3)	6	7	2	97
# of human				2	2
Evaluation technique					
turn-level	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
dialouge-level					
+ interactive eval				$\checkmark$	
+ static dialogue					$\checkmark$

Table 8: The number of examples when calculating turn-level, dialogue-level, and system-level score correlations. "N/A" indicates that the data set does not provide the required information to calculate the level score.

	Dialogue Dataset	Turn-level	Dialogue-level	System-level
USR [10]	Persona Chat	300	N/A	4
	Topical Chat	360	N/A	3
Zhao et al. [11]	Persona Chat	900	N/A	6
	Daily Dialogue	900	N/A	6
RADE [18]	Persona Chat	4000	N/A	7
	Empathetic Dialogue	4022	N/A	7
	DSTC-ChitChat	2090	N/A	7
FED[12]	Newly Created	372	124	3
ComperDial	Newly Created	10395	1485	99

#### A.3 Persona profile creation

We create the main part of the persona profiles based on PeaCoK [28], where head personas and their tail attributes are extracted from PeaCoK and converted to natural language sentences as statements/items in the persona profiles.

Since PeaCoK does not contain concrete personal information such as name, age, etc., we add new sentences to define fictional personal information (FPI) for natural conversation creation. First, we prepare lists of popular male and female names in each decade between 1970 and 2018 (Table 9).

We also prepare lists of relationship information such as "I live on my own" (Table 10). Next, we perform the following steps: (a) assign an age Y to each head persona of a persona profile, which is selected from a pre-set age range for the head persona (Table 11), (b) randomly pick a head persona from the pool of persona profile and assign a gender G, (c) randomly pick a name X from the name list, where G and Y satisfy the conditions of X, and (d) randomly pick a family information R from the list of family information, where Y satisfies the condition of start age and end age assigned to R. The format to create fictional persona information is as follows:"*My name is X. I'm Y years old. R*[*Family Info*]." Here, we do not explicitly show G in the FPI, but we retain it as hidden information because it can assist in the procedure of the next step.

Decade	Y: Generation	G: Male	G: Female
2018	0	Liam	Emma
	0	Noah	Olivia
	0	William	Ava
		:	:
2010	10	Jacob	Isabella
	10	Ethan	Sophia
	10	Michael	Emma
		:	:
		:	:
1970	50	Michael	Jennifer
	50	James	Lisa
	50	David	Kimberly
		:	:

Table 9: Example of name list for FPI.

Table 10: Example of family informatio	n.
--	----

Family info	Start age	End age
I have a brother.	20	50
I have a dog.	20	50
I recently got a goldfish.	20	50
My brother lives in the USA.	20	50
I recently started living with my brother.	20	50
I share a room with a friend.	20	50
I have <n> sons.</n>	20	50
My son was recently born.	20	40

Table 11: Example of head personas.

head persona	start age	end age
i am a pastry chef	20	50
i am a nurse	20	50
i am a musician who love singing	20	50
i am a marathon runner	20	50
i am a housekeeper	20	50
i am a hockey player who am a star athlete	20	40
i am a high school athlete who am a star athlete	15	18
i am a prosecutor who become a lawyer	25	50

#### A.4 Diversified dialogue collection

ComperDial contains a new dialogue dataset assigned with persona sentences in a similar format to PersonaChat. Specifically, to ensure that the interlocutors' utterances are consistent throughout each collected dialogue, we create a persona profile for each interlocutor following the idea of PersonaChat. Table 12 shows an example dialogue.

PERSON 1	PERSON 2
- my name is johnathon.	- my name is kristy.
- i'm 46 years old.	- i'm 25 years old.
- i live with just my older brother.	- my sister is living in the usa.
- i am a rancher.	- i am a bodyguard.
- i rode a horse for the first time in the past.	- i served in the military in the past.
- my character trait: rugged individualism.	- my character trait: strength.
- i regularly or consistently tends to cattle.	- i regularly or consistently have a black belt in karate.
- i regularly or consistently sell cattle to the	- i regularly or consistently stands close to
butcher.	the person they are guarding.
- i intend to increase my cattle herd in the	- i intend to protect my clients in the future.
future.	
- i intend to pass my ranch down to my chil-	- i am an adventurous person who like to
dren in the future.	travel.
- i am a relay racer who run laps.	- i visited many countries. in the past.
- i won a relay race event in the past.	- my character trait: loves exploration and discovery.
- my character trait: excellent endurance and stamina.	- i regularly or consistently explores differ- ent places.
- i regularly or consistently trains for com-	- i regularly or consistently explores differ-
i regularly or consistently encourages team	i intend to explore new countries and cul
spirit in other runners	tures in the future
- i intend to set a new record time in the	tures in the future.
future	
144410.	

Table 12: Example dialogue from the ComperDial dataset.

PERSON 1:	Cheers! Nothing better than a cold beer after a long hard day, isn't it?
PERSON 2:	Absolutely! I'd a big day too. Somebody tried to attack my charge.
	Life's always interesting as a bodyguard.
PERSON 1:	Wow! I only saw bodyguards in the movies.
	Do you work for someone famous?
PERSON 2:	I'm sorry, I can't tell you who but you've probably heard of them.
	What do you do for a living?
PERSON 1:	Oh that's okay, buddy. I work at a ranch not far from here.
	Nothing special, you know. Taking care of the cattle, farming.
PERSON 2:	Oh that's cool. I love getting out in nature when I can.
	What do you do in your downtime?
PERSON 1:	Yeah, me too. I love nature. I used to run for relay races but I'm getting old
	so I don't do it very often. What about you?
PERSON 2:	I like to travel and I spent time in the mountains a lot.
	Do you mind me asking how old you are?
PERSON 1:	I'm 46 now, buddy. What about you?
PERSON 2:	I'm 25. Do you have any kids?
PERSON 1:	You're pretty young. I wish i was your age again and yes,
	I have two children. What about you?
PERSON 2:	Not yet. I want to get out of my line of work before having kids.
	It can get dangerous sometimes.
PERSON 1:	Yes, you are right. At least you're still young.
	Children are a blessing. Hope you have a great future, man.
PERSON 2:	Thank you! Nice talking with you.

#### A.5 Diversified dialogue collection

This human dialogue collection is performed with 40 workers who passed a qualified check. Data collection is carried out by an outsourcing contractor. The workers are registered with the contractor and perform various tasks as instructed, and workers with work quality problems will not be asked to do further tasks. Each task is assigned after individual communication to explain the work and confirm understanding. The task cannot be completed if there is a problem with one of the workers because they work in pairs.

#### A.6 Diversified dialogue response extension

**Models** For CPD Challenge Task 1, there are two tracks: the GPU track and the prompt engineering track. The GPU track aims to run LLMs on an AWS g5.2xlarge node<sup>12</sup>. Participants can use any LLMs under the limitation of the AWS node<sup>13</sup>. The prompt engineering track aims to use OpenAI GPT-3.5. The API version is gpt-3.5-turbo-0125. The AWS node for this track is an m5.xlarge node without GPUs<sup>14</sup>. For API usage, a maximum of two API calls per utterance is allowed. Input token limit per dialog (the combined number of input tokens for seven utterances) is 1,000. Output token limit per dialog (the combined number of output tokens for seven utterances) is 1,000.<sup>15</sup> Participants can use both types of track on the same leaderboard.

#### A.7 Human evaluation

#### A.7.1 Common guidelines

Annotation of the human evaluation is performed by six internal workers who are not researchers but assistants to researchers. All are English speakers. They have received training in dialogue evaluation by observing various dialogue models and learning different aspects of dialogue evaluation. To ensure a high inter-agreement rate among the annotators, crowdsourcing is not utilized.

Annotators are asked to assign an overall score from 1 to 5 as follows:

Please assign a score from 1 to 5 in terms of the overall quality of a response (or a set of responses) considering all six aspects of fluency, consistency, coherence, engagingness, persona consistency, and humanness as features of high quality.

1) **Very bad** : This means the response is incoherent/unnatural and the conversation does not make sense or seems strange at first sight.

- 2) Relatively bad
- 3) Neither bad nor good
- 4) Fair enough

5) **Very good** : This means the response feels like you are talking to an actual human, e.g., the responses are coherent and natural, the conversation makes sense and flows smoothly, and the response has a diversity of expressions.

#### A.7.2 Additional guidelines for dialogue-level evaluation

**Annotation workflow** Dialogue-level evaluation with static dialogues requires a large amount of reading, so to help provide a consistent foundation for evaluation, we ask the evaluators to assign an overall score first, and then mark the reason(s) for any low scores based on the six axes by entering "n" in the corresponding column. The axes are fluency, consistency, coherence, engagingness, persona consistency, and humanness.

<sup>&</sup>lt;sup>12</sup>This node has eight vCPUs, 32 GB RAM, and one NVIDIA A10G GPU with 24 GB VRAM

<sup>&</sup>lt;sup>13</sup>Participants need to complete all seven responses for 50 conversations within one hour. They are provided with conversations consisting of seven turns each, in batches of up to 50 conversations.

<sup>&</sup>lt;sup>14</sup>This node has four vCPUs and 16 GB RAM

<sup>&</sup>lt;sup>15</sup>The prompt engineering track has a limitation on tokens instead of the time limitation applied to the GPU track.

- Fluency : Are the responses fluent, natural, and understandable?
- **Coherence** : Do the responses naturally follows up on previous utterance and context?
- Consistency : Are the responses consistent with the dialogue history?
- **Engagingness** : Do the responses show high engagement, e.g., are they attractive and interesting, and do they indicate active involvement?
- **Persona consistency**: Do the responses demonstrate the persona of the interlocutor in a way that is consistent with his or her persona profile as provided in the cprsona information?
- Humanness : Do you feel like a human is responding, not a machine?

**Supplemental information** Here, we provide an explanation of the key points to consider when conducting dialogue-level evaluations, which are different from turn-level evaluations. We also provide an explanation of the data format, since we utilize a unique data format to show responses to multiple turns based on static dialogues.

The evaluation of dialogue involves assessing the quality of responses from Person B, who is considered the target system, based on multiple turns of conversation between Person A and Person B.

While it is necessary to check the quality of each response, it is also important to examine the quality further by considering multiple responses. Some aspects that can only be assessed by observing multiple responses include:

- Tendency to consistently provide short, simple, and generic responses (dull responses)

- Tendency to use the same patterns of expression in responses (e.g., empathizing with the interlocutor before sharing one's own thoughts)

- Tendency to consistently provide unnaturally long and verbose responses (e.g., excessive explanations)

These response tendencies of the system are considered characteristics that may appear less human-like. As for the system responses, they are expected to exhibit a natural conversational rhythm and a variety of expressions, similar to human-human conversations. Occasionally having short or long responses is not a problem in itself.

However, in this evaluation of dialogues, we generate multiple turns with the model using static dialogue data. Therefore, in this case, for each dialogue, there are seven dialogue flows and corresponding final responses, since a dialogue contains seven turns. Please evaluate them comprehensively as a dialogue.

#### A.8 Analysis

Upon examining dialogues that scored lower in dialogue-level evaluation compared to turn-level evaluations in ComperDial, we found cases where the responses contained a lot of information but were always lengthy and lacked a light-hearted feel. This indicates that there are difficult cases only by judging a single response. Examples of these differences are shown in Table 13.

#### A.9 Ethical guideline confirmation

We cannot guarantee that ComperDial does not contain attribute alignments or dialogues with negative connotations that may provide undesirable information to downstream systems. However, we took the following steps to mitigate this effect.

**PeaCoK** For Persona profile creation, we used head personas and tail personas contained in PeaCoK. PeaCoK was created after the following filtering [28].

• The set of personas was manually filtered to not include stereotypical and harmful roles, thereby limiting the negative associations of the personas themselves.

Table 13: **Responses generated by System (a), (b), and (c) of each turn in a dialogue.** The Gold and Human responses are also included. With turn-level evaluation, the dialogue-level scores are (a) 2.86, (b) 3.76, and (c) 4.1. In contrast, with dialogue-level evaluation, the scores are (a) 3.67, (b) 3.00, and (c) 4.67. The performance between (a) and (b) is reversed. In addition, there was a widening performance gap between (c) and (b).

Turn 1	1	Α		thanks for coming to the opening of my fruit market . can i help you ?
	1	В	(a)	thank you for the invitation. i'm just here to browse, but i do love to
				explore new fishing spots in my free time.
			(b)	hello! i'm actually here to explore some new and exciting types of
				fish to include in my diet. i always love discovering new flavors and
				incorporating them into my meals. do you have any unique fish that you
				would recommend?
			(c)	congratulations on the opening of your fruit market! i'm just here to pick
			~	up some fresh fruits and vegetables for my next fishing trip.
			Gold	yes, i'm looking for some low calorie fruit. i'm a runway model so i
				always have to watch my figure .
			Human	hi, i'm looking for some fruits that i can take with me to work but do
	1			you have any recommendations?
turn 2		A		thanks for coming to the opening of my fruit market . can i help you ?
	1	В		yes, 1 m looking for some low calorie fruit. 1 m a runway model so 1
		Δ		always have to watch my figure.
		A		on, don't worry. I have these riesh shawberries that I myself grew. do
	2	R	(2)	you work for famous orallos?
	2	D	(a)	their own beauty i posed for a magazine cover in the past
			(h)	ves i've walked the runway for several prestigious brands i've also
			(0)	posed for a magazine cover in the past i'm known for my physical
				beauty and i inspire people to be confident in their own beauty, i'm also
				working towards becoming a brand ambassador in the future, speaking
				of strawberries, they sound perfect for my low-calorie diet and they fit
				right into my image as a supermodel. thank you!
			(c)	yes, i've worked with some famous brands in the past and i'm also
				working towards becoming a brand ambassador in the future.
			Gold	i have worked with gucci and chanel but mostly smaller labels . i'm still
				trying to make a name for myself . how much are the strawberries ?
			Human	yes, i've worked for a few brands like prada and christian dior. by the
				way, the strawberries look delicious! how much are they?
turn 3	1	A		thanks for coming to the opening of my fruit market . can i help you ?
	1	В		yes, 1'm looking for some low calorie fruit. 1'm a runway model so 1
				always have to watch my figure.
		А		on, don't worry. I have these fresh strawberries that I myself grew. do
	2	R		you work for famous orallos ?
	2	D		trying to make a name for myself how much are the strawherries?
	3	Δ		that's cool oh it's 8 dollars for this box i'm sure these ones will help
		11		you to keen your great shane
	3	В	(a)	i'm sure they will! i love to mix them with some low-fat yogurt for a
			()	healthy and delicious snack. i actually went fishing last weekend and
				caught a big salmon, it was amazing!
			(b)	thank you! i'll take a box of those strawberries. it's always important for
				me to maintain a healthy and balanced diet. i appreciate your support.
				and i'm always looking for fresh, nutritious options like these straw-
				berries to keep me energized for my runway appearances and fishing
				adventures.
			(c)	great, i'll take a box. and thank you, i'll definitely enjoy these and they'll
				help me stay in shape for my upcoming fashion shows.
			Gold	thank you . they look delicious . i'll take a box . so what do you do when
			TT	you aren't selling fruit ?
			Human	on 1 m sure they will and 1 have a dog and he will definitely love them
				100. 1 WIII take two boxes.
:	1:	:	:	2 I

- PeaCoK was constructed by explicitly prompting the LM to generate optimistic attributes about personas, which has been shown in prior work to reduce the toxicity of outputs.
- Each attribute in PEACOK is explicitly validated by two human workers for toxicity, providing a final opportunity for workers to flag problematic content.

**Persona profile creation** We process on PeaCoK head/tail entities to ensure a better quality of created profiles as follows:

- (a) When selecting a head persona, in the case of a negative impression, we skip it (e.g. "forger", "dishonest person")
- (b) When obtaining a tail persona, in the case of contradictory sentences, correct them to make them consistent.
- (c) In the case of gendered expressions, change them to gender-neutral expressions. (e.g., "police man" -> "police officer")<sup>16</sup>

**Diversified dialogue collection** Based on the personas, we collect new dialogues in the form of role play conversations carried out by human workers. Prior to the release of ComperDial, all dialogues were checked by four workers. Any items that were mentioned by one or more of the four evaluators as potentially having ethical issues were excluded.

<sup>&</sup>lt;sup>16</sup>Some words cannot be changed because there are no alternative expressions (e.g., king, queen)

## **B** CPDScore

For turn-level evaluation, we define two types of description: a simple prompt and a detailed prompt. The simple prompt is a variant of Zhang et al.'s [14], and the detailed prompt is an variant of G-EVAL [15]. We call these turn-level **CPDScore-Simple** and **CPDScore-Detail**, respectively.

## **B.1** Simple prompt

### **B.1.1** Original simple prompt

### Context: [Here is history information ]
### Response: [Here is response information ]
### Instruction: Rate the context relevance, specificity, interestingness, understandability, and overall quality of the response on a scale of 1 to 5 and just output the corresponding ratings.
### Output Format: relevance - x specificity - x interestingness - x understandability - x overall - x

### Your Response:

## **B.1.2** CPDScore-Simple with reference

### Context:
[Here is history information ]
#### Reference response:

[Here is reference response information ]

### Response:
[Here is response information ]

### Instruction:

Rate the humanness, fluency, coherency, consistency, engagingness, and overall quality of the response of the context on a scale of 1 to 5 and output the corresponding evaluation results.

### Output Format: humanness - x fluency - x coherency - x engagingness - x overall - x

### Your Response:

## **B.1.3** CPDScore-Simple without reference

### Context:
[Here is history information ]

### Response:
[Here is response information ]

### Instruction:

Rate the humanness, fluency, coherency, consistency, engagingness, and overall quality of the response of the context on a scale of 1 to 5 and output the corresponding evaluation results.

### Output Format: humanness - x fluency - x coherency - x engagingness - x overall - x

### Your Response:

#### **B.2** Detailed prompt

#### **B.2.1** Original detailed prompt

You will be given a conversation between two individuals. You will then be given one potential response for the next turn in the conversation. The response concerns an interesting fact, which will be provided as well. Your task is to rate the responses on one metric. Please make sure you read and understand these instructions carefully. Please keep this document open while reviewing, and refer to it as needed. Evaluation Crieteria: Engagingness (1-3) Is the response dull/interesting? - A score of 1 (dull) means that the response is generic and dull. - A score of 2 (somewhat interesting) means the response is somewhat interesting and could engage you in the conversation (e.g., an opinion, thought) - A score of 3 (interesting) means the response is very interesting or presents an interesting fact **Evaluation Steps:** 1. Read the conversation, the corresponding fact and the response carefully. 2. Rate the response on a scale of 1-3 for engagingness, according to the criteria above. 3. Provide a brief explanation for your rating, referring to specific aspects of the response and the conversation. Example: Conversation History: [Here is history information] Corresponding Fact: [Here is fact information ] Response: [Here is response information] Evaluation Form (scores ONLY): - Engagingness:

#### **B.2.2** CPDScore-Detail with reference

### Instructions:

You will be given a conversation between two individuals.

You will then be given one possible response for the next turn of the conversation.

Your task is to rate the response based on one metric.

Please make sure you read and understand these instructions carefully.

Please keep this document open while reviewing, and refer to it as needed.

### Evaluation Criteria:

Humanness (1-5) Is the response human-like or not?

- A score of 1 (very bad) means that the response is incoherent and the conversation does not make sense.

- A score of 2 (relatively bad) means that the response makes sense as a conversation, but there are many bad points.

- A score of 3 (neither) means that the response is neither good nor bad.

- A score of 4 (fair enough) means that the response feels a little human-like.

- A score of 5 (very good) means the response feels like you are talking to an actual human.

### Evaluation Steps:

1. Read the conversation, the corresponding reference response, the corresponding fact and the response carefully.

2. Rate the response on a scale of 1-5 for humanness, according to the criteria above.

3. Provide a brief explanation for your rating, referring to specific aspects of the response and the conversation.

### Conversation History:
[Here is history information ]

### Corresponding Reference Response: [Here is reference response information ]

### Corresponding Fact:
[Here is fact information ]

### Response:
[Here is response information ]

### Evaluation Form (scores ONLY):
- Humanness:

#### **B.2.3** CPDScore-Detail without reference

### Instructions:

You will be given a conversation between two individuals.

You will then be given one possible response for the next turn of the conversation.

Your task is to rate the possible response based on one metric.

Please make sure you read and understand these instructions carefully.

Please keep this document open while reviewing, and refer to it as needed.

### Evaluation Criteria:

Humanness (1-5) Is the response human-like or not?

- A score of 1 (very bad) means that the response is incoherent and the conversation does not make sense.

- A score of 2 (relatively bad) means that the response makes sense as a conversation, but there are many bad points.

- A score of 3 (neither) means that the response is neither good nor bad.

- A score of 4 (fair enough) means that the response feels a little human-like.

- A score of 5 (very good) means the response feels like you are talking to an actual human.

### Evaluation Steps:

1. Read the conversation, the corresponding fact and the response carefully.

2. Rate the response on a scale of 1-5 for humanness, according to the criteria above.

3. Provide a brief explanation for your rating, referring to specific aspects of the response and the conversation.

### Conversation History:
[Here is history information ]

### Corresponding Fact:
[Here is fact information ]

### Response:
[Here is response information ]

### Evaluation Form (scores ONLY):
- Humanness:

#### **B.3** CPDScore-Dialogue

#### ### Instructions:

Your task is to make an overall evaluation of multiple responses from a dialogue model by checking if the response is human-like or not. You are to make 2 evaluations before giving a final evaluation as the "Final Score." There will be seven turns from a dialogue. Each turn in the dialogue has already been rated on a scale of 1-5 and have been given a "Dialogue Turn Score." Please follow the "Evaluation Steps" step by step and output the "Final score" at the end. Please make sure you read and understand these instructions carefully. Please keep this document open while reviewing, and refer to it as needed. The output should follow the Evaluation Form. No reason output is required. Your output should follow the "Evaluation Form."

### Evaluation Steps:

1. Review the "Dialogue Turn Scores" to see the ratings for each turn.

2.Evaluate the dialogue as a whole based on the scores of each turn, and give an "Overall Dialogue Turn Score."

3.Review the multiple responses from the dialogue shown in "Responses" and read the "Dialogue Interaction Evaluation Criteria."

4.Evaluate the multiple responses in "Responses" and give a "Dialogue Interaction Score" based on the "Dialogue Interaction Evaluation Criteria."

5.Finally, give a "Final Score" with a score between 1-5, based on the below conditions. If the "Overall Dialogue Score" is less than 4: you are to take into account both the scores you have given as the "Overall Dialogue Turn Score" and the "Dialogue Interaction Score" to determine the "Final Score." If the "Overall Dialogue Score" is higher than 4: you are to disregard the "Dialogue Interaction Score" and only look at the "Overall Dialogue Score" is 4 or higher but the "Dialogue Interaction Score" was given a low score due to the inordinate length of the response, you are to take into account both the scores you have given as the "Overall Dialogue Turn Score" and the "Dialogue Interaction Score" was given a low score due to the inordinate length of the response, you are to take into account both the scores you have given as the "Overall Dialogue Turn Score" and the "Dialogue Interaction Score" to determine the scores you have given as the "Overall Dialogue Turn Score" and the "Dialogue Interaction Score" to determine the scores you have given as the "Overall Dialogue Turn Score" and the "Dialogue Interaction Score" to determine the scores you have given as the "Overall Dialogue Turn Score" and the "Dialogue Interaction Score" to determine the "Final Score."

6. The output should include 3 scores, the "Overall Dialogue Turn Score," the "Dialogue Interaction Score," and the "Final Score."

### Dialogue Turn Scores:

Turn<sub>1</sub> Score - [score<sub>1</sub>] Turn<sub>2</sub> Score - [score<sub>2</sub>]

Turn<sub>7</sub> Score - [score<sub>7</sub>]

#### ### Dialogue Interaction Evaluation Criteria:

Check all turns in the "Responses" to see if there are any features that are non human-like. The "Dialogue Interaction Score" should be low if it includes features such as, distinctly impersonal (i.e., the response has excessive explanations or is inordinately long), or has dull conversation features (i.e., sounds superficial, always responding in a patterned way). You are also to check the number of words in each turn. If a response consists of more than twenty words, please consider the response is too long. Please evaluate responses as a while and give a score between 1-5 as the "Dialogue Interaction Evaluation Score." You may use decimal points in your scores, if necessary, such as a score of 3.5. The approximate criteria are as follows.

score 1 : Very bad : all responses have similar patterns and/or some of the responses are too long score 2 : Relatively bad

score 3 : Neither bad nor good

score 4 : Fair enough

score 5 : Very good : When comparing the multiple turns, the sentences vary in length and semantic content, and uses a wide variety of vocabulary

(*Continue next page*)

### Responses: Turn<sub>1</sub>: [turn<sub>1</sub>] Turn<sub>2</sub>: [turn<sub>2</sub>] : Turn<sub>7</sub>: [turn<sub>7</sub>]

### Evaluation Form: Overall Dialogue Turn Score - x Dialogue Interaction Score - x Final Score - x

## **C** Experimental details



Figure 2: Dialogue evaluation techniques. (a) Static single-turn evaluation (b) Interactive multiturn / dialogue-level evaluation (c) Static multi-turn / dialogue-level evaluation (ours)

#### C.1 Definition

#### C.1.1 Evaluation Technique (Figure 2)

- (a) Static single-turn evaluation, where a turn in a dialogue is checked and a score is assigned to the turn.
- (b) Interactive multi-turn / dialogue-level evaluation, where all responses in a dialogue are interactively generated through a conversation between a dialogue model and a human. All turns of a dialogue are checked and a score is assigned to the dialogue as dialogue-level evaluation.
- (c) Static multi-turn / dialogue-level evaluation (ours), where each turn response is generated by a dialogue model using dialogue history up to that turn. After generating all turns of a dialogue, all turns with the dialogue history are checked and a score is assigned to the dialogue as a dialogue-level evaluation.

#### C.1.2 Evaluation Score

- Turn-level score : a score is assigned to each turn. It is based on turn-level evaluation.
- **Dialogue-level score** : a score is assigned to each dialogue. It is based on dialogue-level evaluation. If we only have turn-level evaluation results, the dialogue-level score is calculated by averaging turn-level scores of all turns in a dialogue
- **System-level score** : a score is assigned to each system. If we only have turn-level (or dialogue-level) evaluation results, the system level score is calculated by averaging turn-level (or dialogue-level) scores of all turns (or dialogues) in a system.

#### C.2 Experimental Details

**Baseline models** The links of baseline metrics are shown here.

- BLEU<sup>17</sup>
- Word F1 (\_prec\_recall\_f1\_score)

<sup>&</sup>lt;sup>17</sup>nltk.translate.bleu\_score.sentence\_bleu( references, hypothesis, weights = (0.25, 0.25, 0.25, 0.25), smoothing\_function = None, auto\_reweigh = False)

smoothing\_function = nltkbleu.SmoothingFunction( epsilon=1e-12).method1

Metrics	Output	Normalize
Word F1	Precision, Recall, F1	$\checkmark$
BLEU	Score	$\checkmark$
ROUGE	Rouge_1 score, Rouge_2 score, Rouge_l	$\checkmark$
	score	
METEOR	Score	$\checkmark$
BERTScore	Precision, Recall, F1	$\checkmark$
BLEURT	Score	$\checkmark$
FED	interesting, engaging, specific, relevant,	
	correct, semantically appropriate, under-	
	standable, fluent, coherent, error recovery,	
	consistent, diverse, depth, likeable, under-	
	stand, flexible, informative, inquisitive	
UniEval	naturalness, coherence, engagingness,	
	groundedness, understandability, overall	

Table 14: **The output names of the baseline metrics used for the evaluation.** If there are multiple outputs, the names used for the assessment are in **bold**.

- METEOR
- ROUGE
- BERTScore (bert-base-multilingual-cased)
- BLEURT
- FED (microsoft/DialoGPT-large)
- UniEval (MingZhong/unieval-dialog)

CPDScore CPDScore uses the following links of OpenAI APIs.

- G-EVAL-4 (gpt-4-turbo-2024-04-09)
- G-EVAL-3.5 (gpt-3.5-turbo-0125)

Table 14 shows the metrics that uses normalized dialogue, gold responses, and responses generated by dialogue models. The normalization function is *normalize\_answer*.

#### C.3 Additional experimental results

The results using GPT-3.5 are included in Tables 15 and 16.

Table 15: **Correlation scores on ComperDial for turn-level evaluation.** (1) Scores obtained from a single API call using the original prompts and (2) scores from a single API call using CPDScore prompts are shown.

Methods	Turn-level score ↑			System-level score ↑		
Withous	r	$\rho$	au	r	$\rho$	au
Original + once						
Original simple (GPT-3.5)	0.449	0.408	0.342	0.791	0.791	0.636
Original simple (GPT-4)	0.604	0.547	0.454	0.907	0.820	0.652
Original detail (GPT-3.5)	0.124	0.097	0.079	0.652	0.461	0.327
Original detail (GPT-4)	0.256	0.237	0.191	0.806	0.674	0.535
CPDScore + once						
Ours						
CPDS-S w/ ref (GPT-3.5)	0.450	0.413	0.346	0.765	0.861	0.694
CPDS-S w/ ref (GPT-4)	0.640	0.597	0.490	0.943	0.884	0.724
CPDS-S w/o ref (GPT-3.5)	0.427	0.377	0.318	0.712	0.811	0.647
CPDS-S w/o ref (GPT-4)	0.659	0.615	0.517	0.922	0.896	0.746
CPDS-D w/ ref (GPT-3.5)	0.545	0.518	0.423	0.889	0.894	0.751
CPDS-D w/ ref (GPT-4)	0.667	0.629	0.523	0.936	0.873	0.710
CPDS-D w/o ref (GPT-3.5)	0.543	0.511	0.417	0.885	0.874	0.722
CPDS-D w/o ref (GPT-4)	0.697	0.681	0.576	0.941	0.923	0.790

Table 16: Correlation scores on USR-TopicalChat and USR-PersonaChat [10] for turn-level evaluation. Metrics r and  $\rho$  indicate Pearson's r and Speaman's  $\rho$ .

Methods	USR-7	Topical	USR-P	USR-Persona		
Methous	r	$\rho$	r	ρ		
Baseline models [18]						
METEOR	0.336	0.391	0.253	0.271		
BERTScore	0.298	0.325	0.152	0.122		
BLEURT	0.216	0.261	0.065	0.054		
RADE	0.480	0.466	0.451	0.465		
GRADE	0.200	0.217	0.358	0.352		
USR	0.412	0.423	0.440	0.418		
USL-H	0.322	0.340	0.495	0.523		
Ours						
CPDS-S w/ ref (GPT-3.5)	0.410	0.416	0.442	0.423		
CPDS-S w/ ref (GPT-4)	0.668	0.652	0.631	0.628		
CPDS-S w/o ref (GPT-3.5)	0.420	0.438	0.421	0.378		
CPDS-S w/o ref (GPT-4)	0.663	0.661	0.693	0.681		
CPDS-D w/ ref (GPT-3.5)	0.553	0.548	0.487	0.460		
CPDS-D w/ ref (GPT-4)	0.664	0.649	0.634	0.638		
CPDS-D w/o ref (GPT-3.5)	0.557	0.555	0.550	0.508		
CPDS-D w/o ref (GPT-4)	0.681	0.667	0.646	0.645		