Prompts as Auto-Optimized Training Hyperparameters: Training Best-in-Class IR Models from Scratch with 10 Gold Labels

Jasper Xian¹, Saron Samuel², Faraz Khoubsirat¹, Ronak Pradeep¹, Md Arafat Sultan³, Radu Florian³, Salim Roukos³, Avirup Sil³, Christopher Potts², Omar Khattab²

¹University of Waterloo, ²Stanford University, ³IBM Research AI

Abstract

We develop a method for training small-scale (under 100M parameter) neural information retrieval models with as few as 10 gold relevance labels. The method depends on generating synthetic queries for documents using a language model (LM), and the key step is that we automatically optimize the LM prompt that is used to generate these queries based on training quality. In experiments with the BIRCO benchmark, we find that models trained with our method outperform RankZephyr and are competitive with RankLLama, both of which are 7B parameter models trained on over 100K labels. These findings point to the power of automatic prompt optimization for synthetic dataset generation.

1 Introduction

The past few years have witnessed massive improvements in information retrieval (IR) quality, thanks to many ways of applying and supervising pretrained language models (LMs) for IR. However, almost all current IR models, especially those known to generalize well to new long-tail domains, are trained on hundreds of thousands or even millions of queries and relevance judgments. From a scientific perspective, it is unclear if this magnitude of data is necessary for optimizing LMs for tasks like IR. At the same time, from an engineering standpoint, it remains unclear how to best train IR models for extremely long-tail domains or languages for which labeled IR data is scarce.

Motivated by these questions, we study the difficult problem of training an IR system from scratch, given nothing but a text corpus of passages C and as few as 10 relevance judgments. To study this problem with limited confounders, we train only pretrained LMs that have under 100M parameters and have not been explicitly trained on labeled IR datasets like MS MARCO (Bajaj et al., 2016) or undergone any similar supervision to the best of our knowledge.



Figure 1: An overview of the PATH pipeline for training a reranker with synthetic queries. A user only needs to input a prompt with the task description and as few as 10 relevance judgements to achieve strong results.

An increasingly common paradigm to tackle the lack of IR data in a given domain is to use LMs to synthesize hypothetical search queries qthat are derived from passages p in a corpus C. For example, Promptagator (Dai et al., 2023) and UDAPDR (Saad-Falcon et al., 2023) use LMs like GPT-3 and Flan-T5 (Chung et al., 2024) to generate queries. Each query–passage pair $\langle q, p \rangle$ becomes a relevant training item, negative passages are sampled from C, and the resulting dataset is used to train an IR model.

However, such work either uses static prompts for LMs (Promptagator) or constructs prompts in automatic but static ways (UDAPDR). As a result, the LM-based data generation process receives no feedback from the IR model trained. This is a substantial limitation; many IR tasks, like those in BIRCO (Wang et al., 2024) such as ArguAna (Wachsmuth et al., 2018), have nuanced notions of relevance, so simply relying on the priors of an LM for synthesizing queries may not suffice.

To overcome this, we propose **PATH**, for *Prompts as Auto-optimized Training Hyperparameters*, to optimize the prompt used to generate synthetic queries. Figure 1 provides an overview of

PATH. Steps 1–3 represent a typical pipeline for training IR models on synthetic data generated by an LM. Step 4 is the crucial addition: the prompt to the LM is updated using feedback from the reranker evaluation. In this paper, we adopt the simple strategy of having the LM generate candidate modifications of our initial instruction and choosing the one that ultimately leads to the best reranker.

We express PATH in the DSPy programming model (Khattab et al., 2024), which allows us to treat the prompt responsible for synthesizing the queries as a parameter to learn. For optimization, DSPy requires a scalar metric. For the first time, we propose the metric of using the generated outputs of the prompt, i.e., the synthetic queries, to train an IR model and then returning the average quality of the resulting IR model directly as the score. This scoring can use as few as 10 gold labels.

We evaluate this idea using DeBERTa (He et al., 2021) and MiniLM (Wang et al., 2020) on the BIRCO benchmark for difficult and non-traditional IR tasks. We leverage gpt-3.5-turbo for query generation and prompt optimization. We find that applying PATH with 10 positive labels performs very competitively. In particular, averaged in NDCG@10 across tasks and LMs, it outperforms BM25 by 6.0 points, fine-tuned LMs on the 10 positive labels by 6.5 points, and hand-prompting GPT-3.5 for synthetic query generation by 4.5 percentage points. Moreover, our approach performs roughly at the same level of quality as directly training on all available training triples for each task and are competitive with the best available off-the-shelf cross-encoders like MonoT5 and RankLLaMA, which are orders of magnitude larger in both parameter count and training set size.

Preliminaries 2

Given a large corpus of documents \mathcal{D} $\{d_1, d_2, \ldots, d_n\}$ and a query q, a retriever is a model that can find an ordered set S of $k \ll |\mathcal{D}|$ documents that are most *relevant* to q, as measured using some metric(s) of relevance such as nDCG or recall. We focus on the downstream task of reranking the documents in S into a more accurate ordering. In particular, we are interested in training Transformer encoder models as point-wise *rerankers*, i.e. a model \mathcal{R} that can take the query and each document $d_i \in S$ in isolation, $\mathcal{R}(q, d_i)$, and output a scalar score that can be used for reordering S to achieve higher relevance.

Algorithm 1 PATH for training a reranker with a small number, N, of relevance judgments.

- 1: Input: Large Autoregressive Language Model LM
- 2: Input: Small Pretrained Encoder Model Enc
- 3: **Input:** Document Corpus \mathcal{D}
- 4: Input: Number of Trials M, number of negatives m
- 5: **Input:** Relevance Judgments $\mathcal{J} = \{ \langle q_i, d_i, r_i \rangle : i \in [N] \}$
- 6: **Input:** Initial Prompt Instructions \mathcal{I}_0 for query generation 7
- 8: function TRAINRERANKER(Prompt Template P)

```
9٠
             Sample a random subset \mathcal{D}' \subseteq \mathcal{D}, where |\mathcal{D}'| = 1000
10:
             Triplets \mathcal{T} \leftarrow \{\}
11:
             for d^+ \in \mathcal{D} do
```

```
Synthetic Query q \leftarrow \mathbf{LM}.generate(P.format(d))
12:
13:
```

Negatives $d_1^-, \ldots, d_m^- \leftarrow \text{SampleNegatives}(\mathcal{D}, q, d^+)$

```
Extend \mathcal{T} with \{\langle q, d^+, d_i^- \rangle : j \in [m]\}
```

```
15:
        end for
```

14:

```
Reranker \mathcal{R} \leftarrow \mathbf{Enc}.trainOnTriplets(\mathcal{T})
16:
```

```
17:
             return \mathcal{R}
```

```
18:
    end function
```

```
19:
20: function AVGNDCG(\mathcal{R}, \mathcal{J})
```

```
21:
```

```
\begin{array}{l} \mathsf{T} = \{ \ \mathcal{R}.\mathsf{rerank}(q_i, \mathsf{BM25}.\mathsf{retrieve}(q_i)) \colon q_i \in \mathcal{J}.\mathsf{queries}() \ \} \\ \textbf{return} \ \frac{1}{N} \sum_{i=1}^N \ \mathsf{NDCG}(\mathsf{T}_i, \mathcal{R}) \end{array}
22:
```

```
23: end function
```

```
24:
```

```
25: Initialize Attempts List \mathcal{A} \leftarrow \{\}
```

```
26: while i in [M] do
```

```
27:
               \mathcal{P}_i \leftarrow \text{PROPOSENEWPROMPT}(\mathcal{I}_0, \mathcal{A}) \triangleright \text{See Sec 3 for how}
```

```
28:
             \mathcal{R}_i \leftarrow \text{TRAINRERANKER}(\mathcal{P}_i)
29:
              Validation Score s \leftarrow AvgNDCG(\mathcal{R}_i, \mathcal{J})
```

```
30:
                Extend \mathcal{A} with (s, \mathcal{R}_i, \mathcal{P}_i)
```

```
31: end while
```

32. 33: Let the selected reranker be the best-scoring \mathcal{R}_i

When only few labeled query-document pairs are available, synthetic data generation can augment the training dataset of a reranker (Dai et al., 2023; Bonifacio et al., 2022). Canonically, this often involves sampling a subset of the documents in \mathcal{D} randomly and, with some prompt template \mathcal{P} , asking an LM to generate a relevant query q_s for each $d = d^+$ in our sample. Each synthetic query is then paired with its source document to create a (q_s, d^+) positive tuple, which is then augmented by producing a set of m hard negatives $(d_1^-, d_2^-, \ldots, d_m^-)$, sampled from the non-positive top results of an existing retriever. This process outputs a set of tuples $(q_s, d^+, d_1^-, d_2^-, \ldots, d_m^-)$ and uses them to train the reranker.

3 **PATH: Training Rerankers With Optimized Data-Generation Prompts**

Algorithm 1 describes our method for training rerankers using a very small number of taskspecific relevance labels. Our goal is to train reranker $\hat{\mathcal{R}}$ that would have high quality on the (unseen) underlying distribution of \mathcal{J} . Unfortunately, simply training on the labels in (the very few labels in) \mathcal{J} will result in drastic overfitting

(Sec 4). Our algorithm resolves that as follows.

We require access to (i) a large, autoregressive **LM** for prompting and (ii) a small pretrained encoder model **Enc** that we will finetune as a reranker. The algorithm takes as input two task-specific human inputs. (1) A small set, like 10 labels, of relevance judgments \mathcal{J} , each indicating a realistic query and a document that is assigned some relevance grade like 0 (irrelevant) or 3 (perfectly relevant).¹ (2) An initial instruction \mathcal{I}_0 , which may be task-aware, for the **LM** generating queries, e.g. "Given a passage, return a question a user may ask that is answered by this passage".

The core of the algorithm is TRAINRERANKER, a pipeline for generating synthetic queries (Line 11) and building triples (Lines 12–13) to train a point-wise Transformer encoder as a reranker \mathcal{R} (Line 15). Crucially, the training of \mathcal{R} depends on a prompt template \mathcal{P} , responsible for instructing the **LM** on the nature of the queries it must synthesize. Our central contribution is that we seek to automate the construction of a prompt template $\hat{\mathcal{P}}$ that maximizes the quality of the resulting \mathcal{R} .

$$\hat{\mathcal{P}} = \underset{\mathcal{P}}{\operatorname{arg\,max}} \operatorname{AvgNDCG}(\operatorname{TrainReranker}(\mathcal{P}), \mathcal{J})$$

This is essentially the problem of automatic hyperparameter optimization: automatically tuning \mathcal{P} so that training \mathcal{R} with gradient descent achieves a high score. However, we uniquely have a *string template* as a hyperparameter. Optimizing a string prompt is a difficult problem that has been studied extensively in the past few years. We do not propose a new prompt optimization algorithm nor do we claim that a specific optimizer works best. Instead, we show that very simple choices about prompt optimization are sufficient to find a prompt $\hat{\mathcal{P}}$ that allows us to produce very high quality $\hat{\mathcal{R}}$.

To this end, we express Algorithm 1 in the DSPy framework (Khattab et al., 2024), which provides a suite of tools to algorithmically optimize LM prompts and weights in the context of larger programs. These tools can be thought of as instantiating the abstract PROPOSENEWPROMPT in Algorithm 1. Concretely, we express TRAINRERANKER as a DSPy program with one Chain-of-Thought (Wei et al., 2022) layer, which takes in each sampled passage and outputs a syntheized query. We use one of DSPy's simplest prompt optimizers, CA-OPRO,² which iteratively refines the initial instruction \mathcal{I}_0 using suggestions by the LM.

In our primary experiments, we set CA-OPRO's depth = 1, which reduces PROPOSENEWPROMPT (Line 26) to simply feeding the LM our initial instruction \mathcal{I}_0 and asking it to produce a new proposed instruction that leads to higher accuracy. In this simplest instantiation of Lines 24–30, our algorithm simply tries M = 10 different (automatic) prompt variants, executing TRAINRERANKER to synthesize queries and train a new reranker each time. This process is quick since we use very small encoders Enc, trained on small synthetic sets. The reranker $\hat{\mathcal{R}}$ that scores highest on AVGNDCG is then selected for deployment and returned for heldout evaluation (Sec 4). In the appendix, we report the before-and-after prompts (Table 3).

Many other optimizer choices are possible. For example, in the appendix (Table 2), we report successful application of CA-OPRO's depth = 2 (Figure 2), which allows richer feedback to flow back to the LM proposing instructions. In particular, PROPOSENEWPROMPT (Line 26) will now see the prompts it generated earlier and how well they performed on AVGNDCG, essentially creating momentum in the right prompting direction. Other optimizers in DSPy work by crafting examples (e.g., of queries that have been effective) instead of instructions or even by updating the weights of LM. These all suggest straightforward extensions of our method but we leave them for future work.

4 Evaluation

We use the BIRCO benchmark for information retrieval, a collection of five complex QA tasks, each with a development dataset and a test dataset. All final results shown are on the full held-out test set. For Algorithm 1, we sample $|\mathcal{J}|$ positive relevance judgments, which in our primary experiments are N = 10, for prompt optimization. We use gpt-3.5-turbo as the LM. Each passage is used to generate one synthetic query, which is used to mine m = 19 hard negatives randomly sampled from the top 20 to 100 hits retrieved by BM25.

¹For simplicity, we assume the provided judgments are all positive, i.e. $r \ge 1$. These relevance scores enable relevance metrics like NDCG@10 to assign a score to the ranking S established by a reranker on a given query, relative to the ideal ranking which places the documents assigned the largest relevance grades first.

²This is an extension of the OPRO algorithm (Yang et al., 2023), which generalizes it via Coordinate Ascent (CA) so it can apply to *multi-prompt* programs as well as to scenarios in which quality is measured via a reward metric, like AVGNDCG, rather than a pre-defined correct output.

	ArguA	CTrial	DMAE	Relic	WTB	AVG		
(0) BM25	35.0	9.9	52.6	10.1	16.5	24.8		
(1) Training directly using $N = 10$ judgments								
DeBERTA-v3 (86M)	34.8	7.3	45.5	14.1	16.3	23.6		
MiniLM-L12 (33M)	44.2	6.0	46.0	11.8	17.8	25.2		
(2) Manual Prompting for Synthetic Queries								
DeBERTA-v3 (86M)	41.6	14.7	48.0	12.2	16.9	26.7		
MiniLM-L12 (33M)	38.0	13.2	50.5	9.2	19.3	26.0		
(3) Unoptimized DSPy Synthetic Queries								
DeBERTA-v3 (86M)	40.5	15.5	55.5	14.0	18.0	28.7		
MiniLM-L12 (33M)	33.9	15.2	54.6	11.5	19.7	27.0		
(4) PATH : Optimized with DSPy CA-OPRO via $N = 10$ judgments								
DeBERTA-v3 (86M)	<u>49.7</u>	14.3	57.1	<u>15.3</u>	23.4	32.0		
MiniLM-L12 (33M)	40.6	14.9	55.5	12.4	25.3	29.7		
(5) Reference Rerankers, trained on massive data like MS MARCO								
monoT5 (220M)	25.7	15.3	53.6	12.7	18.3	25.1		
monoT5 (3B)	39.8	17.6	61.2	11.2	30.8	32.1		
RankZephyr (7B)	35.2	15.7	65.9	10.4	29.4	31.3		
RankLlama (7B)	41.6	13.7	<u>66.8</u>	15.0	35.7	<u>34.6</u>		

Table 1: nDCG@10 on BIRCO with CA-OPRO, other baselines, and various rerankers. All rerankers are pointwise except RankZephyr which is listwise. We use a window size of 20 and a step size of 10 for RankZephyr. In any setting that we use 10 positive labels, we average nDCG@10 over 7 different samples and runs. The best results overall are underlined, and the best results with DeBERTA and MiniLM are bolded.

For our Enc encoder models, we choose MiniLM-L12-H384-uncased (33M backbone parameters) and DeBERTA-v3-base (86M backbone parameters), both known for strong performance relative to parameter size. We train each on the synthesized triples (Line 16) using LCE cross-entropy loss (Gao et al., 2021) over 2 epochs, validating AVGNDCG on \mathcal{J} every half-epoch. As our goal is to evaluate rerankers trained *without* large collections like MS MARCO, we use BM25 as our initial retriever. All methods rerank the top-50 BM25 document retrievals.

We consider several baselines. Baseline (1) evaluates the idea of using the N = 10 available positive judgments to create training triplets equivalently to Lines 10–16 of Algorithm 1 but using only the real positive queries from \mathcal{J} instead of generating any synthetic queries (Line 12).³ Baseline (2) shows a more standard approach for training in low-data regimes, which is to manually prompt our LM to produce synthetic queries, i.e. the TRAINR-ERANKER algorithm invoked with a manual prompt template \mathcal{P} . Baseline (3) shows a simple variant of that, which uses an (unoptimized) version of the TRAINRERANKER algorithm expressed with a DSPy Chain-Of-Thought pipeline, but receiving no feedback from the IR model. Finally, we also include Baseline (5) which is a collection of large, popular reference rerankers that we evaluate on BIRCO. These models are given access to much more IR data for training, so their role here is to serve as reference points for high-quality out-ofthe-box performance.

5 Results & Discussion

Table 1 reports our primary results. Methods (1) and (4) involve sampling N = 10 judgments, so we re-sample and re-run for a total of 7 times and report the average score in each cell. With only 10 labels, PATH leads to training a reranker that performs an average of 4.5 nDCG@10 points better than manually-written prompts and 3.0 points better than DSPy unoptimized queries across all datasets. The biggest improvement came in ArguAna (Wachsmuth et al., 2018) and DORIS-MAE (Wang et al., 2023), with improvements of almost 10.0 points each on DeBERTA. We also see that, with only 10 labeled relevance judgements, it is far better to use them with PATH as opposed to directly training with the labels. Training directly with labels yields worse perfomance on average (by 6.5 points) and on each dataset split, particularly Clinical-Trial (Koopman and Zuccon, 2016).

Our small rerankers trained with PATHgenerated tuples are also competitive with current state-of-the-art LM rerankers trained on large datasets such as MS MARCO (Bajaj et al., 2016). For instance, with PATH and 10 labels, a finetuned DeBERTA outperforms state-of-the-art models on ArguAna and Relic (Thai et al., 2022), which are relatively complicated QA tasks. Notably, with De-BERTA we outperform RankZephyr (Pradeep et al., 2023) and RankLLama (Ma et al., 2023), which are 7B models trained on MS MARCO, on ArguAna by 14.5 and 8.1 points respectively. We also outperform 3B models monoT5-3B (Nogueira et al., 2020) as well as UPR (Sachan et al., 2022), whose reranker uses T0_3B (Sanh et al., 2021), by similar margins. In contrast, the stable of billion-parameter rerankers perform well on DORIS MAE and WhatsThatBook (Lin et al., 2023), which are comparatively more straightforward relevance tasks akin to the datasets they were trained on.

³In all settings in which we train directly on top of judgments, we train for 2000 steps, mirroring the number of training tuples seen during each iteration of training within PATH. In cases where the development dataset is very small (i.e., 2000 training steps is greater than 10 epochs of training), we limit training to 10 epochs.

6 Limitations

This work uses one possible set of many potential hyperparameters that may affect the performance of PATH. We only ran full experiments with one initial, human-written prompt per task, and it is unclear how changing that will affect downstream performance. We also use a fixed learning rate (5e-5) and warmup ratio (0.1), amongst other hyperparameters, across each experiment. These are examples of potential hyperparameters that can be optimized in future work. We also define an arbitrary floor for "positive" relevance in the DORIS-MAE dataset (Wang et al., 2023), as DORIS-MAE has multi-level floating point relevance. This floor has been manually tuned for Baseline (7) in Table 2, but not for PATH. Different choices for defining positive relevance in DORIS-MAE may yield differing results. We used Tesla-V100s and Titan-V GPUs for our experiments. Our work is done with small, sub-100M parameter models, and we encourage future work to extrapolate to larger, billion-parameter models, which may achieve even higher quality.

7 Acknowledgements

We thank Jimmy Lin and Martin Franz for their valuable guidance and feedback.

References

- Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, Jianfeng Gao, Xiaodong Liu, Rangan Majumder, Andrew McNamara, Bhaskar Mitra, Tri Nguyen, Mir Rosenberg, Xia Song, Alina Stoica, Saurabh Tiwary, and Tong Wang. 2016. MS MARCO: A human generated machine reading comprehension dataset. arXiv:arXiv:1611.09268v3.
- Luiz Bonifacio, Hugo Abonizio, Marzieh Fadaee, and Rodrigo Nogueira. 2022. InPars: Unsupervised dataset generation for information retrieval. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, SIGIR '22, page 2387–2392, New York, NY, USA. Association for Computing Machinery.
- Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, Albert Webson, Shixiang Shane Gu, Zhuyun Dai, Mirac Suzgun, Xinyun Chen, Aakanksha Chowdhery, Alex Castro-Ros, Marie Pellat, Kevin Robinson, Dasha Valter, Sharan Narang, Gaurav Mishra, Adams Yu, Vincent Zhao, Yanping Huang, Andrew Dai, Hongkun Yu, Slav Petrov, Ed H. Chi, Jeff Dean, Jacob Devlin, Adam Roberts, Denny Zhou, Quoc V. Le, and Jason Wei. 2024. Scaling instruction-finetuned

language models. *Journal of Machine Learning Research*, 25(70):1–53.

- Zhuyun Dai, Vincent Y Zhao, Ji Ma, Yi Luan, Jianmo Ni, Jing Lu, Anton Bakalov, Kelvin Guu, Keith Hall, and Ming-Wei Chang. 2023. Promptagator: Fewshot dense retrieval from 8 examples. In *The Eleventh International Conference on Learning Representations*.
- Luyu Gao, Zhuyun Dai, and Jamie Callan. 2021. Rethink training of bert rerankers in multi-stage retrieval pipeline. In *The 43rd European Conference On Information Retrieval (ECIR)*.
- Pengcheng He, Xiaodong Liu, Jianfeng Gao, and Weizhu Chen. 2021. Deberta: Decoding-enhanced bert with disentangled attention. In *International Conference on Learning Representations*.
- Omar Khattab, Arnav Singhvi, Paridhi Maheshwari, Zhiyuan Zhang, Keshav Santhanam, Sri Vardhamanan A, Saiful Haq, Ashutosh Sharma, Thomas T. Joshi, Hanna Moazam, Heather Miller, Matei Zaharia, and Christopher Potts. 2024. DSPy: Compiling declarative language model calls into stateof-the-art pipelines. In *The Twelfth International Conference on Learning Representations*.
- Bevan Koopman and Guido Zuccon. 2016. A test collection for matching patients to clinical trials. In Proceedings of the 39th International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR '16, page 669–672, New York, NY, USA. Association for Computing Machinery.
- Kevin Lin, Kyle Lo, Joseph E. Gonzalez, and Dan Klein. 2023. Decomposing complex queries for tip-of-thetongue retrieval. *Preprint*, arXiv:2305.15053.
- Xueguang Ma, Liang Wang, Nan Yang, Furu Wei, and Jimmy Lin. 2023. Fine-tuning llama for multi-stage text retrieval. *Preprint*, arXiv:2310.08319.
- Rodrigo Nogueira, Zhiying Jiang, Ronak Pradeep, and Jimmy Lin. 2020. Document ranking with a pretrained sequence-to-sequence model. In *Findings* of the Association for Computational Linguistics: EMNLP 2020, pages 708–718, Online. Association for Computational Linguistics.
- Ronak Pradeep, Sahel Sharifymoghaddam, and Jimmy Lin. 2023. RankZephyr: Effective and robust zero-shot listwise reranking is a breeze! *arXiv*:2312.02724.
- Jon Saad-Falcon, Omar Khattab, Keshav Santhanam, Radu Florian, Martin Franz, Salim Roukos, Avirup Sil, Md Arafat Sultan, and Christopher Potts. 2023. UDAPDR: Unsupervised domain adaptation via LLM prompting and distillation of rerankers. In *The* 2023 Conference on Empirical Methods in Natural Language Processing.

- Devendra Singh Sachan, Mike Lewis, Mandar Joshi, Armen Aghajanyan, Wen-tau Yih, Joelle Pineau, and Luke Zettlemoyer. 2022. Improving passage retrieval with zero-shot question generation.
- Victor Sanh, Albert Webson, Colin Raffel, Stephen H. Bach, Lintang Sutawika, Zaid Alyafeai, Antoine Chaffin, Arnaud Stiegler, Teven Le Scao, Arun Raja, Manan Dey, M Saiful Bari, Canwen Xu, Urmish Thakker, Shanya Sharma Sharma, Eliza Szczechla, Taewoon Kim, Gunjan Chhablani, Nihal Nayak, Debajyoti Datta, Jonathan Chang, Mike Tian-Jian Jiang, Han Wang, Matteo Manica, Sheng Shen, Zheng Xin Yong, Harshit Pandey, Rachel Bawden, Thomas Wang, Trishala Neeraj, Jos Rozen, Abheesht Sharma, Andrea Santilli, Thibault Fevry, Jason Alan Fries, Ryan Teehan, Stella Biderman, Leo Gao, Tali Bers, Thomas Wolf, and Alexander M. Rush. 2021. Multitask prompted training enables zero-shot task generalization. *Preprint*, arXiv:2110.08207.
- Katherine Thai, Yapei Chang, Kalpesh Krishna, and Mohit Iyyer. 2022. RELiC: Retrieving evidence for literary claims. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 7500–7518, Dublin, Ireland. Association for Computational Linguistics.
- Henning Wachsmuth, Shahbaz Syed, and Benno Stein. 2018. Retrieval of the best counterargument without prior topic knowledge. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 241–251, Melbourne, Australia. Association for Computational Linguistics.
- Jianyou Wang, Kaicheng Wang, Xiaoyue Wang, Prudhviraj Naidu, Leon Bergen, and Ramamohan Paturi. 2023. Doris-mae: Scientific document retrieval using multi-level aspect-based queries. *Preprint*, arXiv:2310.04678.
- Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. 2020. Minilm: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. *Preprint*, arXiv:2002.10957.
- Xiaoyue Wang, Jianyou Wang, Weili Cao, Kaicheng Wang, Ramamohan Paturi, and Leon Bergen. 2024. Birco: A benchmark of information retrieval tasks with complex objectives. *Preprint*, arXiv:2402.14151.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, brian ichter, Fei Xia, Ed H. Chi, Quoc V Le, and Denny Zhou. 2022. Chain of thought prompting elicits reasoning in large language models. In Advances in Neural Information Processing Systems.
- Chengrun Yang, Xuezhi Wang, Yifeng Lu, Hanxiao Liu, Quoc V Le, Denny Zhou, and Xinyun Chen. 2023. Large language models as optimizers. *arXiv preprint arXiv:2309.03409*.

	ArguA	CTrial	DMAE	Relic	WTB	AVG
(6) Base Models						
DeBERTA-v3-base (86M)	5.9	7.4	41.8	2.4	3.9	12.3
MiniLM-L12 (33M)	22.7	9.9	50.1	8.7	10.6	20.4
(7) Training directly using all relevance judgements						
DeBERTA-v3-base (86M)	60.0	8.4	49.0	22.0	19.8	31.8
MiniLM-L12 (33M)	58.5	6.7	62.4	16.6	20.0	32.8
(8) PATH : Optimized with DSPy CA-OPRO at depth=1 via all judgments						
DeBERTA-v3-base (86M)	48.2	13.9	58.9	16.5	23.9	32.3
MiniLM-L12 (33M)	44.3	14.4	58.0	13.1	26.3	31.2
(9) PATH : Optimized with DSPy CA-OPRO at depth=2 via all judgments						
DeBERTA-v3-base (86M)	48.8	13.7	61.7	16.0	23.9	32.8
MiniLM-L12 (33M)	44.6	14.4	60.1	13.3	32.0	32.9

Table 2: nDCG@10 on BIRCO with PATH given access to the full development sets.

A PATH Results with Full Development Set

Table 2 shows the performance of PATH given at various depths given access to the entire BIRCO development set. On average, PATH at depth = 2 performs 0.5 points better than directly training with the full development set.

B Meta Prompting with CA-OPRO

Figure 2 shows an example of the meta-prompting strategy used by CA-OPRO. The proposed optimal instructions are sent back through TRAINRERANKER and evaluated again by AVGNDCG. This interaction occurs before each depth level > 1, thereby repeating until ideally converging on more optimal instructions.

C Analysis of PATH Prompts

We visualize the effects of PATH in Table 3. The initial manual prompts were used in Baselines (2) and (3) in Table 1, and the final PATH prompts are drawn from training DeBERTA in Baseline (9) in Table 2.



Figure 2: An example of CA-OPRO's meta-prompts for prompt optimization. Orange text represents the meta-prompt, blue text represents attempted trial instructions, and green text represents CA-OPRO's new proposed instructions.

Task	Initial Manual Prompt	Final PATH-optimized Prompt	Final PATH-optimized Suffix	nDCG@10 Improve- ment
ArguA	Given a passage with an argument, please return the best counterargument that refutes the input passage. The counterargument should be a few sen- tences long. Only return the counter- argument; do not reason or explain.	Generate a succinct counterargument that refutes the input passage.	Counterargument:	7.2
CTrial	Given a passage with the description of a clinical trial, return the a patient record that would match that of the required subjects for the input clini- cal trial. Please describe this patient record in a few sentences.	Instruction #11: Starting with the clin- ical trial description, create a compre- hensive patient record containing de- mographic information, medical his- tory, current medications, and any other pertinent details professionally arranged to capture the essence of the trial's requirements.	Comprehensive Patient Record:	-1.0
DMAE	Given a passage consisting of an ab- stract of a computer science paper, please return a complex, multiple- sentence research question that is best answered by the input abstract. Only return the question; do not reason or explain.	Given an abstract of a computer science paper, construct a multi- dimensional research question that delves deeply into the topic and ex- plores new dimensions beyond the pro- vided information. Integrate analysis of the main goals and contributions along with potential areas for further study.	Further Inquiry:	13.7
Relic	Given a literary quotation, return an excerpt of text that is most likely to include the input quotation within it. The output excerpt should include the token [masked sentence(s)] replacing the input quotation, as well as a few sentences before and after the token. Only return the excerpt; do not reason or explain.	Review several paragraphs surround- ing the given literary quotation and intelligently formulate an excerpt that seamlessly integrates the quote. En- sure the generated text captures the essence and context of the input quo- tation authentically.	Literary Excerpt:	3.8
WTB	Given the description of a book, please return a tip-of-the-tongue description that someone might use in order to try and identify the book the input describes. The output should be in first-person. Only return the tip-of-the- tongue description; do not reason or explain. Follow the following format.	Consider the key plots, characters, and themes of the book to gener- ate a memorable and concise tip-of- the-tongue description reflecting its essence. Avoid using explicit titles or characters in the output to encourage creative thinking in forming the tip-of- the-tongue description.	I'm thinking of a book that	7.0

Table 3: A comparison of initial manual prompts and final, PATH-optimized prompts.