Multi-Layer Ranking with Large Language Models for News Source Recommendation

Wenjia Zhang Computer Science University of Warwick Coventry, UK wenjia.zhang@warwick.ac.uk Lin Gui Informatics King's College London London, UK lin.1.gui@kcl.ac.uk

ABSTRACT

To seek reliable information sources for news events, we introduce a novel task of expert recommendation, which aims to identify trustworthy sources based on their previously quoted statements. To achieve this, we built a novel dataset, called NewsQuote, consisting of 23,571 quote-speaker pairs sourced from a collection of news articles. We formulate the recommendation task as the retrieval of experts based on their likelihood of being associated with a given query. We also propose a multi-layer ranking framework employing Large Language Models to improve the recommendation performance. Our results show that employing an in-context learning based LLM ranker and a multi-layer ranking-based filter significantly improve both the predictive quality and behavioural quality of the recommender system.

CCS CONCEPTS

- Information systems \rightarrow Retrieval models and ranking.

KEYWORDS

Recommender System, In-Context Learning, Large Language Model

1 INTRODUCTION

Identifying credible information sources plays a crucial role in ensuring the integrity and accuracy of journalism. First, the reliability of the source of a claim strengthens the groundwork for accurate assessments regarding the authenticity of the claim [1, 6, 16, 18, 24]. Second, external information sources can provide additional evidence for verifying claims' veracity [2, 8, 10, 11, 20, 21, 25, 27, 29]. Most fact-checking research assumes that the information provided by a reputable platform is trustworthy. However, it is crucial to recognise that these platforms can only be considered as secondary sources comparison to the primary speakers quoted in articles. In practice, it is essential for fact-checkers and journalists to seek out and consult credible primary sources within the relevant field to gain insights [17].

Tailored software toolkits are designed to accommodate various strategies for evaluating information sources, including the consideration of diversity [22] and topic relevance [5]. Moreover, datasets have been curated to facilitate insights into the extraction and attribution of quotes in news articles [26, 32]. Quote Erat is the first interface designed for interactive exploration of large-scale corpora of quotes from the news domain [28], allowing users to retrieve relevant quotes and articles based on their queries. These Rob Procter Computer Science University of Warwick Coventry, UK The Alan Turing Institute London, UK rob.procter@warwick.ac.uk Yulan He Informatics King's College London London, UK The Alan Turing Institute London, UK yulan.he@kcl.ac.uk

systems do not directly recommend potential information sources, such as experts or organizations, in response to user queries.

In the booming of Large Language Models (LLMs) [4], contentbased recommendation methods have experienced a surge in effectiveness, particularly due to the advancements in In-Context Learning[13]. Various prompting techniques have been designed to enhance the capabilities of recommender systems, serving diverse roles such as being a recommender [7, 14], a ranker [9], or a designer [15, 30]. In these approaches, LLMs function as a substitute for a specific step within recommendation systems.

In this paper, we present an expert-based recommendation system for identifying information sources by analyzing quote-speaker pairs within news articles. Our contributions are: (1) We describe the construction of a novel dataset, named NewsQuote¹, which contains quote-speaker pairs extracted from a collection of news articles. (2) We implement a source recommendation system that retrieves potential information sources for a given query by leveraging historical quotations. (3) We enhance the expert retrieval approach by integrating a multi-layer ranking-based filtering mechanism consisting of LLM rankers. (4) Experimental results show that multi-layer LLM ranking improves the predictive quality of the recommendation system while mitigating popularity bias.

2 DATA CONSTRUCTION

We built our NEwSQUOTE dataset from the AYLIEN coronavirus dataset², which contains news articales published between November 2019 and August 2020. Apart from text, each article is also accompanied with the meta data such as authors, keywords, summary, source, publishing time, topical categories coded by both the Interactive Advertising Bureau (IAB) taxonomy³ and the IPTC NewsCodes⁴, as well as the recognized entities and entity links from the DBpedia.

Data Deduplication As the same news story may be posted by multiple sources, we removed news articles that are similar to what have already been published. News articles were first sorted in chronological order. News duplicates were then detected using a RoBERTa classifier⁵ trained with title-body pairs using semisupervised learning [19]. For processing efficiency, the dataset was split into 16 equal-sized subsets. For each subset, the titles and the first sentence of the news summaries of the temporally-ordered

¹The dataset can be accessed at https://zenodo.org/records/11032190

²https://aylien.com/resources/datasets/coronavirus-dataset

³https://www.iab.com

⁴https://iptc.org/standards/newscodes/

⁵https://huggingface.co/vslaykovsky/roberta-news-duplicates

news articles were sequentially fed as input to the RoBERTa classifier. Any duplicates were removed. After data deduplication, 158,325 news articles were kept.

	Test	Valid	Train
No. of samples	2000	1961	19610
No. of articles	1749	1741	13728
No. of speakers	936	923	2843
Avg. quote length	18.24	16.04	16.12
No. of domains	184	185	258
No. of news categories	441	428	634
No. of keywords	21672	21769	70560

Table 1: The NEWSQUOTE Dataset statistics. Speaker is the information source, domain is the platform where article was published. Quote length is the No. of words.

Quote Trigger Word Filtering For each of the selected articles, we segmented the the main body into sentences, and then used a pre-trained BERT-based semantic role labeling model [23] to extract verbs (or predicates), subjects, and objects. We obtained a candidate verb list sorted by their occurrence frequencies. After manually checking the most frequent candidate verbs with occurrences over 100, we identified 352 quote trigger words which are more likely indicative of direct or indirect quotes. Some of the verbs are clearly indicative of quotes, such as 'said', while others may not be associated with quotes in a traditional sense, for example, 'tweet'. After identifying the quote trigger words, we only kept the sentences with at least one trigger word, one subject, and one object. The subject is regarded as a potential speaker and the object is considered as a potential quotation. To ensure that the quotations are informative, we also require that the length of the object should be more than three words.

Speaker and Quote Filtering We required that the subject of a candidate sentence should be a person or an organisation, and therefore identified potential speaker entities via the accompanied DBpedia ontology labels⁶ in the dataset. As the same subject could have multiple mentions, we use the DBPedia entity links for entity resolution and normalisation. In addition, we required a named entity to appear at least twice in the dataset. Finally, to avoid the sentence split error, we required the quotation marks to be paired in sentences that contain direct quotes and mixed quotes.

Test Set Annotation Since in practice, given a topic, we can only identify experts based on their previous quotes published in earlier news articles, we divide the dataset into training, validation and test sets by the publishing timestamps of news articles, ensuring speaker-quote pairs in the validation and the test sets occurred later than those in the training set. To ensure data quality, samples in the test set were manually screened by one annotator.

Dataset Statistics Our data covers three categories of quotes: direct quote, indirect quote and mixed quote. In short, direct quotations are placed inside quotation marks while indirect quotations are not, and a mix of direct and indirect quotations have only part of the quotations placed inside quotation marks. We roughly estimated the weight of each quotation type on the dataset by the number and

position of quotation marks: 81% for indirect quotes, 11% for direct quotes, and 7% for mixed quotes. In the test set, there are 1,582 (79%) indirect quotes, 178 (9%) mixed quotes, and 240 direct quotes (12%). Table 1 shows the statistics of our final NEwsQuote dataset. In summary, we have a total of 23,571 English speaker-quote pairs with 2,843 speakers from 263 global domains.

3 APPROACHES

In our dataset, each sample S_i consists of a context d_i , a quotespeaker pair $(q, e)_i$ extracted from the context, and metadata m_i inherited from the article where it originates. The context contains three sentences, the primary sentence containing the speaker and quote, its preceding sentence and the following sentence. The metadata are defined at the document level and are sourced from the AYLIEN coronavirus dataset. We formulate source recommendation as a retrieval problem, aiming at identifying sources capable of commenting on the topic discussed in a given query, guided by the historical quotes of the sources in news reports, and subsequently ranking them by their relevance to the query. In our scenario, each context is treated as a document, and a preprocessed news article title serves as the query.

3.1 Expert Finding

We implemented both candidate-based and document-based expert retrieval methods [3] for this source recommendation task.

The *Candidate-based Expert Retrieval* assumes that each term in the query is sampled identically and independently, also that the document and the expert source candidate are conditionally independent. The candidate-based approach estimates P(k|e) by:

$$\begin{split} P(k|e) &= \prod_{t \in k} \{(1-\lambda) (\sum_{d \in D} p(t|d)p(d|e)) + \lambda p(t)\}^{n(t,k)} \\ \lambda &= \frac{\beta}{\beta + n(e)}, \quad \beta = \frac{\sum_{E} |\{d: n(e,d) > 0\}| \cdot |d|}{|E|}, \end{split}$$

where λ is the smoothing parameter, p(t|d), p(d|e) and p(t) are the conditional probability of a term t in document d, the conditional probability of a document d given source e, and the probability of term t, respectively. Both p(t|d) and p(t) are estimated by maximum likelihood. n(t, k) is the number of times a term t appears in the query k, n(e, d) is the occurrence frequency of an source e appeared in the document d, n(e) is the total number of tokens in all documents associated with the source e, |d| is the average document length, and |E| is the total number of sources.

The *Document-based Expert Retrieval* approach searches for sources via relevant document collection by assuming the conditional independence between the query and candidate, and estimates the probability of a term t in each document. The P(k|e) is then calculated as:

$$P(k|e) = \sum_{d \in D} \{ \prod_{t \in k} ((1 - \lambda)p(t|d) + \lambda p(t))^{n(t,k)} \} p(d|e)$$
$$\lambda = \frac{\beta}{\beta + n(d)}, \quad \beta = |d|,$$

where n(d) is the length of document d.

In both expert finding approaches, the document-candidate associations p(d|e) is estimated by a simple Boolean model.

⁶http://mappings.dbpedia.org/server/ontology/classes/



Multi-Layer Ranking-based Filter

Figure 1: Illustration of the LLM Ranker and the Multi-layer Ranking-based Filter

3.2 LLM-based Multi-Layer Ranking

Purely probability-based approaches face significant constraint due to the limitation of the document corpus, making it challenging to efficiently enhance models with additional knowledge in advance, especially when facing unpredictable news topics. Instead, we take advantage of Large Language Models to improve the performance of the recommender system.

LLM Ranker After obtaining a list of recommendations returned by the Expert Finding methods, we employ LLMs to rerank the top recommended candidates. This is achieved by devising a one-shot prompt template:

"You are a knowledgeable referrer. Given a query and the 10 potential information sources (which may include both individuals and organizations) retrieved based on the query, you need to rank the 10 potential sources in order of relevance to the query, placing the source that is most likely to provide information relevant to the query at the top of the list. Return the new rank of sources only in the form of python list (exactly the same form of the given list, just rerank it), please do not provide other words except for the list. Here is an example: Query: <Example Query>. 10 potential sources are: <Candidate List for the Example Query>, and then the output should be: <Reranked Candidate List>. Now the query is: <Query>. The source candidates are: <Candidate List to Be Reranked>"

Multi-layer Ranking-based Filter When using an LLM ranker to improve ranking quality, the system's predictive efficacy still depends on the probability-based retrieval approach that provides the initial candidates. To expand the pool of candidates considered for rankings, we propose a *Multi-layer Ranking-based Filter*. This filter uses the one-shot LLM ranker as a component to generate result from a wider range of candidates by sequentially sorting and filtering through multiple layers. As shown in Fig. 1, in each layer, the input candidate list is first randomly divided into several subgroups, and then each subgroup is fed into an LLM ranker. The filter keeps only a subset of the top-ranked candidates from each reranked subgroup candidate list, and concatenates them into a new list of candidates for the subsequent layer. Inspired by the Sequential Monte Carlo Steering [12], the LLM-based filter operates N times to clone promising candidates and cull low-likelihood ones.

Filter Strategy In our framework, the aforementioned filter undergoes multiple iterations to generate confidence scores for the resulting candidates. We employ two strategies to determine the final output based on the frequency of retention by the filter. The *Most Frequent Strategy* only considers the output from the last layer of the Multi-layer Ranking-based Filter. It selects candidates with the highest frequency of occurrence across the repeated runs. On the other hand, the *Layer-Weighted Strategy* considers the outputs of all filter layers. It calculates the average repetition frequency of each layer using a pre-defined set of weights, and then returns candidates with the highest weighted occurrence score.

4 EXPERIMENTS

In this section, we describe how we set up experiments and evaluate the results.

4.1 Setup

In experiments, we utilized context samples from the training set as the document database and used article titles from the test set as queries. There could be more than one source of information corresponding to an article title query. We employed the GPT-3.5-Turbo and GPT4-Turbo as LLM rankers, and GPT-3.5-Turbo as the Multi-layer Ranking-based Filter. The filter comprised a 2-layer structure: (1) In the first layer, we initialized with 100 candidates returned by the document-centric approach, dividing them randomly into 10 groups. Each group then underwent reranking by an LLM ranker, with the top 5 candidates from each group being retained; (2) Subsequently, in the second layer, the top 50 candidates from the first layer were shuffled, divided into 5 groups, and reranked by an LLM ranker. Only the top 2 candidates from each group, as returned by the LLM ranker, were kept. Upon each run of the 2layer ranking-based filter, we obtained a list of 10 candidates. After repeating this process 20 times, we determined the final output by adopting different filter strategies mentioned in 3.2, resulting in the top 20 recommendations.

4.2 Metrics

Recall is the proportion of correctly identified information sources in the top recommendations out of the total number of sources quoted in the article.

Mean Averaged Precision (MAP) is the mean of the precision at the points where the relevant sources were retrieved.

Normalized Discounted Cumulative Gain at K first discounts the gain scale at the *i*-th rank position by $\frac{1}{\log_2(i)}$, then adds up the converted gain scales up to rank *k*, and finally normalizes the result by the ideal ranking order.

Diversity is calculated as the average pairwise distance between items appeared in the recommendation list. To encode entity features, we trained Wikipedia2Vec embeddings [31] on a Wikipedia database publish in Jan 2024.

Coverage shows the percentage of information sources from the training dataset being recommended on the test set.

Average Recommendation Popularity is the averaged popularity of the recommended items on the training set. Here, we use the number of occurrences in the training set as the popularity of the information source.

5 RESULTS

	CER	DER	ReDE4	ReDE3.5
Recall MAP NDCG10	0.2454 0.1342 0.1619	0.3241 0.2016 0.2327	0.3244 0.2257 0.2512	0.3249 0.1822 0.2176

Table 2: Results of the Expert Retrieval baselines and LLM ranker. CER is the Candidate-based Expert Retrieval, and DER is the Document-based Expert Retrieval. ReDE3.5 used GPT-3.5 to rerank the top 10 candidates returned by the DER, while ReDE4 used GPT-4.

As baselines, the Document-based Retrieval method performed much better than the Candidate-based Retrieval method, scoring 7% to 8% higher in Recall, MAP, and NDCG@10. This disparity is likely attributed to the fact that the training set is organized by documents rather than by information source candidates. When we applied the LLM ranker on the top 10 candidated returned by the Document-based Retrieval approach, GPT-4 improved the MAP and NDCG@10 by 2%, but GPT-3.5 did not yield improvement. This may be because GPT-4 possesses more up-to-date knowledge compared to GPT-3.5. Interestingly, both the GPT-4 and GPT-3.5 rankers yielded a slight improvement in Recall, albeit negligible. We attribute this phenomenon to the stochastic nature of LLM generation.

Although the single GPT-3.5 ranker did not perform well in reordering the top 10 candidates, integrating a multi-layer structural filter into the baseline approach resulted in a modest improvement in Recall of the top 20 candidates from the top 100 candidates by 0.5% to 2%. Given the task of recommending sources for news stories, the diversity and comprehensiveness of sources are also important alongside their reliability in providing accurate information. Following the application of the Multi-layer Ranking-based Filter, the average recommendation popularity decreased significantly from 71.68 to around 40. This indicates that our approach has the capability to divert the baseline from favoring popular sources. Moreover, allocating more weights from the last layer to the first layer led to a slight decrease in recall, while increasing MAP, NDCG@10, and popularity bias. Consequently, we conclude that the multi-layer structure sacrifices ranking precision to increase recall and mitigate popularity bias.

	DER	MRF	MRF0	MRF1	MRF2
Recall	0.3909	0.4098	0.4080	0.4012	0.3940
MAP	0.2056	0.1719	0.1808	0.1805	0.1795
NDCG10	0.2318	0.2059	0.2126	0.2127	0.2117
Diversity	10.34	5.889	5.896	5.894	5.894
Coverage	0.2085	0.2595	0.2562	0.2497	0.2497
ARP	71.68	39.11	39.44	39.63	40.05

Table 3: Evaluations of the Multi-layer Ranking-based Filter on the top 20 candidates. DER denotes the Documentbased Expert Retrieval. MRF represents the DER results augmented by the multi-layer ranking-based filter using the most frequent strategy. MRF0(MRF1, MRF2) denotes the DER results augmented by the multi-layer ranking-based filter with the layer-weighted strategy and layer weights [0.25,0.75]([0.5,0.5],[0.75,0.25]).

In evaluating the results, the golden answers refer to sources that were actually cited in news reports, averaging only 1.052 golden answers per query. These golden answers received a score of 1, while all other candidates received a score of 0 when calculating Recall, MAP, and NDCG@10. As such, we posit that the potential of the recommender system could be underestimated. In reality, sources not cited in news articles may still hold value, and therefore should be scored higher than zero.

6 CONCLUSION AND FUTURE WORK

This paper outlines the development of a novel dataset comprising quote-source pairs extracted from news articles. It also presents a recommendation task, aimed at identifying information sources for a given news topic query. Based on the NEwsQUOTE dataset, we explored the Expert Finding baselines for this task, and proposed a Multi-layer Ranking-based Filter, which integrates LLM rankers to enhance the capability of the recommender system. Results show that the Multi-layer LLM Ranker improves predictive accuracy and mitigates popularity bias, albeit at the expense of ranking precision. In future work, we will engage with a more diverse document corpus and utilize human evaluations to provide more practical ratings.

ACKNOWLEDGEMENTS

This work was supported in part by the UK Engineering and Physical Sciences Research Council (EP/V048597/1, EP/X019063/1) and a Turing AI Fellowship (EP/V020579/1, EP/V020579/2).

REFERENCES

- Mabrook Al-Rakhami and Atif Alamri. 2020. Lies Kill, Facts Save: Detecting COVID-19 Misinformation in Twitter. *IEEE Access* 8 (2020), 155961–155970. https://doi.org/10.1109/ACCESS.2020.3019600
- [2] Isabelle Augenstein, Christina Lioma, Dongsheng Wang, Lucas Chaves Lima, Casper Hansen, Christian Hansen, and Jakob Grue Simonsen. 2019. MultiFC: A Real-World Multi-Domain Dataset for Evidence-Based Fact Checking of Claims. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing, EMNLP-IJCNLP 2019, Hong Kong, China, November 3-7, 2019, Kentaro Inui, Jing Jiang, Vincent Ng, and Xiaojun Wan (Eds.). Association for Computational Linguistics, 4684–4696. https://doi.org/10.18653/V1/D19-1475
- [3] Krisztian Balog, Leif Azzopardi, and Maarten de Rijke. 2009. A language modeling framework for expert finding. Inf. Process. Manag. 45, 1 (2009), 1–19. https: //doi.org/10.1016/J.IPM.2008.06.003
- [4] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. Language Models are Few-Shot Learners. In Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual, Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (Eds.). https://proceedings.neurips.cc/paper/2020/ hash/1457c0d6bfcb4967418bfb8ac142f64a-Abstract.html
- [5] Tien Duc Cao, Ludivine Duroyon, François Goasdoué, Ioana Manolescu, and Xavier Tannier. 2019. BeLink: Querying Networks of Facts, Statements and Beliefs. In Proceedings of the 28th ACM International Conference on Information and Knowledge Management, CIKM 2019, Beijing, China, November 3-7, 2019, Wenwu Zhu, Dacheng Tao, Xueqi Cheng, Peng Cui, Elke A. Rundensteiner, David Carmel, Qi He, and Jeffrey Xu Yu (Eds.). ACM, 2941–2944. https://doi.org/10. 1145/3357384.3357851
- [6] Zi Chu, Steven Gianvecchio, Haining Wang, and Sushil Jajodia. 2012. Detecting Automation of Twitter Accounts: Are You a Human, Bot, or Cyborg? IEEE Trans. Dependable Secur. Comput. 9, 6 (2012), 811–824. https://doi.org/10.1109/TDSC. 2012.75
- [7] Sunhao Dai, Ninglu Shao, Haiyuan Zhao, Weijie Yu, Zihua Si, Chen Xu, Zhongxiang Sun, Xiao Zhang, and Jun Xu. 2023. Uncovering ChatGPT's Capabilities in Recommender Systems. In Proceedings of the 17th ACM Conference on Recommender Systems, RecSys 2023, Singapore, Singapore, September 18-22, 2023, Jie Zhang, Li Chen, Shlomo Berkovsky, Min Zhang, Tommaso Di Noia, Justin Basilico, Luiz Pizzato, and Yang Song (Eds.). ACM, 1126–1132. https: //doi.org/10.1145/3604915.3610646
- [8] Andreas Hanselowski, Christian Stab, Claudia Schulz, Zile Li, and Iryna Gurevych. 2019. A Richly Annotated Corpus for Different Tasks in Automated Fact-Checking. In Proceedings of the 23rd Conference on Computational Natural Language Learning, CoNLL 2019, Hong Kong, China, November 3-4, 2019, Mohit Bansal and Aline Villavicencio (Eds.). Association for Computational Linguistics, 493–503. https: //doi.org/10.18653/V1/K19-1046
- [9] Yupeng Hou, Junjie Zhang, Zihan Lin, Hongyu Lu, Ruobing Xie, Julian J. McAuley, and Wayne Xin Zhao. 2024. Large Language Models are Zero-Shot Rankers for Recommender Systems. In Advances in Information Retrieval - 46th European Conference on Information Retrieval, ECIR 2024, Glasgow, UK, March 24-28, 2024, Proceedings, Part II (Lecture Notes in Computer Science, Vol. 14609), Nazli Goharian, Nicola Tonellotto, Yulan He, Aldo Lipani, Graham McDonald, Craig Macdonald, and Iadh Ounis (Eds.). Springer, 364–381. https://doi.org/10.1007/978-3-031-56060-6_24
- [10] Georgi Karadzhov, Preslav Nakov, Lluís Màrquez, Alberto Barrón-Cedeño, and Ivan Koychev. 2017. Fully Automated Fact Checking Using External Sources. In Proceedings of the International Conference Recent Advances in Natural Language Processing, RANLP 2017, Varna, Bulgaria, September 2 - 8, 2017, Ruslan Mitkov and Galia Angelova (Eds.). INCOMA Ltd., 344–353. https://doi.org/10.26615/978-954-452-049-6_046
- [11] Neema Kotonya and Francesca Toni. 2020. Explainable Automated Fact-Checking for Public Health Claims. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing, EMNLP 2020, Online, November 16-20, 2020, Bonnie Webber, Trevor Cohn, Yulan He, and Yang Liu (Eds.). Association for Computational Linguistics, 7740–7754. https://doi.org/10.18653/V1/2020.EMNLP-MAIN.623
- [12] Alexander K Lew, Tan Zhi-Xuan, Gabriel Grand, and Vikash K Mansinghka. 2023. Sequential Monte Carlo Steering of Large Language Models using Probabilistic Programs. arXiv preprint arXiv:2306.03081 (2023).
- [13] Jiazheng Li, Runcong Zhao, Yulan He, and Lin Gui. 2023. OverPrompt: Enhancing ChatGPT Capabilities through an Efficient In-Context Learning Approach. CoRR abs/2305.14973 (2023). https://doi.org/10.48550/ARXIV.2305.14973

arXiv:2305.14973

- [14] Junling Liu, Chao Liu, Renjie Lv, Kang Zhou, and Yan Zhang. 2023. Is chatgpt a good recommender? a preliminary study. arXiv preprint arXiv:2304.10149 (2023).
- [15] Hanjia Lyu, Song Jiang, Hanqing Zeng, Yinglong Xia, and Jiebo Luo. 2023. Llmrec: Personalized recommendation via prompting large language models. arXiv preprint arXiv:2307.15780 (2023).
- [16] Arjun Mukherjee, Abhinav Kumar, Bing Liu, Junhui Wang, Meichun Hsu, Malú Castellanos, and Riddhiman Ghosh. 2013. Spotting opinion spammers using behavioral footprints. In *The 19th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, KDD 2013, Chicago, IL, USA, August 11-14, 2013*, Inderjit S. Dhillon, Yehuda Koren, Rayid Ghani, Ted E. Senator, Paul Bradley, Rajesh Parekh, Jingrui He, Robert L. Grossman, and Ramasamy Uthurusamy (Eds.). ACM, 632–640. https://doi.org/10.1145/2487575.2487580
- [17] Rob Procter, Miguel Arana Catania, Yulan He, Maria Liakata, Arkaitz Zubiaga, Elena Kochkina, and Runcong Zhao. 2023. Some Observations on Fact-Checking Work with Implications for Computational Support. arXiv preprint arXiv:2305.02224 (2023).
- [18] Khubaib Ahmed Qureshi, Rauf Ahmed Shams Malick, Muhammad Sabih, and Hocine Cherifi. 2022. Deception detection on social media: A source-based perspective. *Knowl. Based Syst.* 256 (2022), 109649. https://doi.org/10.1016/J. KNOSYS.2022.109649
- [19] Andreas Rücklé, Nafise Sadat Moosavi, and Iryna Gurevych. 2019. Neural Duplicate Question Detection without Labeled Training Data. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing, EMNLP-IJCNLP 2019, Hong Kong, China, November 3-7, 2019, Kentaro Inui, Jing Jiang, Vincent Ng, and Xiaojun Wan (Eds.). Association for Computational Linguistics, 1607–1617. https://doi.org/10.18653/V1/D19-1171
- [20] Arkadiy Saakyan, Tuhin Chakrabarty, and Smaranda Muresan. 2021. COVID-Fact: Fact Extraction and Verification of Real-World Claims on COVID-19 Pandemic. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing, ACL/IJCNLP 2021, (Volume 1: Long Papers), Virtual Event, August 1-6, 2021, Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (Eds.). Association for Computational Linguistics, 2116–2129. https://doi.org/10.18653/V1/2021.ACL-LONG.165
- [21] Tal Schuster, Adam Fisch, and Regina Barzilay. 2021. Get Your Vitamin C! Robust Fact Verification with Contrastive Evidence. In Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2021, Online, June 6-11, 2021, Kristina Toutanova, Anna Rumshisky, Luke Zettlemoyer, Dilek Hakkani-Tür, Iz Beltagy, Steven Bethard, Ryan Cotterell, Tanmoy Chakraborty, and Yichao Zhou (Eds.). Association for Computational Linguistics, 624–643. https://doi.org/10.18653/ V1/2021.NAACL-MAIN.52
- [22] Xiaoxiao Shang, Zhiyuan Peng, Qiming Yuan, Sabiq Khan, Lauren Xie, Yi Fang, and Subramaniam Vincent. 2022. DIANES: A DEI Audit Toolkit for News Sources. In SIGIR '22: The 45th International ACM SIGIR Conference on Research and Development in Information Retrieval, Madrid, Spain, July 11 - 15, 2022, Enrique Amigó, Pablo Castells, Julio Gonzalo, Ben Carterette, J. Shane Culpepper, and Gabriella Kazai (Eds.). ACM, 3312–3317. https://doi.org/10.1145/3477495.3531660
- [23] Peng Shi and Jimmy Lin. 2019. Simple bert models for relation extraction and semantic role labeling. arXiv preprint arXiv:1904.05255 (2019).
- [24] Kai Shu, Xinyi Zhou, Suhang Wang, Reza Zafarani, and Huan Liu. 2019. The role of user profiles for fake news detection. In ASONAM '19: International Conference on Advances in Social Networks Analysis and Mining, Vancouver, British Columbia, Canada, 27-30 August, 2019, Francesca Spezzano, Wei Chen, and Xiaokui Xiao (Eds.). ACM, 436–439. https://doi.org/10.1145/3341161.3342927
- [25] James Thorne, Andreas Vlachos, Oana Cocarascu, Christos Christodoulopoulos, and Arpit Mittal. 2018. The Fact Extraction and VERification (FEVER) Shared Task. In Proceedings of the First Workshop on Fact Extraction and VERification (FEVER). Association for Computational Linguistics, Brussels, Belgium, 1–9. https: //doi.org/10.18653/v1/W18-5501
- [26] Timoté Vaucher, Andreas Spitz, Michele Catasta, and Robert West. 2021. Quotebank: A Corpus of Quotations from a Decade of News. In WSDM '21, The Fourteenth ACM International Conference on Web Search and Data Mining, Virtual Event, Israel, March 8-12, 2021, Liane Lewin-Eytan, David Carmel, Elad Yom-Tov, Eugene Agichtein, and Evgeniy Gabrilovich (Eds.). ACM, 328–336. https://doi.org/10.1145/3437963.3441760
- [27] Juraj Vladika and Florian Matthes. 2023. Scientific Fact-Checking: A Survey of Resources and Approaches. In Findings of the Association for Computational Linguistics: ACL 2023, Toronto, Canada, July 9-14, 2023, Anna Rogers, Jordan L. Boyd-Graber, and Naoaki Okazaki (Eds.). Association for Computational Linguistics, 6215-6230. https://doi.org/10.18653/V1/2023.FINDINGS-ACL.387
- [28] Vuk Vukovic, Akhil Arora, Huan-Cheng Chang, Andreas Spitz, and Robert West. 2022. Quote Erat Demonstrandum: A Web Interface for Exploring the Quotebank Corpus. In SIGIR '22: The 45th International ACM SIGIR Conference on Research and Development in Information Retrieval, Madrid, Spain, July 11 - 15, 2022, Enrique Amigó, Pablo Castells, Julio Gonzalo, Ben Carterette, J. Shane Culpepper, and

Gabriella Kazai (Eds.). ACM, 3350-3354. https://doi.org/10.1145/3477495.3531696

- [29] David Wadden, Shanchuan Lin, Kyle Lo, Lucy Lu Wang, Madeleine van Zuylen, Arman Cohan, and Hannaneh Hajishirzi. 2020. Fact or Fiction: Verifying Scientific Claims. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing, EMNLP 2020, Online, November 16-20, 2020, Bonnie Webber, Trevor Cohn, Yulan He, and Yang Liu (Eds.). Association for Computational Linguistics, 7534–7550. https://doi.org/10.18653/V1/2020.EMNLP-MAIN.609
- [30] Wenjie Wang, Xinyu Lin, Fuli Feng, Xiangnan He, and Tat-Seng Chua. 2023. Generative recommendation: Towards next-generation recommender paradigm. arXiv preprint arXiv:2304.03516 (2023).
- [31] Ikuya Yamada, Akari Asai, Jin Sakuma, Hiroyuki Shindo, Hideaki Takeda, Yoshiyasu Takefuji, and Yuji Matsumoto. 2020. Wikipedia2Vec: An Efficient Toolkit for Learning and Visualizing the Embeddings of Words and Entities from

Wikipedia. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations, EMNLP 2020 - Demos, Online, November 16-20, 2020, Qun Liu and David Schlangen (Eds.). Association for Computational Linguistics, 23–30. https://doi.org/10.18653/V1/2020.EMNLP-DEMOS.4

[32] Yuanchi Zhang and Yang Liu. 2022. DirectQuote: A Dataset for Direct Quotation Extraction and Attribution in News Articles. In Proceedings of the Thirteenth Language Resources and Evaluation Conference, LREC 2022, Marseille, France, 20-25 June 2022, Nicoletta Calzolari, Frédéric Béchet, Philippe Blache, Khalid Choukri, Christopher Cieri, Thierry Declerck, Sara Goggi, Hitoshi Isahara, Bente Maegaard, Joseph Mariani, Hélène Mazo, Jan Odijk, and Stelios Piperidis (Eds.). European Language Resources Association, 6959–6966. https://aclanthology.org/2022.lrec-1.752