A NOVEL ENERGY-BASED MODELING FRAMEWORK

R. ALTMANN^{\dagger}, P. SCHULZE^{\ddagger}

ABSTRACT. We introduce an energy-based model, which seems especially suited for constrained systems. The proposed model provides an alternative to the popular port-Hamiltonian framework and exhibits similar properties such as energy dissipation as well as structure-preserving interconnection and Petrov–Galerkin projection. In terms of time discretization, the midpoint rule and discrete gradient methods are dissipationpreserving. Besides the verification of these properties, we present ten examples from different fields of application.

Key words. energy-based modeling, dissipation, structure preservation AMS subject classifications. 37J06, 65P10, 65M60

1. INTRODUCTION

Mathematical modeling of time-dependent systems usually leads to ordinary differential equations (ODEs) or partial differential equations (PDEs). Moreover, in many applications the governing equations also include algebraic equations which arise from constraints such as coupling conditions or constitutive relations. In the particular case of PDEs, constraints may also appear naturally due to structural properties, the inclusion of boundary conditions, or limiting situations [MZ23]. In all these cases, the mathematical model is given by a system of (partial) differential–algebraic equations (DAEs). Especially when considering physical systems, the mathematical model typically also has some relevant qualitative properties, as for instance stability or conserved quantities. Since the violation of these properties may lead to unphysical behavior, it is desirable to preserve these properties when discretizing or approximating the mathematical model. One possible approach is to preserve the properties by maintaining a certain structure of the governing equations. Well-known examples include GENERIC [GO97], gradient [HS74], Hamiltonian [Arn89], or port-Hamiltonian (pH) [vdSJ14] structures.

PH systems extend classical Hamiltonian systems by taking internal energy dissipation and energy exchange with the environment or other subsystems into account. As a consequence, these systems ensure that the corresponding Hamiltonian, which often represents an energy, satisfies a dissipation inequality. Therefore, pH systems are passive and under additional assumptions on the Hamiltonian also stable, see e.g. [vdSJ14]. Furthermore, power-preserving interconnections of pH systems lead again to a pH system, which makes the pH formalism especially useful for control [MvdS92, VLM16, SPF⁺21] and for network modeling [vdS04, HMM⁺20, AMU21]. Besides, the pH formalism is well-suited for multiphysics applications where energy serves as the *lingua franca* between different physical domains, see e.g. [VS14, CRMPB17, KS21]. Moreover, mathematical models for which pH formulations are already available cover a wide range of application areas including chemistry [HCJLG11, RMS13, WMvdS18], electromagnetism [PMH20, GHRvdS21],

Date: July 19, 2024.

mechanics [MM04, AS17, BAPBM19, RCSS21], and thermodynamics [EM04, LKL21]. While originally introduced for finite-dimensional ODE systems, the pH formalism has been extended to infinite-dimensional systems [JZ12, RCvdSS20, MZ23] and to port-Hamiltonian differential-algebraic equations (pH-DAEs) [vdSM20, MvdS23, MU23]. In addition, numerical schemes have been derived which preserve pH structures under discretization [Kot19, BRS22, Mor24, GKT24] or model order reduction [PvdS12, GPBvdS12, CBG16].

Within this paper, we consider dynamical systems which can be written in the form

(1.1)
$$\begin{bmatrix} \partial_{z_1} H\\ \dot{z}_2\\ 0 \end{bmatrix} = (\mathbf{J} - \mathbf{R}) \begin{bmatrix} \dot{z}_1\\ \partial_{z_2} H\\ z_3 \end{bmatrix}$$

for some given energy function H, possibly with additional inputs or inhomogeneities, see the precise definition in Section 2. Such a structure includes classical pH systems (with vanishing z_1, z_3) as well as gradient systems (with vanishing z_2, z_3). The proposed framework seems especially suited for constrained systems with poroelasticity as a prominent example. For poroelasticity, pH formulations require an extension of the system [AMU21], which is not necessary in the proposed setting. Moreover, the state z_3 provides more freedom in modeling and, hence, enlarges the applicability of the framework as we will prove by a broad list of examples.

Within Section 2, we prove that systems of the form (1.1) are (just as pH systems) automatically energy dissipative. We further show that the interconnection of two such systems preserves the structure if the connection is done in a power-preserving manner and discuss how Petrov–Galerkin projections need to be designed in order to preserve the proposed structure. In terms of time stepping schemes, we consider the midpoint scheme as well as discrete gradient methods. Both approaches are shown to be dissipation-preserving, i.e., also the discrete energy dissipates for vanishing inputs. Finally, Section 3 provides ten examples which fit in the given framework. This includes finite-dimensional examples as well as PDE models with a corresponding structure.

Notation. Throughout this paper, we use the Matlab notation for vectors, i.e., we write $[x;y] := [x^T, y^T]^T$ for two column vectors x, y. Besides, we use $\text{Diag}(\mathbf{A}_1, \mathbf{A}_2, \dots, \mathbf{A}_k)$ to denote (block) diagonal matrices with diagonal (block) entries $\mathbf{A}_1, \dots, \mathbf{A}_k$. To indicate that a matrix \mathbf{A} is positive (semi-)definite, we write $\mathbf{A} > 0$ ($\mathbf{A} \ge 0$). Moreover, we introduce the empty vector \bullet in order to distinguish it from possible zero entries. With this, we have, e.g., $[x; \bullet] = x$. For the Euclidean inner product, we write $\langle x, y \rangle = x^T y$.

2. Energy-Based Modeling Framework

This section is devoted to the introduction of an energy-based framework, which is especially suited for constrained systems. Consider a state $z = [z_1; z_2; z_3] \in \mathbb{R}^{n_1+n_2+n_3}$, $n \coloneqq n_1 + n_2 + n_3$, and an energy function $H(t) = H(z_1(t), z_2(t))$. For a skew-symmetric matrix $\mathbf{J} = -\mathbf{J}^T \in \mathbb{R}^{n,n}$ and a symmetric positive semi-definite matrix $\mathbf{R} = \mathbf{R}^T \in \mathbb{R}^{n,n}$, we consider the model equations

(2.1a)
$$\begin{bmatrix} \partial_{z_1} H \\ \dot{z}_2 \\ 0 \end{bmatrix} = (\mathbf{J} - \mathbf{R}) \begin{bmatrix} \dot{z}_1 \\ \partial_{z_2} H \\ z_3 \end{bmatrix} + \begin{bmatrix} \mathbf{B}_1 \\ \mathbf{B}_2 \\ \mathbf{B}_3 \end{bmatrix} u,$$

(2.1b)
$$y = \begin{bmatrix} \mathbf{B}_1^T & \mathbf{B}_2^T & \mathbf{B}_3^T \end{bmatrix} \begin{bmatrix} \dot{z}_1 \\ \partial_{z_2} H \\ z_3 \end{bmatrix}.$$

Therein, $u, y \in \mathbb{R}^m$ denote the in- and outputs and $\mathbf{B}_i \in \mathbb{R}^{n_i, m}$ are arbitrary matrices. We would like to emphasize that the state z_3 is not part of the energy. The introduction of such a state, however, enlarges the class of possible applications as we will illustrate in Section 3.

Remark 2.1. For simplicity, we consider constant matrices \mathbf{J} , \mathbf{R} , and \mathbf{B}_i in (2.1). However, we emphasize that the results presented in the following extend to the case where these matrices depend on time or the state, as long as \mathbf{J} and \mathbf{R} are pointwise skew-symmetric and symmetric positive semi-definite, respectively.

Remark 2.2. In the special case $z_3 = 0$, $\mathbf{R} = 0$, and u = 0, system (2.1) reduces to a hybrid representation of a Dirac structure as presented in [vdSJ14, Sect. 5.3]. Such representations are obtained by exchanging parts of the effort and flow variables and, thereby, differ from the classical input-state-output representation of pH systems where the flows are expressed in terms of the efforts, cf. [vdSJ14, Sect. 4.2].

2.1. Energy dissipation and interconnections. We summarize properties of system (2.1). Similar as for pH systems, we prove energy dissipation and discuss power-preserving interconnections.

Lemma 2.3 (energy dissipation). The energy satisfies $\frac{d}{dt}H \leq \langle y, u \rangle$. In particular, system (2.1) is energy dissipative for vanishing inputs.

Proof. Due to the assumptions on **J** and **R**, a direct calculation shows

$$\begin{split} \frac{\mathrm{d}}{\mathrm{d}t}H(t) &= \langle \partial_{z_1}H, \dot{z}_1 \rangle + \langle \partial_{z_2}H, \dot{z}_2 \rangle \\ &= \left\langle \begin{bmatrix} \dot{z}_1 \\ \partial_{z_2}H \\ z_3 \end{bmatrix}, \begin{bmatrix} \partial_{z_1}H \\ \dot{z}_2 \\ 0 \end{bmatrix} \right\rangle \\ &= -\left\langle \begin{bmatrix} \dot{z}_1 \\ \partial_{z_2}H \\ z_3 \end{bmatrix}, \mathbf{R} \begin{bmatrix} \dot{z}_1 \\ \partial_{z_2}H \\ z_3 \end{bmatrix} \right\rangle + \left\langle \begin{bmatrix} \dot{z}_1 \\ \partial_{z_2}H \\ z_3 \end{bmatrix}, \begin{bmatrix} \mathbf{B}_1 \\ \mathbf{B}_2 \\ \mathbf{B}_3 \end{bmatrix} u \right\rangle \leq \langle y, u \rangle. \end{split}$$

Hence, we have $\frac{d}{dt}H \leq 0$ in the case u = 0.

Similarly as for pH systems (see, e.g., [MM19]), the structure of (2.1) is preserved under power-conserving as well as dissipative interconnections as the following lemma shows.

Lemma 2.4 (structure-preserving interconnection). Consider two systems of the form (2.1), namely

F • 1 -

$$\begin{bmatrix} \partial_1 H^{[i]} \\ \dot{z}_2^{[i]} \\ 0 \end{bmatrix} = \left(\mathbf{J}^{[i]} - \mathbf{R}^{[i]} \right) \begin{bmatrix} \dot{z}_1^{[i]} \\ \partial_2 H^{[i]} \\ z_3^{[i]} \end{bmatrix} + \begin{bmatrix} \mathbf{B}_1^{[i]} \\ \mathbf{B}_2^{[i]} \\ \mathbf{B}_3^{[i]} \end{bmatrix} u^{[i]},$$

$$y^{[i]} = \begin{bmatrix} \mathbf{B}_{1}^{[i] T} & \mathbf{B}_{2}^{[i] T} & \mathbf{B}_{3}^{[i] T} \end{bmatrix} \begin{bmatrix} \dot{z}_{1}^{[i]} \\ \partial_{2} H^{[i]} \\ z_{3}^{[i]} \end{bmatrix}$$

with respective states $z^{[1]}$, $z^{[2]}$, energy functions $H^{[1]}$, $H^{[2]}$, and the short notation $\partial_k H^{[i]} = \partial_{z_h^{[i]}} H^{[i]}$. Then an interconnection of the form

$$\begin{bmatrix} u^{[1]} \\ u^{[2]} \end{bmatrix} = \left(\mathbf{F}_{skew} - \mathbf{F}_{sym} \right) \begin{bmatrix} y^{[1]} \\ y^{[2]} \end{bmatrix} + \begin{bmatrix} \tilde{u}^{[1]} \\ \tilde{u}^{[2]} \end{bmatrix}$$

with $\mathbf{F}_{skew} = -\mathbf{F}_{skew}^{T}$ and positive semi-definite $\mathbf{F}_{sym} = \mathbf{F}_{sym}^{T}$ yields again a system of the form (2.1).

Proof. We define

$$z_1 \coloneqq \begin{bmatrix} z_1^{[1]} \\ z_1^{[2]} \end{bmatrix}, \quad z_2 \coloneqq \begin{bmatrix} z_2^{[1]} \\ z_2^{[2]} \end{bmatrix}, \quad z_3 \coloneqq \begin{bmatrix} z_3^{[1]} \\ z_3^{[2]} \end{bmatrix}, \quad u \coloneqq \begin{bmatrix} u^{[1]} \\ u^{[2]} \end{bmatrix}, \quad \tilde{u} \coloneqq \begin{bmatrix} \tilde{u}^{[1]} \\ \tilde{u}^{[2]} \end{bmatrix}, \quad y \coloneqq \begin{bmatrix} y^{[1]} \\ y^{[2]} \end{bmatrix}$$

and the total energy $H(z) \coloneqq H^{[1]}(z^{[1]}) + H^{[2]}(z^{[2]})$. Assuming the block structure

$$\mathbf{J}^{[i]} = \begin{bmatrix} \mathbf{J}_{11}^{[i]} & \mathbf{J}_{12}^{[i]} & \mathbf{J}_{13}^{[i]} \\ -\mathbf{J}_{12}^{[i]T} & \mathbf{J}_{22}^{[i]} & \mathbf{J}_{23}^{[i]} \\ -\mathbf{J}_{13}^{[i]T} & -\mathbf{J}_{23}^{[i]T} & \mathbf{J}_{33}^{[i]} \end{bmatrix}, \qquad \mathbf{R}^{[i]} = \begin{bmatrix} \mathbf{R}_{11}^{[i]} & \mathbf{R}_{12}^{[i]} & \mathbf{R}_{13}^{[i]} \\ \mathbf{R}_{12}^{[i]T} & \mathbf{R}_{22}^{[i]} & \mathbf{R}_{23}^{[i]} \\ \mathbf{R}_{13}^{[i]T} & \mathbf{R}_{23}^{[i]T} & \mathbf{R}_{33}^{[i]} \end{bmatrix},$$

we define the matrices

$$\mathbf{J} \coloneqq \begin{bmatrix} \mathbf{J}_{11}^{[1]} & 0 & \mathbf{J}_{12}^{[1]} & 0 & \mathbf{J}_{13}^{[1]} & 0 \\ 0 & \mathbf{J}_{11}^{[2]} & 0 & \mathbf{J}_{12}^{[2]} & 0 & \mathbf{J}_{13}^{[2]} \\ -\mathbf{J}_{12}^{[1]T} & 0 & \mathbf{J}_{22}^{[1]T} & 0 & \mathbf{J}_{23}^{[1]} & 0 \\ 0 & -\mathbf{J}_{12}^{[2]T} & 0 & \mathbf{J}_{22}^{[2]} & 0 & \mathbf{J}_{23}^{[2]} \\ -\mathbf{J}_{13}^{[1]T} & 0 & -\mathbf{J}_{23}^{[1]T} & 0 & \mathbf{J}_{33}^{[1]} & 0 \\ 0 & -\mathbf{J}_{13}^{[2]T} & 0 & -\mathbf{J}_{23}^{[2]T} & 0 & \mathbf{J}_{33}^{[2]} \end{bmatrix}, \qquad \mathbf{B} \coloneqq \begin{bmatrix} \mathbf{B}_{1}^{[1]} & 0 \\ 0 & \mathbf{B}_{1}^{[2]} \\ \mathbf{B}_{2}^{[1]} & 0 \\ 0 & \mathbf{B}_{2}^{[2]} \\ \mathbf{B}_{3}^{[1]} & 0 \\ 0 & \mathbf{B}_{3}^{[2]} \end{bmatrix},$$

and **R** correspondingly. Since $\mathbf{J}^{[i]}$ is skew-symmetric, so are $\mathbf{J}_{11}^{[i]}$, $\mathbf{J}_{22}^{[i]}$ and $\mathbf{J}_{33}^{[i]}$ for i = 1, 2. Hence, **J** is skew-symmetric. Similarly, it follows that **R** is symmetric. Moreover, by permuting the block rows and columns of **R** as $\{1, 2, 3, 4, 5, 6\} \rightarrow \{1, 3, 5, 2, 4, 6\}$, one observes that **R** is congruent to $\text{Diag}(\mathbf{R}^{[1]}, \mathbf{R}^{[2]})$ and, therefore, positive semi-definite. The two output equations can be combined to

$$y = \begin{bmatrix} y^{[1]} \\ y^{[2]} \end{bmatrix} = \begin{bmatrix} \mathbf{B}_{1}^{[1]T} & 0 & \mathbf{B}_{2}^{[1]T} & 0 & \mathbf{B}_{3}^{[1]T} & 0 \\ 0 & \mathbf{B}_{1}^{[2]T} & 0 & \mathbf{B}_{2}^{[2]T} & 0 & \mathbf{B}_{3}^{[2]T} \end{bmatrix} \begin{bmatrix} \dot{z}_{1}^{[1]} \\ \dot{z}_{1}^{[2]} \\ \partial_{2}H^{[1]} \\ \partial_{2}H^{[2]} \\ z_{3}^{[1]} \\ z_{3}^{[2]} \end{bmatrix} =: \mathbf{B}^{T} \begin{bmatrix} \dot{z}_{1} \\ \partial_{z_{2}}H \\ z_{3} \end{bmatrix}.$$

The interconnection equation reads $u = (\mathbf{F}_{skew} - \mathbf{F}_{sym}) y + \tilde{u}$. With this, we get

$$\begin{bmatrix} \partial_{z_1} H \\ \dot{z}_2 \\ 0 \end{bmatrix} = (\mathbf{J} - \mathbf{R}) \begin{bmatrix} \dot{z}_1 \\ \partial_{z_2} H \\ z_3 \end{bmatrix} + \mathbf{B} (\mathbf{F}_{\text{skew}} - \mathbf{F}_{\text{sym}}) y + \mathbf{B} \tilde{u}$$
$$= \left((\mathbf{J} + \mathbf{B} \mathbf{F}_{\text{skew}} \mathbf{B}^T) - (\mathbf{R} + \mathbf{B} \mathbf{F}_{\text{sym}} \mathbf{B}^T) \right) \begin{bmatrix} \dot{z}_1 \\ \partial_{z_2} H \\ z_3 \end{bmatrix} + \mathbf{B} \tilde{u},$$

which is again of the form (2.1), since $\mathbf{BF}_{skew}\mathbf{B}^T$ is skew-symmetric and $\mathbf{BF}_{sym}\mathbf{B}^T$ symmetric positive semi-definite.

2.2. **Petrov–Galerkin projection.** Next, we discuss the restriction of the dynamics as considered, e.g, in model order reduction. For this, we restrict ourselves to a quadratic Hamiltonian. More precisely, we assume that

(2.2)
$$H = H(z_1, z_2) = \frac{1}{2} \langle z_1, \mathbf{M}_1 z_1 \rangle + \frac{1}{2} \langle z_2, \mathbf{M}_2 z_2 \rangle$$

with symmetric matrices $\mathbf{M}_1 \in \mathbb{R}^{n_1, n_1}$ and $\mathbf{M}_2 \in \mathbb{R}^{n_2, n_2}$.

Lemma 2.5 (structure-preserving Petrov–Galerkin projection). Consider a quadratic Hamiltonian as in (2.2) and vanishing inputs. Further assume full-rank matrices

$$\mathbf{V}_1 \in \mathbb{R}^{n_1, r_1}, \qquad \mathbf{V}_2 \in \mathbb{R}^{n_2, r_2}, \qquad \mathbf{V}_3 \in \mathbb{R}^{n_3, r_3}$$

with $r_j \leq n_j$, j = 1, 2, 3, spanning approximation spaces of lower dimension such that $V_2^T M_2 V_2$ is invertible. Then the Petrov-Galerkin approximation with test spaces \mathbf{V}_1 , $\mathbf{M}_2 \mathbf{V}_2$, and \mathbf{V}_3 yield again a system of the form (2.1).

Proof. For the solution $[z_1; z_2; z_3] \in \mathbb{R}^{n_1+n_2+n_3}$, we consider (Galerkin) approximations defined through $[y_1; y_2; y_3] \in \mathbb{R}^{r_1+r_2+r_3}$ via

$$z_1 \approx \mathbf{V}_1 y_1, \qquad z_2 \approx \mathbf{V}_2 y_2, \qquad z_3 \approx \mathbf{V}_3 y_3.$$

The corresponding energy reads $\tilde{H} = \frac{1}{2} \langle \mathbf{V}_1 y_1, \mathbf{M}_1 \mathbf{V}_1 y_1 \rangle + \frac{1}{2} \langle \mathbf{V}_2 y_2, \mathbf{M}_2 \mathbf{V}_2 y_2 \rangle$ and the approximate solutions solve the reduced dynamics which are obtained by restricting the test space. For this, we require the residual to be orthogonal to \mathbf{V}_1 , $\mathbf{M}_2 \mathbf{V}_2$, and \mathbf{V}_3 , respectively. Hence, $[y_1; y_2; y_3]$ solves the reduced system

$$\begin{bmatrix} \mathbf{V}_1^T & 0 & 0\\ 0 & \mathbf{V}_2^T \mathbf{M}_2 & 0\\ 0 & 0 & \mathbf{V}_3^T \end{bmatrix} \begin{bmatrix} \mathbf{M}_1 \mathbf{V}_1 y_1\\ \mathbf{V}_2 \dot{y}_2\\ 0 \end{bmatrix} = \begin{bmatrix} \mathbf{V}_1^T & 0 & 0\\ 0 & \mathbf{V}_2^T \mathbf{M}_2 & 0\\ 0 & 0 & \mathbf{V}_3^T \end{bmatrix} (\mathbf{J} - \mathbf{R}) \begin{bmatrix} \mathbf{V}_1 & 0 & 0\\ 0 & \mathbf{M}_2 \mathbf{V}_2 & 0\\ 0 & 0 & \mathbf{V}_3 \end{bmatrix} \begin{bmatrix} \dot{y}_1\\ y_2\\ y_3 \end{bmatrix}$$

In order to bring this system in the form (2.1), we introduce $w = [y_1; \mathbf{V}_2^T \mathbf{M}_2 \mathbf{V}_2 y_2; y_3]$ as state. This yields $\partial_{w_1} \tilde{H} = \mathbf{V}_1^T \mathbf{M}_1 \mathbf{V}_1 y_1$ and $\partial_{w_2} \tilde{H} = (\mathbf{V}_2^T \mathbf{M}_2 \mathbf{V}_2)^{-1} w_2 = y_2$. With this, the reduced system has the form

$$\begin{bmatrix} \partial_{w_1} \tilde{H} \\ \dot{w}_2 \\ 0 \end{bmatrix} = (\tilde{\mathbf{J}} - \tilde{\mathbf{R}}) \begin{bmatrix} \dot{w}_1 \\ \partial_{w_2} \tilde{H} \\ w_3 \end{bmatrix}$$

with $\tilde{\mathbf{J}} = \text{Diag}(\mathbf{V}_1, \mathbf{M}_2\mathbf{V}_2, \mathbf{V}_3)^T \mathbf{J}$ $\text{Diag}(\mathbf{V}_1, \mathbf{M}_2\mathbf{V}_2, \mathbf{V}_3)$ being skew-symmetric and, similarly, $\tilde{\mathbf{R}} = \text{Diag}(\mathbf{V}_1, \mathbf{M}_2\mathbf{V}_2, \mathbf{V}_3)^T \mathbf{R}$ $\text{Diag}(\mathbf{V}_1, \mathbf{M}_2\mathbf{V}_2, \mathbf{V}_3)$ being symmetric positive semidefinite.

Remark 2.6. Although the projection scheme in Lemma 2.5 ensures structure preservation, the algebraic constraints are, in general, not preserved. Constraint-preserving model reduction techniques typically rely on a splitting of the differential and the algebraic part of the system and subsequent reduction of the differential part only. For a general overview on model reduction for DAEs, we refer to [BS17].

2.3. Discretization in time. In this section, we finally discuss two particular time discretization schemes which are dissipation-preserving. First, we apply the midpoint rule to (2.1) and show that the discrete energy dissipates as well if the Hamiltonian is quadratic. For this, we assume an equidistant partition of the time interval [0, T] with constant step size τ , leading to discrete time points $t^n \coloneqq n\tau$. Accordingly, we denote by x^n the approximation of some variable x at time t^n . Moreover, we make use of the typical notation $x^{n+1/2} = \frac{1}{2}(x^n + x^{n+1})$ and $u^{n+1/2} = u(t^{n+1/2})$ for the input. The midpoint rule applied to (2.1) then yields

(2.3a)
$$\begin{bmatrix} \tau \partial_{z_1} H^{n+1/2} \\ z_2^{n+1} - z_2^n \\ 0 \end{bmatrix} = (\mathbf{J} - \mathbf{R}) \begin{bmatrix} z_1^{n+1} - z_1^n \\ \tau \partial_{z_2} H^{n+1/2} \\ \tau z_3^{n+1/2} \end{bmatrix} + \tau \begin{bmatrix} \mathbf{B}_1 \\ \mathbf{B}_2 \\ \mathbf{B}_3 \end{bmatrix} u^{n+1/2},$$
(2.3b)
$$\tau y^{n+1/2} = \begin{bmatrix} \mathbf{B}_1^T & \mathbf{B}_2^T & \mathbf{B}_3^T \end{bmatrix} \begin{bmatrix} z_1^{n+1} - z_1^n \\ \tau \partial_{z_2} H^{n+1/2} \\ \tau z_3^{n+1/2} \end{bmatrix}.$$

The following result states the property of being dissipation-preserving for quadratic Hamiltonians.

Lemma 2.7 (discrete energy dissipation, midpoint rule). Let the Hamiltonian be quadratic as in (2.2) and set $H^n := H(z^n)$. Then the midpoint scheme (2.3) satisfies $H^{n+1} - H^n \leq \tau \langle y^{n+1/2}, u^{n+1/2} \rangle$ and, in particular, $H^{n+1} \leq H^n$ for vanishing inputs.

Proof. We first note that

$$2H(z) = \langle z_1, \mathbf{M}_1 z_1 \rangle + \langle z_2, \mathbf{M}_2 z_2 \rangle = \langle z_1, \partial_{z_1} H \rangle + \langle z_2, \partial_{z_2} H \rangle = \langle z, \partial_z H \rangle.$$

With this, we conclude that

$$H^{n+1} - H^n = \left\langle z^{n+1} - z^n, \partial_z H^{n+1/2} \right\rangle = \left\langle \begin{bmatrix} z_1^{n+1} - z_1^n \\ \partial_{z_2} H^{n+1/2} \\ z_3^{n+1/2} \end{bmatrix}, \begin{bmatrix} \partial_{z_1} H^{n+1/2} \\ z_2^{n+1} - z_2^n \\ 0 \end{bmatrix} \right\rangle$$

Together with (2.3), this yields

$$\tau \left(H^{n+1} - H^n \right) = \left\langle \begin{bmatrix} z_1^{n+1} - z_1^n \\ \tau \partial_{z_2} H^{n+1/2} \\ \tau z_3^{n+1/2} \end{bmatrix}, \begin{bmatrix} \tau \partial_{z_1} H^{n+1/2} \\ z_2^{n+1} - z_2^n \\ 0 \end{bmatrix} \right\rangle \le \left\langle \tau y^{n+1/2}, \tau u^{n+1/2} \right\rangle,$$

which completes the proof.

The second discretization scheme is based on discrete gradients and does not require the Hamiltonian to be a quadratic function of the state. Discrete gradients have been originally introduced in [Gon96] for Hamiltonian systems and are also used for discretizing dissipative and pH systems, cf. [MQR99, CH17, KTBK23, FGLSM24, Sch24]. A continuous map $\overline{\nabla}H \colon \mathbb{R}^n \times \mathbb{R}^n \to \mathbb{R}^n$ with $n = n_1 + n_2$ is called a discrete gradient of H if it satisfies

(2.4)
$$\overline{\nabla}H(z,z) = z$$
 and $\langle \overline{\nabla}H(z,z'), z'-z \rangle = H(z') - H(z)$ for all $z, z' \in \mathbb{R}^n$

Examples for the explicit construction of discrete gradients are presented, e.g., in [MQR99, Eid22]. In the following, we use the notation $\overline{\partial_{z_1}}H$ and $\overline{\partial_{z_2}}H$ to denote the first n_1 and the last n_2 entries of $\overline{\nabla}H$, respectively, and we propose the time discrete system

(2.5a)
$$\begin{bmatrix} \tau \overline{\partial_{z_1}} H\left(\begin{bmatrix} z_1^n \\ z_2^n \end{bmatrix}, \begin{bmatrix} z_1^{n+1} \\ z_2^{n+1} - z_1^n \end{bmatrix} \right) \\ z_2^{n+1} - z_2^n \\ 0 \end{bmatrix} = (\mathbf{J} - \mathbf{R}) \begin{bmatrix} z_1^{n+1} - z_1^n \\ \tau \overline{\partial_{z_2}} H\left(\begin{bmatrix} z_1^n \\ z_2^n \end{bmatrix}, \begin{bmatrix} z_1^{n+1} \\ z_2^{n+1/2} \end{bmatrix} \right) \\ \tau z_3^{n+1/2} \end{bmatrix} + \tau \begin{bmatrix} \mathbf{B}_1 \\ \mathbf{B}_2 \\ \mathbf{B}_3 \end{bmatrix} u^{n+1/2},$$
(2.5b)
$$\tau y^{n+1/2} = \begin{bmatrix} \mathbf{B}_1^T & \mathbf{B}_2^T & \mathbf{B}_3^T \end{bmatrix} \begin{bmatrix} z_1^{n+1} - z_1^n \\ \tau \overline{\partial_{z_2}} H\left(\begin{bmatrix} z_1^n \\ z_2^n \end{bmatrix}, \begin{bmatrix} z_1^{n+1} - z_1^n \\ z_2^{n+1/2} \end{bmatrix} \right) \\ \tau z_3^{n+1/2} \end{bmatrix}.$$

Here, we use for simplicity the midpoint approximation $u^{n+1/2}$ as input. Note, however, that the following lemma and its proof can be easily extended to other consistent time discretizations of u.

Lemma 2.8 (discrete energy dissipation, discrete gradient method). The discrete gradient scheme (2.5) satisfies $H^{n+1} - H^n \leq \tau \langle y^{n+1/2}, u^{n+1/2} \rangle$ and, in particular, $H^{n+1} \leq H^n$ for vanishing inputs.

Proof. We use the second equation in (2.4) and proceed similarly as in the proof of Lemma 2.7 to obtain

$$\begin{split} \tau \left(H^{n+1} - H^n \right) &= \tau \left\langle \overline{\nabla} H \left(\begin{bmatrix} z_1^n \\ z_2^n \end{bmatrix}, \begin{bmatrix} z_1^{n+1} \\ z_2^{n+1} \end{bmatrix} \right), \begin{bmatrix} z_1^{n+1} - z_1^n \\ z_2^{n+1} - z_1^n \end{bmatrix} \right\rangle \\ &= \left\langle \begin{bmatrix} z_1^{n+1} - z_1^n \\ \tau \overline{\partial}_{z_2} H \left(\begin{bmatrix} z_1^n \\ z_2^n \end{bmatrix}, \begin{bmatrix} z_1^{n+1} \\ z_2^{n+1} \end{bmatrix} \right) \\ \tau z_3^{n+1/2} \end{bmatrix}, \begin{bmatrix} \tau \overline{\partial}_{z_1} H \left(\begin{bmatrix} z_1^n \\ z_2^n \end{bmatrix}, \begin{bmatrix} z_1^{n+1} \\ z_2^{n+1} \end{bmatrix} \right) \\ z_2^{n+1} - z_2^n \\ 0 \end{bmatrix} \right\rangle \\ &\leq \left\langle \tau y^{n+1/2}, \tau u^{n+1/2} \right\rangle. \end{split}$$

After the introduction of the energy-based framework and the discussion of important properties, we now turn to specific examples.

3. Collection of Examples

We start with examples which do not need the third variable z_3 . This includes classical input-state-output pH systems as well as the equations of poroelasticity. For semi-explicit DAEs of index 2, we will see that z_3 allows the direct formulation without the need of an index reduction. Afterwards, we consider circuit models and constrained mechanical systems. Finally, we give three (constrained) PDE examples, which fit in the given framework if the matrices are replaced by operators with analogous properties.

3.1. Example I: pH systems and gradient systems. Consider an input–state–output pH system (without constraints) as in [vdSJ14, Sect. 4.2]. Without feedthrough term, such a system has the form

$$\dot{x} = (\mathbf{J} - \mathbf{R}) \,\partial_x H(x) + \mathbf{B}u,$$
$$y = \mathbf{B}^T \partial_x H(x).$$

This directly translates into the form (2.1) with $z_1 = \bullet$ (no z_1 variable needed), $z_2 = x$, and $z_3 = \bullet$. On the other hand, one may consider a gradient system as in [EHS21], i.e.,

$$\mathbf{C}(u)\dot{u} = -\partial_u H(u)$$

with **C** being symmetric positive definite. In this case, we reach the form (2.1) with the state $z = [u; \bullet; \bullet]$ and $\mathbf{J} = 0$, $\mathbf{R} = \mathbf{C}$. If **C** is skew-symmetric instead, then we have a Hamiltonian system and set $\mathbf{J} = \mathbf{C}$, $\mathbf{R} = 0$.

3.2. Example II: poroelasticity. We now turn to a first DAE example for which the introduced setting is more suitable than the classical pH framework. A spatial discretization of the linear poroelasticity equations [Bio41, Sho00] yields the DAE

(3.1)
$$\begin{bmatrix} 0 & 0 \\ \mathbf{D} & \mathbf{C} \end{bmatrix} \begin{bmatrix} \dot{u} \\ \dot{p} \end{bmatrix} = \begin{bmatrix} -\mathbf{A} & \mathbf{D}^T \\ 0 & -\mathbf{B} \end{bmatrix} \begin{bmatrix} u \\ p \end{bmatrix} + \begin{bmatrix} f \\ g \end{bmatrix}$$

with initial conditions $u(0) = u^0$, $p(0) = p^0$. Here, the unknowns u and p model the deformation of the material and the pressure of the fluid, respectively. The stiffness matrix $\mathbf{A} \in \mathbb{R}^{n_u,n_u}$ describes the elasticity in the mechanical part of the problem. Assuming a suitable discretization, which also includes the (homogeneous) boundary conditions, \mathbf{A} is symmetric positive definite. The same applies for $\mathbf{B} \in \mathbb{R}^{n_p,n_p}$, which equals the stiffness matrix related to the fluid flow. Moreover, $\mathbf{C} \in \mathbb{R}^{n_p,n_p}$ is a mass matrix which describes the compressibility of the fluid under pressure and is also assumed to be symmetric positive definite. Finally, $\mathbf{D} \in \mathbb{R}^{n_p,n_u}$ is a rectangular matrix of full (row) rank. The energy, which is relevant from a physical point of view, reads

(3.2)
$$H(t) = \frac{1}{2} \left\langle u(t), \mathbf{A}u(t) \right\rangle + \frac{1}{2} \left\langle p(t), \mathbf{C}p(t) \right\rangle.$$

In [AMU21], the pH structure of (3.1) has been discussed. One possibility is to consider an extended system with the additional variable $w = \dot{u}$. With this, the system can be written in the form

$$\begin{bmatrix} 0 & 0 & 0 \\ 0 & \mathbf{A} & 0 \\ 0 & 0 & \mathbf{C} \end{bmatrix} \begin{bmatrix} \dot{w} \\ \dot{u} \\ \dot{p} \end{bmatrix} = \begin{bmatrix} 0 & -\mathbf{A} & \mathbf{D}^T \\ \mathbf{A} & 0 & 0 \\ -\mathbf{D} & 0 & -\mathbf{B} \end{bmatrix} \begin{bmatrix} w \\ u \\ p \end{bmatrix} + \begin{bmatrix} f \\ 0 \\ g \end{bmatrix},$$

which has the typical pH structure $\mathbf{E}\dot{z} = (\mathbf{J}-\mathbf{R})z + h$ with $z = [w; u; p], \mathbf{E} = \text{Diag}(0, \mathbf{A}, \mathbf{C}),$

$$\mathbf{J} = \begin{bmatrix} 0 & -\mathbf{A} & \mathbf{D}^T \\ \mathbf{A} & 0 & 0 \\ -\mathbf{D} & 0 & 0 \end{bmatrix} = -\mathbf{J}^T, \qquad \mathbf{R} = \begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & \mathbf{B} \end{bmatrix} = \mathbf{R}^T \ge 0.$$

The corresponding Hamiltonian $H = \frac{1}{2} \langle z, \mathbf{E}z \rangle$ coincides with the energy (3.2) and satisfies (for vanishing right-hand sides) $\frac{d}{dt}H = \langle z, \mathbf{E}\dot{z} \rangle = -\langle z, \mathbf{R}z \rangle = -\langle p, \mathbf{B}p \rangle \leq 0.$

An alternative formulation, also presented in [AMU21], can be obtained by the introduction of a more artificial variable q via $\mathbf{B}q = \mathbf{D}u + \mathbf{C}p$. This then leads to a pH formulation with a different energy. We would like to emphasize that both formulations require an extension of the system equations in order to obtain the desired pH structure. This is not desirable, since the involved matrices are usually large as they result from a spatial discretization of the original PDE system.

The energy-based framework (2.1), in turn, allows a direct formulation without any extensions. For this, we set $z = [u; \mathbf{C}p; \bullet]$. Due to $\partial_{z_1}H = \mathbf{A}u$ and $\partial_{z_2}H = \mathbf{C}^{-1}z_2 = p$, we can rewrite (3.1) as

$$\begin{bmatrix} \mathbf{A}u \\ \mathbf{C}\dot{p} \end{bmatrix} = \begin{bmatrix} 0 & \mathbf{D}^T \\ -\mathbf{D} & -\mathbf{B} \end{bmatrix} \begin{bmatrix} \dot{u} \\ p \end{bmatrix} + \begin{bmatrix} f \\ g \end{bmatrix}.$$

The dissipation inequality from Lemma 2.3 then directly implies $\frac{d}{dt}H = -\langle p, \mathbf{B}p \rangle$ for the homogeneous case.

Remark 3.1. If the permeability is allowed to depend on the porosity of the material, the diffusion term in the second equation of (3.1) depends (in a nonlinear way) on the displacement u, cf. [CCM13]. Hence, the constant matrix **B** from the linear model turns into **B**(u). Assuming the same assumptions as in the linear case with **B**(u) being symmetric and (uniformly) positive definite, we recover the structure from the linear case. Hence, also nonlinear poroelasticity can be written in the form (2.1), cf. Remark 2.1.

3.3. Example III: a class of index-1 DAEs. In the previous section, we have discovered that the equations of poroelasticity provide a DAE, where the pH formulation does not seem to be the natural choice of modeling. In fact, DAEs where the Hamiltonian equals a quadratic norm of the entire state cannot be modeled as a pH system without extending the system equations. A particular class of such DAEs has the form

$$\mathbf{D}\dot{z}_1 + \dot{z}_2 = (\mathbf{J}_2 - \mathbf{R}_2) \,\mathbf{M}_2 z_2,$$
$$0 = \mathbf{M}_1 z_1 - \mathbf{D}^T \mathbf{M}_2 z_2$$

with $\mathbf{J}_2 = -\mathbf{J}_2^T$, $\mathbf{R}_2 = \mathbf{R}_2^T \ge 0$ and $\mathbf{M}_1 = \mathbf{M}_1^T > 0$, $\mathbf{M}_2 = \mathbf{M}_2^T > 0$. Note that the first equation gives a differential equation for z_2 , whereas the second equation provides an algebraic equation which can be solved for z_1 . Hence, the system is of index 1. We proceed with defining the state $z = [z_1; z_2; \bullet]$ and the quadratic energy

$$H(t) = \frac{1}{2} \left\langle z_1(t), \mathbf{M}_1 z_1(t) \right\rangle + \frac{1}{2} \left\langle z_2(t), \mathbf{M}_2 z_2(t) \right\rangle.$$

Due to $\partial_{z_1} H = \mathbf{M}_1 z_1$ and $\partial_{z_2} H = \mathbf{M}_2 z_2$, the above DAE can be written in the form (2.1), namely

$$\begin{bmatrix} \mathbf{M}_1 z_1 \\ \dot{z}_2 \end{bmatrix} = \left(\begin{bmatrix} 0 & \mathbf{D}^T \\ -\mathbf{D} & \mathbf{J}_2 \end{bmatrix} - \begin{bmatrix} 0 & 0 \\ 0 & \mathbf{R}_2 \end{bmatrix} \right) \begin{bmatrix} \dot{z}_1 \\ \mathbf{M}_2 z_2 \end{bmatrix}$$

3.4. Example IV: semi-explicit index-2 DAEs. Consider a semi-explicit DAE

- (3.3a) $\mathbf{M}\dot{u} + \mathbf{A}u + \mathbf{B}^T \lambda = f,$
- (3.3b) Bu = g

with symmetric positive definite matrices \mathbf{M} , \mathbf{A} and a full-rank matrix \mathbf{B} . In this case, we have a system of index 2; see [HW96, Ch. VII.1]. One possible strategy to reduce the index of the system is the introduction of a singular perturbation in the second equation. More precisely, we may replace the original DAE by the system

$$\mathbf{M}\dot{u} + \mathbf{A}u + \mathbf{B}^T\lambda = f,$$

$$\varepsilon^2 \dot{\lambda} + \mathbf{B}u = g$$

with a small parameter $1 \gg \varepsilon > 0$. Note that this system equals an ODE. To bring this into the form (2.1), we introduce $z = [u; \varepsilon \lambda; \bullet]$ as state and the Hamiltonian $H = \frac{1}{2}\langle u, \mathbf{A}u \rangle + \langle u, \mathbf{B}^T \lambda \rangle$. This leads to $\partial_{z_1} H = \mathbf{A}u + \mathbf{B}^T \lambda$, $\partial_{z_2} H = \frac{1}{\varepsilon} \mathbf{B}u$, and the system equations

$$\begin{bmatrix} \mathbf{A}u + \mathbf{B}^T \lambda \\ \varepsilon \dot{\lambda} \end{bmatrix} = \begin{bmatrix} -\mathbf{M} & 0 \\ 0 & -\mathbf{I} \end{bmatrix} \begin{bmatrix} \dot{u} \\ \varepsilon^{-1} \mathbf{B}u \end{bmatrix} + \begin{bmatrix} f \\ \varepsilon^{-1}g \end{bmatrix}$$

with I denoting the identity matrix. An alternative way to reduce the index is to replace the constraint by its derivative $\mathbf{B}\dot{u} = \dot{g}$. In this case, one may consider the state $z = [u; \bullet; \lambda]$ together with the energy functional $H = \frac{1}{2} \langle u, \mathbf{A}u \rangle$. This then gives

$$\begin{bmatrix} \mathbf{A}u\\0 \end{bmatrix} = \begin{bmatrix} -\mathbf{M} & -\mathbf{B}^T\\\mathbf{B} & 0 \end{bmatrix} \begin{bmatrix} \dot{u}\\\lambda \end{bmatrix} + \begin{bmatrix} f\\-\dot{g} \end{bmatrix}.$$

Considering as Hamiltonian $H = \frac{1}{2} \langle u, \mathbf{M}u \rangle$, one may also include the index-2 system (3.3) without any index reduction. For this, we set $z_1 = \mathbf{0}$, $z_2 = \mathbf{M}u$, and $z_3 = \lambda$, leading to

$$\begin{bmatrix} \mathbf{M}\dot{u} \\ 0 \end{bmatrix} = \begin{bmatrix} -\mathbf{A} & -\mathbf{B}^T \\ \mathbf{B} & 0 \end{bmatrix} \begin{bmatrix} u \\ \lambda \end{bmatrix} + \begin{bmatrix} f \\ -g \end{bmatrix}.$$

3.5. Example V: DC power network. Another example, for which the extension of the state by a third component is necessary, is the linear electrical circuit from [MM19, Sect. 4.1]. For given parameters $R_G, R_L, R_R, L, C_1, C_2 > 0$ and a voltage source E_G , the model equations read

(3.4a)
$$LI = -R_L I + V_2 - V_1,$$

$$(3.4b) C_1 \dot{V}_1 = I - I_G,$$

(3.4c)
$$C_2 \dot{V}_2 = -I - I_R,$$

(3.4d)
$$0 = -R_G I_G + V_1 + E_G,$$

$$(3.4e) 0 = -R_R I_R + V_2$$

with unknowns I, V_1, V_2, I_G, I_R . The corresponding energy has the form

$$H(I, V_1, V_2) = \frac{1}{2}LI^2 + \frac{1}{2}C_1V_1^2 + \frac{1}{2}C_2V_2^2.$$

In [MM19], it is shown that this system can be written as a pH-DAE. More precisely, summarizing the unknowns in a vector x, there exist $\mathbf{J} = -\mathbf{J}^T$ and $\mathbf{R} = \mathbf{R}^T \ge 0$ such that (3.4) is equivalent to

$$\mathbf{E}\dot{x} = (\mathbf{J} - \mathbf{R})x + \mathbf{B}u = (\mathbf{J} - \mathbf{R})x + e_4 E_G$$

with $\mathbf{E} = \text{Diag}(L, C_1, C_2, 0, 0)$ and output $y = \mathbf{B}^T x$. Defining the states $z_1 = \bullet, z_2 = [LI; C_1V_1; C_2V_2]$, and $z_3 = [I_G; I_R]$, we have

$$\begin{bmatrix} \dot{z}_2\\ 0 \end{bmatrix} = \mathbf{E}\dot{x}, \qquad \begin{bmatrix} \partial_{z_2}H\\ z_3 \end{bmatrix} = x.$$

Hence, we directly obtain the structure (2.1) with the same matrices **J** and **R**.

3.6. Example VI: nonlinear circuit model. In [GHRvdS21, eq. (13)], the authors present a general nonlinear circuit model of the form

$$\begin{aligned} A_{\rm C}\dot{q}_{\rm C} + A_{\rm R}G(A_{\rm R}^T\phi) + A_{\rm L}i_{\rm L} + A_{\rm S}i_{\rm S} &= 0, \\ -A_{\rm L}^T\phi + \dot{\psi}_{\rm L} &= 0, \\ -A_{\rm S}^T\phi + u_{\rm S} &= 0, \\ A_{\rm C}^T\phi - \nabla H_{\rm C}(q_{\rm C}) &= 0, \\ i_{\rm L} - \nabla H_{\rm L}(\psi) &= 0 \end{aligned}$$

with matrices $A_{\rm C}$, $A_{\rm R}$, $A_{\rm L}$, $A_{\rm S}$ representing edges connected to capacitances, resistances, inductances, and sources, respectively. Moreover, $q_{\rm C}$ contains the charges at the capacitances, G is a function describing the current-voltage relation at the resistances satisfying $\langle \eta, G(\eta) \rangle \geq 0$ for all vectors η of appropriate dimension, ϕ contains the vertex potentials, $i_{\rm L}$ and $i_{\rm S}$ are the currents at the inductances and sources, respectively, $\psi_{\rm L}$ the magnetic fluxes at the inductances, $u_{\rm S}$ the voltages at the sources, and $H_{\rm C}$ and $H_{\rm L}$ denote the energy stored in the capacitances and inductances, respectively.

In the following, we eliminate the last equation and the variable $i_{\rm L}$. We further consider the special case where G is linear and can be represented by a positive semi-definite matrix. As Hamiltonian, we consider the total energy $H(t) = H_{\rm C}(q_{\rm C}(t)) + H_{\rm L}(\psi(t))$. Then, introducing $z_1 = q_{\rm C}$, $z_2 = \psi_{\rm L}$, and $z_3 = [i_{\rm S}; \phi]$, we may write the system in the structured form

$$\begin{bmatrix} \nabla H_{\rm C} \\ \dot{\psi}_{\rm L} \\ 0 \\ 0 \end{bmatrix} = (\mathbf{J} - \mathbf{R}) \begin{bmatrix} \dot{z}_1 \\ \partial_{z_2} H \\ z_3 \end{bmatrix} + \mathbf{B} u_{\rm S} = \begin{bmatrix} 0 & 0 & 0 & A_{\rm C}^T \\ 0 & 0 & 0 & A_{\rm L}^T \\ 0 & 0 & 0 & A_{\rm S}^T \\ -A_{\rm C} & -A_{\rm L} & -A_{\rm S} & -A_{\rm R} G A_{\rm R}^T \end{bmatrix} \begin{bmatrix} \dot{q}_{\rm C} \\ \nabla H_{\rm L} \\ \dot{i}_{\rm S} \\ \phi \end{bmatrix} - \begin{bmatrix} 0 \\ 0 \\ u_{\rm S} \\ 0 \end{bmatrix} .$$

3.7. Example VII: constrained mechanical systems. Mechanical systems are typically modeled by differential equations of second order, often in combination with constraints. If we consider nonholonomic constraints on velocity level, the system equations read

$$\mathbf{M}\ddot{x} + \mathbf{D}\dot{x} + \mathbf{K}x + \mathbf{B}^T\lambda = f,$$

$$\mathbf{B}\dot{x} = g,$$

which equals a DAE of index 2. Therein, the mass and stiffness matrices **M** and **K** are assumed to be symmetric positive definite, whereas the damping matrix **D** is symmetric positive semi-definite. For the corresponding first-order formulation, we introduce the variable $y := \dot{x}$. With this, the combination of kinetic and potential energy reads

$$H = \frac{1}{2} \left\langle y, \mathbf{M}y \right\rangle + \frac{1}{2} \left\langle x, \mathbf{K}x \right\rangle$$

Introducing $z_1 = \bullet$, $z_2 = [x; \mathbf{M}y]$, and $z_3 = \lambda$ as states, we get $\partial_{z_2} H = [\mathbf{K}x; y]$, leading to

$$\begin{bmatrix} \dot{x} \\ \mathbf{M}\dot{y} \\ 0 \end{bmatrix} = \begin{bmatrix} \dot{z}_2 \\ 0 \end{bmatrix} = (\mathbf{J} - \mathbf{R}) \begin{bmatrix} \partial_{z_2} H \\ z_3 \end{bmatrix} + \begin{bmatrix} 0 \\ f \\ -g \end{bmatrix} = \begin{bmatrix} 0 & \mathbf{I} & 0 \\ -\mathbf{I} & -\mathbf{D} & -\mathbf{B}^T \\ 0 & \mathbf{B} & 0 \end{bmatrix} \begin{bmatrix} \mathbf{K}x \\ y \\ \lambda \end{bmatrix} + \begin{bmatrix} 0 \\ f \\ -g \end{bmatrix}$$

with I denoting again the identity matrix.

If we consider a mechanical system with holonomic constraints, i.e., with constraints on x rather than \dot{x} , we obtain a DAE of index 3. In this case, one may consider an index reduction. The corresponding GGL-formulation [GGL85] includes the derivative of the constraint and an additional Lagrange multiplier. One variant reads

$$\begin{aligned} \mathbf{K}\dot{x} - \mathbf{K}y &+ \mathbf{B}^{T}\mu = 0, \\ \mathbf{M}\dot{y} + \mathbf{D}y + \mathbf{K}x + \mathbf{B}^{T}\lambda = f, \\ \mathbf{B}x &= g, \\ \mathbf{B}u &= \dot{a}. \end{aligned}$$

To bring this into the form (2.1), we set $z_1 = \bullet$, $z_2 = [\mathbf{K}x; \mathbf{M}y]$, and $z_3 = [\lambda; \mu]$. Considering the same energy as before, this implies $\partial_{z_2}H = [x; y]$ such that the system can be written as

$$\begin{bmatrix} \mathbf{K}\dot{x} \\ \mathbf{M}\dot{y} \\ 0 \\ 0 \end{bmatrix} = \begin{bmatrix} \dot{z}_2 \\ 0 \end{bmatrix} = (\mathbf{J} - \mathbf{R}) \begin{bmatrix} \partial_{z_2} H \\ z_3 \end{bmatrix} = \begin{bmatrix} 0 & \mathbf{K} & 0 & -\mathbf{B}^T \\ -\mathbf{K} & -\mathbf{D} & -\mathbf{B}^T & 0 \\ 0 & \mathbf{B} & 0 & 0 \\ \mathbf{B} & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} x \\ y \\ \lambda \\ \mu \end{bmatrix} + \begin{bmatrix} 0 \\ f \\ -\dot{g} \\ -g \end{bmatrix}.$$

An alternative approach, which comes along without an index reduction, is to add a vanishing term to the energy. More precisely, we define

$$H = \frac{1}{2} \langle y, \mathbf{M}y \rangle + \frac{1}{2} \langle x, \mathbf{K}x \rangle + \langle \lambda, \mathbf{B}x - g \rangle,$$

which equals the original energy on the solution manifold. For this, the choice $z_1 = [x; y; \lambda]$, $z_2 = z_3 = \bullet$ leads to

$$\begin{bmatrix} \mathbf{K}x + \mathbf{B}^T \lambda \\ \mathbf{M}y \\ \mathbf{B}x - g \end{bmatrix} = \partial_{z_1} H = (\mathbf{J} - \mathbf{R}) \dot{z}_1 = \begin{bmatrix} -\mathbf{D} & -\mathbf{M} & 0 \\ \mathbf{M} & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} \dot{x} \\ \dot{y} \\ \dot{\lambda} \end{bmatrix} + \begin{bmatrix} f \\ 0 \\ 0 \end{bmatrix}.$$

Remark 3.2. Exchanging the terms on the left and on the right, one easily obtains the classical pH structure. This however, corresponds to a different energy which is not of physical relevance.

3.8. Example VIII: vibrating string. We now turn to PDE examples, starting with the vibrating string in one space dimension [JZ12, Sect. 1.1]. Let ρ denote the mass density and T the Young modulus of the material. Then we seek the (vertical) displacement w satisfying

$$\rho \,\ddot{w}(x,t) = \partial_x \big(T \partial_x w(x,t) \big)$$

for all $x \in (0, 1)$ and $t \in [0, T]$ together with homogeneous Dirichlet boundary conditions. The corresponding energy reads

$$H(t) = \frac{1}{2} \left\langle \dot{w}, \rho \dot{w} \right\rangle + \frac{1}{2} \left\langle \partial_x w, T \partial_x w \right\rangle \coloneqq \frac{1}{2} \int_0^1 \rho \, \dot{w}^2 \, \mathrm{d}x + \frac{1}{2} \int_0^1 T \left(\partial_x w \right)^2 \, \mathrm{d}x$$

Note that, leaving the finite-dimensional setting, the brackets $\langle \cdot, \cdot \rangle$ now denote the inner product in $L^2(0,1)$. As for the pH formulation (see, e.g., [MZ23]), one can set $z_2 = [\rho \dot{w}; \partial_x w]$ and $z_1 = z_3 = \bullet$. This then yields

$$\begin{bmatrix} \rho \ddot{w} \\ \partial_x \dot{w} \end{bmatrix} = \dot{z}_2 = (\mathbf{J} - \mathbf{R}) \, \partial_{z_2} H = \begin{bmatrix} 0 & \partial_x \\ \partial_x & 0 \end{bmatrix} \begin{bmatrix} \dot{w} \\ T \partial_x w \end{bmatrix}$$

Hence, we have $\mathbf{R} = 0$ and \mathbf{J} is skew-symmetric (or, better, skew-adjoint), since $\langle \partial_x u, v \rangle = -\langle u, \partial_x v \rangle$ if at least one of the functions u, v has vanishing boundary data.

3.9. Example IX: viscoelastic Stokes problem. Following [Ren89], a model for the fluid flow in a structure such as molten polymers is given by

$$\rho \dot{v} - \nabla \cdot T + \nabla p = f,$$

$$\varepsilon \dot{T} - \frac{\eta}{2} \left(\nabla v + (\nabla v)^T \right) + T = g,$$

$$\nabla \cdot v = 0.$$

Therein, the unknowns are the velocity field v (assumed here to have homogeneous Dirichlet boundary conditions on the boundary of the computational domain Ω), the symmetric Cauchy stress tensor T, and the pressure p. Moreover, we have the density ρ , the zero-shear-rate viscosity η , and the relaxation time ε as given parameters of the system. As energy function, we consider

$$H(t) = \int_{\Omega} \frac{\eta \rho}{2} |v(x,t)|^2 + \frac{\varepsilon}{2} |T(x,t)|^2 \,\mathrm{d}x.$$

We show that also this example fits in the framework of (2.1) if the appearing matrices are replaced by (differential) operators. Considering $z_1 = \bullet$, $z_2 = [\rho v; \varepsilon T]$, and $z_3 = p$, we get $\partial_{z_2} H = [\eta v; T]$. With this, we can write the (homogeneous) viscoelastic Stokes problem in the form

$$\begin{bmatrix} \rho \dot{v} \\ \varepsilon \dot{T} \\ 0 \end{bmatrix} = \begin{bmatrix} \dot{z}_2 \\ 0 \end{bmatrix} = (\mathbf{J} - \mathbf{R}) \begin{bmatrix} \partial_{z_2} H \\ z_3 \end{bmatrix} = \begin{bmatrix} 0 & \nabla \cdot & -\nabla \\ \nabla^{\mathrm{s}} & -\mathrm{id} & 0 \\ -\nabla \cdot & 0 & 0 \end{bmatrix} \begin{bmatrix} \eta v \\ T \\ p \end{bmatrix}$$

where ∇^{s} equals the symmetric gradient. Hence, the dissipative part is given by $\mathbf{R} = \text{Diag}(0, \text{id}, 0)$. To see that the remaining part is indeed skew-adjoint, we use the homogeneous boundary conditions of v and the symmetry of T, leading to

$$2\langle \nabla^{\mathrm{s}}v,T\rangle = \langle \nabla v,T\rangle + \langle (\nabla v)^{T},T\rangle = -\langle v,\nabla \cdot T\rangle - \langle v,\nabla \cdot (T^{T})\rangle = -2\langle v,\nabla \cdot T\rangle.$$

3.10. Example X: Cahn-Hilliard equation. In this final example, we consider the Cahn-Hilliard equation in the weak form. In a bounded space-time domain $\Omega \times [0,T]$ with $\Omega \subset \mathbb{R}^d$, $d \in \{2,3\}$, and $T < \infty$ the Cahn-Hilliard equations [CH58, ES86] are given by

(3.5a)
$$\dot{u} - \sigma \Delta w = 0$$
 in $\Omega \times [0, T]$,

(3.5b)
$$-\varepsilon \Delta u + \varepsilon^{-1} W'(u) = w \quad \text{in } \Omega \times [0, T].$$

Therein, ε denotes the so-called interaction length and W the energy potential. Modeling a material, which does not interact with the surrounding boundary, we consider homogeneous Neumann boundary conditions for u and w. With the outer normal unit vector n, these conditions read $\partial_n u = 0$ and $\partial_n w = 0$ on $\partial \Omega \times [0, T]$.

For the weak formulation, we introduce $\mathcal{V} \coloneqq H^1(\Omega)$ and the differential operator

$$\mathcal{K} \colon \mathcal{V} \to \mathcal{V}^*, \qquad \langle \mathcal{K}u, v \rangle \coloneqq \int_{\Omega} \nabla u \cdot \nabla v \, \mathrm{d}x.$$

Then, system (3.5) is equivalent to

$$\dot{u} + \sigma \mathcal{K} w = 0,$$

$$\varepsilon \mathcal{K}u + \varepsilon^{-1}W'(u) = w.$$

The corresponding energy reads

$$H_{\text{bulk}}(t) = \int_{\Omega} \frac{\varepsilon}{2} \nabla u \cdot \nabla u + \frac{1}{\varepsilon} W(u) \, \mathrm{d}x = \frac{\varepsilon}{2} \left\langle \mathcal{K}u, u \right\rangle + \int_{\Omega} \frac{1}{\varepsilon} W(u) \, \mathrm{d}x.$$

Considering the state $z = [u; \bullet; w]$, we get the energy-based formulation

$$\begin{bmatrix} \varepsilon \mathcal{K} u + \varepsilon^{-1} W'(u) \\ 0 \end{bmatrix} = \begin{bmatrix} \partial_{z_1} H \\ 0 \end{bmatrix} = (\mathbf{J} - \mathbf{R}) \begin{bmatrix} \dot{z}_1 \\ z_3 \end{bmatrix} = \left(\begin{bmatrix} 0 & \mathrm{id} \\ -\mathrm{id} & 0 \end{bmatrix} - \begin{bmatrix} 0 & 0 \\ 0 & \sigma \mathcal{K} \end{bmatrix} \right) \begin{bmatrix} \dot{u} \\ w \end{bmatrix}.$$

Remark 3.3. One may also consider dynamic boundary conditions which additionally reflect the surface energy; see, e.g., [KEM⁺01]. With $\Gamma := \partial \Omega$, the overall energy is then given as

$$H(t) = H_{\text{bulk}}(t) + H_{\text{surf}}(t) = H_{\text{bulk}}(t) + \int_{\Gamma} \frac{\delta}{2} \nabla_{\Gamma} u \cdot \nabla_{\Gamma} u + \frac{1}{\delta} W_{\Gamma}(u) \, \mathrm{d}x$$

with the interaction length on the boundary δ and the boundary energy potential W_{Γ} . For the particular model introduced in [LW19], system (3.5) is closed by

$$\partial_n w = 0 \qquad \text{on } \Gamma \times [0, T],$$
$$\dot{u} - \Delta_{\Gamma} w_{\Gamma} = 0 \qquad \text{on } \Gamma \times [0, T],$$
$$-\delta \Delta_{\Gamma} u + \delta^{-1} W'_{\Gamma}(u) + \varepsilon \partial_n u = w_{\Gamma} \qquad \text{on } \Gamma \times [0, T].$$

Hence, one still assumes that the chemical potential w does not interact with the solid wall, whereas a new boundary chemical potential w_{Γ} is introduced. A possible weak formulation of the system is presented in [AZ23]. After an additional index reduction, the resulting system can again be written in the form (2.1).

4. Conclusions

A novel energy-based model framework is introduced which covers a large number of examples from different fields of application. Systems which can be modeled in such a way are energy dissipative and can be interconnected in a structure preserving way. Moreover, a discretization by the midpoint rule or a discrete gradient method preserves the dissipativity property for the discrete energy.

Acknowledgments

The authors would like to thank Volker Mehrmann and Riccardo Morandin for helpful discussions on the paper. Moreover, RA acknowledges support by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) - 467107679.

References

[AMU21]	R. Altmann, V. I	Mehrmann, an	d B. Unger.	Port-Hamiltonian	formulations	of poroelastic
	network models. I	Math. Comput.	Model. Dyn.	Sys., 27(1):429-45	2, 2021.	

- [AS17] R. Altmann and P. Schulze. A port-Hamiltonian formulation of the Navier–Stokes equations for reactive flows. *Systems Control Lett.*, 100:51–55, 2017.
- [AZ23] R. Altmann and C. Zimmer. Dissipation-preserving discretization of the Cahn-Hilliard equation with dynamic boundary conditions. *Appl. Numer. Math.*, pages 254–269, 2023.
- [Arn89] V. I. Arnold. Mathematical Methods of Classical Mechanics. Springer New York, USA, second edition, 1989.

- [BS17] P. Benner and T. Stykel. Model order reduction for differential–algebraic equations: A survey. In Surveys in Differential–Algebraic Equations IV, pages 107–160. Springer International Publishing, Cham, Switzerland, 2017.
- [Bio41] M. A. Biot. General theory of three-dimensional consolidation. J. Appl. Phys., 12(2):155–164, 1941.
- [BAPBM19] A. Brugnoli, D. Alazard, V. Pommier-Budinger, and D. Matignon. Port-Hamiltonian formulation and symplectic discretization of plate models part I: Mindlin model for thick plates. *Appl. Math. Model.*, 75:940–960, 2019.
- [BRS22] A. Brugnoli, R. Rashad, and S. Stramigioli. Dual field structure-preserving discretization of port-Hamiltonian systems using finite element exterior calculus. J. Comput. Phys., 471:111601, 2022.
- [CH58] J. W. Cahn and J. E. Hilliard. Free energy of a nonuniform system. I. Interfacial free energy. J. Chem. Phys., 28(2):258–267, 1958.
- [CCM13] Y. Cao, S. Chen, and A.J. Meir. Analysis and numerical approximations of equations of nonlinear poroelasticity. *Discrete Cont. Dyn.-B*, 18(5):1253–1273, 2013.
- [CRMPB17] F. L. Cardoso-Ribeiro, D. Matignon, and V. Pommier-Budinger. A port-Hamiltonian model of liquid sloshing in moving containers and application to a fluid-structure system. J. Fluids Struct., 69:402–427, 2017.
- [CH17] E. Celledoni and E. H. Høiseth. Energy-preserving and passivity-consistent numerical discretization of port-Hamiltonian systems. ArXiv preprint 1706.08621v1, 2017.
- [CBG16] S. Chaturantabut, C. Beattie, and S. Gugercin. Structure-preserving model reduction for nonlinear port-Hamiltonian systems. SIAM J. Sci. Comput., 38(5):B837–B865, 2016.
- [EM04] D. Eberard and B. Maschke. Port Hamiltonian systems extended to irreversible systems: the example of the heat conduction. *IFAC Proceedings Volumes*, 37(13):243–248, 2004.
- [EHS21] H. Egger, O. Habrich, and V. Shashkov. On the energy stable approximation of Hamiltonian and gradient systems. *Comput. Methods Appl. Math.*, 21(2):335–349, 2021.
- [Eid22] S. Eidnes. Order theory for discrete gradient methods. *BIT Numer. Math.*, 62:1207–1255, 2022.
- [ES86] C. M. Elliott and Z. Songmu. On the Cahn-Hilliard equation. Arch. Rational Mech. Anal., 96(4):339–357, 1986.
- [FGLSM24] A. Frommer, M. Günther, B. Liljegren-Sailer, and N. Marheineke. Operator splitting for port-Hamiltonian systems. In K. Burnecki, J. Szwabiński, and M. Teuerle, editors, *Progress* in Industrial Mathematics at ECMI 2023. Springer, 2024. Accepted for publication.
- [GGL85] C.W. Gear, G.K. Gupta, and B. Leimkuhler. Automatic integration of Euler-Lagrange equations with constraints. J. Comput. Appl. Math., 12–13:77–90, 1985.
- [GHRvdS21] H. Gernandt, F. E. Haller, T. Reis, and A. J. van der Schaft. Port-Hamiltonian formulation of nonlinear electrical circuits. J. Geom. Phys., 159:103959, 2021.
- [GKT24] J. Giesselmann, A. Karsai, and T. Tscherpel. Energy-consistent Petrov–Galerkin time discretization of port-Hamiltonian systems. ArXiv preprint 2404.12480, 2024.
- [Gon96] O. Gonzalez. Time integration and discrete Hamiltonian systems. J. Nonlinear Sci., 6:449–467, 1996.
- [GO97] M. Grmela and H. C. Öttinger. Dynamics and thermodynamics of complex fluids. I. Development of a general formalism. *Phys. Rev. E*, 56:6620–6632, 1997.
- [GPBvdS12] S. Gugercin, R. V. Polyuga, C. Beattie, and A. J. van der Schaft. Structure-preserving tangential interpolation for model reduction of port-Hamiltonian systems. *Automatica*, 48(9):1963– 1974, 2012.
- [HW96] E. Hairer and G. Wanner. Solving Ordinary Differential Equations II: Stiff and Differential-Algebraic Problems. Springer-Verlag, Berlin, second edition, 1996.
- [HMM⁺20] S.-A. Hauschild, N. Marheineke, V. Mehrmann, J. Mohring, A. Moses Badlyan, M. Rein, and M. Schmidt. Port-Hamiltonian modeling of district heating networks. In Progress in Differential-Algebraic Equations II, pages 333–355, Paderborn, Germany, 2020.
- [HS74] M. W. Hirsch and S. Smale. Differential Equations, Dynamical Systems, and Linear Algebra. Academic Press, New York, NY, USA, 1974.

- [HCJLG11] H. Hoang, F. Couenne, C. Jallut, and Y. Le Gorrec. The port Hamiltonian approach to modeling and control of continuous stirred tank reactors. J. Process Contr., 21(10):1449– 1458, 2011.
- [JZ12] B. Jacob and H. Zwart. *Linear port-Hamiltonian Systems on Infinite-Dimensional Spaces*. Birkhäuser, Basel, 2012.
- [KEM⁺01] R. Kenzler, F. Eurich, P. Maass, B. Rinn, J. Schropp, E. Bohl, and W. Dietrich. Phase separation in confined geometries: Solving the Cahn–Hilliard equation with generic boundary conditions. *Comp. Phys. Comm.*, 133:139–157, 2001.
- [KTBK23] P. L. Kinon, T. Thoma, P. Betsch, and P. Kotyczka. Discrete nonlinear elastodynamics in a port-Hamiltonian framework. Proc. Appl. Math. Mech., 23(3):e202300144, 2023.
- [Kot19] P. Kotyczka. Numerical Methods for Distributed Parameter Port-Hamiltonian Systems. TUM. University Press, Munich, Germany, 2019.
- [KS21] A. Krishna and J. Schiffer. A port-Hamiltonian approach to modeling and control of an electro-thermal microgrid. *IFAC-PapersOnLine*, 54(19):287–293, 2021.
- [LW19] C. Liu and H. Wu. An energetic variational approach for the Cahn-Hilliard equation with dynamic boundary condition: Model derivation and mathematical analysis. Arch. Rational Mech. Anal., 233:167-247, 2019.
- [LKL21] M. Lohmayer, P. Kotyczka, and S. Leyendecker. Exergetic port-Hamiltonian systems: modelling basics. Math. Comput. Model. Dyn. Syst., 27(1):489–521, 2021.
- [MM04] A. Macchelli and C. Melchiorri. Modeling and control of the Timoshenko beam. The distributed port Hamiltonian approach. SIAM J. Control Optim., 43(2):743–767, 2004.
- [MvdS92] B. Maschke and A. J. van der Schaft. Port-controlled Hamiltonian systems: modelling origins and systemtheoretic properties. *IFAC Proceedings Volumes*, 25(13):359–365, 1992.
- [MQR99] R. I. McLachlan, G. R. W. Quispel, and N. Robidoux. Geometric integration using discrete gradients. *Phil. Trans. R. Soc. Lond.*, 357(1754):1021–1045, 1999.
- [MM19] V. Mehrmann and R. Morandin. Structure-preserving discretization for port-Hamiltonian descriptor systems. In 2019 IEEE 58th Conference on Decision and Control (CDC), pages 6863–6868, 2019.
- [MU23] V. Mehrmann and B. Unger. Control of port-Hamiltonian differential–algebraic systems and applications. *Acta Numer.*, 32:395–515, 2023.
- [MvdS23] V. Mehrmann and A. J. van der Schaft. Differential–algebraic systems with dissipative Hamiltonian structure. Math. Control Signals Syst., 35:541–584, 2023.
- [MZ23] V. Mehrmann and H. Zwart. Abstract dissipative Hamiltonian differential-algebraic equations are everywhere. ArXiv preprint 2311.03091, 2023.
- [Mor24] R. Morandin. Modeling and numerical treatment of port-Hamiltonian descriptor systems. PhD thesis, Technische Universität Berlin, Germany, 2024.
- [PMH20] G. Payen, D. Matignon, and G. Haine. Modelling and structure-preserving discretization of Maxwell's equations as port-Hamiltonian system. *IFAC-PapersOnLine*, 53(2):7581–7586, 2020.
- [PvdS12] R. V. Polyuga and A. J. van der Schaft. Effort- and flow-constraint reduction methods for structure preserving model reduction of port-Hamiltonian systems. Systems Control Lett., 61(3):412–421, 2012.
- [RMS13] H. Ramirez, B. Maschke, and D. Sbarbaro. Irreversible port-Hamiltonian systems: a general formulation of irreversible processes with application to the CSTR. Chem. Eng. Sci., 89:223– 234, 2013.
- [RCSS21] R. Rashad, F. Califano, F. P. Schuller, and S. Stramigioli. Port-Hamiltonian modeling of ideal fluid flow: part I. Foundations and kinetic energy. J. Geom. Phys., 164:104201, 2021.
- [RCvdSS20] R. Rashad, F. Califano, A. J. van der Schaft, and S. Stramigioli. Twenty years of distributed port-Hamiltonian systems: a literature review. IMA J. Math. Control Inf., 37(4):1400–1422, 2020.
- [Ren89] M Renardy. Mathematical analysis of viscoelastic flows. Ann. Rev. Fluid Mech., 21:21–34, 1989.
- [SPF⁺21] M. Schaller, F. Philipp, T. Faulwasser, K. Worthmann, and B. Maschke. Control of port-Hamiltonian systems with minimal energy supply. *Eur. J. Control*, 62:33–40, 2021.

- [Sch24] P. Schulze. Structure-preserving time discretization of port-Hamiltonian systems via discrete gradient pairs. In K. Burnecki, J. Szwabiński, and M. Teuerle, editors, *Progress in Industrial Mathematics at ECMI 2023*. Springer, 2024. Accepted for publication.
- [Sho00] R. E. Showalter. Diffusion in poro-elastic media. J. Math. Anal. Appl., 251(1):310–340, 2000.
- [vdS04] A. J. van der Schaft. Port-Hamiltonian systems: Network modeling and control of nonlinear physical systems. In H. Irschik and K. Schlacher, editors, Advanced Dynamics and Control of Structures and Machines, pages 127–167. Springer Vienna, Austria, 2004.
- [vdSJ14] A. J. van der Schaft and D. Jeltsema. Port-Hamiltonian systems theory: an introductory overview. Found. Trends Syst. Control, 1(2–3):173–378, 2014.
- [vdSM20] A. J. van der Schaft and B. Maschke. Dirac and Lagrange algebraic constraints in nonlinear port-Hamiltonian systems. Vietnam J. Math., 48:929–939, 2020.
- [VS14] T. Voß and J. M. A. Scherpen. Port-Hamiltonian modeling of a nonlinear Timoshenko beam with piezo actuation. SIAM J. Control Optim., 52(1):493–519, 2014.
- [VLM16] N. M. T. Vu, L. Lefèvre, and B. Maschke. A structured control model for the thermomagneto-hydrodynamics of plasmas in tokamaks. *Math. Comput. Model. Dyn. Syst.*, 22(3):181–206, 2016.
- [WMvdS18] L. Wang, B. Maschke, and A. J. van der Schaft. Port-Hamiltonian modeling of non-isothermal chemical reaction networks. J. Math. Chem., 56:1707–1727, 2018.

[†] Institute of Analysis and Numerics, Otto von Guericke University Magdeburg, Universitätsplatz 2, 39106 Magdeburg, Germany

[‡] Institute of Mathematics, Technische Universität Berlin, Str. des 17. Juni 136, 10623 Berlin, Germany

Email address: robert.altmann@ovgu.de, pschulze@math.tu-berlin.de