

Pushing the Frontier on Approximate EFX Allocations

Georgios Amanatidis^{1,4}, Aris Filos-Ratsikas², and Alkmini Sgouritsa^{3,4}

¹School of Mathematics, Statistics and Actuarial Science, University of Essex; Colchester, UK

²School of Informatics, University of Edinburgh; Edinburgh, UK

³Department of Informatics, Athens University of Economics and Business; Athens, Greece

⁴Archimedes / Athena RC; Athens, Greece

Abstract

We study the problem of allocating a set of indivisible goods to a set of agents with additive valuation functions, aiming to achieve approximate envy-freeness up to any good (α -EFX). The state-of-the-art results on the problem include that (exact) EFX allocations exist when (a) there are at most three agents, or (b) the agents' valuation functions can take at most two values, or (c) the agents' valuation functions can be represented via a graph. For α -EFX, it is known that a 0.618-EFX allocation exists for any number of agents with additive valuation functions. In this paper, we show that $2/3$ -EFX allocations exist when (a) there are at most *seven agents*, (b) the agents' valuation functions can take at most *three values*, or (c) the agents' valuation functions can be represented via a *multigraph*. Our results can be interpreted in two ways. First, by relaxing the notion of EFX to $2/3$ -EFX, we obtain existence results for strict generalizations of the settings for which exact EFX allocations are known to exist. Secondly, by imposing restrictions on the setting, we manage to beat the barrier of 0.618 and achieve an approximation guarantee of $2/3$. Therefore, our results push the *frontier* of existence and computation of approximate EFX allocations, and provide insights into the challenges of settling the existence of exact EFX allocations.

1 Introduction

The existence of EFX allocations is arguably the most important open problem in the area of computational fair division with indivisible goods. In this setting, a set of agents have values over a set of indivisible goods, and the goal is to allocate the goods to the agents in a way that is perceived as *fair* by everyone. One of the most well-established notions of fairness is *envy-freeness*, introduced in the late 1950s by [Gamow and Stern \[1958\]](#), see also [\[Varian, 1974, Foley, 1966\]](#) in the context of *divisible* resources; this notion stipulates that no agent would prefer another agent's allocation to her own. For indivisible goods, it is not hard to see that envy-free allocations may not be possible. Indeed, consider the case where there is a single good which is positively valued by multiple agents; some agent will receive the good and the others will be envious.

Motivated by this obvious impossibility, the literature has defined *relaxed* fairness notions, which are appropriate for indivisible goods allocation. [Budish \[2011\]](#) first defined the notion of *envy-freeness up to one good (EF1)*, which deems an allocation fair if the envy of an agent is eliminated after the removal of *some* good from the bundle of another envied agent. This notion was implicitly introduced earlier by [Lipton et al. \[2004\]](#) who showed that EF1 allocations always exist, and for monotone valuation functions it can be achieved in polynomial time via simple algorithms. On the minus side, in certain applications EF1 might be unsatisfactory, as it might require the removal of a very valuable good to restore envy-freeness. To address this shortcoming, [Gourvès et al. \[2014\]](#) and [Caragiannis et al. \[2019b\]](#) introduced the notion of *envy-freeness up to any good (EFX)*, which stipulates that the envy is eliminated even if the least valuable good, from the envious agent's perspective, is removed from the envied agent's bundle.

Contrary to the case of EF1 allocations, the existence of EFX allocations is much more intricate. In fact,

as we mentioned above, this is one of the major open problems in the area of computational fair division, currently carrying great momentum and being met with intensive efforts from the research community. The associated research has adopted a systematic approach to tackling this evidently very challenging question, by first obtaining existence results for special cases of the problem, developing a deeper understanding of its intricacies, and ultimately aiming to synthesize these ideas into an answer to the main problem. Among those results, three of the most notable ones are that EFX allocations exist when

- there are at most three agents [Chaudhury et al., 2023],
- each agent’s value for each good can be one of *two* numbers a or b [Amanatidis et al., 2021],
- the agents’ valuation functions can be represented by a *graph*, with edges corresponding to goods and nodes corresponding to agents [Christodoulou et al., 2023].

Other interesting restrictions that have been studied in the literature include agents with values that induce the same ordering over goods [Plaut and Roughgarden, 2020] and leaving some goods unallocated [Caragiannis et al., 2019a, Chaudhury et al., 2021b, Berger et al., 2022].

A related line of work has studied *approximations* to the EFX notion, referred to as α -EFX. An allocation is α -EFX if after the removal of any good from the envied agent’s bundle, the envy is bounded by a multiplicative factor of α . A $1/2$ -EFX allocation is achievable via slight modifications to techniques that achieve EF1, e.g., see [Chan et al., 2019]. The state of the art for approximate EFX allocations is a $\phi - 1 = 0.618$ approximation due to Amanatidis et al. [2020], which in fact seems to be the limit of the techniques that the literature has developed for the problem; see also Farhadi et al. [2021]. Markakis and Santorinaios [2023] were able to beat the 0.618 barrier and achieve $2/3$ -EFX allocations for a restricted case where all of the n agents agree on which n goods are the most valuable. Whether $2/3$ -EFX allocations can be achieved in general is a very intriguing open problem. If sufficiently many goods are left unallocated, it has been shown that near optimal approximations to EFX can be achieved [Chaudhury et al., 2021a].

The state of the art results in the literature can thus be seen as lying on a certain kind of *frontier*: indeed, a certain set of parameters (e.g., the number of agents, the type of values of the agents, the approximation factor), can be seen as a point on a search space, with those points for which we have obtained existence results constituting the frontier of our current understanding of the problem. The ultimate goal is to move towards the point corresponding to (exact) EFX for any number of agents and without restrictions on the values. Given the challenging nature of this endeavor, however, it seems sensible to try to “push” this frontier towards that goal.

1.1 Our Results and Techniques

In this work, we prove that $2/3$ -EFX allocations exist and can be efficiently computed for agents with additive valuation functions in three important cases, namely when:

- There are at most *seven* agents (Theorem 4.7).
- Each agent’s value for each good can be one of *three* non-negative numbers a , b , or c (Theorem 5.1).
- The agents’ values can be represented by a *multigraph*, with edges corresponding to goods and nodes corresponding to agents (Theorem 4.4). Here an agent has nonzero value for a good only if this good is incident to her. This setting generalizes the setting studied recently by Christodoulou et al. [2023].

We make progress in all three settings through the same algorithmic framework, although each one requires its own modifications. While all of these are nontrivial, the most intricate case is, somewhat surprisingly, the case of three values. We next present an overview of our techniques.

Property-Preserving Partial Allocations. Our approach is based on the following general principle: obtain a *partial* allocation X of goods to agents that satisfies a certain set of properties. Then this allocation can be transformed into a complete allocation that is $2/3$ -EFX.

To be more precise, all of the known algorithms for α -EFX in the literature [Amanatidis et al., 2020, Markakis and Santorinaios, 2023, Farhadi et al., 2021] start by producing a partial allocation X using only a subset of the goods. How this partial allocation is obtained may differ between different algorithms, but they all serve the same purpose: once X is obtained, then one can run the Envy Cycle Elimination algorithm of Lipton et al. [2004], with initial input X , to produce an allocation that is approximately EFX. For this to be possible, X has to satisfy certain properties, mainly that (a) it is α -EFX, for the approximation factor α that we are aiming to prove, and (b) none of the agents consider any of the goods that are left unallocated *too valuable*. Formally, an unallocated good is “too valuable” for an agent i if her value for that good is at least a factor β of her value for her allocated bundle in the partial allocation X . These goods lie at the heart of our approach and we refer to them as *critical goods*. This is captured by the following lemma, stated informally here (its formal statement, restricted to $2/3$ -EFX, is Lemma 4.2 in Section 4.1).

Informal Lemma 1 (Markakis and Santorinaios [2023]). *If a partial allocation X is α -EFX and does not induce any critical goods (defined via a parameter β), then it can be transformed into a complete $\min\{\alpha, \frac{1}{\beta+1}\}$ -EFX allocation.*

Therefore, the value of β that makes a good critical depends on the approximation factor α that we are aiming to prove existence for. For $\alpha = 0.618$ (achieved by Amanatidis et al. [2020]), it is also the case that $\beta = 0.618$. From a technical perspective, the “balance” of these terms makes the construction of a partial allocation X that does not induce any critical goods achievable via relatively simple algorithms. In fact, said algorithms also guarantee that the cardinality of each bundle in X is at most 2. In the context of (approximate) EFX, bundles of cardinality at most 2 are much more manageable. For larger values of α however, $\alpha \neq \beta$ and we will have a natural imbalance. For $\alpha = 2/3$ in particular, we have $\beta = 1/2$. In this case, it can be shown that even for the cases that we consider, it is not possible for X to be both $2/3$ -EFX and induce no critical goods, unless agents receive bundles of cardinality 3 or more. We demonstrate that concretely via the following example with only three agents and three possible values.

Example 1. Consider an instance with three agents 1, 2, 3 and six goods g_1, g_2, g_3, g_4, g_5 and g_6 . The values of the agents for the goods are given by the following table. Assume that we have a partial allocation X

	g_1	g_2	g_3	g_4	g_5	g_6
agent 1	1	1	$3/5$	$1/100$	$1/100$	$1/100$
agent 2	1	1	$1/100$	$3/5$	$1/100$	$1/100$
agent 3	1	1	$1/100$	$1/100$	$3/5$	$1/100$

where the bundle X_i of each agent $i \in \{1, 2, 3\}$ contains at most two goods. If either g_1 or g_2 are unallocated, they are critical for each of the agents. If they are allocated, assume without loss of generality that g_1 is allocated to agent 1. For X to be $2/3$ -EFX, g_2 cannot be allocated to agent 1 as well, so it must be allocated to some other agent, say agent 2. This means that neither of agents 1 and 2 can have another good in her bundle, as otherwise agent 3 (who does not have g_1 or g_2 in her bundle) would envy that agent by more than $2/3$. Since agent 3’s bundle contains at most two goods, one of g_3, g_4 and g_5 must be unallocated. These would be critical for agents 1, 2 and 3 respectively, so in the end there must be some critical good in X . ■

Our goal will be to obtain a $2/3$ -EFX partial allocation X without critical goods *in two stages*. First, we devise a general algorithm called PROPERTY-PRESERVING PARTIAL ALLOCATION algorithm (3PA), which obtains a partial allocation X^1 that satisfies a certain set of properties (see Algorithm 1). One such property is that it

is $2/3$ -EFX, as required by [Informal Lemma 1](#) above. This partial allocation X^1 will still have critical goods, but it will limit the number of such goods to at most *one per agent*, and only for agents that have singleton bundles in X^1 . This, together with the other properties of X^1 will prepare the ground for allocating the critical goods to the agents in a subsequent stage, resulting in a new partial allocation X^2 . This X^2 will now satisfy the properties of [Informal Lemma 1](#), and it will eventually be transformed into a complete $2/3$ -EFX allocation.

Swap steps and different types of envy graphs. The aforementioned 3PA algorithm is based on a series of steps which are executed in sequence according to a certain priority structure. Most of these are *swap steps*, i.e., steps that enable certain agents to exchange (parts of) their bundles in the partial allocation X with certain unallocated goods. The priority is determined by the cardinality of the bundles in X , as well as the value of the agents for those unallocated goods. Besides the swap steps, the algorithm also includes steps that are performed on several different types of envy graphs, associated with allocation X . A (standard) envy graph for a partial allocation X is a graph in which the nodes corresponds to agents, and an edge (i, j) signifies that agent i envies agent j . Envy graphs are very common in the design of algorithms for fair division of indivisible goods, starting with the Envy Cycle Elimination algorithm of [Lipton et al. \[2004\]](#). We also consider two different types of graphs, namely *reduced* graphs and *enhanced* graphs. In the former, any envy towards agents with singleton bundles is disregarded, unless it is high enough. In the latter, we add edges of *near* envy, as long as the value of the target bundle is above a certain threshold. By exchanging bundles along cycles and paths in these graphs, we obtain the flexibility to deal with the inherently most challenging case of “moving value” from and to agents with singleton bundles. In the case of three values we further refine our graphs, including edges that indicate ties in the values. This allows for more options on how the partial allocations evolve, but adds an extra layer of complexity in the analysis.

Throughout the execution of the 3PA algorithm, the value of an agent for her bundle may decrease several times, but this is done in a controlled way that allows us to allocate the critical goods in subsequent steps. We remark that since the steps of the 3PA algorithm and its variants repeatedly allocate and de-allocate goods, their polynomial running time, or even their termination is far from obvious; to this end we provide proofs based on carefully crafted potentials and appropriate combinatorial arguments.

1.2 Further Discussion on Related Work

The literature on the fair division of indivisible goods is extensive. Here we discuss the works most relevant to us, and defer the reader to the recent survey of [Amanatidis et al. \[2023\]](#) for more details.

The existence of EFX allocations for three agents with additive valuations by [Chaudhury et al. \[2023\]](#) was a breakthrough which followed the existence result for two agents due to [Plaut and Roughgarden \[2020\]](#). This result was recently simplified (and generalized to somewhat larger valuation classes) by [Akrami et al. \[2023\]](#). Our first aforementioned result above shows that if we relax the requirement from EFX to $2/3$ -EFX, we can guarantee its existence for up to 7 agents. Our algorithm for this case also runs in polynomial time, contrary to the aforementioned algorithms for exact EFX and three agents. [Amanatidis et al. \[2021\]](#) were the first to study the existence of EFX on instances with two values (2-value instances). First, they showed that the Maximum Nash Welfare (the geometric mean of the agents’ values for their allocated bundles) guarantees EFX in this setting, and then developed a polynomial-time algorithm to achieve EFX allocations. [Babaioff et al. \[2021\]](#) consider a setting where the valuations need not be additive, but have binary marginals and prove the existence of EFX allocations in that case. The approaches for two values clearly fall short if one considers instances with three values. Our approach is fundamentally different from that of [Amanatidis et al. \[2021\]](#) and shows that existence is possible, at the expense of a loss in the approximation factor. Finally, the question of the existence of EFX allocations on graphs was studied very

recently by Christodoulou et al. [2023]; the authors point out that their techniques are insufficient when applied to instances on multigraphs. Using our framework, we show how to obtain 2/3-EFX allocations on multigraphs in polynomial time, and in a relatively simple manner.

2 Preliminaries

Let N be the set of agents and let M be the set of indivisible goods. Let $n = |N|$ and $m = |M|$. Our goal is to assign the goods to the agents in a fair way. This assignment is captured by the notion of an *allocation*, which can be *partial* or complete.

Definition 2.1 ((Partial) Allocation). A *partial allocation* $\mathbf{X} = (X_1, \dots, X_n)$ is an ordered tuple of disjoint subsets of M , i.e., (i) for every agent i , $X_i \subseteq M$, and (ii) for any two distinct agents i and j , it holds that $X_i \cap X_j = \emptyset$.

A partial allocation \mathbf{X} corresponds to an assignment of (some of the) goods to the agents; we call X_i the *bundle* of agent i . An *allocation* is a partial allocation for which $\bigcup_{i \in N} X_i = M$. We also say that a partial allocation is of size at most k if $\max_{i \in N} |X_i| \leq k$.

It will also be useful to refer to the set of unallocated goods as “the pool”.

Definition 2.2 (The Pool). Given a partial allocation \mathbf{X} , we refer to $M \setminus \bigcup_{i \in N} X_i$ as *the pool*, and we denote it by $\mathcal{P}(\mathbf{X})$.

2.1 Valuation Functions and Fairness Notions

Next we define the value of an agent for a bundle of goods.

Definition 2.3 (Agent Valuation Functions). Given a function $v_i : M \rightarrow \mathbb{R}_{\geq 0}$, where $v_i(g)$ represents the value of agent i for good g , we can define the *value* of an agent $i \in N$ for a bundle of goods $X \subseteq M$ by extending v_i to an *additive* function, i.e., $v_i(X) = \sum_{g \in X} v_i(g)$.

In this work, we only study additive instances of the problem, i.e., instances where all agents have additive valuation functions. We will also be interested in two special cases of additive instances, namely *multigraph value* and *3-value* instances. As we discussed in the Introduction, these strictly generalize the classes of instances for which the state-of-the-art results on the existence of EFX have been established.

Definition 2.4 (Multigraph Value Instances). We say that an instance of the problem is a *multigraph value instance*, if for any agent $i \in N$, the function v_i is additive, and there is a labeled multigraph $H = (V, E)$ with its vertices labeled via a bijection to N and its edges labeled via a bijection to M , such that for any $i \in N$ and for any good $g \in M$, it holds that $v_i(g) \neq 0$ only if g is the label of an edge incident to the vertex labeled as i .

Intuitively, we can see a multigraph value instance as a multigraph, where the vertices are agents, the edges are the goods, and any agent has value 0 for any edge not incident to her.

Definition 2.5 (3-Value Instances). We say that an instance of the problem is a *3-value instance*, if for any agent $i \in N$ and for any good $g \in M$, the function v_i is additive and it holds that $v_i(g) \in \{a, b, c\}$, for some $a \geq b \geq c \in \mathbb{R}_{\geq 0}$.

Clearly, in instances where $a = b = c = 0$ any allocation is EFX, so we only consider instances where $a > 0$. In fact, without loss of generality, we assume that $a = 1$, as the values of the other two goods can be scaled appropriately.

We are now ready to define our main fairness notion, that of *approximate EFX*.

Definition 2.6 (Envy, Envy-Freeness, α -EFX). Given a partial allocation \mathbf{X} , a constant $\alpha > 0$, and two agents $i, j \in N$, we will say that

- agent i *does not α -envy* or, equivalently, *is α -envy-free towards agent j* , if $v_i(X_i) \geq \alpha \cdot v_i(X_j)$;
- agent i *does not α -envy agent j up to any good* or, equivalently, *is α -EFX towards agent j* , if for any good $g \in X_j$, it holds that $v_i(X_i) \geq \alpha \cdot v_i(X_j \setminus \{g\})$.

A partial allocation \mathbf{X} is α -envy-free (respectively α -EFX) if, given \mathbf{X} , every agent $i \in N$ is α -envy-free (respectively α -EFX) towards any other agent $j \in N$. When $\alpha = 1$, we drop the prefixes; e.g., we write EFX instead of 1-EFX.

Often, we need to compare the value $v_i(X_i)$ an agent has for her bundle with the value $v_i(S)$ she has for a set S which is not the bundle of any other agent. Then, if $v_i(S) \geq \alpha \cdot v_i(X_i)$, instead of using envy terminology, we say that agent i *prefers S by a factor of at least α* ; moreover, when S is a singleton, we drop the braces.

The goal is to find a (complete) allocation which is α -EFX. Note that for $m \leq n$, it is trivial to produce an exact EFX allocation by giving at most one good to each agent arbitrarily. So, in what follows we assume that $m > n$. This will allow us to consider partial α -EFX allocations where no bundle is empty throughout the course of our algorithms, thus avoiding trivial cases in several of our proofs. We next define the notion of *critical goods*, which is in the epicenter of our approach.

Definition 2.7 (Critical Good). Given a partial allocation \mathbf{X} , a good $g \in \mathcal{P}(\mathbf{X})$ is *critical* for agent $i \in N$ if i prefers g by a factor of at least $1/2$, i.e., $v_i(g) > \frac{1}{2}v_i(X_i)$.

As we have mentioned above (recall the related discussion in the Introduction), one could give a parameterized definition of criticality [see, e.g., [Markakis and Santorinaios, 2023](#)], but as we only care about a specific value here which is appropriate for our goal of achieving $2/3$ -EFX allocations, we avoided this.

2.2 Envy Graphs

The notion of an envy graph is ubiquitous in the design of algorithms for variants and relaxations of envy-freeness. Besides the “vanilla” version, we define and use two additional envy-based graphs.

Definition 2.8 (Envy Graph G). Given a partial allocation \mathbf{X} , the *envy graph on \mathbf{X}* , $G(\mathbf{X}) = (N, E(\mathbf{X}))$, is a directed graph whose vertex set is the set of agents. Its edge set contains a directed edge (i, j) if and only if agent i envies agent j , i.e., $E(\mathbf{X}) = \{(i, j) : v_i(X_i) < v_i(X_j)\}$.

Definition 2.9 (Reduced Envy Graph G_r). Given a partial allocation \mathbf{X} , the *reduced envy graph on \mathbf{X}* , $G_r(\mathbf{X}) = (N, E_r(\mathbf{X}))$, is a subgraph of the envy graph $G(\mathbf{X})$, where we remove all edges (i, j) , such that $|X_i| > 1$, $|X_j| = 1$, and i is $\frac{2}{3}$ -envy-free towards j . That is $E_r(\mathbf{X}) = E(\mathbf{X}) \setminus \{(i, j) : |X_i| > 1, |X_j| = 1, \text{ and } v_i(X_i) \geq \frac{2}{3}v_i(X_j)\}$.

Definition 2.10 (Enhanced Envy Graph G_e). Given a partial allocation \mathbf{X} , the *enhanced envy graph on \mathbf{X}* , $G_e(\mathbf{X}) = (N, E_e(\mathbf{X}))$, is a supergraph of the reduced envy graph $G_r(\mathbf{X})$, where we add all edges (i, s) , such that s is a source (i.e., vertex of in-degree 0) in $G_r(\mathbf{X})$, $|X_i| = 1$, $|X_s| > 1$, and $v_i(X_s) \geq \frac{2}{3}v_i(X_i)$. We color these additional edges *red*.

Occasionally, when it is clear what the partial allocation \mathbf{X} is from context, we just write G , G_r , and G_e instead of $G(\mathbf{X})$, $G_r(\mathbf{X})$, and $G_e(\mathbf{X})$, respectively.

2.3 Basic Subroutines

Before we proceed with the presentation of our algorithms, we first define some useful subroutines that we will be using throughout their design. The first one is a procedure which eliminates a given cycle in a (standard, reduced, or enhanced) envy graph by swapping the bundles of the agents backwards along the cycle. We refer to this process as a *cycle resolution* on the graph, see Subroutine 1. Similarly, we can define a subroutine that eliminates all cycles in a (standard, reduced, or enhanced) envy graph, see Subroutine 2.

Here we should discuss two small conventions, made for the sake of readability. First, the full information about the instance is available to all of our subroutines and algorithms. Nevertheless, we only include the “necessary” arguments as input, e.g., we write `ALLCYCLESRESOLUTION(\mathbf{X}, \tilde{G})` rather than `ALLCYCLESRESOLUTION($N, (v_i)_{i \in N}, \mathbf{X}, \tilde{G}(\mathbf{X}), M$)`. Secondly, whenever one of the envy graph variants is used in any subroutine or algorithm, it is assumed that it is up to date. That is, every time the allocations change, the relevant envy graphs are “quietly” updated, although we have opted not to add these extra steps to our already lengthy pseudocode descriptions. In general, tie-breaking is not important for the properties of our subroutines and algorithms, so we assume that any tie-breaking is always done lexicographically.

SUBROUTINE 1: `CYCLERESOLUTION(\mathbf{X}, \tilde{G}, C)`

Input: A partial allocation \mathbf{X} , its graph $\tilde{G}(\mathbf{X})$, and a cycle C in $\tilde{G}(\mathbf{X})$

Output: An updated partial allocation \mathbf{X} such that the (implied) graph $\tilde{G}(\mathbf{X})$ no longer contains the cycle C .

```

 $\tilde{X} \leftarrow \mathbf{X}$  //  $\tilde{X}$  is an auxiliary allocation
for every edge  $(i, j) \in C$  do
   $X_i \leftarrow \tilde{X}_j$  // swap the bundles backwards along the cycle
return  $\mathbf{X}$ 

```

In our case, the graph \tilde{G} in Subroutines 1 and 2 can be any of the envy graph G , the reduced envy graph G_r , or the enhanced envy graph G_e . It is well-known that the `ALLCYCLESRESOLUTION` subroutine terminates in polynomial time: we add a short proof here for completeness.

SUBROUTINE 2: `ALLCYCLESRESOLUTION(\mathbf{X}, \tilde{G})`

Input: A partial allocation \mathbf{X} and its graph $\tilde{G}(\mathbf{X})$.

Output: An updated partial allocation \mathbf{X} such that its graph $\tilde{G}(\mathbf{X})$ is acyclic.

```

while there exists a cycle  $C$  in  $\tilde{G}(\mathbf{X})$  do
   $\mathbf{X} = \text{CYCLERESOLUTION}(\tilde{G}(\mathbf{X}), C)$ 
return  $\mathbf{X}$ 

```

Lemma 2.11. *The `ALLCYCLESRESOLUTION` subroutine terminates in polynomial time.*

Proof. Note that every time a cycle is resolved within the body of the while loop of the subroutine, the number of edges in the graph $\tilde{G}(\mathbf{X})$ strictly decreases, compared to its previous number, before \mathbf{X} was updated. This means that the while loop will terminate in at most m iterations. Each iteration, however, only needs $O(n)$ steps, if $\tilde{G}(\mathbf{X})$ is given, or $O(n^2 + m)$ steps, if $\tilde{G}(\mathbf{X})$ has to be constructed from scratch. \square

The third subroutine deals with swapping bundles along paths of the (-, reduced, enhanced) envy graph. In particular, for any edge (i, j) in the path, agent i will receive the bundle of agent j . We do not specify what the bundle of the last agent on the path (for whom, since we will be considering paths of maximum cardinality, there will be no outgoing edge) will be. Similarly, we do not specify what will happen to the bundle that the first agent in the path (the source) had before the swap. Both of these will be handled by our algorithms later. We refer to this process as a *path resolution* on the graph; see Subroutine 3. The

PATHRESOLUTION subroutine obviously runs in $O(|\Pi|) = O(n)$ time. Again, in our case, the graph \tilde{G} in Subroutine 3 can be any of the envy graph G , the reduced envy graph G_r , or the enhanced envy graph G_e .

SUBROUTINE 3: PATHRESOLUTION(X, \tilde{G}, Π)

Input: A partial allocation X , its graph $\tilde{G}(X)$, and a path $\Pi = (i_1, i_2, \dots, i_\ell)$ in $\tilde{G}(X)$

Output: An updated set of bundles X_i , one for every agent $i \in \{i_1, i_2, \dots, i_{\ell-1}\}$.

```

for  $k \leftarrow 1$  to  $\ell - 1$  do                                // go through every  $i$  such that  $(i, j) \in \Pi$  following the path
   $X_{i_k} \leftarrow X_{i_{k+1}}$                                 // assign to  $i_k$  the bundle of the agent  $i_{k+1}$  that she envies
return  $(X_i)_{i \in N: \exists (i, j) \in \Pi}$ 

```

Note that PATHRESOLUTION does not return a partial allocation, but only the updated bundles of the agents along the path, except for the bundle of the last agent. This is to allow some flexibility in building the latter when PATHRESOLUTION is used as a subroutine. Using the PATHRESOLUTION subroutine, we can also define the following useful subroutine. The subroutine will assume that the sources of the graph G have two goods in their bundles; our algorithms will ensure this is the case. Then, it will perform PATHRESOLUTION on the path with respect to a target agent $i \in N$, and allocate i one of the goods of the respective source and a designated good from the pool, which is given as input.

SUBROUTINE 4: PATHRESOLUTION*(X, \tilde{G}, Π)

Input: A partial allocation X , its graph $\tilde{G}(X)$, and a path $\Pi = (s, \dots, i)$ in $\tilde{G}(X)$ starting at a source s of $\tilde{G}(X)$ with $|X_s| = 2$

Output: An updated partial allocation X .

```

Let  $g_s \in \arg \max_{g \in X_s} v_i(g)$                                 // recall that  $s$  is the first and  $i$  is the last vertex of  $\Pi$ 
Let  $g_* \in \arg \max_{g \in \mathcal{P}(X)} v_i(g)$ 

```

```

 $(X_i)_{i \in N: \exists (i, \ell) \in \Pi} = \text{PATHRESOLUTION}(X, \tilde{G}, \Pi)$ 

```

```

 $X_i \leftarrow \{g_*, g_s\}$ 

```

```

 $\mathcal{P}(X) \leftarrow (\mathcal{P}(X) \cup X_s) \setminus \{g_*, g_s\}$ 

```

```

// agent  $i$  gets her favorite goods from  $X_s$  and  $\mathcal{P}(X)$ 

```

```

return  $X$ 

```

3 The Property-Preserving Partial Allocation (3PA) Algorithm

As we mentioned in the Introduction, our approach to achieving 2/3-EFX allocations will be the following. We will first construct a partial allocation X^1 that satisfies certain properties related to the values and level of envy of agents for bundles of other agents and unallocated goods, as well as the number of critical goods. Then, we will allocate these critical goods ensuring that the resulting partial allocation X^2 is still 2/3-EFX. Then, it is known that we can run the Envy Cycle Elimination algorithm of Lipton et al. [2004] to complete X^2 , resulting in a 2/3-EFX allocation, see also Lemma 4.2 in Section 4.1. Given this, it suffices to focus on obtaining the allocation X^2 .

In this section, we first define the aforementioned properties, and then we develop the algorithm that produces the partial allocation X^1 that satisfies these properties, see Algorithm 1. We refer to X^1 as a *Property-Preserving Partial Allocation (3PA)*, and to the corresponding algorithm as the *3PA algorithm*. This will in fact be the “basic” variant of the algorithm, which is sufficient to achieve 2/3-EFX for multigraph value instances and—with a small additional step—for a small number of agents, which we present in Section 4. For the case of 3-value instances, we will need a refined version of this list, which we present in Section 5.

Desired properties of a partial allocation \mathbf{X} :

- (a) Every agent $i \in N$ with $|X_i| = 1$ is EFX towards any other agent.
- (b) Every agent $i \in N$ is 2/3-EFX towards any other agent.
- (c) Every agent i prefers her bundle to any single unallocated good, i.e., for every agent $i \in N$ and good $g \in \mathcal{P}(\mathbf{X})$, $v_i(X_i) \geq v_i(g)$.
- (d) Every agent $i \in N$ with $|X_i| > 1$ does not have any critical goods, i.e., for every agent $i \in N$ and any good $g \in \mathcal{P}(\mathbf{X})$, $v_i(g) \leq \frac{1}{2}v_i(X_i)$.
- (e) Any agent i with $|X_i| = 1$ has at most one critical good g_i , and she values that good at most $\frac{2}{3}$ of the value of her current bundle, i.e., for every agent i , there is at most one good $g_i \in \mathcal{P}(\mathbf{X})$ such that $v_i(g_i) > \frac{1}{2}v_i(X_i)$ and it holds that $v_i(g_i) \leq \frac{2}{3}v_i(X_i)$.

It is easy to see that [Properties \(d\) and \(e\)](#) imply [Property \(c\)](#). Nevertheless, we keep this redundancy for the sake of presentation, as we view [Properties \(d\) and \(e\)](#) as special cases of the simpler [Property \(c\)](#).

We are almost ready to state the 3PA algorithm. To allow flexibility in the use of the algorithm as a potential subroutine, 3PA takes as input a partial allocation \mathbf{X} of size at most 2, which does not contain any empty bundles and satisfies [Properties \(a\) and \(b\)](#). We call any such allocation a *seed allocation*. For our results in the following section, it suffices to start with a seed allocation in which each agent arbitrarily receives a single good (recall that this is possible as we have assumed that $m > n$). Then the algorithm executes a series of steps, each of which is executed only if the previous one is not. At a high level, for several of the steps of the algorithm, certain agents are enabled to swap (parts) of their bundles with goods from the pool. These agents are considered according to a certain priority, which depends on the cardinality of their bundles in the partial allocation \mathbf{X} . Several steps of the algorithm also consider the reduced envy-graph G_r and the enhanced envy-graph G_e and eliminate the cycles in those graphs via invoking the ALLCYCLESRESOLUTION subroutine. Finally, the algorithm also takes care of the corner case where the pool no longer contains enough goods valuable enough for trades, which is addressed via the SINGLETONPOOL subroutine (Subroutine 5).

SUBROUTINE 5: SINGLETONPOOL(\mathbf{X})

Input: A partial allocation \mathbf{X} (of size at most 2 with a *single* unallocated good g , which some agent i —who has $|X_i| = 1$ and is not a source in $G_r(\mathbf{X})$ —values more than $2/3 \cdot v_i(X_i)$).

Output: A partial allocation \mathbf{X}' , such that $g \notin \mathcal{P}(\mathbf{X}')$ and some other good g' is returned to $\mathcal{P}(\mathbf{X}')$.

Let g be the only good in $\mathcal{P}(\mathbf{X})$ and let $i \in N$ be such that $|X_i| = 1$ and $v_i(g) > \frac{2}{3}v_i(X_i)$

// when SINGLETONPOOL is called, such g and i do exist and i is not a source in $G_r(\mathbf{X})$

Let Π be a path in $G_r(\mathbf{X})$ starting from some source s of $G_r(\mathbf{X})$ and terminating at i

// when SINGLETONPOOL is called, no sources in $G_r(\mathbf{X})$ own only one good

$\mathbf{X} \leftarrow \text{PATHRESOLUTION}^*(\mathbf{X}, G_r, \Pi)$

return \mathbf{X}

The following lemma establishes that the partial allocation produced by 3PA satisfies [Properties \(a\) to \(e\)](#), and that its enhanced envy graph has a source without critical goods.

Lemma 3.1. *Let \mathbf{X} be a seed allocation. Then the output of $3\text{PA}((v_i)_{i \in N}, \mathbf{X})$ is a partial allocation \mathbf{X}^1 of size at most 2 that satisfies [Properties \(a\) to \(e\)](#). Furthermore, if \mathbf{X}^1 is not a complete allocation, then $G_e(\mathbf{X}^1)$ has at least one source, and every source s in $G_e(\mathbf{X}^1)$ has $|X_s^1| = 2$.*

Note that the fact that $|X_s^1| = 2$ combined with [Property \(d\)](#) directly imply that this source s of $G_e(\mathbf{X}^1)$ has

ALGORITHM 1: PROPERTY-PRESERVING PARTIAL ALLOCATION (3PA) $((v_i)_{i \in N}, \mathbf{X})$

Input: The values $v_i(g)$ for every agent $i \in N$ and every good $g \in M$, and a partial allocation \mathbf{X} of size at most 2 which satisfies [Properties \(a\)](#) and [\(b\)](#).

Output: A Property-Preserving Partial Allocation \mathbf{X}^1 of size at most 2, i.e., a partial allocation \mathbf{X}^1 of size at most 2 which satisfies [Properties \(a\)](#) to [\(e\)](#).

while $\mathcal{P}(\mathbf{X}) \neq \emptyset$ **do**

```
1   (Step 1) if there is  $i \in N$  with  $|X_i| = 1$  and a good  $g \in \mathcal{P}(\mathbf{X})$  such that  $v_i(g) > v_i(X_i)$  then
    |    $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \cup \{X_i\}) \setminus \{g\}$  and  $X_i \leftarrow \{g\}$ 
    |   // If an agent with 1 good prefers 1 good from the pool, swap them.
2   (Step 2) else if there is  $i \in N$  with  $|X_i| = 2$  and a good  $g \in \mathcal{P}(\mathbf{X})$  such that  $v_i(g) > \frac{3}{2}v_i(X_i)$  then
    |    $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \cup \{X_i\}) \setminus \{g\}$  and  $X_i \leftarrow \{g\}$ 
    |   // Else if an agent with 2 goods prefers 1 good from the pool by more than 3/2, swap her
    |   // bundle with that good.
3   (Step 3) else if there is  $i \in N$  with  $|X_i| = 1$  and goods  $g_1, g_2 \in \mathcal{P}(\mathbf{X})$  such that  $v_i(\{g_1, g_2\}) > \frac{2}{3}v_i(X_i)$  then
    |    $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \cup \{X_i\}) \setminus \{g_1, g_2\}$  and  $X_i \leftarrow \{g_1, g_2\}$ 
    |   // Else if an agent with 1 good prefers 2 goods from the pool by more than 2/3, swap that 1
    |   // good with the two goods from the pool.
4   (Step 4) else if there is  $i \in N$  with  $|X_i| = 2$ , and goods  $g \in \mathcal{P}(\mathbf{X})$  and  $g' \in X_i$  such that  $v_i(g) > v_i(g')$  then
    |    $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \cup \{g'\}) \setminus \{g\}$  and  $X_i \leftarrow (X_i \cup \{g\}) \setminus \{g'\}$ .
    |   // Else if an agent with 2 good prefers 1 good from the pool to one of her own goods, swap
    |   // that good with the one good from the pool.
5   (Step 5) else if the reduced envy graph  $G_r(\mathbf{X})$  has cycles then
    |    $\mathbf{X} \leftarrow \text{ALLCYCLESRESOLUTION}(\mathbf{X}, G_r)$ 
    |   // Else if the reduced envy graph has cycles, resolve them by swapping the bundles.
6   (Step 6) else if in the reduced envy graph  $G_r$  there is a source  $s$  with  $|X_s| = 1$  then
    |    $\mathcal{P}(\mathbf{X}) \leftarrow \mathcal{P}(\mathbf{X}) \setminus \{g^*\}$ ,  $X'_s \leftarrow X_s \cup \{g^*\}$ , where  $g^* \in \arg \max_{g \in \mathcal{P}(\mathbf{X})} v_i(g)$ .
    |   // Else if there is a source in the reduced envy graph with a single good, add her most
    |   // valuable good from the pool to her bundle.
7   (Step 7) else if  $|\{g \in \mathcal{P}(\mathbf{X}) : \exists i \text{ such that } |X_i| = 1 \text{ and } v_i(g) > \frac{2}{3}v_i(X_i)\}| = 1$  then
    |    $\mathbf{X} \leftarrow \text{SINGLETONPOOL}(\mathbf{X})$ 
    |   // Else if there is a single unallocated good and some agent with 1 good prefers it strictly
    |   // more than 2/3, run the SINGLETONPOOL subroutine to allocate it.
8   (Step 8) else if the enhanced envy graph  $G_e(\mathbf{X})$  has cycles then
    |    $\mathbf{X} \leftarrow \text{ALLCYCLESRESOLUTION}(\mathbf{X}, G_e)$ 
    |   // Else if the enhanced envy graph has cycles, resolve them by swapping the bundles.
9   (Step 9) else
    |   break
```

return \mathbf{X}

no critical goods in \mathbf{X}^1 . To prove the [Lemma 3.1](#), we will devise and prove a series of other lemmata. We start with the following lemma, which establishes that \mathbf{X}^1 satisfies [Properties \(a\)](#) and [\(b\)](#). This is the most challenging part of proving [Lemma 3.1](#).

Lemma 3.2. *Let \mathbf{X} be a seed allocation. Then the output of $3PA((v_i)_{i \in N}, \mathbf{X})$ is a partial allocation \mathbf{X}^1 of size at most 2 that satisfies [Properties \(a\)](#) and [\(b\)](#).*

Proof. We first argue that \mathbf{X}^1 is of size at most 2. Since \mathbf{X} is a seed allocation, initially all the bundles have cardinality 1 or 2. Then it is just a matter of inspection to see that no step in 3PA can increase the cardinality of a bundle from 1 or 2 to more than 2.

Next we will prove by induction that **Properties (a)** and **(b)** are satisfied at the end of the execution of the algorithm. In particular, we will prove that the properties are always satisfied right before the condition of the main while loop of the algorithm is checked. For the base case, it follows by assumption on the input partial allocation \mathbf{X} that **Properties (a)** and **(b)** are satisfied, before the first iteration of the loop. We will assume that the properties are satisfied before iteration k of the loop and we will prove that (if the loop condition is met) they are satisfied at the end of iteration k as well, or, equivalently, before iteration $k + 1$. Notice that in each iteration of the while loop, only one of the steps of the algorithm will be executed. In particular, Step $i \in \{1, \dots, 9\}$ will only be executed if all Steps $j \in \{1, \dots, i - 1\}$ are *not* executed. We will consider each possible step and argue that **Properties (a)** and **(b)** are satisfied after the execution of that step. For ease of reference, we will use \mathbf{X} and \mathbf{X}' to denote the partial allocation before and after the execution of the step respectively.

To avoid unnecessary repetition, in each case we will completely disregard pairs of agents whose bundles did not change during the iteration at hand; this extends to pairs (i, j) , such that i 's bundle did not change and j received a preexisting bundle via some exchange. It is implicit that for such pairs, **Properties (a)** and **(b)** are always satisfied after the execution of the loop, given that they were satisfied before it. Also, we will omit explicit references to trivial cases like **Property (a)** being true for agents with two goods or **Property (b)** being true for agents with one good for whom **Property (a)** holds.

If Step 1 is executed: Obviously $v_i(X'_i) > v_i(X_i)$, hence **Properties (a)** and **(b)** are satisfied for agent i by the induction hypothesis. Since $|X'_i| = 1$, any other agent $j \in N \setminus \{i\}$ is obviously EFX towards agent i , and hence **Properties (a)** and **(b)** are satisfied for all agents.

If Step 2 is executed: By the induction hypothesis, agent i was $2/3$ -EFX towards any other agent $j \in N \setminus \{i\}$ in \mathbf{X} . Since $v_i(X'_i) \geq \frac{3}{2}v_i(X_i)$, this implies that in \mathbf{X}' agent i is EFX towards any other agent, and **Properties (a)** and **(b)** are satisfied for agent i . For agent i , we now have $|X'_i| = 1$, so any other agent $j \in N \setminus \{i\}$ is also trivially EFX towards agent i as well. Thus, **Properties (a)** and **(b)** are satisfied for all agents.

If Step 3 is executed: In this step, the value of agent i for X'_i might be reduced, to at least $2/3$ of her value for X_i , i.e., $v_i(X'_i) \geq \frac{2}{3}v_i(X_i)$. In \mathbf{X} , agent i was EFX towards every other agent, since $|X_i| = 1$, by the induction hypothesis. By the inequality above, agent i in \mathbf{X}' is now $2/3$ -EFX towards any agent $j \in N \setminus \{i\}$. Now consider any other agent $j \in N \setminus \{i\}$; we have two cases:

- $|X_j| = 1$. In this case we know that for $\ell \in \{1, 2\}$, $v_i(X_j) \geq v_j(g_\ell)$, i.e., agent j (weakly) prefers her own allocation X_j to any of the two goods g_1, g_2 that constitutes agent i 's bundle X'_i . This is because otherwise j could have swapped X_j with one of g_1 and g_2 in Step 1, which by assumption was not executed. From this, it follows that agent j is EFX towards agent i .
- $|X_j| = 2$. We have that for $\ell \in \{1, 2\}$, $v_j(g_\ell) \leq \frac{3}{2}v_j(X_j)$; otherwise, Step 2 could have been executed and agent j would have swapped X'_i with one of g_1 or g_2 . It follows that agent j is $2/3$ -EFX towards agent i .

In both cases, **Properties (a)** and **(b)** are satisfied for all agents.

If Step 4 is executed: Again, we have that $v_i(X'_i) > v_i(X_i)$, hence **Properties (a)** and **(b)** are satisfied for agent i by the induction hypothesis. Now consider any agent $j \in N \setminus \{i\}$; we have two cases:

- $|X_j| = 1$. Similarly to before, we know that $v_j(X_j) \geq v_j(g)$, i.e., agent j does not prefer the good added to agent i 's bundle X'_i from the pool, as otherwise Step 1 of the algorithm would have been executed, and agent j would have swapped X_j for g . We also have that $v_j(X_j) \geq v_j(X'_i \setminus \{g\})$, i.e., agent j does not prefer the good that was part of agent i 's bundle X_i previously, before g' was removed and g was added. This holds because of the induction hypothesis, as **Property (a)** ensures that agent j was EFX towards agent i . This establishes that **Property (a)** holds for agent j in \mathbf{X}' as well.

- $|X_j| = 2$. The argument here is similar to the case above. We know that $v_j(g) \leq \frac{3}{2}v_j(X_j)$, as otherwise Step 2 of the algorithm could have been executed, and agent j would have swapped her bundle X_j with the good g from the pool. Additionally, by **Property (b)** which holds for \mathbf{X} by the induction hypothesis, we know that $v_j(X'_i \setminus \{g\}) = v_j(X_i \setminus \{g'\}) \leq \frac{3}{2}v_j(X_j)$. This establishes that in \mathbf{X}' , agent j does not value any of the goods in X'_i by more than $3/2$ of her value for X_j , and **Property (b)** is satisfied.

If Step 5 is executed: After this step, we obviously have $v_i(X'_i) \geq v_i(X_i)$, for any $i \in N$, as the utility of any agent cannot decrease. For any agent i with $|X_i| = 1$, the agent was EFX towards any other agent in \mathbf{X} , by the induction hypothesis, and therefore she is also EFX towards any other agent in \mathbf{X}' . Similarly, for any agent $i \in N$ such that $|X_i| = |X'_i| = 2$, the agent is $2/3$ -EFX towards any other agent in \mathbf{X}' , since this was the case in \mathbf{X} by the induction hypothesis. It remains to show that every agent i for whom $|X_i| = 2$ and $|X'_i| = 1$ is now EFX in \mathbf{X}' towards every other agent, noting that the agent was $2/3$ -EFX in \mathbf{X} by the induction hypothesis. This is indeed the case here, since i received a bundle X'_i that she valued more than $3/2$ of her value for X_i , i.e., $v_i(X'_i) > \frac{3}{2}v_i(X_i)$. To see this, note that otherwise there would not be an edge (i, j) in the reduced envy graph, where $X_j = X'_i$. This establishes that in \mathbf{X}' , agent i is EFX towards any other agent. In the end, **Properties (a)** and **(b)** are satisfied for all agents.

If Step 6 is executed: Consider agent s first; we have $v_s(X'_s) > v_s(X_s)$. By the induction hypothesis, since $|X_s| = 1$, agent s was EFX towards every other agent by **Property (a)**. This means that in \mathbf{X}' agent s is EFX towards any other agent, and **Properties (a)** and **(b)** are satisfied. Now consider any other agent $j \in N \setminus \{s\}$; again we distinguish two cases.

- $|X_j| = 1$. Similarly to before, we know that $v_j(X_j) \geq v_j(g^*)$, otherwise Step 1 would have been executed and agent j would have swapped X_j with g^* . Since s was a source of $G_r(\mathbf{X})$, we also know that $v_j(X_j) \geq v_j(X_s)$. This establishes that agent j is EFX towards agent s , and therefore **Property (a)** is satisfied.
- $|X_j| = 2$. Again, we know that $v_j(X_j) \geq v_j(g^*)$, otherwise Step 2 would have been executed and agent j would have swapped X_j with g^* . Additionally, since s was a source of $G_r(\mathbf{X})$ with $|X_s| = 1$, we also know that $v_j(X_j) \geq \frac{2}{3}v_j(X_s)$, as otherwise there would be an edge (j, s) in $G_r(\mathbf{X})$. These two inequalities imply that agent j is $2/3$ -EFX towards agent s , and therefore **Property (b)** is satisfied.

If Step 7 is executed: The SINGLETONPOOL subroutine performs a path resolution on the reduced graph $G_r(\mathbf{X})$. Consider the agent i in the resolved path P that lies at the end of the path (the “target” vertex of the path), who receives the good g and one good from X_s . This is also the agent that “triggered” the execution of the SINGLETONPOOL subroutine, as $|X_i| = 1$ and $v_i(g) > \frac{2}{3}v_i(X_i)$. For all agents $j \in N \setminus \{i\}$, we have that $v_j(X'_j) \geq v_j(X_j)$. For those agents, very similar arguments to the ones in the Step 6 establish that **Properties (a)** and **(b)** are satisfied in \mathbf{X}' . Now consider agent i , whose utility in \mathbf{X}' was possibly reduced. Since $|X_i| = 1$, and by **Property (a)** in \mathbf{X} which is satisfied by the induction hypothesis, we have that agent i was EFX towards any other agent in \mathbf{X} . Since $v_i(g) > \frac{2}{3}v_i(X_i)$, it follows that $v_i(X'_i) \geq \frac{2}{3}v_i(X_i)$ and hence agent i is now $2/3$ -EFX towards any other agent. Since $|X'_i| = 2$, **Property (b)** now holds for agent i .

If Step 8 is executed: In this step, the ALLCYCLESRESOLUTION subroutine eliminated all the cycles of $G_e(\mathbf{X})$. We will argue that for every execution of CYCLERESOLUTION within ALLCYCLESRESOLUTION, **Properties (a)** and **(b)** are satisfied. Let $i \in N$ be some agent that is part of the cycle C resolved by CYCLERESOLUTION; after the resolution, the agent receives agent j 's bundle, where (i, j) was an edge in $G_e(\mathbf{X})$; i.e., $X'_i = X_j$. We consider three cases:

- $|X_i| = |X_j|$. In this case, we know that $(i, j) \in G_r$, i.e., it is not red, since in G_e additional edges are from agents with bundles of cardinality 1 to agents with bundles of cardinality 2. Therefore, we have that $v_i(X'_i) = v_i(X_j) > v_i(X_i)$. Since agent i 's utility increased and her bundle did not change in size, **Properties (a)** and **(b)** are satisfied for this agent by the induction hypothesis.

- $|X_i| = 2$ and $|X_j| = 1$. Again, we know that $(i, j) \in G_r$, i.e., it is not red, since in G_e we only add edges originating from agents with bundles of cardinality 1. By definition of $G_r(\mathbf{X})$, we have that $v_i(X'_i) = v_i(X_j) > \frac{2}{3}v_i(X_i)$. By the induction hypothesis, **Property (b)** was satisfied for agent i in \mathbf{X} , and now **Property (a)** is satisfied for agent i in \mathbf{X}' .
- $|X_i| = 1$ and $|X_j| = 2$. In this case the edge (i, j) may be red or not. In either case, it holds that $v_i(X'_i) = v_i(X_j) \geq \frac{2}{3}v_i(X_i)$. Since **Property (a)** was satisfied for agent i by the induction hypothesis, **Property (b)** is now satisfied for i .

In all cases, **Properties (a)** and **(b)** are satisfied for all agents.

If Step 9 is executed: With this step, the algorithm terminates. In particular, the step does not change the allocation \mathbf{X} , and therefore **Properties (a)** and **(b)** are satisfied trivially by the induction hypothesis. \square

Our next lemma establishes that the allocation \mathbf{X}^1 outputted by the 3PA algorithm also satisfies **Properties (c)** to **(e)**.

Lemma 3.3. *Let \mathbf{X} be a seed allocation. Then the output \mathbf{X}^1 of $3PA((v_i)_{i \in N}, \mathbf{X})$ satisfies **Properties (c)** to **(e)**.*

Proof. Assume by contradiction that \mathbf{X}^1 violates one of **Properties (c)** to **(e)**. Assume first that it violates **Property (c)**. That means that there exists some agent $i \in N$ that prefers some good $g \in \mathcal{P}(\mathbf{X}^1)$ from the pool to her bundle X_i^1 . We consider two cases:

- $|X_i^1| = 1$. In that case, the 3PA algorithm would not have terminated and Step 1 would be executed.
- $|X_i^1| = 2$. In that case, the 3PA algorithm would not have terminated and one of the steps up to Step 4 would be executed.

Next assume that **Property (d)** is not satisfied. That means that there exists some agent $i \in N$ with $|X_i^1| = 2$ that has a critical good, i.e., a good $g^* \in \mathcal{P}(X_i^1)$ such that $v_i(g^*) > \frac{1}{2}v_i(X_i^1)$. This means that $v_i(g^*) > \min_{g \in X_i^1} v_i(g)$, i.e., there is a good from the pool $\mathcal{P}(\mathbf{X}^1)$ that agent i prefers to one of the goods in her bundle; this follows by the additivity of the values. In that case, the 3PA algorithm would not have terminated and one of the steps up to Step 4 would be executed.

Finally, assume that **Property (e)** is not satisfied. That has one of the following two implications:

- there exists some agent $i \in N$ with $|X_i^1| = 1$ that has at least two critical goods, or
- there exists some agent $i \in N$ with $|X_i^1| = 1$ that has exactly one critical good $g_i \in \mathcal{P}(\mathbf{X}^1)$, but that good has value more than $2/3$ of her bundle, i.e., $\frac{2}{3}v_i(X_i^1) < v_i(g_i)$.

Consider first the first case, and let g_i and \tilde{g}_i be two of the critical goods of agent i . This means that $v_i(\{g_i, \tilde{g}_i\}) > v_i(X_i^1)$ and since $g_i, \tilde{g}_i \in \mathcal{P}(\mathbf{X}^1)$, Step 3 of the algorithm could have been executed for the agent to swap X_i^1 with $\{g_i, \tilde{g}_i\}$. This contradicts the fact that the algorithm terminated. Next consider the second case, where g_i is the critical good of agent i , for which we have $v_i(g_i) > \frac{2}{3}v_i(X_i^1)$. Assume first that there is some other good $g' \in \mathcal{P}(\mathbf{X}^1)$; in that case we have that $v_i(\{g_i, g'\}) > \frac{2}{3}v_i(X_i^1)$, since $v_i(g') \geq 0$. This implies that Step 3 of the algorithm could have been executed for agent i to swap X_i^1 with $\{g_i, g'\}$, contradicting the fact that the algorithm terminated. Finally, assume that $\mathcal{P}(\mathbf{X}^1) = \{g_1\}$. This is precisely the condition of Step 7 of the 3PA algorithm, and hence that step could have been executed, contradicting the fact that the algorithm terminated. In the end, this establishes that the partial allocation \mathbf{X}^1 satisfies **Properties (c)** to **(e)**. \square

Our final lemma establishes that the enhanced graph G_e of \mathbf{X}^1 has a source without critical goods.

Lemma 3.4. *Let \mathbf{X} be a seed allocation and \mathbf{X}^1 be the output of $3PA((v_i)_{i \in N}, \mathbf{X})$. If \mathbf{X}^1 is not a complete allocation, then $G_e(\mathbf{X}^1)$ has at least one source, and every source s in $G_e(\mathbf{X}^1)$ has $|X_s^1| = 2$.*

Proof. The existence of a source s in $G_e(\mathbf{X}^1)$ is immediate by Step 8 of the 3PA algorithm, which resolves all cycles in the graph $G_e(\mathbf{X}^1)$ and is guaranteed to run because $\mathcal{P}(\mathbf{X}^1) \neq \emptyset$. By the definition of the reduced and enhanced graphs G_r and G_e respectively, it also immediately follows that if s is a source in $G_e(\mathbf{X}^1)$, it is also as source in $G_r(\mathbf{X}^1)$. Since $\mathcal{P}(\mathbf{X}^1) \neq \emptyset$, it is not possible to have $|X_s^1| = 1$, as then Step 6 of the algorithm could have been executed and agent s would have received an extra good from $\mathcal{P}(\mathbf{X}^1)$. Recall, however, that $|X_s^1| \geq 1$ (see the beginning of the proof of Lemma 3.2). Thus, $|X_s^1| > 1$. \square

Clearly, combining Lemmata 3.2 to 3.4 completes the proof of Lemma 3.1. We conclude the section with a proof that the 3PA algorithm (Algorithm 1) terminates in polynomial time.

Lemma 3.5. *The 3PA algorithm terminates in polynomial time.*

Proof. We begin with the easy fact that there are $\binom{m}{2} + \binom{m}{1}$ possible bundles for an agent, given that the 3PA algorithm maintains a partial allocation of size at most 2. For any $m \geq 1$, this quantity is at most m^2 . Next, observe that in every iteration of the while loop of the 3PA algorithm, except in the very last one, there is at least one agent whose bundle changes. We next claim that although the bundle of an agent might change, it never becomes one of the bundles she saw in the past iterations.

Claim 3.6. *Once the bundle of an agent changes from S to S' during the execution of 3PA, it will never go back to S in any future iteration.*

Proof of Claim 3.6. Fix an agent $i \in N$ and consider the finite sequence of her bundles $X_i^{(0)}, X_i^{(1)}, X_i^{(2)}, \dots$, where the superscript indicates how many iterations of the while loop have been executed. First, observe that the only way that i 's value for her bundle decreases is through Steps 3, 7, and 8, but this happens only by moving from a bundle of cardinality 1 to a bundle of cardinality 2 and, despite the decrease, she maintains at least $2/3$ of the previous value. In any other case, i 's value for her bundle strictly increases. In particular, when moving from a bundle of cardinality 2 to a bundle of cardinality 1 (through Steps 2, 5, or 8) this increase is by a factor strictly larger than $3/2$.

Consider all the iterations $\ell_1 < \ell_2 < \dots$, during which the bundle of agent i changes, i.e., $X_i^{(\ell_{\kappa-1})} \neq X_i^{(\ell_{\kappa})}$ for any $\kappa \geq 1$. Using strong induction on κ , we are going to show that $v_i(X_i^{(\ell_{\kappa})})$ is strictly larger than all the preceding bundles of cardinality $|X_i^{(\ell_{\kappa})}|$. This would imply Claim 3.6.

For $\kappa = 1$, observe that $X_i^{(0)} = X_i^{(1)} = \dots = X_i^{(\ell_1-1)}$. There are two simple cases. First, if $|X_i^{(\ell_1-1)}| = |X_i^{(\ell_1)}|$, then it must be $v_i(X_i^{(\ell_1-1)}) < v_i(X_i^{(\ell_1)})$, through Steps 1, 5, or 8, if $|X_i^{(\ell_1)}| = 1$, and through Steps 4, 5, or 8, if $|X_i^{(\ell_1)}| = 2$. Secondly, if $|X_i^{(\ell_1-1)}| \neq |X_i^{(\ell_1)}|$, then $v_i(X_i^{(\ell_1)})$ is strictly larger than all the preceding bundles of cardinality $|X_i^{(\ell_1)}|$ trivially (as there are no other such bundles).

Assuming the induction hypothesis for all indices up to and including κ , consider the bundle $X_i^{(\ell_{\kappa+1})}$.

- First, assume that $|X_i^{(\ell_{\kappa+1}-1)}| = |X_i^{(\ell_{\kappa+1})}|$. Like in the base case, it must be $v_i(X_i^{(\ell_{\kappa+1}-1)}) < v_i(X_i^{(\ell_{\kappa+1})})$, through Steps 1, 5, or 8, if $|X_i^{(\ell_{\kappa+1})}| = 1$, and through Steps 4, 5, or 8, if $|X_i^{(\ell_{\kappa+1})}| = 2$. By the definition of the ℓ_j s, however, we have $X_i^{(\ell_{\kappa})} = X_i^{(\ell_{\kappa+1})} = \dots = X_i^{(\ell_{\kappa+1}-1)}$ and $v_i(X_i^{(\ell_{\kappa})})$ is strictly larger than all the preceding bundles of cardinality $|X_i^{(\ell_{\kappa})}|$ by the induction hypothesis. Thus, $v_i(X_i^{(\ell_{\kappa+1})})$ is strictly larger than all the preceding bundles of cardinality $|X_i^{(\ell_{\kappa+1})}|$.
- Next, assume that $|X_i^{(\ell_{\kappa+1}-1)}| \neq |X_i^{(\ell_{\kappa+1})}|$. If there is no preceding bundle of cardinality $|X_i^{(\ell_{\kappa+1})}|$ then the desired property of $v_i(X_i^{(\ell_{\kappa+1})})$ trivially holds. So, assume that this is not the case, and let r be the largest superscript less than κ for which $|X_i^{(\ell_r)}| = |X_i^{(\ell_{\kappa+1})}|$. We first assume that $|X_i^{(\ell_{\kappa+1})}| = 1$. This means that the subsequence $X_i^{(\ell_r)}, X_i^{(\ell_{r+1})}, \dots, X_i^{(\ell_{\kappa+1})}$ maintains cardinality 1 for some iterations (until $X_i^{(\ell_{r+1}-1)}$), then

moves *once* from cardinality 1 to cardinality 2 (namely, from $X_i^{(\ell_{r+1}-1)}$ to $X_i^{(\ell_{r+1})}$), possibly maintains cardinality 2 for a number of iterations (until $X_i^{(\ell_{\kappa+1}-1)}$) and, finally, moves once from cardinality 2 back to cardinality 1. In terms of value, this translates to a possible increase, followed by a decrease that maintains at least $2/3$ of the value, then by a possible increase, and, finally, by an increase by a factor strictly larger than $3/2$. That is, $v_i(X_i^{(\ell_{\kappa+1})}) > v_i(X_i^{(\ell_r)})$. Now, given that (a) $v_i(X_i^{(\ell_r)})$ is strictly larger than all the preceding bundles of cardinality $|X_i^{(\ell_r)}|$, (b) $X_i^{(\ell_r)} = X_i^{(\ell_{r+1})} = \dots = X_i^{(\ell_{\kappa+1}-1)}$, and (c) the bundles $X_i^{(\ell_{r+1})}, \dots, X_i^{(\ell_{\kappa+1}-1)}$ all have cardinality 2, we conclude that $v_i(X_i^{(\ell_{\kappa+1})})$ is strictly larger than all the preceding bundles of cardinality $|X_i^{(\ell_{\kappa+1})}|$. The remaining case is $|X_i^{(\ell_{\kappa+1})}| = 2$. The argument is completely analogous with the only difference being that the subsequence $X_i^{(\ell_r)}, X_i^{(\ell_{r+1})}, \dots, X_i^{(\ell_{\kappa+1})}$ maintains cardinality 2 for some iterations, then moves once from cardinality 2 to cardinality 1, possibly maintains cardinality 1 for a number of iterations and, finally, moves once from cardinality 1 back to cardinality 2. \square

Claim 3.6 implies that after every iteration at least one of the possible bundles is lost forever to at least one agent. As a result, the possible choices for all agents will be exhausted after at most nm^2 iterations of the main loop of the 3PA algorithm, so $nm^2 + 1$ is an immediate upper bound on the maximum number iterations before the 3PA algorithm terminates. The polynomial running time now follows by observing that only one step of the loop is executed in each iteration and that every such step runs in polynomial time. The latter is straightforward to see, given that building the graphs G_r and G_e , finding a cycle or all sources in them, and resolving cycles can all be done in polynomial time. \square

4 2/3-EFX on Multigraphs or For a Small Number of Agents

In this section, we provide our first main results, namely that $2/3$ -EFX allocations exist and can be obtained in polynomial time for (i) multigraph value instances, or (ii) additive instances with up to 7 agents. We begin with some auxiliary results.

4.1 Key Lemmata

Recall that in [Section 3](#) we mentioned that we plan to obtain a $2/3$ -EFX partial allocation X^2 that does not induce any critical goods. [Lemma 4.2](#) below establishes that obtaining such an X^2 suffices; we can then complete a $2/3$ -EFX allocation via running the Envy Cycle Elimination algorithm of [Lipton et al. \[2004\]](#). Given an envy graph, this algorithm extends a partial allocation one good at a time by allocating the next available good to an agent who is a source in the envy graph. If such an agent does not exist, the algorithm first resolves one or more envy cycles. For completeness, we state below a parametric version of Envy Cycle Elimination. The algorithm is stated so that it can run on a subset of the goods having a partial allocation as a starting point.

In general, tie-breaking is not important for the properties of the algorithm we need and which are summarized in the next lemma. As usual, we may assume that any tie-breaking is done lexicographically.

Lemma 4.1 (Follows by [Lipton et al. \[2004\]](#)). *Fix an agent i , and let $X_i^{(\ell)}$ be the bundle assigned to i at the end of the ℓ -th iteration of the for loop, for any $\ell \in \mathbb{N}$. Then, for $k \geq \ell$, it holds that $v_i(X_i^{(k)}) \geq v_i(X_i^{(\ell)})$. Furthermore, the algorithm terminates in polynomial time.*

[Lemma 4.2](#) below follows from results by [Markakis and Santorinaios \[2023\]](#) as part of a general approximation framework; see also [[Amanatidis et al., 2020](#), [Farhadi et al., 2021](#)]. We adapt the statement to our terminology, and provide a short proof for completeness.

ALGORITHM 2: ENVYCYCLEELIMINATION(X, G)

Input: A partial allocation X and its envy graph $G(X)$.

Output: A complete allocation X' .

```
for every  $g \in M'$  in arbitrary order do
  while there is no source in  $G(X)$  do
    Find a cycle  $C$  in  $G(X)$ 
     $X \leftarrow \text{CYCLERESOLUTION}(X, G(X), C)$ 
  Let  $s \in N$  be a source in  $G(X)$ 
   $X_i \leftarrow X_i \cup \{g\}$ 
return  $X$ 
```

Lemma 4.2 (Markakis and Santorinaios [2023]). *Let X be a 2/3-EFX partial allocation that induces no critical goods. Then a 2/3-EFX allocation \tilde{X} can be obtained from X in polynomial time.*

Proof. The complete allocation \tilde{X} is obtained from X by running the Envy Cycle Elimination algorithm of Lipton et al. [2004]; in particular, here we will assume that \tilde{X} is the output of ENVYCYCLEELIMINATION($X, G(X)$). The polynomial running time follows by the fact that ENVYCYCLEELIMINATION runs in polynomial time; see Lemma 4.1. For the 2/3-EFX guarantee, consider any agent $i \in N$. We know that $v_i(\tilde{X}_i) \geq v_i(X_i)$ because during a run of ENVYCYCLEELIMINATION, the utility of any agent never decreases; see Lemma 4.1. Now consider an arbitrary agent $j \in N \setminus \{i\}$.

If no good is ever added to \tilde{X}_j by ENVYCYCLEELIMINATION, then $\tilde{X}_j = X_{j'}$, for some $j' \in N$ (possibly different from j). But agent i was 2/3-EFX towards j' in X , and as her value did not decrease, she is now 2/3-EFX towards j in \tilde{X} .

The remaining case is that \tilde{X}_j has been augmented by ENVYCYCLEELIMINATION. Let g be the last good that was added to \tilde{X}_j by ENVYCYCLEELIMINATION. Right before good g was added to \tilde{X}_j , the bundle belonged to some agent $j' \in N$, who was a source of the envy graph $G(\tilde{X}^t)$, where \tilde{X}^t is the allocation at that point. For \tilde{X}_i^t , the corresponding bundle of agent i , we have that $v_i(\tilde{X}_i^t) \geq v_i(\tilde{X}_{j'}^t) = v_i(\tilde{X}_j \setminus \{g\})$. Recall that $\mathcal{P}(X)$ does not induce any critical goods; in particular, g was not critical for i . This directly gives us $v_i(g) \leq \frac{1}{2}v_i(X_i) \leq \frac{1}{2}v_i(\tilde{X}_i^t)$. This, in turn, implies that

$$v_i(\tilde{X}_j) = v_i(\tilde{X}_j \setminus \{g\}) + v_i(g) \leq v_i(\tilde{X}_i^t) + \frac{1}{2}v_i(\tilde{X}_i^t) = \frac{3}{2}v_i(\tilde{X}_i^t) \leq \frac{3}{2}v_i(\tilde{X}_i).$$

Hence agent i is 2/3-EFX towards agent j in \tilde{X} .

Since both agents i and j were chosen arbitrarily, we conclude that \tilde{X} is 2/3-EFX for all agents. \square

Our next lemma regards the allocation of critical goods, which will transform the partial allocation X^1 obtained as the output of the 3PA algorithm into the partial allocation X^2 that will in turn be transformed into a complete 2/3-EFX allocation by Lemma 4.2. In particular, it concerns the special case when every critical good is critical for at most one agent. This task is handled by the UNCONTESTEDCRITICAL algorithm (Algorithm 3) that allocates all the remaining critical goods by carefully resolving cycles in the envy graph of the given partial allocation.

This algorithm is similar in nature to the Envy Cycle Elimination algorithm of Lipton et al. [2004]. The key difference is that we do not simply choose any source, but a source of a path that leads to the agent with the critical good which we aim to allocate in the current round. Then, if the addition of the good creates an envy cycle involving this agent, we resolve this particular cycle first.

ALGORITHM 3: UNCONTESTEDCRITICAL(\mathbf{X}, \tilde{G})

Input: A partial allocation \mathbf{X} satisfying the conditions (i), (ii) and (iii) of Lemma 4.3, and its graph $\tilde{G}(\mathbf{X})$.

Output: A partial allocation \mathbf{X}' which does not induce any critical goods.

$\mathbf{X} \leftarrow \text{ALLCYCLESRESOLUTION}(\mathbf{X}, \tilde{G}(\mathbf{X}))$

while there exists $i \in N$ and $g_i \in \mathcal{P}(\mathbf{X})$ such that $v_i(g_i) > \frac{1}{2}v_i(X_i)$ **do**

// while there exists an agent with a critical good

Let s be a source of $\tilde{G}(\mathbf{X})$ such that there exists some path Π from s to i in $\tilde{G}(\mathbf{X})$

if $v_i(X_s \cup \{g_i\}) > v_i(X_i)$ **then**

// if agent i prefers the source's bundle augmented with her critical good

$(X_j)_{j \in N: \exists(j, \ell) \in \Pi} \leftarrow \text{PATHRESOLUTION}(\mathbf{X}, \tilde{G}, \Pi)$

// every agent on the path except agent i receives the bundle of her successor

$X_i \leftarrow X_s \cup \{g_i\}$ // agent i receives the bundle of the source plus her critical good g_i

else

$X_s \leftarrow X_s \cup \{g_i\}$ // agent i 's critical good is given to the source of the path

$\mathbf{X} = \text{ALLCYCLESRESOLUTION}(\mathbf{X}, \tilde{G})$ // Update \mathbf{X} by eliminating all envy cycles in $\tilde{G}(\mathbf{X})$

return \mathbf{X}

Lemma 4.3. *Let \mathbf{X} be a partial allocation such that (i) \mathbf{X} is 2/3-EFX, (ii) each agent has at most one critical good, and (iii) no good is critical for more than one agent. Then UNCONTESTEDCRITICAL($\mathbf{X}, G(\mathbf{X})$) returns, in polynomial time, a partial allocation \mathbf{X}' that is 2/3-EFX and in which no agent has a critical good.*

Proof. First we argue that \mathbf{X}' can be obtained in polynomial time. To see this, recall that ALLCYCLESRESOLUTION runs in polynomial time (Lemma 2.11), as does PATHRESOLUTION. With respect to the while loop of UNCONTESTEDCRITICAL(\mathbf{X}, G), note that in each iteration, the number of goods in the pool $\mathcal{P}(\mathbf{X})$ decreases, as one critical good is allocated to some agent, and no goods are ever returned to $\mathcal{P}(\mathbf{X})$. This implies that the algorithm will terminate after at most m iterations of the while loop. Clearly, each iteration here runs in polynomial time.

The fact that in \mathbf{X}' there are no agents with critical goods is an immediate consequence of the algorithm UNCONTESTEDCRITICAL terminating. We next argue that \mathbf{X}' is 2/3-EFX. We will prove by induction that properties (i), (ii), and (iii) of the statement of the lemma hold at every iteration right before the condition of the while loop of UNCONTESTEDCRITICAL is checked. Then, the properties will also hold at the termination of the execution of UNCONTESTEDCRITICAL($\mathbf{X}, G(\mathbf{X})$); this is enough to establish that \mathbf{X}' is 2/3-EFX, as this is property (i).

For the base case, it is easy to see that the properties are satisfied before the first iteration of the loop: they hold for the initial partial allocation \mathbf{X} by assumption, and they continue to hold after running the ALLCYCLESRESOLUTION subroutine, which only swaps bundles between agents, never reducing their values.

Now consider the k -th iteration of the while loop. Let \mathbf{X} and $\tilde{\mathbf{X}}$ be the partial allocations right before and right after the k -th iteration respectively. After the end of the iteration, we have that $v_i(\tilde{X}_i) \geq v_i(X_i)$ for all $i \in N$, and that $\mathcal{P}(\tilde{\mathbf{X}}) \subseteq \mathcal{P}(\mathbf{X})$. By the induction hypothesis, it follows that properties (ii) and (iii) are trivially satisfied in $\tilde{\mathbf{X}}$. To establish property (i), notice that for every agent $j \in N \setminus \{i\}$, it holds that $v_j(X_s) \leq v_j(X_j)$, since s is a source of $G(\mathbf{X})$, and $v_j(g_i) \leq \frac{1}{2}v_j(X_j)$, since g_i is critical only for i . By adding the two inequalities, we have that agent j is 2/3-EFX towards any agent who receives the bundle $X_s \cup \{g_i\}$ in $\tilde{\mathbf{X}}$ (either agent i or agent s). Recall that by the induction hypothesis, \mathbf{X} right before the k -th iteration was 2/3-EFX. Since all other bundles (i.e., all bundles besides X_s) do not change as sets and they are possibly exchanged so that no agent's value is decreased, we conclude that $\tilde{\mathbf{X}}$ is also 2/3-EFX. \square

4.2 2/3-EFX for Multigraph Value Instances

Given the machinery that we have set up so far, it is fairly easy to show that it is possible to achieve 2/3-EFX allocations in multigraph value instances, also in polynomial time.

ALGORITHM 4: MULTIGRAPHALLOCATE($N, (v_i)_{i \in N}, M$)

Input: A multigraph value instance.

Output: A 2/3-EFX allocation X .

Let X^0 be an arbitrary partial allocation where each bundle has cardinality 1

$X^1 \leftarrow 3PA((v_i)_{i \in N}, X^0)$

$C \leftarrow \{g \in \mathcal{P}(X^1) : \text{there are distinct } i, j \in N \text{ so that } g \text{ is critical for both } i, j\}$

// the set of critical goods which are critical for more than one agent

Let s be a source of $G_e(X^1)$

// at least one such s exists, and has $|X_s^1| > 1$ and no critical goods, by [Lemma 3.1](#)

$\tilde{X}_s \leftarrow X_s^1 \cup C$

// we just give the whole C to s

$\tilde{X}_i \leftarrow X_i^1$ for any other $i \in N \setminus \{s\}$

$X^2 \leftarrow \text{UNCONTESTEDCRITICAL}(\tilde{X}, G(\tilde{X}))$

// we handle the remaining critical goods

$X \leftarrow \text{ENVYCYCLEELIMINATION}(X^2, G(X^2))$

// we complete the allocation

return X

Theorem 4.4. *Let $(N, (v_i)_{i \in N}, M)$ be a multigraph value instance. Then MULTIGRAPHALLOCATE constructs a 2/3-EFX allocation in polynomial time.*

Proof. The partial allocation X^0 where each agent receives a single good arbitrarily trivially satisfies [Properties \(a\) to \(d\)](#). We use this allocation as input to the 3PA algorithm ([Algorithm 1](#)) to obtain a partial allocation X^1 ; by [Lemma 3.5](#), X^1 can be obtained in polynomial time. By [Lemma 3.1](#), X^1 also satisfies [Properties \(a\) to \(e\)](#), and either it is a complete allocation or its enhanced graph $G_e(X^1)$ has at least one source s , and this (as any other source of $G_e(X^1)$) does not have any critical goods.

Next, we consider the set C of critical goods which are critical for more than one agent. Since this is a multigraph value instance, any good in C is critical for *exactly* two agents, as only two agents could have positive value for it. We then assign every good $g \in C$ to s , i.e., $\tilde{X}_s = X_s^1 \cup C$. Finding s , C , and constructing \tilde{X} obviously can be done in polynomial time. We will show the following claim about \tilde{X} :

Claim 4.5. *The partial allocation \tilde{X} satisfies the conditions in the statement of [Lemma 4.3](#).*

Proof of Claim 4.5. First notice that condition “(iii) no good is critical for more than one agent” is directly satisfied by the removal of C from $\mathcal{P}(\tilde{X})$. Further, the condition “(ii) each agent has at most one critical good” is met because it holds for X^1 (by [Property \(e\)](#)) and, by moving to \tilde{X} , we have $\mathcal{P}(\tilde{X}) \subseteq \mathcal{P}(X^1)$ and no agent had her value reduced. It remains to show that \tilde{X} is 2/3-EFX (i.e., condition “(i)” of [Lemma 4.3](#)). Looking at the partial allocation X^1 , first notice that for any good $g \in C$ corresponding to an edge (j, ℓ) , g must be critical for both agents j and ℓ , but it has no value for anyone else, i.e., for any agent $i \in N \setminus \{j, \ell\}$, we have $v_i(g) = 0$.

Now consider any agent $i \in N$ with a critical good $g_i \in C$. By [Property \(d\)](#) of X^1 , it must be that $|X_i^1| = 1$. Recall that the source agent s had no critical goods. So, i must be distinct from s and hence $\tilde{X}_i = X_i^1$. Also, by [Property \(e\)](#) of X^1 , every other good $g \in C \setminus \{g_i\}$ is not critical for agent i . This implies that $v_i(g) = 0$ for all $g \in C \setminus \{g_i\}$. From this, we obtain that $v_i(C) = v_i(g_i) \leq \frac{2}{3}v_i(X_i^1)$, where the last inequality follows again by [Property \(e\)](#) of X^1 . Also, since s is a source in $G_e(X^1)$, we have $v_i(X_s^1) < \frac{2}{3}v_i(X_i^1)$, by the definition

of $G_e(\mathbf{X}^1)$ and the cardinalities of X_s^1, X_i^1 . Therefore,

$$v_i(\tilde{X}_s) = v_i(X_s^1 \cup C) < \frac{2}{3}v_i(X_i^1) + \frac{2}{3}v_i(X_i^1) \leq \frac{3}{2}v_i(X_i^1) = \frac{3}{2}v_i(\tilde{X}_i),$$

where the last equality follows from the fact that $\tilde{X}_i = X_i^1$. So, agent i is 2/3-EFX towards agent s in $\tilde{\mathbf{X}}$. Given that she was 2/3-EFX towards anyone else in \mathbf{X}^1 (by [Properties \(a\)](#) and [\(b\)](#)), we conclude that agent i is 2/3-EFX towards everyone in $\tilde{\mathbf{X}}$.

Next, consider any agent $i \in N$ with no critical goods in C (where i could be s here). By the discussion about the value of goods in C above, we have $v_i(C) = 0$. Moreover, by the choice of s , the definition of $G_e(\mathbf{X}^1)$, and the fact that $|X_s^1| > 1$, we have $v_i(X_s^1) \leq v_i(X_i^1)$ (independently of the cardinality of X_i^1). Thus, we get $v_i(\tilde{X}_s) = v_i(X_s^1 \cup C) \leq v_i(X_i^1) + 0 \leq \frac{3}{2}v_i(\tilde{X}_i)$. So, again, agent i is 2/3-EFX towards s in $\tilde{\mathbf{X}}$. As she was 2/3-EFX towards anyone else in \mathbf{X}^1 (by [Properties \(a\)](#) and [\(b\)](#)), agent i is 2/3-EFX towards everyone in $\tilde{\mathbf{X}}$. \square

Given [Claim 4.5](#), [Lemma 4.3](#) implies that the partial allocation \mathbf{X}^2 returned by the UNCONTESTEDCRITICAL algorithm in polynomial time is 2/3-EFX and it does not induce any critical goods. By [Lemma 4.2](#), we can then obtain a complete 2/3-EFX allocation \mathbf{X} in polynomial time via ENVYCYCLEELIMINATION. \square

4.3 2/3-EFX for up to 7 Agents

Next we show the existence of 2/3-EFX allocations for 7 agents, and that they can be computed in polynomial time. For this we need a slight variant of the 3PA algorithm augmented by one additional step between Steps 8 and 9 as shown below as 3PA⁺.

ALGORITHM 5: PROPERTY-PRESERVING PARTIAL ALLOCATION⁺ (3PA⁺) $((v_i)_{i \in N}, \mathbf{X})$

Input / Output: (as in 3PA)

... (same as 3PA) ...

```

8 | (Step 8) else if ...
   | | ...
8.5 | (Step 8.5) else if for some  $i \in N$ , there exists a path  $\Pi = (s, \dots, i)$  in  $G_r(\mathbf{X})$ 
   | | such that  $v_i(X_i) < v_i(\{g, g'\})$  for some  $g \in \mathcal{P}(\mathbf{X})$  and some  $g' \in X_s$  then
   | |   Let  $\Pi$  be such a path
   | |    $\mathbf{X} \leftarrow \text{PATHRESOLUTION}^*(\mathbf{X}, G_r, \Pi)$ 
   | |   // Else if there exists a path from a source  $s$  to some agent  $i$  in  $G_r(\mathbf{X})$ , such that  $i$  prefers a
   | |   good from the pool and a good from  $X_s$  to her own bundle, swap the bundles along the envy
   | |   path and give those two goods to  $i$ .
...
return X

```

Whenever Step 8.5 is executed, [Properties \(a\)](#) to [\(e\)](#) hold for the same reasons they hold whenever Steps 4 and 5 are executed. In fact, with minimal changes to the proofs of [Lemmata 3.1](#) and [3.5](#), we get their analogs for 3PA⁺; this is summarized in [Lemma 4.6](#) below. Recall that a seed allocation is a partial allocation of size at most 2, which does not contain any empty bundles and satisfies [Properties \(a\)](#) and [\(b\)](#).

Lemma 4.6. *Let \mathbf{X} be a seed allocation. Then, in polynomial time, 3PA⁺ $((v_i)_{i \in N}, \mathbf{X})$ outputs a partial allocation \mathbf{X}^1 of size at most 2 that satisfies [Properties \(a\)](#) to [\(e\)](#). Furthermore, if \mathbf{X}^1 is not a complete allocation, then $G_e(\mathbf{X}^1)$ has at least one source, and every source s in $G_e(\mathbf{X}^1)$ has $|X_s^1| = 2$.*

Now we are ready to state the main algorithm for a small number of agents. Of course, the general idea is very similar to MULTIGRAPHALLOCATE, yet the process of handling the critical goods is more refined here.

ALGORITHM 6: FEWAGENTSALLOCATE($N, (v_i)_{i \in N}, M$)

Input: An additive instance with at most 7 agents.

Output: A 2/3-EFX allocation X .

Let X^0 be an arbitrary partial allocation where each bundle has cardinality 1

$X^1 \leftarrow 3PA^+((v_i)_{i \in N}, X^0)$

$C \leftarrow \{g \in \mathcal{P}(X^1) : \text{there are distinct } i, j \in N \text{ so that } g \text{ is critical for both } i, j\}$

// the set of critical goods which are critical for more than one agent

if $|C| = 2$ (say, $C = \{g_1, g_2\}$) **and there are at least two sources, s_1, s_2 , in $G_e(X^1)$ then**

// recall that $|X_{s_1}^1| > 1$, $|X_{s_2}^1| > 1$, and s_1, s_2 have no critical goods, by [Lemma 3.1](#)

$\tilde{X}_{s_1} \leftarrow X_{s_1}^1 \cup \{g_1\}$	// we split C among s_1, s_2
$\tilde{X}_{s_2} \leftarrow X_{s_2}^1 \cup \{g_2\}$	
$\tilde{X}_i \leftarrow X_i^1$ for any other $i \in N \setminus \{s_1, s_2\}$	

else

Let s be a source of $G_e(X^1)$

// at least one such s exists, and has $|X_s^1| > 1$ and no critical goods, by [Lemma 3.1](#)

$\tilde{X}_s \leftarrow X_s^1 \cup C$	// we give the whole C to s
---------------------------------------	---------------------------------

$\tilde{X}_i \leftarrow X_i^1$ for any other $i \in N \setminus \{s\}$	
--	--

$X^2 \leftarrow \text{UNCONTESTEDCRITICAL}(\tilde{X}, G(\tilde{X}))$ // we handle the remaining critical goods

$X \leftarrow \text{ENVYCYCLEELIMINATION}(X^2, G(X^2))$ // we complete the allocation

return X

Theorem 4.7. *Let $(N, (v_i)_{i \in N}, M)$ be any additive instance with $n \leq 7$. Then FEWAGENTSALLOCATE constructs a 2/3-EFX allocation in polynomial time.*

Proof. Initially, we argue like in the proof of [Theorem 4.4](#). The partial allocation X^0 trivially satisfies [Properties \(a\) to \(d\)](#). When used as input to the $3PA^+$ algorithm ([Algorithm 5](#)) we obtain in polynomial time a partial allocation X^1 , which also satisfies [Properties \(a\) to \(e\)](#), and either it is a complete allocation or its enhanced graph $G_e(X^1)$ has at least one source s and this (as any other source) has a bundle of size 2 (by [Lemma 4.6](#)). Again we consider the set C of critical goods which are critical for more than one agent, but now we need to argue about its cardinality.

If there are at least two sources, s_1, s_2 , in the enhanced envy graph $G_e(X^1)$, then there are at most 5 agents that are not sources and may have a critical good. (Indeed, recall that since $X_{s_1}^1 = X_{s_2}^1 = 2$, by [Property \(c\)](#) of X^1 , s_1, s_2 cannot have critical goods.) This immediately implies that $|C| \leq 2$. The case where $|C| \leq 1$ is handled in the *else* part of FEWAGENTSALLOCATE and is analysed later in the proof. For now, we consider the case where $|C| = 2$, say $C = \{g_1, g_2\}$, which is handled in the *if* part of FEWAGENTSALLOCATE. To define the next partial allocation, \tilde{X} , we assign one good from C to each of s_1, s_2 , i.e., $\tilde{X}_{s_i} = X_{s_i}^1 \cup \{g_i\}$, for $i \in \{1, 2\}$. Finding s_1, s_2, C , and constructing \tilde{X} can be clearly done in polynomial time.

Claim 4.8. *If the partial allocation \tilde{X} is constructed in the if case, it satisfies the conditions in the statement of [Lemma 4.3](#).*

Proof of Claim 4.8. The conditions “(ii) each agent has at most one critical good” and “(iii) no good is critical for more than one agent” are satisfied exactly like in the proof of [Claim 4.5](#). We only need to show condition “(i)”, i.e., that \tilde{X} is 2/3-EFX.

First consider any agent $i \in N$ with a critical good in C under the partial allocation X^1 . We assume that i 's critical good is g_1 , the other case being completely symmetric. By [Property \(d\)](#) of X^1 , we have $|X_i^1| = 1$. Also, by [Property \(e\)](#) of X^1 , we have $v_i(g_2) \leq v_i(g_1) \leq \frac{2}{3}v_i(X_i^1)$. Recall that s_1, s_2 had no critical goods. So,

i must be distinct from both s_1 and s_2 and hence $\tilde{X}_i = X_i^1$. Finally, since s_1, s_2 are sources in $G_e(\mathbf{X}^1)$, we have $v_i(X_{s_j}^1) < \frac{2}{3}v_i(X_i^1)$, $j \in \{1, 2\}$, by the definition of $G_e(\mathbf{X}^1)$ and the cardinalities of $X_{s_1}^1, X_{s_2}^1, X_i^1$. We now have, for $j \in \{1, 2\}$,

$$v_i(\tilde{X}_{s_j}) = v_i(X_{s_j}^1 \cup \{g_j\}) < \frac{2}{3}v_i(X_i^1) + \frac{2}{3}v_i(X_i^1) \leq \frac{3}{2}v_i(X_i^1) = \frac{3}{2}v_i(\tilde{X}_i).$$

So, agent i is 2/3-EFX towards both s_1 and s_2 in $\tilde{\mathbf{X}}$. Given that she was 2/3-EFX towards anyone else in \mathbf{X}^1 (by **Properties (a)** and **(b)**), we conclude that agent i is 2/3-EFX towards everyone in $\tilde{\mathbf{X}}$.

Next, consider any agent $i \in N$ with no critical goods in C (where i could be s_1 or s_2 here). This immediately implies that $\max_{j \in \{1, 2\}} v_i(g_j) \leq \frac{1}{2}v_i(X_i^1) \leq \frac{1}{2}v_i(\tilde{X}_i)$. Moreover, for $j \in \{1, 2\}$, by the choice of s_j , the definition of $G_e(\mathbf{X}^1)$, and the fact that $|X_{s_j}^1| > 1$, we have $v_i(X_{s_j}^1) \leq v_i(X_i^1)$ (independently of the cardinality of X_i^1). Thus, we get

$$v_i(\tilde{X}_{s_j}) = v_i(X_{s_j}^1 \cup \{g_j\}) \leq v_i(X_i^1) + \frac{1}{2}v_i(X_i^1) \leq \frac{3}{2}v_i(\tilde{X}_i).$$

So, again, agent i is 2/3-EFX towards s in $\tilde{\mathbf{X}}$. As she was 2/3-EFX towards anyone else in \mathbf{X}^1 (by **Properties (a)** and **(b)**), agent i is 2/3-EFX towards everyone in $\tilde{\mathbf{X}}$. \square

Similarly to how we argued above, if there is a single source, s , in $G_e(\mathbf{X}^1)$, then there are at most 6 agents that are not sources and may have a critical good, and this implies that $|C| \leq 3$. Both this case and the case where we may have multiple sources but $|C| \leq 1$ are handled together in the *else* part of FEWAGENTSALLOCATE. There, to define the partial allocation $\tilde{\mathbf{X}}$, we assign the whole C to s (which may be the unique source or any one of multiple sources). That is, $\tilde{X}_s = X_s^1 \cup C$. Finding s , C , and constructing $\tilde{\mathbf{X}}$ can be done in polynomial time.

Claim 4.9. *If the partial allocation $\tilde{\mathbf{X}}$ is constructed in the else case, it satisfies the conditions in the statement of Lemma 4.3.*

Proof of Claim 4.9. Again, the conditions “(ii) each agent has at most one critical good” and “(iii) no good is critical for more than one agent” are satisfied exactly like in the proof of Claim 4.5. We only need to show condition “(i)”, i.e., that $\tilde{\mathbf{X}}$ is 2/3-EFX.

First consider any agent $i \in N$ with a critical good g_i (not necessarily in C) under the partial allocation \mathbf{X}^1 . By **Property (d)** of \mathbf{X}^1 , we have $|X_i^1| = 1$. Also, since s is a source in $G_e(\mathbf{X}^1)$, we have $v_i(X_s^1) < \frac{2}{3}v_i(X_i^1)$, by the definition of $G_e(\mathbf{X}^1)$ and the cardinalities of X_s^1, X_i^1 .

Since no step of the 3PA⁺ algorithm can be applied on \mathbf{X}^1 , the condition of Step 3 fails, i.e., for any two goods $g, g' \in \mathcal{P}(\mathbf{X})$, $v_i(\{g, g'\}) \leq \frac{2}{3}v_i(X_i^1)$. However, as g_i is critical for i , $v_i(g_i) > \frac{1}{2}v_i(X_i^1)$. It then follows that for any $g \in \mathcal{P}(\mathbf{X}) \setminus \{g_i\}$, it must be $v_i(g) \leq \frac{1}{6}v_i(X_i^1)$, as $v_i(\{g, g_i\}) \leq \frac{2}{3}v_i(X_i^1)$. Now it is not hard to bound $v_i(C)$. If $g_i \notin C$, then $v_i(C) \leq |C|\frac{1}{6}v_i(X_i^1) \leq \frac{1}{2}v_i(X_i^1)$. If $g_i \in C$, it could be that $|C| \leq 2$, and thus $v_i(C) \leq \frac{2}{3}v_i(X_i^1)$, by the discussion above, or it could be that $|C| \leq 2$, say $C = \{g_i, g, g'\}$, and thus $v_i(C) = v_i(\{g_i, g\}) + v_i(g') \leq \frac{2}{3}v_i(X_i^1) + \frac{1}{6}v_i(X_i^1) = \frac{5}{6}v_i(X_i^1)$. In any case, $v_i(C) \leq \frac{5}{6}v_i(X_i^1)$. To show that $\tilde{\mathbf{X}}$ is 2/3-EFX, we distinguish two cases.

Case 1 ($|C| = 3$): Then any agent $i \in N \setminus \{s\}$ has a critical good in $\mathcal{P}(\mathbf{X}^1)$. Therefore,

$$v_i(\tilde{X}_s) = v_i(X_s^1) + v_i(C) \leq \frac{2}{3}v_i(X_i^1) + \frac{5}{6}v_i(X_i^1) = \frac{3}{2}v_i(X_i^1).$$

So, agent i is 2/3-EFX towards s in $\tilde{\mathbf{X}}$, and as she was 2/3-EFX towards anyone else in \mathbf{X}^1 (by **Properties (a)** and **(b)**), she is 2/3-EFX towards everyone in $\tilde{\mathbf{X}}$. It is also straightforward that agent s is 2/3-EFX towards everyone in $\tilde{\mathbf{X}}$, as her value did not decrease and every other agent maintained the bundle she had in \mathbf{X}^1 .

Case 2 ($|C| \leq 2$): Showing that any agent $i \in N \setminus \{s\}$ who has a critical good in $\mathcal{P}(X^1)$ is 2/3-EFX towards everyone in \tilde{X} is almost the same as in Case 1, except the upper bound for $v_i(C)$ is now $\frac{2}{3}v_i(X_i^1)$ rather than $\frac{5}{6}v_i(X_i^1)$.

The interesting case is that of agent who have no critical goods, so let $i \in N$ be such an agent (possibly i is s herself). We have $v_i(X_i^1) \geq v_i(X_s^1)$, since s is a source of $G_e(X^1)$. Also, since Steps 3 and 4 of 3PA⁺ fail to apply on X^1 , we have $v_i(X_i^1) \geq v_i(C)$, and since Step 8.5 of 3PA⁺ fails to apply on X^1 , we have that for any goods $g \in X_s^1$ and $g' \in C$, $v_i(X_i^1) \geq v_i(\{g, g'\})$. Overall, for any two goods $g, g' \in \tilde{X}_s$, $v_i(X_i^1) \geq v_i(\{g, g'\})$. This in turns means that for any three goods $g, g', g'' \in \tilde{X}_s$, $v_i(X_i^1) \geq \frac{2}{3}v_i(\{g, g', g''\})$. That is, for any good $g \in \tilde{X}_s$,

$$v_i(\tilde{X}_i) \geq v_i(X_i^1) \geq \frac{2}{3}v_i(\tilde{X}_s \setminus \{g\}),$$

and, thus, agent i is 2/3-EFX towards s in \tilde{X} , and as she was 2/3-EFX towards anyone else in X^1 (by [Properties \(a\) and \(b\)](#)), she is 2/3-EFX towards everyone in \tilde{X} . \square

Given [Claims 4.8 and 4.9](#), [Lemma 4.3](#) implies that the partial allocation X^2 returned in polynomial time by the UNCONTESTEDCRITICAL algorithm is 2/3-EFX and it does not induce any critical goods. By [Lemma 4.2](#), we then obtain a complete 2/3-EFX allocation X in polynomial time via ENVYCYCLEELIMINATION. \square

5 2/3-EFX for 3-Value Instances

The last setting we consider is 3-value instances with values $a \geq b \geq c \geq 0$. We assume that $a > b > c$, as, otherwise, the problem is either trivial or reduces to the 2-value setting where it is known that EFX allocations can be computed in polynomial time [[Amanatidis et al., 2021](#)]. Therefore, as we mentioned in [Section 2](#), it is without loss of generality to set $a = 1$ and rescale b and c appropriately. The main result here is the following theorem about our THREEVALUESALLOCATE algorithm ([Algorithm 8](#)).

Theorem 5.1. *Let $(N, (v_i)_{i \in N}, M)$ be any 3-value instance. Then THREEVALUESALLOCATE constructs a 2/3-EFX allocation in polynomial time.*

For the proof of the theorem, but also for the description of our algorithm, we consider three cases depending on the range of the values of b and c , namely:

- (a) $b \leq \frac{1}{2}$;
- (b) $b > \frac{1}{2}$ and $b + c \geq \frac{2}{3}$;
- (c) $b > \frac{1}{2}$ and $b + c < \frac{2}{3}$.

It turns out that [Case \(a\)](#) can be completely handled by our existing machinery, whereas [Case \(b\)](#) requires a minor modification of the 3PA algorithm similar to what we did by adding [Step 8.5](#) in 3PA⁺. By replacing [Step 8.5](#) with a slightly more refined version of itself, we get the 3PA* algorithm ([Algorithm 7](#)) below. [Case \(c\)](#), however, turns out to be much more challenging, and requires significant refinements to our general approach. The variant of 3PA we design here, 3PA⁺⁺ ([Algorithm 7](#) in [Section 5.1.4](#)), is rather intricate, as is the proof about the properties it maintains, and we defer it to [Section 5.1](#).

Whenever [Step 8.5*](#) is executed, [Properties \(a\) to \(e\)](#) hold for the same reasons they hold whenever [Steps 4, 5 and 8](#) of 3PA are executed. Note that, like [Steps 3, 7 and 8](#), [Step 8.5*](#) may decrease the value an agent has for her bundle, but again this only happens by moving from a bundle of cardinality 1 to a bundle of cardinality 2 and always maintains at least 2/3 of the previous value. As it was the case with 3PA⁺ and [Lemma 4.6](#), with minimal changes to the proofs of [Lemmata 3.1 and 3.5](#), we get the following for 3PA*.

ALGORITHM 7: PROPERTY-PRESERVING PARTIAL ALLOCATION* (3PA*) $((v_i)_{i \in N}, \mathbf{X})$

Input / Output: (as in 3PA)

... (same as 3PA) ...

```
8   (Step 8) else if ...
    |   ...
8.5* (Step 8.5*) else if for some  $i \in N$ , there exists a path  $\Pi = (s, \dots, i)$  in  $G_r(\mathbf{X})$  starting at a source  $s$  of  $G_r(\mathbf{X})$ ,
    |   such that  $v_i(X_i) \leq \frac{1}{2}(4 - |X_i|) v_i(\{g, g'\})$  for some  $g \in \mathcal{P}(\mathbf{X})$  and some  $g' \in X_s$  then
    |   |   Let  $\Pi$  be such a path
    |   |    $\mathbf{X} \leftarrow \text{PATHRESOLUTION}^*(\mathbf{X}, G_r, \Pi)$ 
    |   |   // Compare to Step 8.5: we still require  $v_i(X_i) < v_i(\{g, g'\})$  when  $|X_i| = 2$ , but only
    |   |   |    $v_i(X_i) < \frac{3}{2} v_i(\{g, g'\})$  when  $|X_i| = 1$ .
    |   |
    |   ...
return  $\mathbf{X}$ 
```

Lemma 5.2. *Let \mathbf{X} be a seed allocation. Then, in polynomial time, $3\text{PA}^*((v_i)_{i \in N}, \mathbf{X})$ outputs a partial allocation \mathbf{X}^1 of size at most 2 that satisfies [Properties \(a\) to \(e\)](#). Furthermore, if \mathbf{X}^1 is not a complete allocation, then $G_e(\mathbf{X}^1)$ has at least one source, and every source s in $G_e(\mathbf{X}^1)$ has $|X_s^1| = 2$.*

We have all the components needed to state the complete algorithm for 3-value instances, called `THREEVALUESALLOCATE` (Algorithm 8), except for the significant modification of 3PA that handles [Case \(c\)](#), called 3PA^{++} . We state the algorithm here and we defer the description of 3PA^{++} to [Section 5.1](#) which, as already mentioned, is dedicated to proving [Theorem 5.1](#) for [Case \(c\)](#). It is worth noting that, given the three variants, 3PA, 3PA^* , and 3PA^{++} , we can directly produce a partial allocation without any critical goods in any of the three cases. That is, for 3-value instances, we do not rely on an analog of `UNCONTESTEDCRITICAL` or on other subroutines for dealing with critical goods, but only run `ENVYCYCLEELIMINATION` on the output of 3PA, 3PA^* , or 3PA^{++} .

ALGORITHM 8: THREEVALUESALLOCATE $(N, (v_i)_{i \in N}, M)$

Input: An 3-value instance with values $a = 1 > b > c \geq 0$.**Output:** A $2/3$ -EFX allocation \mathbf{X} .Let \mathbf{X}^0 be an arbitrary partial allocation where each bundle has cardinality 1

```
if  $b \leq \frac{1}{2}$  then // Case (a)
  |  $\mathbf{X}^1 \leftarrow 3\text{PA}((v_i)_{i \in N}, \mathbf{X}^0)$ 
else if  $b > \frac{1}{2}$  and  $b + c \geq \frac{2}{3}$  then // Case (b)
  |  $\mathbf{X}^1 \leftarrow 3\text{PA}^*((v_i)_{i \in N}, \mathbf{X}^0)$ 
else // Case (c)
  | if  $c = 0$  then // the  $c = 0$  case is reduced to the  $c > 0$  case below
  | | Update  $(v_i)_{i \in N}$  so that  $c \leftarrow \varepsilon$  for sufficiently small  $\varepsilon > 0$ 
  | | // roughly,  $\varepsilon$  will be as small as the smallest possible (weighted) difference between two
  | | | bundles under the original  $(v_i)_{i \in N}$  scaled down by  $3m$ ; see Lemma 5.31
  | |  $\mathbf{X}^1 \leftarrow 3\text{PA}^{++}((v_i)_{i \in N}, \mathbf{X}^0)$  // handles Case \(c\) for  $c > 0$ 
 $\mathbf{X} \leftarrow \text{ENVYCYCLEELIMINATION}(\mathbf{X}^1, G(\mathbf{X}^1))$  // we just complete the allocation (no critical goods)
return  $\mathbf{X}$ 
```

Proof of Cases (a) and (b) of [Theorem 5.1](#). Let \mathbf{X}^1 be the partial allocation outputted by 3PA or 3PA^* when initiated with an allocation \mathbf{X}^0 of size at least 1 and at most 2 which satisfies [Properties \(a\)](#) and [\(b\)](#) as shown in `THREEVALUESALLOCATE` (Algorithm 8). By [Lemma 3.1](#), \mathbf{X}^1 satisfies [Properties \(a\)](#) and [\(b\)](#). We will argue

that, in both cases, are no critical goods induced by X^1 . Therefore, running ENVYCYCLEELIMINATION on X^1 results in a $2/3$ -EFX allocation, by Lemma 4.2. The polynomial running time directly follows from the running time of 3PA, 3PA*, and ENVYCYCLEELIMINATION (Lemmata 3.1, 4.1 and 5.2).

A simple, but very useful, observation that we will be using in both cases below is that if an agent i has a critical good g_i , by Properties (d) and (e) of X^1 , it holds that $|X_i^1| = 1$ and $1/2 < v_i(g_i) \leq 2/3$. This implies that $v_i(X_i^1) = 1$ or $v_i(X_i^1) = b$; if $v_i(X_i^1) = c$, the agent cannot have a critical good.

Case (a): $b \leq \frac{1}{2}$ Suppose, towards a contradiction, that there exists some agent $i \in N$ that has a critical good $g \in \mathcal{P}(X^1)$. Consider first the case when $v_i(X_i^1) = 1$. In this case, there are no candidate critical goods g such that $1/2 < v_i(g) \leq 2/3$ violating Property (e). Next, consider the case $v_j(X_j^1) = b$. By Property (e), we have that $v_i(g) = c$, as otherwise we would have $v_i(g) > \frac{2}{3}v_i(X_i^1)$. Now consider a source s of the enhanced envy graph $G_e(X^1)$; such a source exists by Lemma 3.4 (since here we assumed $\mathcal{P}(X^1) \neq \emptyset$) and recall that $|X_s| = 2$. By virtue of s being a source, we have $v_i(X_i^1) \geq v_i(X_s^1)$. This is only possible if $v_i(X_s^1) = 2c$ or if $v_i(X_s^1) = b + c$ and $c = 0$. In the latter case g is not critical for agent i . In the former case, the inequality $v_i(X_i^1) \geq v_i(X_s^1)$ implies that $b \geq 2c$, which means that g is not critical for agent i . Both cases, contradict the choice of g .

Case (b): $b > \frac{1}{2}$ and $b + c \geq \frac{2}{3}$ Again, suppose, towards a contradiction, that there exists some agent $i \in N$ that has a critical good $g \in \mathcal{P}(X^1)$. Because of Step 9, we know that $G_e(X^1)$ and, thus, $G_r(X^1)$ are acyclic. Let $\Pi = (s, \dots, i)$ be a maximal path in $G_r(X^1)$ leading to agent i . Due to maximality, the initial vertex s of Π must be a source and, because Step 6 did not run in the last iteration of 3PA*, s must be distinct from i herself. Let $g_s \in X_s$. Obviously $v_i(g_s) \geq c$. We will argue that $v_i(\{g_s, g\}) \geq \frac{2}{3}v_i(X_i)$. By the observation made before Case (a), we have that $v_i(X_i^1) = 1$ and $v_i(g) \in \{b, c\}$, or $v_i(X_i^1) = b$ and $v_i(g) = c$. If $v_i(g) = b$, then $v_i(\{g_s, g\}) \geq b + c \geq \frac{2}{3} \geq \frac{2}{3}v_i(X_i)$, since $v_i(X_i) \leq 1$. If $v_i(g) = c$, we have $c > \frac{1}{2}v_i(X_i)$ and therefore $v_i(\{g_s, g\}) \geq 2c > v_i(X_s)$. In any case, $v_i(\{g_s, g\}) \geq \frac{2}{3}v_i(X_i)$, directly contradicting the fact that Step 8.5* did not run in the last iteration of 3PA*. \square

5.1 Instances with $b > \frac{1}{2}$ and $b + c < \frac{2}{3}$

As we mentioned earlier, our general technique needs to be significantly refined and expanded to deal with Case (c). To this end, we develop a rather complicated refinement of the 3PA+ algorithm (see Algorithm 9 below). Before going into the technical details, it is worth discussing the additional challenges and the high-level idea behind designing the 3PA++ algorithm.

As we showed in Example 1, even when considering 3-value instances, there is no way to allocate all critical goods without resulting in allocated bundles of cardinality larger than 2. This brings up two main challenges that we need to address: (i) Agents receiving a single good may not be EFX towards other agents if we just add a good to the bundle of a source of the enhanced envy graph. For example, suppose that agent i has a single good for which she has value 1 and a source s has two goods for which i has value $b + c < \frac{2}{3}$. Then i will not be EFX towards s if we give an extra good to s for which i has value b ; this was not the case when the bundles are restricted to having cardinality at most 2. (ii) Agents with more than 2 goods may have critical goods. For example, an agent with 3 goods for which she has value b may have a critical good for which she has value 1.

To overcome the first challenge, we modify the enhanced envy graph so that a red edge does not represent near-envy of at least $2/3$ from an agent i with a critical good to a source s of the reduced envy graph, but rather the fact that i has value b for one good in the possession of s . This modification resolves the situation in (i) above, but now agent i may see her value drop by more than $2/3$ (yet no more than $1/2$) if she receives the set of s . This is resolved with the addition of a number of sophisticated steps in the 3PA++ algorithm that prevent the formation of bundles with many goods that i values by more than $2/3$ even

after removing a single good.

Regarding the second challenge, we allow agents with many goods who still have a critical good to exchange *all but one* of their goods with their critical good. This may reduce their value and result in these agents not being 2/3-EFX towards agents that hold specific types of bundles. To avoid this violation of 2/3-EFX, we introduce more elaborate versions of the enhanced envy graph (see [Definitions 5.4](#) and [5.5](#)) that prevent the formation of such bundles through carefully defined additional edges.

For everything that follows up until [Lemma 5.31](#), we will assume that $c > 0$. When $c = 0$, [Lemma 5.31](#) shows how to reduce the problem back to the $c > 0$ case in polynomial time; this is also reflected to the `THREEVALUESALLOCATE` algorithm. Hence, the $c > 0$ assumption is without loss of generality.

For showing the [Case \(c\)](#) of [Theorem 5.1](#), we have to go through the properties of the $3PA^{++}$ algorithm like we did for [Cases \(a\)](#) and [\(b\)](#) with $3PA$ and $3PA^*$. That is, we would like to show that the partial allocation X^1 outputted by $3PA^{++}$ when initiated with X^0 in `THREEVALUESALLOCATE` ([Algorithm 8](#)) satisfies [Properties \(a\)](#) and [\(b\)](#) and is computed in polynomial time. These two properties of $3PA^{++}$ are established in [Lemmata 5.9](#) and [5.10](#).

We begin with some definitions which extend those that we presented in [Section 2](#).

5.1.1 Definitions and Modifications

We first provide refined versions of the various envy-graphs that we will use.

Definition 5.3 (Reduced+ Envy Graph G_r^+). Given a partial allocation X , the *reduced+ envy graph* $G_r^+(X)$ of X is defined as a supergraph of $G_r(X)$ (recall [Definition 2.9](#)) with the addition of any edge (i, j) such that $|X_i| = |X_j| = 1$ and $v_i(X_i) = v_i(X_j) = 1$. We color those extra edges *grey* and note that they represent zero envy.

Definition 5.4 (Enhanced+ Envy Graph G_e^+). Given a partial allocation X and its reduced+ envy graph $G_r^+(X)$, we construct the *enhanced+ envy graph* $G_e^+(X)$ as follows. In $G_r^+(X)$ we add any edge (i, j) such that j is a source of $G_r^+(X)$ and the following three properties hold: (a) $|X_i| = 1$, (b) there exists $g \in X_j$ such that $v_i(g) = b$, and (c) there exists $g' \in \mathcal{P}(X)$ such that $v_i(g') = b$.

Definition 5.5 (Doubly Enhanced Graph G_{de}). Given a partial allocation X and its enhanced+ envy graph $G_e^+(X)$, we construct the *doubly enhanced graph* $G_{de}(X)$ as follows. In $G_e^+(X)$ we add any edge (i, j) such that j is a source of $G_e^+(X)$ and the following three properties hold:

- (a) $1 + b \leq v_i(X_i) < 2$, i.e., from the perspective of i , X_i consists of either three goods of value b or one good of value 1 and one good of value b , and the rest of the goods have value c ,
- (b) from the perspective of i , X_j consists of three goods of value b and the rest of the goods have value c ,
- (c) there exists $g' \in \mathcal{P}(X)$ such that $v_i(g') = b$.

In $G_{de}(X)$ we allow *self loops* (i, j) , where $j = i$, if the above properties hold.

We remark that in the graphs described above we might have paths or cycles that consist solely of grey edges. Since there is no envy between any of the agents involved in these, we will refer to those as *unjaundiced* paths or cycles, respectively.

Definition 5.6 (Unjaundiced Path or Cycle). Consider any path Π (resp. cycle C) in $G_r^+(X)$, $G_e^+(X)$, or $G_{de}(X)$. We say that Π (resp. C) is *unjaundiced* if it consists entirely of grey edges; otherwise we say it is *jaundiced*.

Next we introduce a notion that captures the fact that there might be groups of agents who each have a good of value a (from their perspective) but are not envied (in the sense captured by G_r^+) by anyone outside

of their group.

Definition 5.7 (Secluded Set). Given a partial allocation \mathbf{X} , let S be a set of agents such that $v_i(X_i) = 1$, for all $i \in S$, and for any $j \notin S$, there is not an edge (j, i) in $G_r^+(\mathbf{X})$. We will refer to S as a *secluded set*.

Lemma 5.8. *Given a partial allocation \mathbf{X} , there is a unique secluded set $R(\mathbf{X})$ of maximum cardinality and can be found in polynomial time.*

Proof. By its definition, a secluded set cannot contain any agent j such that $v_j(X_j) \neq 1$ nor any agent reachable from j in $G_r^+(\mathbf{X})$. We argue that all remaining agents form a secluded set and, thus, this is the unique secluded set of maximum cardinality. Let $R(\mathbf{X}) = \{i \in N : \text{there is no path } \Pi = (j, \dots, i) \text{ in } G_r^+(\mathbf{X}), \text{ such that } v_j(X_j) \neq 1\}$. Clearly, $R(\mathbf{X})$ can be constructed in polynomial time. Also, for any $i \in R(\mathbf{X})$ we have $v_i(X_i) = 1$, by the definition of $R(\mathbf{X})$, and any $j \notin R(\mathbf{X})$ could not be in any secluded set as argued above. What remains to be shown is that there is no edge (j, i) with $i \in R(\mathbf{X})$ and $j \notin R(\mathbf{X})$. Suppose, towards a contradiction that (j, i) was such an edge. This means that j is reachable by some j' such that $v_{j'}(X_{j'}) \neq 1$. But then, so is i and thus $i \notin R(\mathbf{X})$, contradicting the choice of (j, i) . \square

For the rest of the section, we will use $R(\mathbf{X})$, as in the statement of [Lemma 5.8](#), to denote the unique maximal secluded set induced by \mathbf{X} .

Finally, let k_{\max} be the unique integer such that

$$b + (k_{\max} - 1)c \geq \frac{2}{3} \text{ and } b + (k_{\max} - 2)c < \frac{2}{3}.$$

This will be (an upper bound on) the *maximum cardinality* of any allocated bundle as long as there are agents that have critical goods (see [Lemma 5.12](#)). Since $b + c < \frac{2}{3}$, it must be that $k_{\max} \geq 3$.

5.1.2 Potential Function

To show the termination of our algorithm, we will need to use a potential function. For any partial allocation \mathbf{X} , we define the following sets of agents:

$$N_{[2,\infty)}(\mathbf{X}), N_{[1+b,2)}(\mathbf{X}), N_{(1,1+b)}(\mathbf{X}), N_{[2/3,1)}(\mathbf{X}), N_{1,(0,2/3)}(\mathbf{X}),$$

where

- $N_{[2,\infty)}(\mathbf{X}) = \{i \in N : v_i(X_i) \in [2, \infty)\}$, i.e., agents whose value in \mathbf{X} lies in $[2, \infty)$.
- $N_{[1+b,2)}(\mathbf{X}) = \{i \in N : v_i(X_i) \in [1 + b, 2)\}$, i.e., agents whose value in \mathbf{X} lies in $[1 + b, 2)$.
- $N_{(1,1+b)}(\mathbf{X}) = \{i \in N : v_i(X_i) \in (1, 1 + b)\}$, i.e., agents whose value in \mathbf{X} lies in $(1, 1 + b)$.
- $N_{[2/3,1)}(\mathbf{X}) = \{i \in N : v_i(X_i) \in [2/3, 1)\}$, i.e., agents whose value in \mathbf{X} lies in $[2/3, 1)$.
- $N_{1,(0,2/3)}(\mathbf{X}) = \{i \in N : v_i(X_i) = 1 \text{ or } v_i(X_i) \in [0, 2/3)\}$ i.e., agents whose value in \mathbf{X} is either 1 or lies in $(0, 2/3)$.

We define as the potential function the tuple

$$\mathcal{F}(\mathbf{X}) = (|N_{[2,\infty)}(\mathbf{X})|, |N_{[1+b,2)}(\mathbf{X})|, |N_{(1,1+b)}(\mathbf{X})|, |N_{[2/3,1)}(\mathbf{X})|, SW_{(0,1+b)}(\mathbf{X})),$$

where $SW_{(0,1+b)}(\mathbf{X}) = \sum_{i \in N: v_i(X_i) < 1+b} v_i(X_i)$ is the social welfare of only the agents who value their bundles less than $1 + b$. We will show that in each step of our algorithm, the potential function would only lexicographically increase, with the exception of finitely many steps during which it may remain constant.

5.1.3 Additional Properties

Besides [Properties \(a\) and \(b\)](#), here we need the following two properties, instead of [Properties \(c\) to \(e\)](#).

Further Desired properties of a partial allocation \mathbf{X} :

(F.1) For any agent $i \in N_{1,(0,2/3)}(\mathbf{X})$ and any good $g \in \mathcal{P}(\mathbf{X})$, it holds that $v_i(g) < 1$.

(F.2) For any agent $i \in N_{1,(0,2/3)}(\mathbf{X})$ and any agent $j \neq i$, such that $|X_j| \geq 2$, it holds that $v_i(g) < 1$ for any $g \in X_j$.

5.1.4 A Refined Version of the Property-Preserving Partial Allocation Algorithm

Here we present the refinement of the 3PA algorithm; see [Algorithm 9](#). In contrast to the results of [Section 4](#), 3PA⁺⁺ will produce the desired allocation \mathbf{X}^2 *directly*, i.e., \mathbf{X}^2 will be the allocation \mathbf{X}^1 similarly to [Cases \(a\) and \(b\)](#). In other words, the processes of obtaining a property-preserving partial allocation and of allocating the critical goods left in the pool will be intertwined. Still, the logic of the algorithm is similar to 3PA, and therefore we refer to this version as a refinement.

In a number of occasions (in particular, in [Steps 5, 9, and 10](#)) the algorithm needs to allocate a few goods in a round-robin fashion. As a shortcut, we introduce [Subroutine 6](#) below. SINGLEROUNDROBIN takes a partial allocation and a set of agents as input, and augments the allocation by considering the specified agents one after the other, giving to each of them her favorite unallocated good.

SUBROUTINE 6: SINGLEROUNDROBIN(\mathbf{X}, S)

Input: A partial allocation \mathbf{X} and a set of agents S .

Output: An updated partial allocation \mathbf{X} , in which each $i \in S$ adds her favourite available good from the pool to her bundle, in a round-robin fashion.

// The agents in S pick their favourite good from the pool one by one, until each one gets one good, or the pool empties.

while $S \neq \emptyset$ **and** $\mathcal{P}(\mathbf{X}) \neq \emptyset$ **do**

```

    Select  $i \in S$ 
    Let  $g^* \in \arg \max \mathcal{P}(\mathbf{X})$ 
     $X_i \leftarrow X_i \cup g^*$ 
     $\mathcal{P}(\mathbf{X}) \leftarrow \mathcal{P}(\mathbf{X}) \setminus \{g^*\}$ 
     $S \leftarrow S \setminus \{i\}$ 

```

return \mathbf{X}

[Sections 5.1.5 and 5.1.6](#) will be devoted to proving the following two lemmata. By [Lemma 4.2](#), [Lemma 5.9](#) implies the existence of a complete 2/3-EFX allocation, and [Lemma 5.10](#) establishes that this allocation can be obtained in polynomial time. This implies [Case \(c\)](#) of [Theorem 5.1](#), completing the theorem's proof.

Lemma 5.9. *Let \mathbf{X}^1 be the partial allocation outputted by 3PA⁺⁺. Then \mathbf{X}^1 is 2/3-EFX, with no critical goods for any agent.*

Lemma 5.10. *The 3PA⁺⁺ algorithm terminates in polynomial time.*

5.1.5 The Proof of [Lemma 5.9](#)

To prove [Lemma 5.9](#), we develop a sequence of technical lemmata and claims. We begin with some very simple observations, but as we progress our statements (and proofs) will become increasingly more complex.

ALGORITHM 9: PROPERTY-PRESERVING PARTIAL ALLOCATION⁺⁺ (3PA⁺⁺) $((v_i)_{i \in N}, \mathbf{X})$

Input: The values $v_i(g)$ for every $i \in N$ and every $g \in M$, and a partial allocation \mathbf{X} in which $|X_i| = 1$ for all $i \in N$.

Output: A Property-Preserving Partial Allocation, a partial allocation \mathbf{X}^1 satisfying Properties (a), (b), (F.1), and (F.2)

while $\mathcal{P}(\mathbf{X}) \neq \emptyset$ **do**

```
1 | (Step 1) if there is a jaundiced cycle  $C$  in  $G_r^+(\mathbf{X})$  then
   |    $\mathbf{X} \leftarrow \text{CYCLERESOLUTION}(\mathbf{X}, G_r^+)$ 
2 | (Step 2) else if there is  $i \in N$  with  $|X_i| = 1$  and a good  $g \in \mathcal{P}(\mathbf{X})$  such that  $v_i(g) > v_i(X_i)$  then
   |    $X_i \leftarrow \{g\}$  and  $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \cup \{X_i\}) \setminus \{g\}$ 
3 | (Step 3) else if there is  $i \in N$  with  $|X_i| = 2$  and a good  $g \in \mathcal{P}(\mathbf{X})$  such that  $v_i(g) > \frac{3}{2}v_i(X_i)$  then
   |    $X_i \leftarrow \{g\}$  and  $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \cup \{X_i\}) \setminus \{g\}$ 
4 | (Step 4) else if there is a jaundiced path  $\Pi = (i_1, \dots, i_\ell)$  in  $G_r^+(\mathbf{X})$  and a good  $g \in \mathcal{P}(\mathbf{X})$  so that  $v_{i_\ell}(X_{i_\ell}) = v_{i_\ell}(g)$  then
   |    $(X_j)_{j \in \{i_1, \dots, i_{\ell-1}\}} = \text{PATHRESOLUTION}(\mathbf{X}, G_e^+, \Pi)$ 
   |    $X_{i_\ell} \leftarrow \{g\}$  and  $\mathcal{P}(\mathbf{X}) = \mathcal{P}(\mathbf{X}) \cup X_{i_\ell}$ 
5 | (Step 5) else if  $R(\mathbf{X}) \neq \emptyset$  then // there is a nonempty secluded set
   |    $\mathbf{X} \leftarrow \text{SINGLEROUNDRROBIN}(\mathbf{X}, R(\mathbf{X}))$ 
6 | (Step 6) else if there is  $i \in N$  with  $|X_i| = 1$  and two goods  $g_1, g_2 \in \mathcal{P}(\mathbf{X})$  such that  $v_i(\{g_1, g_2\}) > v_i(X_i)$  then
   |    $X_i \leftarrow \{g_1, g_2\}$  and  $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \cup \{X_i\}) \setminus \{g_1, g_2\}$ 
   |   else if  $\mathcal{P}(\mathbf{X}) = \{g\}$  and some  $i \in N$ , with  $|X_i| = 1$  and  $v_i(X_i) = v_i(g)$ , is a source of  $G_r^+(\mathbf{X})$  then
   |      $X_i \leftarrow X_i \cup \{g\}$ 
7 | (Step 7) else if there is  $i \in N$  with  $|X_i| \geq 2$  and a good  $g^* \in \mathcal{P}(\mathbf{X})$  such that  $v_i(g^*) > v_i(X_i \setminus \{g_1\})$ , where
   |    $g_1 \in \arg \max_{g \in X_i} v_i(g)$  then
   |      $X_i \leftarrow \{g_1, g^*\}$  and  $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \cup X_i) \setminus \{g_1\}$ 
8 | (Step 8) else if there exists  $i \in N$  and goods  $g_1, g_2, g_3 \in X_i$  such that  $v_i(g_j) = b$ , for  $j \in \{1, 2, 3\}$ , and  $v_i(g) = c$ , for any
   |   other good  $g \in X_i \setminus \{g_1, g_2, g_3\}$  (if any), and there exists a good  $g^* \in \mathcal{P}(\mathbf{X})$  such that  $v_i(g^*) = 1$  then
   |      $X_i \leftarrow \{g_1, g^*\}$  and  $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \setminus \{g^*\}) \cup (X_i \setminus \{g_1\})$ 
9 | (Step 9) else if in the enhanced+ envy graph  $G_e^+(\mathbf{X})$  there is a jaundiced cycle  $C$  then
   |   Let  $T(C) = \{i \in N : s \text{ is a source of } G_r^+(\mathbf{X}) \text{ and } (i, s) \in C\}$  //  $T(C) \neq \emptyset$ ; implied by Lemma 5.15
   |   Let  $i^* \in T(C)$  and let  $s_{i^*}$  be the source of  $G_r^+(\mathbf{X})$  such that there is an edge  $(i^*, s_{i^*})$  in  $G_r^+(\mathbf{X})$ 
   |    $\mathbf{X} = \text{CYCLERESOLUTION}(\mathbf{X}, G_e^+, C)$ 
   |   Let  $g \in X_{i^*}$  such that  $v_{i^*}(g) = b$  // exists by the definition of  $G_r^+$ , since  $X_{i^*}$  was  $s_{i^*}$ 's bundle right before
   |   Let  $g^* \in \mathcal{P}(\mathbf{X})$  such that  $v_i(g^*) = b$  // exists by the definition of  $G_e^+$ 
   |    $X_{i^*} \leftarrow \{g, g^*\}$  and  $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \setminus \{g^*\}) \cup (X_{i^*} \setminus \{g\})$ 
   |    $\mathbf{X} = \text{SINGLEROUNDRROBIN}(\mathbf{X}, T(C) \setminus \{i^*\})$ 
10 | (Step 10) else if  $k_{\max} \geq 4$  and in the double enhanced graph  $G_{de}(\mathbf{X})$  there is a jaundiced cycle or self-loop  $C$  then
   |   Let  $i^* \in N$  be such that  $(i^*, s_{i^*})$  is an edge of  $C$  and  $s_{i^*}$  is a source of  $G_e^+(\mathbf{X})$ 
   |   // Note that such an  $i^*$  always exists since Step 9 was not executed, and hence any cycle in  $G_e^+$  is unjaundiced
   |   Let  $T(C) = \{i \in N : s \text{ is a source of } G_r^+(\mathbf{X}) \text{ and } (i, s) \in C \cap G_e^+(\mathbf{X})\}$ 
   |    $\mathbf{X} = \text{CYCLERESOLUTION}(\mathbf{X}, G_{de}, C)$ 
   |   Let  $\{g_1, g_2, g_3\} \in X_{i^*}$  be such that  $v_{i^*}(g_j) = b$ , for  $j \in \{1, 2, 3\}$ 
   |   //  $\{g_1, g_2, g_3\}$  exist by the definition of  $G_{de}$ , since  $X_{i^*}$  was  $s_{i^*}$ 's bundle right before
   |   Let  $g^* \in \mathcal{P}(\mathbf{X})$  such that  $v_i(g^*) = b$  // exists by the definition of  $G_{de}$ 
   |    $X_{i^*} \leftarrow \{g_1, g_2, g_3, g^*\}$  and  $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \setminus \{g^*\}) \cup (X_{i^*} \setminus \{g_1, g_2, g_3\})$ 
   |    $\mathbf{X} = \text{SINGLEROUNDRROBIN}(\mathbf{X}, S)$ , where  $S \leftarrow T(C) \cap \{i \in N : |X_i| = 1\}$ 
11 | (Step 11) else if there is  $i \in N$  with a critical good  $g$  and a source  $s$  in  $G_{de}(\mathbf{X})$  with  $|X_s| < k_{\max}$  then
   |    $X_s \leftarrow X_s \cup \{g\}$ 
12 | (Step 12) else if there is an agent  $i$  with a critical good  $g$ , and for every source  $s$  in  $G_{de}(\mathbf{X})$ , it holds that  $|X_s| = k_{\max}$  then
   |   Let  $s_i$  be a source of  $G_{de}(\mathbf{X})$  such that there exists a path  $\Pi$  from  $s_i$  to  $i$  in  $G_{de}(\mathbf{X})$  and let  $g' \in X_{s_i}$ 
   |    $X_i \leftarrow (X_{s_i} \cup \{g\}) \setminus \{g'\}$  and  $\mathcal{P}(\mathbf{X}) \leftarrow (\mathcal{P}(\mathbf{X}) \cup \{g'\}) \setminus \{g\}$ 
   |    $(X_j)_{j \in N, \exists (j, \ell) \in \Pi} = \text{PATHRESOLUTION}(\mathbf{X}, G_{de}, \Pi)$ 
13 | (Step 13) else
   |   break
```

return \mathbf{X}

Lemma 5.11. *It holds that $c < \frac{1}{6}$.*

Proof. This is easy to see since $b + c < \frac{2}{3}$ and $b > \frac{1}{2}$, and so $c < \frac{2}{3} - b < \frac{2}{3} - \frac{1}{2} = \frac{1}{6}$. \square

Lemma 5.12. *At the end of any iteration of the while loop of the 3PA⁺⁺ algorithm, the cardinality of any allocated bundle of goods is at most k_{\max} .*

Proof. Recall that since $b + c < \frac{2}{3}$ and by the definition of k_{\max} , we have that $k_{\max} \geq 3$. The only steps where the 3PA⁺⁺ algorithm may allocate bundles of cardinality more than 2 are Steps 10, 11 and 12, where Step 10 only runs when $k_{\max} \geq 4$. In any case, after each step, clearly the cardinality of the allocated bundles does not exceed k_{\max} . \square

Lemma 5.13. *Consider any agent $i \in N$ and any set of goods X , with $|X| \leq k_{\max}$. If, from the perspective of agent i , X consists of*

1. *exactly one good of value b and possibly other goods of value c , then $v_i(X) < \frac{5}{6}$ and $v_i(X \setminus \{g\}) < \frac{2}{3}$, for any $g \in X$.*
2. *only goods of value c , then $v_i(X) < \frac{1}{2}$.*

Proof. For the first case, by the definition of k_{\max} , we have that $v_i(X) < \frac{2}{3} + c$, which implies $v_i(X \setminus \{g\}) < \frac{2}{3}$, for any $g \in X$. By Lemma 5.11 and the additivity of the values, we have $v_i(X) < \frac{2}{3} + \frac{1}{6} = \frac{5}{6}$. For the second case, we have that $v_i(X) \leq k_{\max} \cdot c$. By the definition of k_{\max} and Lemma 5.11, we have that $k_{\max} \cdot c < \frac{2}{3} - b + 2c < \frac{2}{3} - \frac{1}{2} + \frac{2}{6} = \frac{1}{2}$. \square

Lemma 5.14. *At the end of any iteration of the while loop of 3PA⁺⁺, for any agent $i \in N$ and any allocated bundle X , if $v_i(X) \in \{1, b, c\}$, then $|X| = 1$.*

Proof. We consider three cases, depending on $v_i(X)$.

Case 1: $v_i(X) = 1$. Assume by contradiction that $|X| > 1$. Note that X cannot contain any good g such that $v_i(g) = 1$ or any two goods g_1, g_2 such that $v_i(g_1) = v_i(g_2) = b$. This is because, since $c > 0$, in each case that would imply that $v_i(X) > 1$. This means that X contains at most one good g such that $v_i(g) = b$, and for any other good $g' \in X$, it holds that $v_i(g') = c$. By Lemma 5.13, it holds that $v_i(X) < \frac{5}{6} < 1$, a contradiction.

Case 2: $v_i(X) = b$. Assume by contradiction that $|X| > 1$. Note that X cannot contain any good g such that $v_i(g) = 1$ or $v_i(g) = b$, because in that case we would have $v_i(X) > b$ (again, since $c > 0$). This means that X contains only goods g such that $v_i(g) = c$. By Lemma 5.13, $v_i(X) < \frac{1}{2}$, a contradiction, since $b > \frac{1}{2}$.

Case 3: $v_i(X) = c$. In this case the statement of the lemma holds trivially by the fact that $c > 0$. \square

Lemma 5.15. *Let X be a partial allocation for which $G_r^+(X)$ only has unjaundiced cycles, and for which $R(X) = \emptyset$, i.e., every secluded set is empty (i.e., Steps 1 and 5 of the 3PA⁺⁺ algorithm do not run). Then, there exists at least one source s in the reduced+ envy graph $G_r^+(X)$.*

Proof. Assume by contradiction that there does not exist any source s in the reduced+ envy graph $G_r^+(X)$. From $G_r(X)$, we generate a new graph H as follows: as long as there is a cycle C in $G_r^+(X)$, we create a new node x , and for any $i \notin C$, we add an edge (i, x) if there exists an edge (i, j) for some $j \in C$, and an edge (x, i) if there exists an edge (j, i) for some $j \in C$. Then, we remove all the nodes of C and all the edges adjacent to them. At the end of this procedure H is acyclic.

Let s be a source of H . If s is also a node of $G_r^+(\mathbf{X})$ then it is a source of $G_r^+(\mathbf{X})$ and we obtain a contradiction. Therefore suppose that s is not a node of $G_r^+(\mathbf{X})$ and let $R'(\mathbf{X})$ be the set of nodes of $G_r^+(\mathbf{X})$ that s “replaced” in all rounds of the aforementioned procedure. This means that any $i \in R'(\mathbf{X})$ was part of some cycle of $G_r^+(\mathbf{X})$, since it was replaced. By the premise of the lemma statement, each cycle in $G_r(\mathbf{X})$ is unjaundiced. This implies that for every agent $i \in R'(\mathbf{X})$, it holds that $v_i(X_i) = 1$. Since s is a source of H , there is no edge (j, i) of $G_r^+(\mathbf{X})$ for any $i \in R'(\mathbf{X})$ and any $j \notin R'(\mathbf{X})$ by construction of H . This means that $R'(\mathbf{X})$ is a nonempty secluded set, and Step 5 of the 3PA⁺⁺ algorithm would have been executed, giving us a contradiction. \square

Before we continue with the statement of the remaining lemmata, we define the notion of an agent hierarchy, based on our potential function defined earlier in the section.

Definition 5.16 (Agent Hierarchy for a Partial Allocation). Given a partial allocation \mathbf{X} , we consider a *hierarchy* of the agents according to their value for their bundle as follows:

$$(L.1) \ N_{[2, \infty)}(\mathbf{X})$$

$$(L.2) \ N_{[1+b, 2)}(\mathbf{X})$$

$$(L.3) \ N_{(1, 1+b)}(\mathbf{X})$$

$$(L.4) \ N_{[2/3, 1)}(\mathbf{X})$$

$$(L.5) \ N_{1, (0, 2/3)}(\mathbf{X})$$

When comparing two partial allocations \mathbf{X} and \mathbf{X}' , we will say that an agent *falls in hierarchy from \mathbf{X} to \mathbf{X}'* , if in \mathbf{X} and \mathbf{X}' she is on Levels (L. i) and (L. i') respectively, with $i < i'$.

Lemma 5.17. *Let \mathbf{X} and \mathbf{X}' be any two partial allocations obtained in the course of the 3PA⁺⁺ algorithm, with \mathbf{X}' being obtained after \mathbf{X} . For any agent $i \in N$, the agent does not fall in hierarchy from \mathbf{X} to \mathbf{X}' .*

Proof. An agent can only fall in hierarchy if $v_i(X'_i) \neq v_i(X_i)$. We first consider the steps of the 3PA⁺⁺ algorithm during which $v_i(X'_i) < v_i(X_i)$, these are Steps 8, 9, 10 and 12. Consider Step 8 and consider agent i whose allocation changes in this step. Before the step, we had that $i \in N_{[1+b, 2)}(\mathbf{X})$ (i.e. the agent was at Level (L.2)). After the step, she receives a bundle X'_i for which $v_i(X'_i) = 1 + b$; this means that $i \in N_{[1+b, 2)}(\mathbf{X}')$. Next consider Step 9. The only agent(s) $i \in N$ for whom the value for their bundle possibly decreases are the ones with $|X_i| = 1$ and $v_i(X_i) = 1$. Those agents belong to the set of Level (L.5), i.e., $i \in N_{1, (0, 2/3)}(\mathbf{X})$, so they cannot fall in hierarchy by definition. Step 12 is slightly more involved. Here the agents $j \in N$ for whom the value for their bundle possibly decreases are either the ones with $|X_j| = 1$ and $v_j(X_j) = 1$ like in Step 9 (including the main agent i of the step, by Lemma 5.26) who cannot fall in hierarchy by definition, or the agents who drop in value but stay in $N_{[1+b, 2)}(\mathbf{X}')$ because of edges which are unique to G_{de} . Finally consider Step 10. The set of agents for whom the value for their bundle possible decreases consists of agents like the ones considered in Step 9, who belong to Level (L.5) and cannot fall in hierarchy, as well as some agents in $N_{[1+b, 2)}(\mathbf{X})$, i.e., those with $v_i(X_i) \in [1 + b, 2)$. Each agent i among the latter receives a bundle X'_i such that $v_i(X_i) \geq 3b > 1 + b$, so $i \in N_{[1+b, 2)}(\mathbf{X}')$.

We now consider the remaining case, i.e., when $v_i(X'_i) > v_i(X_i)$, and agent i possibly falling in hierarchy from Level (L.4) to Level (L.5), i.e., $i \in N_{[2/3, 1)}(\mathbf{X})$ and $i \in N_{1, (0, 2/3)}(\mathbf{X}')$. For this to be possible, it must be the case that $\frac{2}{3} \leq v_i(X_i) < 1$ and $v_i(X'_i) = 1$. In turn, this can only happen if $|X_i| > 1$ and, by Lemma 5.14, $|X'_i| = 1$. However, during the execution of the the 3PA⁺⁺ algorithm, if an agent with $|X_i| \geq 2$ finds herself with a bundle X'_i such that $|X'_i| = 1$, her value must increase by *more than* $\frac{3}{2}$ (see Step 3 of the 3PA⁺⁺ algorithm and the definition of the reduced+ envy graph G_r^+ in Definition 5.3), leading to a contradiction. \square

Lemma 5.18. *Let \mathbf{X} be a partial allocation for which*

- (a) *all the cycles in $G_r^+(\mathbf{X})$ are unjaundiced,*
- (b) *all the paths in $G_r^+(\mathbf{X})$ ending at an agent i with $v_i(X_i) = v_i(g)$ for some $g \in \mathcal{P}(\mathbf{X})$ are unjaundiced,*
- (c) *all the secluded sets are empty ($R(\mathbf{X}) = \emptyset$),*

(i.e., Steps 1, 4 and 5 of the 3PA⁺⁺ algorithm do not run). Then, for any agent $i \in N$ such that either $v_i(X_i) = 1$ or i is not a source of the reduced+ envy graph $G_r^+(\mathbf{X})$, it holds that $v_i(X_i) \neq v_i(g)$ for any $g \in \mathcal{P}(\mathbf{X})$.

Proof. Assume by contradiction that there exists some agent $i \in N$ that is either not a source of $G_r^+(\mathbf{X})$ or for which $v_i(X_i) = 1$, and some good $g \in \mathcal{P}(\mathbf{X})$ such that $v_i(g) = v_i(X_i)$. By the statement of the lemma, we know that any path Π in $G_r^+(\mathbf{X})$ is unjaundiced. Let $R'(\mathbf{X}) = \{j \in N : j \text{ is on some path } \Pi \text{ to } i \text{ in } G_r^+(\mathbf{X})\}$, and add agent i to $R'(\mathbf{X})$ only if $v_i(X_i) = 1$. By definition, since every agent $j \in R'(\mathbf{X})$ lies on some unjaundiced path to agent i , we have $v_j(X_j) = 1$, by definition of $G_r^+(\mathbf{X})$. We remark that $R'(\mathbf{X}) \neq \emptyset$. Indeed, if there is at least one unjaundiced path ending at agent i , all the agents of that path would be included in $R'(\mathbf{X})$. If there are no such paths, by the second condition of the statement of the lemma, there are no paths ending at agent i in $G_r^+(\mathbf{X})$ in general. This implies that i is a source of $G_r^+(\mathbf{X})$; this would violate the assumption at the beginning of the proof, unless $v_i(X_i) = 1$. In this case however, $i \in R'(\mathbf{X})$ and hence $R'(\mathbf{X}) \neq \emptyset$. We will next argue that $R'(\mathbf{X})$ is a secluded set.

Let $j \notin R'(\mathbf{X})$; if such a j does not exist then $R'(\mathbf{X})$ is trivially a secluded set. Let $\ell \in R'(\mathbf{X})$; such an ℓ exists since $R'(\mathbf{X}) \neq \emptyset$. Assume first that $j \neq i$. We argue that there is no edge (j, ℓ) in the $G_r^+(\mathbf{X})$: indeed, if such an edge existed, there would be a path from j to i (via ℓ , since there is a path from j to ℓ), contradicting the fact that $j \notin R'(\mathbf{X})$. Since j and ℓ were chosen arbitrarily, this implies that $R'(\mathbf{X})$ is a secluded set. Now assume that $j = i$. Again we argue that there is no edge (i, ℓ) in the $G_r^+(\mathbf{X})$: indeed, if such an edge existed, there would be cycle C including i (through the edge (i, ℓ) and since there is a path from ℓ to i by definition of $R'(\mathbf{X})$). Since $i = j \notin R'(\mathbf{X})$ by assumption, we have that $v_i(X_i) \neq 1$. This implies that the edge (i, ℓ) is not grey, and C is jaundiced, contradicting the first condition of the lemma statement. The lemma follows. \square

Corollary 5.19. *Let \mathbf{X} be a partial allocation obtained in an iteration of the while loop of the 3PA⁺⁺ algorithm in which Steps 1-5 did not run. For any agent i with $v_i(X_i) = 1$, it holds that $v_i(g) < 1$ for any $g \in \mathcal{P}(\mathbf{X})$.*

Proof. The corollary follows immediately by Lemma 5.18. \square

Lemma 5.20. *Let \mathbf{X} be a partial allocation obtained in an iteration of the while loop of the 3PA⁺⁺ algorithm in which Steps 1-5 did not run. Then \mathbf{X} satisfies Property (F.1).*

Proof. For any agent $i \in N$ with $v_i(X_i) < \frac{2}{3}$ and any good $g \in \mathcal{P}(\mathbf{X})$, it must be the case that $v_i(g) < 1$, as otherwise one of Steps 2 or 3 of the 3PA⁺⁺ algorithm would have run. If $v_i(X_i) = 1$, by Corollary 5.19, it holds that $v_i(g) < 1$ for any good $g \in \mathcal{P}(\mathbf{X})$. \square

Lemma 5.21. *Let \mathbf{X} be a partial allocation at the end of any iteration of the while loop of the 3PA⁺⁺ algorithm such that $\mathcal{P}(\mathbf{X}) \neq \emptyset$. Then \mathbf{X} satisfies Property (F.2).*

Proof. We will prove the lemma by induction on the number of iterations of the while loop of the 3PA⁺⁺ algorithm. For the base case, Property (F.2) is trivially for the input allocation \mathbf{X} before the execution of the first loop, since $|X_i| = 1$ for all $i \in N$.

Suppose that Property (F.2) holds at the beginning of some iteration of the while loop and the allocation \mathbf{X} ; we will show that after the end of the iteration and the allocation \mathbf{X}' , regardless of which step ran, the

property still holds. Note that by [Lemma 5.17](#), the set $N_{1,(0,2/3)}(\mathbf{X})$ can only become smaller, so we will show that [Property \(F.2\)](#) will hold for the $N_{1,(0,2/3)}(\mathbf{X})$ set either as formed prior to the application of the current step or after.

If Step 1 is executed: All bundles remain unchanged, so [Property \(F.2\)](#) holds by the induction hypothesis.

If any of Steps 2-4 is executed: The only bundle X_i that is modified still consists of a single good, i.e., $|X_i| = |X'_i| = 1$, and [Property \(F.2\)](#) holds by the induction hypothesis.

If Step 5 is executed: The only agents whose bundles are modified are the agents in the secluded set $R(\mathbf{X})$. In particular, each agent $i \in R(\mathbf{X})$ will receive an extra good from the pool in X' , and hence $i \notin N_{1,(0,2/3)}(\mathbf{X}')$. Consider any agent $i \in R(\mathbf{X})$ and any agent $j \in N_{1,(0,2/3)}(\mathbf{X}) \setminus R(\mathbf{X})$. Let $g \in \mathcal{P}(\mathbf{X})$ be the good such that $g \in X'_i$. Since Step 2 or Step 3 did not run, this implies that $v_j(X_j) < 1$, then $v_j(g) < 1$. Moreover, by the definition of $R(\mathbf{X})$, we have that $v_j(X_i) \leq v_j(X_j) < 1$, and thus $v_j(g') < 1$ for any $g' \in X_j$. If $v_j(X_j) = 1$, by [Corollary 5.19](#), we have that $v_j(g) < 1$. Moreover, by the definition of $R(\mathbf{X})$, we have that $v_j(X_i) < v_j(X_j) = 1$ (otherwise there would be a grey edge (j, i)), and again we have $v_j(g') < 1$ for any $g' \in X_i$. This establishes that [Property \(F.2\)](#) holds for \mathbf{X}' .

If any of Steps 6 - 8 is executed: The only bundle that is modified from \mathbf{X} to \mathbf{X}' now consists only of goods from $\mathcal{P}(\mathbf{X})$, and possibly one good from a bundle with X $|X| \geq 1$ in \mathbf{X} ; By the induction hypothesis and by [Lemma 5.20](#), [Property \(F.2\)](#) holds for \mathbf{X}' .

If any of Steps 9 - 12 is executed: Consider any bundle X in \mathbf{X} that is modified to X' in \mathbf{X}' . X' consists of a subset of X together with one good $g \in \mathcal{P}(\mathbf{X})$. By [Lemma 5.20](#), for any agent $i \in N_{1,(0,2/3)}(\mathbf{X})$, $v_i(g) < 1$. Prior to the application of that step, □

Lemma 5.22. *Let X be a partial allocation at the end of any iteration of the while loop of the 3PA⁺⁺ algorithm, and let X be any allocated bundle with $|X| \geq 3$. For any agent $i \in N_{1,(0,2/3)}(\mathbf{X})$*

- let $g \in \max_{x \in X} v_i(x)$; then $v_i(g) \leq b$
- for any $g' \in X \setminus \{g\}$, it holds that $v_i(g') = c$.

Proof. By [Lemma 5.21](#), for any $g' \in X$, we have that $v_i(g') < 1$, and thus $v_i(g') \leq b$. Assume by contradiction that there exist distinct $g_1, g_2 \in X$ such that $v_i(g_1) = v_i(g_2) = b$.

Consider the first iteration of the while loop r after which $\{g_1, g_2\} \in \tilde{X}$ for some bundle \tilde{X} and none of them is removed from \tilde{X} afterwards until the allocation \mathbf{X} is reached. Let \mathbf{X}' and \mathbf{X}'' be the partial allocation after and prior, respectively, the execution of iteration r , and also let X' and X'' be the aforementioned set \tilde{X} , after and prior, respectively, the execution of iteration r . So $g_1, g_2 \in X'$.

If $|X'| = 2$, agent i would prefer X' over her own bundle in all iterations until \mathbf{X} is reached. This is because $i \in N_{1,(0,2/3)}(\mathbf{X})$ and by [Lemma 5.17](#), agent i 's value for her bundle is at most 1 in all those iterations, and by our assumption that $v_i(X') = 2b > 1$. The cardinality of a bundle can only increase from 2 to more goods in Steps 11 and 12, and only if it is allocated to a source of the doubly enhanced graph. The bundle X' can never be allocated to a source in all iterations until \mathbf{X} is reached, which is a contradiction to the fact that $|X| \geq 3$.

Suppose now that $|X'| \geq 3$. A bundle \tilde{X} is updated to another bundle with cardinality at least 3 only in Steps 10 - 12. In these steps, only a single good is added to \tilde{X} from the pool. Assume without loss of generality that $g_1 \in X''$ and $g_2 \in \mathcal{P}(X'')$, i.e., g_1 was already allocated to X'' , and g_2 was added to X'' from the pool during the execution of iteration r . This also means that $|X''| \geq 2$. Regardless of which of Steps 10 - 12 ran at iteration r , the bundle X'' had to be assigned to some source s of the enhanced+ envy

graph $G_e^+(X'')$. We will show that this cannot happen by considering all different cases for agent i , who, by [Lemma 5.17](#), is in $N_{1,(0,2/3)}(X'')$:

- $v_i(X_i'') \leq b$. In this case i would envy s in X'' , since X'' contains at least two goods, one of which has value b for i . So s cannot be a source in $G_e^+(X'')$.
- $b < v_i(X_i'') < 1$. By the second case of [Lemma 5.13](#), there exists a good $g' \in X_i''$, such that $v_i(g') = b$, and $v_i(X_i'' \setminus \{g'\}) < \frac{1}{2}$. Since $v_i(g_2) = b$, Step 7 would have ran, where agent i would swap $X_i'' \setminus \{g'\}$ with g_2 . So, the 3PA⁺⁺ algorithm would not execute any of Steps 10 - 12.
- $v_i(X_i'') = 1$. In this case g_2 is a critical good for agent i . Since $v_i(g_1) = b$ and i has a critical good, there should be an (i, s) in the enhanced+ envy graph $G_e^+(X'')$ and therefore s cannot be a source of $G_e^+(X'')$.

Overall, we ended up with a contradiction to our assumption that there exist $g_1, g_2 \in X$ such that $v_i(g_1) = v_i(g_2) = b$, and the lemma follows. \square

Lemma 5.23. *Let X be a partial allocation at the end of any iteration of the while loop of the 3PA⁺⁺ algorithm, and let X be any allocated bundle. For any agent $i \in N_{[1+b,2)}(X)$, it holds that $v_i(X \setminus \{g\}) < b + \frac{5}{3}$, for any $g \in X$.*

Proof. In the following two claims we show that

- there are no two goods $g_1, g_2 \in X$ such that $v_i(g_1) = v_i(g_2) = 1$, unless $|X| = 2$,
- if $|X| \geq 5$ there are no four goods $g_1, g_2, g_3, g_4 \in X$ such that $v_i(g_j) \geq b$, for $j \in \{1, 2, 3, 4\}$.

This means that for any $g \in X$, by [Lemma 5.13](#),

- if $|X| \leq 4$, it holds that $v_i(X \setminus \{g\}) \leq 1 + 2b < b + \frac{5}{3}$, and
- if $|X| \geq 5$, $v_i(X \setminus \{g\}) \leq 1 + 2b + (k_{\max} - 4)c < b + \frac{5}{3}$.

Claim 5.24. *If $|X| \geq 3$ there are no two goods $g_1, g_2 \in X$ such that $v_i(g_1) = v_i(g_2) = 1$.*

Proof of Claim 5.24. Suppose, towards a contradiction, that there exist $g_1, g_2 \in X$ such that $v_i(g_1) = v_i(g_2) = 1$. Consider the first iteration of the while loop r after which g_1 and g_2 were assigned together in the same set \tilde{X} and none of them is removed from \tilde{X} until the allocation X is reached. Let X' and X'' be the allocation after and prior, respectively, the execution of iteration r , and also let X' and X'' be that set \tilde{X} , again after and prior, respectively, the execution of iteration r , so $g_1, g_2 \in X'$.

If $|X'| = 2$, then $v_i(X') = 2$ and agent i would envy the set X' in all iterations until X is reached. This is because $i \in N_{[1+b,2)}(X)$ and by [Lemma 5.17](#), i values her bundle by less than 2 in all those iterations. The cardinality of a set may only increase from $|\tilde{X}| = 2$ to $|\tilde{X}| > 2$ in Steps 11 and 12, and only if it was assigned to a source of the doubly enhanced graph. X' can never belong to a source in all iterations until X is reached, which is a contradiction to the fact that $|X| \geq 3$.

Suppose now that $|X'| \geq 3$. A set \tilde{X} is updated to another set with cardinality at least 3, only in Steps 10 - 12. In all those steps only one good is added to \tilde{X} from the pool. Assume w.l.o.g. that $g_1 \in X''$ and $g_2 \in \mathcal{P}(X'')$. We will show that another step should have been executed instead of Steps 10 - 12, since g_2 was in the pool and $v_i(g_2) = 1$.

If $i \in N_{1,(0,2/3)}$, by [Lemma 5.20](#), one of Steps 2 - 5 of the 3PA⁺⁺ algorithm would have run. Consider now the case where $i \in N_{(1,1+b)}(X'') \cup N_{[2/3,1)}(X'')$. In that case $|X_i''| \geq 2$ and $2/3 \leq v_i(X_i'') < 1 + b$. By the second case of [Lemma 5.13](#), there exists $g' \in X_i''$ such that $v_i(g') \geq b$, in which case Step 7 would have been run, where agent i would swap $X_i'' \setminus \{g'\}$ with g_2 . Suppose now that $i \in N_{[1+b,2)}(X'')$. If there exists $g' \in X_i''$ such that $v_i(g') \geq 1$, Step 7 would have run as above. If no such g' exists, it must be the case that

there are three goods in X_i'' that i values a b , in which case Step 8 would have been executed. Note that by Lemma 5.17, $i \notin N_{[2,\infty)}(\mathbf{X}'')$.

Overall, we ended up with a contradiction and the claim follows. \square

Claim 5.25. *If $|X| \geq 5$, there are no four goods $g_1, g_2, g_3, g_4 \in X$ such that $v_i(g_j) \geq b$, for $j \in \{1, 2, 3, 4\}$.*

Proof of Claim 5.25. Suppose, towards a contradiction, that there exist $g_1, g_2, g_3, g_4 \in X$ each of which is valued at least b by agent i . Consider the first iteration r of the while loop of the 3PA⁺⁺ algorithm, after which g_1, g_2, g_3, g_4 were part of the same bundle \tilde{X} and none of them is removed from \tilde{X} afterwards until the allocation \mathbf{X} is reached. Let \mathbf{X}' and \mathbf{X}'' be the allocation after and prior, respectively, the execution of iteration r , and also let X' and X'' be that bundle, again after and prior, respectively, the execution of iteration r , so $g_1, g_2, g_3, g_4 \in X'$.

A bundle \tilde{X} is updated to another bundle with cardinality at least 4 only in Steps 10, 11 and 12. In all those steps only one good is added to \tilde{X} from the pool. Assume w.l.o.g. that $g_1, g_2, g_3 \in X''$ and $g_4 \in X_p''$. If Step 10 is executed, then $X' = \{g_1, g_2, g_3, g_4\}$. Then, the cardinality can only increase to at least 5 in Step 11, where this bundle should be assigned to a source of the double enhance graph, but i would envy that bundle and therefore it can never be assigned to a source vertex. If one of Steps 11 and 12 was executed at iteration r , then X'' had to be assigned to some source s of the doubly enhanced graph $G_{\text{de}}(\mathbf{X}'')$. If $v_i(X_i'') < 1 + b$, then i would envy s , since $v_i(X'') \geq 3b > 1 + b$, and s would not be a source in $G_{\text{de}}(\mathbf{X}'')$.

So, by Lemma 5.17, it can only be the case that $i \in N_{[1+b,2)}(\mathbf{X}'')$, and recall that $g_4 \in \mathcal{P}(\mathbf{X}'')$ with $v_i(g_4) \geq b$. If $v_i(g_4) = 1$, either Step 7 should be executed for i , if i values one good in her bundle at 1, or Step 8 should be executed for i , because the only other case for $i \in N_{[1+b,2)}(\mathbf{X}'')$ is that she values three goods in her bundle at b (see the second case of Lemma 5.13). Suppose now that $v_i(g_4) = b$. If i values any of $g_1, g_2, g_3 \in X''$ at 1, then i envies s , so s cannot be a source of the doubly enhanced graph $G_{\text{de}}(\mathbf{X}'')$. If $v_i(g_1) = v_i(g_2) = v_i(g_3) = b$ for $g_1, g_2, g_3 \in X''$, there should be an edge (i, s) (it may as well be a self loop) in the doubly enhanced graph $G_{\text{de}}(\mathbf{X}'')$ and therefore s cannot be a source in $G_{\text{de}}(\mathbf{X}'')$.

Overall, we ended up with a contradiction and the lemma follows. \square

With those two claims we complete the proof of the lemma. \square

Lemma 5.26. *Let \mathbf{X} be a partial allocation at the end of any iteration of the while loop of the 3PA⁺⁺ algorithm. If Steps 1-8 of the algorithm did not run, for any agent $i \in N$ that has a critical good g we have $|X_i| = 1$, $v_i(X_i) = 1$, and $v_i(g) = b$.*

Proof. Consider any agent $i \in N$ and any good $g \in \mathcal{P}(\mathbf{X})$. Regardless of whether $|X_i| = 1$ or $|X_i| > 1$, it must be the case that $v_i(X_i) \geq v_i(g)$, as otherwise either Step 2 or Step 3 would have run. Given this, by Lemma 5.18, it follows that $v_i(g) < v_i(X_i)$, which implies that $v_i(X_i) > c$, as c is the minimum value of any good, as otherwise one of Steps 1, 4, or 5 would have run. Consider first the case when $|X_i| = 1$. In this case $v_i(X_i) > c$ implies either that $v_i(X_i) = b$ or that $v_i(X_i) = 1$. In the former case, we obviously have that $v_i(g) = c$, and by Lemma 5.11, we have that $v_i(X_i) > 2 \cdot v_i(g)$, since $b > 1/2$. This means that g cannot be a critical good for agent i . In the latter case, g obviously cannot be critical for agent i , if $v_i(g) = c$, and therefore we conclude that if g is critical, it must be that $v_i(g) = b$.

Now consider the case when $|X_i| > 1$. We will prove that it is not possible for agent i to have a critical good. First, if $v_i(g) = c$, then we trivially have that $v_i(X_i) \geq 2 \cdot v_i(g)$ since $|X_i| > 1$, and g cannot be critical for agent i . Therefore we may assume that $v_i(g) \geq b$. Let $g^* \in \arg \max_{g \in X_i} v_i(g)$ be a good of maximum value for agent i in her bundle X_i . We argue that there exists $g \in X_i \setminus \{g^*\}$ such that $v_i(g) \geq b$. If this was not the case, by applying Lemma 5.13 for the set $X_i \setminus \{g^*\}$, we infer $v_i(X_i \setminus \{g^*\}) < \frac{1}{2} < b$, and therefore the

agent would have swapped $X_i \setminus \{g^*\}$ with g from the pool (since $v_i(g) \geq b$) in Step 7, which by assumption in the statement of the lemma did not run. From this, we infer that there are at least two goods g^*, \tilde{g}^* in X_i for which $v_i(g') \geq b$, for $g' \in \{g^*, \tilde{g}^*\}$. If $v_i(g) = b$, this implies that g cannot be critical for agent i , so assume that $v_i(g) = 1$. In turn, since Step 7 did not run, we have that $v_i(X_i \setminus \{g'\}) \geq 1$, where $g' \in \{g^*, \tilde{g}^*\}$ is the good with the minimum value for agent i among the two. We consider three cases:

- $v_i(g') = 1$. In that case we have $v_i(X_i) \geq 2 \cdot v_i(g)$, and hence g cannot be critical for agent i .
- $v_i(X_i \setminus \{g'\}) \geq 3b$. Similarly, in that case we have $v_i(X_i) \geq 2 \cdot v_i(g)$, and hence g cannot be critical for agent i .
- there exist exactly three goods $\{g_1, g_2, g_3\}$ in X_i for which $v_i(g_i) = b$, for $i \in \{1, 2, 3\}$ and $v_i(g'') = c$ for any other good $g'' \in X_i$. This is precisely the condition of Step 8, contradicting the assumption of the lemma that this step did not run. \square

The following lemma establishes that **Properties (a) and (b)** are satisfied at the end of each iteration of the while loop of the algorithm, unless the algorithm has terminated with a complete (2/3)-EFX allocation, in which case we are done.

Lemma 5.27. *Let \mathbf{X} be a partial allocation obtained at the end of any iteration of the while loop of the 3PA⁺⁺ algorithm.*

- If $\mathcal{P}(\mathbf{X}) \neq \emptyset$, then \mathbf{X} satisfies **Properties (a) and (b)**.
- If $\mathcal{P}(\mathbf{X}) = \emptyset$, then \mathbf{X} is a complete (2/3)-EFX allocation.

Proof. We will prove the statement by induction on the number of iterations of the while loop of the 3PA⁺⁺ algorithm. Before the first iteration **Properties (a) and (b)** are satisfied, any if $\mathcal{P}(\mathbf{X}) = \emptyset$, then \mathbf{X} is a complete (2/3)-EFX allocation. Now consider any arbitrary iteration of the while loop, and let \mathbf{X} be the partial allocation of the algorithm before the iteration, and \mathbf{X}' be the partial allocation over the iteration. We first state and prove the following two useful claims which address situations that may occur in several steps of the algorithm.

Claim 5.28. *Suppose that at the current iteration of the while loop, any step except Step 2 or Step 3 runs. Let X be any allocated bundle in \mathbf{X} , with $|X| \geq 2$, and for any two agents $i, j \in N$,*

- $X'_i = \{g, g'\}$ for any good $g \in \mathcal{P}(\mathbf{X})$ and any good $g' \in X$,
- $v_j(X'_j) \geq \frac{3}{2}v_j(X_j)$, if $|X_j| > |X'_j| = 1$, and $v_j(X'_j) \geq v_j(X_j)$, otherwise.

Then, if $|X'_j| = 1$, j is EFX towards i , and if $|X'_j| > 1$, j is (2/3)-EFX towards i .

Proof of Claim 5.28. Consider first the case when $|X_j| = 1$. Since Step 2 did not run, for every good $\tilde{g} \in \mathcal{P}(\mathbf{X})$ we have $v_j(\tilde{g}) \leq v_j(X_i)$ and hence also $v_j(g) \leq v_j(X_j)$. By **Property (a)** which holds by the induction hypothesis, we also have $v_j(X_j) \geq v_i(g')$, since $|X| \geq 2$ and X is an allocated bundle in \mathbf{X} . This, together with the fact that $v_j(X'_j) \geq v_j(X_j)$, implies that in \mathbf{X}' agent j is EFX (and hence also trivially (2/3)-EFX) towards agent i . Now consider the case when $|X_j| > 1$. Since Step 2 did not run, for every good $\tilde{g} \in \mathcal{P}(\mathbf{X})$ we have that $v_j(\tilde{g}) \leq \frac{3}{2}v_j(X_j)$, which implies $v_j(g) \leq \frac{3}{2}v_j(X_j)$. By **Property (b)** which holds that by the induction hypothesis, we have that $v_j(X_j) \geq \frac{2}{3}v_j(g')$, since $|X| \geq 2$ and X is an allocated bundle in \mathbf{X} . If $|X'_j| = 1$, by the statement of the claim we have that $v_j(X'_j) \geq \frac{3}{2}v_j(X_j)$, which implies that in \mathbf{X}' agent j is EFX towards agent i . If $|X'_j| > 1$, by the statement of the claim we have that $v_j(X'_j) \geq v_j(X_j)$, which implies that agent j is (2/3)-EFX towards agent i . \square

Claim 5.29. *Suppose that at the current iteration of the while loop, any step except Steps 1-8 run. Let s be any source in the reduced+ envy graph $G_r(\mathbf{X})$, and for any two agents i, j ,*

- $X'_i \subseteq X_s \cup \{g\}$, for any good $g \in \mathcal{P}(\mathbf{X})$, and $|X'_i| \leq k_{\max}$,
- $v_j(X'_j) \geq \frac{3}{2}v_j(X_j)$, if $|X_j| > |X'_j| = 1$, and $v_j(X'_j) \geq v_j(X_j)$, otherwise.

Then, if $|X'_j| = 1$, j is EFX towards i , and if $|X'_j| > 1$, j is $\frac{2}{3}$ -EFX towards i .

Proof of Claim 5.29. If $|X_j| = 1$, by Lemma 5.26, $v_j(X_j) \geq b$, otherwise $\mathcal{P}(\mathbf{X}) = \emptyset$. If $v_j(X_j) = b$ again by Lemma 5.26, it holds that $v_j(g) = c$. Since s is a source of $G_r(\mathbf{X})$ it holds that $v_j(X_j) \geq v_j(X_s) = v_j(X_s \cup \{g\}) - c \geq v_j(X'_i \setminus \{g'\})$, for any $g' \in X'_i$, and so agent j is EFX (and also trivially $2/3$ -EFX) towards agent i . Suppose now that $v_j(X_j) = 1$. By Lemma 5.26, it holds that $v_j(g) \leq b$. Since s was a source vertex of $G_r(\mathbf{X})$, we have that $v_j(g') \leq b$, for any $g' \in X_s$. If $|X'_i| \leq 2$, it holds that $v_j(X'_i \setminus \{g'\}) \leq b < v_j(X_j)$, for any $g' \in X'_i$. If $|X'_i| \geq 3$, Lemmata 5.13 and 5.22, we have that $v_j(X_j) > v_j(X'_i)$. Therefore, in this case agent j is EFX (and also trivially $2/3$ -EFX) towards agent i .

Suppose now that $|X_j| > 1$. By Lemma 5.26, it holds that $v_j(g) \leq \frac{1}{2}v_j(X_j)$, and since s is a source of $G_r^+(\mathbf{X})$, it also holds that $v_j(X_j) \geq v_j(X_s)$. By combining these two inequalities, we obtain that $v_j(X_j) \geq \frac{2}{3}v_j(X'_i)$. We conclude the proof by observing that

- If $|X'_j| = 1$, by the statement of the claim, $v_j(X'_j) \geq \frac{3}{2}v_j(X_j)$, and so j is EFX towards i .
- If $|X'_j| > 1$, by the statement of the claim, $v_j(X'_j) \geq v_j(X_j)$, and so j is $\frac{2}{3}$ -EFX towards i . □

Now can continue with the proof of Lemma 5.27. We consider cases depending on which step of the algorithm ran in this iteration of the while loop.

If Step 1 or Step 4 is executed: For each agent $i \in N$ we have $v_i(X'_i) \geq v_i(X_i)$. Therefore, by the induction hypothesis, it suffices to consider the case of an agent j that went from $|X_j| = 2$ (and for which Property (b) was satisfied) to $|X'_j| = 1$ (where now Property (a) must be satisfied). Since in these steps we are considering the reduced+ envy graph $G_r^+(\mathbf{X})$, this only happens when $v_j(X'_j) \geq \frac{3}{2}v_j(X_j)$. This establishes Property (a), and thus both properties are satisfied.

If Step 2 is executed: Consider the agent $i \in N$ whose bundle was updated in this step, and notice that $v_i(X'_i) \geq v_i(X_i)$. By Property (a) which is satisfied in \mathbf{X} by the induction hypothesis, and since $|X'_i| = 1$, Properties (a) and (b) are satisfied in \mathbf{X}' also. Since $|X'_i| = 1$, every other agent $j \in N$ is EFX towards agent i , and so Properties (a) and (b) are satisfied for those agents as well.

If Step 3 is executed: Consider the agent $i \in N$ whose bundle was updated in this step. By Property (b) which holds by the induction hypothesis, agent i was $2/3$ -EFX towards any other agent $j \in N$ in \mathbf{X} . Since $v_i(X'_i) \geq \frac{3}{2}v_i(X_i)$, agent i is EFX towards any other agent in \mathbf{X}' , which implies Properties (a) and (b) for agent i . Since $|X'_i| = 1$, every other agent $j \in N$ is EFX towards agent i , and so Properties (a) and (b) are satisfied for those agents as well.

If Step 5 is executed: Consider the agents in $R(\mathbf{X})$ whose bundles changed from \mathbf{X} to \mathbf{X}' , and notice that for each $i \in R(\mathbf{X})$, we have $|X_i| = 1$ and $|X'_i| = 2$, as well as $v_i(X'_i) \geq v_i(X_i)$. Consider any other agent $j \in N$. Assume first that $j \notin R(\mathbf{X})$. By the definition of $R(\mathbf{X})$, $v_j(X_j) \geq v_j(X_i)$ (otherwise there would be an edge (j, i) in $G_r^+(\mathbf{X})$). Furthermore,

- since Step 2 did not run, if $|X_j| = 1$, it holds that $v_j(X_j) \geq v_j(g)$ for all $g \in \mathcal{P}(\mathbf{X})$,
- since Step 3 did not run, if $|X_j| = 2$, it holds that $v_j(X_j) \geq \frac{2}{3}v_j(g)$ for all $g \in \mathcal{P}(\mathbf{X})$.

This means that

- if $|X'_j| = 1$, $v_i(X_j) = v_i(X'_j) \geq v_j(X'_j \setminus \{g\})$ for any good g that was added to agent i 's bundle, and hence agent j is EFX towards agent i in \mathbf{X}' ,
- if $|X'_j| = 2$, $v_i(X_j) = v_i(X'_j) \geq \frac{2}{3}v_j(X'_j \setminus \{g\})$ for any good g that was added to agent i 's bundle, and hence agent j is 2/3-EFX towards agent i in \mathbf{X}' .

Since $v_i(X'_i) \geq v_i(X_i)$, agent i is EFX towards agent j in \mathbf{X}' by the induction hypothesis, which ensures that she was EFX towards j in \mathbf{X} .

Now assume that $j \in R(\mathbf{X})$. In that case $v_i(X'_j) \geq v_j(X_j) = 1$. Since both i and j are in the set $R(\mathbf{X})$ it follows that $v_j(X_j) \geq v_j(X_i) = v_j(g_i)$ where g_i is the good that constitutes X_i . Letting $g'_i = X'_i \setminus \{g_i\}$ be the good that was added to agent i 's bundle by the `SINGLEROUNDRUBIN` routine in Step 5, we also have that $v_j(X_j) \geq v_j(g'_i)$, as otherwise Step 2 would have run. Since $v_j(X'_j) \geq v_j(X_j)$, agent j is EFX towards agent i in \mathbf{X}' , and **Properties (a)** and **(b)** are satisfied for agent j . Finally, for any pair of agents $i, j \notin R(\mathbf{X})$, their bundles have not changed in \mathbf{X} , so when considered against each other, **Properties (a)** and **(b)** hold by the induction hypothesis.

If Step 6 is executed: Consider the agent i whose bundle was updated in this step and notice that $v_i(X'_i) \geq v_i(X_i)$. **Property (a)** was satisfied for the agent in \mathbf{X} by the induction hypothesis, since $|X_i| = 1$. This means that **Properties (a)** and **(b)** are satisfied for the agent in \mathbf{X}' . Consider any other agent $j \in N$. Looking at agent i 's bundle X'_i , we observe that it contains 2 goods which she either received both from $\mathcal{P}(\mathbf{X})$, or one from $\mathcal{P}(\mathbf{X})$ and one from X_i , as a source of $G_r^+(\mathbf{X})$. Similarly to the argument for Step 5 above,

- since Step 2 did not run, if $|X_j| = 1$, it holds that $v_j(X_j) \geq v_j(g)$ for all $g \in \mathcal{P}(\mathbf{X})$,
- since Step 3 did not run, if $|X_j| = 2$, it holds that $v_j(X_j) \geq \frac{2}{3}v_j(g)$ for all $g \in \mathcal{P}(\mathbf{X})$.

So, by the induction hypothesis, agent j is EFX towards agent i if $|X'_j| = 1$ and 2/3-EFX towards i if $|X'_j| > 1$, since $X_j = X'_j$. This implies that **Properties (a)** and **(b)** are satisfied for all agents.

If Step 7 is executed: Consider the agent $i \in N$ whose bundle was updated in this step and notice that $v_i(X'_i) \geq v_i(X_i)$. Since $|X_i| \geq 2$ and $|X'_i| \geq 2$, the induction hypothesis implies that **Property (b)** is satisfied for agent i (and so is **Property (a)** vacuously). Looking at agent i 's bundle X'_i , we observe that it contains 2 goods, one that she received from $\mathcal{P}(\mathbf{X})$ and one from X_i . By [Claim 5.28](#), **Properties (a)** and **(b)** are satisfied for any other agent $j \in N \setminus \{i\}$, so overall both properties are satisfied.

If Step 8 is executed: Consider the agent $i \in N$ whose bundle was updated in this step. By definition of the sets in the hierarchy (see [Definition 5.16](#)), $i \in N_{[1+b,2]}(\mathbf{X})$. From the allocation update of the step, we have that $v_i(X'_i) \geq 1 + b$. Consider any other agent $j \in N$. By [Lemma 5.23](#), for any $g \in X_j$, it holds that

$$\frac{2}{3}v_i(X_j \setminus \{g\}) < \frac{2}{3}\left(b + \frac{5}{3}\right) = b - \frac{b}{3} + \frac{10}{9} < b - \frac{1}{6} + \frac{10}{9} = b + \frac{17}{18} < 1 + b,$$

and therefore **Property (b)** is still satisfied for agent i . By [Claim 5.28](#), **Properties (a)** and **(b)** are satisfied for any agent $j \in N \setminus \{i\}$, so overall both properties are satisfied.

If Step 9 or Step 10 is executed: Consider any bundle X that was updated (meaning that the goods it contains changed) in this step, and observe that in \mathbf{X} it was the set X_i of some source $i \in N$ of $G_r^+(\mathbf{X})$. Let X' be its updated version in \mathbf{X} (assigned to some agent ℓ as bundle X'_ℓ). Looking at X' , we observe that it consists of one good $g^* \in \mathcal{P}(\mathbf{X})$, and one good of X . By [Claim 5.29](#), **Properties (a)** and **(b)** are satisfied in \mathbf{X}' for any agent j such that $v_j(X'_j) \geq v_j(X_j)$. Note that for any agent j such that $|X'_j| = 1$ and $|X_j| \geq 2$, it holds that $v_j(X'_j) \geq \frac{3}{2}v_j(X_j)$ by the definition of the reduced+ envy graph $G_r^+(\mathbf{X})$.

Now consider any agent $i \in N$ such that $v_i(X'_i) < v_i(X_i)$. Note that this implies that either $i \in N_{1,(0,2/3)}(\mathbf{X}')$, or $i \in N_{[1+b,2]}(\mathbf{X}')$ (this happens only if we executed Step 10). Suppose first that $i \in N_{1,(0,2/3)}(\mathbf{X}')$. By

Lemmata 5.13 and **5.22**, for any other agent $j \in N \setminus \{i\}$, we have that $v_i(X'_j \setminus \{g\}) < \frac{2}{3}$ for any $g \in X'_j$. By the definition of the enhanced+ envy graph $G_e^+(\mathbf{X})$, it further holds that $v_i(X'_i) > b > \frac{4}{9} > \frac{2}{3}v_i(X_j \setminus \{g\})$. Moreover, we either have that $|X_i| > 1$, in which case **Property (b)** is satisfied for i , or $\mathcal{P}(\mathbf{X}') = \emptyset$ during this step, and the lemma follows.

If $i \in N_{[1+b,2)}(\mathbf{X}')$, then **Property (b)** is satisfied for agent i for the same reasons as if we executed Step 8 above. Overall, **Properties (a)** and **(b)** are satisfied or the allocation is complete and it is $(2/3)$ -EFX.

If Step 11 is executed: In this step, only some set X_i is modified in \mathbf{X}' by setting $X'_i = X_i \cup \{g\}$ for some good $g \in \mathcal{P}(\mathbf{X})$. Notice that $v_i(X'_i) \geq v_i(X_i)$, which, combined with the fact the $|X_i| \leq |X'_i|$ implies that **Properties (a)** and **(b)** are satisfied by the induction hypothesis. Notice also that agent i was a source of $G_{de}(\mathbf{X})$ and therefore also a source of $G_r^+(\mathbf{X})$. By **Claim 5.29**, **Properties (a)** and **(b)** are satisfied in \mathbf{X}' for any agent $j \in N \setminus \{i\}$.

If Step 12 is executed: In this step, there is only one bundle X (allocated as X_ℓ to some agent $\ell \in N$ in \mathbf{X}) that is modified. Let X' be its updated version in \mathbf{X}' (allocated to some agent i as X'_i). We have that $X' = X \setminus \{g\} \cup \{g'\}$, where $g \in X$ and $g' \in \mathcal{P}(X)$. For any agent $j \in N \setminus \{i\}$, **Properties (a)** and **(b)** are satisfied by **Claim 5.29** and by the definition of $G_r^+(\mathbf{X})$, since X was the bundle of a source in $G_r^+(\mathbf{X})$ (before it was updated and assigned to agent i). We next argue that agent i is $2/3$ -EFX towards any other agent $j \in N$, with bundle X'_j (with possibly $X'_j = X_j$). By the condition of Step 12, agent i had a critical good $g_i \in \mathcal{P}(\mathbf{X})$. By **Lemma 5.26**, this implies that $v_i(X_i) = 1$. By **Lemmata 5.13** and **5.22**, for any agent $j \in N \setminus \{i\}$, we have that $v_i(X_j \setminus \{g\}) < 2/3$ for any $g \in X_i$. Additionally, by **Lemma 5.14**, it follows that $|X_i| = 1$, so trivially, $v_i(X_i \setminus \{g\}) = 0 < \frac{2}{3}$ for any $g \in X_i$. Finally, we have that $v_i(X'_i) \geq b + (k_{\max} - 1)c \geq 2/3$ by the definition of k_{\max} (more precisely $v_i(X'_i) = b + (k_{\max} - 1)c$). This implies that **Property (b)** is satisfied for agent i in \mathbf{X}' as well. Overall, **Properties (a)** and **(b)** are satisfied.

If Step 13 is executed: In this case $\mathbf{X}' = \mathbf{X}$ and the algorithm terminates; **Properties (a)** and **(b)** are satisfied trivially by the induction hypothesis. \square

Concluding the proof of Lemma 5.9. We argue that as long as there exists some agent $i \in N$ with a critical good, some step of the $3PA^{++}$ algorithm other than Step 13 will run. Assume by contradiction that in the last iteration of the while loop of the algorithm Step 13 ran. Since Steps 1 and 5 did not run, by **Lemma 5.15** the reduced+ envy graph $G_r^+(\mathbf{X})$ has a source vertex s . Consider the enhanced+ envy graph $G_e^+(\mathbf{X})$, and assume first that it does not have a source; this means that s must be contained in some cycle of $G_e^+(\mathbf{X})$. Consider any such cycle C , and let (i, s) be an edge in C . Since s is a source of $G_r^+(\mathbf{X})$, (i, s) is not an edge of $G_r^+(\mathbf{X})$. From this it follows that (i, j) is not a grey edge, which in turns implies that C is jaundiced. That means that Step 9 of the $3PA^{++}$ algorithm would have run, a contradiction.

Now assume that there is a source in $G_e^+(\mathbf{X})$, and consider the doubly enhanced graph $G_{de}(\mathbf{X})$. Similarly to before, if there is no source in $G_{de}(\mathbf{X})$, there would be a cycle that is jaundiced and Step 10 would have run, a contradiction. So we may assume further that there exists a source s in $G_{de}(\mathbf{X})$. By definition of $G_{de}(\mathbf{X})$, s is also a source of $G_e^+(\mathbf{X})$. In that case however, if $|X_s| < k_{\max}$, Step 11 would have run, and if $|X_s| = k_{\max}$, Step 12 would have run. In each case, we obtain a contradiction.

5.1.6 The Proof of Lemma 5.10

We will show that the potential function we introduced in **Section 5.1.2** lexicographically increases at each round of $3PA^{++}$ that performs any step, except possibly of 1, 8, and 11. Applying Steps 1, 8, or 11 may leave the potential function unaffected, yet we will argue that those three steps may be applied sequentially for

a polynomially bounded number of steps. Recall the potential function:

$$\mathcal{F}(\mathbf{X}) = (|N_{[2,\infty)}(\mathbf{X})|, |N_{[1+b,2)}(\mathbf{X})|, |N_{(1,1+b)}(\mathbf{X})|, |N_{[2/3,1)}(\mathbf{X})|, SW_{(0,1+b)}(\mathbf{X}))$$

By Lemma 5.17, while running 3PA⁺⁺ none of the first four coordinates of the potential function ever decreases. Hence, $\mathcal{F}(\mathbf{X})$ increases if one of its terms increases.

- If Step 2 or 3 is applied, one agent will improve her value by getting a single good, so $SW_{(0,1+b)}(\mathbf{X})$ is improved.
- If Step 4 is applied, no agent decreases their value. Let (i', i) be the *last* non-grey edge in the path. We first argue that $|X_i| = 1$. This is true, since either i is not the last vertex in the path so, the next edge is grey, or it is the last vertex in the path, for whom it holds $v_i(X_i) = v_i(g)$, for some $g \in \mathcal{P}(\mathbf{X})$. By Lemma 5.14, $|X_i| = 1$. Therefore, agent i' will strictly improve her value by getting a single good, so $SW_{(0,1+b)}(\mathbf{X})$ is improved.
- If Step 5 is applied, no agent in $R(\mathbf{X})$ belonged to any of the sets $N_{[2,\infty)}(\mathbf{X})$, $N_{[1+b,2)}(\mathbf{X})$, $N_{(1,1+b)}(\mathbf{X})$, since they had value 1 for their bundles. However, after applying Step 5, they belong to one of them (unless the pool empties and the algorithm terminates), so the cardinality of at least one of them increases.
- If Step 6 is applied no value is decreased and, by Lemma 5.20, the agent whose bundle is modified, values her new set by at most $2b$, so $SW_{(0,1+b)}(\mathbf{X})$ is improved, unless the pool empties and 3PA⁺⁺ terminates.
- If Step 7 is applied, let i be the agent that modifies her bundle. If her value for her updated set is less than $1 + b$, $SW_{(0,1+b)}(\mathbf{X})$ is improved. The cases that left to examine is that her value for her updated set is either $1 + b$, in which case $|N_{[1+b,2)}(\mathbf{X})|$ increases, or 2, in which case $|N_{[2,\infty)}(\mathbf{X})|$ increases.
- If Step 9 or 10 is applied, some agents may reduce their value, but in Step 9 $|N_{(1,1+b)}(\mathbf{X})|$ will increase (an agent with value 1 will increase her value to $2b$) and in Step 10 $|N_{[2,\infty)}(\mathbf{X})|$ will increase (an agent with value less than 2 will increase her value to $4b$).
- If Step 12 is applied, $|N_{[2/3,1)}(\mathbf{X})|$ will increase, since an agent with value 1 will receive a set for which she has value $b + (k_{\max} - 1)c \geq \frac{2}{3}$.
- If Step 8 is applied, the potential function remains unchanged because only an agent from $N_{[1+b,2)}(\mathbf{X})$ changes her bundle and remains in $N_{[1+b,2)}(\mathbf{X})$.
- If Step 1 or 11 is applied, no agent reduces their value, whereas the potential may or may not improve.

Next we argue that it is not possible to consecutively apply Steps 1, 8, and 11 $2mn^2$ times without increasing $\mathcal{F}(\mathbf{X})$. First note that Step 1 can be executed consecutively less than n^2 times, since each time the number of edges in $G_r(\mathbf{X})$ decreases. If only Steps 1 and 8 are executed, Step 8 can be executed at most m times, since the cardinality of the pool always increases, so both steps can be consecutively executed less than mn^2 times. In the following claim we prove that if Steps 1 and 8 cannot be applied at any point, then Step 8 may be only applied after the potential function has increased.

Claim 5.30. *If for some allocation \mathbf{X} Steps 1 and 8 of 3PA⁺⁺ cannot apply, Step 8 may be only applied after the increment of the potential function.*

Proof of Claim 5.30. If any of the Steps 2-7, 9, 10, or 12 can be applied on \mathbf{X} , the potential function will increase and the claim follows. So, assume that Steps 2-8 cannot be applied on \mathbf{X} . This means that for any agent $i \in N_{[1+b,2)}(\mathbf{X})$ and any good $g \in \mathcal{P}(\mathbf{X})$, $v_i(g) < 1$, otherwise either Step 7 or Step 8 would apply. Suppose, towards a contradiction, that it is possible that only Steps 1 and 11 are executed until we get an allocation \mathbf{X}' where Step 8 can be applied again; otherwise the potential function would increase and the claim would follow. The set $N_{[1+b,2)}(\mathbf{X})$ remains the same during all those rounds, otherwise the potential function would increase. During Steps 1 and 11, $\mathcal{P}(\mathbf{X})$ may only stay the same or shrink, so for any agent

$i \in N_{[1+b,2]}(\mathbf{X}')$ and any good $g \in \mathcal{P}(\mathbf{X}') \subseteq \mathcal{P}(\mathbf{X})$, $v_i(g) < 1$, and therefore Step 8 cannot be applied on \mathbf{X}' . This contradicts our assumption, and the claim follows. \square

As an immediate consequence of the claim, we get that after less than mn^2 steps (during which we have assumed that the potential remains the same), Steps 1 and 8 cannot be applied anymore. Then, however, only Steps 1 and 11 could be executed without the improving $\mathcal{F}(\mathbf{X})$. Similarly to the above, if only Steps 1 and 11 are executed, Step 11 can be executed at most m times, since the pool always shrinks, so both steps can be executed sequentially less than mn^2 times. Overall, all three steps can be consecutively executed, without the execution of any other step, for less than $2mn^2$ times.

Equivalently, within $2mn^2$ steps, $\mathcal{F}(\mathbf{X})$ will improve. Already this suffices to show that 3PA⁺⁺ terminates. This follows from the simple fact that eventually either the allocation will be complete, or the potential function will become equal to $(n, 0, 0, 0, 0)$, i.e., all agents will enter the set $N_{[2,\infty)}(\mathbf{X})$. Once an agent gets into $N_{[2,\infty)}(\mathbf{X})$ (i.e., **Level (L.1)**), by **Lemma 5.17**, she never leaves this set (as she cannot fall in hierarchy). It is easy to check that if $N_{[2,\infty)}(\mathbf{X}) = N$, none of the Steps 1-12 can be applied and the algorithm terminates. Nevertheless, we are going to show something stronger, namely that 3PA⁺⁺ terminates in polynomially many iterations. As each iteration only involves checking the conditions of the different steps in polynomial time and one of the steps running, again in polynomial time, this would prove the statement.

So, every $2mn^2$ steps at most, $\mathcal{F}(\mathbf{X})$ improves. We are going to distinguish two types of improvements: *welfare improvements*, where only the restricted social welfare $SW_{(0,1+b)}(\mathbf{X})$ increases, and *ascend improvements*, where some of the other coordinates of $\mathcal{F}(\mathbf{X})$ increases, i.e., at least one agent ascends in the hierarchy. Each agent can trigger at most 4 ascend improvements, as she never falls in hierarchy. So there are at most $4n$ ascend improvements in total. In fact, by the above discussion, after at most $4n$ ascend improvements, the 3PA⁺⁺ algorithm must terminate.

Finally, we are going to bound the number of welfare improvements between two ascend improvements. By the definition of an ascent improvement, between any two of them, the set of agents contributing to $SW_{(0,1+b)}(\mathbf{X})$, i.e., agents at **Levels (L.3) to (L.5)**, remains unchanged. As long as none of the Steps 5, 9, 10, or 12 is executed (all of which force an ascend improvement) every agent at **Levels (L.3) to (L.5)** never decreases her value. Moreover, every $2mn^2$ steps at most, at least one of those agents strictly increases her value through Steps 2-4 or 7, *always* by getting a bundle of cardinality 1 or 2, as one can see by simple inspection of the different steps. Every time this happens for a specific agent $i \in N_{(1,1+b)}(\mathbf{X}) \cup N_{[2/3,1)}(\mathbf{X}) \cup N_{1,(0,2/3)}(\mathbf{X})$, she must have a distinct value for her bundle. Since there are only 7 possible bundles of cardinality at most 2 that allow i to be in that set, i can trigger at most 6 welfare improvements between two ascend improvements. So there are at most $6n$ welfare improvements, in total, between two ascend improvements.

Therefore, every $14mn^3$ steps or less, at least one ascend improvement occurs. Therefore, if the 3PA⁺⁺ algorithm did not terminate earlier, within $56mn^4$ iterations at most, all possible ascend improvements will happen, guaranteeing termination.

5.1.7 Dealing with Zero Values

In the pseudocode of **THREEVALUESALLOCATE** the case where $c = 0$ is handled by replacing these zeros by a sufficiently small number. Here we will show that this is indeed a valid approach that reduces the problem to the $c > 0$ case we already dealt with. Moreover, as it is evident by the definition of c' in the statement of the next lemma, a sufficient value for ε in **THREEVALUESALLOCATE** can be found in $O(m^2)$ time.

Lemma 5.31. *Consider a 3-value instance $(N, (v_i)_{i \in N}, M)$ such that $a = 1 > b > c = 0$ and construct the*

instance $(N, (\tilde{v}_i)_{i \in N}, M)$ by replacing any value that is 0 by

$$c' = \frac{1}{3m} \min\{|k + \ell b| : k, \ell \in \{-3m, \dots, 2m\} \text{ and } k + \ell b \neq 0\}.$$

Then any 2/3-EFX allocation for $(N, (\tilde{v}_i)_{i \in N}, M)$, is also a 2/3-EFX allocation for $(N, (v_i)_{i \in N}, M)$.

Proof. First, note that for any two $S, T \subseteq M$ and any $i \in n$, we have that $|2v_i(S) - 3v_i(T)|$ is either 0 or takes a value in the set $\{|k + \ell b| : k, \ell \in \{-3m, \dots, 2m\} \text{ and } k + \ell b \neq 0\}$. In particular, if $|2v_i(S) - 3v_i(T)| \neq 0$, then $|2v_i(S) - 3v_i(T)| \geq \min\{|k + \ell b| : k, \ell \in \{-3m, \dots, 2m\} \text{ and } k + \ell b \neq 0\} = 3mc'$.

Let \mathbf{X} be a 2/3-EFX allocation for $(N, (\tilde{v}_i)_{i \in N}, M)$ and consider any two agents $i, j \in N$. Of course, we have $\tilde{v}_i(X_i) \geq \frac{2}{3} \max_{g \in X_j} \tilde{v}_i(X_j \setminus \{g\})$. By the definition of \tilde{v}_i , we have $\tilde{v}_i(X_i) \leq v_i(X_i) + |X_i|c'$ and $\max_{g \in X_j} \tilde{v}_i(X_j \setminus \{g\}) \geq \max_{g \in X_j} v_i(X_j \setminus \{g\})$. That is

$$v_i(X_i) + |X_i|c' \geq \frac{2}{3} \max_{g \in X_j} v_i(X_j \setminus \{g\}), \text{ or equivalently, } 2v_i(Y_j) - 3v_i(X_i) \leq 3|X_i|c',$$

where $Y_j \subseteq X_j$ such that $v_i(Y_j) = \max_{g \in X_j} v_i(X_j \setminus \{g\})$.

Suppose, that $v_i(X_i) < \frac{2}{3} \max_{g \in X_j} v_i(X_j \setminus \{g\})$. Then, $2v_i(Y_j) - 3v_i(X_i) > 0$ and, by the above discussion, it must be $2v_i(Y_j) - 3v_i(X_i) > 3mc' \geq 3|X_i|c' \geq 2v_i(Y_j) - 3v_i(X_i)$, which is a contradiction. Hence, \mathbf{X} be a 2/3-EFX allocation for $(N, (v_i)_{i \in N}, M)$ as well. \square

6 Conclusion and Discussion

In this work we have pushed the frontier of existence and computation results for approximate EFX allocations in three natural settings for which we show that 2/3-EFX allocations can be computed in polynomial time. Interestingly, these settings strictly generalize the settings for which the state-of-the-art is known about exact EFX allocations. The algorithmic framework that we develop, via the introduction of the 3PA algorithm and its variants, has the potential to be a powerful tool in obtaining approximate EFX allocations, possibly in polynomial time. While the existence of EFX allocations remains the holy grail of this line of work, one of the most sensible next steps would be to aim for the existence of 2/3-EFX allocations for (general) additive valuation functions. The case of 3-value instances already reveals many of the intricacies one has to deal with in this endeavour.

Another natural question here is whether our framework can be applied when the resources are indivisible chores, i.e., each item has non-positive value for everyone. The existence of—exact or approximate—EFX allocations in this case (under the natural modification of [Definition 2.6](#)) seems to be equally, if not more, opaque. Currently, the best known approximation factors for additive valuation functions are 2 for 3 agents [[Christoforidis and Santorinaios, 2024](#)] and $O(n^2)$ in general [[Zhou and Wu, 2024](#)]. Although the mechanics of criticality are quite different for chores, we believe that the high level approach of this work, i.e., the recursive improvement of an initial partial allocation and the use of multiple envy graphs, could be a good starting point for obtaining positive results in similar restricted cases.

Acknowledgements

Georgios Amanatidis was supported by the NWO Veni project No. VI.Veni.192.153. Aris Filos-Ratsikas was supported by the UK Engineering and Physical Sciences Research Council (EPSRC) grant EP/Y003624/1. Alkmini Sgouritsa was supported by the H.F.R.I. Project No. 15635 which is implemented in the framework of H.F.R.I call “Basic research Financing (Horizontal support of all Sciences)” under the National Recovery

and Resilience Plan “Greece 2.0” funded by the European Union–NextGenerationEU. Georgios Amanatidis and Alkmini Sgouritsa were also supported by the project MIS 5154714 of the National Recovery and Resilience Plan “Greece 2.0” funded by the European Union–NextGenerationEU.

References

- Hannaneh Akrami, Noga Alon, Bhaskar Ray Chaudhury, Jugal Garg, Kurt Mehlhorn, and Ruta Mehta. EFX: a simpler approach and an (almost) optimal guarantee via rainbow cycle number. In *Proceedings of the 24th ACM Conference on Economics and Computation*, pages 61–61, 2023.
- Georgios Amanatidis, Evangelos Markakis, and Apostolos Ntokos. Multiple birds with one stone: Beating $1/2$ for EFX and GMMS via envy cycle elimination. *Theoretical Computer Science*, 841:94–109, 2020.
- Georgios Amanatidis, Georgios Birmpas, Aris Filos-Ratsikas, Alexandros Hollender, and Alexandros A Voudouris. Maximum Nash welfare and other stories about EFX. *Theoretical Computer Science*, 863: 69–85, 2021.
- Georgios Amanatidis, Haris Aziz, Georgios Birmpas, Aris Filos-Ratsikas, Bo Li, Hervé Moulin, Alexandros A Voudouris, and Xiaowei Wu. Fair division of indivisible goods: Recent progress and open questions. *Artificial Intelligence*, page 103965, 2023.
- Moshe Babaioff, Tomer Ezra, and Uriel Feige. Fair and truthful mechanisms for dichotomous valuations. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 5119–5126, 2021.
- Ben Berger, Avi Cohen, Michal Feldman, and Amos Fiat. Almost full EFX exists for four agents. In *Proceedings of the 36th AAAI Conference on Artificial Intelligence (AAAI)*, pages 4826–4833, 2022.
- Eric Budish. The combinatorial assignment problem: Approximate competitive equilibrium from equal incomes. *Journal of Political Economy*, 119(6):1061–1103, 2011.
- Ioannis Caragiannis, Nick Gravin, and Xin Huang. Envy-freeness up to any item with high Nash welfare: The virtue of donating items. In *Proceedings of the 2019 ACM Conference on Economics and Computation (EC)*, pages 527–545, 2019a.
- Ioannis Caragiannis, David Kurokawa, Hervé Moulin, Ariel D Procaccia, Nisarg Shah, and Junxing Wang. The unreasonable fairness of maximum Nash welfare. *ACM Transactions on Economics and Computation*, 7(3):1–32, 2019b.
- Hau Chan, Jing Chen, Bo Li, and Xiaowei Wu. Maximin-aware allocations of indivisible goods. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 137–143, 2019.
- Bhaskar Ray Chaudhury, Jugal Garg, Kurt Mehlhorn, Ruta Mehta, and Pranabendu Misra. Improving EFX guarantees through rainbow cycle number. In *Proceedings of the 22nd ACM Conference on Economics and Computation (EC)*, pages 310–311, 2021a.
- Bhaskar Ray Chaudhury, Telikepalli Kavitha, Kurt Mehlhorn, and Alkmini Sgouritsa. A little charity guarantees almost envy-freeness. *SIAM Journal on Computing*, 50(4):1336–1358, 2021b.
- Bhaskar Ray Chaudhury, Jugal Garg, and Kurt Mehlhorn. EFX Exists for Three Agents. *Journal of the ACM*, *accepted*, 2023.
- George Christodoulou, Amos Fiat, Elias Koutsoupias, and Alkmini Sgouritsa. Fair allocation in graphs. In *Proceedings of the 24th ACM Conference on Economics and Computation (EC)*, 2023.

- Vasilis Christoforidis and Christodoulos Santorinaios. On the pursuit of EFX for chores: Non-existence and approximations. In *Proceedings of the 33rd International Joint Conference on Artificial Intelligence, IJCAI 2024*. ijcai.org, 2024.
- Alireza Farhadi, MohammadTaghi Hajiaghayi, Mohamad Latifian, Masoud Seddighin, and Hadi Yami. Almost envy-freeness, envy-rank, and Nash social welfare matchings. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 5355–5362, 2021.
- Duncan Karl Foley. *Resource allocation and the public sector*. Yale University, 1966.
- George Gamow and Marvin Stern. *Puzzle-math*. Viking Press, 1958.
- Laurent Gourvès, Jérôme Monnot, and Lydia Tlilane. Near fairness in matroids. In *21st European Conference on Artificial Intelligence (ECAI 2014)*, volume 263 of *Frontiers in Artificial Intelligence and Applications*, pages 393–398. IOS Press, 2014.
- Richard J Lipton, Evangelos Markakis, Elchanan Mossel, and Amin Saberi. On approximately fair allocations of indivisible goods. In *Proceedings of the 5th ACM Conference on Electronic Commerce*, pages 125–131, 2004.
- Evangelos Markakis and Christodoulos Santorinaios. Improved EFX approximation guarantees under ordinal-based assumptions. In *Proceedings of the 2023 International Conference on Autonomous Agents and Multiagent Systems*, pages 591–599, 2023.
- Benjamin Plaut and Tim Roughgarden. Almost envy-freeness with general valuations. *SIAM Journal on Discrete Mathematics*, 34(2):1039–1068, 2020.
- Hal R. Varian. Equity, envy, and efficiency. *Journal of Economic Theory*, 9(1):63–91, 1974. doi: 10.1016/0022-0531(74)90075-1.
- Shengwei Zhou and Xiaowei Wu. Approximately EFX allocations for indivisible chores. *Artif. Intell.*, 326: 104037, 2024.