Growing Trees on Sounds: Assessing Strategies for End-to-End Dependency Parsing of Speech

Adrien Pupier, Maximin Coavoux, Jérôme Goulian, Benjamin Lecouteux


Univ. Grenoble Alpes, CNRS, Grenoble INP, LIG, 38000 Grenoble, France first.last@univ-grenoble-alpes.fr

Abstract


Direct dependency parsing of the speech signal -as opposed to parsing speech transcriptionshas recently been proposed as a task (Pupier et al., 2022), as a way of incorporating prosodic information in the parsing system and bypassing the limitations of a pipeline approach that would consist of using first an Automatic Speech Recognition (ASR) system and then a syntactic parser. In this article, we report on a set of experiments aiming at assessing the performance of two parsing paradigms (graphbased parsing and sequence labeling based parsing) on speech parsing. We perform this evaluation on a large treebank of spoken French, featuring realistic spontaneous conversations. Our findings show that (i) the graph-based approach obtain better results across the board (ii) parsing directly from speech outperforms a pipeline approach, despite having 30% fewer parameters.

1 Introduction

Dependency parsing is a central task in natural language processing (NLP). In the NLP community, it has mostly been addressed on textual data, either natively written texts or sometimes speech transcriptions. Yet, speech is the main form of communication between humans, as well as arguably one of the most realistic types of linguistic data, which motivates the design of NLP systems able to deal directly with speech, both for applicative purposes and to construct corpora annotated with linguistic information. When parsing speech transcriptions, most prior work has focused on disfluency detection and removal (Charniak and Johnson, 2001; Johnson and Charniak, 2004; Rasooli and Tetreault, 2013; Honnibal and Johnson, 2014; Jamshid Lou et al., 2019), in an effort to 'normalize' the transcriptions and make them suitable input for NLP systems trained on written language. Using only transcriptions as input is a natural choice from an



(a) The two models based on audio features, blue arrow is **AUDIO**, red arrow is **ORACLE**.



(b) The two baseline models based on a pretrained language model, blue arrow is **PIPELINE** (predicted transcription), read arrow is **TEXT** (gold transcriptions).

Figure 1: Overview of architectures with the 4 settings described in Section 4.

NLP perspective: it makes it possible to use offthe-shelf NLP parsers 'as is'. However, predicted transcriptions can be very noisy, in particular for speech from spontaneous conversations. Furthermore, transcriptions are abstractions that contain much less information than the speech signal. The prosody, and the pauses in the speech utterances are very important clues for parsing (Price et al., 1991) that are completely absent from transcriptions. Hence, we address speech parsing using only the speech signal as input. With the popularization of self-supervised method and modern neural network architecture (pretrained transformers), both speech and text domains now use similar techniques (Chrupała, 2023). This convergence of methodology has raised interest in other applications of speech models to go beyond 'simple' speech recognition. Thus, addressing classical NLP tasks directly on speech is a natural step and design NLP tools able to deal with spontaneous speech, arguably the most realistic type of linguistic production. In short, Our contributions are the following:

- we introduce a graph-based end-to-end dependency parsing algorithm for speech;
- we evaluate the parser on Orféo, a large treebank of spoken French that features spontaneous speech, and compare its performance to pipeline systems and to a parsing-as-tagging parser;
- we release our code at https://github. com/Pupiera/Growing_tree_on_sound.¹

2 Parsers and pre-trained models

We define speech parsing as the task of predicting a dependency tree from an audio signal corresponding to a spoken utterance.²

Our parser is composed of 2 modules (Figure 1a): (i) an acoustic module that is used to predict transcriptions and a segmentation of the signal in words and (ii) a parsing module that uses the segmentation to construct audio word embeddings and predict trees.

Word level representations from speech To extract representations from the raw speech, we use a pre-trained wav2vec2 model trained on seven thou-

sand hours of French speech: LeBenchmark7K³ (Parcollet et al., 2024). Parsing requires word-level representations. We use the methodology of Pupier et al. (2022) to construct audio word embeddings from the implicit frame level segmentation provided by the CTC speech recognition algorithm (Graves et al., 2006). The method consists in combining the frame vectors corresponding to a single predicted word with an LSTM.

Graph-based parsing We use the audio word embeddings –whose construction is described above– as input to our implementation of a classical graph-based biaffine parser (Dozat and Manning, 2016): (i) compute a score every possible arc with a biaffine classifier and (ii) find the best scoring tree with a maximum spanning tree algorithm.

Sequence labeling The sequence labeling parser follows Pupier et al. (2022) and is based on the *dep2label* approach (Gómez-Rodríguez et al., 2020; Strzyz et al., 2020), specifically the relative POS-based encoding (Strzyz et al., 2019). This method reduces the parsing problem to a sequence labeling problem. The head of each token is encoded in a label of the form ±Integer@POS. The integer stands for the relative position of the head considering only words of the POS category. Eg., -3@NOUN means that the head of the current word is the third noun before it.

3 Dataset

We use the CEFC-Orféo treebank (Benzitoun et al., 2016), a dependency-annotated French corpus composed of multiple subcorpora (CLESTHIA, 2018; ICAR, 2017; ATILF, 2020; Mathieu et al., (2012-2020; André, 2016; Carruthers, 2013; Cresti et al., 2004; DELIC et al., 2004; Francard et al., 2009; Kawaguchi et al., 2006; Husianycia, 2011), and released with the audio recordings. The treebank consists of various types of interactions, all of which feature spontaneous discussions, except for the French Oral Narrative corpus (audiobooks). Orféo features many types of speech situations (eg. commercial interactions, interviews, informal discussions between friends) and is the largest French spoken corpus annotated in dependency syntax. The annotation scheme has been designed specifically for Orféo (Benzitoun et al., 2016) and differs from the Universal Dependency framework in many re-

¹The code is also archived at https://doi.org/10.5281/zenodo.11474162.

²For the sake of simplicity, we will use the term 'sentence' in the rest of the article, even though the very definition of a sentence is debatable in the spoken domain.

³https://huggingface.co/LeBenchmark/ wav2vec2-FR-7K-large

gards (in particular: its POS tagset is finer-grained, whereas the syntactic function tagset has only 14 relations). The syntactic annotations of Orféo were done manually for 5% of the corpus and automatically for the rest of the corpus. The train/dev/test split we use makes sure that the test section only contains gold annotations. Nevertheless, the subcorpora with gold syntactic annotations correspond to low-quality recordings, which makes them a very challenging benchmark.

4 Experiments

Experimental settings Our experiments aim at: (i) comparing our graph-based parser to the seq2label model, (ii) comparing to pipeline approaches with text-based parsers, and (iii) assessing the robustness of word representations with control experiments: using word boundaries (provided in the corpus) as input for the audio models and gold transcriptions for the text-based model. We compare the following settings (illustrated in Figure 1):

- AUDIO: Access to raw audio only, the model creates word-level representation from the acoustic model as described in Section 2.
- ORACLE: Access to raw audio and silver⁴
 word-level timestamps, making it easier to
 create word representations and mitigating the
 impact of the quality of the speech recognition
 on parsing.
- PIPELINE: Access to predicted transcriptions from the acoustic model only, then a language model uses the transcriptions as input for parsing. The training trees are modified to take into account any deletion and insertion of words. However, as for the speech approach, deletion or insertion penalizes the global score of the model since the model is evaluated against the gold transcriptions and not the modified one. The drawback of this approach is that no information about prosody or pauses is available.
- TEXT: Access to **gold transcriptions**: this unrealistic setting provides an upper bound performance in the ideal case (perfect ASR).

Both PIPELINE and TEXT settings use a French BERT model: camembert-base⁵ (Martin et al., 2020) to extract contextualized word embeddings.

For PIPELINE and TEXT settings, on top of our implementations, we use hops (Grobol and Crabbé, 2021), an external state-of-the-art graph-based parser. The hops parser uses a character-bi-LSTM in addition to BERT to produce word embeddings, whereas our implementation does not (in an effort to make both versions of our parser, text-based and audio-based, as similar as possible).

Each parsing method for each modality is trained with the same number of epochs, the same hyperparameters (see Table 4 and 5 of Appendix A), and approximately the same number of parameters. We select the best checkpoint on the development set in each setting for the final evaluation. Our implementations use speechbrain (Rayanelli et al., 2021).

Metrics We use classical evaluation measures: Word Error Rate (WER) and Character Error Rate (CER) for speech recognition, POS accuracy (POS), Unlabeled Attachment Score (UAS), and Labeled Attachment Score (LAS) for dependency parsing.

We report results in Table 1 for the full corpus, and in Table 2 for a sub-corpus of the test set (Valibel) for which speech recognition is easier.

Evaluation To evaluate our architecture, we use a modified version of the evaluation script provided by the CoNLL 2018 Shared Task. The main limitation of this evaluation protocol is that it requires the two sequences to be exactly the same, which is not the case when speech recognition is involved. Thus, we modify this evaluation script to work even when the two sequences to evaluate are not of the same length. However, the modified script requires an alignement between the 2 sequences. For our purpose, we use an alignment based on edit distance, i.e. the same alignment strategy already used to compute WER.

The modified script work by following this simple set of rules, depending on the edit operations:

- for word deletions: the predicted sequence is shorter, thus add a dummy token in the output sequence at the correct index to realign the sequences;
- for word additions: the predicted sequence is longer, thus add a dummy token in the gold sequence at the correct index to realign the sequence;
- for word substitutions: do nothing;

⁴The corpus contained word-level timestamps that have been automatically constructed through forced alignment.

⁵https://huggingface.co/almanach/ camembert-base

⁶https://universaldependencies.org/conll18/ evaluation.html

Model	WER↓	CER↓	POS↑	UAS↑	LAS↑	Parameters	Pre-training
AUDIO SEQ2LABEL AUDIO GRAPH	35.9	22.3	73.0	65.7	60.4	315M + 34.9M	Wav2vec2
	35.6	22.1	73.1	66.0	60.9	315M + 34.9M	Wav2vec2
ORACLE SEQ2LABEL ORACLE GRAPH	36.3	22.2	75.6	68.7	62.7	315M + 34.9M	Wav2vec2
	35.6	22.2	77.4	73.3	67.5	315M + 34.9M	Wav2vec2
PIPELINE SEQ2LABEL PIPELINE GRAPH PIPELINE HOPS	35.6	22.0	70.8	63.8	58.4	314M + 110M + 39.2M	Wav2vec2 + CamemBERT
	35.6	22.0	69.3	60.5	53.1	314M + 110M + 41.4M	Wav2vec2 + CamemBERT
	35.6	22.0	72.4	65.8	61.0	314M + 110M + 100M	Wav2vec2 + CamemBERT
TEXT SEQ2LABEL TEXT GRAPH TEXT HOPS	0	0	96.9	88.8	85.7	110M + 39.2M	CamemBERT
	0	0	95.1	87.4	84.0	110M + 41.4M	CamemBERT
	0	0	98.2	90.3	87.7	110M + 100M	CamemBERT

Table 1: Evaluation on the full Orféo test set with the settings described in Section 4.

Model	WER↓	CER↓	POS↑	UAS↑	LAS↑	Parameters	Pre-training
AUDIO SEQ2LABEL	31.0	18.4	77.1 77.0	70.2	65.2	315M + 34.9M	Wav2vec2
AUDIO GRAPH	30.6	18.2		70.9	66.2	315M + 34.9M	Wav2vec2
ORACLE SEQ2LABEL ORACLE GRAPH	30.9 31.4	18.6 19.2	78.3 79.8	71.9 76.0	66.2 70.4	315M + 34.9M 315M + 34.9M	Wav2vec2 Wav2vec2
PIPELINE SEQ2LABEL PIPELINE GRAPH PIPELINE HOPS	30.5	18.2	74.7	67.7	62.4	314M + 110M + 39.2M	Wav2vec2 + CamemBERT
	30.5	18.2	73.5	64.2	57.3	314M + 110M + 41.4M	Wav2vec2 + CamemBERT
	30.5	18.2	76.3	69.4	64.6	314M + 110M + 100M	Wav2vec2 + CamemBERT
TEXT SEQ2LABEL TEXT GRAPH TEXT HOPS	0	0	94.5	86.7	83.1	110M + 39.2M	CamemBERT
	0	0	96.8	88.3	84.5	110M + 41.4M	CamemBERT
	0	0	98.2	90.3	87.1	110M + 100M	CamemBERT

Table 2: Evaluation on the Valibel corpus (a subset of the test set).

						Parameters
Graph-tiny	35.74	22.32	72.97	65.86	60.79	314M + 11.7M 314M + 34.9M
Graph-base	35.63	22.10	73.13	66.05	60.90	314M + 34.9M
Graph-large	35.60	22.02	73.17	65.96	60.67	314M + 67.6M

Table 3: Comparison of parsing metrics with the graphbased architecture and different number of parameters.

 The syntactic information of the inserted token must differ from that of the corresponding word in the other sequence. Thus every insertion and deletion are considered parsing errors

Results: Speech recognition effect on parsing quality In Table 1, we observe that both graph-based and seq2label-based approaches give similar results when using no additional information, which shows that the limiting factor of the model is the speech recognition, rather than the parsing.

It is important to note that due to the nature of the speech corpus (spontaneous discussions), the WER is higher than what is typically expected on ASR benchmarks (usually containing 'read' speech). As a matter of fact, the ASR module used in our model reaches around 8 WER when trained and evaluated

on CommonVoice5.1 (Ardila et al., 2020).

Further evidence of the limitation caused by the speech recognition module is shown in Table 3: changing the number of parameters of the graph-based parser does not significantly alter performance. Additionally, in Table 2 we observe a clear improvement in all the parsing metrics when evaluating on a test corpus with better speech recognition performance. The model's speech recognition ability directly affects the number of predicted tokens (some words may be deleted or added), which in turn impacts parsing.

Results: Difference between sequence labeling approach and graph-based approach. It is somewhat surprising that on the text modality (PIPELINE), the sequence labeling parser outperforms the graph-based approach, since this is not the case on the other modality (AUDIO). However, it does not outperform a larger graph-based model with an additional character-bi-LSTM such as hops. The character bi-LSTM may mitigate the impact of out-of-vocabulary words produced by misspelling errors from the ASR.

A hypothesis about the graph-based model per-

formance on AUDIO and the ORACLE settings may be that it is able to extract more relevant syntactic information from the signal due to its global decoding than simpler approaches such as sequence labeling.

The largest gap between the two parsing approaches occur when more information about speech segmentation is given to the models (ORACLE), reducing the overall influence of the speech recognition task on parsing.

Transcribe then parse or directly parse? The **PIPELINE** approach with hops does reach a similar performance as the **AUDIO** model with our graph-based parser. However, hops is a more complex model not fully comparable to our graph-based parser. Moreover, it has 50% as many parameters as the model working directly on audio, requires 2 pretrained models, and is thus more expensive to train.

Lastly, Table 2 shows that the **AUDIO** approach outperforms the **PIPELINE** approach when the quality of the speech recognition improves. This result suggests that parsing benefits from **AUDIO** as soon as ASR reaches reasonable quality.

5 Conclusion

We introduced a graph-based speech parser that takes only the raw audio signal as input and assessed its performance in various settings and in several control experiments. We show that a simple graph-based approach with wav2vec2 audio features is on a par with or outmatches a more complex pipeline approach that requires two pretrained models.

From control experiments (**ORACLE**), we show that acquiring good quality word representations directly from speech is the main challenge for speech parsing. We will focus future work on improving the quality of word segmentation on the speech signal.

Limitations

We only evaluate our parsers on French, due to the availability of a large treebank, hence our conclusions should be interpreted with this restricted scope. We plan to extend to other languages and treebanks in future work.

We did not do a full grid search for hyperparameter tuning, due to computational resource limitations and environmental considerations, although we dedicated approximately the same computation

budget to each model in a dedicated setting. However, we acknowledge that not doing a full hyperparameter search may have affected the final performance of the parsers.

Acknowledgements

This work is part of the PROPICTO project (French acronym standing for PRojection du langage Oral vers des unités PICTOgraphiques), funded by the Swiss National Science Foundation (N°197864) and the French National Research Agency (ANR-20-CE93-0005). MC gratefully acknowledges the support of the French National Research Agency (grant ANR-23-CE23-0017-01).

References

Virginie André. 2016. Fleuron: Français langue Étrangère universitaire–ressources et outils numériques.

Rosana Ardila, Megan Branson, Kelly Davis, Michael Kohler, Josh Meyer, Michael Henretty, Reuben Morais, Lindsay Saunders, Francis Tyers, and Gregor Weber. 2020. Common voice: A massively-multilingual speech corpus. In *Proceedings of the Twelfth Language Resources and Evaluation Conference*, pages 4218–4222, Marseille, France. European Language Resources Association.

ATILF. 2020. Tcof: Traitement de corpus oraux en français. ORTOLANG (Open Resources and TOols for LANGuage) –www.ortolang.fr.

Christophe Benzitoun, Jeanne-Marie Debaisieux, and Henri-José Deulofeu. 2016. Le projet orféo: un corpus d'étude pour le français contemporain. *Corpus*, (15).

Janice Carruthers. 2013. French oral narrative corpus. Commissioning Body / Publisher: Oxford Text Archive.

Eugene Charniak and Mark Johnson. 2001. Edit detection and parsing for transcribed speech. In Second Meeting of the North American Chapter of the Association for Computational Linguistics.

Grzegorz Chrupała. 2023. Putting natural in natural language processing. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 7820–7827, Toronto, Canada. Association for Computational Linguistics.

CLESTHIA. 2018. Cfpp2000. ORTOLANG (Open Resources and TOols for LANGuage) –www.ortolang.fr.

- Emanuela Cresti, Fernanda Bacelar do Nascimento, Antonio Moreno Sandoval, Jean Veronis, Philippe Martin, and Khalid Choukri. 2004. The c-oral-rom corpus. a multilingual resource of spontaneous speech for romance languages. pages 26–28.
- Equipe DELIC, Sandra Teston-Bonnard, and Jean Véronis. 2004. Présentation du corpus de référence du français parlé. *Recherches sur le français parlé*, 18:11–42. Equipe DELIC.
- Timothy Dozat and Christopher D Manning. 2016. Deep biaffine attention for neural dependency parsing. In *International Conference on Learning Representations*.
- Michel Francard, Philippe Hambye, Anne-Catherine Simon, and Anne Dister. 2009. Du corpus à la banque de données.: Du son, des textes et des métadonnées. l'évolution de banque de données textuelles orales valibel (1989-2009). Cahiers de l'Institut de linguistique de Louvain-CILL, 33(2):113.
- Carlos Gómez-Rodríguez, Michalina Strzyz, and David Vilares. 2020. A unifying theory of transition-based and sequence labeling parsing. In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 3776–3793, Barcelona, Spain (Online). International Committee on Computational Linguistics.
- Alex Graves, Santiago Fernández, Faustino Gomez, and Jürgen Schmidhuber. 2006. Connectionist temporal classification: Labelling unsegmented sequence data with recurrent neural networks. In *Proceedings of the 23rd International Conference on Machine Learning*, ICML '06, page 369–376, New York, NY, USA. Association for Computing Machinery.
- Loïc Grobol and Benoit Crabbé. 2021. Analyse en dépendances du français avec des plongements contextualisés (French dependency parsing with contextualized embeddings). In Actes de la 28e Conférence sur le Traitement Automatique des Langues Naturelles. Volume 1 : conférence principale, pages 106–114, Lille, France. ATALA.
- Matthew Honnibal and Mark Johnson. 2014. Joint incremental disfluency detection and dependency parsing. Transactions of the Association for Computational Linguistics, 2:131–142.
- Magali Husianycia. 2011. Caractérisation de types de discours dans des situations de travail. Theses, Université Nancy 2.
- ICAR. 2017. Clapi. ORTOLANG (Open Resources and TOols for LANGuage) –www.ortolang.fr.
- Paria Jamshid Lou, Yufei Wang, and Mark Johnson. 2019. Neural constituency parsing of speech transcripts. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 2756–2765, Minneapolis, Minnesota. Association for Computational Linguistics.

- Mark Johnson and Eugene Charniak. 2004. A TAGbased noisy-channel model of speech repairs. In Proceedings of the 42nd Annual Meeting of the Association for Computational Linguistics (ACL-04), pages 33–39, Barcelona, Spain.
- Yuji Kawaguchi, Susumu Zaima, and Toshihiro Takagaki, editors. 2006. *Spoken Language Corpus and Linguistic Informatics*. John Benjamins.
- Louis Martin, Benjamin Muller, Pedro Javier Ortiz Suárez, Yoann Dupont, Laurent Romary, Éric de la Clergerie, Djamé Seddah, and Benoît Sagot. 2020. CamemBERT: a tasty French language model. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7203–7219, Online. Association for Computational Linguistics.
- Avanzi Mathieu, Béguelin Marie-José, Corminboeuf Gilles, Diémoz Federica, and Johnsen Laure Anne. (2012-2020). Corpus ofrom corpus oral de français de suisse romande. Université de Neuchâtel.
- Titouan Parcollet, Ha Nguyen, Solène Evain, Marcely Zanon Boito, Adrien Pupier, Salima Mdhaffar, Hang Le, Sina Alisamir, Natalia Tomashenko, Marco Dinarelli, Shucong Zhang, Alexandre Allauzen, Maximin Coavoux, Yannick Estève, Mickael Rouvier, Jerôme Goulian, Benjamin Lecouteux, François Portet, Solange Rossato, Fabien Ringeval, Didier Schwab, and Laurent Besacier. 2024. Lebenchmark 2.0: A standardized, replicable and enhanced framework for self-supervised representations of french speech. *Computer Speech & Language*, 86:101622.
- Patti J Price, Mari Ostendorf, Stefanie Shattuck-Hufnagel, and Cynthia Fong. 1991. The use of prosody in syntactic disambiguation. *the Journal of the Acoustical Society of America*, 90(6):2956–2970.
- Adrien Pupier, Maximin Coavoux, Benjamin Lecouteux, and Jerome Goulian. 2022. End-to-End Dependency Parsing of Spoken French. In *Proc. Interspeech* 2022, pages 1816–1820.
- Mohammad Sadegh Rasooli and Joel Tetreault. 2013. Joint parsing and disfluency detection in linear time. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*, pages 124–129, Seattle, Washington, USA. Association for Computational Linguistics.
- Mirco Ravanelli, Titouan Parcollet, Peter Plantinga, Aku Rouhe, Samuele Cornell, Loren Lugosch, Cem Subakan, Nauman Dawalatabad, Abdelwahab Heba, Jianyuan Zhong, Ju-Chieh Chou, Sung-Lin Yeh, Szu-Wei Fu, Chien-Feng Liao, Elena Rastorgueva, François Grondin, William Aris, Hwidong Na, Yan Gao, Renato De Mori, and Yoshua Bengio. 2021. SpeechBrain: A general-purpose speech toolkit. ArXiv:2106.04624.
- Michalina Strzyz, David Vilares, and Carlos Gómez-Rodríguez. 2019. Viable dependency parsing as se-

quence labeling. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 717–723, Minneapolis, Minnesota. Association for Computational Linguistics.

Michalina Strzyz, David Vilares, and Carlos Gómez-Rodríguez. 2020. Bracketing encodings for 2-planar dependency parsing. In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 2472–2484, Barcelona, Spain (Online). International Committee on Computational Linguistics.

A Training Details

Table 4 and 5 describe in more detail the hyperparameters used for each parser for the different sets of modalities.

Epoch 30 30 8	Parser	SEQ	GRAPH					
Tuning parameters Learning rate	Epoch	30	30					
Learning rate 0.0001 0.0001 Optimizer AdaDelta AdaDelta Model name LeBenchmark7K Encoder Encoder layer 3 3 Dropout 0.15 0.15 Encoder Dim 1024 1024 Activation LeakyReLU LeakyRelu Fusion LSTM Layer 2 2 Dim 500 500 Bidirectional False False Bias True True Layer 2 3 Dim 800 768 Bidirectional True True Labeler (SEQ2LABEL) Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Linear head dim 768 Layer 1	Batch size	8	8					
Optimizer Model nameAdaDelta LeBenchmark7KEncoderEncoder layer Dropout Encoder Dim Activation3 1024 LeakyReLU LeakyReLU LeakyReluFusion LSTMLayer Dim Bidirectional Bias True2 False False TrueLSTM parserLayer Dim Bidirectional2 False TrueLayer Dim Labeler (SEQ2LABEL)Dim Layer Linear head dim arc Linear head dim POS Layer Linear head dim label Dim Layer Linear head dim Layer Linear head dim768 1 768 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 2 1 1 2 1 2 1 2 2 3 3 4 5 4 5 4 5 4 5 5 5 5 6 8 1 1 1 1 1 2 1 1 2 3 4 5 4 5 5 5 5 5 6 7 6 8 1 1 1 1 2 1 2 3 4 4 5 4 5 4 5 5 5 5 5 5 5 6 7 6 8 1 1 1 1 1 1 2 1 2 3 4 3 4 5 4 5 4 5 5 5 5 6 8 5 4 5 5 5 6 8 5 5 6 8 9 <br< td=""><td>Tuning</td><td colspan="6"></td></br<>	Tuning							
Nodel name	Learning rate	0.0001	0.0001					
Encoder Encoder A	Optimizer	AdaDelta	AdaDelta					
Encoder layer 3 3 Dropout 0.15 0.15 Encoder Dim 1024 1024 Activation LeakyReLU LeakyRelu Fusion LSTM Layer 2 2 Dim 500 500 Bidirectional False False Bias True True Layer 2 3 Dim 800 768 Bidirectional True True Labeler (SEQ2LABEL) Dim 1600 1600 Layer 1 1 Linear head dim arc 846 1 Linear head dim label 19 19 Arc MLP (GRAPH) Dim 768 Layer 1 1 Linear head dim 768 Layer 1 1 Head dim 768 1 POS MLP (GRAPH) 768 1 Dim 7	Model name	LeBench	mark7K					
Dropout 0.15 0.15 Encoder Dim 1024 1024 Fusion LSTM Layer 2 2 Dim 500 500 Bidirectional False False Bias True True LSTM parser Layer 2 3 Dim 800 768 Bidirectional True True Labeler (SEQ2LABEL) Dim 1600 Layer Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 T68 Layer 1 Linear head dim 768 Layer 1 Linear head dim 768 Layer 1 1 Linear head dim 768 1 Layer 1 1 Head dim 768 1 POS MLP (GRAPH) 768	Eı	ncoder						
Encoder Dim 1024 1024 Fusion LSTM Layer 2 2 Dim 500 500 Bidirectional False False Bias True True LSTM parser Layer 2 3 Dim 800 768 Bidirectional True True Labeler (SEQ2LABEL) Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 768 Layer 1 1 Linear head dim 768 1 Label MLP (GRAPH) 768 1 Dim 768 1 Layer 1 1 Head dim 768 1 POS MLP (GRAPH) 768	Encoder layer	3	3					
LeakyReLU LeakyRelu Fusion LSTM Layer 2 2 Dim 500 500 Bidirectional False False Bias True True Layer 2 3 Dim 800 768 Bidirectional True True Labeler (SEQ2LABEL) Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 768 Layer 1 1 Linear head dim 768 1 Label MLP (GRAPH) Tom 768 Layer 1 1 Head dim 768 1 POS MLP (GRAPH) Tom 768		0.15	0.15					
Fusion LSTM	Encoder Dim	1024	1024					
Layer 2 2 Dim 500 500 Bidirectional False False Bias True True Layer 2 3 Dim 800 768 Bidirectional True True Labeler (SEQ2LABEL) Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Linear head dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) 768 Dim 768 POS MLP (GRAPH) 768	Activation	LeakyReLU	LeakyRelu					
Dim 500 500 Bidirectional False False Bias True True Layer 2 3 Dim 800 768 Bidirectional True True Labeler (SEQ2LABEL) Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Label MLP (GRAPH) Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768	Fusio	on LSTM						
Bidirectional Bias False True False True LSTM parser Layer 2 3 Dim 800 768 Bidirectional True True Labeler (SEQ2LABEL) Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Linear head dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768 POS MLP (GRAPH) Dim 768	Layer	2	2					
Bias True True LSTM parser Layer 2 3 Dim 800 768 Bidirectional True True Labeler (SEQ2LABEL) Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Label MLP (GRAPH) Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768	Dim	500	500					
Layer 2 3	Bidirectional	False	False					
Layer 2 3 Dim 800 768 Bidirectional True True Labeler (SEQ2LABEL) Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Label MLP (GRAPH) Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768	Bias	True	True					
Dim 800 768 Bidirectional True True Labeler (SEQ2LABEL) Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Linear head dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) 768 Dim 768 Dim 768	LST	LSTM parser						
Bidirectional True True Labeler (SEQ2LABEL) 1 Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Linear head dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768 POS MLP (GRAPH) 768	Layer	2	3					
Labeler (SEQ2LABEL) Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Linear head dim 768 Label MLP (GRAPH) Dim 768 Layer 1 Label MLP (GRAPH) Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim POS MLP	Dim	800	768					
Dim 1600 Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Linear head dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768 POS MLP (GRAPH) 768	Bidirectional	True	True					
Layer 1 Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Linear head dim 768 Label MLP (GRAPH) Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768	Labeler (SEQ2LABEL)						
Linear head dim arc 846 Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Linear head dim 768 Label MLP (GRAPH) Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768	Dim	1600						
Linear head dim POS 23 Linear head dim label 19 Arc MLP (GRAPH) Dim 768 Layer 1 Linear head dim 768 Label MLP (GRAPH) Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768	Layer	1						
Linear head dim label 19 Arc MLP (GRAPH) 768 Dim 768 Layer 1 Linear head dim 768 Label MLP (GRAPH) Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768	Linear head dim arc	846						
Arc MLP (GRAPH) 768	Linear head dim POS	23						
Dim 768 Layer 1 Linear head dim 768 Label MLP (GRAPH) Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768	Linear head dim label	19						
Layer 1 Linear head dim 768 Label MLP (GRAPH) 768 Layer 1 Head dim 768 POS MLP (GRAPH) 768								
Linear head dim 768 Label MLP (GRAPH) 768 Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) 768	Dim		768					
Label MLP (GRAPH) Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) Dim 768	Layer		1					
Dim 768 Layer 1 Head dim 768 POS MLP (GRAPH) 768	Linear head dim		768					
Layer 1 Head dim 768 POS MLP (GRAPH) 768 Dim 768	Label MLP (GRAPH)							
Head dim 768 POS MLP (GRAPH) 768	Dim		768					
POS MLP (GRAPH) Dim 768	Layer		1					
Dim 768	Head dim		768					
	POS MLP (GRAPH)							
Linear head dim 24	Dim		768					
	Linear head dim		24					

Table 4: AUDIO and ORACLE SEQ2LABEL and GRAPH hyperparameters.

Parser	seq2label	GRAPH	HOPS					
Epoch	40	40	40					
Batch size	32 32		32					
Tuning parameters								
Learning rate	0.001	0.001	0.00003					
optimizer	Adam	Adam	Adam					
Embedding	Last layer	Last layer	Mean First 12 layers					
Embedding dim	768	768	768					
BERT	camembert_base							
	Char Bi-LST	ТМ норѕ						
Embedding dim			128					
	Word Embedo	ding HOPS						
Embedding dim			256					
	LSTM p	arser						
Dim	768	768	512					
Layers	3	2	3					
Bidirectional	True	True	True					
	Labeler (SEQ	2LABEL)						
Dim	1536							
Layer	1							
Linear head dim arc	846							
Linear head dim POS	23							
Linear head dim label	19							
	Arc MLP (GRAPH and HOPS)							
Dim		768	1024					
Layer		1	2					
Linear head dim		768	768					
Label MLP (GRAPH)								
Dim		768	1024					
Layer		1	2					
Head dim		768	768					
POS MLP (GRAPH)								
Dim		768	1024					
Linear head dim		24	24					

Table 5: PIPELINE and TEXT SEQ2LABEL, GRAPH and PIPELINE hyperparameters.