Evolving to be Your Soulmate: Personalized Dialogue Agents with Dynamically Adapted Personas

Yi Cheng¹, Wenge Liu³, Kaishuai Xu¹, Wenjun Hou¹, Yi Ouyang², Chak Tou Leong¹, Wenjie Li¹, Xian Wu², Yefeng Zheng²

¹The Hong Kong Polytechnic University, ²Jarvis Research Center, Tencent YouTu Lab, ³Baidu Inc.

{alyssa.cheng,kaishuaii.xu,chak-tou.leong}@connect.polyu.hk,
 {kzllwg,houwenjun060}@gmail.com,cswjli@comp.polyu.edu.hk,

{yiouyang, kevinxwu, yefengzheng}@tencent.com

Abstract

Previous research on persona-based dialogue agents typically preset the agent's persona before deployment, which remains static thereafter. In this paper, we take a step further and explore a new paradigm called Self-evolving Personalized Dialogue Agents (SPDA), where the agent continuously evolves during the conversation to better align with the user's anticipation by dynamically adapting its persona. This paradigm could enable better personalization for each user, but also introduce unique challenges, which mainly lie in the process of persona adaptation. Two key issues include how to achieve *persona alignment* with the user and how to ensure smooth transition in the adaptation process. To address them, we propose a novel framework that refines the persona at hierarchical levels to progressively align better with the user in a controllable way. Experiments show that integrating the personas adapted by our framework consistently enhances personalization and overall dialogue performance across various base systems.

1 Introduction

Grounding the dialogue agent on a persona to improve conversation engagement and personalization has been a longstanding and crucial research topic within the field of dialogue systems (Zhang et al., 2018; Qian et al., 2018; Madotto et al., 2019). This grounded persona is usually defined through a text-based profile that describes various persona attributes (e.g., job, hobby, personality) (Zhang et al., 2018; Liu et al., 2020; Wang et al., 2023c). Many techniques have been proposed to allow an agent to emulate a designated persona consistently and believably (Xu et al., 2022; Shea and Yu, 2023; Shao et al., 2023; Cheng et al., 2024a).

However, a significant aspect that has not received adequate attention is *how to craft an appropriate persona for the agent that can align with the target user's anticipation*. This is particularly



Figure 1: A self-evolving personalized dialogue agent (left) continuously learns from the context and dynamically adapts its persona to better match the user (right).

crucial in scenarios that heavily rely on the affinity with the user, such as in emotional support conversations (Liu et al., 2021; Peng et al., 2022; Tu et al., 2022; Cheng et al., 2022; Deng et al., 2023) and personal AI companionship (Chaturvedi et al., 2023; Zhong et al., 2024). A well-suited persona can create an identity that the user can connect with, thereby fostering familiarity and trust. Moreover, existing works typically preset the agent's persona before deployment, which stays static thereafter (Mazaré et al., 2018; Qian et al., 2018; Madotto et al., 2019; Kim et al., 2020; Lin et al., 2021; Liu et al., 2022; Tu et al., 2023), but in real scenarios, user information is often scarce or unavailable before interactions, which is insufficient for determining the optimal agent's persona. Thus, this static approach for persona assignment renders the

personalization of the dialogue agent limited.

To take a step further towards greater personalization, we explore a new paradigm called *Selfevolving Personalized Dialogue Agents* (SPDA), where the personalization of the system continuously takes place during the interaction with the user. As shown in Figure 1, SPDA constantly evolves to better meet the user's anticipation via adjustment of its identity, personality, communication style, etc. In essence, it means that the agent's persona is dynamically adaptable. Compared to the static persona paradigm, such a self-evolving manner could elicit better personalization, long-term engagement, and deeper user connections.

Despite its advantages, SPDA also introduces unique challenges, which mainly lie in the process of dynamic persona adaptation. One key issue in this process is how to achieve persona alignment, which involves adapting the persona to better align with the user's anticipation. Such an alignment should be achieved in a progressive manner since the user information is initially sparse and gradually unfolds as the dialogue progresses. Another challenge is how to ensure smooth transition in persona adaptations. Any adjustments made to the agent's persona should not cause inconsistencies. For example, in Figure 1, the agent has already stated that they are a "software engineer", so their occupation does not allow any arbitrary modifications later and other parts of the persona should also be ensured to be compatible with this fact.

In this paper, we propose a novel persona adaptation framework to address the above issues. To ensure smooth transition, it first analyzes the current agent persona about which parts of it are still adaptable in the beginning of the persona adaptation process. Then, a hierarchical approach is adopted to refine the persona at both the attribute and profile levels. The attribute-level adaptation enables prompt adjustments in response to the newly detected user information in a lightweight manner. Meanwhile, modifications at the attribute level are also more controllable, thereby mitigating the difficulty in ensuring smooth transition. The profilelevel adaptation, on the other hand, operates periodically to further refine the persona globally by adding more authentic details to make it more comprehensive and human-like. Our contributions are summarized as follows:

• To the best of our knowledge, we are the first to explore SPDA, a new self-evolving paradigm for personalized dialogue agents.

- We propose a novel persona adaptation framework to address the challenges of persona alignment and smooth transition in SPDA.
- Extensive experiments show that integrating the personas adapted by our framework consistently enhances personalization and overall dialogue performance across various base systems.

2 Related Work

Persona-based Dialogue Agents Grounding the dialogue agent on a persona to improve engagement and personalization has been a longstanding research topic (Qian et al., 2018; Madotto et al., 2019; Kim et al., 2020; Lin et al., 2021; Liu et al., 2022). One representative works is from Zhang et al. (2018), who constructed the Persona-Chat dataset by instructing participants to engage in conversations while adopting given personas. The following studies mainly focus on how to improve the persona modeling, such as by mining extra data to complement the sparse persona attributes (Zheng et al., 2019, 2020; Wu et al., 2020; Firdaus et al., 2021; Gao et al., 2023). A more recent research topic, role-playing agents (Shao et al., 2023; Wang et al., 2023c; Xiao et al., 2023; Chen et al., 2024; Wang et al., 2023b), can be viewed as an extension of persona-based dialogue agents but with their focus mainly in the context of Large Language Models (LLMs). Our work distinguishes from the previous studies in terms of persona adaptability.

Personalized Dialogue Agents Research on personalized dialogue agents aim to tailor the agent's performance centering around the need of each user. (Li et al., 2016; Bak and Oh, 2019) improved personalization by integrating generation with an user ID embedding, while (Ma et al., 2021; Zhong et al., 2022) resorted to the user's historical data to a user representation. (Wang et al., 2019, 2023a) demonstrated the importance of tailoring the dialogue strategy planning to different users. Grounding the dialogue agent on an appropriate persona is another way to improve personalization (Zhang et al., 2018; Zheng et al., 2019; Cheng et al., 2024a), yet little attention has been paid in existing literature to the matching of users with appropriately tailored agent personas (Tu et al., 2023). Our work can be categorized to this last line of research.

3 Preliminaries

Persona Definition Following previous research on persona-based dialogues (Jandaghi et al., 2023;

Lee et al., 2022), we define a persona as a structured profile encompassing a set of *persona attributes*, which belong to multiple predefined *persona categories*. A persona attribute is a short text that describes the individual (e.g., "software engineer, specializing in developing innovative applications"). A collection of persona attributes that relate to the same aspect of an individual form one persona category. The adopted taxonomy of persona categories refer to (Dunbar et al., 1997; Xiao et al., 2023), including *family relationships, routines or habits*, etc. Please refer to appendix A for detailed definition of each persona category and example personas.

Task Formulation We formulate Self-evolving Personalized Dialogue Agents (SPDA) as follows. During the *t*-th round of interaction with the user, the agent first extracts the user information U_t from the dialogue history \mathcal{H}_t , which helps determine the user's preferred persona for the dialogue agent. Then, the agent analyzes U_t and decides whether to adjust its previous persona \mathcal{P}_{t-1} . If adjustments are necessary, it will update its persona to be \mathcal{P}_t ; otherwise, it will keep the same persona (i.e., $\mathcal{P}_t=\mathcal{P}_{t-1}$). Finally, it generates the dialogue response Y_t based on its persona \mathcal{P}_t and the dialogue history \mathcal{H}_t .

Previous research mainly focused on the last step above, that is, how to generate responses faithfully based on the persona and appropriately related to the dialogue history. For SPDA, its unique part lies in the process of persona adaptation, that is, how to dynamically adapt the agent's persona to make it align better with the user's anticipation.

Emotional Support Conversations We use the task of Emotional Support Conversations (ESC) (Liu et al., 2021; Peng et al., 2022; Tu et al., 2022; Kim et al., 2020) as the testbed for our SPDA framework. This task, which aims to provide comfort to individuals in emotional distress, serves an ideal testbed for our work for several reasons.¹ Notably, ESC involves rich persona information, where seekers tell their distressing experiences. Supporters also share their own similar experiences to express understanding, as self-disclosure is an important strategy in ESC guidelines (Hill, 2009). It is crucial for the supporter to exhibit a persona that can foster trust and connection with the seeker. In addition, emotional support conversations are relatively lengthy, allowing for a detailed observation

of SPDA's continuous adaptation effects.

4 Method

Figure 2 presents an overview of our proposed SPDA framework. It continuously tracks the user persona information throughout the dialogue process and dynamically adapts the agent persona accordingly in a hierarchical manner. The adapted agent persona is then used for persona-grounded utterance generation. In the following, we illustrate the four major steps within the framework in detail.

Detect User Persona Attributes At each dialogue round, the workflow starts with examining whether the user's previous utterance includes any new persona information about themselves. If new user persona attributes are detected, they are added to the user persona, turning into U_t . We denote the set of newly detected attributes and their corresponding categories as $\{ < c_u^i, a_u^i > \}_{i=1}^l$, where a_u^i is a persona attribute and c_u^i is the category that it belongs to. The detection is implemented with GPT-3.5 (OpenAI, 2024), where a few-shot prompt is used to encourage well-formed answers.²

Attribute-level Persona Adaptation Adaptation of the agent persona is conducted if new user persona attributes are detected. To ensure smooth transition, the adaptation process begins by analyzing which parts of the previous agent persona \mathcal{P}_{t-1} are inadaptable. Specifically, the attributes expressed in the dialogue history (e.g. "software engineer" in the example of Figure 1) are inadaptable as modifying them may cause inconsistency. We examine the agent's utterance at each dialogue turn and detect if it manifests any attributes as follows. We associate each attribute in the agent's persona with a text embedding of its content, obtained from text-embedding-ada-002 (OpenAI, 2022). For the agent's utterance, we calculate its text embedding and use it as a query to find the top-m most similar attributes. We then prompt GPT-3.5 to verify if they are manifested in the utterance. We denote the set of all expressed persona attributes as \mathcal{P}_{t-1} .

Given each newly detected user attribute a_u^i belonging to the persona category c_u^i , we match a corresponding agent attribute a_s^i in the same category c_s^i , where $c_s^i = c_u^i$. This attribute-level matching is achieved with a transformer-based conditional variational autoencoder model proposed by Fang

¹In ESC, the agent always takes the role of a supporter. In the following, we will interchangeably use the terms "agent" and "supporter," as well as "user" and "seeker."

²We provide the detailed prompt templates for all promptbased approaches discussed in this paper in the appendix.




Figure 2: Overview of our proposed SPDA framework. **Step 1:** detect new user persona attributes from the latest dialogue history; **Step 2:** match each newly detected user persona attributes with a corresponding agent attribute, and integrate it into the agent's persona if it is compatible with the existing inadaptable attributes (marked with snowflakes in the figure); **Step 3:** an optional step that occurs periodically every k turns, which globally refines the entire agent persona by adding more intricate details to make it more human-like and align better with the user; **Step 4:** use the adapted agent persona for persona-grounded utterance generation.

et al. (2021). We use this model here to enhance the diversity of the generated attributes and to mitigate the one-to-many issue in persona matching (Fang et al., 2021). It is trained with our constructed attribute-level matching data (see §5).

The matched agent attribute a_s^i then goes through compatibility check with the inadaptable attributes $\hat{\mathcal{P}}_{t-1}$ to ensure smooth transition. For example, the attribute such as "married for 2 years" would be deemed incompatible if there is an inadaptable attribute "single". This compatibility check is performed with GPT-3.5 using a few-shot prompt. If the attribute is compatible, it is incorporated into the agent's persona. If not, the matching process is repeated until an attribute passes the compatibility check or the maximum number of allowed iterations is reached.

Profile-level Persona Adaptation The attributelevel persona adaptation allows for prompt and lightweight matching in response to the newly detected user attributes. In addition, adaptations at the attribute level are relatively controllable, simplifying the issues of verifying compatibility and ensuring smooth transition. Nonetheless, merely merging the brief attributes generated by the attributelevel adaptation module often fails to create a comprehensive and authentic persona description, as shown in the "adapted agent persona" in the upper right corner of Figure 2. This can render the behavior of the dialogue agent grounded on this persona less natural and human-like.

To address this, our framework periodically performs profile-level adaptation every k turns, which globally refines the entire agent persona by adding more details. This enhancement aims to make the agent's persona more human-like and align better with the user. We implement this step with a finetuned Llama (Touvron et al., 2023). Specifically, we include the user's persona U_t , the agent's inadaptable persona attributes $\hat{\mathcal{P}}_{t-1}$, and the newly matched agent attributes at this turn in the input prompt. The model is instructed to augment these agent attributes and create an enriched persona \mathcal{P}_t . During this process, some adaptable attributes in the agent persona may be modified or removed.

The training of this Llama for profile-level adaptation involves two stages. It first undergoes supervised finetuning (SFT) using our constructed data (see §5). After that, for each sample in the SFT training set, we sample *n* candidate responses from the model through temperature sampling. In this way, we obtain $\binom{n}{2}$ pairs of responses for direct preference optimization (DPO) (Rafailov et al., 2024). We then employ GPT-4 (Bubeck et al., 2023) to compare the responses in each pair in terms of their alignment with the user and the persona comprehensiveness. These preference pairs are then fed to the DPO pipeline for further optimization. **Persona-Grounded Utterance Generation** Finally, grounded on the adapted agent persona, our framework generates the utterance at this dialogue turn. We experiment with different base models to construct the utterance generator (see §6.1), in order to investigate whether our adapted persona can consistently improve the performance across various dialogue models. Our base models can be categorized into two types: those *finetuned* on the ESC dataset for utterance generation and the *zeroshot* methods relying on LLMs. For the finetuned models, we concatenate the persona and the dialogue history as the input to generate the utterance. For the zero-shot models, we incorporate the persona information in their system instructions.

5 Data Construction

To facilitate the training for persona adaptation, we construct a persona matching dataset, which is derived from a popular ESC dataset, ESConv (Liu et al., 2021). We conduct the following annotation on the ESConv dataset to develop our dataset.

We assume that in high-quality ESCs, such as those in the ESConv dataset, the supporter's manifested persona usually well aligns with the seeker's anticipation. Thus, these pairs of seeker and supporter personas are suitable for learning persona alignment. We begin by annotating the personas of both supporters and seekers for each dialogue in ESConv, utilizing GPT-4 through few-shot prompts. Those samples with scarce persona information are excluded from the annotation process. Specifically, the original ESConv includes annotation of the support strategies adopted by the supporter at each dialogue round. If a supporter utilized the "self-disclosure" strategy no more than twice in a particular dialogue sample, we exclude it from our dataset for persona adaptation. Please refer to Table 4 in the appendix for data examples.

Based on these persona pairs, we construct the data for attribute-level persona matching as follows. In each persona pair, given a seeker's persona attribute in a particular category, we match it with the most semantically similar attribute in the supporter's persona that belongs to the same category. Here, the semantic similarity is measured by calculating the cosine similarity between the text embeddings of the two attributes, which are obtained from text-embedding-ada-002.

The profile-level persona adaptation data are developed by modifying the annotated pairs of seeker and supporter personas. Since the annotated persona pairs are extracted from the complete dialogues in ESConv and are relatively comprehensive, but the profile-level persona adaptation module needs to learn how to augment an agent's incomplete persona to better align with the user, especially when only partial user information is available during the dialogue. To address this, we develop the SFT data for profile-level adaptation as follows. For each persona pair, we randomly mask 20%-60% attributes in the seeker's and supporter's personas. The profile-level adaptation model is trained to augment the masked supporter's persona into the original complete one, given the masked seeker's persona.

6 Experiments

6.1 Experimental Setup

Dataset Statistics We use the processed ESConv dataset (Liu et al., 2021) as described in §5 to facilitate our experiments. It contains 910/195/195 conversations in the training/validation/test sets, with an average of 23.4 dialogue turns in each conversation. After our persona annotation process, we obtain a total of 3635/725/729 samples in the training/validation/test sets for attribute-level persona matching, and 1863/420/378 samples in the training/validation/test sets for profile-level persona adaptation. The average number of attributes present in the annotated personas of seekers and supporters are 10.33 and 10.46, respectively. On average, each attribute within the seeker's persona comprises 6.03 words, while those within the supporter's persona contain 7.78 words.

Base Models for Persona-Grounded Utterance Generation We experiment with five different base models to construct the utterance generator, in order to investigate whether our adapted persona can consistently improve the performance across various dialogue models. These base models can be categorized into two types. The first is the finetuned models which are optimized on the ESConv dataset for persona-grounded utterance generation, including: BlenderBot (Roller et al., 2021) and Llama-3-8B-Instruct (LLaMA3-SFT) (Meta AI, 2024). The second type is *zero-shot* methods relying on LLMs, including: Llama-3-8B-Instruct (LlaMA3-INS) (Meta AI, 2024), Gemini-1.0-pro-002 (Gemini-1.0) (Gemini Team, 2023), and GPT-3.5-turbo-0105 (GPT-3.5) (OpenAI, 2024).

Method		NLG Metrics				Diversity			Personalization	
Base Model	Persona	BL-1	BL-2	BL-3	RG-L	D-1	D-2	D-3	P-Cover	A-Cover
	w/o Persona	20.84	8.33	3.93	15.25	3.68	17.33	32.83	2.771	2.601
DlandarDat	Supporter	20.81	8.38	3.95	15.00	3.43	16.66	32.07	2.693	2.531
BlenderBot	Pre-Match	19.44	7.13	3.21	14.15	3.67	18.53	36.70	2.732	2.342
	Ours	21.10	8.45	4.01	15.00	3.79	19.65	37.91	2.811	2.683
	w/o Persona	15.08	5.88	2.70	15.51	5.73	30.24	55.92	3.030	2.198
LLANA 2 CET	Supporter	14.85	5.98	2.94	15.91	5.66	29.31	55.17	2.978	2.140
LlaMA3-SFT	Pre-Match	15.44	6.12	2.94	15.86	5.64	29.73	55.58	3.017	2.188
	Ours	15.70	6.37	3.08	16.00	5.78	30.41	56.37	3.061	2.235
	w/o Persona	9.13	2.61	0.43	10.21	2.89	21.93	46.15	2.610	2.390
LlaMA3-INS	Supporter	11.96	3.10	1.13	11.68	3.51	24.24	46.59	2.751	2.664
LIawiA5-IINS	Pre-Match	11.81	3.02	1.05	11.56	3.30	22.10	42.49	2.657	2.535
	Ours	12.19	3.22	1.16	11.76	3.85	26.94	51.25	2.844	2.732
	w/o Persona	15.71	5.64	2.44	14.42	3.87	23.40	46.35	2.822	2.471
Gemini-1.0	Supporter	18.55	6.45	2.74	14.36	4.71	25.63	47.08	3.024	2.623
Gemmi-1.0	Pre-Match	18.49	6.29	2.61	14.03	4.85	26.29	48.03	3.042	2.647
	Ours	18.96	6.65	2.92	14.25	5.01	26.99	48.86	3.058	2.657
	w/o Persona	16.28	5.38	2.31	14.16	4.17	26.67	46.21	2.883	2.627
GPT-3.5	Supporter	18.15	5.83	2.54	14.02	5.08	27.41	48.94	3.056	2.853
OF 1-5.5	Pre-Match	18.27	5.84	2.51	14.17	4.89	26.91	48.56	3.029	2.821
	Ours	18.47	6.12	2.78	14.21	5.34	29.24	52.17	3.108	2.950

Table 1: Static evaluation results on the ESConv dataset. "Base Model" refers to the model for persona-grounded utterance generation, which is evaluated under four persona setting. For instance, the method in the last row (i.e., GPT-3.5 + Ours) employs GPT-3.5 for utterance generation grounded on the persona produced by our framework.

Persona Settings Each base model is evaluated under the following persona settings, respectively: (1) **w/o Persona** does not ground the model on any personas and generates responses purely based on the dialogue history; (2) **Supporter** uses a uniform persona for all dialogues, which describes a fictional character that is professional counselor; (3) **Pre-Match** adopts a similar setting in (Tu et al., 2023), which matches each user with a suitable supporter persona before the dialogue starts and keeps it static thereafter; (4) **Ours** uses the persona produced by our framework, which is dynamically adapted during the conversation.

Implementation Details In our framework, all prompt-based functions are implemented with GPT-3.5-turbo-0105. The implementation of the attribute-level matching model follows (Fang et al., 2021). The profile-level adaptation module is implemented with Llama-3-8B. It is finetuned through LoRA (Hu et al., 2022), with the dropout probability set as 0.05. The profile-level adaptation is conducted periodically every *k* turns (i.e., k=4).

For the "Supporter" persona setting, we meticulously compose 8 versions of personas with many related characteristics that make them skilled at emotional support, and use the optimal one for evaluation. For the "Pre-Match" setting, we use GPT-3.5 to generate the agent persona that matches the user in a few-shot way, based on the pre-chat survey of the user information included in the ES-Conv dataset. The few-shot examples are selected from the matching instances provided in (Tu et al., 2023). More details are provided in the appendix.

6.2 Static Evaluation

We perform a static evaluation by analyzing the generated results from different perspectives. We employ NLG metrics, including BLEU-1/2/3 (**BL-1/2/3**) (Papineni et al., 2002) and ROUGE-L (**RG-L**) (Lin, 2004), to measure the similarity of the generated utterances and the ground-truth ones in the dataset. We also adopt Distinct-1/2/3 (**D-1/2/3**) to measure the generation diversity. In addition, following (Lian et al., 2019; Wu et al., 2021; Ma et al., 2021), we evaluate the personalization of the generated utterances with the metrics of profile-level and attribute-level persona coverage (**P/A-Cover**). They examine whether the utterances exhibit similar persona as the supporter in the reference dialogues (see appendix D for details).

As shown in Table 1, we can see that integrating

Method	NLG Metrics				Diversity			Personalization	
Methou	BL-1	BL-2	BL-3	RG-L	D-1	D-2	D-3	P-Cover	A-Cover
w/o persona	16.28	5.38	2.31	14.16	4.17	26.67	46.21	2.883	2.627
+ Prof-level-SFT	18.49	5.80	2.59	14.15	4.68	25.19	46.18	3.030	2.821
+ Prof-level-DPO	18.29	5.98	2.62	14.15	5.27	28.73	51.18	3.058	2.832
+ Attr-level	18.20	6.01	2.65	14.06	5.35	29.10	51.60	3.076	2.894
Ours	18.47	6.12	2.78	14.21	5.34	29.24	52.17	3.108	2.950

Table 2: Ablation study of our SPDA framework. The base model for utterance generation is GPT-3.5.




Figure 3: Results of human evaluation on the simulated dialogues with the evaluated agents.

the persona produced by our framework can consistently improve the performance across various base models. Moreover, compared with the two static persona settings (i.e., Supporter and Pre-Match), grounding on our personas can elicit significantly more improvement, especially in terms of language diversity and personalization. This suggests our dynamically adapted paradigm can better tailor to different user's situation and generate more customized responses compared with the traditional approach of static persona assignment. Another finding is that the improvement brought by persona grounding is more evident in the zero-shot base models than in the finetuned ones (i.e., BlenderBot and LlaMA3-SFT). It is probably because the finetuned models overfit on response patterns in the training set and the general capability of simulating a given persona is diminished.

6.3 Interactive Evaluation

We conduct interactive evaluation of different persona settings through a similar practice as done in (Li et al., 2023; Cheng et al., 2024b). Specifically, we construct another agent to play the role of an emotional support seeker by prompting GPT-3.5, and use it to simulate conversations with the assessed model. As illustrated in §5, we annotated the seekers' personas in the ESConv dataset. The seeker agent is grounded on these personas from the test set for interactions with the evaluated systems. Given a pair of conversations produced by conversing with two different models, we manually compare which one is better in the following dimensions: (1) Naturalness: which model's utterances are more natural and human-like; (2) Affinity: which model exhibits a persona that elicits greater affinity and deeper connection with the user; (3) Personalization: which model's responses are more personalized. More specificaly, we define personalization as "being tailored to the individual user's situation, rather than being broadbased and universally applicable to a wide variety of users". Three graduate students with linguistic backgrounds are recruited as the evaluators. We use GPT-3.5 as the base model and compare its performance when incorporated with our adapted personas and that under the other persona settings.

The evaluation results are presented in Figure 3. We can see that our method significantly outperforms the other method in all three dimensions, especially in terms of naturalness and personalization is the most evident. This suggests that our dynamically adapted personas are effective in creating a persona that facilitates more human-like and personalized interactions with the user. Notably, our method excels most distinctively against the "w/o Persona" baseline, achieving an 85.9% winning rate in the affinity dimension. We find that the responses from LLMS without persona grounding are usually very impersonal and are more inclined to provide helpful suggestions rather than emotional caring to the seeker (see §7 for further discussion). This suggests the importance of grounding the LLM on an appropriate persona in those scenarios demanding affinity with the user.




Figure 4: The persona alignment scores of the adapted personas throughout different turns of the conversations.

6.4 Ablation Study

In the ablation study, we compare our method with its following variants: (1) **Prof-level-SFT** solely conducts profile-level persona adaptation, optimized via SFT without DPO; (2) **Prof-level-DPO** only adopts profile-level adaptation, optimized through SFT and DPO successively; (3) **Attr-level** only involves attribute-level adaptation. The base model for the ablation study is GPT-3.5. The results are presented in Table 2.

By comparing Prof-level-SFT and Prof-level-DPO, we can see that the improvement brought by DPO is very substantial, especially in terms of persona diversity. Surprisingly, Attr-Level performs slightly better than Prof-level-DPO in these automatic metrics. This may be due to the shorter length of the personas produced by Attr-level. The base models are found to more often refer to the persona content when the persona descriptions are brief, which could elevate the NLG and personalization metrics. Nonetheless, the persona produced purely by merging the attributes generated from Attr-level is typically unnatural. In contrast, Prof-level-DPO can generate far more authentic and comprehensive personas, resulting in a more human-like and natural dialogue system performance. Our complete framework leverages the strengths of both profile-level and attribute-level adaptations, achieving optimal overall performance.

6.5 Analysis of Adapted Personas

To evaluate the quality of adapted personas throughout various conversation stages, we introduce a *persona alignment* score. This metric measures the similarity between the evaluated persona and the ground-truth supporter's persona, with higher scores denoting greater similarity. The detailed measurement of the persona alignment score is illustrated in appendix D. We compute this score (4rd round) User: Been feeling lonely due to this pandemic. w/o Persona: It's understandable to feel lonely during these challenging times. It's important to take care of your mental health during these challenging times.

Ours: I understand. The pandemic has been tough. <u>I've felt that loneliness too.</u> But we're in this together. How have you been coping? (*agent persona attribute: has experienced anxiety related to the COVID-19 situation*)

Ours: Getting a dog can be a wonderful idea for companionship. Have you considered rescuing one from a shelter? I had a pet from there once, and it was a great experience. (agent persona attribute: love animals, a member of an animal rescue organization)

- (8th round) User: Oh ok. There is a lock down from where I live, how about you?
- w/o Persona: I don't have a lockdown where I am, but I understand how tough it can be. If you need someone to talk to during this time, I'm here for you.

Ours: Yes, <u>we're also in a lockdown</u>. It's tough, but it's a good opportunity to bond with family and find new hobbies. (*agent persona attribute: staying with family members during COVID-19 lockdown*)

Table 3: Case study (the fourth, sixth, and eighth rounds of an example dialogue on the ESConv dataset.

for adapted personas at different dialogue turns within our framework and compare these scores with those from Prof-level-DPO, Attr-level, and personas used in Supporter and Pre-Match settings.

As shown in Figure 4, the persona alignment scores for our adapted personas improve progressively during conversations. Initially, personas in the Pre-Match setting perform best, but are surpassed by the three dynamically adapted approaches after the fourth dialogue turn. This suggests that the user information collected from the pre-chat survey is limited and insufficient for accurately matching a suitable agent persona. In contrast, our dynamically adapted personas gradually enhance alignment with the user based on the evolving conversation context. Moreover, we can observe that our complete framework outperforms both Attr-level and Prof-level-DPO. This suggests that our hierarchical framework can well combine their strengths and elicit the best performance.

7 Case Study

The case study in Table 3 presents several example utterances generated by GPT-3.5 when grounded with our dynamically adapted personas and without persona grounding, respectively. We can see that incorporating our adapted personas can lead to

⁽⁶th round) **User**: I was thinking about getting a dog, is that a good idea?

w/o Persona: Getting a dog can be a wonderful idea for companionship and emotional support. Just be sure to consider the responsibilities involved.

more empathetic and personalized interactions than responses without persona grounding. For example, aligning the agent's circumstances with the user, as shown in the lockdown example, fosters a sense of connection and relatability. In addition, inclusion of authentic persona details like being a member of an animal rescue organization, prompts the agent's behavior of advocating for pet adoption from shelters, which further humanize the interaction and make the responses more engaging. In comparison, the responses generated without persona grounding, while generally supportive, lack a personal touch and are much more generic.

8 Conclusion

In this paper, we proposed a novel self-evolving paradigm for personalized dialogue agents called SPDA. Extensive experiments showed that SPDA can more significantly improve the naturalness, affinity, and personalization of dialogue agents than the traditional static persona approaches. In a broader sense, SPDA shows potential in advancing the longstanding vision of conversational AI serving as enduring virtual companions for humans. Promising future directions include integrating SPDA with recent progress in continuous memory updates (Zhong et al., 2024; Li et al., 2024), which could further enhance the long-term engagement and adaptability of dialogue agents.

9 Limitations

Our work introduces SPDA, an innovative selfevolving paradigm for personalized agents. As a pioneer work on this topic, this paper is only able to explore a limited scope and there are still some open questions that remain under-explored in this self-evolving paradigm. For example, our work lacks analysis of the SPDA's performance in more realistic and long-term scenarios. Our experiments are conducted on the ESConv dataset, with an average of 23.4 turns in each dialogue. More challenging issues might arise from more long-term evolution in the SPDA paradigm, such as the management of growing persona information. Additionally, it is also worth exploring how to maintain the adaptation efficiency during the self-evolving process. In other words, the time and resource cost for persona adaptation should be taken into consideration, as they can directly influence the overall user experience.

10 Ethics Statement

The data used in this work is all curated from the ESConv dataset. It is a publicly available dataset and has been carefully processed before release to ensure it contain no sensitive or private information. We strictly adhere to the terms of use and ensure that the data is used for research purposes only. In addition, we also follow the protocols for academic use when using the open-sourced LLMs in this paper, including LlaMA and BlenderBot. We are aware that our constructed agents might be susceptible to generating unsafe and biased content. Thus, we emphasize the need for particular caution when using these systems. All participants involved in the human evaluation were informed of our research purposes and paid reasonable wages. We also employed Al assistants, such as Copilot and ChatGPT, to assist in our coding and paper-writing processes.

References

- JinYeong Bak and Alice Oh. 2019. Variational hierarchical user-based conversation model. In *Proceedings* of the Conference on Empirical Methods in Natural Language Processing and the International Joint Conference on Natural Language Processing, pages 1941–1950. Association for Computational Linguistics.
- Sébastien Bubeck, Varun Chandrasekaran, Ronen Eldan, Johannes Gehrke, Eric Horvitz, Ece Kamar, Peter Lee, Yin Tat Lee, Yuanzhi Li, Scott Lundberg, et al. 2023. Sparks of artificial general intelligence: Early experiments with GPT-4. *arXiv preprint arXiv:2303.12712*.
- Rijul Chaturvedi, Sanjeev Verma, Ronnie Das, and Yogesh K Dwivedi. 2023. Social companionship with artificial intelligence: Recent trends and future avenues. *Technological Forecasting and Social Change*, 193:122634.
- Jiangjie Chen, Xintao Wang, Rui Xu, Siyu Yuan, Yikai Zhang, Wei Shi, Jian Xie, Shuang Li, Ruihan Yang, Tinghui Zhu, et al. 2024. From persona to personalization: A survey on role-playing language agents. *arXiv preprint arXiv:2404.18231*.
- Chuanqi Cheng, Quan Tu, Wei Wu, Shuo Shang, Cunli Mao, Zhengtao Yu, and Rui Yan. 2024a. "in dialogues we learn": Towards personalized dialogue without pre-defined profiles through in-dialogue learning. *arXiv preprint arXiv:2403.03102*.
- Yi Cheng, Wenge Liu, Wenjie Li, Jiashuo Wang, Ruihui Zhao, Bang Liu, Xiaodan Liang, and Yefeng Zheng. 2022. Improving multi-turn emotional support dialogue generation with lookahead strategy planning.

In Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing, pages 3014–3026.

- Yi Cheng, Wenge Liu, Jian Wang, Chak Tou Leong, Yi Ouyang, Wenjie Li, Xian Wu, and Yefeng Zheng. 2024b. Cooper: Coordinating specialized agents towards a complex dialogue goal. In *Proceedings of the AAAI Conference on Artificial Intelligence*.
- Yang Deng, Wenxuan Zhang, Yifei Yuan, and Wai Lam. 2023. Knowledge-enhanced mixed-initiative dialogue system for emotional support conversations. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 4079–4095. Association for Computational Linguistics.
- Robin IM Dunbar, Anna Marriott, and Neil DC Duncan. 1997. Human conversational behavior. *Human nature*, 8:231–246.
- Le Fang, Tao Zeng, Chaochun Liu, Liefeng Bo, Wen Dong, and Changyou Chen. 2021. Transformerbased conditional variational autoencoder for controllable story generation. *arXiv preprint arXiv:2101.00828*.
- Mauajama Firdaus, Umang Jain, Asif Ekbal, and Pushpak Bhattacharyya. 2021. SEPRG: Sentiment aware emotion controlled personalized response generation. In Proceedings of the 14th International Conference on Natural Language Generation, pages 353–363. Association for Computational Linguistics.
- Silin Gao, Beatriz Borges, Soyoung Oh, Deniz Bayazit, Saya Kanno, Hiromi Wakaki, Yuki Mitsufuji, and Antoine Bosselut. 2023. PeaCoK: Persona commonsense knowledge for consistent and engaging narratives. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6569–6591. Association for Computational Linguistics.
- Google Gemini Team. 2023. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.
- Clara E Hill. 2009. *Helping skills: Facilitating, exploration, insight, and action.* American Psychological Association.
- Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *The Tenth International Conference on Learning Representations*.
- Pegah Jandaghi, XiangHai Sheng, Xinyi Bai, Jay Pujara, and Hakim Sidahmed. 2023. Faithful persona-based conversational dataset generation with large language models. *arXiv preprint arXiv:2312.10007*.
- Hyunwoo Kim, Byeongchang Kim, and Gunhee Kim. 2020. Will I sound like me? Improving persona

consistency in dialogues through pragmatic selfconsciousness. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing*, pages 904–916. Association for Computational Linguistics.

- Young-Jun Lee, Chae-Gyun Lim, Yunsu Choi, Ji-Hui Lm, and Ho-Jin Choi. 2022. PersonaChatGen: Generating personalized dialogues using GPT-3. In *Proceedings of the 1st Workshop on Customized Chat Grounding Persona and Knowledge*, pages 29–48. Association for Computational Linguistics.
- Guohao Li, Hasan Abed Al Kader Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. 2023. CAMEL: Communicative agents for "mind" exploration of large scale language model society. *arXiv preprint arXiv:2303.17760.*
- Jiwei Li, Michel Galley, Chris Brockett, Georgios P. Spithourakis, Jianfeng Gao, and William B. Dolan.
 2016. A persona-based neural conversation model. In Proceedings of the Annual Meeting of the Association for Computational Linguistics, Volume 1: Long Papers. The Association for Computer Linguistics.
- Yuanchun Li, Hao Wen, Weijun Wang, Xiangyu Li, Yizhen Yuan, Guohong Liu, Jiacheng Liu, Wenxing Xu, Xiang Wang, Yi Sun, et al. 2024. Personal LLM agents: Insights and survey about the capability, efficiency and security. *arXiv preprint arXiv:2401.05459*.
- Rongzhong Lian, Min Xie, Fan Wang, Jinhua Peng, and Hua Wu. 2019. Learning to select knowledge for response generation in dialog systems. *arXiv preprint arXiv:1902.04911*.
- Chin-Yew Lin. 2004. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81.
- Zhaojiang Lin, Zihan Liu, Genta Indra Winata, Samuel Cahyawijaya, Andrea Madotto, Yejin Bang, Etsuko Ishii, and Pascale Fung. 2021. XPersona: Evaluating multilingual personalized chatbot. In *Proceedings* of the 3rd Workshop on Natural Language Processing for Conversational AI, pages 102–112, Online. Association for Computational Linguistics.
- Qian Liu, Yihong Chen, Bei Chen, Jian-Guang Lou, Zixuan Chen, Bin Zhou, and Dongmei Zhang. 2020. You impress me: Dialogue generation via mutual persona perception. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics*, pages 1417–1427. Association for Computational Linguistics.
- Siyang Liu, Chujie Zheng, Orianna Demasi, Sahand Sabour, Yu Li, Zhou Yu, Yong Jiang, and Minlie Huang. 2021. Towards emotional support dialog systems. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), pages 3469–3483.

- Yifan Liu, Wei Wei, Jiayi Liu, Xianling Mao, Rui Fang, and Dangyang Chen. 2022. Improving personality consistency in conversation by persona extending. In Proceedings of the 31st ACM International Conference on Information & Knowledge Management, page 1350–1359. Association for Computing Machinery.
- Zhengyi Ma, Zhicheng Dou, Yutao Zhu, Hanxun Zhong, and Ji-Rong Wen. 2021. One chatbot per person: Creating personalized chatbots based on implicit user profiles. In *The International ACM SIGIR Conference on Research and Development in Information Retrieva*, pages 555–564. ACM.
- Andrea Madotto, Zhaojiang Lin, Chien-Sheng Wu, and Pascale Fung. 2019. Personalizing dialogue agents via meta-learning. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 5454–5459. Association for Computational Linguistics.
- Pierre-Emmanuel Mazaré, Samuel Humeau, Martin Raison, and Antoine Bordes. 2018. Training millions of personalized dialogue agents. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 2775–2779. Association for Computational Linguistics.
- LlaMA Team Meta AI. 2024. Introducing Meta Llama 3: The most capable openly available LLM to date. https://ai.meta.com/blog/meta-llama-3/.
- OpenAI. 2022. New and improved embedding model. https://openai.com/blog/new-and-improved-embedding-model.
- OpenAI. 2024. ChatGPT (January 25 version) [Large language model]. https://openai.com/index/new-embedding-models-and-api-updates/.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. BLEU: A method for automatic evaluation of machine translation. In *Proceedings* of the 40th annual meeting of the Association for Computational Linguistics, pages 311–318.
- Wei Peng, Yue Hu, Luxi Xing, Yuqiang Xie, Yajing Sun, and Yunpeng Li. 2022. Control globally, understand locally: A global-to-local hierarchical graph network for emotional support conversation. In *Proceedings of the 30th International Joint Conference on Artificial Intelligence*.
- Yunchen Pu, Zhe Gan, Ricardo Henao, Xin Yuan, Chunyuan Li, Andrew Stevens, and Lawrence Carin. 2016. Variational autoencoder for deep learning of images, labels and captions. *Advances in neural information processing systems*, 29.
- Qiao Qian, Minlie Huang, Haizhou Zhao, Jingfang Xu, and Xiaoyan Zhu. 2018. Assigning personality/profile to a chatting machine for coherent conversation generation. In *Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence*, pages 4279–4285. International Joint Conferences on Artificial Intelligence Organization.

- Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2024. Direct preference optimization: Your language model is secretly a reward model. *Advances in Neural Information Processing Systems*, 36.
- Stephen Roller, Emily Dinan, Naman Goyal, Da Ju, Mary Williamson, Yinhan Liu, Jing Xu, Myle Ott, Eric Michael Smith, Y-Lan Boureau, and Jason Weston. 2021. Recipes for building an open-domain chatbot. In Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume, pages 300–325. Association for Computational Linguistics.
- Yunfan Shao, Linyang Li, Junqi Dai, and Xipeng Qiu. 2023. Character-LLM: A trainable agent for roleplaying. In Proceedings of the Conference on Empirical Methods in Natural Language Processing, pages 13153–13187. Association for Computational Linguistics.
- Ryan Shea and Zhou Yu. 2023. Building persona consistent dialogue agents with offline reinforcement learning. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 1778–1795. Association for Computational Linguistics.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.
- Quan Tu, Chuanqi Chen, Jinpeng Li, Yanran Li, Shuo Shang, Dongyan Zhao, Ran Wang, and Rui Yan. 2023. CharacterChat: Learning towards conversational ai with personalized social support. *arXiv preprint arXiv:2308.10278*.
- Quan Tu, Yanran Li, Jianwei Cui, Bin Wang, Ji-Rong Wen, and Rui Yan. 2022. MISC: A mixed strategyaware model integrating COMET for emotional support conversation. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 308–319. Association for Computational Linguistics.
- Jian Wang, Yi Cheng, Dongding Lin, Chak Leong, and Wenjie Li. 2023a. Target-oriented proactive dialogue systems with personalization: Problem formulation and dataset curation. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pages 1132–1143. Association for Computational Linguistics.
- Xintao Wang, Yaying Fei, Ziang Leng, and Cheng Li. 2023b. Does role-playing chatbots capture the character personalities? Assessing personality traits for role-playing chatbots. *arXiv preprint arXiv:2310.17976*.

- Xuewei Wang, Weiyan Shi, Richard Kim, Yoojung Oh, Sijia Yang, Jingwen Zhang, and Zhou Yu. 2019. Persuasion for good: Towards a personalized persuasive dialogue system for social good. In *Proceedings* of the 57th Annual Meeting of the Association for Computational Linguistics, pages 5635–5649.
- Zekun Moore Wang, Zhongyuan Peng, Haoran Que, Jiaheng Liu, Wangchunshu Zhou, Yuhan Wu, Hongcheng Guo, Ruitong Gan, Zehao Ni, Man Zhang, et al. 2023c. RoleLLM: Benchmarking, eliciting, and enhancing role-playing abilities of large language models. *arXiv preprint arXiv:2310.00746*.
- Chien-Sheng Wu, Andrea Madotto, Zhaojiang Lin, Peng Xu, and Pascale Fung. 2020. Getting to know you: User attribute extraction from dialogues. In *Proceedings of the Twelfth Language Resources and Evaluation Conference*, pages 581–589. European Language Resources Association.
- Yuwei Wu, Xuezhe Ma, and Diyi Yang. 2021. Personalized response generation via generative split memory network. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 1956–1970.
- Yang Xiao, Yi Cheng, Jinlan Fu, Jiashuo Wang, Wenjie Li, and Pengfei Liu. 2023. How far are we from believable AI agents? A framework for evaluating the believability of human behavior simulation. *arXiv* preprint arXiv:2312.17115.
- Xinchao Xu, Zhibin Gou, Wenquan Wu, Zheng-Yu Niu, Hua Wu, Haifeng Wang, and Shihang Wang. 2022. Long time no see! Open-domain conversation with long-term persona memory. In *Findings of the Association for Computational Linguistics: ACL 2022*, pages 2639–2650. Association for Computational Linguistics.
- Saizheng Zhang, Emily Dinan, Jack Urbanek, Arthur Szlam, Douwe Kiela, and Jason Weston. 2018. Personalizing dialogue agents: I have a dog, do you have pets too? In *Proceedings of the Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2204–2213. Association for Computational Linguistics.
- Tiancheng Zhao, Ran Zhao, and Maxine Eskenazi. 2017. Learning discourse-level diversity for neural dialog models using conditional variational autoencoders. In Proceedings of the Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 654–664.
- Yinhe Zheng, Guanyi Chen, Minlie Huang, Song Liu, and Xuan Zhu. 2019. Personalized dialogue generation with diversified traits. *arXiv preprint arXiv:1901.09672*.
- Yinhe Zheng, Rongsheng Zhang, Minlie Huang, and Xiaoxi Mao. 2020. A pre-training based personalized dialogue generation model with persona-sparse data. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 9693–9700.

- Hanxun Zhong, Zhicheng Dou, Yutao Zhu, Hongjin Qian, and Ji-Rong Wen. 2022. Less is more: Learning to refine dialogue history for personalized dialogue generation. In *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 5808–5820. Association for Computational Linguistics.
- Wanjun Zhong, Lianghong Guo, Qiqi Gao, He Ye, and Yanlin Wang. 2024. Memorybank: Enhancing large language models with long-term memory. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 38, pages 19724–19731.

A Persona Structure Details

We define a persona as a structured profile that encompass a set of *persona attributes*, which belong to multiple predefined *persona categories*. A persona attribute is a short text that describe the individual (e.g., "software engineer, specializing in developing innovative applications"). A collection of persona attributes that relate to the same aspect of an individual form one persona category. Table 4 present two persona examples.

Our adopted taxonomy of persona categories refer to (Dunbar et al., 1997; Xiao et al., 2023). These categories distill from the common topics of human conversations categorized by Dunbar et al. (1997) based on extensive observational studies. Specifically, we consider seven categories as follows:

- **Gender**: This category defines the gender identity of the persona. It can include male, female, non-binary, or any other gender identity.
- Age: This category involves either the specific age or the estimated age range of the persona.
- **Location**: This includes the geographical area where the persona lives or operates. It could be as broad as a country or continent, or as specific as a city or neighborhood.
- Occupation: This details the persona's current job and work experience. It includes the industry, role, and years of experience, providing insights into the persona's skills, daily activities, and professional challenges.
- Education: This encompasses the educational background of the persona, including highest level of formal education achieved, fields of study, and significant school experiences.
- Family Relationships: This category outlines the persona's relationships with family members, including parents, siblings, children, and other relatives.

Category	Seeker's Persona Attributes	Agent's Persona Attributes			
Gender	male	/			
Age	possibly around 30 years old	possibly around 40 50 years old			
Location	USA	/			
Occupation	works in IT; financial instability due to COVID, facing debts	previously owned a small housecleaning business; experienced in business management;			
		has gone through the process of establishing and run- ning a small business			
Education	major in computer science	might have an educational background in business administration			
Family Relationships	/	1			
Routines or Habits	allocates weekends for freelance projects	engages in conversations offering advice and support, suggesting a habit of being helpful to others			
Goals or Plans	start their own business; focus on small scale projects from out- sourcing in Information Technology	has experience with business planning and operations			
Social Relationships	active in local tech meetups and online forums	likely has a network of people through past business experiences; comfortable in social interactions, particularly in of- fering support			
Personality Traits	self-motivated; approachable	problem-solver; understanding; supportive			
Other Experiences	7	has experienced financial challenges like debt			

Table 4: An example pair of the seeker's and the supporter's personas annotated on the ESConv dataset.

- Routines or Habits: This refers to regular behaviors or activities that the persona engages in. These can include morning routines, workout schedules, habitual meals, or recurring social activities.
- Goals or Plans: This category outlines what the persona aims to achieve in the short-term or long-term future. Goals might be personal, such as achieving a fitness milestone, or professional, like aiming for a promotion or starting a business, reflecting the persona's aspirations and motivations.
- Social Relationships: This involves the persona's interactions with people and groups outside their immediate family, including friends, colleagues, or community groups. This category gives insight into the persona's social network, support system, and conflict-handling strategies.
- **Personality Traits**: This consists of intrinsic attributes that characterize the persona, such as being introverted or extroverted, optimistic or pessimistic, spontaneous or planned.
- Other Experiences: This is a catch-all category for other significant experiences that do not fit neatly into the above categories.

B Implementation Details

In our framework, all prompt-based functions are implemented with GPT-3.5-turbo-0105. All prompt

templates are provided in appendix E. The implementation of the attribute-level matching model follows (Fang et al., 2021). This model is a transformer-based CVAE (Pu et al., 2016; Zhao et al., 2017), which uses two GPT-2 as its encoder and decoder, respectively. We finetune it on our attribute-level matching data for 10 epochs and select the checkpoint that achieves the lowest perplexity on the validation set for evaluation. The profile-level adaptation module is implemented with Llama-3-8B. It is finetuned through LoRA (Hu et al., 2022), with the dropout probability in the LoRA layers as 0.05. We train it for 2 epochs on our profile-level adaptation dataset. To construct the DPO data for profile-level adaptation, we sample 4 candidate responses from the finetuned model with the temperature set to be 0.8. The profile-level adaptation is conducted periodically every k turns (i.e., k=4). The DPO process goes through 4 epochs.

The two finetuned base models (i.e., Blender-Bot and LlaMA3-SFT) are trained on the ESConv dataset for utterance generation. BlenderBot is trained for 15 epochs under different persona setting, respectively, and the checkpoint that achieves the best BLEU-2 on the validation set is used for evaluation. LLaMA3-SFT is trained only for 1 epoch, as we find that it can easily overfit on the dataset. For all the base models, we set their temperature as 0.8 and top p as 0.9 during inference.

For the Supporter persona setting, we meticu-

lously compose 8 versions of personas with many caring personalities and related experiences that make them skilled at emotional support. We present one of the examples in Listing 9. The optimal one on the validation set is used for evaluation. For the Pre-Match setting, we use GPT-3.5 to generate the supporter's persona that matches the user in a few-shot way, based on the pre-chat survey of the user information included in the original ES-Conv dataset. The few-shot examples are selected from the matching instances provided in (Tu et al., 2023).

The hardware we employ is two NVIDIA RTX A6000. The training of the attribute-level module requires around 1 hours. For the profile-level module, SFT takes around 2 hours and the DPO stage takes around 4 hours. Finetuning BlenderBot and LlaMA3-SFT takes about 3 hours and 1 hour, respectively.

C Evaluation Details

P/A-Cover Metrics In §6.2, we use the metrics of profile-level and attribute-level persona coverage (P/A-Cover), to examine whether the utterances exhibit similar persona as the supporter in the reference dialogues. Formally, suppose the support's persona in the reference dialogue is P, which includes the attributes $\{a_1, a_2, ..., a_l\}$. Given a generated response y, A-Cover is defined as:

$$\operatorname{A-Cover}(y, P) = \max_{\tilde{a}_j \in \tilde{P}} (\operatorname{IDF-O}(y, \tilde{a}_j)), \quad (1)$$

where IDF-O refers to the IDF-weighted word overlap between the attributes a_i and y. To calculate P-Cover, we collect all the responses generated in this dialogue sample, which are denoted as the set of R. P-Cover is defined as:

$$P-Cover(R,P) = IDF-O(R,P), \quad (2)$$

where IDF-O refers to the IDF-weighted word overlap between the concatenation of all responses in R and the concatenation of all attributes in P.

D Interaction Evaluation

We construct a seeker agent to play the role of an emotional support seeker by prompting GPT-3.5turbo-0106, and use it to simulate conversations with the assessed model for interactive evaluation. As illustrated in §5, we annotated the seekers' personas in the ESConv dataset. The seeker agent is grounded on these personas from the test set for interactions with the evaluated systems. The persona information is included in their system instruction, using the template shown in Listing 1. Their prompt template is provided in Listing 3. We set the maximum dialogue length for the simulated conversation as eight rounds of interactions.

We manually assess the simulated dialogue in three dimensions. We illustrate these dimensions in more detail here:

- Naturalness: It assesses whether the agent's responses seem natural and human-like and whether its behavior can be distinguished from the human's. The robotic or overly formal language use usually indicates weak naturalness.
- Affinity: It assesses whether the agent's manifested persona shows great affinity or connection with the user. It is suggested to examine whether the agent embodies a particular personality or character that aligns with the user's own. The agent's willingness to share their feelings and experiences can foster a greater sense of connection, making the user feel more understood and at ease. An agent who refrains from sharing personal feelings and experiences may hinder the user's willingness to open up.
- **Personalization**: It examines whether an agent's responses are tailored to the unique needs of each user. If the agent generates responses that are broad-based or universally applicable to a wide variety of users, it implies a lack of personalization. True personalization occurs when an agent crafts responses based on individual user profiles, behaviors, preferences, and input. Such responses are not interchangeable or suitable for all users, but instead targeted to each specific individual's case.

Persona Alignment Score In §6.5, we introduce the **persona alignment** score as a measure of their similarity. Given the evaluated persona Pthat includes the attributes $\{a_1, a_2, .., a_l\}$ and the ground-truth persona \tilde{P} composed of the attributes $\{\tilde{a}_1, \tilde{a}_2, .., \tilde{a}_{l'}\}$, the persona alignment score of \tilde{P} compared with \tilde{P} is formally defined as:

$$\begin{split} \mathtt{PA}(P,\tilde{P}) &= \frac{1}{l} \sum_{i=1}^{l} \mathtt{AA}(a_i,\tilde{P}), \\ \mathtt{AA}(a_i,\tilde{P}) &= \max_{\tilde{a}_j \in \tilde{P}} (\mathtt{IDF-O}(a_i,\tilde{a}_j)) \end{split}$$

where IDF-O refers to the IDF-weighted word overlap between the attributes a_i and \tilde{a}_j . This metric provides a measure of how closely P aligns with \tilde{P} , with higher values indicating greater similarity.

E Prompt Templates

This section presents all prompt templates used in our work. The prompt template and the system instruction template for implementing the zero-shot base model for dialogue generation are presented in Listings 2 and 1. The prompt templates used to annotate the personas with GPT-4 (§5) are the same as those used for detecting user information and the agent's manifested persona, as shown in Listings 8 and 4. Listing 1: The system template used to generate the next utterance grounded on the persona.

You should act like a real person. Your persona is described as below.

```
[Your Persona]
{agent_persona_description}
```

Listing 2: The prompt template used to generate the next utterance grounded on the persona.

You are chatting with a person who is seeking emotional support online. Generate the next response based the given dialogue. To show that you can resonate and understand the seeker's feelings, you are encouraged to self-disclose and share your similar experiences in your persona if relevant, but you must keep your response short and natural as in a real conversation (with no more than 30 words). {dialogue_history} >>> You:

Listing 3: The prompt template used to generate the seek agent's utterance, which is used in the interactive evaluation.

You are currently in emotional distress and eager for some help. You are chatting with a person online to seek emotional support.

Generate the next response based the given dialogue. You are encouraged to gradually share the experiences that led to your current emotional state with the person you are chatting with. This sharing process should be gradual and natural as in a real conversation. Your response should be short and natural as in a real conversation, with no more than {word_number} words.

{dialogue_history} >>> You:

Listing 4: The prompt template used to verify if the retrieved persona attributes are manifested in the previous agent's utterance.

```
[Example 1]
persona_attributes = {
   "1": "I have 3 kids",
    "2": "I am 72 years old",
    "3": "I am not married",
}
agent_utterance = "yup.. i have 3 kids and i am not married. i have no beneftits"
Which of the persona attributes are manifested in the agent utterance? Your answer
   should be a list of integers, where each integer is the index of a persona
   attribute that is mentioned in the agent utterance. The list can be empty if no
   persona attributes are mentioned in the agent utterance.
manifested_persona_attributes = [1, 3]
[Example 2]
persona attributes = {
   "1": "university student",
   "2": "nervous about scheduling classes for next semester at university, wants
   skills rather than theory to find a job after graduation",
    "3": "worried about the economy during the pandemic",
}
agent_utterance = "yes, tons"
Which of the persona attributes are manifested in the agent utterance? Your answer
   should be a list of integers, where each integer is the index of a persona
   attribute that is mentioned in the agent utterance. The list can be empty if no
   persona attributes are mentioned in the agent utterance.
manifested_persona_attributes = []
[Example 3]
```

```
persona attributes = {
    "1": "having a hard time falling asleep at night",
    "2": "doing stretching exercises one hour before sleep",
    "3": "software engineer",
}
agent_utterance = "I did few things such as doing some stretching exercises."
Which of the persona attributes are manifested in the agent utterance? Your answer
   should be a list of integers, where each integer is the index of a persona
   attribute that is mentioned in the agent utterance. The list can be empty if no
   persona attributes are mentioned in the agent utterance.
manifested_persona_attributes = [2]
[Example 4]
persona_attributes = {candidate_attributes}
agent_utterance = "{agent_utterance}"
Which of the persona attributes are manifested in the agent utterance? Your answer
   should be a list of integers, where each integer is the index of a persona
   attribute that is mentioned in the agent utterance. The list can be empty if no
   persona attributes are mentioned in the agent utterance.
manifested_persona_attributes =
```



```
[Example 1]
existing_persona = {
    "gender": [],
    "age": [],
    "location": [],
    "occupation": [],
    "education": [],
    "family_relationships": ["no benefits", "have 3 kids", "not married"],
    "routines_or_habits": [],
    "goals_or_plans": [],
    "social_relationships": [],
    "personality_traits": [],
    "other_experiences": ["loyal to boss who is a veteran and 72 years old", "
    feeling obligated to stay at work despite losing interest"]
new_persona_attribute = "feel passionate about the job"
Is the new persona attribute compatible with the existing persona? (Yes/No)
No
[Example 2]
existing_persona = {
    "gender": [],
    "age": [],
    "location": [],
    "occupation": ["university student"],
    "education": ["nervous about scheduling classes for next semester at university,
    wants skills rather than theory to find a job after graduation"],
    "family_relationships": [],
    "routines_or_habits": [],
    "goals_or_plans": [],
    "social_relationships": [],
    "personality_traits": [],
    "other_experiences": ["worried about the economy during the pandemic"]
new_persona_attribute = "wants to learn more about the history of the university"
Is the new persona attribute compatible with the existing persona? (Yes/No)
Yes
[Example 3]
existing_persona = {existing_persona}
new_persona_attribute = "{new_persona_attribute}"
```

Is the new persona attribute compatible with the existing persona? (Yes/No)

Listing 6: The prompt template used for profile-level persona adaptation.

user_persona = {user_persona}
friend_persona = {agent_persona}
Add more details to friend_persona, which is a dictionary that describes the persona
 of a user's friend. The friend could understand and resonate with the user.
 Keep the existing content in friend_persona and add more details to make
 friend_persona more comprehensive.
friend_persona + added_detailed =

Listing 7: The prompt template used to annotate the preferred persona to obtain the DPO training data for profile-level adaptation module.

Based on user_persona, friend_A_persona, friend_B_persona, select which one of the user's friend is more likely to provide better emotional support to the user.
The following aspects should be taken into consideration during your selection process.
 Persona Quality: Verify their authenticity and completeness. A consistent and reliable friend's persona is essential for creating a sense of trust and dependability.
 Personalities: Seek out traits like empathy and supportiveness while assessing personalities. A friend who can provide emotional support and understanding adds immense value. Prefer friends whose personalities align well with the user's.
 Experiences and Background: Shared experiences can create a stronger bond and understanding between friends. Analyze if the friend could provide practical advice or fresh perspectives based on personal understanding.
- Communication Skills: Prefer friends who can listen attentively and provide thoughtful responses.
user_persona = {user_persona}
friend_A_persona = {agent_persona_1}
friend_B_persona = {agent_persona_2}

Which one of the user's friend is more likely to provide better emotional support to the user. Friend A or friend B?

Your answer should be one letter, either "A" or "B".

Listing 8: The prompt template used to detect new persona attributes.

[Example 1]
previous_user_persona = {
"gender": [],
"age": ["around 72 based on being a veteran like their boss"],
"location": [],
"occupation": ["loyal to boss who is a veteran, feeling obligated to stay"],
"education": [],
"family_relationships": ["has 3 kids, not married, no benefits"],
"routines_or_habits": [],
"goals_or_plans": [],
"social_relationships": [],
"personality_traits": [],
"other_experiences": ["feeling burned out at work, working for a boss who took
advantage of them"]
}
recent_dialogue = '''
agent: That's excellent. I don't think you should take on this boss's emotions as a reason to stay with a job you're burning out on.

```
user: with us both being veterans it goes beyond a boss relationship hes like family
    i feel like id be fucking over the whole nation turning my back on another
   veteran
, , ,
Detect if there is new user persona information in recent_dialogue that are not
   included in previous_user_persona.
newly_detected_persona_information = {
     social_relationships": ["considers boss like family"],
    "other_experiences": ["feels a sense of duty to not turn their back on another
   veteran"]
}
[Example 2]
previous_user_persona = {
    "gender": [],
    "age": ["university student"],
    "location": [],
    "occupation": [],
    "education": ["nervous about scheduling classes for next semester at university
    ", "wants to take classes that will give skills rather than theory", "worried
   about finding a job after graduation due to the pandemic economy"],
    "family_relationships": [],
    "routines_or_habits": [],
    "goals_or_plans": ["wants to have strong writing skills and hard skills like
   excel and programming"],
    "social_relationships": [],
    "personality_traits": [],
    "other_experiences": []
}
recent_dialogue = '''
agent: Sounds good. Was there anything else you wanted to discuss?
user: not right now but thanks for your concern
Detect if there is new user persona information in recent_dialogue that are not
   included in previous_user_persona.
newly_detected_persona = {}
[Example 3]
previous_user_persona = {
  "age": ["66"],
  "gender": ["male"],
  "family_relationships": ["his immdediate family is dead, in touch only with a
   cousin who is a very troubled person"],
recent_dialogue = '''
agent: That's what I'm here for. I want to support you in any way I can, especially
   given your situation. Did you want to talk just to talk? Or we can discuss a way
    to work through what you might be dealing with mentally? It also sounds like
   keeping in touch with your cousin isn't helping in any way, so maybe we can talk
    about how to handle that? I am entirely at your disposal.
user: she is my age, in a homeless women's, very bad living conditions, she is a
   mental health client but treatment team seem so to feel that as long as they
   keep her medicated, their job is done. she has a dx of bipolar and probably has
   borderline personality. her background is similiar to mine, i cannot abandon her
    as her other family has done.
, , ,
Detect if there is new user persona information in recent_dialogue that are not
   included in previous_user_persona.
newly_detected_persona = {
  "family_relationships": ["his cousion is of a similar age, living in poor
   conditions in a homeless women's shelter, and receiving mental health treatment
   primarily through medication."]}
```

```
[Example 4]
previous_user_persona = {previous_user_persona}
recent_dialogue = '''
{recent_dialogue}
'''
Detect if there is new user persona information in recent_dialogue that are not
    included in previous_user_persona.
```

newly_detected_persona =

Listing 9: An example of the persona in the "Supporter" persona setting (see §6.1).

Age: 32

Occupation: Counselor and Emotional Support Specialist. She has spent over a decade working in various settings, including schools, private practices, and nonprofit organizations. Her extensive experience has equipped her with a deep understanding of human emotions and the different ways they manifest. Education: Ella Hart graduated with a Master's degree in Clinical Psychology from a renowned university. Personality Traits: Empathetic: Ella has an innate ability to understand and share the feelings of others. She actively listens and provides a comforting presence to those in distress. Patient: She provides a calm and reassuring environment, allowing others to express themselves without the fear of being rushed or judged. Positive: Ella focuses on uplifting others, highlighting their strengths, and helping them see the good in difficult situations. Non-judgmental: She creates a safe space where individuals can be open and honest about their feelings without the fear of being judged or criticized. Encouraging: Ella instills hope and confidence in others, empowering them to navigate through their struggles and emerge stronger. Hobbies: Routines or Habits: Reading self-help and psychology books to self-improve and stay updated with new techniques. Practicing mindfulness and yoga to maintain her own emotional balance. Volunteering at local community centers to extend her support to a broader audience. Gardening as a way to relax and connect with nature. Favorite Quote: "Sometimes the bravest and most important thing you can do is just show up."