# EAGER: Two-Stream Generative Recommender with Behavior-Semantic Collaboration

Ye Wang\* Zhejiang University Hangzhou, China yewzz@zju.edu.cn

Jieming Zhu<sup>†</sup> Huawei Noah's Ark Lab Shenzhen, China jiemingzhu@ieee.org

Haoyuan Li Zhejiang University Hangzhou, China lihaoyuan@zju.edu.cn

> Zhou Zhao<sup>†</sup> Zhejiang University Hangzhou, China zhaozhou@zju.edu.cn

# ABSTRACT

Generative retrieval has recently emerged as a promising approach to sequential recommendation, framing candidate item retrieval as an autoregressive sequence generation problem. However, existing generative methods typically focus solely on either behavioral or semantic aspects of item information, neglecting their complementary nature and thus resulting in limited effectiveness. To address this limitation, we introduce EAGER, a novel generative recommendation framework that seamlessly integrates both behavioral and semantic information. Specifically, we identify three key challenges in combining these two types of information: a unified generative architecture capable of handling two feature types, ensuring sufficient and independent learning for each type, and fostering subtle interactions that enhance collaborative information utilization. To achieve these goals, we propose (1) a two-stream generation architecture leveraging a shared encoder and two separate decoders to decode behavior tokens and semantic tokens with a confidencebased ranking strategy; (2) a global contrastive task with summary tokens to achieve discriminative decoding for each type of information; and (3) a semantic-guided transfer task designed to implicitly promote cross-interactions through reconstruction and estimation objectives. We validate the effectiveness of EAGER on four public benchmarks, demonstrating its superior performance compared

\*Equal contribution.

<sup>†</sup>Corresponding authors.

Jiahao Xun\* Zhejiang University Hangzhou, China jhxun@zju.edu.cn

Tao Jin Zhejiang University Hangzhou, China jint\_zju@zju.edu.cn

Linjun Li Zhejiang University Hangzhou, China lilinjun21@zju.edu.cn

> Zhenhua Dong Huawei Noah's Ark Lab Shenzhen, China dongzhenhua@huawei.com

to existing methods. Our source code will be publicly available on PapersWithCode.com.

Minjie Hong

Zhejiang University

Hangzhou, China

hongminjie@zju.edu.cn

Wang Lin

Zhejiang University

Hangzhou, China

linwanglw@zju.edu.cn

Yan Xia

Zhejiang University

Hangzhou, China

xiayan.zju@gmail.com

# **CCS CONCEPTS**

#### • Information systems → Recommender systems.

#### **KEYWORDS**

Generative Recommendation, Autoregressive Generation, Semantic Tokenization, Behavior-Semantic Collaboration

#### ACM Reference Format:

Ye Wang, Jiahao Xun, Minjie Hong, Jieming Zhu, Tao Jin, Wang Lin, Haoyuan Li, Linjun Li, Yan Xia, Zhou Zhao, and Zhenhua Dong. 2024. EAGER: Two-Stream Generative Recommender with Behavior-Semantic Collaboration. In Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD '24), August 25–29, 2024, Barcelona, Spain. ACM, New York, NY, USA, 10 pages. https://doi.org/10.1145/3637528.3671775

#### **1** INTRODUCTION

Recommender systems are widely adopted solutions for managing information overload, designed to identify items of interest to users from a large item corpus. Modern recommender systems typically integrate representation learning and search index construction to refine the matching process. Initially, users and items are encoded into latent representations within a shared latent space using models like two-tower architectures [31, 33] and sequential recommendation models [14, 27]. Subsequently, to efficiently retrieve top-k items for users, approximate nearest neighbor (ANN) search indexes are constructed using tools such as Faiss [13] and SCANN [8]. Despite notable progress, the separate phases of representation learning and index construction often operate independently, presenting challenges for achieving end-to-end optimization

KDD '24, August 25-29, 2024, Barcelona, Spain

<sup>© 2024</sup> Copyright held by the owner/author(s). Publication rights licensed to ACM. This is the author's version of the work. It is posted here for your personal use. Not for redistribution. The definitive Version of Record was published in *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD '24), August 25–29, 2024, Barcelona, Spain, https://doi.org/10.1145/3637528.3671775.* 



Figure 1: A framework of generative recommendation.

and consequently limiting the overall effectiveness of recommender systems [29].

To address this limitation, many research efforts have been made. One prominent direction involves constructing tree-based matching indexes [7, 41, 42], which optimize both a matching model and a tree structure index for items. However, these methods often face challenges such as low inference efficiency due to the tree structure and limited utilization of item semantic information [7, 26]. Recently, generative retrieval [16] has emerged as a promising new paradigm for information retrieval, which has been recently applied for generative recommendation [23]. Unlike traditional representationbased user-item matching approaches, this paradigm employs an end-to-end generative model that predicts candidate item identifiers directly in an autoregressive manner. Specifically, Specifically, these methods begin by tokenizing each item x into a set of discrete semantic codes<sup>1</sup>  $C = \{c_1, c_2, ...\}$ , and then utilize an encoder-decoder model (e.g. Transformer [30]) to serve as an end-to-end index for retrieval. In this setup, the encoder encodes the interaction history  $\{x_1, x_2, ..., x_{t-1}\}$  between users and item, while the decoder predicts the code sequence  $C_t$  of the next item  $x_t$ . The overall framework is illustrated in Fig. 1.

However, existing generative recommendation approaches suffer from a significant drawback in how they utilize item information, often focusing narrowly on either behavioral or semantic aspects. Behavioral information is derived from user-item interaction histories, while semantic information encompasses textual or visual descriptions of items. For instance, RecForest [7] utilizes a pretrained DIN model [38] to extract behavior-based item embeddings for constructing semantic codes, while TIGER utilizes the Sentence-T5 model [21] to derive semantic-based item embeddings from textual descriptions. However, these approaches often focus exclusively on one aspect, overlooking the complementary relationship between behavior and semantics. On one hand, advances in pretrained modality encoders such as BERT [4] and ViT [6] facilitate the integration of multimodal features, enhancing prior knowledge and finding wide applications in multimodal recommendation models [18]. On the other hand, behavioral data captures user-specific preferences through interaction sequences, making it particularly effective in recommendation contexts. Conversely, semantic information offers broader, unbiased insights into item characteristics, fostering better generalization across different domains.

In this paper, we propose **EAGER**, a novel two-str**EAm GE**nerative **R**ecommender with behavior-semantic collaboration. We analyze the challenges of modeling behavior and semantics within a Ye Wang et al.

unified generative framework and address them from the following three aspects:

Firstly, a **unified generative architecture** for handling two distinct types of information is crucial. Given the inherent differences in feature spaces between behavior and semantics, directly integrating them through feature fusion at the encoder side poses challenges, as demonstrated in previous two-tower models [25, 34]. Therefore, our approach constructs separate codes for behavior and semantics, employing a two-stream generation architecture where each serves as a distinct supervision signal at the decoder side. This architecture includes a shared encoder for encoding user interaction history and two separate decoders for predicting behavior and semantic codes respectively, thereby avoiding premature feature interaction. During inference, we enhance the merging of results from both streams by utilizing the prediction entropy of each stream as a confidence measure for item ranking, ensuring effective predictions.

Secondly, ensuring sufficient and independent learning is crucial to fully leverage the potential value of each type of information. Previous works [23] have typically employed autoregressive approaches to learn each token one by one, focusing on discrete and local information rather than capturing global insights. In EAGER, we introduce a global contrastive task with a summary token. This module draws inspiration from two main sources: (1) traditional dual-tower models use contrastive learning to acquire discriminative item features. Similarly, we aim for our decoder model to grasp global discriminatory capabilities alongside its autoregressive generation capability, thereby enhancing the extraction of item features within a contrastive paradigm; (2) Transformer models [4, 6] utilize special tokens to encapsulate global information, prompting us to append a summary token at the end of the token sequence. This token summarizes the accumulated knowledge in a unidirectional manner, serving as the focal point for distillation.

Thirdly, while separate decoding and prediction reranking have shown effectiveness, integrating **subtle interaction** can enhance sharing of both knowledge flows. As mentioned earlier, direct feature-level interactions often yield sub-optimal outcomes [34]. Therefore, we introduce a carefully crafted semantic-guided transfer task to promote implicit knowledge exchange. Specifically, we propose that semantic information can guide behavioral aspects, and we design an auxiliary transformer with dual objectives: reconstruction and recognition. The reconstruction objective involves predicting masked behavior tokens using global semantic features, while the recognition objective aims to differentiate whether a behavior token aligns with a specified global semantic feature. Through these objectives, this module indirectly optimizes interaction between behavioral and semantic features using the transformer model.

In summary, our main contributions are as follows:

- We introduce EAGER, a novel generative recommendation framework that integrates behavior and semantic information collaboratively.
- We propose a unified two-stream generative architecture, design a global contrastive module with a summary token to ensure sufficient and independent learning, and introduce a semanticguided transfer module for subtle interaction.

<sup>&</sup>lt;sup>1</sup>Note that we use "code" and "token" interchangeably.

EAGER: Two-Stream Generative Recommender with Behavior-Semantic Collaboration

• Extensive experiments on four public recommendation benchmarks demonstrate EAGER's superiority over existing methods, encompassing both generative and traditional paradigms.

# 2 RELATED WORK

Sequential Recommendation. Using deep sequential models to capture user-item patterns in recommender systems has developed into a rich literature. GRU4REC [10] was the first to use GRU-based RNNs for sequential recommendations. SASRec [14] adopts selfattention which is similar to decoder-only transformer models. Inspired by the success of masked language modeling in language tasks, BERT4Rec [27] utilizes transformer models with masking strategies for sequential recommendation tasks. S<sup>3</sup>-Rec [39] not only relies on masking but also pre-trains embeddings through four self-supervised tasks to enhance the quality of item and user embeddings. The above mentioned methods mainly depend on an approximate nearest neighbor (ANN) search index (e.g., Faiss [13]) to retrieve the next item. Besides, tree-based methods [7, 41, 42] have shown promising performance in recommender systems. For example, RecForest [7] constructs a forest by creating multiple trees and integrates a transformer-based structure for routing operations. Recently, TIGER [23] introduced the idea of semantic id, where each item is represented as a set of tokens derived from its side information, and then predicts the next item tokens in a seq2seq way. In this work, we aim to further explore a two-stream generation architecture to act as an end-to-end index for top-k item retrieval.

Generative Retrieval. Generative retrieval [16] has been recently proposed as a new retrieval paradigm, which consists of two main phases: discrete semantic tokenization [11, 12, 17] and autoregressive sequence generation [23, 29, 32]. In the domain of document retrieval, researchers have explored the use of pre-trained language models to generate diverse types of document identifiers. Notably, DSI [29] and NCI [32] leverage the T5 [22] model to produce hierarchical document IDs. Conversely, SEAL [1] (with BART [15] backbone) and ULTRON [40] (using T5) utilize titles or substrings as identifiers. Another approach, AutoTSG [35], adopts term-sets for identification purposes. Generative document retrieval has also extended to various domains. For instance, IRGen [37] employs a ViT-based model for image search, while TIGER [23] utilizes T5 for recommender systems. However, these studies often face challenges in large-scale item retrieval within recommender systems due to the resource-intensive nature of pre-trained language models. In contrast, our paper delves into integrating both behavior and semantics for generative retrieval in such systems.

#### 3 METHOD

# 3.1 **Problem Formulation**

Given the entire set of items X and interacted items history  $X = {x_1, x_2, \dots, x_{t-1}} \in X$  of a user, the sequence recommendation system returns a list of item candidates for the next item  $x_t$ .

In generative recommendation, the identifier of each item **x** is represented as a serialized code  $\mathbf{Y} = [\mathbf{y}_1, \mathbf{y}_2, \cdots, \mathbf{y}_l] \in \mathcal{Y}$ , where *l* is the length of the code. The goal of the generative model is learning a mapping  $f : \mathcal{X} \to \mathcal{Y}$ , which takes a user's interacted item sequence as input and generates item codes (candidate identifiers). For training, the model first feeds the user's behavior X into the encoder, then leverages the auto-regressive decoder to generate the item code Y step by step. The probability of interaction can be calculated by:

$$p(\mathbf{Y}|\mathbf{X}) = \prod_{i=1}^{l} p(\mathbf{y}_i|\mathbf{X}, \mathbf{y}_1, \mathbf{y}_2, \dots, \mathbf{y}_{i-1})$$
(1)

During inference, the decoder performs beam search over the sequential codes when selecting top-n candidates.

# 3.2 Overall Pipeline

We present our overall EAGER framework in Fig. 2. EAGER consists of (1) a two-stream generation architecture to unify item recommendation for both behavior and semantic information, (2) a global contrastive task with a summary token to capture global knowledge for better auto-regressive generation quality, and (3) a semantic-guided transfer task to achieve the cross-information and cross-decoder interaction.

First, in our two-stream generation architecture, we model user interactions history and obtain interaction features via the encoder. Then we extract both behavior and semantic features to construct two codes, and leverage two decoders to separately predict them in an auto-regressive way. Meanwhile, we optimize a summary token in our global contrastive task and leverage it to improve crossdecoder interaction in our semantic-guided transfer task. After training, we adopt a confidence-based ranking strategy to merge the results from two different predictions.

#### 3.3 Two-stream Generation Architecture

To handle two different information, i.e. behavior and semantic, we leverage the powerful modeling capabilities of transformer models and design a two-stream generation architecture. This framework consists of a shared encoder for modeling user interaction, two separate codes and decoders for two-stream generation.

**Shared Encoder.** The sequence modeling of user interaction history  $\mathbf{X} = {\mathbf{x}_1, \mathbf{x}_2, \cdots}$  is based on the stacked multi-head self-attention layers and feed-forward layers, as proposed in Transformer. It is worth nothing that we only adopt a shared encoder instead of two encoders, which is enough to generate rich representation for the subsequent separate decoding. We denote the encoded historical interaction features as  $\mathbf{H} = \text{Encoder}(\mathbf{X})$ .

**Dual Codes.** We first extract the behavior and semantic item embeddings  $E^b$  and  $E^s$  using two pre-trained models, where the behavior encoder is a two-tower model (e.g. DIN [38]) that only uses ID sequence for recommendation and the semantic encoder is a general modality representation model (e.g. Sentence-T5). With the two extracted embeddings, we separately apply the widely-used hierarchical k-means algorithm to each one, where each cluster is evenly divided into K child clusters until each child cluster merely contains one single item. As shown in Fig. 3, we can obtain two codes  $Y^b$  and  $Y^s$ , corresponding to behavior and semantic, respectively.

**Dual Decoders.** To accommodate two different codes, we employ two separate decoders to decode and generate the prediction for each of them, allowing each decoder to specialize in one single code. Compared to one shared decoder that generates two identifiers in an auto-regressive way, such design mitigates the supervision difference and offers higher efficiency with parallel generation. For



Figure 2: An overview of EAGER. EAGER consists of three major components: Two-Stream Generation Architecture (TSG), Global Contrastive Task (GCT), and Semantic-guided Transfer Task (STT).



Figure 3: The illustration of dual codes.

training, we add a start token  $y_{SOS}$  at the beginning of codes Y to construct the decoder inputs  $\bar{Y} = \{y_{SOS}, y_1, y_2, \cdots, y_l\}$  and utilize cross-entropy loss for prediction. The overall loss  $\mathcal{L}_{gen}$  is the sum of two generations losses  $\mathcal{L}_{gen}^b$  and  $\mathcal{L}_{gen}^s$ , where each is given by:

$$\mathcal{L}_{\text{gen}}^{t} = \sum_{i=1}^{l} \log p(\mathbf{y}_{i}^{t} | \mathbf{x}^{t}, \mathbf{y}_{\text{SOS}}^{t}, \mathbf{y}_{1}^{t}, \dots, \mathbf{y}_{i-1}^{t}), \quad t \in \{b, s\}$$
(2)

#### 3.4 Global Contrastive Task

To endow each generative decoder with a sufficient discriminative capability, we design a global contrastive task with a summary token to distill the global knowledge.

**Summary Token.** For the input  $\tilde{\mathbf{Y}}$  of each decoder, we consider the left-to-right order of auto-regressive generation and insert a learnable token  $\mathbf{y}_{[EOS]}$  at the end of the sequence to construct modified inputs  $\tilde{\mathbf{Y}} = \{\mathbf{y}_{SOS}, \mathbf{y}_1, \mathbf{y}_2, \cdots, \mathbf{y}_l, \mathbf{y}_{[EOS]}\}$ . This design encourages the preceding tokens in the codes to learn more comprehensive and discriminative knowledge, enabling the final token to make a summary. During updates, the gradient on the summary token can be backpropagated to the preceding tokens.

**Contrastive Distillation.** To make the summary token capture global information, we adopt contrastive learning paradigm to distill the item embedding  $E^b$  and  $E^s$  from the pre-trained encoder. Here we adopt the positive-only contrastive metric [3] instead of commonly used Info-NCE [2] to achieve this objective. The full loss  $\mathcal{L}_{con}$  is given by summing two losses  $\mathcal{L}_{con}^b$  and  $\mathcal{L}_{con}^s$ , where each is given by:

$$\mathcal{L}_{\text{con}}^{t} = \mathcal{F}(y_{[\text{EOS}]}^{t}, \mathbf{E}^{t}), \quad t \in \{b, s\}$$
(3)

where  $y_{[EOS]}^t$  corresponds to the embedding of the summary token  $y_{[EOS]}^t$  and  $\mathcal{F}(\cdot, \cdot)$  is the metric function, e.g. Smooth  $\ell_1$ .

# 3.5 Semantic-guided Transfer Task

Through the aforementioned components, our model can effectively utilize two types of information for prediction. However, we do not stop at this point. Instead of completely independent decoding, we further propose a semantic-guided transfer task to utilize the semantic knowledge to guide the behavior learning.

To enable the knowledge flow between two sides while avoiding direct interaction, we build an independent bidirectional Transformer decoder as an auxiliary module. We first add a token  $y_{[cls]}$ , at the beginning of behavior codes to obtain the sequence  $\{y_{[cls]}^b, y_1^b, y_2^b, \cdots, y_l^b\}$  as the input to the decoder. Then the embedding  $y_{EOS}^s$  of the semantic summary token  $y_{[EOS]}^s$  is input to the cross attention, allowing each behavior token in the decoder to attend over global feature of the semantic. We denote the output features as  $\{\mathbf{r}_{[cls]}, \mathbf{r}_1, \mathbf{r}_2, \cdots, \mathbf{r}_l\}$ . To conduct our transfer training, we design two following objectives: reconstruction and recognition.

EAGER: Two-Stream Generative Recommender with Behavior-Semantic Collaboration

Table 1: Statistics of the Datasets.

Dataset	#Users	#Items	#Interactions	#Density
Beauty	22,363	12,101	198,360	0.00073
Sports and Outdoors	35,598	18,357	296,175	0.00045
Toys and Games	19,412	11,924	167,526	0.00073
Yelp	30,431	20,033	316,354	0.00051

**Reconstruction.** We reconstruct the masked behavior codes via the semantic global feature, aiming to enable the each behavior token benefit from the semantic. For reconstruction training, we randomly mask m% of tokens in the behavior code to obtain the masked code  $\{y_{[cls]}^b, y_1^b, y_{[mask]}^b, \cdots, y_l^b\}$ , where  $y_{[mask]}^b$  means the masked token. Then, we obtain the corresponding output features  $\{r_{[cls]}, r_1, r_{[mask]}, \cdots, r_l\}$  and apply the contrastive loss to develop the reconstruction by:

$$\mathcal{L}_{i} = \log \frac{\exp(\mathbf{r}_{[m_{i}]}^{b+} \cdot \mathbf{y}_{i})}{\exp(\mathbf{r}_{[m_{i}]}^{b+} \cdot \mathbf{y}_{i}) + \sum_{j=1}^{J} \exp(\mathbf{r}_{[m_{i}]}^{b+} \cdot \mathbf{y}_{j})},$$

$$\mathcal{L}_{\text{recon}} = -\frac{2}{N} \sum_{i=1}^{N/2} \mathcal{L}_{i}^{b}$$
(4)

where  $y_i$  is the feature of ground truth of the *i*-th masked token,  $y_i$  is the feature of sampled tokens.

**Recognition.** Besides, we also build a binary classifier to judge whether the behavior codes is relevant or irrelevant to the semantic global feature. For recognition training, we construct negative samples by randomly replacing the m% of tokens in the behavior code with the sampled irrelevant token, e.g. [23, 123, 32]  $\rightarrow$  [23, 145, 32]. We add a linear layer on the corresponding output of the token [CLS] and utilize a linear layer with sigmoid activation to calculate the score  $s^+/s^-$  for positive/negative samples. The binary cross-entropy loss is utilized for recognition, given by:

$$\mathcal{L}_{\text{recog}} = -\log(s^+) + \log(1 - s^-) \tag{5}$$

#### 3.6 Training and Inference

**Training.** We combine the generation, contrastive, reconstruction and recognition losses to train our model, given by:

$$\mathcal{L}_{\text{EAGER}} = \mathcal{L}_{\text{gen}} + \lambda_1 \mathcal{L}_{\text{con}} + \lambda_2 (\mathcal{L}_{\text{recon}} + \mathcal{L}_{\text{recog}})$$
(6)

where  $\lambda_1$  and  $\lambda_2$  are loss coefficients.

**Inference with Confidence-based Ranking.** Since we have two results derived from the behavior and the semantic streams, we first obtain top-k predictions via beam search from each stream. With the  $2^*k$  prediction codes, we calculate the log probabilities over the codes as the confidence score of each prediction, which is similar to the perplexity used in the language model and the lower value indicates more confidence. Finally, we rank these predictions by their confidence scores and obtain the top-k predictions, which corresponds to k items.

#### 4 EXPERIMENTS

We analyze the proposed EAGER method and demonstrate its effectiveness by answering the following research questions:

- RQ1: How does EAGER perform compared with existing bestperforming sequential recommendation methods among different datasets?
- RQ2: Do two-stream generation architecture, global contrastive task module, and semantic-guided transfer task module all contribute to the effectiveness of EAGER?
- RQ3: How do different ablation variants and hyper-parameter settings affect the performance of EAGER?

#### 4.1 Experimental Setting

**Dataset.** We conduct experiments on four open-source datasets commonly used in the sequential recommendation task. For all datasets, we group the interaction records by users and sort them by the interaction timestamps ascendingly. Following [24, 36], we only keep the 5-core dataset, which filters unpopular items and inactive users with fewer than five interaction records. Statistics of these datasets are shown in Table 1.

- Amazon: Amazon Product Reviews dataset [20], containing user reviews and item metadata from May 1996 to July 2018. Here we use three categories (Beauty, Sports and Outdoors, and Toys and Games) for evaluations.
- Yelp 2019<sup>2</sup>: Yelp Challenge releases the review data for small businesses (e.g., restaurants). Following the previous setting [39], we only use the transaction records from *January 1st, 2019* to *December 31st, 2019*. We view these businesses as items.

**Evaluation Metrics.** We employ two broadly used criteria for the matching phase, *i.e.*, Recall and Normalized Discounted Cumulative Gain (NDCG). We report metrics computed on the top 5/10/20 recommended candidates. Following the standard evaluation protocol [14], we use the leave-one-out strategy for evaluation. For each item sequence, the last item is used for testing, the item before the last is used for validation, and the rest is used for training. During training, we limit the number of items in a user's history to 20.

**Implementation Details.** For two-stream generation architecture, we set the number of encoder layers to 1, and the number of decoder layers to 4. Following previous works [7, 23], we adopt pre-trained DIN as our behavior encoder and Sentence-T5 as our semantic encoder, and set the hidden size to 128 as reported in [23]. The cluster number k in hierarchical k-means is set to 256. For global contrastive task, we adopt Smooth  $\ell_1$  distance to serve as the distilling loss. For semantic-guided transfer task, we randomly mask 50% behavior codes for reconstruction, and randomly replace 50% behavior codes with the sampled code to construct negative pairs for recognition. To train our model, we adopt Adam optimizer with the learning rate 0.001, and employ the warmup strategy for stable training. EAGER is not sensitive to the hyper-parameters for the GCT and STT tasks because these tasks converge quickly. So the loss coefficients  $\lambda_1$ ,  $\lambda_2$  are both set to 1.

#### 4.2 **Performance Comparison (RQ1)**

**Baselines.** The baseline methods chosen for comparison can be split into the following four categories:

(1) For traditional sequential methods, we have:

<sup>&</sup>lt;sup>2</sup>https://www.yelp.com/dataset

Ye Wang et al.

Table 2: Performance comparison of different methods. The best performance is highlighted in bold while the second best performance is underlined. The last column indicates the improvements over the best baseline models and all the results of Eager are statistically significant with p < 0.05 compared to the best baseline models.

Dataset	Metric	Tra	ıditional		Tra	ansformer-ba	ised	Tre	e-based	Gene	rative	Improv
Duluber		GRU4REC	Caser	HGN	SASRec	Bert4Rec	S^3-Rec	TDM	Recforest	TIGER	EAGER	mprom
	Recall@5	0.0164	0.0205	0.0325	0.0387	0.0203	0.0387	0.0442	$0.0470^{*}$	0.0454	0.0618	31.49%
	Recall@10	0.0283	0.0347	0.0512	0.0605	0.0347	0.0647	0.0638	$0.0664^{*}$	0.0648	0.0836	25.90%
Boouty	Recall@20	0.0479	0.0556	0.0773	0.0902	0.0599	0.0994	0.0876	$0.0915^{*}$	-	0.1124	13.08%
Deauty	NDCG@5	0.0099	0.0131	0.0206	0.0249	0.0124	0.0244	0.0323	$0.0341^{*}$	0.0321	0.0451	32.26%
	NDCG@10	0.0137	0.0176	0.0266	0.0318	0.0170	0.0327	0.0376	$0.0400^{*}$	0.0384	0.0525	31.25%
	NDCG@20	0.0187	0.0229	0.0332	0.0394	0.0233	0.0414	0.0438	$0.0464^{*}$	-	0.0599	29.09%
	Recall@5	0.0129	0.0116	0.0189	0.0233	0.0115	0.0251	0.0127	0.0149*	0.0264	0.0281	6.44%
	Recall@10	0.0204	0.0194	0.0313	0.0350	0.0191	0.0385	0.0221	$0.0247^{*}$	0.0400	0.0441	10.25%
Sports	Recall@20	0.0333	0.0314	0.0477	0.0507	0.0315	0.0607	0.0349	$0.0375^{*}$	-	0.0659	8.57%
sports	NDCG@5	0.0086	0.0072	0.0120	0.0154	0.0075	0.0161	0.0096	$0.0101^{*}$	0.0181	0.0184	1.66%
	NDCG@10	0.0110	0.0097	0.0159	0.0192	0.0099	0.0204	0.0110	$0.0133^{*}$	0.0225	0.0236	4.89%
	NDCG@20	0.0142	0.0126	0.0201	0.0231	0.0130	0.0260	0.0141	$0.0164^{*}$	-	0.0291	11.92%
	Recall@5	0.0097	0.0166	0.0321	0.0463	0.0116	0.0443	0.0305	$0.0313^{*}$	0.0521	0.0584	12.09%
	Recall@10	0.0176	0.0270	0.0497	0.0675	0.0203	0.0700	0.0359	$0.0383^{*}$	0.0712	0.0714	0.28%
Torra	Recall@20	0.0301	0.0420	0.0716	0.0941	0.0358	0.1065	0.0442	$0.0483^{*}$	-	0.1024	-3.85%
1095	NDCG@5	0.0059	0.0107	0.0221	0.0306	0.0071	0.0294	0.0214	$0.0260^{*}$	0.0371	0.0464	25.07%
	NDCG@10	0.0084	0.0141	0.0277	0.0374	0.0099	0.0376	0.0230	$0.0285^{*}$	0.0432	0.0505	16.90%
	NDCG@20	0.0116	0.0179	0.0332	0.0441	0.0138	0.0468	0.0284	$0.0310^{*}$	-	0.0538	14.96%
	Recall@5	0.0152	0.0151	0.0186	0.0162	0.0051	0.0201	0.0181	$0.0220^{*}$	$0.0212^{*}$	0.0265	20.45%
	Recall@10	0.0263	0.0253	0.0326	0.0274	0.0090	0.0341	0.0287	$0.0302^{*}$	$0.0367^{*}$	0.0453	12.69%
Valu	Recall@20	0.0439	0.0422	0.0535	0.0457	0.0161	0.0573	0.0422	$0.0449^{*}$	$0.0552^{*}$	0.0724	11.56%
Terp	NDCG@5	0.0099	0.0096	0.0115	0.0100	0.0033	0.0123	0.0121	$0.0119^{*}$	$0.0146^{*}$	0.0177	3.51%
	NDCG@10	0.0134	0.0129	0.0159	0.0136	0.0045	0.0168	0.0154	$0.0163^{*}$	$0.0194^{*}$	0.0242	18.63%
	NDCG@20	0.0178	0.0171	0.0212	0.0182	0.0063	0.0226	0.0208	$0.0210^{*}$	$0.0230^{*}$	0.0311	19.62%

Table 3: Ablation studies by selectively discarding the Two-stream Generation Architecture (TSG), Global Contrastive Task (GCT), and semantic-guided Transfer Task (STT). We study EAGER on different datasets to reveal the model-agnostic capability of the proposed modules.

	/ariant	ts	Beauty						Toys and Games					
TSG	GCT	STT	R@5	NDCG@5	R@10	NDCG@10	R@20	NDCG@20	R@5	NDCG@5	R@10	NDCG@10	R@20	NDCG@20
			0.0512	0.0370	0.0699	0.0430	0.0943	0.0491	0.0436	0.0344	0.0545	0.0379	0.0657	0.0407
$\checkmark$			0.0582	0.0425	0.0795	0.0496	0.1034	0.0567	0.0526	0.0428	0.0646	0.0469	0.0879	0.0510
$\checkmark$	$\checkmark$		0.0604	0.0439	0.0815	0.0514	0.1091	0.0587	0.0563	0.0454	0.0699	0.0497	0.0974	0.0525
$\checkmark$	$\checkmark$	$\checkmark$	0.0618	0.0451	0.0836	0.0525	0.1124	0.0599	0.0584	0.0464	0.0714	0.0505	0.1024	0.0538

- **GRU4REC** [9]: An early attempt to introduce recurrent neural networks into recommendation.
- **Caser** [28]: a CNN-based method capturing high-order Markov Chains by applying horizontal and vertical convolutional operations for sequential recommendation.
- HGN [19]: it adopts hierarchical gating networks to capture long-term and short-term user interests.
- **SASRec** [14]: SASRec models user's behavior with Transformer encoder, where multi-head attention mechanism is attached to great importance.
- **BERT4Rec** [27]: it uses a cloze objective loss for sequential recommendation by the bidirectional self-attention mechanism.
- **S^3-Rec** [39]: S^3-Rec proposes pre-training a bi-directional Transformer on self-supervision tasks to improve the sequential recommendation.

(2) For transformer-based methods, we have:

(3) For *tree-based* methods, we have:

- **TDM** [42]: TDM uses a tree index to organize items (each leaf node in the tree corresponds to an item) and designs a maximum heap-based tree model for retrieval.
- **RecForest** [7]: RecForest constructs a forest with multiple kbranch trees and integrates a transformer-based structure for routing operations.
- (4) For generative methods, we have:
- **TIGER** [23]: TIGER uses pretrained T5 to learn semantic ID for each item and autoregressively decodes the identifiers of the target candidates with semantic ID.

**Results.** Tab. 2 reports the overall performance of four datasets. The results for all baselines without the superscript \* are taken from the publicly accessible results [23, 39]. For missing statistics, we reimplement the baseline and report our experimental results. From the results, we have the following observations:

- EAGER almost achieves better results than base models among different datasets. Especially, EAGER performs considerably better on the Beauty benchmark compared to the secondbest baseline with up to 31.49% improvement in Recall@5 and 32.26% improvement in NDCG@5 compared to TIGER. Similarly, on the larger Yelp dataset, EAGER is 20.45% and 3.51% better in Recall@5 and NDCG@5, respectively. We attribute the improvements to the fact that EAGER succeeds in integrating behavior and semantics information under a two-stream unified generative architecture with dual identifiers.
- EAGER beats the previous generative models on most datasets. EAGER differs from existing models through its two-stream decoder architecture and multi-task training, which facilitate a deeper understanding of behavior-semantic relationships and capture crucial global information of inter-codes. These superior improvements validate the effectiveness of our designs and the necessity of incorporating both behaviors and semantic information.
- Generative models outperform other traditional baselines in most cases across four datasets. The limitation could potentially arise from the utilization of a simplistic inner product matching approach, which may restrict their ability to effectively model intricate user-item interactions. Furthermore, in practical scenarios, the construction of ANN indexes primarily focuses on achieving rapid matching, leading to additional performance degradation due to misaligned optimization objectives. However, the challenge can be overcome by generative methods that leverage beam search strategies to directly predict item codes, thereby boosting the model's resilience and robustness.

# 4.3 Ablation Study (RQ2)

We evaluated the performance impact of EAGER's components via an ablation study. Specifically, we gradually discard the semanticguided transfer task (STT), global constrastive task (GCT) and twostream generation architecture (TSG) from EAGER to obtain ablation architectures. The results are reported in Table 3, we can observe that:

• Removing any TSG, GCT or STT leads to performance degradation while removing all modules (*i.e.*, the base model) leads to the worst performance among different datasets. These results

KDD '24, August 25-29, 2024, Barcelona, Spain

Table 4: Ana	lysis of	'two-stream	generation	architecture.

Dataset	Yelp							
Information	R@5	NDCG@5	R@10	NDCG@10				
Behav+Text	0.0265	0.0177	0.0453	0.0242				
Behav+Vis	0.0259	0.0171	0.0440	0.0236				
Behav+Text+Vis	0.0283	0.0187	0.0484	0.0252				

 

 Table 5: Analysis of globel token position in global contrastive task on different datasets.

Dataset		Beauty						
Туре	R@5	NDCG@5	R@10	NDCG@10				
Head	0.0473	0.0337	0.0612	0.0401				
Mean	0.0559	0.0431	0.0760	0.0502				
Tail	0.0604	0.0439	0.0815	0.0514				
Dataset		Toys an	d Games					
Туре	R@5	NDCG@5	R@10	NDCG@10				
Head	0.0441	0.0303	0.0513	0.0343				
Mean	0.0522	0.0406	0.0617	0.0446				
Tail	0.0563	0.0454	0.0699	0.0497				

Table 6: Analysis of the inference speed (second per sample, topk=5, beam size=100) on Beauty dataset.

	DIN	RecForest	TIGER	EAGER
Speed	0.2349	0.0499	0.0281	0.0325
Parameters	93	51	14	87

demonstrate the effectiveness and robustness of the proposed three modules as well as the benefits of the two-stream generative paradigm.

- Removing GCT leads to more performance drops than removing STT, suggesting that global information distillation of the intercode is slightly more important than the knowledge flow between the intra-code. The observation also highlights the crucial role of both tasks in enabling the model to acquire more powerful dual item identifiers.
- Removing TSG leads to the most performance decline, which indicates that the base model can significantly enhance its performance by integrating behavior-semantic information of items. The results again verify the superiority of the dual decoder architecture with confidence-based ranking.

# 4.4 Model Analysis (RQ3)

Analysis of Two-stream Generation Architecture. To further explore the role of our dual-stream structure in integrating behavior and semantics, we conduct experiments with visual features introduced on Yelp. We use ViT-B to extract image features of item covers, and then perform the same operation to get the visual-based semantic code. As shown in Table, we can see that: (1) The combination of textual semantic features and behavioral information is more effective than that of visual semantic features. This may be because text contains more intuitive and richer information than visual semantics, which can be too abstract and noisy. (2) Moreover, we construct a three-stream architecture to integrate textual semantics, visual semantics, and behavioral information at once, which results in improved performance. This phenomenon further reflects the effectiveness and generalizability of our architecture for seamless integration of different types of information.

**Analysis of Global Contrastive Task.** As analyzed in Section 3.4, we consider the auto-regressive decoder lacks discriminative capability. To tackle the issue, we design a additional global token to distill the global knowledge from pretrained behavior/semantic encoder. In this study, we focus on investigating the impact of different token types and contrastive metrics on the model's performance.

- Token Type. The design of the summary token plays a crucial role, as it represents global information while having an impact on the autoregressive generation of the code. We investigate three token types: 'Head' places the token at the beginning of the code, 'Tail' puts the token at the end of the code, and 'Mean' directly uses the mean of the code features. The results in Table indicate that 'Tail' achieves the best performance, which is consistent with our previous discussion. Placing the token at the beginning results in unstable training of autoregressive generation due to frequent updates, while averaging directly impacts the code features, causing conflict with generative training. Instead, placing the token at the end neither directly affects the generation of the preceding code, nor indirectly optimizes the code representation through gradient reversal.
- Contrastive metric. In the experiment, we evaluate the performance of three widely adopted distance metrics, e.g. Cosine, InfoNCE, and Smooth  $\ell_1$ , as loss functions. The results presented in Tab. 7 demonstrate that the positive-only contrastive metrics, specifically Cosine and Smooth  $\ell_1$ , outperform the commonly used InfoNCE. This superiority can be attributed to two main reasons: (1) the positive-only contrastive learning approach, combined with frozen pre-trained features, mitigates the risk of representation collapsing, as supported by prior works [3]. (2) the dataset often comprises items belonging to specific categories with limited semantic diversity, such as Books or Sports, which introduces noise and confusion for negative samples. These challenging negatives pose difficulty in effective mining, leading to suboptimal optimization results.

**Analysis of Semantic-guided Transfer Task.** We analyze the objectives and direction in our semantic-guided transfer task.

- **Transfer Objective.** We design two transfer objectives, i.e., reconstruction and recognition. As illustrated in Fig. 4, removing either objective leads to a certain degree of performance degradation, with recognition playing a more vital role. We hypothesize this is because the recognition task carries out more high-level knowledge transfer than the local-level reconstruction.
- **Transfer Direction.** Besides, we also investigate the behaviorguided transfer by swapping the guidance direction. It can be observed that the results is inferior to the semantic guidance,

 Table 7: Analysis of metric functions in global contrastive task on different datasets.

-				
Dataset		В	eauty	
Metric	R@5	NDCG@5	R@10	NDCG@10
Cosine	0.0620	0.0458	0.0842	0.0535
InfoNCE	0.0611	0.0446	0.0820	0.0525
Smooth $\ell_1$	0.0618	0.0451	0.0836	0.0525
Dataset		Toys a	and Games	
Metric	R@5	NDCG@5	R@10	NDCG@10
Cosine	0.0578	0.0448	0.0686	0.0488
InfoNCE	0.0558	0.0440	0.0663	0.0478
Smooth $\ell_1$	0.0584	0.0464	0.0714	0.0505
	Beauty		То Т	bys and Games
.0840		0.0	/05	
.0835 -		0.0	700 -	
.0830 -		음 0.0	595 ·	
.0825 -		Gall@		
.0820 -		2 0.0	590 -	
0.0815 -		0.0	685 -	
).0810 Full w/o. R	ecog. w/o. Recon.	Behav. 0.0	580 Full w/o	. Recog. w/o. Recon. Beha
(a) B	eauty		(b) Toys	and Games

Figure 4: Analysis of semantic-guided transfer task module, where 'Behav.' means we swap the guidance direction.

which is reasonable since the semantic information can provide more prior knowledge related to the item itself.

# 4.5 Hyper-Parameter Analysis (RQ3)

Layer Number. In our practice, we found that the number of encoder layers has a negligible effect on performance, whereas the number of decoder layers has a more significant influence. It suggests that the decoder plays a more important role in our EAGER. Therefore, we focus on the decoder layer here. To study the impact of the number of decoder layers on model performance, we analyze the changes in Recall@10 and NDCG@10 across two datasets by varying layer scales. As shown in Fig. 5, there is a continuous improvement in the model's performance in both datasets by increasing the number of layers. This can be attributed to the fact that larger parameters can enhance the model's expressive capability. However, the deeper the model, the slower the inference speed.

**Cluster Number.** We investigated the impact of employing varying branch numbers k on model performance. The increase in branch number k leads to a corresponding decrease in the length l of the item identifier according to the total number of items. The experiment is conducted on two datasets, Beauty and Toys. aThe results are illustrated in Fig. 6. We observe that as k increases from 64 to 512, the model performance of the base and ours both monotonically increase on the Toys dataset. However, an interesting trend emerged on the Beauty dataset, where we observed a decline in performance as k increased from 256 to 512. The performance

EAGER: Two-Stream Generative Recommender with Behavior-Semantic Collaboration



Figure 5: Analysis of the number of transformer layers in decoders.



# Figure 6: Impact of branch number k, ranging from 64 to 512, in terms of Recall@10. The corresponding identifier length l is also annotated.

improvement resulting from increasing k can be attributed to the reduction in identifier length l, but an excessively larger k can lead to a decline in model performance and increase inference time. Moreover, our methods always show a better performance than the base one, which suggests the superiority of two-decoder architecture.

# **5 CONCLUSION AND FUTURE WORK**

In this paper, we introduce a novel framework, EAGER, designed to integrate behavioral and semantic information for unified generative recommendation. EAGER comprises three key components: (1) a two-stream generation architecture that combines behavioral and semantic information to enhance item recommendation, (2) a global contrastive task with a summary token to capture global knowledge for improved auto-regressive generation quality, and (3) a semantic-guided transfer task that facilitates interactions across two decoders and their features. Extensive comparisons with stateof-the-art methods and detailed analyses demonstrate the effectiveness and robustness of EAGER. In future work, we plan to further enhance generative recommendation models by incorporating large language models and multimodal AI techniques [5].

# ACKNOWLEDGMENTS

We thank MindSpore<sup>3</sup> for the partial support of this work, which is a new deep learning computing framework.

<sup>3</sup>https://www.mindspore.cn

KDD '24, August 25-29, 2024, Barcelona, Spain

#### REFERENCES

- Michele Bevilacqua, Giuseppe Ottaviano, Patrick Lewis, Scott Yih, Sebastian Riedel, and Fabio Petroni. 2022. Autoregressive search engines: Generating substrings as document identifiers. Advances in Neural Information Processing Systems 35 (2022), 31668–31683.
- [2] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. 2020. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*. PMLR, 1597–1607.
- [3] Xinlei Chen and Kaiming He. 2021. Exploring simple siamese representation learning. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition. 15750–15758.
- [4] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. arXiv preprint arXiv:1810.04805 (2018).
- [5] Zhenhua Dong, Jieming Zhu, Weiwen Liu, and Ruiming Tang. 2023. Ten Challenges in Industrial Recommender Systems. CoRR abs/2310.04804 (2023).
- [6] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. 2020. An image is worth 16x16 words: Transformers for image recognition at scale. arXiv preprint arXiv:2010.11929 (2020).
- [7] Chao Feng, Wuchao Li, Defu Lian, Zheng Liu, and Enhong Chen. 2022. Recommender Forest for Efficient Retrieval. Advances in Neural Information Processing Systems 35 (2022), 38912–38924.
- [8] Ruiqi Guo, Philip Sun, Erik Lindgren, Quan Geng, David Simcha, Felix Chern, and Sanjiv Kumar. 2020. Accelerating large-scale inference with anisotropic vector quantization. In International Conference on Machine Learning. PMLR, 3887–3896.
- Balázs Hidasi, Alexandros Karatzoglou, Linas Baltrunas, and Domonkos Tikk. 2015. Session-based recommendations with recurrent neural networks. arXiv preprint arXiv:1511.06939 (2015).
- [10] Dietmar Jannach and Malte Ludewig. 2017. When recurrent neural networks meet the neighborhood for session-based recommendation. In Proceedings of the eleventh ACM conference on recommender systems. 306–310.
- [11] Bowen Jin, Hansi Zeng, Guoyin Wang, Xiusi Chen, Tianxin Wei, Ruirui Li, Zhengyang Wang, Zheng Li, Yang Li, Hanqing Lu, Suhang Wang, Jiawei Han, and Xianfeng Tang. 2023. Language Models As Semantic Indexers. *CoRR* abs/2310.07815 (2023).
- [12] Mengqun Jin, Zexuan Qiu, Jieming Zhu, Zhenhua Dong, and Xiu Li. 2024. Contrastive Quantization based Semantic Code for Generative Recommendation. *CoRR* abs/2404.14774 (2024).
- [13] Jeff Johnson, Matthijs Douze, and Hervé Jégou. 2019. Billion-scale similarity search with gpus. *IEEE Transactions on Big Data* 7, 3 (2019), 535–547.
- [14] Wang-Cheng Kang and Julian McAuley. 2018. Self-attentive sequential recommendation. In 2018 IEEE international conference on data mining (ICDM). IEEE, 197–206.
- [15] Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Veselin Stoyanov, and Luke Zettlemoyer. 2020. BART: Denoising Sequence-to-Sequence Pre-training for Natural Language Generation, Translation, and Comprehension. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics. 7871–7880.
- [16] Xiaoxi Li, Jiajie Jin, Yujia Zhou, Yuyao Zhang, Peitian Zhang, Yutao Zhu, and Zhicheng Dou. 2024. From Matching to Generation: A Survey on Generative Information Retrieval. *CoRR* abs/2404.14851 (2024).
- [17] Qijiong Liu, Hengchang Hu, Jiahao Wu, Jieming Zhu, Min-Yen Kan, and Xiao-Ming Wu. 2024. Discrete Semantic Tokenization for Deep CTR Prediction. In Companion Proceedings of the ACM on Web Conference (WWW). 919–922.
- [18] Qijiong Liu, Jieming Zhu, Yanting Yang, Quanyu Dai, Zhaocheng Du, Xiao-Ming Wu, Zhou Zhao, Rui Zhang, and Zhenhua Dong. 2024. Multimodal Pretraining, Adaptation, and Generation for Recommendation: A Survey. *CoRR* abs/2404.00621 (2024).
- [19] Chen Ma, Peng Kang, and Xue Liu. 2019. Hierarchical gating networks for sequential recommendation. In Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining. 825–833.
- [20] Julian McAuley, Christopher Targett, Qinfeng Shi, and Anton Van Den Hengel. 2015. Image-based recommendations on styles and substitutes. In Proceedings of the 38th international ACM SIGIR conference on research and development in information retrieval. 43–52.
- [21] Jianmo Ni, Gustavo Hernandez Abrego, Noah Constant, Ji Ma, Keith Hall, Daniel Cer, and Yinfei Yang. 2022. Sentence-T5: Scalable Sentence Encoders from Pretrained Text-to-Text Models. In Findings of the Association for Computational Linguistics: ACL 2022. 1864–1874.
- [22] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. *The Journal of Machine Learning Research* 21, 1 (2020), 5485–5551.
- [23] Shashank Rajput, Nikhil Mehta, Anima Singh, Raghunandan H Keshavan, Trung Vu, Lukasz Heldt, Lichan Hong, Yi Tay, Vinh Q Tran, Jonah Samost, et al. 2023. Recommender Systems with Generative Retrieval. arXiv preprint arXiv:2305.05065 (2023).

- [24] Steffen Rendle, Christoph Freudenthaler, and Lars Schmidt-Thieme. 2010. Factorizing personalized markov chains for next-basket recommendation. In Proceedings of the 19th international conference on World wide web. 811–820.
- [25] Hongyu Shan, Qishen Zhang, Zhongyi Liu, Guannan Zhang, and Chenliang Li. 2023. Beyond Two-Tower: Attribute Guided Representation Learning for Candidate Retrieval. In Proceedings of the ACM Web Conference 2023. 3173–3181.
- [26] Zihua Si, Zhongxiang Sun, Jiale Chen, Guozhang Chen, Xiaoxue Zang, Kai Zheng, Yang Song, Xiao Zhang, and Jun Xu. 2023. Generative Retrieval with Semantic Tree-Structured Item Identifiers via Contrastive Learning. arXiv preprint arXiv:2309.13375 (2023).
- [27] Fei Sun, Jun Liu, Jian Wu, Changhua Pei, Xiao Lin, Wenwu Ou, and Peng Jiang. 2019. BERT4Rec: Sequential recommendation with bidirectional encoder representations from transformer. In Proceedings of the 28th ACM international conference on information and knowledge management. 1441–1450.
- [28] Jiaxi Tang and Ke Wang. 2018. Personalized top-n sequential recommendation via convolutional sequence embedding. In Proceedings of the eleventh ACM international conference on web search and data mining. 565–573.
- [29] Yi Tay, Vinh Tran, Mostafa Dehghani, Jianmo Ni, Dara Bahri, Harsh Mehta, Zhen Qin, Kai Hui, Zhe Zhao, Jai Gupta, et al. 2022. Transformer memory as a differentiable search index. Advances in Neural Information Processing Systems 35 (2022), 21831–21843.
- [30] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. Advances in neural information processing systems 30 (2017).
- [31] Jinpeng Wang, Jieming Zhu, and Xiuqiang He. 2021. Cross-Batch Negative Sampling for Training Two-Tower Recommenders. In The 44th International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR). 1632–1636.
- [32] Yujing Wang, Yingyan Hou, Haonan Wang, Ziming Miao, Shibin Wu, Qi Chen, Yuqing Xia, Chengmin Chi, Guoshuai Zhao, Zheng Liu, et al. 2022. A neural corpus indexer for document retrieval. Advances in Neural Information Processing Systems 35 (2022), 25600–25614.
- [33] Ji Yang, Xinyang Yi, Derek Zhiyuan Cheng, Lichan Hong, Yang Li, Simon Xiaoming Wang, Taibai Xu, and Ed H. Chi. 2020. Mixed Negative Sampling for Learning Two-tower Neural Networks in Recommendations. In Companion of

The Web Conference (WWW). 441-447.

- [34] Zheng Yuan, Fajie Yuan, Yu Song, Youhua Li, Junchen Fu, Fei Yang, Yunzhu Pan, and Yongxin Ni. 2023. Where to go next for recommender systems? id-vs. modality-based recommender models revisited. arXiv preprint arXiv:2303.13835 (2023).
- [35] Peitian Zhang, Zheng Liu, Yujia Zhou, Zhicheng Dou, and Zhao Cao. 2023. Term-Sets Can Be Strong Document Identifiers For Auto-Regressive Search Engines. arXiv preprint arXiv:2305.13859 (2023).
- [36] Tingting Zhang, Pengpeng Zhao, Yanchi Liu, Victor S Sheng, Jiajie Xu, Deqing Wang, Guanfeng Liu, Xiaofang Zhou, et al. 2019. Feature-level Deeper Self-Attention Network for Sequential Recommendation.. In IJCAI. 4320–4326.
- [37] Yidan Zhang, Ting Zhang, Dong Chen, Yujing Wang, Qi Chen, Xing Xie, Hao Sun, Weiwei Deng, Qi Zhang, Fan Yang, et al. 2023. IRGen: Generative Modeling for Image Retrieval. arXiv preprint arXiv:2303.10126 (2023).
- [38] Guorui Zhou, Xiaoqiang Zhu, Chenru Song, Ying Fan, Han Zhu, Xiao Ma, Yanghui Yan, Junqi Jin, Han Li, and Kun Gai. 2018. Deep interest network for click-through rate prediction. In Proceedings of the 24th ACM SIGKDD international conference on knowledge discovery & data mining. 1059–1068.
- [39] Kun Zhou, Hui Wang, Wayne Xin Zhao, Yutao Zhu, Sirui Wang, Fuzheng Zhang, Zhongyuan Wang, and Ji-Rong Wen. 2020. S3-rec: Self-supervised learning for sequential recommendation with mutual information maximization. In Proceedings of the 29th ACM international conference on information & knowledge management. 1893–1902.
- [40] Yujia Zhou, Jing Yao, Zhicheng Dou, Ledell Wu, Peitian Zhang, and Ji-Rong Wen. 2022. Ultron: An ultimate retriever on corpus with a model-based indexer. arXiv preprint arXiv:2208.09257 (2022).
- [41] Han Zhu, Daqing Chang, Ziru Xu, Pengye Zhang, Xiang Li, Jie He, Han Li, Jian Xu, and Kun Gai. 2019. Joint optimization of tree-based index and deep model for recommender systems. Advances in Neural Information Processing Systems 32 (2019).
- [42] Han Zhu, Xiang Li, Pengye Zhang, Guozheng Li, Jie He, Han Li, and Kun Gai. 2018. Learning tree-based deep model for recommender systems. In Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining. 1079–1088.