AI-coupled HPC Workflow Applications, Middleware and Performance

Wes Brewer¹, Ana Gainaru¹, Frédéric Suter¹, Feiyi Wang¹, Murali Emani², and Shantenu Jha³

¹Oak Ridge National Laboratory, Oak Ridge, TN, USA ²Argonne National Laboratory, Lemont, IL, USA ³Rutgers University, New Brunswick, NJ, USA

Abstract

AI integration is revolutionizing the landscape of HPC simulations, enhancing the importance, use, and performance of AI-driven HPC workflows. This paper surveys the diverse and rapidly evolving field of AI-driven HPC and provides a common conceptual basis for understanding AI-driven HPC workflows. Specifically, we use insights from different modes of coupling AI into HPC workflows to propose six execution motifs most commonly found in scientific applications. The proposed set of execution motifs is by definition incomplete and evolving. However, they allow us to analyze the primary performance challenges underpinning AI-driven HPC workflows. We close with a listing of open challenges, research issues, and suggested areas of investigation including the the need for specific benchmarks that will help evaluate and improve the execution of AI-driven HPC workflows.

Introduction

Multiple recent publications have demonstrated how AI coupled with traditional HPC simulations can provide practical performance enhancements of 10^3 or more [1, 2, 3]. AI-coupled-HPC workflows – as opposed to decoupled AI and HPC – involve the concurrent, real-time coupled execution of AI and HPC tasks in ways that allow the AI systems to steer or inform the HPC tasks and vice versa. The real-time coupling and concurrency of HPC and AI tasks are fundamental, as it allows allows bidirectional influence. The online coupling of an AI system to HPC workflows can be used for a variety of scenarios, e.g., an AI-surrogate model to substitute part of expensive simulation, an AI system to learn the function or determine the parameters or the practical fields, and an AI system to guide a campaign using an objective function or performance Pareto-optimal or resource-optimal experiments (using, for example, Active/Reinforcement Learning).

Driving the need to couple AI systems to traditional HPC simulations is the promise of enhancing the "effective performance" of HPC workflows, where enhancement is measured by "science for a given amount of computing". AI-coupled HPC workflows continue to overcome the limitations of traditional forward simulations in increasingly sophisticated and pervasive ways. Further, AI-coupled HPC workflows will overcome traditional bottlenecks that prevent greater scale – physical and temporal or higher resolutions. The integration of AI into a computational workflow is also a sustainable and scalable way to obtain significant performance gains and present an opportunity to avoid simulation enhancements that are overly sensitive to processor architecture [4, 5]. Put together, AI-coupled HPC workflows present a promising paradigm [6, 7, 8] which leverages the ubiquitous interest and wide capabilities being developed for AI but employs them to overcome performance bottlenecks due to unsustainable approaches.

Integrating AI systems into traditional high-performance computing workflows has demonstrably enabled highly accurate modeling and holds significant promise for accelerating scientific discovery. There exist multiple promising examples of workflows that couple AI methods with traditional HPC workflows, typically by extending HPC workflows with additional capabilities to support the concurrent execution of AI modules [9, 10, 11, 12]. Multiple solutions have successfully coupled AI systems to be either "about" the HPC workflows or "outside" (typically in the outer loop or even possibly remote from) the main HPC workflow. However, the ability to substitute an AI system "inside" of an HPC simulation remains challenging, with most solutions being customized to specific simulation software or platforms. Figure 1 shows a typical science application where AI has advanced simulations and experiments by coupling AI to HPC workflows via different mechanisms. Furthermore, in molecular science and engineering – which covers a diverse range of domains from biophysics to materials to chemical engineering – AI has been used to make simulation workflows more efficient and effective [13]. AI has been used to predict ever more complex properties, such as energetic materials, solid-state materials properties, and even the structure of complex materials. In addition, several machine-learned potentials that enable access to quantum-chemical-like accuracies at a fraction of the cost have emerged.



Figure 1: Example of an AI-coupled HPC workflow using models to replace expensive high-fidelity simulations for steering instruments

The focus in this paper is on the scientific workflows that involve the online (real-time) coupling and concurrent execution of AI and HPC, not offline training and inference. In addition to providing an overview of existing AI-coupled HPC workflows, the primary objectives of this paper are to identify classes of AI-coupled-HPC workflows and to provide an overview of the software systems used to support them. The paper also discusses performance and systems challenges, identifying both robust solutions and the lack thereof. Finally, the paper highlights some open research issues to advance AI-HPC workflows.

The paper is organized as follows: Section 2 reviews coupling modes between AI and HPC tasks and introduces six execution motifs that describe the interaction and coordination patterns of AI and HPC components. These motifs are used to understand a range of AI-driven HPC workflow applications and primary performance challenges underpinning AI-driven HPC workflows. Execution motifs are important at multiple levels, not the least of which is their influence on the design of application-level software systems and task runtime systems. For instance, the frequency of interaction in a given motif informs the performance requirements and the optimizations available to lower-level libraries. Further, the diversity of AI approaches and model types means intrinsic variation in training and execution times. Section 3 presents several frameworks and libraries developed to ease the coupling of AI and HPC components in a single workflow and illustrates how each of these frameworks relates to the proposed high-level modes of execution motifs. Section 4 discusses various performance issues related to AI-HPC workflows – organized around the motifs – such as load balancing, workload management, and dataflow performance bottlenecks. We conclude in Section 5 with a discussion of several open issues and challenges that the field of AI-coupled HPC workflows presents.

2 Execution Motifs

AI systems can be coupled to HPC workflows using different methods at multiple levels. Such AI-coupled HPC workflows, integrate AI systems with HPC simulations are AI-in-HPC, AI-out-HPC, and AI-about-HPC simulations. These three modes of coupling [6, 5] correspond to the placement of AI methods relative to HPC simulations. **AI-in-HPC** represents the scenario in which an AI system is introduced instead of a component of the HPC simulation, or possibly, instead of the whole simulation itself, i.e., the AI model serves as a "total surrogate" [14]. **AI-out-HPC** captures situations where an AI system resides "outside" of the traditional HPC simulation loop but dynamically controls the progression of the HPC workflow [15, 16] (e.g., control of computational campaigns via reinforcement learning). Finally, **AI-about-HPC** represents the situation where AI systems are concurrent and coupled to the main HPC tasks: analysis and training codes use the output of the HPC simulation to provide further insights. These three modes are not mutually exclusive; in fact, we contend [4, 17, 5] that increasingly, scientific applications will achieve performance gains and methodological advances by combining all three modes. Thus, if not unified, software solutions for managing the execution of each component and their data transfers for all three modes must be compatible.

Building on the concept of coupling modes (AI-x-HPC, where x could be in, out, or about), we introduce execution motifs. Whereas modes provide insight into the static coupling of AI systems with HPC simulations, execution motifs capture and provide information on recurring dynamic interaction patterns between the AI systems and the HPC simulations, driven by a high-level functional goal.

We define an execution motif using the characteristics the following characteristics:

• The first class of characteristics defines the **interaction patterns** between the AI and HPC components: (1) dataflow type (e.g., one-to-one or one-to-many) and direction (i.e., HPC-to-AI or AI-to-HPC or both); (2) control flow type and direction (e.g., one/many AI components steering one or many HPC simulations, HPC simulation guiding the AI training process, etc.); and (3) user-involvement in the process.



Figure 2: Defining characteristics of AI-coupled HPC workflows: (left) Breakdown of the main characteristics used to define the different behavioral motifs; (right) Main components (boxes) participating in the workflow execution with two or more components interacting given different control and data flow patterns (arrows).

- The second class defines the **coupling patterns** between AI and HPC components, namely: (4) concurrency requirements between the AI and HPC components (e.g., real-time interaction or post-mortem analysis); (5) dynamism requirements in the composition of the workflow (e.g., spawning/terminating new processes or training sequences) and in the interaction patterns (e.g., data/control flow keeps changing, new connections are spawned/terminated); and (6) federation requirements (e.g, network requirements between AI and HPC components or heterogeneity in resources).
- Each motif is associated with a **scope** which represents its primary purpose (e.g., is AI used to improve or optimize HPC components, is HPC used to build improved AI models, or both)

These execution motifs serve as identifiers for (groups of) AI-coupled HPC workflows that exhibit similar interaction and coupling patterns between AI and HPC components, and thus encounter similar performance bottlenecks and require similar optimizations when deployed on HPC systems.

Figure 2 illustrates (left hand-side) one column for each class of characteristics. Figure 2 (right hand-side) shows the main components participating in the workflow execution (namely: traditional HPC simulations and codes; AI analysis and training; instruments; and humans in the loop) together with the interactions between them (dashed lines show the control flow and uninterrupted lines, the data flow). For each motif, different components will be present, and the control and data flow will connect them in different ways. In this section, we will use this diagram to further illustrate the specific interaction and coupling patterns exhibited by each motif.

Based on a literature survey of large-scale workflows, we identify and characterize six primary execution motifs that couple AI and HPC. Specifically, we identify five common execution motifs wherein AI enhances HPC workflows (#1-5), two of them improving both HPC and AI (#3-4) and one where HPC workflows are used to develop or improve AI systems or models (#6). We briefly describe these execution motifs below and summarize their characteristics in Table 1:

1. **AI-based steering ensembles of simulations:** In this motif, a HPC workflow, such as an ensemble of simulations are "steered" by an AI system. Sometimes, the AI can terminate or spawn simulations, making the coupling between components dynamic. In subsequent tables and figures, we refer to this motif as *Steering*.

2. Multistage pipeline: This motif represents a campaign composed of multiple stages with a typical AI-based function that reduces/filters simulations to spawn in the next stage based on the output of the current stage.

3. **Inverse design:** This motif captures the process of calculating, from a set of observations, the causal factors that produced them (e.g., calculating an image in X-ray computed tomography). AI-driven optimizations are used to iteratively identify causal factors from observational data that can be fed back into the experiment or simulation. The AI system can also be improved in the process thanks to the same feedback loop mechanism.

4. **Digital replica:** This motif includes the concurrent use of simulations and AI digital replicas (e.g., digital twins or multi-fidelity models) for scientific predictions and health monitoring of experiments or high-fidelity simulations. This motif can be executed in real-time, completely autonomously, or involve a scientist in deciding to guide future experiments.

5. Distributed models and dynamic data: This motif corresponds to workflows deployed over wide area networks. These workflows couple HPC simulations and experiments distributed across multiple remote sites with AI-based reduction/analysis and visualization. The AI can be used simply for compression, refactoring, or remote visualization of dynamic data or for steering the simulation or experiments. Workflows in this motif use highly heterogeneous resources, including edge devices, large leadership facilities, local clusters, or individual laptops for running and connecting different components. We refer to this motif as *Distributed Models* in subsequent tables and figures. 6. Adaptive execution for training large AI models: This motif couples the distributed training of large AI systems with HPC simulations and experiments. Such workflows can include training components using datasets previously generated by HPC simulations or real-time model optimization by running the training sequence concurrent with HPC simulations that are steered to generate the data required to cover the search space more efficiently. In subsequent tables and figures, we refer to this motif as *Adaptive Training*.

Table 1 summarizes the distinct patterns of each motif according to the characteristics introduced in Figure 2.

Hereafter, we describe each motif in greater detail and provide examples of existing and future implementations of these execution motifs.

AI-based steering ensembles of simulations

AI-based steering is used in many fields to improve the performance of large multi-physics, multi-resolution simulations, experiments, or an ensemble of simulations. Figure 3a presents a typical workflow in this motif where the steering decisions are informed by an AI system, external to the simulations, that analyzes the generated data in near-real time or adaptively selects scientifically meaningful simulations or experiments to run next.

- Interaction patterns: Typically, one or many HPC simulations and/or experiments generate data being analyzed by one AI analysis code. This analysis frequently includes visualization for human-in-the-loop decision-making. Data thus flows from the HPC to the AI, while control goes from AI to HPC.
- Coupling patterns: Near real-time analysis is typically required but not always necessary, with some analysis codes steering the configuration of the next ensemble of simulations. Simulations can be terminated, or new instances can be spawned based on the analysis. If experiments are involved, the AI and HPC components might be executed in a distributed fashion. However, such workflows are typically executed on a single system.
- Scope: Workflows in this motif usually create models of the simulations offline, based on previous results or synthetic data, and use the AI inference online to improve the HPC components.



Botton X Data Data Data Data Data Data Trigger other simulations HPC simulation Y ... [next stage]

(a) AI system steering (ensembles of) high-fidelity HPC simulations or experiments to avoid undesired results or guide the workflow towards better solutions.

(b) Sequential coupling of data-dependent multistage AIcoupled HPC workflow as a pipeline with filtering/analysis codes between stages.

Figure 3: Workflow computational patterns for the **Steering** (a) and **Multistage Pipeline** (b) motifs

The following literature survey focuses on workflows for the *Steering* execution motif. These workflows use AI systems to analyze how "well" (ensembles of) simulations are progressing toward their initial scientific objective. Based on that analysis, they can change the "trajectory" when exploring the parameter space. This allows them to avoid undesired results either or increase performance or accuracy. The training of the AI system is done offline before the execution of the workflow. Workflows in which the steering process is also used to guide the online training of the AI system will be investigated as part of the *Adaptive Training* motif.

The AI-based steering execution motifs can be found in workflows designed to solve scientific problems in molecular dynamics [2, 19], fusion [20], or energy systems simulations [21]. These workflows show orders of magnitude speed-ups

Motif / Scope	Interaction Patterns	Coupling Patterns	Example Use Case
Steering AI improving HPC	 Control and data flow in one direction: data from HPC to AI, control from AI to HPC One AI to one or many HPC Optionally human in the loop 	 Real-time requirements Dynamic composition with HPC simulations spawned or terminated on the fly Usually running in one fa- cility 	AI-out-HPC - Command-and-control of physical experiments and simulations (e.g. between shots feedback for plasma physics)
Multistage Pipeline AI improving HPC	 Data flows in one direction from HPC to one or many AI or HPC components AI filters control many HPC simulations Typically interaction done without human in the loop 	 Real-time requirements Dynamic composition with branching in the workflow based on filters Running in one facility 	AI-in-HPC and AI-out- HPC - Large-scale MD simula- tions using AI sampling of a system with many degrees of freedom
Inverse Design AI improving HPC HPC improving AI	 Control flow from AI to HPC Multiple HPC simulations and/or instruments sending data to AI (one or many) Typically interaction done without human in the loop 	 Real-time is optional (AI can use existing datasets) Execution can be concurrent or asynchronous Running in one facility 	AI-in-HPC - Materials discovery to ad- dress the problem of data sparsity and reduce the need for domain-specific knowledge
Digital Replica AI improving HPC HPC improving AI	 Data/control flow in both directions combining exper- iments and/or HPC with AI Multiple HPC to one AI Potentially human-in-the- loop to adjust future runs 	 Real-time requirements with monitoring and visual- ization Static composition with only visualization started on the fly Components can po- tentially be executed dis- tributed 	 AI-about-HPC Digital twin of a fusion reactor running concurrent with ITER [18] and moni- toring Digital twin for new in- sights into disease mecha- nisms.
Distributed Models AI improving HPC	 Data and control flow in both direction (AI to HPC and other AI and HPC to AI) One or many HPC and many AI (analysis, repli- cas) Optional human in the loop 	 Near real-time requirements Typically static composition, dynamic for adapting to the WAN performance (e.g. compression accuracy) Geographically distributed 	 AI-out-HPC and AI-about- HPC Edge-to-HPC execution of large-scale simulations Interactive notebook- based analyses of instru- ment data and AI output
Adaptive Training HPC improving AI	 Data flows from one HPC simulation to multiple AI Control flows from analy- sis to HPC and AI training No human-in-the-loop 	 Near real-time requirements for AI, optional with HPC Dynamic composition Running in one facility, pos- sible federated in the future 	AI-out-HPC-Hyperparameter opti-mization workflows-Distributed training oflarge language models

Table 1: Summary of motif characteristics according to their scope, interaction patterns, and coupling patterns and example use cases.

in pursuing their scientific objective. For example, this speed-up can be measured as the gain in terms of simulated time performed while covering the same parameter space, quantified by the states sampled by the HPC simulation. The corresponding studies use either custom-designed solutions to couple the codes [19] or workflow management systems, such as DeepDriveMD [22] for protein folding simulations, or Colmena for electrolyte design [23].

Generally, the steering is done in near real-time, with the AI inference running concurrently and interacting with the simulations. A human-in-the-loop component can be added to the workflow, as in [24], to enable the interactive deployment and steering of ensembles of fluid dynamics simulations. This framework provides distributed steering and visualization through a user interface. It allows for the performant execution of interactive simulations for many scenarios while increasing their accuracy via hierarchical refinements thanks to inputs from both the analysis codes and scientists.

DeepDriveMD [2] is a general-purpose framework to run an analysis code (as a separate application) that pre-processes the simulation data (e.g. selecting only a subset of atoms of interest or calculating physical parameters for a protein's native state), and then uses machine learning (ML) models on the pre-processed data to decide which simulations to run next and terminates the less productive MD simulations. By focusing on promising regions of the parameter space, AI-based steering can efficiently navigate complex, high-dimensional systems that were previously intractable. AI systems can also significantly reduce the computational resources required to obtain accurate results by steering simulations toward more relevant configurations.

The aforementioned example is a typical implementation of the Steering motif, but other examples using different coupling solutions while sharing the characteristics presented in Table 1 exist. The AI system analyzes the output of the HPC simulation and either steers the existing simulation or triggers new simulations based on the outcome.

Multistage pipeline

Many HPC applications are executed as a pipeline with distinct stages and data dependencies between these stages. The transition between subsequent stages can be controlled via AI-based logic that decides whether the next stage needs to be triggered based on reaching some set criteria or meeting a specified objective. A transition can also involve an analysis to filter out data between subsequent stages. All these patterns are composed into the Multistage Pipeline motif illustrated by Figure 3b.

- Interaction patterns: Data moves from HPC stages generating data to one or many AI analyses consuming it, but can also be passed between HPC applications executed in sequential stages. AI controls which HPC stage will be executed. Thus, data and control flow in one direction in a many-to-many or many-to-one fashion. Most of the time, the process is automated without requiring humans to analyze the output of the AI codes.
- Coupling patterns: While near real-time interaction is a requirement, processes are not typically spawned or terminated as in the Steering motif. However, the workflow flow is dynamic by definition, with branching based on filters. Typically, the entire workflow is executed on a single system.
- Scope: AI is primarily used to branch the execution of HPC to guide it toward optimized results. The scope of the Multistage Pipeline motif is thus to improve HPC.

The following examples are typical implementations of the Multistage Pipeline motif that we identified in the literature. The AI/HPC stages are either separate applications or integrated into multiple hybrid applications typically deployed on HPC systems sequentially or pipelined.

High-Throughput Virtual Screening Pipelines are emblematic of this motif. For instance, a virtual drug discovery pipeline can use AI to improve the effective sampling of individual stages [25]. Integrating multiple workflows, which can each be an AI-coupled HPC workflow, into a single multistage pipeline is another example of AI-driven discovery [26]. AI can also be used in workflows composing multiple multi-fidelity simulations to dynamically adjust how many and what fidelity levels to run based on the desired outcome [27].

Less complex multistage pipelines can be found in neuroscience [28, 29] and cancer research [30]. Both fields employ workflows composed of a sequence of medical image processing applications that process the same Magnetic Resolution Image (MRI) or Whole Slide Image (WSI) with the output of one application informing the following decision. Each image-processing application is typically a mix of HPC and AI codes composed of multiple stages, including cleaning, standardizing, analysis, and post-processing within one large code or as separate applications. One such workflow is, for instance, used to identify lesions in the brain [29]. It consists of a 3-stage pipeline, starting with a set of MRI images that go through a whole segmentation code, followed by a surface reconstruction application, and finally by an application to create a structure of the brain in MRI space. Based on the output of these three applications, the workflow can further trigger additional codes depending on the research objectives. Similar strategies are used in biological and material sciences [31]. For instance, an AI system can parse the output of a first simulation to extract the respective starting configurations of an ensemble of simulations, each performed on patches consisting of multiple lipids and containing one or more proteins [32]. With further advancements in AI algorithms in these fields, the coupling patterns might also evolve, allowing a closer interaction between the AI and HPC. This can be done either by having the AI produce new intermediate data on demand or by allowing the AI to integrate data from various resources to optimize existing ones in the HPC simulations that are executed concurrently.

Inverse design

Deep learning has been used to solve inverse problems, i.e., determining causal factors from a set of observations, in many scientific fields, including material science [33, 34], nanophotonics [35, 36, 37], or heat transfer [38]. However, the lack of sufficiently large training data sets is often a crucial issue for these learning algorithms since their accuracy heavily relies on the amount and the quality of the available data. This is, for instance, the case with material characteristics identification, which requires a huge amount of user time to acquire observational data. HPC simulations have recently started generating sufficient noise-free data to train AI models. The new challenge is getting accurate simulation results, often requiring extensive testing and expertise to fine-tune input parameters. This can also be time-consuming and resource-intensive, especially for complex simulations since it requires validation over many tests. AI-coupled HPC workflows following the *Inverse Design* motif address this data sparsity problem and reduce the demand for domain-specific knowledge in determining the input parameters of a simulation.

Figure 4a illustrates the typical structure of the Inverse Design execution motif. Inverse Design algorithms usually rely on gradient-based AI algorithms searching through a high-dimensional design space's enormous degrees of freedom. They are coupled with simulations or experiments to guide the simulation towards more efficient designs and may re-train or update the models online as the simulation and experiment progress.

- Interaction patterns: Workflows in this motif execute multiple HPC simulations (potentially together with instruments), sending data to AI (possibly multiple if online training is used). Control flows from AI to HPC using iterative refinement of design parameters. Typically, there is no human steering in the loop.
- Coupling patterns: The AI can use data that has been previously generated (in which case real-time interaction is optional). The execution of the HPC and AI components is static, concurrent, or asynchronous and usually occurs in the same system.
- Scope: AI models are improved to reflect physical phenomena better, while the model can improve HPC simulations. Thus, the Inverse Design motif aims at improving both AI and HPC components.

A powerful illustration of this motif is its application to material design [39]. The method determines material behaviors and consists of three phases: data generation, training, and the inverse phase. The data generation phase uses a set of HPC simulations, each testing different material properties using various material parameters as inputs. In the training phase, a Deep Neural Network (DNN) model is trained on the simulation outputs and the material parameters. The inverse phase compares the prediction and real input values to improve the DNN model and simulation performance. Based on the model's output, new simulations are triggered, improving both the HPC simulation's performance and the AI system's accuracy.

Examples of inverse design workflows can be found in several other fields: bioinformatics, biochemistry, material science, and nanophotonics. Recent breakthroughs in AI-based protein structure prediction (i.e., sequence from the structure) have set the stage for the use of AI models for solving the inverse problem in molecular sciences (e.g., protein design) [40, 41, 42]. Similarly, in materials science [43, 44] workflows for the inverse design problem have been implemented where the physics simulation is coupled with different optimization methods (e.g., directional Gaussian smoothing for nanophotonics [43]) to improve the model used.

Digital replica

The Digital Replica motif incorporates workflows that couple the training or usage of AI systems that simulate the behavior of physical phenomena (e.g., for digital twins [45]) with the HPC simulation and/or a scientific instrument for a variety of scenarios and situations in a range of disciplines and fields. These workflows typically utilize low-fidelity models or advanced data-driven AI models to generate insights not possible using traditional high-fidelity simulations or observational models (given time and computing resource restrictions). Figure 4b presents an overview of the computational pattern for this motif. The digital replica receives data from the HPC simulation/instrument. It triggers analyses to steer the simulation (in near real-time automatically or post-mortem using a human-in-the-loop intervention to tune the parameters



(a) Iterative refinement of design parameters combining experiments with HPC simulations and AI surrogates



(b) Physics-based models combining HPC high-fidelity simulations and AI reduced order models and/or digital twins

Figure 4: Workflow computational patterns for the Inverse Design (a) and Digital Replica (b) motifs

of the next simulation run). Initial training is typically done offline before the execution of the workflow and re-triggered to update the model based on discrepancies between what is predicted by the simulation and feedback from the analysis.

- Interaction patterns: Data and control flow in both directions, with the HPC simulation/instrument data being used to steer the training of AI models and the data generated by the digital replica being used to predict and control the HPC components. Humans may be involved in monitoring and adjusting current and future runs.
- Coupling patterns: Real-time interaction is required. Typically, the composition of the workflow is static, and the flow patterns change only when visualization is turned on. The AI and HPC components can run in the same facility or are geographically distributed (e.g. when instruments are involved).
- Scope: Both AI and HPC components are improved, the AI predictions improve the run of the HPC and the data generated by HPC improve the digital replica.

Relevant studies that fit this motif come from diverse domains (e.g., bioinformatics / medical domain [46, 47]) where machine learning and multiscale modeling are combined to create a digital twin, steer expensive analysis codes towards new insights into disease mechanisms, and help to identify new targets and treatment strategies.

The coupling of HPC simulations with surrogate AI models can be implemented and deployed in HPC systems differently with different performance implications [48]. This study explores three coupling schemes: tightly coupled, which forms a single executable with one-to-one node mapping; semi-tightly coupled, with separate executables mapped in various ways; and loosely coupled, where separate executables run on different machines using many-to-many mapping. It also recommends running digital twins on different architectures and with different models. It shows the potential benefits of these workflows with a use case in materials science.

Fusion energy researchers are turning to digital twins as a promising avenue for efficient whole-device optimization and virtual component qualification, crucial for successfully designing fusion reactor components under conditions that defy real-world testing. Digital twin workflows are primed to play a crucial role in ensuring the success of ITER [18], and pave the way for the future of commercial fusion energy. Several studies [49, 50, 51] presents the vision of the fusion science community to develop future workflows. They all discuss the design of a workflow combining digital twins of different parts of the fusion reactor (e.g., the Central Solenoid Converter Power Supply grid [49]) coupled with real-time simulation strategies to monitor and study the performance of the ITER grid while the reactor is functional.

Distributed models and dynamic data

The data analytics modules (e.g., the AI system) in previous motifs are typically executed using the same computing resources as the simulation. In some cases (e.g., when visualization is used or instrument data needs to be managed),

parts of the workflow can be executed on a remote site, including the scientist's laptop. However, resource management strategies are usually static, and workflows do not adapt their structure to performance changes. The rapid development of edge infrastructures and localizing large amounts of potentially unnecessary data have motivated the development of edge analytics. The corresponding execution motif is illustrated by Figure 5a. Workflows in this motif couple HPC simulations and instruments with geographically distributed AI digital twins, AI surrogate models, and AI analytics (including multiple clusters, compute resources on the edge, user laptops, etc.). The workflows dynamically adapt to the network and compute capabilities from the point of view of task placement and resource management (e.g., triggering new analysis or compression, adapting the accuracy of the data transfer, allocating new resources, or spawning redundant computation for better resilience).

- Interaction patterns: Data and control flow in both directions from multiple AI to multiple HPC (e.g., edge AI monitoring or AI filtering steering, AI digital replicas generating data, HPC simulations generating data, and updating the AI edge analysis components). For near real-time experiment steering, no human is involved in the process; however, configuring the execution of future experiments or large-scale simulations typically requires humans in the loop to monitor the output of the previous analysis.
- Coupling patterns: Near real-time is required to analyze the state of the simulations/digital replicas and the state of the networks for the workflow to adapt. The workflows typically use static composition in the executed components but employ dynamic flow paths and configurations to provide good performance regardless of the state of the systems and applications. The execution is always performed in a federated manner.
- Scope: The main scope of workflows in the Distributed Models motif is to improve the execution and/or productivity of the HPC simulation or instruments.

Typical examples of this motif include diverse models on the edge-to-exascale continuum [52] and coupled simulations across multiple HPC centers [53, 54]. The workflows presented in [52] combine resources and services at the center of the network (in Cloud and HPC data centers) with computing and storage capabilities at the edge and in transit along the data path.

For coupling simulations across multiple HPC centers, it is possible to rely on a single workspace that provides a global view of information shared from multiple geo-distributed HPC data centers [53]. The feasibility of distributed workflows has been shown by coupling the Rosetta-based scientific tools with interactive notebook-based analyses executed outside the HPC center [54]. Another application of this approach is for neutron scattering science [55], for which the performance challenges related to the transfer of large files between the HPC center and the experimental facility have been identified as one of the main performance bottlenecks for the deployment of workflow motif. A complementary work to these studies investigates the overhead and performance of coupling non-HPC systems (equivalent to edge devices) to handle HPC workflows [56].

Finally, a survey of the field of federated learning [57] highlights potential performance bottlenecks. The study of challenges associated with orchestrating complex workflows in geographically dispersed environments [58] also highlights the lack of efficient mechanisms for managing multistage workflows that dynamically traverse distributed computing resources, edge devices, and instrument networks. Addressing this gap requires novel paradigms for orchestrating workflow execution across diverse platforms and geographical boundaries.

Adaptive execution for training large AI models

The previous motifs include training as part of their execution workflow either offline before running the workflow or online by updating the models based on the discrepancies between the simulation output and the predictions. This last motif (Adaptive Training) focuses on the training phase as a standalone workflow. It encapsulates all the adaptive methods to train one or an ensemble of models using an existing dataset or running coupled with the HPC simulation that generates the required training data (Figure 5b). The training algorithm can interact with the simulation and guide its execution to guarantee better data coverage for building robust models. This guidance can be done within the training code or through a separate analysis code (e.g., the figure's "Data quality" box). The analysis code that verifies the accuracy of the created models may trigger a new training event (e.g., using different model parameters) or spawn new simulation instances. The workflow can have a human-in-the-loop component to guide the process towards specialized models.

• Interaction patterns: Data flows from HPC to multiple AI; if surrogates are used to generate data, the data flow is from AI to AI training. Control flows from the analysis code to the HPC and AI training. Typically, the process is automatic, and the human controls only the initial configuration of the workflow.





(a) HPC simulations coupled with experiments and AI surrogate models and AI analytics geographically distributed using dynamic interaction and resource management

(b) Adaptive methods for training ensemble of models with large datasets on HPC potentially coupled with simulations that generate the data needed for training

Figure 5: Workflow computational patterns for the **Distributed Models** (a) and **Adaptive Training** (b) motifs

- Coupling patterns: Real-time coupling between AI and HPC is optional since previously generated datasets can be used. The AI and analysis components require real-time coupling. Dynamic composition is required, with the analysis code optimizing the training process by terminating low-accuracy models and spawning processes with configurations likely to increase the accuracy. Typically, the training is done on the same system. However, federating learning might start using similar workflows in the future.
- Scope: The scope of the Adaptive Training workflows is to train accurate models and to improve AI components.

There have been a variety of HyperParameter Optimization (HPO) approaches in the recent years for designing hyperparameters for deep learning on HPC, including using Bayesian optimization [59], evolutionary algorithms [60], or genetic algorithms [61]. These methods have been used in HPC for the development of AI surrogate models and traditional semi-analytic reduced models (e.g., to build an AI model predictive control for optimal real-time control landing of spacecraft [62]) or for building AI-based analysis routines (e.g., the MENNDL HPO is used to build models for cancer pathology to classify tumor-infiltrating lymphocytes [60]). Other examples of this motif include Neural Architecture Search (NAS) [63, 64], Large Language Model (LLM) searches [65, 66], Adaptive LLM training [67, 68]. Enabling dynamic interactions between learning agents like HPO, NAS or LLMs, and HPC simulations (with or without human intervention) is becoming increasingly used in several fields: computational fluids dynamics [69], fusion [20], energy physics [21], and climate science [70]. These studies combine HPC with AI to optimize the training process by steering the simulation to generate real-time data. The FASTRAN-IPS [20] workflow is an example of the training being done online in a strongly coupled fashion. The simulation generates data iteratively that is then used to train a surrogate model. At every step, the AI algorithm identifies gaps in the parameter space and steers the simulation to generate the missing data. Coupling AI and simulation with visualization is also used to allow users to interactively explore complex parameter spaces given by a large number of simulation runs and interactively steer or span new simulations to cover the missing parts in the parameter space. This is when reduced-form simulations developed through machine learning techniques are coupled with visualization to allow interactive feedback and steer the simulation to generate new data [21]. Estimates of the results of the full simulations at a fraction of the computational cost are used to steer the learning process, as the workflow requires a human to inspect the outcome of the simulation.

Summary: Scientific Workflow Applications Using Multiple Motifs

The motifs presented in this section use different coupling and interaction patterns when executing HPC and AI for different scopes. These motifs are not mutually exclusive; we expect future large-scale workflows to combine several motifs. One such example deploys an AI-driven workflow, combining three motifs [71]: (1) it adaptively *steer* MD simulation ensembles; (2) it further couples this workflow with AI-based methods in a *multistage pipeline* fashion; (3) it uses *adaptive execution*

to learn which parts of the parameter space have been sampled sufficiently and to trigger simulations from under-sampled regions. Each component depends on a distinct solution: the steering uses DeepDriveMD, the learning employs a 3D PointNet-based adversarial autoencoder [72], and the overall integration relies on a custom solution.

Scientific computing infrastructure trends toward an integrated research infrastructure (IRI) [73] that will unite data resources, experimental user facilities, and advanced computing resources to accelerate the deployment of large-scale simulations and workflows. Such integrated infrastructures will accelerate the trend of coupling multiple HPC simulations, surrogate models, and digital twins with AI analysis at multiple levels.

However, while initiatives like the IRI will drastically simplify workflow building and deployment, enabling the efficient execution of complex workflows that span diverse scientific landscapes and combine multiple AI-HPC coupling motifs is non trivial. There is currently no solution that fits all requirements across multiple applications and fields and often specialized solutions are preferred at all levels of the software stack. In the next sections, we present solutions for workflow management systems targeted at individual motifs and/or specific to certain domains, discuss the performance of current workflows, and highlight potential directions for this fast-paced changing field.

3 AI-coupled HPC Workflow Management Frameworks

For two decades, automation, simplification, and workflow management optimization have been active research topics in the HPC and distributed systems communities. This has led to developing many libraries, frameworks, and tools for domain scientists to advance their scientific agenda. More recently, diverse research communities in both industry and academia have been working on allowing AI frameworks to go beyond being a standalone black-box operator to facilitate their inclusion into more complex workflows. While the previous section highlighted that several studies involving AI-coupled HPC workflows relied on custom solutions with low portability and high maintenance cost, we observe a convergence of the efforts related to workflow management in both the HPC and AI communities with the recent development of workflow frameworks specifically targeting AI-coupled HPC workflows. We review some of these frameworks and identify their connections with the execution motifs identified in the previous section. Then, we identify several challenges related to the development of those frameworks.

3.1 Overview of Workflow Management Frameworks

Table 2 lists these frameworks and summarizes their main characteristics. When applicable, we also indicate the underlying workflow technology on which the framework is built. We distinguish frameworks developed with a specific application domain from more general-purpose tools that address issues shared by several application domains, e.g., optimizing data access patterns and related I/O operations.

The Cancer-Distributed Learning Environment (CANDLE) [74, 75] application workflow includes data acquisition, analysis, model formulation, and molecular dynamics simulations. AI is used to develop and test protein binding hypotheses and better understand proteins' behavior on cell membranes. This requires performing Hyperparameter optimization to identify the most effective model implementations efficiently. CANDLE directly incorporates parameter exploration methods for the efficient exploration of parameter spaces of orders greater than 10⁹. These methods manage large amounts of data and rely on scalable data parallelism to speed up the AI model.

The DeepDriveMD [76] framework has been designed to effectively reduce the dimensionality of MD simulations to get insights into how proteins fold. The objectives are to build latent representations that automatically correspond to biophysically relevant reaction coordinates (RCs) and drive MD simulations to automatically sample potentially novel conformational states based on these RCs. The AI-coupled HPC workflow underlying DeepDriveMD is composed of four main steps: (i) A large ensemble of MD simulations generates the initial data needed to (ii) train a Deep Learning algorithm, (iii) whose inference step identifies new starting points in the ensemble of MD simulations, and (iv) enable the actual steering of the ensemble. This AI-driven steering may consist of either expanding the pool of initial MD simulations or pruning simulations that seem to be stuck in meta-stable states.

The objective of the Multiscale Machine-Learned Modeling Infrastructure (MuMMI) [77] is to couple a large-scale parallel simulation of a macro-scale model based on dynamic density functional theory that spans micrometer lengthand millisecond time-scales with a micro-scale model based on high-fidelity MD simulations. MuMMI completes this workflow with an AI-driven importance-sampling framework to bridge the resolution gap between the models. It identifies sub-regions of scientific importance in the results of the macro-scale model, which then serves as candidate inputs to many thousands of coarse-grained MD simulations. The results of these fast-responding simulations are analyzed in situ to avoid the cost of storing them on disk and feed a self-healing feedback loop to improve the parameters of the macro model. To manage such an AI-coupled HPC workflow and steer the framework towards the highest scientific interest simulations, MuMMI relies on the Maestro workflow conductor [78]. Regarding data management, the coarse-grained MD simulations

Framework	Application Domain	Execution Motif(s)	Underlying
			System
CANDLE [74, 75]	Cancer research	Steering — Multistage Pipeline	SWIFT/T
		— Adaptive Training	
DeepDriveMD [76]	Biophysics/Molecular	Steering — Multistage Pipeline	Radical
	Simulations	— Adaptive Training	
MuMMI [77]	Biophysics/Molecular	Steering — Multistage Pipeline	Maestro [78]
	Simulations	— Adaptive Training	
IMPECCABLE [79]	Virtual drug discovery	Multistage Pipeline — Inverse	Radical
	pipeline	Design — Adaptive Training	
Colmena [23]	General-purpose steering	Steering — Adaptive Training	Parsl
	of ensembles		
SmartSim [80, 81]	A scalable, open-source,	Steering — Multistage Pipeline	Redis
	multi-physics simulation	— Digital Replica — Adaptive	
	API.	Training	
Stimulus [82]	General-purpose data	Inverse Design — Digital	-
	management library	Replica — Adaptive Training	
NoPFS [83]	General-purpose I/O	Inverse Design — Digital	-
	middleware for model	Replica — Adaptive Training	
	training		

Table 2: Characteristics of domain-specific and general-purpose AI-coupled HPC Workflow frameworks.

launched by MuMMI could generate PB of data in over 400 million files, a number to multiply by 10 when AI is added to the workflow. MuMMI implements several local in situ and data aggregation strategies to reduce the demand on the filesystem.

The IMPECCABLE [79] project aims at defining an integrated modeling pipeline to identify effective chemical compounds to fight COVID-19, by screening tens of billions of molecules. IMPECCABLE uses AI methods to improve both the initial sampling of candidate molecules and the design of surrogate models of multi-physics simulations. It also integrates these AI components and HPC simulations into a single unified three-stage pipeline. IMPECCABLE relies on the Radical-Cybertools [84] to manage the execution of this heterogeneous AI-coupled HPC workflow on leadership computing facilities.

In addition to these frameworks proposed to address the challenges related to the coupling of AI and HPC in a specific scientific domain, we detail hereafter, the intents and characteristics of more general-purpose frameworks that propose solutions applicable to several domains.

Colmena [23] is a framework allowing users to steer simulation ensembles using an AI model. It handles the dispatch of highly computational simulation runs and model retraining tasks, collating the simulation results and invocating the AI model. It relies on the Parsl workflow management system to handle the heavy computations and their results. Colmena also offers a framework called the Thinker to design a decision-making multi-agent process adapted to the users' needs. Each agent can post task requests, handle results, or react to resource-related events using Redis queues. The AI component thus serves as the actual pilot of the simulation campaigns, deciding which inputs to select, in what order, and when to execute each simulation run.

The SmartSim [80, 81] framework, developed by Hewlett Packard Enterprise enables the composition of HPC simulations and AI models into an in situ workflow. The HPC simulations act as data producers, that generate training and inference data while the AI component consumes this data either for training or inference. SmartSim relies on an in-memory database to store any information shared by the HPC simulations and the AI components for the duration of the run, which allows for interactions without having to pay for expensive file-based accesses on a shared parallel file system. It also exposes a multi-language communication API based on the publish/subscribe paradigm, which facilitates the connection of scientific codes, usually written in C, C++, or Fortran, and the Python-based ML frameworks.

Stimulus [82] is a data management library designed to ingest scientific data into popular AI frameworks efficiently and safely. It aims to address the problem of data format and access pattern incompatibility when HPC simulations and AI components are combined in one of the motifs introduced in the previous section. Indeed, following a strongly coupled approach in which HPC simulations and AI components would share the same format is intractable and will duplicate efforts. The approach followed by Stimulus is to unify several popular scientific data formats (e.g., NetCDF, HDF5, ADIOS) under a single interface that hides the complexity of each format. Additionally, Stimulus proposes a generic data ingestion pipeline that any tensor-operator-based AI framework can execute.

NoPFS (Near-Optimal PreFetching System) [83] is Machine Learning I/O middleware aims to reduce shared filesystem contention when ingesting data to train a model. To this end, NoPFS leverages the clairvoyance an I/O system can have by determining how access will be made from the initial seed of a pseudo-random number generator. This clairvoyance allows NoPFS to efficiently prefetch data, exploiting the whole storage hierarchy available on a compute node and minimizing access to the shared filesystem. It is not an AI-coupled HPC workflow system per se, but using NoPFS to manage the I/O model training would free some throughput on the parallel file system, which could then be used by HPC simulations.

Note that the integration of AI components into more complex analysis workflows is not limited to the HPC community. For instance, the Kafka-ML project [85] aims to connect the Apache Kakfa distributed messaging system to AI models to get more insight from the continuous data streams from the Internet of Things sensors. Similarly, the Redis NoSQL database server includes a module, RedisAI, allowing to develop inference servers fed with Redis data streams [81] In the context of initiatives such as the Integrated Research Infrastructure from DOE that aims to connect experimental facilities producing such data streams to leadership-class HPC systems, we envision that stream processing frameworks will become part of complex AI-coupled HPC workflows soon.

3.2 Challenges

Studying these different frameworks highlights two main challenges to developing AI-coupled HPC workflow management frameworks. The first challenge is the coexistence and communication between HPC and AI tasks in the same workflow. This communication is mainly impaired by the difference in programming languages used in HPC (i.e., C, C++, and Fortran) and AI (i.e., Python). One solution to circumvent this language barrier would be to consider that all communications between HPC simulations and AI models are done through data. However, this raises other issues related to differences in data format and access patterns [86]. The successful and efficient management of AI-coupled HPC workflows thus call for a more unified data plane management in which high-level data abstractions could be exposed, and the complexities of the format conversion and data storage and transport could be hidden from both the HPC simulations and AI models.

The second challenge concerns using the insight provided by AI models in the HPC simulations. For the motifs outlined, this insight is used to guide, steer, or modify the shape of the workflow by triggering or stopping new simulations. This implies that the workflow management system must be able to ingest and react dynamically to inputs coming from the AI models. However, most existing workflow management systems enforce a static description and execution of the workflows. New methods must be designed to enable more flexible and adaptive workflow executions. Moreover, the more complex and evolving data transfer patterns associated with such more dynamic workflows may directly impact the performance of AI-coupled HPC workflows if not managed properly. As feedback loops have additional dependencies between workflow components, any delay in data production and storage directly impacts the components that consume data, which have to wait to start their execution and remain idle.

In this section, we considered frameworks developed to automate the execution of AI-coupled HPC workflows in different scientific domains or designed to address some common challenges from the perspective of their matching with the proposed execution motifs. However, the sheer amount of data handled by these frameworks (e.g., "scaling to full memory (> PB) on the largest supercomputers" [74]), the high level of task concurrency they manage (e.g., 16k concurrent tasks for DeepDriveMD [76]) or both (e.g., 36k concurrent tasks and several PB of raw data for MuMMI [77]) can have some important performance implications. In the next section, we focus on these performance considerations of AI-coupled HPC workflows.

4 Performance

To analyze the performance of AI-coupled HPC workflow executions, we consider its fundamental components and various strategies. Furthermore, we discuss each workflow component's challenges and performance implications and explore how different coupling strategies affect performance. Then, we review the six execution motifs in the context of these components and their coupling, addressing the various challenges and bottlenecks. Summarizing the section in Table 3, we provide a comprehensive overview of the main characteristics of each motif, the associated typical performance bottlenecks, and coupling strategies. Lastly, we investigate the implications of software implementation and the significance of benchmarking such workflows.

As we delve deeper into the intricacies of AI-coupled HPC workflows, it becomes evident that several open issues emerge, particularly regarding interoperability, data handling, and resource allocation. These challenges underscore the importance of understanding the performance and highlight broader opportunities to enhance the efficiency and effectiveness of such workflows.

4.1 Workflow Components

Each workflow component has performance implications individually and in their coupling. In general, for AI, especially for AI raining, there is a trade-off between <u>computation</u> vs. <u>communication</u> [87]. Offloading to AI accelerators requires data movement and may be largely affected by how the accelerators are integrated into the main supercomputer. GPUs typically achieve lower latencies for large batch queries, although they incur significant loading overhead; conversely, CPUs usually exhibit lower loading latencies and excel with smaller batch sizes [88]. This topic has been studied comprehensively in Ref. [89] for an AI-driven simulation across cross-facility infrastructure performing simulations on a traditional HPC supercomputer while offloading the AI model to a Cerebras accelerator, a wafer-scale application-specific integrated circuit (ASIC) device.

Data Ingestion	\rightarrow Data Transformation \div	Model Training –	• Model Deployment
(a) Machine learning training and deployment pipeline			



(b) Pipeline for typical HPC applications

Figure 6: The HPC and AI pipelines concurrently running within a workflow typically overlap different stages depending on the type of workflow they are deployed in

Understanding these performance implications is crucial when considering the entire machine learning training and deployment pipeline, as shown in Figure 6a [90]. The computation and communication trade-offs inherent in using accelerators like GPUs or specialized hardware such as Cerebras influence this pipeline at each step. For example, while GPUs might accelerate the Model Training stage for large batch sizes, the initial Data Ingestion and Data Transformation stages might still depend heavily on traditional CPU processing. This interplay between different hardware capabilities emphasizes the need for a nuanced approach in optimizing each pipeline stage for efficient AI model development and deployment in HPC environments. Note that we do not consider the evaluation of the model in performance analysis, as it is primarily concerned with the accuracy of the model, while its computational cost will be discussed in the section on the Model Deployment.

The HPC pipeline illustrated in Figure 6b has typical I/O and communication network performance considerations. As HPC simulations evolved to include GPU kernels and/or AI in their codes, the trade-offs described in the previous paragraph are also becoming relevant for the HPC components. When deployed together, the AI and HPC components will overlap different stages of their respective pipelines and face new performance bottlenecks that are unnecessary during individual runs. For example, the Data Production phase of the HPC application will typically overlap with Data Ingestion for the Steering motif, which might cause concurrent read/write access to the same datasets, resulting in performance penalties due to I/O contention.

4.1.1 Data Ingestion

Traditional HPC simulations rely on I/O libraries highly tuned towards large sequential file access (like ADIOS2 or HDF5), Deep learning frameworks typically train on mini-batches of data, which tends to perform poorly on parallel file systems such as Lustre and GPFS [91]. Efforts such as tf.data seek to improve parallel I/O performance by encapsulating the batches as files [92]. On the HPC side, studies are trying to integrate AI loaders with I/O libraries having different strategies and performance implications. For instance, Stimulus [82], discussed in Section 3, is a data management library for ingesting scientific data into AI frameworks such as TensorFlow, PyTorch, and Caffe. Other solutions (like HVAC [93]) use caching mechanisms to exploit the node-local storage or near node-local storage to accelerate read I/O and metadata lookups for deep learning applications running on HPC systems.

4.1.2 Data Transformation

Before data is used, it typically needs to be pre-processed, which may involve feature scaling, resizing, etc. This is true both for training and inference. Brewer et al. [94] studied the life-cycle performance of distributed inference requests and showed that pre-processing on the CPU can be the most expensive component in the inference life-cycle. Recently, there have been efforts to speed up pre-processing using GPU. For example, Schifferer et al.[95] were able to speed up their feature engineering pipeline by using a combination of RAPIDS CuDF, Dask, UCX, and XGBoost on a single machine with multiple V100 GPUs.

4.1.3 Training

Model training is performed either on a single device or multiple devices in a distributed way, which is generally implemented as *data-based* parallelism, *model-based* parallelism, or both. Data-based parallelism methods shard the training data, such that synchronous parallel processes each use a portion of the training data, and either collective communication libraries – such as NCCL, MPI, or Gloo – are used to perform an all-reduce to average the gradients during training [96], or RPC-based methods such as gRPC are used to communicate the gradients. Model-based parallelism may be required when the *memory footprint* of the model exceeds the capacity afforded by the GPU. Additional techniques such as Tensor-parallelism and Pipeline-parallelism extend this approach by partitioning across or within the model's layers.

The performance of AI models is sensitive to floating point number precision, and there exists support from software stacks on diverse systems to support various formats such as half-precision to double-precision. Mixed-precision enabled implementations vary the precision per layer and can be enabled on the fly, such as the Automatic Mixed Precision (AMP) on Nvidia GPUs. Benchmarks play a pivotal role in evaluating the performance of training such models, which we will further discuss in Section 5.3.

4.1.4 Model Deployment

Model deployment involves optimizing the model for inference performance, which may involve freezing weights, fusing network layers, quantization, and calibration [97]. Tools such as TensorRT for NVIDIA accelerators and OpenVINO for Intel accelerators may perform such optimizations for specific targets. Brewer et al. [98] show a 10X speedup using TensorRT to deploy a MobileNetV2 model on an NVIDIA T4 GPU. Inference is performed asynchronously parallelly using in-memory approaches such as TensorFlow C API or distributed inference serving approaches such as TensorFlow Serving or RedisAI [81].

Large-scale inference, such as required for LLMs as Transformers, poses additional challenges. Pope et al. [99] studied the inference performance of Transformer models with 500B+ parameters and elucidated the challenges involved in efficiently scaling inference for LLMs. First, because the models are generative, they proceed sequentially in time, so subsequent inferences depend on the former ones. Second, models with a large *memory footprint*, exceeding the capacity of a single accelerator, need to be partitioned across multiple accelerators, resulting in additional communication overhead. They study optimal ways of partitioning the models to maximize inference efficiency and demonstrate scaling the Transformer model across 64 TPU v4 chips.

The speed and efficiency of these inference processes are heavily influenced by how multiple components are coupled (e.g., how the HPC simulation is coupled to an AI model) and whether the inference is executed in memory or sent to a remote inference server on a CPU or GPU. The inference latency, a critical factor in these scenarios, is affected by the network and interconnect performance and the capability of the AI accelerator or GPU. Fast and efficient inference is thus a culmination of optimized model deployment strategies, appropriate use of hardware resources, and effective management of network and interconnect systems. Using benchmarks is crucial to assessing these complex challenges in model deployment and large-scale inference. This aspect, including how benchmarks inform strategies for scaling and optimizing inference performance, will be elaborated in Section 5.3.

4.2 Coupling Approaches and Protocols

Having discussed the performance implications of individual workflow components, we now focus on the broader context of AI-coupled HPC workflows. In particular, we will explore various coupling approaches used in AI-coupled HPC workflows, each utilizing specific protocols and middleware patterns tailored to their use cases. To clarify, an *approach* refers to the overall method or strategy used for coupling components, including both the interaction patterns (e.g., data-flow and control flow types and directions) and coupling patterns (e.g., concurrency and dynamism requirements), whereas the *protocol* describes the implementation details of how the data and control messages are exchanged. For instance, inference deployments often employ request-response type interaction patterns, such as HTTP or gRPC, which facilitate communication between client applications and server-side inference models. For example, SmartSim deployments of *digital replicas* use the the Redis Serialization Protocol (RESP) to perform request-response inference calls. In contrast, distributed deep learning architectures using in *adaptive execution* typically rely on ring-all reduce type coupling patterns, using protocols like MPI, NCCL/RCCL, or Gloo, to efficiently handle gradient averaging across multiple nodes. More traditional machine learning applications, like those found in data analytics, tend to use map-reduce style interaction patterns, exemplified by frameworks such as Spark or Hadoop, for processing and analyzing large datasets. Additionally, *distributed models* in edge computing or IoT scenarios may adopt publish-subscribe interaction patterns, with protocols like MQTT (used in systems like KubeEdge), to manage data flow between various distributed devices.

To exemplify performance differences between types of distributed training implementations, consider that early versions of TensorFlow, which used the parameter server (request-response) architecture for distributed training, achieved only 50% parallel scaling efficiency, whereas early versions of Horovod using ring-all reduce achieved 90% parallel scaling efficiency [96]. In addition, implementations such as MPI can take advantage of InfiniBand, whereas protocols such as gRPC only support communication over Ethernet.

The critical insight to remember is that the performance of a specific workflow is substantially influenced not only by the efficiency of its elements but also by the way those elements are interconnected and integrated. Several studies have attempted to investigate how the coupling of workflow components affects overall performance [100, 101, 102, 103, 104, 105, 106]. Several studies have attempted to investigate how the coupling of workflow components affects overall performance [100, 101, 102, 103, 104, 105, 106].

Regarding protocol performance, Brewer et al. [100] benchmarked inference performance using three different inference serving techniques: HTTP over InfiniBand via a Python-based HTTP server, gRPC over Ethernet via TensorFlow Serving, and the Redis serialization protocol (RESP) via RedisAI. They experimented with several different approaches for load balancing, including using a thread pool, an HAProxy round-robin load balancer, and using MPI. Achieving good scalability required maximizing the batch sizes, which were on the order of 262k samples, and running a single load balancer per node, which round-robinned the inference requests to the multiple GPUs on that particular node (i.e., strong coupling). They demonstrated one million inferences per second for their model on 192 GPUs on the Summit supercomputer. Boyer et al. [102] extended this approach to benchmark *digital replicas* in online inferencing mode. They noted that naïve methods of integrating the simulation with the AI model caused substantial slow-downs, which were significantly mitigated by employing the previously mentioned inference server and load balancing techniques.

Regarding coupling strategies, Yin et al. [101] investigated coupling a Monte Carlo simulation to a machine-learned surrogate model using both TensorFlow C++ API and RedisAI inference server. They studied the effect of coupling on inference performance by defining three different coupling types: (1) tightly coupled—in-memory inference with one-to-one mapping between process and accelerator, (2) loosely coupled—distributed inference service on different nodes with many-to-many mapping between the simulation and the model inference server, and (3) semi-tightly coupled—running on same node using inference serving approach, which can have one-to-one, many-to-one, or many-to-many mapping. This is depicted in Fig. 7. They show that tightly coupled deployments are preferred for latency-bound applications, whereas loosely coupled deployments provide better usability via the easy-to-use SmartRedis API.



Figure 7: Various strategies for AI-HPC coupling [101]. Tightly coupled systems embed the AI inference in-memory with the simulation. The resource here represents a type of AI accelerator such as GPU or ASIC. The simulation can be decoupled from the AI model via an inference server. Semi-tightly coupled systems may integrate the components within a single compute node or across multiple nodes on a single supercomputer. Loosely-coupled integrations distribute the components across disparate resources, e.g., in the cloud.

4.3 Motif Performance

We now analyze performance issues for each of the motifs introduced in Section 2 regarding their components and coupling methods. Table 3 summarizes the typical performance bottlenecks for each motif and associated implementation.

Execution Motif	Coupling between HPC sim-	Typical Bottlenecks	
	ulation and AI component		
Steering	In-situ coupling, loose or tight	Data transfer between simula-	
	coupling strategies	tion and AI, latency in decision-	
		making	
Multistage Pipeline	Chaining of components, use of	Data transfer between stages,	
	intermediate data storage	time spent in each stage	
Inverse Design	Iterative feedback loops,	Convergence of optimization al-	
	surrogate-assisted optimiza-	gorithm, computationally expen-	
	tion	sive simulations	
Digital Replica	Co-training of models, hybrid	Model integration and communi-	
	modeling approaches	cation, training physics-informed	
		AI models	
Distributed Models	MQTT, IoT protocols (e.g., Zig-	Edge-to-HPC network latency,	
	Bee), streaming data	limited memory and compute ca-	
		pacity of edge devices	
Adaptive Training	MPI, NCCL, use of data paral-	Interconnect performance, net-	
	lelism or model parallelism	work size variability leading to	
		long-job impediment (NAS)	

Table 3: Summary of execution motif characteristics, performance bottlenecks, and coupling strategies [107].

4.3.1 AI-based steering ensembles of simulations

The Steering motif uses machine-learned models to steer ensembles of simulations. Colmena is an example of such a framework for implementing such a task on HPC and has been demonstrated for molecular design [23]. This type of architecture is similar to distributed reinforcement learning applications, designed to maximize a reward function by running many simulations (environments) in parallel [108]. Dataflow performance is the main challenge for these workflows, especially when a centralized server for task planning that can become a performance bottleneck.

In the Steering motif, data is ingested from parallel simulations, processed, and used to train machine learning models. These models are then evaluated for effectiveness in guiding simulations and deployed in an HPC environment to steer ensembles. For example, Colmena has three processes: a thinker, a task server, and a worker. The thinker communicates with the task server using a request-response architecture, specifically Redis queues, which use the Redis Serialization Protocol (RESP). Workers are scaled up on the system using Parsl [109].

4.3.2 Multistage pipeline

Campaigns involved in the Multistage Pipeline motif are common when integrating several methods at different scales and resolutions. For example, the space of possible molecular configurations might be very large, and any single method cannot explore all possibilities with uniform probability. By using different methods with varying levels of cost and accuracy, the space of possible configurations can be traversed intelligently.

In addition to dataflow across different "executables", this gives rise to numerous performance issues. For example, the concurrent execution of multiple different stages with different computational costs and resource requirements results in a significant load balancing and workload management challenge. Furthermore, suppose AI models are used in conjunction with or as a substitute for each stage. In that case, many of the problems intrinsic to other motifs arise (e.g., dataflow performance bottlenecks in the Steering motif).

Computational campaigns such as IMPECCABLE [25] use a master/worker-type architecture to manage tasks, whereas MPI is used to scale horizontally across multiple nodes. Inference workloads tend to be I/O bound due to tens of thousands of compressed files that must be distributed across all the worker nodes.

4.3.3 Inverse design

Inverse design is a technique of calculating the causal factors that produced them from a set of observations. Such approaches in various domains such as the search for catalysts [110], nanophotonics [111], and material design [112]. Performance in this motif is primarily influenced by how representative the model can capture the causal factors that produced it. This is prone to vary based on the model architecture, computational cost, and ability to work with high data rates. High-energy X-ray Diffraction Microscopy (HEDM) relies on the high-precision (sub-pixel) position of Bragg

diffraction peaks. The computational cost of conventional methods becomes a bottleneck, especially for in-situ experiments with complex detector technologies. BraggNN [113] is a neural network designed to localize Bragg peak positions more efficiently than a traditional conventional pseudo-Voigt peak fitting method in extracting the peak information. A key challenge is enabling trained models to accommodate high data rates from emerging synchrotron facilities [114].

4.3.4 Digital replica

The Digital Replica motif describes the integration of simulations with machine learning models, either in cognitive simulations (CogSim) or digital twins. The performance depends primarily on how the model is integrated into the simulation (coupling type) and compute heterogeneity. As mentioned earlier, this falls into two approaches: (1) in-memory or (2) distributed (via inference server). Jia et al. [115] used an in-memory inference approach via the TensorFlow C API to integrate a molecular dynamics (MD) simulation with a machine-learned model. Their model can efficiently scale up to the entire Summit supercomputer, achieving 91 PFLOPS in double precision and 162/275 PFLOPS in mixed-single/half-precision. For this reason, they won the Gordon Bell Prize in 2020.

Partee et al. [81] investigated coupling a climate-scale, numerical ocean simulation to a machine-learned oceanic eddy kinetic energy (EKE) surrogate model on a heterogeneous cluster, where the simulation was running on many CPU compute nodes. In contrast, the AI model was being served on one or more GPU nodes using a RedisAI-based inference server on a single GPU node with multiple CPU-based compute nodes sending inference requests to the GPU node (i.e., weak coupling). Their model achieved 1.86 million online inferences per second.

Boyer et al. [102] tested both in-memory inference and distributed inference using TensorFlow Serving and RedisAI for three types of physics simulations. They show that using an inference serving approach can outperform in-memory approaches by enabling multi-threading on the inference server and sending concurrent requests to the same GPU, exploiting advantages akin to hyper-threading.

4.3.5 Distributed models and dynamic data

The Distributed Models motif describes workflows where components of the workflow are typically distributed across disparate resources, called the edge-to-cloud continuum, and may be realized as reinforcement learning, distributed deep learning, online learning, transfer or multi-task learning, federated learning, and lifelong or continual learning workflows [52].

There are a couple of performance issues to consider for this motif: (1) performing inference at the edge (whether this will be performed via single-stream, multi-stream, or offline mode), and (2) continually retraining the model to keep up with data skew and drift. When inferencing at the edge, possible considerations must be taken because edge devices usually have reduced memory and computing capacity compared with HPC. Such implementations are complicated by the additional policy considerations for implementation. Tools such as FuncX/Globus Compute[116] lower the barrier to deployment of such models by exposing endpoints publicly via Globus, where authentication is done in the cloud.

Suhas et al. [117] discuss the challenges of building a federated ecosystem for interfacing experimental facilities with simulations on HPC. They mention that one of the main challenges in this workflow motif is to "close the latency gap between computation and instruments". Yin et al. [55] study an example of this approach applied to neutron scattering and also note the performance challenges of transferring large files between the HPC and the experimental facilities.

In addition to the considerations outlined, Dube et al. [118] emphasize the evolving landscape of HPC in the context of distributed models, underscoring the convergence of HPC with AI and data analytics across diverse environments. This 'Internet of Workflows' highlights the growing need for computational models that efficiently manage data movement and optimize workflows across cloud, edge, and traditional supercomputers. Understanding and adapting to these trends is crucial for enhancing performance and scalability in distributed AI-HPC systems.

4.3.6 Adaptive execution for training large AI models

We discuss this motif for three types of implementations: Hyperparameter Optimization (HPO), Neural Architecture Search (NAS), and training LLMs. HPO is typically used to optimize a set of training hyperparameters, such as batch size, learning rate, etc.; this is typically performed by training several neural networks in an asynchronous parallel fashion. Optimization methods generally fall into either random search or Bayesian camps, with novel augmentations such as Hyperband designed to speed up the evaluations by adaptive resource allocation and early stopping [119]. Tools such as KerasTuner may be run distributed using a chief-worker strategy to scale such methods across many nodes on HPC [120].

NAS, on the other hand, is primarily concerned with designing optimal neural network architectures. Two popular methods for NAS include evolutionary algorithms (primarily in the form of genetic algorithms) [121] and reinforcement learning [122]. Regarding implementing such approaches on HPC, Young et al. [123] present the Multi-node Evolutionary

Neural Networks for Deep Learning (MENNDL), which was used to design a Convolutional Neural Network (CNN) on the Titan supercomputer at Oak Ridge National Laboratory. Martinez et al. [124] developed a similar approach called Deep Learning for Evolutionary Optimization (DLEO) and used it to solve a complex compressed sensing problem for reconstructing vibration spectra. Such implementations are generally map-reduce style architecture implementations, which map many training events to multiple accelerators on HPC, reduce the model performance, generate a new set of candidate networks to evaluate, and so on until convergence. Because of such a pattern, researchers have exploited map-reduce frameworks such as Apache Spark to perform such tunings on HPC [125]. Such implementations become more complex when the models are so large each candidate must be distributed across multiple GPUs, as in the case of training LLMs. Such examples of *adaptive training* utilize asynchronous map-reduce style communications organized by the job scheduler. Because different architectural candidates may take longer to evaluate, the typical bottleneck is waiting on a straggling candidate architecture job before proceeding to the next generation in the optimization process. Another performance implication is the cost of the reduction call for each generation.

LLMs are particularly challenging to train primarily because the models are generally much larger than what can fit within the memory of a single GPU, and the models need to be trained on colossal amounts of data. For example, GPT-3 has 175 billion trainable parameters and is trained on 499 billion tokens [126]; it has been estimated that it would take 288 years to train GPT-3 on a single V100 GPU [127]. Considerable developments in data and model parallelism have enabled significant speedup by using data-based parallelism methods, such as Horovod, and a combination of pipeline and tensor model parallelism [128]. Using such a triad strategy of data, tensor, and pipeline model parallelism along with DeepSpeed by Microsoft, Narayan et al. [127] have demonstrated the ability to train an LLM with one trillion parameters at 502 PF/s on 3,072 GPUs. Additionally, with the increasing number of non-traditional AI accelerators, training LLMs require approaches to leverage the hardware. Emani et al. [129] provided a comparative evaluation of training LLM models on diverse AI accelerators. Recent studies have also further explored efficient training strategies and performance implications of up to a trillion-parameter LLMs on leadership-class supercomputers [130, 131]. Achieving such a feat required overcoming GPU memory limitations and minimizing inter-node communication latencies using a combination of pipeline and tensor model parallelism.

5 Open challenges and opportunities

In this section, we identify two main challenges in deploying AI-coupled HPC workflows at scale: (i) the need for codesigning facilities, middleware, and benchmarks that address the performance of both traditional HPC simulations and emerging AI algorithms and (ii) the need to design efficient interfaces that would allow users to describe their workflow needs and their AI-HPC interaction. In light of these challenges, this section aims to reveal open opportunities in each area for the future advancement of AI-HPC workflows.

5.1 Hardware-Software Nexus

One of the main challenges for traditional HPC systems in accommodating AI-HPC workflows is engineering a system adept at performing both traditional simulations and modern AI tasks. This balance hinges heavily on the performance of the internal interconnect, which is highlighted by the vast contrast in performance results between the HPL-MxP [132] and the HPCG [133] benchmarks. The former primarily measures FLOP performance, while the latter measures GPU-CPU interconnect and GPU memory bandwidth performance.

Recognizing this challenge, innovators like SambaNova, Groq, GraphCore, Untether AI, Tachyum, NextSilicon, Cerebras, and Fungible are pushing the envelope, with a central focus on optimizing data movement–a crucial step to boosting efficiency in modern AI training and inference. One of the main ways this is achieved is by "moving the compute element directly adjacent to memory cells" (untether.ai). Secondly, special-purpose ASIC chips are designed for inference, such as tensor processing units (TPU), intelligent processing units (IPU), data processing units (DPU), language processing units (LPU), tensor cores, etc. Another factor to consider is the exploitation of reduced or mixed-precision training and inference. Using tensor cores at reduced precision offers order-of-magnitude improvements in inference performance [100, 98], while GPU CUDA cores support training performance at double precision. There does not always seem to be a good general understanding of what level of precision is required for such scientific applications; such largely depends on the type of application.

Understanding diverse AI accelerators is critical to leveraging them for AI-HPC workflows. These accelerators exhibit great diversity in their hardware and software stacks, which enables them to run a subset of AI models efficiently. For example, the Cerebras wafer scale engine has massive compute cores. In contrast, the SambaNova SN30 DataScale system has one terabyte of memory per device, which supports models with large memory footprints, and Groq aims to accelerate inference-based workloads. The performance of AI models is impacted by choice of implementation, such as C++ or Scikit-learn for classical ML algorithms or frameworks such as Horovod [134], PyTorch DDP [135], DeepSpeed [136], Colossal AI [137], MagmaDNN [138], TensorRT[139], and ONNX [140]. Each framework provides unique capabilities to run the AI models efficiently across varying deployment scales such as edge, cloud, and HPC scales. When DL models are run at a large scale, their performance is impacted by the collective communication overheads, and there exist various algorithms imbibed into these frameworks, such as AllReduce for DDP and Scatter_Gather for DeepSpeed. Specialized libraries such as NCCL provide tunable parameters to further optimize collective communications.

With the increasing model complexity and memory footprint, distributed implementation of AI models [141] is an effective way to deploy models at scale. These approaches include techniques such as data-parallel, model-parallel, tensorparallel, and pipeline-parallel implementations in currently used frameworks. Ben-nun and Hoefler [142] present a survey of approaches for parallelizing various DL networks through parallelism in network training and inference. The authors discuss techniques critical to efficiently running distributed models, such as neural architecture search, asynchronous stochastic optimization, and collective communication schemes. Mayer and Jacobsen [143] discuss the challenges and techniques for scalable deep learning on distributed infrastructures, including hardware resource scheduling, methods, and training and model data management.

5.2 Data and I/O Challenge

HPC platforms have settled on POSIX-compliant parallel file systems as the primary storage engine and interface. Even for an object-based solution such as DAOS, a POSIX shim layer is still needed to meet the requirement of more traditional modes in scientific applications. However, large, sequential read-and-write is no longer the dominant workload pattern for many data-intensive AI-driven workflows. Instead, small, random read/write is much more prevalent – which traditional POSIX-based parallel file systems have struggled to keep pace with. The nominal approach is to provision a node-local storage layer, where a small amount of SSD-backed devices are positioned close to the compute blades and generally outside the storage network used by the parallel file system. The challenge is that decoupling from primary storage necessitates data staging, which can be achieved through policy-driven data tiering or workflow support to streamline the process. The current solution space is not mature enough and thus renders this a particular bottleneck to overcome for data-intensive workflow integration. Projects such as NoPFS and SmartRedis discussed in Section 3 are attempts in the right direction. More recent OLCF-6 RFP [144] calls for an AI-optimized storage system and highlights the challenges and needs in this domain.

5.3 Benchmarking

To effectively evaluate the performance of AI-HPC workflows, benchmarking them on diverse use case scenarios/motifs is essential. Such benchmarks could reveal potential performance bottlenecks and, hence, lead to optimized solutions. Several efforts in this direction include MLPerf [145], HPCAI500 [146], SAIBench from BenchCouncil [147], and HPL-AI [132]. MLPerf [145], developed by the MLCommons consortium of industry, academia, and research laboratories, is a state-of-the-art benchmark suite that includes various machine learning tasks. The MLPerf HPC benchmark [148] has been developed to represent scientific machine learning workloads typical of traditional HPC environments. There is also an ongoing effort to include AI-HPC workflow benchmarks in this suite in collaboration with the MLCommons Science group [149].

In the context of *training* benchmarks, MLPerf [145] and HPCAI500 [146] are notable for their comprehensive approach. These benchmarks often utilize metrics such as "training time to convergence" and "time to train to a specified accuracy", providing a more nuanced view of performance than traditional metrics like "time per batch" or "number of epochs". Recent trends in benchmarking have shifted towards measuring the time required to train models to a certain level of accuracy, reflecting a more realistic assessment of AI model efficiency in practical scenarios. However, these benchmarks' major limitations are the smaller dataset sizes and the complexity of the deep learning models in scientific applications, which do not always represent realistic scenarios in HPC centers. The HPL-MxP (formerly HPL-AI) benchmark [132], for instance, implements the LINPACK benchmark at a lower precision. Currently, there is a lack of a comprehensive suite of AI-coupled HPC workflow-based benchmarks covering most of the motifs presented in Section 2. To leverage these benchmarks effectively, it is important to define performance metrics such as end-to-end execution time, AI model throughput, and accuracy.

In addition to training benchmarks, evaluating *inference* performance is equally crucial in AI-coupled HPC workflows. Methods such as MLPerf Inference [150] offer a comprehensive framework for this, measuring sequential inference performance across various modes, including single-stream, multi-stream, server, and offline (batch) modes. Inference benchmarks like smiBench [100] are particularly useful for studying offline distributed inference performance on HPC systems. Inference *latency* is a key metric representing the time taken for a batch of data to be processed, with results typically reported in seconds or milliseconds. This metric, along with *throughput* measured in Hz or samples per second, provides a detailed view of the efficiency of AI models during the inference phase. The MLPerf Inference benchmark, for instance, adapts its metrics based on the scenario, using 90th-percentile latency for single-stream inferencing and throughput for offline batch inferencing [150].

What do the motifs teach us about benchmarking? Most of the current benchmarking efforts consider an application or model in isolation. There is a gap in incorporating workflows that help measure end-to-end workflows' performance and the crucial components to accelerate the workflow. Since it may be expensive to use the workflows with massive datasets, expensive simulation runs, and complex models, it may be worthwhile to investigate benchmarks that are representative of the actual production runs besides using synthetic data instead of experimental or simulated datasets.

Understanding the performance intricacies is extremely challenging as we see an increased adoption of workflow tools in scientific machine learning applications. This challenge could be addressed by leveraging existing benchmarking efforts in ML and HPC and working to design and develop new benchmarks accordingly. As this benchmarking process is expensive regarding resources and human effort, it is worthwhile to invest in building benchmark-friendly versions of end-to-end workflow use cases, which mimic realistic workflow execution with minimal overheads in datasets and the scale of runs.

5.4 Cross-cutting: Interoperability, Energy-Efficiency and Resource Allocation

AI-coupled HPC workflows often require a high-level of *interoperability*, typically entailing connecting/interfacing with multiple endpoints for data, AI models, and workflow integration. There are two emerging patterns of choice: (1) REST API [151] and (2) message queue-based approach [152]. Each has pros and cons; currently, no widely accepted interfacing mechanisms exist. Further, time-sensitive patterns and long-term campaign patterns, as highlighted by the IRI blueprint report [73], demonstrate the need for interfacing beyond a single institution's boundary, which brings a host of related challenges such as federated IDs, authentication, authorization, access control, etc., to implement a true end-to-end workflow integration. These challenges are more pronounced in motifs connecting experiments with HPC simulations (e.g., Distributed Models and Inverse Design) and in supporting Steering and Multistage Pipeline motifs, which is only partially addressed by specialized frameworks such as MuMMI or DeepDriveMD, and more general frameworks such as SmartSim (ref. Section 3).

The importance of *energy efficiency* in high-performance computing (HPC) has intensified due to the hard limits on maximum power capacity. A critical observation in most AI-HPC workflows is their relatively low utilization of peak performance, which may be due to data movement or other I/O activities [94]. This sub-optimal utilization prompts a vital question: what should be the ultimate goal in this context? The answer might lie in optimizing how one could optimize productivity (Science/Watt) rather than raw performance (FLOP/Watt). This optimization raises a further dilemma: should the focus be on time-to-solution or throughput? One approach could be accelerating processes through high concurrency levels and GPU utilization. Alternatively, engaging GPUs less frequently might be more power-efficient, leading to a trade-off of lower throughput for energy conservation, albeit with longer processing times [153]. Other research areas for improving the energy efficiency of AI-coupled HPC workflows involve dynamic scheduling policies, data locality, ensemble pruning of unnecessary runs, and optimizations of convolution implementations [154]. Benchmarking AI-coupled HPC workflows will be key for understanding how to optimize energy efficiency [155].

The traditional batch-based job scheduling approach to *resource allocation* in HPC is at odds with scientific workflows' iterative and interactive nature. These systems, designed for resource efficiency, struggle with the flexibility and ondemand resource allocation required for modern scientific discovery. Specifically, to meet the requirements of AI-coupled HPC workflows outlined in this paper, HPC resource management must evolve to accommodate the changing demands of scientific research. This could involve more adaptive scheduling algorithms, leveraging cloud resources for elasticity, or creating virtualized environments for better resource control. A shift towards an application-centric approach in HPC resource allocation is necessary to support scientific workflows' diverse and evolving patterns. This ensures that computational resources are used efficiently and infrastructural limitations do not hinder discoveries. Hybrid techniques such as LSF-Kubernetes [156] and serverless heterogeneous computing [157] seek to address this issue.

6 Summary and Discussion

This paper surveyed the extensive landscape of AI-driven HPC workflows, categorizing them into six execution motifs commonly used in scientific workflows: Steering, Multistage Pipeline, Inverse Design, Digital Replica, Distributed Models, and Adaptive Training. We highlighted prominent middleware exemplars of each motif and discussed their respective performance implications, revealing the performance challenges due to the complexity of integrating workflows across disparate resources. Moreover, we identify the main challenges of deploying AI-coupled HPC workflows at scale, such as the need for co-designed facilities and further development of middleware and benchmarks. We also identify opportunities for advancement in each area. Specifically, our survey identified a significant gap in the available workflow benchmarks to assess the performance of the six execution motifs. As such, we acknowledge one of the weaknesses in our survey is related to this dearth of benchmarks, which limited our performance discussions to simpler workflows. To address this issue, we propose a new suite of benchmarks designed to target each execution motif.

As the landscape of AI-enabled HPC workflows continues to evolve, this survey provides a snapshot of the current state of the art. It serves as a roadmap for developing *next-generation* workflows. For example, there are three general categories of how advanced AI systems such as Foundation Models (FM) [158] or generative AI may be used with or as part of AI-coupled HPC workflows: (1) Workflows to generate the data and train AI systems; (2) Once the advanced AI system is trained, use those as intelligent ways of steering the simulation; (3) Using advanced AI systems to create the coupling framework between the AI and the simulation.

AI-coupled HPC workflows also offer benefits for pre-training and fine-tuning of advanced AI systems. For example, in the context of the Adaptive Training motif, training LLMs at scale on HPC offers potentially more efficient alternatives at larger scales and lower costs than training in the cloud due to specific performance optimizations at scale. In general, the deployment of advanced AI systems within AI-coupled HPC workflows will benefit from the robust computational power of HPC systems.

A significant application of generative AI in AI-coupled HPC workflows is their potential to generate new workflows and associated job scripts based on specific application needs, user requirements, and the computing infrastructure. By understanding the objectives and constraints expressed in natural language, LLMs can propose optimized workflows, tailor job scripts, and suggest resource allocations that align with the desired outcomes. This type of optimal workflow generation enhances efficiency and ensures that computational resources are utilized most effectively.

Workflows are becoming first-class applications for procuring future DOE HPC systems and implementing the Integrated Research Infrastructure (IRI) [73]. For example, the NERSC-10 RFP technical specifications [159] highlight three classes of workflows to support scientific research campaigns on the future HPC system: high-performance simulations and modeling workflows, high-performance AI workflows, and cross-facility workflows for real-time steering of experiments. These workflows will likely exhibit one or more or a combination of the AI-coupled HPC workflow motifs introduced in Section 2. Similarly, the technical specifications of OLCF-6 at the Oak Ridge National Laboratory [144] also emphasize the fact that scientific campaigns are inherently formulated as workflows that include "phases of HPC simulation, highbandwidth communication, interleaved AI training with simulation and inferencing, and data processing". In both cases, one of the main objectives in explicitly including workflows in the specifications is to move (part of) the management of such workflows from user space to the software ecosystem operated by the facilities. A closer and hopefully better integration with the platform should address the performance challenges related to AI-coupled HPC workflows that we listed in Section 4.

Moreover, ESnet conducted a meta-analysis of workflow patterns across DOE Office of Science programs in the context of the forthcoming IRI [160]. This report highlights three main science patterns: time-sensitive workflows requiring nearreal-time response across facilities for timely decision-making and steering; data integration-intensive workflows that combine and analyze data from multiple sources; and long-term campaign workflows that require sustained access to resources over years or decades to accomplish a well-defined objective. In that context, the integration of AI and HPC in workflows will likely occur in time-sensitive and data integration-intensive workflows and be an important driver in designing the IRI framework.

The next step in scientific computing performance, scale, and sophistication will require AI-coupled HPC workflows to be a central component of future scientific campaigns. A thorough understanding of AI-coupled HPC workflows and the development of new benchmarks will create a strong foundation for addressing future advancements in the post-exascale era [161].

Acknowledgments

This manuscript has been authored by UT-Battelle, LLC, under contract DE-AC05-00OR22725 with the US Department of Energy (DOE). The US government retains and the publisher, by accepting the article for publication, acknowledges that the US government retains a nonexclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this manuscript, or allow others to do so, for US government purposes. DOE will provide public access to these results of federally sponsored research in accordance with the DOE Public Access Plan (https://www.energy.gov/doe-public-access-plan).

This research used resources of the Oak Ridge Leadership Computing Facility at the Oak Ridge National Laboratory, supported by the Office of Science of the U.S. Department of Energy under Contract No. DE-AC05-000R22725.

Declaration of generative AI and AI-assisted technologies in the writing process

During the preparation of this work the authors used GPT-4 in order to improve grammar structures in certain places. After using this tool/service, the authors reviewed and edited the content as needed and take full responsibility for the content of the publication.

References

- Andreas S. Panayides, Amir Amini, Nenad D. Filipovic, Ashish Sharma, Sotirios A. Tsaftaris, Alistair Young, David Foran, Nhan Do, Spyretta Golemati, Tahsin Kurc, Kun Huang, Konstantina S. Nikita, Ben P. Veasey, Michalis Zervakis, Joel H. Saltz, and Constantinos S. Pattichis. Ai in medical imaging informatics: Current challenges and future directions. IEEE Journal of Biomedical and Health Informatics, 24(7):1837–1857, 2020.
- [2] Alexander Brace, Igor Yakushin, Heng Ma, Anda Trifan, Todd Munson, Ian Foster, Arvind Ramanathan, Hyungro Lee, Matteo Turilli, and Shantenu Jha. Coupling streaming AI and HPC ensembles to achieve 100–1000× faster biomolecular simulations. In <u>2022 IEEE International Parallel and Distributed Processing Symposium (IPDPS)</u>, pages 806–816. IEEE, 2022.
- [3] Austin Clyde, Xuefeng Liu, Thomas Brettin, Hyunseung Yoo, Alexander Partin, Yadu Babuji, Ben Blaiszik, Jamaludin Mohd-Yusof, Andre Merzky, Matteo Turilli, Shantenu Jha, Arvind Ramanathan, and Rick Stevens. Aiaccelerated protein-ligand docking for sars-cov-2 is 100-fold faster with no significant change in detection. <u>Scientific</u> Reports, 13(1):2105, Feb 2023.
- [4] Geoffrey Fox, James Glazier, JCS Kadupitiya, Vikram Jadhao, Minje Kim, Judy Qiu, James P Sluka, Endre Somogy, Madhav Marathe, and Abhijin Adiga. Learning everywhere: Pervasive machine learning for effective highperformance computation. In <u>IEEE International Parallel and Distributed Processing Symposium Workshops</u>, pages 422–429. IEEE, 2019. https://arxiv.org/abs/1902.10810.
- [5] Shantenu Jha and Geoffrey Fox. Understanding ML Driven HPC: Applications and Infrastructure. In 2019 15th International Conference on eScience (eScience), pages 421–427. IEEE, 2019. https://arxiv.org/abs/1909.02363.
- [6] Shantenu Jha, Vincent R Pascuzzi, and Matteo Turilli. Ai-coupled hpc workflows. <u>Chapter 28, Artificial Intelligence</u> for Science, pp. 515-534 (2023), page arXiv:2208.11745, August 2022.
- Merchant, A., Batzner, S., Schoenholz, S.S. Scaling deep learning for materials discovery. Nature (2023). https://doi.org/10.1038/s41586-023-06735-9.
- [8] Remi Lam, Alvaro Sanchez-Gonzalez, Matthew Willson, Peter Wirnsberger, Meire Fortunato, Ferran Alet, Suman Ravuri, Timo Ewalds, Zach Eaton-Rosen, and Weihua Hu. Learning skillful medium-range global weather forecasting. Science, page eadi2336, 2023.
- [9] Hanchen Wang, Tianfan Fu, Yuanqi Du, Wenhao Gao, Kexin Huang, Ziming Liu, Payal Chandak, Shengchao Liu, Peter Van Katwyk, and Andreea Deac. Scientific discovery in the age of artificial intelligence. <u>Nature</u>, 620(7972):47– 60, 2023.
- [10] Alexander Lavin, David Krakauer, Hector Zenil, Justin Gottschlich, Tim Mattson, Johann Brehmer, Anima Anandkumar, Sanjay Choudry, Kamil Rocki, and Atılım Güneş Baydin. Simulation intelligence: Towards a new generation of scientific methods. arXiv preprint arXiv:2112.03235, 2021.
- [11] Abigail Dommer, Lorenzo Casalino, Fiona Kearns, Mia Rosenfeld, Nicholas Wauer, Surl-Hee Ahn, John Russo, Sofia Oliveira, Clare Morris, Anthony Bogetti, Anda Trifan, Alexander Brace, Terra Sztain, Austin Clyde, Heng Ma, Chakra Chennubhotla, Hyungro Lee, Matteo Turilli, Syma Khalid, Teresa Tamayo-Mendoza, Matthew Welborn, Anders Christensen, Daniel G. A. Smith, Zhuoran Qiao, Sai Krishna Sirumalla, Michael O' Connor, Frederick Manby, Anima Anandkumar, David Hardy, James Phillips, Abraham Stern, Josh Romero, David Clark, Mitchell Dorrell, Tom Maiden, Lei Huang, John McCalpin, Christopher Woods, Alan Gray, Matt Williams, Bryan Barker, Harinda Rajapaksha, Richard Pitts, Tom Gibbs, John Stone, Daniel Zuckerman, Adrian Mulholland, Thomas Miller, Shantenu Jha, Arvind Ramanathan, Lillian Chong, and Rommie Amaro. #covidisairborne: Ai-enabled multiscale computational microscopy of delta sars-cov-2 in a respiratory aerosol. bioRxiv, 2021.

- [12] Yihang Wang, Joao Marcelo Lamim Ribeiro, and Pratyush Tiwary. Machine learning approaches for analyzing and enhancing molecular dynamics simulations. Current Opinion in Structural Biology, 61:139–145, 2020.
- [13] David E Graff, Eugene I Shakhnovich, and Connor W Coley. Accelerating high-throughput virtual screening through molecular pool-based active learning. Chemical science, 12(22):7866–7881, 2021.
- [14] M. F. Kasim, D. Watson-Parris, L. Deaconu, S. Oliver, H. Hatfield, D. H. Froula, G. Gregori, M. Jarvis, S. Khatiwala, J. Korenaga, J. Topp-Mugglestone, E. Viezzer, and S. M. Vinko. Building high accuracy emulators for scientific simulations with deep neural architecture search. Machine Learning: Science and Technology, page in press, 2021.
- [15] Huachen Tao, Tianyi Wu, Matteo Aldeghi, Tony C Wu, Alan Aspuru-Guzik, and Eugenia Kumacheva. Nanoparticle synthesis assisted by machine learning. Nature reviews materials, 6(8):701–716, 2021.
- [16] Zhenpeng Yao, Benjamín Sánchez-Lengeling, N Scott Bobbitt, Benjamin J Bucior, Sai Govind Hari Kumar, Sean P Collins, Thomas Burns, Tom K Woo, Omar K Farha, Randall Q Snurr, et al. Inverse design of nanoporous crystalline reticular materials with deep generative models. Nature Machine Intelligence, 3(1):76–86, 2021.
- [17] Geoffrey Fox and Shantenu Jha. Learning Everywhere: A Taxonomy for the Integration of Machine Learning and Simulations. In <u>2019 15th International Conference on eScience (eScience)</u>, pages 439–448. IEEE, 2019. https://arxiv.org/abs/1909.13340.
- [18] N. Holtkamp. An overview of the iter project. <u>Fusion Engineering and Design</u>, 82(5):427–434, 2007. Proceedings of the 24th Symposium on Fusion Technology.
- [19] Silvina Caino-Lores, Michel Cuendet, Jack Marquez, Ekaterina Kots, Trilce Estrada, Ewa Deelman, Harel Weinstein, and Michela Taufer. Runtime steering of molecular dynamics simulations through in situ analysis and annotation of collective variables. In <u>Proceedings of the Platform for Advanced Scientific Computing Conference</u>, PASC '23, New York, NY, USA, 2023. Association for Computing Machinery.
- [20] Wael Elwasif, Ross Whitfield, Jin Myung Park, and Mark Cianciosa. Containers for massive ensemble of i/o bound hierarchical coupled simulations. In 2020 2nd International Workshop on Containers and New Orchestration Paradigms for Isolated Environments in HPC (CANOPIE-HPC), pages 26–34, 2020.
- [21] Brian Bush, Nicholas Brunhart-Lupo, Bruce Bugbee, Venkat Krishnan, Kristin Potter, and Kenny Gruchalla. Coupling visualization, simulation, and deep learning for ensemble steering of complex energy models. In <u>2017 IEEE</u> Workshop on Data Systems for Interactive Analysis (DSIA), pages 1–5, 2017.
- [22] Hyungro Lee, Heng Ma, Matteo Turilli, Debsindhu Bhowmik, Shantenu Jha, and Arvind Ramanathan. Deepdrivemd: Deep-learning driven adaptive molecular simulations for protein folding. CoRR, abs/1909.07817, 2019.
- [23] Logan Ward, Ganesh Sivaraman, J Gregory Pauloski, Yadu Babuji, Ryan Chard, Naveen Dandu, Paul Redfern, Rajeev Assary, Kyle Chard, Larry Curtiss, Rajeev Thakur, and Ian Foster. Colmena: Scalable Machine-Learning-Based Steering of Ensemble Simulations for High Performance Computing. In <u>Proceedings of the 2021 IEEE/ACM</u> Workshop on Machine Learning in High Performance Computing Environments (MLHPC), pages 9–20. IEEE, 2021.
- [24] Atanas Atanasov, Hans-Joachim Bungartz, Jérôme Frisch, Miriam Mehl, Ralf-Peter Mundani, Ernst Rank, and Christoph van Treeck. Computational steering of complex flow simulations. <u>CoRR</u>, abs/1807.00567, 2018.
- [25] Aymen Al Saadi, Dario Alfe, Yadu Babuji, Agastya Bhati, Ben Blaiszik, Thomas Brettin, Kyle Chard, Ryan Chard, Peter Coveney, Anda Trifan, Alex Brace, Austin Clyde, Ian Foster, Tom Gibbs, Shantenu Jha, Kristopher Keipert, Thorsten Kurth, Dieter Kranzlmller, Hyungro Lee, Zhuozhao Li, Heng Ma, Andre Merzky, Gerald Mathias, Alexander Partin, Junqi Yin, Arvind Ramanathan, Ashka Shah, Abraham Stern, Rick Stevens, Li Tan, Mikhail Titov, Aristeidis Tsaris, Matteo Turilli, Huub Van Dam, Shunzhou Wan, and David Wifling. Impeccable: Integrated modeling pipeline for covid cure by assessing better leads. 50th International Conference on Parallel Processing (ICPP 21), August 912, 2021, Lemont, IL, USA. ACM, New York, NY, USA, 12 pages, 2021.
- [26] Abigail Dommer, Lorenzo Casalino, Fiona Kearns, Mia Rosenfeld, Nicholas Wauer, Surl-Hee Ahn, John Russo, Sofia Oliveira, Clare Morris, Anthony Bogetti, Anda Trifan, Alexander Brace, Terra Sztain, Austin Clyde, Heng Ma, Chakra Chennubhotla, Hyungro Lee, Matteo Turilli, Syma Khalid, Teresa Tamayo-Mendoza, Matthew Welborn, Anders Christensen, Daniel GA Smith, Zhuoran Qiao, Sai K Sirumalla, Michael OConnor, Frederick Manby, Anima Anandkumar, David Hardy, James Phillips, Abraham Stern, Josh Romero, David Clark, Mitchell Dorrell,

Tom Maiden, Lei Huang, John McCalpin, Christopher Woods, Alan Gray, Matt Williams, Bryan Barker, Harinda Rajapaksha, Richard Pitts, Tom Gibbs, John Stone, Daniel M. Zuckerman, Adrian J. Mulholland, III Thomas Miller, Shantenu Jha, Arvind Ramanathan, Lillian Chong, and Rommie E Amaro. #covidisairborne: Ai-enabled multiscale computational microscopy of delta sars-cov-2 in a respiratory aerosol. <u>The International Journal of High Performance</u> Computing Applications, 37(1):28–44, 2023.

- [27] Hyun-Myung Woo, Xiaoning Qian, Li Tan, Shantenu Jha, Francis J. Alexander, Edward R. Dougherty, and Byung-Jun Yoon. Optimal decision making in high-throughput virtual screening pipelines, 2022.
- [28] Oscar Esteban, Christopher J. Markiewicz, Ross W. Blair, Craig A. Moodie, A. Ilkay Isik, Asier Erramuzpe, James D. Kent, Mathias Goncalves, Elizabeth DuPre, Madeleine Snyder, Hiroyuki Oya, Satrajit S. Ghosh, Jessey Wright, Joke Durnez, Russell A. Poldrack, and Krzysztof J. Gorgolewski. fmriprep: a robust preprocessing pipeline for functional mri. Nature Methods, 16(1):111–116, Jan 2019.
- [29] Yuankai Huo, Andrew J Plassard, Aaron Carass, Susan M Resnick, Dzung L Pham, Jerry L Prince, and Bennett A Landman. Consistent cortical reconstruction and multi-atlas brain segmentation. <u>Neuroimage</u>, 138:197–210, September 2016.
- [30] David J Foran, Eric B Durbin, Wenjin Chen, Evita Sadimin, Ashish Sharma, Imon Banerjee, Tahsin Kurc, Nan Li, Antoinette M Stroup, Gerald Harris, Annie Gu, Maria Schymura, Rajarsi Gupta, Erich Bremer, Joseph Balsamo, Tammy DiPrima, Feiqiao Wang, Shahira Abousamra, Dimitris Samaras, Isaac Hands, Kevin Ward, and Joel H Saltz. An expandable informatics framework for enhancing central cancer registries with digital pathology specimens, computational imaging tools, and advanced mining capabilities. J. Pathol. Inform., 13(100167):5, January 2022.
- [31] Robert Pollice, Gabriel dos Passos Gomes, Matteo Aldeghi, Riley J Hickman, Mario Krenn, Cyrille Lavigne, Michael Lindner DAddario, AkshatKumar Nigam, Cher Tian Ser, Zhenpeng Yao, et al. Data-driven strategies for accelerated materials design. Accounts of Chemical Research, 54(4):849–860, 2021.
- [32] Siewert J. Marrink, Luca Monticelli, Manuel N. Melo, Riccardo Alessandri, D. Peter Tieleman, and Paulo C. T. Souza. Two decades of martini: Better beads, broader scope. <u>WIREs Computational Molecular Science</u>, 13(1):e1620, 2023.
- [33] Jia Wang, Yingxue Wang, and Yanan Chen. Inverse design of materials by machine learning. Materials, 15(5), 2022.
- [34] Avni Jain, Jonathan A. Bollinger, and Thomas M. Truskett. Inverse methods for material design. <u>AIChE Journal</u>, 60(8):27322740, May 2014.
- [35] Sunae So, Trevon Badloe, Jaebum Noh, Jorge Bravo-Abad, and Junsuk Rho. Deep learning enabled inverse design in nanophotonics. Nanophotonics, 9(5):1041–1057, 2020.
- [36] Raphaël Pestourie, Carlos Pérez-Arancibia, Zin Lin, Wonseok Shin, Federico Capasso, and Steven G. Johnson. Inverse design of large-area metasurfaces. Opt. Express, 26(26):33732–33747, Dec 2018.
- [37] Xiao Han, Ziyang Fan, Zeyang Liu, Chao Li, and L. Jay Guo. Inverse design of metasurface optical filters using deep neural network with high degrees of freedom. InfoMat, 3(4):432–442, 2021.
- [38] J.J. García-Esteban, J. Bravo-Abad, and J.C. Cuevas. Deep learning for the modeling and inverse design of radiative heat transfer. Phys. Rev. Appl., 16:064006, Dec 2021.
- [39] Li Zhong, Dennis Hoppe, Naweiluo Zhou, and Oleksandr Shcherbakov. Hybrid workflow of simulation and deep learning on hpc: A case study for material behavior determination. In <u>2021 IEEE International Conference on</u> Cluster Computing (CLUSTER), pages 698–704, 2021.
- [40] Eric Stach, Brian DeCost, A Gilad Kusne, Jason Hattrick-Simpers, Keith Brown, Kristofer Reyes, Joshua Schrier, Simon Billinge, Tonio Buonassisi, Ian Foster, et al. Autonomous experimentation systems for materials development: A community perspective. Matter, 4(9):2702–2726, 2021.
- [41] AkshatKumar Nigam, Robert Pollice, Gary Tom, Kjell Jorner, Luca A Thiede, Anshul Kundaje, and Alan Aspuru-Guzik. Tartarus: A benchmarking platform for realistic and practical inverse molecular design. <u>arXiv preprint</u> arXiv:2209.12487, 2022.

- [42] Tianle Wang, Sudip K. Seal, Ramakrishnan Kannan, Cristina Garcia-Cardona, Thomas Proffen, and Shantenu Jha. A parallel machine learning workflow for neutron scattering data analysis. In <u>Proceedings of the 2023 IEEE</u> International Parallel and Distributed Processing Symposium Workshops, pages 795–798, 2023.
- [43] Jiaxin Zhang, Sirui Bi, and Guannan Zhang. A directional gaussian smoothing optimization method for computational inverse design in nanophotonics. Materials & Design, 197:109213, 2021.
- [44] Christopher Yeung, Benjamin Pham, Ryan Tsai, Katherine T. Fountaine, and Aaswath P. Raman. Deepadjoint: An all-in-one photonic inverse design framework integrating data-driven machine learning with optimization algorithms. ACS Photonics, 0(0):null, 0.
- [45] National Academies of Sciences, Engineering, and Medicine et al. <u>Foundational Research Gaps and Future Directions</u> for Digital Twins. The National Academies Press, 2023.
- [46] Mark Alber, Adrian Buganza Tepole, William R Cannon, Suvranu De, Salvador Dura-Bernal, Krishna Garikipati, George Karniadakis, William W Lytton, Paris Perdikaris, Linda Petzold, et al. Integrating machine learning and multiscale modeling—perspectives, challenges, and opportunities in the biological, biomedical, and behavioral sciences. NPJ digital medicine, 2(1):115, 2019.
- [47] Karli Gillette, Matthias A.F. Gsell, Anton J. Prassl, Elias Karabelas, Ursula Reiter, Gert Reiter, Thomas Grandits, Christian Payer, Darko tern, Martin Urschler, Jason D. Bayer, Christoph M. Augustin, Aurel Neic, Thomas Pock, Edward J. Vigmond, and Gernot Plank. A framework for the generation of digital twins of cardiac electrophysiology from clinical 12-leads ecgs. Medical Image Analysis, 71:102080, 2021.
- [48] Junqi Yin, Feiyi Wang, and Mallikarjun Shankar. Strategies for integrating deep learning surrogate models with hpc simulation applications. In <u>2022 IEEE International Parallel and Distributed Processing Symposium Workshops</u> (IPDPSW), pages 01–10, 2022.
- [49] Manuela Minetti, Andrea Bonfiglio, Ivone Benfatto, and Ye Yulong. Strategies for real-time simulation of central solenoid iter power supply digital twin. Energies, 16(13), 2023.
- [50] David J. Kropaczek, Vittorio Badalassi, Prashant K. Jain, Pradeep Ramuhalli, and W. David Pointer. <u>Digital Twins for Nuclear Power Plants and Facilities</u>, pages 971–1022. Springer International Publishing, Cham, 2023.
- [51] Michelle Tindall, Sebastian Rosini, Natasha Bowden, Thomas Deighan, Matthew Mavis, Stephen Biggs-Fox, and Thomas Barrett. Towards a fusion component digital twin virtual test and monitoring of components in chimera by systems simulation. Fusion Engineering and Design, 191:113773, 2023.
- [52] Daniel Rosendo, Alexandru Costan, Patrick Valduriez, and Gabriel Antoniu. Distributed intelligence on the edgeto-cloud continuum: A systematic literature review. Journal of Parallel and Distributed Computing, 2022.
- [53] Awais Khan, Taeuk Kim, Hyunki Byun, and Youngjae Kim. Scispace: A scientific collaboration workspace for geo-distributed hpc data centers. Future Generation Computer Systems, 101:398–409, 2019.
- [54] Alexander S. Ford, Brian D. Weitzner, and Christopher D. Bahl. Integration of the rosetta suite with the python software stack via reproducible packaging and core programming interfaces for distributed simulation. <u>Protein</u> <u>Science</u>, 29(1):43–51, 2020.
- [55] Junqi Yin, Guannan Zhang, Huibo Cao, Sajal Dash, Bryan C. Chakoumakos, and Feiyi Wang. Toward an autonomous workflow for single crystal neutron diffraction. In Kothe Doug, Geist Al, Swaroop Pophale, Hong Liu, and Suzanne Parete-Koon, editors, <u>Accelerating Science and Engineering Discoveries Through Integrated Research Infrastructure for Experiment, Big Data, Modeling and Simulation</u>, pages 244–256, Cham, 2022. Springer Nature Switzerland.
- [56] Aurelio Vivas and Harold Castro. Estimating the overhead and coupling of scientific computing clusters. SIMULATION, 99(3):245–261, 2023.
- [57] Cédric Prigent, Gabriel Antoniu, Alexandru Costan, and Loïc Cudennec. Supporting efficient workflow deployment of federated learning systems across the computing continuum. In SC 2022-SuperComputing, 2022.

- [58] M Asch, T Moore, R Badia, M Beck, P Beckman, T Bidot, F Bodin, F Cappello, A Choudhary, B de Supinski, E Deelman, J Dongarra, A Dubey, G Fox, H Fu, S Girona, W Gropp, M Heroux, Y Ishikawa, K Keahey, D Keyes, W Kramer, J-F Lavignon, Y Lu, S Matsuoka, B Mohr, D Reed, S Requena, J Saltz, T Schulthess, R Stevens, M Swany, A Szalay, W Tang, G Varoquaux, J-P Vilotte, R Wisniewski, Z Xu, and I Zacharov. Big data and extremescale computing: Pathways to convergence-toward a shaping strategy for a future software and data ecosystem for scientific inquiry. The International Journal of High Performance Computing Applications, 32(4):435–479, 2018.
- [59] Prasanna Balaprakash, Michael Salim, Thomas D Uram, Venkat Vishwanath, and Stefan M Wild. Deephyper: Asynchronous hyperparameter search for deep neural networks. In <u>2018 IEEE 25th international conference on high</u> performance computing (HiPC), pages 42–51. IEEE, 2018.
- [60] Robert M. Patton, J. Travis Johnston, Steven R. Young, Catherine D. Schuman, Thomas E. Potok, Derek C. Rose, Seung-Hwan Lim, Junghoon Chae, Le Hou, Shahira Abousamra, Dimitris Samaras, and Joel H. Saltz. Exascale deep learning to accelerate cancer research. CoRR, abs/1909.12291, 2019.
- [61] Daniel Martinez, Wesley Brewer, Gregory Behm, Andrew Strelzoff, Andrew Wilson, and Daniel Wade. Deep learning evolutionary optimization for regression of rotorcraft vibrational spectra. In <u>2018 IEEE/ACM Machine Learning in</u> HPC Environments (MLHPC), pages 57–66, 2018.
- [62] Reza Pirayeshshirazinezhad, Sandra G. Biedro, Jorge Alberto Daz Cruz, Salvador Sosa Gitrn, and Manel Martnez-Ramn. Designing monte carlo simulation and an optimal machine learning to optimize and model space missions. IEEE Access, 10:45643–45662, 2022.
- [63] Yonatan Geifman and Ran El-Yaniv. Deep active learning with a neural architecture search. Advances in Neural Information Processing Systems, 32, 2019.
- [64] Alberto Marchisio, Vojtech Mrazek, Andrea Massa, Beatrice Bussolino, Maurizio Martina, and Muhammad Shafique. Rohnas: A neural architecture search framework with conjoint optimization for adversarial robustness and hardware efficiency of convolutional and capsule networks, 2022.
- [65] Paul Barham, Aakanksha Chowdhery, Jeff Dean, Sanjay Ghemawat, Steven Hand, Daniel Hurt, Michael Isard, Hyeontaek Lim, Ruoming Pang, Sudip Roy, et al. Pathways: Asynchronous distributed dataflow for ml. <u>Proceedings</u> of Machine Learning and Systems, 4:430–449, 2022.
- [66] Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. arXiv preprint arXiv:2204.02311, 2022.
- [67] Andrew Blanchard, Debsindhu Bhowmik, John Gounley, Jens Glaser, Belinda S Akpa, and Stephan Irle. Adaptive Language Model Training for Molecular Design. <u>Journal of Cheminformatics</u>, 15, 2022.
- [68] Andrew E Blanchard, John Gounley, Debsindhu Bhowmik, Mayanka Chandra Shekar, Isaac Lyngaas, Shang Gao, Junqi Yin, Aristeidis Tsaris, Feiyi Wang, and Jens Glaser. Language models for the prediction of sars-cov-2 inhibitors. The International Journal of High Performance Computing Applications, 36(5-6):587–602, 2022.
- [69] Yiqian Mao, Shan Zhong, and Hujun Yin. Drlfluent: A distributed co-simulation framework coupling deep reinforcement learning with ansys-fluent on high-performance computing systems. <u>Journal of Computational Science</u>, 74:102171, 2023.
- [70] Donatello Elia, Sonia Scardigno, Jorge Ejarque, Alessandro DAnca, Gabriele Accarino, Enrico Scoccimarro, Davide Donno, Daniele Peano, Francesco Immorlano, and Giovanni Aloisio. End-to-end workflows for climate science: Integrating hpc simulations, big data processing, and machine learning. In Proceedings of the SC '23 Workshops of <u>The International Conference on High Performance Computing, Network, Storage, and Analysis</u>, SC-W '23, page 20422052, New York, NY, USA, 2023. Association for Computing Machinery.
- [71] Lorenzo Casalino, Abigail Dommer, Zied Gaieb, Emilia P. Barros, Terra Sztain, Surl-Hee Ahn, Anda Trifan, Alexander Brace, Anthony Bogetti, Heng Ma, Hyungro Lee, Matteo Turilli, Syma Khalid, Lillian Chong, Carlos Simmerling, David J. Hardy, Julio D. C. Maia, James C. Phillips, Thorsten Kurth, Abraham Stern, Lei Huang, John McCalpin, Mahidhar Tatineni, Tom Gibbs, John E. Stone, Shantenu Jha, Arvind Ramanathan, and Rommie E. Amaro. Ai-driven multiscale simulations illuminate mechanisms of sars-cov-2 spike dynamics. <u>International Journal of High-Performance Computing Applications (IJHPCA)</u>, 2020. Gordon Bell Prize Award (SC20)
 https://www.biorxiv.org/content/10.1101/2020.11.19.390187v1.

- [72] Charles R Qi, Hao Su, Kaichun Mo, and Leonidas J Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. In <u>Proceedings of the IEEE conference on computer vision and pattern recognition</u>, pages 652–660, 2017.
- [73] Benjamin L Brown, William L Miller, Deborah Bard, Amber Boehnlein, Kjiersten Fagnan, Chin Guok, Eric Lançon, Sreeranjani Jini Ramprakash, Mallikarjun Shankar, and Nicholas Schwarz. Integrated Research Infrastructure architecture blueprint activity (final report 2023). Technical report, US Department of Energy (USDOE), 2023. https://doi.org/10.2172/1984466.
- [74] Xingfu Wu, Valerie Taylor, Justin M. Wozniak, Rick Stevens, Thomas Brettin, and Fangfang Xia. Performance, energy, and scalability analysis and improvement of parallel cancer deep learning candle benchmarks. In <u>Proceedings</u> of the 48th International Conference on Parallel Processing, ICPP 2019, New York, NY, USA, 2019. Association for Computing Machinery.
- [75] ECP CANDLE benchmarks. https://github.com/ECP-CANDLE/Benchmarks.
- [76] Hyungro Lee, Matteo Turilli, Shantenu Jha, Debsindhu Bhowmik, Heng Ma, and Arvind Ramanathan. Deep-DriveMD: Deep-Learning Driven Adaptive Molecular Simulations for Protein Folding. In <u>Proceedings of the 2019</u> IEEE/ACM Third Workshop on Deep Learning on Supercomputers (DLS), pages 12–19, 2019.
- [77] Francesco Di Natale, Harsh Bhatia, Timothy S. Carpenter, Chris Neale, Sara Kokkila-Schumacher, Tomas Oppelstrup, Liam Stanton, Xiaohua Zhang, Shiv Sundram, Thomas R. W. Scogland, Gautham Dharuman, Michael P. Surh, Yue Yang, Claudia Misale, Lars Schneidenbach, Carlos Costa, Changhoan Kim, Bruce D'Amora, Sandrasegaram Gnanakaran, Dwight V. Nissley, Fred Streitz, Felice C. Lightstone, Peer-Timo Bremer, James N. Glosli, and Helgi I. Ingólfsson. A Massively Parallel Infrastructure for Adaptive Multiscale Simulations: Modeling RAS Initiation Pathway for Cancer. In <u>Proceedings of the International Conference for High Performance Computing</u>, Networking, Storage and Analysis, 2019.
- [78] Francesco Di Natale. Maestro Workflow Conductor. [Online]: https://github.com/LLNL/maestrowf, 2017.
- [79] Aymen Al-Saadi, Dario Alfe, Yadu Babuji, Agastya Bhati, Ben Blaiszik, Alexander Brace, Thomas Brettin, Kyle Chard, Ryan Chard, Austin Clyde, Peter Coveney, Ian Foster, Tom Gibbs, Shantenu Jha, Kristopher Keipert, Dieter Kranzlmller, Thorsten Kurth, Hyungro Lee, Zhuozhao Li, Heng Ma, Gerald Mathias, Andre Merzky, Alexander Partin, Arvind Ramanathan, Ashka Shah, Abraham Stern, Rick Stevens, Li Tan, Mikhail Titov, Anda Trifan, Aristeidis Tsaris, Matteo Turilli, Huub Van Dam, Shunzhou Wan, David Wifling, and Junqi Yin. IMPECCABLE: integrated modeling pipelinE for COVID cure by assessing better LEads. In <u>Proceedings of 50th International</u> Conference on Parallel Processing (ICPP), pages 1–12, 2021.
- [80] Riccardo Balin, Filippo Simini, Cooper Simpson, Andrew Shao, Alessandro Rigazzi, Matthew Ellis, Stephen Becker, Alireza Doostan, John Evans, and Kenneth Jansen. In situ framework for coupling simulation and machine learning with application to cfd. arXiv preprint arXiv:2306.12900, 2023.
- [81] Sam Partee, Matthew Ellis, Alessandro Rigazzi, Andrew E Shao, Scott Bachman, Gustavo Marques, and Benjamin Robbins. Using machine learning at scale in numerical simulations with smartsim: An application to ocean climate modeling. Journal of Computational Science, page 101707, 2022.
- [82] Hariharan Devarajan, Anthony Kougkas, Huihuo Zheng, Venkatram Vishwanath, and Xian-He Sun. Stimulus: Accelerate Data Management for Scientific AI applications in HPC. In <u>Proceedings of the 22nd IEEE International</u> Symposium on Cluster, Cloud and Internet Computing (CCGrid), pages 109–118, 2022.
- [83] Nikoli Dryden, Roman Böhringer, Tal Ben-Nun, and Torsten Hoefler. Clairvoyant prefetching for distributed machine learning i/o. In Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis, SC '21, New York, NY, USA, 2021. Association for Computing Machinery.
- [84] Matteo Turilli, Vivek Balasubramanian, Andre Merzky, Ioannis Paraskevakos, and Shantenu Jha. Middleware building blocks for workflow systems. Computing in Science & Engineering, 21(4):62–75, 2019.
- [85] Cristian Martn, Peter Langendoerfer, Pouya Soltani Zarrin, Manuel Daz, and Bartolom Rubio. Kafka-ML: Connecting the data stream with ML/AI frameworks. Future Generation Computer Systems, 126:15–33, 2022.
- [86] Frédéric Suter, Rafael Ferreira da Silva, Ana Gainaru, and Scott Klasky. Driving next-generation workflows from the data plane. In Proceedings of the 19th IEEE Conference on eScience, 2023.

- [87] Suchita Pati, Shaizeen Aga, Mahzabeen Islam, Nuwan Jayasena, and Matthew D Sinclair. Computation vs. communication scaling for future transformers on future hardware. arXiv preprint arXiv:2302.02825, 2023.
- [88] Neeraja J Yadwadkar, Francisco Romero, Qian Li, and Christos Kozyrakis. A case for managed and model-less inference serving. In Proceedings of the Workshop on Hot Topics in Operating Systems, pages 184–191, 2019.
- [89] Anda Trifan, Defne Gorgun, Michael Salim, Zongyi Li, Alexander Brace, Maxim Zvyagin, Heng Ma, Austin Clyde, David Clark, David J Hardy, Tom Burnley, Lei Huang, John McCalpin, Murali Emani, Hyenseung Yoo, Junqi Yin, Aristeidis Tsaris, Vishal Subbiah, Tanveer Raza, Jessica Liu, Noah Trebesch, Geoffrey Wells, Venkatesh Mysore, Thomas Gibbs, James Phillips, S Chakra Chennubhotla, Ian Foster, Rick Stevens, Anima Anandkumar, Venkatram Vishwanath, John E Stone, Emad Tajkhorshid, Sarah A Harris, and Arvind Ramanathan. Intelligent resolution: Integrating cryo-em with ai-driven multi-resolution simulations to observe the severe acute respiratory syndrome coronavirus-2 replication-transcription machinery in action. Int. J. High Perform. Comput. Appl., 36(56):603623, nov 2022.
- [90] Denis Baylor, Eric Breck, Heng-Tze Cheng, Noah Fiedel, Chuan Yu Foo, Zakaria Haque, Salem Haykal, Mustafa Ispir, Vihan Jain, Levent Koc, et al. Tfx: A tensorflow-based production-scale machine learning platform. In Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pages 1387–1395, 2017.
- [91] Sarah Neuwirth and Arnab K Paul. Parallel i/o evaluation techniques and emerging hpc workloads: A perspective. In 2021 IEEE International Conference on Cluster Computing (CLUSTER), pages 671–679. IEEE, 2021.
- [92] Derek G Murray, Jiri Simsa, Ana Klimovic, and Ihor Indyk. tf. data: A machine learning data processing framework. arXiv preprint arXiv:2101.12127, 2021.
- [93] Awais Khan, Arnab K. Paul, Christopher Zimmer, Sarp Oral, Sajal Dash, Scott Atchley, and Feiyi Wang. Hvac: Removing i/o bottleneck for large-scale deep learning applications. In <u>2022 IEEE International Conference on Cluster</u> Computing (CLUSTER), pages 324–335, 2022.
- [94] Wesley Brewer, Greg Behm, Alan Scheinine, Ben Parsons, Wesley Emeneker, and Robert Trevino. iBench: a distributed inference simulation and benchmark suite. In <u>2020 IEEE High Performance Extreme Computing Conference</u> (HPEC), pages 1–6. IEEE, 2020.
- [95] Benedikt Schifferer, Gilberto Titericz, Chris Deotte, Christof Henkel, Kazuki Onodera, Jiwei Liu, Bojan Tunguz, Even Oldridge, Gabriel De Souza Pereira Moreira, and Ahmet Erdem. Gpu accelerated feature engineering and training for recommender systems. In Proceedings of the Recommender Systems Challenge 2020, pages 16–23, 2020.
- [96] Alexander Sergeev and Mike Del Balso. Horovod: fast and easy distributed deep learning in tensorflow. <u>arXiv</u> preprint arXiv:1802.05799, 2018.
- [97] Vivienne Sze, Yu-Hsin Chen, Tien-Ju Yang, and Joel S Emer. Efficient processing of deep neural networks: A tutorial and survey. Proceedings of the IEEE, 105(12):2295–2329, 2017.
- [98] Wesley Brewer, Chris Geyer, Dardo Kleiner, and Connor Horne. Streaming detection and classification performance of a POWER9 edge supercomputer. In <u>2021 IEEE High Performance Extreme Computing Conference (HPEC)</u>, pages 1–7. IEEE, 2021.
- [99] Reiner Pope, Sholto Douglas, Aakanksha Chowdhery, Jacob Devlin, James Bradbury, Anselm Levskaya, Jonathan Heek, Kefan Xiao, Shivani Agrawal, and Jeff Dean. Efficiently scaling transformer inference. <u>arXiv preprint</u> arXiv:2211.05102, 2022.
- [100] Wesley Brewer, Daniel Martinez, Mathew Boyer, Dylan Jude, Andy Wissink, Ben Parsons, Junqi Yin, and Valentine Anantharaj. Production deployment of machine-learned rotorcraft surrogate models on HPC. In <u>2021 IEEE/ACM</u> <u>Workshop on Machine Learning in High Performance Computing Environments (MLHPC)</u>, pages 21–32. IEEE, 2021.
- [101] Junqi Yin, Feiyi Wang, and Mallikarjun Shankar. Strategies for integrating deep learning surrogate models with hpc simulation applications. In <u>2022 IEEE International Parallel and Distributed Processing Symposium Workshops</u> (IPDPSW), pages 01–10. IEEE, 2022.

- [102] Mathew Boyer, Wesley Brewer, Dylan Jude, and Ian Dettwiller. Scalable integration of computational physics simulations with machine learning. In <u>2022 IEEE/ACM Workshop on Artificial Intelligence and Machine Learning</u> for Scientific Applications (AI4S). IEEE, 2022.
- [103] Fabian Orland, Kim Sebastian Brose, Julian Bissantz, Federica Ferraro, Christian Terboven, and Christian Hasse. A case study on coupling OpenFOAM with different machine learning frameworks. In <u>2022 IEEE/ACM International</u> <u>Workshop on Artificial Intelligence and Machine Learning for Scientific Applications (AI4S)</u>, pages 7–12. IEEE, 2022.
- [104] Anass Serhani, Corentin Lapeyre, and Gabriel Staffelbach. PhyDLL Physics Deep Learning Coupler: An Open-Source High-2024. Accessed: 7th March, 2024.
- [105] Weishuo Liu, Ziming Song, and Jian Fang. Nnpred: Deploying neural networks in computational fluid dynamics codes to facilitate data-driven modeling studies. Computer Physics Communications, 290:108775, 2023.
- [106] Jared Willard, Xiaowei Jia, Shaoming Xu, Michael Steinbach, and Vipin Kumar. Integrating physics-based modeling with machine learning: A survey. arXiv preprint arXiv:2003.04919, 1(1):1–34, 2020.
- [107] OpenAI. ChatGPT: An AI language model based on GPT-4 architecture. https://www.openai.com/, n.d. Accessed: [May 3, 2023].
- [108] Eric Liang, Zhanghao Wu, Michael Luo, Sven Mika, Joseph E Gonzalez, and Ion Stoica. RLlib Flow: Distributed reinforcement learning is a dataflow problem. <u>Advances in Neural Information Processing Systems</u>, 34:5506–5517, 2021.
- [109] Yadu Babuji, Anna Woodard, Zhuozhao Li, Daniel S Katz, Ben Clifford, Rohan Kumar, Lukasz Lacinski, Ryan Chard, Justin M Wozniak, Ian Foster, et al. Parsl: Pervasive Parallel Programming in Python. In Proceedings of the 28th International Symposium on High-Performance Parallel and Distributed Computing, pages 25–36, 2019.
- [110] Jessica G Freeze, H Ray Kelly, and Victor S Batista. Search for catalysts by inverse design: artificial intelligence, mountain climbers, and alchemists. Chemical reviews, 119(11):6595–6612, 2019.
- [111] Qizhou Wang, Maksim Makarenko, Arturo Burguete Lopez, Fedor Getman, and Andrea Fratalocchi. Advancing statistical learning and artificial intelligence in nanophotonics inverse design. <u>Nanophotonics</u>, 11(11):2483–2505, 2022.
- [112] Shuaihua Lu, Qionghua Zhou, Xinyu Chen, Zhilong Song, and Jinlan Wang. Inverse design with deep generative models: next step in materials discovery. National Science Review, 9(8):nwac111, 2022.
- [113] Zhengchun Liu, Hemant Sharma, J-S Park, Peter Kenesei, Antonino Miceli, Jonathan Almer, Rajkumar Kettimuthu, and Ian Foster. BraggNN: Fast X-Ray Bragg peak analysis using deep learning. IUCrJ, 9(1), 2022.
- [114] Zhengchun Liu, Ahsan Ali, Peter Kenesei, Antonino Miceli, Hemant Sharma, Nicholas Schwarz, Dennis Trujillo, Hyunseung Yoo, Ryan Coffee, Naoufal Layad, Jana Thayer, Ryan Herbst, Chunhong Yoon, and Ian Foster. Bridging data center AI systems with edge computing for actionable information retrieval. In <u>3rd Annual Workshop on</u> Extreme-scale Experiment-in-the-Loop Computing (XLOOP), pages 15–23, 2021.
- [115] Weile Jia, Han Wang, Mohan Chen, Denghui Lu, Lin Lin, Roberto Car, E Weinan, and Linfeng Zhang. Pushing the limit of molecular dynamics with ab initio accuracy to 100 million atoms with machine learning. In <u>SC20</u>: <u>International conference for high performance computing, networking, storage and analysis</u>, pages 1–14. IEEE, 2020.
- [116] Ryan Chard, Yadu Babuji, Zhuozhao Li, Tyler Skluzacek, Anna Woodard, Ben Blaiszik, Ian Foster, and Kyle Chard. Funcx: A federated function serving fabric for science. In <u>29th International symposium on high-performance parallel</u> and distributed computing, pages 65–76, 2020.
- [117] Suhas Somnath, Rama K Vasudevan, Stephen Jesse, Sergei Kalinin, Nageswara Rao, Christopher Brumgard, Feiyi Wang, Olga Kuchar, Arjun Shankar, Ben Mintz, et al. Building an integrated ecosystem of computational and observational facilities to accelerate scientific discovery. In <u>Smoky Mountains Computational Sciences and Engineering</u> Conference, pages 58–75. Springer, 2021.
- [118] Nicolas Dube, Duncan Roweth, Paolo Faraboschi, and Dejan Milojicic. Future of HPC: The Internet of workflows. IEEE Internet Computing, 25(5):26–34, 2021.

- [119] Lisha Li, Kevin Jamieson, Giulia DeSalvo, Afshin Rostamizadeh, and Ameet Talwalkar. Hyperband: A novel banditbased approach to hyperparameter optimization. The Journal of Machine Learning Research, 18(1):6765–6816, 2017.
- [120] Keras Team. Keras documentation: Kerastuner. <u>Keras.[Online]</u>. Available: <u>https://keras.io/keras_tuner/.[Accessed:</u> 05-Feb-2022], 2022.
- [121] Esteban Real, Alok Aggarwal, Yanping Huang, and Quoc V Le. Regularized Evolution for Image Classifier Architecture Search. In Proceedings of the 33rd AAAI conference on artificial intelligence, pages 4780–4789, 2019.
- [122] Barret Zoph and Quoc V Le. Neural architecture search with reinforcement learning. <u>arXiv preprint</u> arXiv:1611.01578, 2016.
- [123] Steven R Young, Derek C Rose, Thomas P Karnowski, Seung-Hwan Lim, and Robert M Patton. Optimizing deep learning hyper-parameters through an evolutionary algorithm. In <u>Proceedings of the workshop on machine learning</u> in high-performance computing environments, pages 1–5, 2015.
- [124] Daniel Martinez, Wesley Brewer, Gregory Behm, Andrew Strelzoff, Andrew Wilson, and Daniel Wade. Deep learning evolutionary optimization for regression of rotorcraft vibrational spectra. In <u>2018 IEEE/ACM Machine Learning in</u> HPC Environments (MLHPC), pages 57–66. IEEE, 2018.
- [125] Moritz Meister, Sina Sheikholeslami, Amir H Payberah, Vladimir Vlassov, and Jim Dowling. Maggy: Scalable asynchronous parallel hyperparameter search. In <u>Proceedings of the 1st Workshop on Distributed Machine Learning</u>, pages 28–33, 2020.
- [126] Chuan Li. OpenAI's GPT-3 language model: A technical overview, June 2020.
- [127] Deepak Narayanan, Mohammad Shoeybi, Jared Casper, Patrick LeGresley, Mostofa Patwary, Vijay Korthikanti, Dmitri Vainbrand, Prethvi Kashinkunti, Julie Bernauer, Bryan Catanzaro, et al. Efficient large-scale language model training on gpu clusters using megatron-lm. In <u>Proceedings of the International Conference for High Performance</u> Computing, Networking, Storage and Analysis, pages 1–15, 2021.
- [128] Lianmin Zheng, Zhuohan Li, Hao Zhang, Yonghao Zhuang, Zhifeng Chen, Yanping Huang, Yida Wang, Yuanzhong Xu, Danyang Zhuo, Eric P Xing, et al. Alpa: Automating inter-and {Intra-Operator} parallelism for distributed deep learning. In <u>16th USENIX Symposium on Operating Systems Design and Implementation (OSDI 22)</u>, pages 559–578, 2022.
- [129] Murali Emani, Sam Foreman, Varuni Sastry, Zhen Xie, Siddhisanket Raskar, William Arnold, Rajeev Thakur, Venkatram Vishwanath, and Michael E. Papka. A comprehensive performance study of large language models on novel ai accelerators, 2023.
- [130] Junqi Yin, Sajal Dash, John Gounley, Feiyi Wang, and Georgia Tourassi. Evaluation of pre-training large language models on leadership-class supercomputers. The Journal of Supercomputing, 79(18):20747–20768, 2023.
- [131] Sajal Dash, Isaac R. Lyngaas, Junqi Yin, Xiao Wang, Romain Egele, J. Austin Ellis, Matthias Maiterth, Guojing Cong, Feiyi Wang, and Prasanna Balaprakash. Optimizing distributed training on frontier for large language models. In Proceedings of the International Supercomputing Conference (ISC), Hamburg, Germany, May 12–16 2024.
- [132] Shuhei Kudo, Keigo Nitadori, Takuya Ina, and Toshiyuki Imamura. Implementation and numerical techniques for one eflop/s hpl-ai benchmark on fugaku. In <u>2020 IEEE/ACM 11th Workshop on Latest Advances in Scalable</u> Algorithms for Large-Scale Systems (ScalA), pages 69–76, 2020.
- [133] Michael Allen Heroux, Jack Dongarra, and Piotr Luszczek. Hpcg benchmark technical specification. Technical report, Sandia National Lab.(SNL-NM), Albuquerque, NM (United States), 2013.
- [134] Alexander Sergeev and Mike Del Balso. Horovod: fast and easy distributed deep learning in tensorflow, 2018.
- [135] Shen Li, Yanli Zhao, Rohan Varma, Omkar Salpekar, Pieter Noordhuis, Teng Li, Adam Paszke, Jeff Smith, Brian Vaughan, Pritam Damania, et al. Pytorch distributed: Experiences on accelerating data parallel training. <u>arXiv</u> preprint arXiv:2006.15704, 2020.
- [136] Jeff Rasley, Samyam Rajbhandari, Olatunji Ruwase, and Yuxiong He. Deepspeed: System optimizations enable training deep learning models with over 100 billion parameters. In on Knowledge Discovery & Data Mining, pages 3505–3506, 2020.

- [137] Shenggui Li, Jiarui Fang, Zhengda Bian, Hongxin Liu, Yuliang Liu, Haichen Huang, Boxiang Wang, and Yang You. Colossal-ai: A unified deep learning system for large-scale parallel training. arXiv preprint arXiv:2110.14883, 2021.
- [138] Daniel Nichols, Kwai Wong, Stan Tomov, Lucien Ng, Sihan Chen, and Alex Gessinger. MagmaDNN: Accelerated Deep Learning using MAGMA. In <u>Proceedings of the Practice and Experience in Advanced Research Computing</u> on Rise of the Machines (learning), pages 1–6, 2019.
- [139] EunJin Jeong, Jangryul Kim, Samnieng Tan, Jaeseong Lee, and Soonhoi Ha. Deep learning inference parallelization on heterogeneous processors with tensorrt. IEEE Embedded Systems Letters, 14(1):15–18, 2021.
- [140] Open Neural Network Exchange (ONNX). https://onnx.ai.
- [141] Peter H Jin, Qiaochu Yuan, Forrest Iandola, and Kurt Keutzer. How to scale distributed deep learning? <u>arXiv</u> preprint arXiv:1611.04581, 2016.
- [142] Tal Ben-Nun and Torsten Hoefler. Demystifying parallel and distributed deep learning: An in-depth concurrency analysis. ACM Comput. Surv., 52(4), aug 2019.
- [143] Ruben Mayer and Hans-Arno Jacobsen. Scalable deep learning on distributed infrastructures: Challenges, techniques, and tools. ACM Comput. Surv., 53(1), feb 2020.
- [144] Oak Ridge National Laboratory. Technical requirements document for OLCF-6 version 1.0. [Online] https://www. olcf.ornl.gov/draft-olcf-6-technical-requirements, September 2023. Accessed: 2023-12-17.
- [145] Peter Mattson, Christine Cheng, Gregory Diamos, Cody Coleman, Paulius Micikevicius, David Patterson, Hanlin Tang, Gu-Yeon Wei, Peter Bailis, Victor Bittorf, et al. Mlperf training benchmark. <u>Proceedings of Machine Learning</u> and Systems, 2:336–349, 2020.
- [146] Zihan Jiang, Wanling Gao, Lei Wang, Xingwang Xiong, Yuchen Zhang, Xu Wen, Chunjie Luo, Hainan Ye, Xiaoyi Lu, Yunquan Zhang, et al. Hpc ai500: a benchmark suite for hpc ai systems. In <u>Benchmarking, Measuring, and Optimizing: First BenchCouncil International Symposium, Bench 2018, Seattle, WA, USA, December 10-13, 2018, Revised Selected Papers 1, pages 10–22. Springer, 2019.</u>
- [147] Yatao Li and Jianfeng Zhan. Saibench: Benchmarking ai for science. <u>BenchCouncil Transactions on Benchmarks</u>, Standards and Evaluations, 2(2):100063, 2022.
- [148] Steven Farrell, Murali Emani, Jacob Balma, Lukas Drescher, Aleksandr Drozd, Andreas Fink, Geoffrey Fox, David Kanter, Thorsten Kurth, Peter Mattson, et al. Mlperf hpc: A holistic benchmark suite for scientific machine learning on hpc systems. In <u>2021 IEEE/ACM Workshop on Machine Learning in High Performance Computing Environments</u> (MLHPC), pages 33–45. IEEE, 2021.
- [149] Jeyan Thiyagalingam, Gregor von Laszewski, Junqi Yin, Murali Emani, Juri Papay, Gregg Barrett, Piotr Luszczek, Aristeidis Tsaris, Christine Kirkpatrick, Feiyi Wang, Tom Gibbs, Venkatram Vishwanath, Mallikarjun Shankar, Geoffrey Fox, and Tony Hey. Ai benchmarking for science: Efforts from the mlcommons science working group. In Hartwig Anzt, Amanda Bienz, Piotr Luszczek, and Marc Baboulin, editors, <u>High Performance Computing. ISC</u> High Performance 2022 International Workshops, pages 47–64, Cham, 2022. Springer International Publishing.
- [150] Vijay Janapa Reddi, Christine Cheng, David Kanter, Peter Mattson, Guenther Schmuelling, Carole-Jean Wu, Brian Anderson, Maximilien Breughe, Mark Charlebois, William Chou, et al. Mlperf inference benchmark. In <u>2020</u> ACM/IEEE 47th Annual International Symposium on Computer Architecture (ISCA), pages 446–459. IEEE, 2020.
- [151] Bjoern Enders, Debbie Bard, Cory Snavely, Lisa Gerhardt, Jason Lee, Becci Totzke, Katie Antypas, Suren Byna, Ravi Cheema, Shreyas Cholia, et al. Cross-facility science with the superfacility project at lbnl. In <u>2020 IEEE/ACM</u> 2nd Annual Workshop on Extreme-scale Experiment-in-the-Loop Computing (XLOOP), pages 1–7. IEEE, 2020.
- [152] Christian Engelmann, Olga Kuchar, Swen Boehm, Michael J Brim, Thomas Naughton, Suhas Somnath, Scott Atchley, Jack Lange, Ben Mintz, and Elke Arenholz. The INTERSECT open federated architecture for the laboratory of the future. In <u>Smoky Mountains Computational Sciences and Engineering Conference</u>, pages 173–190. Springer, 2022.
- [153] Wesley Brewer, Greg Behm, Alan Scheinine, Ben Parsons, Wesley Emeneker, and Robert P Trevino. Inference benchmarking on HPC systems. In <u>2020 IEEE High Performance Extreme Computing Conference (HPEC)</u>, pages 1–9. IEEE, 2020.

- [154] Jorge Ejarque, Rosa M Badia, Loïc Albertin, Giovanni Aloisio, Enrico Baglione, Yolanda Becerra, Stefan Boschert, Julian R Berlin, Alessandro DAnca, Donatello Elia, et al. Enabling dynamic and intelligent workflows for hpc, data analytics, and ai convergence. Future generation computer systems, 134:414–429, 2022.
- [155] Christine R. Kirkpatrick, Gregor von Laszewski, Gregg Barrett, Piotr Luszczek, Mallikarjun (Arjun) Shankar, Wesley Brewer, Murali Emani, Julie Christopher, Ines Dutra, and Geoffrey Fox. Using benchmarking data to inform decisions related to machine learning resource efficiency. <u>Frontiers in High Performance Computing</u>, 2023. Preprint, not yet published.
- [156] Daniel J Milroy, Claudia Misale, Giorgis Georgakoudis, Tonia Elengikal, Abhik Sarkar, Maurizio Drocco, Tapasya Patki, Jae-Seung Yeom, Carlos Eduardo Arango Gutierrez, Dong H Ahn, et al. One step closer to converged computing: Achieving scalability with cloud-native hpc. In <u>IEEE/ACM 4th International Workshop on Containers</u> and New Orchestration Paradigms for Isolated Environments in HPC, pages 57–70. IEEE, 2022.
- [157] Pedro Bruel, Sai Rahul Chalamalasetti, Aditya Dhakal, Eitan Frachtenberg, Ninad Hogade, Rolando Pablo Hong Enriquez, Alok Mishra, Dejan Milojicic, Pavana Prakash, and Gourav Rattihalli. Predicting heterogeneity and serverless principles of converged high-performance computing, artificial intelligence, and workflows. <u>Computer</u>, 57(1):136–144, 2024.
- [158] Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. arXiv preprint arXiv:2108.07258, 2021.
- [159] RFP Technical Requirements Document for NERSC-10 System Version 5.0. [Online] https://www.nersc.gov/ systems/nersc-10/draft-tech-req, December 2023.
- [160] Eli Dart et al. ESnet requirements review program through the IRI lens: A meta-analysis of workflow patterns across DOE office of science programs. Technical report, Lawrence Berkeley National Laboratory (LBNL), Berkeley, CA (United States), 2023.
- [161] Rafael Ferreira da Silva, Rosa Badia, Deborah Bard, Ian T. Foster, Shantenu Jha, and Frédéric Suter. Frontiers in Scientific Workflows: Pervasive Integration with HPC. <u>IEEE Computer Magazine</u>, 2024.