Healing Powers of BERT: How Task-Specific Fine-Tuning Recovers Corrupted Language Models

Shijie Han * Columbia University sh4460@columbia.edu Zhenyu Zhang * Zhejiang University zhenyuzhang@zju.edu.cn

Andrei Arsene Simion Columbia University aas2148@columbia.edu

Abstract

Language models like BERT excel at sentence classification tasks due to extensive pre-training on general data, but their robustness to parameter corruption is unexplored. To understand this better, we look at what happens if a language model is "broken", in the sense that some of its parameters are corrupted and then recovered by fine-tuning. Strategically corrupting BERT variants at different levels, we find corrupted models struggle to fully recover their original performance, with higher corruption causing more severe degradation. Notably, bottom-layer corruption affecting fundamental linguistic features is more detrimental than top-layer corruption. Our insights contribute to understanding language model robustness and adaptability under adverse conditions, informing strategies for developing resilient NLP systems against parameter perturbations.

1 Introduction

Pre-trained language models like BERT (Kenton and Toutanova, 2019) have propelled tremendous progress in sentence classification, an important natural language processing (NLP) task. The powerful representational capabilities of BERT enable more accurate and robust classification across diverse domains (Yin et al., 2019). While BERT demonstrates exceptional ability in capturing intricate linguistic nuances, enabling it to analyze entire sentences and discern their meanings and relationships (Reimers and Gurevych, 2019), the inner workings of BERT are still not fully understood.

Several studies have investigated the robustness of BERT to various perturbations (Dong et al., 2021; Hauser et al., 2023), but the effects of parameter corruption on fine-tuning performance for specific tasks remain unexplored. In this paper, we explore the impact of controlled parameter corruption on BERT's ability to perform sentence classification tasks. We hypothesize that corrupting a pre-trained BERT model will hinder its fine-tuned performance on sentence classification tasks, and then we explore how BERT recovers its original performance during task-specific fine-tuning.

To build our understanding, we strategically corrupt a pre-trained BERT model and then fine-tune it on a popular set of sentence classification datasets. We compare the fine-tuned performance of the corrupted model with a non-corrupted BERT model fine-tuned on the same task. Given this setup, we hope that this will allow us to quantify the classification performance degradation caused by corruption and assess BERT's ability to mitigate this degradation through fine-tuning.

This work sheds light on several crucial aspects of BERT's inner workings:

- Evaluation of language model robustness: We assess how parameter corruption affects the performance of BERT models across various sentence classification tasks. We demonstrate that corrupted models cannot fully recover their original performance through finetuning, with higher corruption levels leading to more degradation.
- Identification of critical architecture: We reveal that corrupting bottom layers of BERT models has a more detrimental effect on performance compared to top layers. This finding highlights the importance of lower layers in capturing fundamental linguistic features.
- **Insights into Generalizability:** By analyzing the impact of corruption, we gain insight into BERT's ability to generalize from pre-trained knowledge to new tasks despite corruption.

Our findings contribute to a deeper understanding of BERT's robustness and the corrective abil-

^{*}Equal contribution

ities of fine-tuning. This knowledge can inform strategies for improving model robustness and developing more resilient NLP systems.

2 Related Work

BERT (Bidirectional Encoder Representations from Transformers) revolutionized NLP with its pre-training and fine-tuning methods (Kenton and Toutanova, 2019). Unlike GPT-style unidirectional models, BERT uses a bidirectional transformer architecture, understanding word context from both directions. This bidirectional approach and its rich token representations enable BERT to excel in various natural language understanding tasks.

Pre-training of BERT. BERT pre-training involves two objectives: Masked Language Modeling (MLM) and Next Sentence Prediction (NSP). In MLM, some input tokens are randomly masked, and the model learns to predict the masked tokens using the surrounding context. This allows BERT to capture nuanced language patterns and dependencies by considering context from both sides of a token (Radford et al.). The NSP task further enhances BERT by training it to predict if a given sentence B logically follows sentence A (Liu et al., 2019; Sanh, 2019). NSP helps model understand relationships between sentences, which is important for tasks involving sentence pairs (Peters et al., 2018).

Fine-tuning for Text Classification. Once pretrained, BERT can be fine-tuned for specific downstream tasks with minimal architectural modifications. For text classification, a simple linear layer is added on top of the pre-trained model, using the output of the special [CLS] token as the aggregate sequence representation (Kenton and Toutanova, 2019; Sun et al., 2019). During fine-tuning, the entire model is trained on labeled data for the target task. BERT's rich pre-trained knowledge provides a strong foundation that can accurately classify text based on nuanced linguistic features when fine-tuned on labeled datasets (Yin et al., 2019). The [CLS] token output is passed through an additional classification layer to produce the final output, making BERT highly versatile for various text classification applications like sentiment analysis and topic categorization (Wang et al., 2018; Hoang et al., 2019; Xu et al., 2019; George and Sumathy, 2023).

Robustness of internal structure. Despite the impressive performance of the BERT model, its inherent complex architecture also makes it vulnerable to various forms of corruption, such as adversarial attacks and weight perturbations, which can severely impact its performance (Ebrahimi et al., 2018). While some research has attempted targeted interventions to influence model performance based on an understanding of the Transformer architecture, our understanding of how its internal components react to corruption remains limited (Meng et al., 2022; Dai et al., 2022; Geva et al., 2021; De Cao et al., 2021). This highlights the need for a deeper understanding of the model, as enhancing our comprehension of BERT's robustness is crucial for model interpretability and reliable deployment (Feder et al., 2021). To bridge this gap, we conduct an in-depth investigation to reveal the extent to which BERT can recover through fine-tuning after being corrupted.

3 Corruption Method

The real-world corruption of BERT is likely to be random and unpredictable, rather than following the same distribution as the pre-trained parameters. Therefore, we simulate corruption in BERT by randomly initializing their internal parameters. Specifically, for corrupting the parameters of the *LayerNorm* layers, we standardize all weight parameters by setting them to a constant value of 1.0. For the weights of *non-LayerNorm* layers, we re-initialize them using the Kaiming uniform initialization method (He et al., 2015), which draws samples from a uniform distribution with specific bounds determined by the input size of the layer. Additionally, all bias parameters are directly initialized to zero.

By selectively applying this initialization corruption to designated layers, we can assess the effects of corruption across different layer positions within the BERT model. Subsequently, we fine-tune and evaluate the modified language model across various text classification benchmarks.

4 Experiment

4.1 Experimental Settings

Language Models and Datasets. To assess the robustness of language models for parameter corruption during task-specific fine-tuning, we choose three BERT models with different scales: BERT-Base with 110M parameters (Kenton and

Model	Corruption	SST-2		IMDB		AG News		Emotion		DBPedia		TFNT	
		Bottom	Тор	Bottom	Тор	Bottom	Top	Bottom	Top	Bottom	Тор	Bottom	Тор
	0%	92.	11	82.4	41	94.	15	93.	04	98.′	78	89.4	42
Base	25% (1-3)	90.16	91.72	81.79	82.34	93.41	94.06	92.87	93.03	98.72	98.57	86.68	89.16
	50% (1-6)	83.25	87.92	76.91	80.92	91.82	93.59	92.11	92.90	97.40	98.37	84.42	88.08
	75% (1-9)	82.18	84.63	76.26	79.30	92.25	93.03	90.31	92.76	97.17	98.22	84.29	86.28
	100% (1-12)	2) 75.17		76.12		90.36		88.09		94.08		75.98	
	0%	93.	22	84.:	52	94.	18	92.	39	98.′	71	90.	07
	25% (1-6)	90.25	91.78	82.85	83.32	93.52	93.84	16.98	93.38	97.62	98.65	86.99	89.93
Large	50% (1-12)	81.83	86.47	33.97	79.48	92.23	93.70	16.98	93.24	96.82	98.51	81.65	89.25
	75% (1-18)	80.84	84.86	76.60	79.10	91.84	93.38	90.02	92.18	96.65	98.49	83.27	87.39
	100% (1-24)	78.93		76.38		90.66		87.80		93.02		77.62	
	0%	89.	72	81.	74	93.	95	93.	11	98.′	72	89.	10
Distil	50% (1-3)	82.63	83.91	75.70	79.00	92.38	93.48	92.26	93.04	97.91	98.50	84.55	86.89
	100% (1-6)	77.:	50	75.	67	90.	57	88.	30	94.3	32	77.	66

Table 1: Fine-tuned BERT performance under different corruption settings across various datasets. Bold values represent higher values between bottom and top. Red values indicate outliers. Reported F1 score in percentage (%)

Dateset	Categories	Train	Test	Balanced
SST-2	2	56k	12k	Yes
IMDB	2	25k	5k	Yes
AG News	4	48k	6k	Yes
Emotion	6	14k	4k	No
DBPedia	14	50k	12k	Yes
TFNT	20	17k	4k	No

Table 2: Classification datasets details

Toutanova, 2019), BERT-Large with 340M parameters (Kenton and Toutanova, 2019), and Distil-BERT with 66M parameters (Sanh, 2019). We corrupt these models using the method outlined in Section 3 and then fine-tune and evaluate them on six classification datasets spanning sentiment analysis and topic categorization: SST-2 (Socher et al., 2013), IMBD (Maas et al., 2011), AG News (Zhang et al., 2015), Emotion (Saravia et al., 2018), DBPedia (Zhang et al., 2015) and Twitter Financial News Topic (TFNT) (Magic, 2022). To control our experiments, we balance the learning difficulty on a dataset with the available computational resources by truncating portions of the dataset and redefining the training and testing splits, as detailed in Table 2.

Implementation Details. Our implementation utilizes the following software and hardware configurations: *PyTorch* (Paszke et al., 2019) version 1.13.1; *Transformers* (Wolf et al., 2020) library version 4.41.1; *CUDA* version 12.4; *GPU*: one NVIDIA RTX4090D-24G; We employ different learning rates of 1e-5, 2e-5, and 5e-5 and choose the best, training over 10 epochs for each dataset with Adam (Kingma and Ba, 2015) as our opti-

mizer.

4.2 Results

To explore the impact of different positions and degrees of corruption on BERT recovery via finetuning, in addition to testing the original and fully corrupted models, we corrupt them by 25%, 50%, and 75% from the bottom and top respectively (the DistilBERT only performs 50% damage). To assess our experiments, we use the weighted F1 score, and in each case, we test every epoch and choose the best indicator. All results are shown in Table 1. Based on these experimental results, we can make the following analysis:

1. Generally, a corrupted BERT model is unable to fully recover its original performance via fine-tuning. Across all three BERT models and six datasets, the fine-tuned performance on corrupted models does not match the performance of the undamaged models. This trend persists across different corruption levels and datasets, suggesting that the fine-tuning process has limitations in compensating for parameter corruption.

2. As the degree of corruption increases, the fine-tuned performance decreases. When the models are undamaged (0% corruption), they achieve the highest performance. As the corruption degree increases from 25% to 50%, 75%, and 100%, the F1 scores gradually decline, indicating a decreased ability to recover from the parameter corruption through fine-tuning. For instance, with the BERT-Base model on the SST-2 dataset, the F1 score drops from 92.11 (undamaged) to 90.16 (25% bottom), 83.25 (50% bottom), 82.18 (75% bottom), and 75.17 (100% corruption). Similar patterns can



Figure 1: Feature clustering visualizations of BERT-Base output with different corruption settings on AG News. (a) 0% corruption (b) 25% top corruption (c) 25% bottom corruption (d) 100% corruption

be observed for the other models and datasets. This clearly shows that corruption can cause irreparable damage to the model's performance and there is a direct observable pattern to this degradation.

3. When the degree of corruption remains unchanged, the impact of bottom-layer corruption is greater than top-layer corruption. Specifically, comparing performance between the bottom and top corruption at the same level, it is evident that bottom-layer corruption leads to a more substantial decrease in F1 score compared to the top layer. For example, with the BERT-Base model on the IMDB dataset, 50% bottom corruption yields an F1 of 76.91, whereas 50% top corruption results in 80.92. This observation aligns with the understanding that lower layers in BERT capture more fundamental linguistic features, and their corruption can have a more significant impact on the model's performance compared to corrupting the higher layers responsible for task-specific representations.

4.3 Feature Similarity.

We employ the t-SNE (Van der Maaten and Hinton, 2008) algorithm to project [CLS] tokens gained from the fine-tuned BERT models with various corruption patterns to 2D space. t-SNE visualization reveals clusters in features, which help in understanding the classification performance and observing intrinsic feature patterns and relationships.

(a) 0% corruption: In the undamaged BERT model, different classes form well-separated groups in 2D space, indicating the effective semantic distinction between categories. (b) 25% top cor-

ruption: Cluster structure is still visible, but some samples drift closer to other clusters, suggesting top layer corruption interferes with BERT's semantic representation. (c) 25% bottom corruption: Cluster boundaries become more blurred, with numerous samples overlapping with other categories' regions. This observation aligns with our quantitative findings, suggesting that bottom-layer corruption has a more significant impact on BERT's representational capabilities. (d) 100% corruption: In this scenario, the visualization suggests that severe parameter corruption has made the task of separating and clustering different semantic categories considerably more difficult for the model. However, some level of semantic differentiation may still be present, albeit obscured by the high degree of feature mixing and overlap caused by the extensive parameter corruption.

Overall, these visualizations corroborate our previous findings. As the degree of corruption increases, we observe a gradual transition from wellseparated clusters to a completely mixed distribution, reflecting the degradation of the model's semantic understanding capabilities.

4.4 Outlier Analysis.

From our results, intriguing outliers emerge such as a low accuracy of 33.97% for BERT-Large on IMDB with 50% bottom corruption, and 16.98% accuracy on Emotion with 25% and 50% bottom corruption. These anomalies, marked by convergence failures and low metrics, may result from the sensitivity of BERT-Large's middle layers, the complexity of its larger parameter set, and specific characteristics of the IMDB and Emotion datasets. These factors highlight the complex interplay between datasets, architectures, and corruption patterns, sometimes leading to unexpected outcomes.

5 Conclusion

We study the robustness of BERT models to parameter corruption during fine-tuning for sentence classification tasks. By strategically corrupting model parameters, we find that corrupted models cannot fully recover original performance through finetuning, with higher corruption levels causing more severe performance degradation. Bottom-layer corruption has a greater impact than top-layer corruption. Our findings shed light on the interplay between pre-trained language models, fine-tuning, and parameter corruption, highlighting their sensitivity to corruption and limitations in recovering performance. These insights contribute to a deeper understanding of the robustness of language models and the precise effect of parameter corruption.

Limitation

Here are a few limitations of this work:

(1) Corruption Method: Our study employs a specific method of parameter corruption by random initialization. Other types of corruption, such as noise injection or targeted parameter manipulation, can potentially yield different insights.

(2) Model Architectures: The research focuses on the BERT family of language models. The impact of parameter corruption may vary across different model architectures, such as recurrent neural networks, convolutional models, or other Transformer-based models.

(3) Fine-tuning Strategies: The study explores the standard fine-tuning approach, where all model parameters are updated during training. Alternative fine-tuning strategies, such as layer-wise adaptation or low-rank adaptation, could potentially mitigate or exacerbate the effects of parameter corruption.

References

- Rie Kubota Ando and Tong Zhang. 2005. A framework for learning predictive structures from multiple tasks and unlabeled data. *Journal of Machine Learning Research*, 6:1817–1853.
- Roy Bar Haim, Ido Dagan, Bill Dolan, Lisa Ferro, Danilo Giampiccolo, Bernardo Magnini, and Idan Szpektor. 2006. The second PASCAL recognising textual entailment challenge.
- Luisa Bentivogli, Ido Dagan, Hoa Trang Dang, Danilo Giampiccolo, and Bernardo Magnini. 2009. The fifth PASCAL recognizing textual entailment challenge.
- Ido Dagan, Oren Glickman, and Bernardo Magnini. 2006. The PASCAL recognising textual entailment challenge. In *Machine learning challenges. evaluating predictive uncertainty, visual object classification, and recognising tectual entailment*, pages 177–190. Springer.
- Damai Dai, Li Dong, Yaru Hao, Zhifang Sui, Baobao Chang, and Furu Wei. 2022. Knowledge neurons in pretrained transformers. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8493– 8502.
- Nicola De Cao, Wilker Aziz, and Ivan Titov. 2021. Editing factual knowledge in language models. In *Proceedings of the 2021 Conference on Empirical Meth-*

ods in Natural Language Processing, pages 6491–6506.

- Xinshuai Dong, Anh Tuan Luu, Min Lin, Shuicheng Yan, and Hanwang Zhang. 2021. How should pretrained language models be fine-tuned towards adversarial robustness? In *Advances in Neural Information Processing Systems*.
- Javid Ebrahimi, Anyi Rao, Daniel Lowd, and Dejing Dou. 2018. Hotflip: White-box adversarial examples for text classification. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*. Association for Computational Linguistics.
- Amir Feder, Nadav Oved, Uri Shalit, and Roi Reichart. 2021. Causalm: Causal model explanation through counterfactual language models. *Computational Linguistics*, 47(2):333–386.
- Lijimol George and P Sumathy. 2023. An integrated clustering and bert framework for improved topic modeling. *International Journal of Information Technology*, 15(4):2187–2195.
- Mor Geva, Roei Schuster, Jonathan Berant, and Omer Levy. 2021. Transformer feed-forward layers are key-value memories. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 5484–5495.
- Danilo Giampiccolo, Bernardo Magnini, Ido Dagan, and Bill Dolan. 2007. The third PASCAL recognizing textual entailment challenge. In *Proceedings of the ACL-PASCAL workshop on textual entailment and paraphrasing*, pages 1–9. Association for Computational Linguistics.
- Jens Hauser, Zhao Meng, Damian Pascual, and Roger Wattenhofer. 2023. Bert is robust! a case against word substitution-based adversarial attacks. In ICASSP 2023-2023 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pages 1–5. IEEE.
- Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2015. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference* on computer vision, pages 1026–1034.
- Mickel Hoang, Oskar Alija Bihorac, and Jacobo Rouces. 2019. Aspect-based sentiment analysis using bert. In Proceedings of the 22nd nordic conference on computational linguistics, pages 187–196.
- Jacob Devlin Ming-Wei Chang Kenton and Lee Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of NAACL-HLT*, pages 4171–4186.
- Diederik P. Kingma and Jimmy Ba. 2015. Adam: A method for stochastic optimization. In 3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings.

- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. arXiv preprint arXiv:1907.11692.
- Andrew L. Maas, Raymond E. Daly, Peter T. Pham, Dan Huang, Andrew Y. Ng, and Christopher Potts. 2011. Learning word vectors for sentiment analysis. In Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies, pages 142–150, Portland, Oregon, USA. Association for Computational Linguistics.
- Neural Magic. 2022. Twitter financial news sentiment. Accessed: 2022.
- Kevin Meng, David Bau, Alex J Andonian, and Yonatan Belinkov. 2022. Locating and editing factual associations in gpt. In *Advances in Neural Information Processing Systems*.
- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. 2019. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32.
- Matthew Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. 2018. Deep contextualized word representations. In Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers). Association for Computational Linguistics.
- Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. Improving language understanding by generative pre-training.
- Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 3982–3992.
- V Sanh. 2019. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. In *Proceedings* of *Thirty-third Conference on Neural Information Processing Systems (NIPS2019).*
- Elvis Saravia, Hsien-Chi Toby Liu, Yen-Hao Huang, Junlin Wu, and Yi-Shin Chen. 2018. CARER: Contextualized affect representations for emotion recognition. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 3687–3697, Brussels, Belgium. Association for Computational Linguistics.
- Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D. Manning, Andrew Ng, and Christopher Potts. 2013. Recursive deep models for

semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*, pages 1631–1642, Seattle, Washington, USA. Association for Computational Linguistics.

- Chi Sun, Xipeng Qiu, Yige Xu, and Xuanjing Huang. 2019. How to fine-tune bert for text classification? In Chinese computational linguistics: 18th China national conference, CCL 2019, Kunming, China, October 18–20, 2019, proceedings 18, pages 194– 206. Springer.
- Laurens Van der Maaten and Geoffrey Hinton. 2008. Visualizing data using t-sne. *Journal of machine learning research*, 9(11).
- Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. 2018. Glue: A multi-task benchmark and analysis platform for natural language understanding. In *International Conference on Learning Representations*.
- Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. 2019. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In the Proceedings of ICLR.
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. 2020. Transformers: State-of-the-art natural language processing. In Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations, pages 38–45, Online. Association for Computational Linguistics.
- Hu Xu, Bing Liu, Lei Shu, and S Yu Philip. 2019. Bert post-training for review reading comprehension and aspect-based sentiment analysis. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 2324–2335.
- Wenpeng Yin, Jamaal Hay, and Dan Roth. 2019. Benchmarking zero-shot text classification: Datasets, evaluation and entailment approach. In 2019 Conference on Empirical Methods in Natural Language Processing and 9th International Joint Conference on Natural Language Processing, EMNLP-IJCNLP 2019, pages 3914–3923. Association for Computational Linguistics.
- Xiang Zhang, Junbo Zhao, and Yann LeCun. 2015. Character-level convolutional networks for text classification. In *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc.

Appendix

A More Analysis

To further verify the rules summarized in the main paper, we use different experimental settings to perform the following analysis:

A.1 Average Token

We replace the [CLS] token in the BERT output mentioned in Section 2 with the average of all non-[CLS] tokens output by BERT as the input of the classification matrix, and obtain the results in Table 3. These results further corroborate the three main conclusions drawn from the previous experiments. However, it is noteworthy that the results obtained using the average token strategy exhibit some fluctuations compared to the previous experiments using the [CLS] token. On the DBPedia dataset, we can observe some interesting anomalies in the base model. For 75% top corruption achieves a score of 98.49%, which is higher than both 25% and 50% top corruption. This deviates from our previous finding that higher degrees of corruption lead to worse performance. Despite these anomalies, the overall trend across multiple datasets and models still supports the general conclusions drawn earlier.

These fluctuations suggest that the average token strategy may not be as robust as using the [CLS] token for representation, which is specifically designed for classification tasks. The [CLS] token captures task-specific information more effectively, leading to more consistent results across different corruption settings.

A.2 Linear Probe

In previous experiments, we fine-tune all BERT model parameters to assess the impact of parameter corruption on performance. Alternatively, we can use a linear probing approach by freezing the pre-trained BERT parameters and only fine-tuning the classification head. This method allows us to investigate how well corrupted BERT models transfer learned representations to downstream tasks without further adapting the main model parameters.

The results presented in Table 4 appear highly unstable and inconsistent, making it challenging to observe clear trends identified when the entire BERT is fine-tuned. One potential reason for this instability is the optimization process for the classification head may struggle to converge, leading to erratic behavior and performance fluctuations. These irregularities and inconsistencies suggest that the linear probing approach may not be suited for accurately assessing the impact of parameter corruption on the model's performance. The lack of adaptation in the main BERT body could exacerbate the effects of corruption, leading to unstable and unpredictable results.

A.3 Non-classification Task

We also conduct some exploration of non-classified datasets. Specifically, we use the same method to test the RTE and MRPC datasets for text entailment tasks and similarity judgment tasks. The results are shown in Table 5. While the overall trends observed in the previous experiments on classification tasks are also present in the results for non-classification tasks, they are much more volatile and inconsistent. For instance, on the MRPC dataset, the BERT-Base model's performance fluctuates significantly, with 25% bottom corruption (54.22%) outperforming the undamaged model (55.84%), and 75% bottom corruption (53.34%) scoring higher than 50% (53.71%).

These irregularities and inconsistencies suggest that the trends observed in the classification tasks may not be as pronounced or robust in nonclassification tasks. The nature of the tasks, the specific datasets, and the way the models encode and process the data for these tasks could all contribute to the increased volatility in performance under different corruption settings. It reminds us that the behavior of language models can be highly task-dependent, and the impact of parameter corruption may manifest differently across different types of tasks and datasets.

B License of Scientific Artifacts

We discuss the license of the used dataset as follows:

SST-2 It uses a CC-zero License. Anyone can copy, modify, distribute, and perform the work, even for commercial purposes, all without asking permission. CC-zero Link. We have cited the original paper.

IMDB There is no specific license. Anyone using the dataset should cite the (Maas et al., 2011)

AGNews AGNews has Custom (noncommercial) License. The dataset is provided by the academic community for research purposes in data mining (clustering, classification, etc), information retrieval (ranking, search, etc), XML,

Model	Corruption	SST-2		IMDB		AG News		Emotion		DBPedia		TFNT	
		Bottom	Тор	Bottom	Тор	Bottom	Top	Bottom	Top	Bottom	Тор	Bottom	Тор
	0%	91.	67	82.	31	94.	08	93.	20	98.4	42	87.	22
	25% (1-3)	89.54	91.44	81.38	81.96	93.16	93.93	92.89	93.07	97.85	98.43	82.14	87.49
Base	50% (1-6)	83.93	87.03	77.29	80.76	93.02	93.93	92.28	92.90	97.34	98.43	84.07	88.18
	75% (1-9)	83.24	83.15	76.66	79.07	91.95	92.45	89.75	92.76	97.69	98.49	84.71	85.27
	100% (1-12)	77.0	07	76.	29	90.	71	87.	71	94.:	56	76.:	53
	0%	93.	33	82.	31	93.	91	93.	48	98.8	86	89.:	55
	25% (1-6)	90.01	92.30	81.73	81.96	93.51	93.81	92.72	93.27	98.01	98.57	85.03	88.96
Large	50% (1-12)	44.78	87.07	77.29	80.76	91.72	93.59	90.18	92.64	96.77	98.43	81.80	88.60
	75% (1-18)	82.49	84.89	76.66	79.07	92.22	93.30	89.92	92.07	97.55	98.35	83.96	88.37
	100% (1-24)	78.66		76.29		90.47		87.28		93.57		79.36	
	0%	89.1	29	81.	67	93.	92	93.	25	98.0	65	86.	18
Distil	50% (1-3)	81.60	84.02	77.22	79.78	91.85	93.51	92.10	93.14	97.39	98.21	81.46	85.67
	100% (1-6)	77.4	48	76.	20	90.	50	87.	93	95.4	47	75.	64

Table 3: Fine-tuned BERT performance under different corruption settings across various datasets with the average token. Bold values represent higher values between bottom and top. Red values indicate outliers. Reported F1 score in percentage (%)

M. 1.1	Germatien	AG N	lews	DBPedia		
Model	Corruption	Bottom	Тор	Bottom	Тор	
	0%	81.4	41	77.33		
	25% (1-3)	79.73	78.41	76.15	83.27	
Base	50% (1-6)	67.53	80.58	59.85	80.61	
	75% (1-9)	69.93	82.18	66.49	82.54	
	100% (1-12)	50.0	68	53.28		
	0%	65.	65	71.31		
	25% (1-6)	64.38	71.78	53.29	83.07	
Large	50% (1-12)	39.20	77.21	16.81	62.44	
	75% (1-18)	50.93	83.27	32.94	83.88	
	100% (1-24)	51.	19	57.74		
	0%	89.1	29	98.95		
Distil	50% (1-3)	82.98	88.11	91.94	97.19	
	100% (1-6)	54.0	60	71.97		

Table 4: Fine-tuned BERT linear probe performance under different corruption settings across various datasets. Bold values represent higher values between bottom and top. Red values indicate outliers. Reported F1 score in percentage (%)

data compression, data streaming, and any other non-commercial activity. Everyone is encouraged to download this corpus for any non-commercial use.

Emotion The Hugging Face page shows this dataset should be used for educational and research purposes only.

DBPedia The DBPedia ontology classification dataset is licensed under the terms of the Creative Commons Attribution-ShareAlike License and the GNU Free Documentation License.

Twitter Financial News Topic (TFNT) The Twitter Financial Dataset (topic) version 1.0.0 is

Madal	Commution	MR	PC	RTE		
Model	Corruption	Bottom	Тор	Bottom	Тор	
	0%	76.3	38	55.84		
	25% (1-3)	64.73	73.58	54.22	60.85	
Base	50% (1-6)	65.00	73.68	53.71	57.78	
	75% (1-9)	63.10	67.15	53.34	57.20	
	100% (1-12)	60.7	74	47.36		
	0%	77.9	92	60.26		
	25% (1-6)	61.60	79.60	45.39	62.62	
Large	50% (1-12)	44.18	73.63	30.05	52.48	
	75% (1-18)	63.27	65.40	30.05	53.81	
	100% (1-24)	63.2	27	30.05		
	0%	79.03		56.12		
Distil	50% (1-3)	64.49	71.00	57.82	60.66	
	100% (1-6)	63.4	46	52.38		

Table 5: Fine-tuned BERT performance under different corruption settings across non-classified datasets. Bold values represent higher values between bottom and top. Red values indicate outliers. Reported F1 score in percentage (%)

released under the MIT License.

MRPC There is no specific license in this page. Anyone using the dataset should cite the (Ando and Zhang, 2005).

RTE The Recognizing Textual Entailment (RTE) datasets come from a series of annual textual entailment challenges. The authors of the GLUE benchmark combined the data from RTE1 (Dagan et al., 2006), RTE2 (Bar Haim et al., 2006), RTE3 (Giampiccolo et al., 2007) and RTE5 (Bentivogli et al., 2009). Examples are constructed based on news and Wikipedia text. Anyone using the dataset should cite above and GLUE (Wang et al., 2019).

There is no specific license in tac page and acl page.