MMBench-Video: A Long-Form Multi-Shot Benchmark for Holistic Video Understanding

Xinyu Fang^{1,4*}, Kangrui Mao^{2*†}, Haodong Duan^{1‡}, Xiangyu Zhao^{1,2}, Yining Li¹, Dahua Lin^{1,3}, Kai Chen^{1‡} ¹Shanghai AI Laboratory ²Shanghai Jiao Tong University ³ The Chinese University of Hong Kong ⁴ Tongji University fangxinyu, duanhaodong@pjlab.org.cn

Abstract

The advent of large vision-language models (LVLMs) has spurred research into their applications in multi-modal contexts, particularly in video understanding. Traditional VideoQA benchmarks, despite providing quantitative metrics, often fail to encompass the full spectrum of video content and inadequately assess models' temporal comprehension. To address these limitations, we introduce MMBench-Video, a quantitative benchmark designed to rigorously evaluate LVLMs' proficiency in video understanding. MMBench-Video incorporates lengthy videos from YouTube and employs free-form questions, mirroring practical use cases. The benchmark is meticulously crafted to probe the models' temporal reasoning skills, with all questions human-annotated according to a carefully constructed ability taxonomy. We employ GPT-4 for automated assessment, demonstrating superior accuracy and robustness over earlier LLM-based evaluations. Utilizing MMBench-Video, we have conducted comprehensive evaluations that include both proprietary and open-source LVLMs for images and videos. MMBench-Video stands as a valuable resource for the research community, facilitating improved evaluation of LVLMs and catalyzing progress in the field of video understanding. The evalutation code of MMBench-Video will be integrated into VLMEvalKit: https://github.com/open-compass/VLMEvalKit.

1 Introduction

As a ubiquitous format for multimedia, video holds a pivotal role in people's lives, serving purposes such as knowledge dissemination, sharing life experiences, and entertainment. The rapid proliferation of video content has reshaped communication, learning, and connection in the digital age. The vast amount of online video content underscores the importance of algorithmic video understanding. Current video understanding paradigms, which often focus on specific tasks [19, 60, 18], typically excel only on in-domain data. An ideal video understanding system should demonstrate robust zero-shot capabilities, accurately discern contextual, emotional, and linguistic details within a video, and engage in free-form dialogues with humans [30, 36].

With the rapid development of Large Language Models (LLMs) [38, 48, 49], Large Vision Language Models (LVLMs) [39, 47, 34, 16] have also seen significant advancements. Typical video-language models developed by researchers utilize frame-level [36] or clip-level [32] visual features extracted by vision encoders [44, 51, 22], align these features with language embeddings via a projector, and

^{*} These authors contributed equally to this work.

[†] The work was conducted during an internship at Shanghai AI Laboratory.

[‡] Corresponding author.



Figure 1: **Comparing mainstream LVLMs on MMBench-Video.** Two radar graphs illustrate the performance for each coarse (L-2) and each fine-grained (L-3) capability, respectively.

process these embeddings with a fine-tuned large language encoder [13]. The models are fine-tuned with video instruction data and quantitatively assessed on free-form VideoQA benchmarks [58, 24, 52]. The current evaluation of Video-LLMs is characterized by the following limitations:

1. **Short Videos**: Existing VideoQA datasets primarily consist of short videos, typically lasting less than a minute. Meanwhile, most web video content spans several minutes or longer, creating a discrepancy between the evaluation benchmark and real-world application scenarios.

2. Limited Capabilities: Current VideoQA benchmarks are limited to several basic video tasks [23], including concept existence, object relationship recognition, and activity recognition. There are more fine-grained perception and reasoning capabilities [35] not encompassed by existing benchmarks.

3. **Biased Evaluation**: Existing evaluation paradigms employ GPT-3.5 to score open-ended answers generated by video-language models. Our preliminary study indicates that GPT-3.5-based evaluation is less accurate and exhibits significant discrepancy relative to human preferences, diminishing the credibility of the evaluation results.

To address these problems, we develop a new VideoQA benchmark, **MMBench-Video**, to evaluate the effectiveness of LVLMs in video understanding. It incorporates approximately 600 web videos with rich context from YouTube, spanning 16 major categories, including News, Sports, *etc.*, covering most video topics people watch in their daily lives. Each video ranges in duration from 30 secs to 6 mins, to accommodate the evaluation of video understanding capabilities on longer videos. The benchmark includes roughly 2,000 original question-answer (QA) pairs, contributed by volunteers, covering a total of 26 fine-grained capabilities. During dataset collection, we implement quality control strategies to explicitly increase the proportion of temporal indispensable questions⁻¹. Quantitative statistics show that MMBench-Video significantly differs from existing benchmarks in terms of temporal duration, context richness, and temporal indispensability.

During evaluation, an LVLM produces free-form responses to visual questions. Given the variability in the lengths and styles of ground-truth answers, accurately assessing these responses presents a significant challenge. In light of the limitations observed in previous evaluations powered by GPT-3.5, we propose the use of the more powerful GPT-4 [39] for automated scoring. This approach prioritizes semantic similarity while overlooking minor discrepancies in language organization. Employing a carefully crafted evaluation prompt, our GPT-4-based evaluation exhibits improved quality in terms of accuracy, consistency, and alignment with human judgment.

⁻¹A visual question is temporal indispensable if it can not be correctly solved by viewing any random frame.

Based on MMBench-Video, we perform a thorough evaluation of mainstream LVLMs, including opensource video-language models (Video-LLMs), as well as both open-source and proprietary LVLMs for image understanding. We report their performance across diverse capabilities, as depicted in Fig. 1. The performance rankings enable direct comparisons between models, revealing critical insights into their limitations. Surprisingly, existing Video-LLMs exhibit subpar performance on MMBench-Video, significantly underperforming proprietary LVLMs and even lagging behind open-source LVLMs, such as Idefics2 [27] and InternVL-Chat-v1.5 [12]. To further investigate these models' capabilities, we employ image VQA benchmarks to assess their image understanding skills, again observing a substantial gap between Video-LLMs and the state-of-the-art LVLMs. The comprehensive assessment underscores the significant performance disparities between Video-LLMs and leading LVLMs in both spatial and temporal understanding, highlighting areas requiring future improvement.

In summary, the contributions of this work are as follows:

• **Innovative VideoQA Benchmark:** MMBench-Video features long-form, diverse videos sourced from the web, encompassing a broad spectrum of topics. It includes original, high-quality visual questions crafted by volunteers, spanning dozens of fine-grained capabilities.

Enhanced Scoring Methodology: We assess the limitations of using low-quality LLMs, such as GPT-3.5, for scoring model responses. To address this, we implement a GPT-4-based evaluation paradigm, which offers superior accuracy, consistency, and a closer alignment with human judgments.
In-depth Evaluation: Our comprehensive assessment of various LVLMs on MMBench-Video reveals detailed insights into their performance across multiple fine-grained capabilities. The results underscore the current limitations of Video-LLMs in spatial and temporal understanding, guiding future research and development.

2 Related Work

2.1 Large Vision-Language Models

The success of Large Language Models (LLMs) such as GPTs [44, 6, 39] and LLaMA [48, 49] has spurred significant advancements in Large Vision-Language Models (LVLMs). Flamingo [3] has demonstrated impressive few-shot capabilities by integrating gated cross-attention blocks to connect pre-trained vision and language models. BLIP [29, 16] employs a Querying Transformer to bridge the modality gap between a frozen image encoder and a language encoder. LLaVA [34] leverages GPT-4 to create instruction-following data for vision-language tuning, with its learning paradigm and instruction tuning corpus being widely adopted by subsequent works [33, 10, 1, 15]. In the realm of video-language models, Video-ChatGPT [36] aligns frame-level vision features with language embeddings via a linear projector, whereas VideoChat [30] utilizes a learnable Q-former, inspired by BLIP-2. Subsequent works like Video-LLaMA [59] integrate audio features, and Video-LLaVA [32] learns from a mixed dataset of images and videos. Additionally, proprietary APIs such as GPT-[4v/40] [39], Gemini [47], and Reka [42] have been made publicly available, supporting various input formats including single or multiple images. We present a comprehensive evaluation of existing LVLMs, encompassing Video-LLMs as well as open-source and proprietary LVLMs for images, using the proposed MMBench-Video to provide a detailed landscape of their capabilities.

2.2 Video Question Answering

Video Question Answering (VideoQA) is a critical method for assessing the depth of understanding that models possess regarding video content. The research community has progressively developed a wide array of VideoQA benchmarks, spanning various visual domains such as movies [46], TV shows [28, 21], video games [37], synthetic scenarios [57], and egocentric videos [20]. These benchmarks typically assess models trained on their respective training sets, demanding concise answers for evaluation. However, Large Vision and Language Models (LVLMs), which are often not trained on domain-specific data, face challenges in adapting to these benchmarks due to their diverse answer styles. To mitigate this, Video-ChatGPT [36] employs GPT-3.5 as a scoring mechanism for free-form responses from VLMs. The method was applied to evaluate several popular benchmarks [58, 24, 52], covering topics including concept existence, objection relationship, and activity recognition. Despite its broad adoption [32, 54, 45], this approach is limited by suboptimal accuracy and stability, as well as poor alignment with human preferences. Additionally, those benchmarks primarily consist



Figure 2: **Overview of ability dimensions in MMBench-Video.** Currently, MMBench-Video incorporates three levels of ability dimensions (L-1 to L-3), encompassing 26 distinct leaf abilities.

of short videos, which contrasts with the typical length of web videos. In response, we present MMBench-Video, a novel dataset tailored for longer videos, challenging models to generate detailed, free-form responses to complex questions. We adopt GPT-4-based evaluation, which improves correctness and robustness, offering a more stable evaluation strategy compared to previous methods.

3 MMBench-Video

In this section, we delve into the meticulous construction of MMBench-Video, outlining our strategic approach to video question selection, the conceptualization and design of a comprehensive capability taxonomy, and the innovative methods employed to enhance the temporal relevance and quality of questions. Additionally, we present detailed statistics of MMBench-Video and contrast it with existing VideoQA benchmarks, thereby illustrating its unique features and contributions to the field.

3.1 Benchmark Construction

Video Collection. To create a VideoQA benchmark, a prevalent approach involves generating question-answer pairs for videos sourced from existing datasets. For example, MSRVTT-QA and MSVD-QA are derived from video retrieval datasets [53, 9], while ActivityNet-QA is constructed using an action recognition dataset [7]. Most existing VideoQA datasets are limited to short videos with a constrained number of shots, exhibiting limited diversity in content. To develop a benchmark that more closely mirrors the web video content commonly consumed by viewers, we propose the creation of a long-form, multi-shot VideoQA benchmark. The benchmark draws its content directly from YouTube, offering several distinct advantages. Firstly, YouTube's extensive metadata, including video titles, click metrics, and subtitles, provides valuable context for video understanding. Secondly, as a leading global streaming platform, YouTube's vast user base ensures the dataset's diversity.

Drawing inspiration from the YouTube-8M [2] labels, our categorization scheme encompasses 16 major categories (Fig. 3), spanning from engaging topics like 'Entertainment and Sports' to

Table 1: **Comparing the statistics of MMBench-Video and other widely adopted VideoQA benchmarks.** When reporting the video statistics, we follow the format of "mean value (standard deviation)".

Benchmarks	QA pairs Generation	Number of Capabilities	Question Length mean(std) words	Answer Length mean(std) words	Video Duration mean(std) sec	Shot Number mean(std)
MSVD-QA [52]	Automatic	2	6.6(2.5)	1.0(0.0)	9.8(6.6)	2.4(3.4)
MSRVTT-QA [53]	Automatic	2	7.4(3.4)	1.0(0.0)	15.1(5.2)	3.4(2.9)
TGIF-QA [24]	Automatic/Human	4	9.7(2.3)	1.5(0.9)	3.7(2.0)	1.2(1.4)
ActivityNet-QA [58]	Human	3	8.9(2.4)	1.3(0.7)	111.5(66.1)	12.9(20.9)
MMBench-Video	Human	26	10.9 (4.1)	8.4 (7.7)	165.4 (80.7)	32.6 (33.5)

enlightening subjects such as 'Science and Knowledge'. Volunteers are instructed to navigate through YouTube and collect videos that align with these designated categories. In line with our objective to amass long-form content, volunteers are directed to disregard videos with durations of less than 30 seconds. Although we impose no upper limit on the length of the web videos collected, all question-answer pairs composed for a video will be derived from a clip no longer than 6 minutes. This helps maintain a practical balance between video duration and the task complexity.

Capability Taxonomy. Inspired by MMBench [35], we have developped a 3-level (L-1 to L-3) hierarchical capability taxonomy (Fig. 2). The top level encompasses two broad capabilities: Perception and Reasoning. Besides the six L-2 capabilities inherited from MMBench, we further introduce three additional L-2 capabilities specific to MMBench-Video: Hallucination, Commonsense Reasoning, and Temporal Reasoning. **Hallucination** assesses whether a model is prone to generating content that includes misleading or inaccurate information. **Commonsense Reasoning** evaluates a model's ability to integrate necessary commonsense knowledge into its reasoning processes. **Temporal Reasoning** examines a model's proficiency in understanding the relationships between events unfolding at different video points. This taxonomy comprises a total of 26 leaf capabilities, which collectively address a comprehensive spectrum of cognitive processes involved in video comprehension.

Composing Questions and Answers. A well-known issue in existing VideoQA benchmarks is the prevalence of non-temporal questions, which are those that can be accurately answered based on nearly any frame within a video, rendering them effectively 'static'. These questions fail to adequately assess a model's ability to temporal understanding. In the curation of MMBench-Video, we prioritize questions that necessitate temporal reasoning and strive to minimize the occurrence of static questions. Recognizing the necessity of evaluating certain coarse perception capabilities, such as Video Style and Video Topic, it is impractical to entirely eliminate static questions. Instead, we focus on significantly reducing their proportion within the benchmark.

In MMBench-Video, each video is accompanied by multiple independent questions designed to assess one or more specific leaf capabilities. For instance, a question that requires identifying and counting a particular type of object would evaluate both Object Recognition and Counting capabilities. To ensure the quality and relevance of the questions and their corresponding answers, volunteers involved in the collection process are provided with the following five guidelines to adhere to:

1. Each question should **evaluate one or multiple leaf capabilities** within the established taxonomy.

2. You are encouraged to formulate **temporal indispensable questions**, as long as it's feasible for the corresponding video content and capability category.

3. Avoid including specific timestamps in the questions, such as "at 03:20 in the video". Please use relative expressions like "at the end of the video" or "before/after a specific event" instead.

4. The questions should be **free-form** and exhibit **linguistic diversified**. Besides standard formats like *What/Who/How*, questions can also adopt a conversational style⁰.

5. Please provide informative and detailed answers for each question.

All generated question-answer pairs in MMBench-Video will be subjected to a meticulous crossvalidation process to confirm their accuracy and adherence to the established guidelines. In addition to this, we implement an LVLM-based filtering mechanism to identify and eliminate a portion of static questions, as detailed in the supplementary material. The final MMBench-Video dataset comprises a

⁰For example, "What is the score of the football game in the video?" (a "what" question) can be expressed as "Tell me the winning team and the final score." (conversation style).



Figure 3: Video category distribution of Figure 4: Duration distribu-MMBench-Video. tion of MMBench-Video.

Figure 5: Shot number distribution of MMBench-Video and other benchmarks.

Benchmark	MS	SVD	тс	GIF	MSR	RVTT	Activ	ityNet	MMBer	nch-Video	
Input Frames	1	8	1	8	1	8	1	8	1	8	
Original Score	2.62	2.93	2.66	3.18	2.01	2.33	2.65	3.05	0.78	1.63	
Normalized Score	52.4	58.6	53.2	63.6	40.2	46.6	53.0	61.0	26.0	54.3	
Score-[1f] / Score-[8f]	89.4%		80.5%		86.3%		87.0%		47.8%		

Table 2: **Comparing the temporal indispensability of existing VideoQA benchmarks.** MMBench-Video adopts a different grading paradigm compared to other benchmarks (3-grade *vs.* 5-grade). We calculate the 'Normalized Score' (normalize to 0-100) to ease the cross-benchmark comparisons. Benchmarks with smaller 1-frame scores and Score-[1f] / Score-[8f] ratio feature better temporal indispensability.

diverse selection of web videos sourced from YouTube, accompanied by human-composed, original question-answer pairs designed to assess a comprehensive array of fine-grained capabilities.

Evaluation Paradigm. Given the varied length and style of ground-truth answers, automated robust evaluation that aligns with human judgments can be challenging. To address this, we propose a 3-grade marking scheme and utilize GPT-4 [39] as our adjudicator. GPT-4 assigns a score from 0 to 3 based on the content similarity between the model's output and the ground truth. Our experiments show that this evaluation framework exhibits strong consistency and alignment with human assessments.

3.2 Dataset Statistics

MMBench-Video comprises **609** video clips across 16 major categories, as depicted in Fig. 3), with durations spanning from 30 seconds to 6 minutes. The dataset has an average video length of **165** seconds, totaling **28 hours** in aggregated duration. The duration distribution of the clips within MMBench-Video is illustrated in Fig. 4. The dataset includes **1,998** question-answer (QA) pairs, with each QA assessing one or multiple capabilities of a vision-language model. The distribution of QAs corresponding to each capability is visualized in Fig. 2. To highlight the distinct value of MMBench-Video, we compare its statistics with those of existing VideoQA benchmarks:

Duration & Shot Numbers¹. MMBench-Video is specifically designed as a **long-form, multi-shot** video dataset. As indicated in Tab. 1, our dataset boasts a substantially greater average duration than existing benchmarks. As shown in Fig. 5, videos in our benchmark display a long-tail distribution in shot numbers, with a maximum of 210 shots. This significantly surpasses all other benchmarks in average shot count.

Linguistic Characteristics of QAs. MMBench-Video features free-form video QA with rich linguistic diversity. In benchmarks such as MSVD-QA and MSRVTT-QA, questions are automatically generated and invariably begin with pronouns such as 'what', 'who', *etc.* Conversely, a significant proportion of questions in MMBench-Video are framed in a conversational manner, enhancing linguistic diversity (further details are available in the supplementary materials). Regarding answers, previous VideoQA benchmarks often provide responses that are limited to a single word or a brief phrase. In contrast, MMBench-Video strives to offer more comprehensive answers that extend beyond a single word. This is evident in the distribution of answer lengths, as shown in Tab. 1.

Capability Coverage. Existing benchmarks typically cover only a limited set of fine-grained capabilities [23] and often lack an explicit capability taxonomy. For instance, the majority of questions in MSVD-QA and MSRVTT-QA assess the ability to determine the existence of concepts

¹We adopt the open-source tools scenedetect [8] to obtain the shot number of a video.

(such as humans or objects) and to recognize relationships between objects. In contrast, ActivityNet-QA and TGIF-QA extend this by including assessments of activity recognition and repetition counting. In MMBench-Video, we have established a comprehensive taxonomy encompassing 26 fine-grained capabilities, with each capability being evaluated using dozens to hundreds of original QAs.

Temporal Indispensability. In contrast to existing VideoQA benchmarks, MMBench-Video is designed to be temporal indispensable. In a preliminary study, we find that a great proportion of QAs in existing datasets can be correctly answered by LVLMs without providing the temporal context. The underlying factors can be categorized into two primary ones: (1) The brevity of source videos, characterized by the limited number of shots, allows for its content to be adequately represented by a single frame. (2) Many of the QAs are too simplistic and can be answered through guesswork rather than comprehension. For instance, MSVD-QA and MSRVTT-QA are replete with 'who' questions, which are commonly answered with general terms like 'someone', 'man', or 'woman'. In MMBench-Video, we have made significant efforts to mitigate these factors.

To quantitatively measure the temporal indispensability of each VideoQA benchmark, we randomly sample 1000 QAs from MSVD, TGIF, MSRVTT, and ActivityNet, and conduct a study on the subsets as well as MMBench-Video. We evaluate GPT-40 (by far the most powerful LVLM) on these benchmarks under 1-frame and 8-frame settings, and present the results in Tab. 2. Notably, GPT-40 using a 1-frame input achieves a normalized score of approximately 50%, retaining over 80% of its performance compared to an 8-frame input across MSVD, TGIF, MSRVTT, and ActivityNet. In contrast, when assessed on the MMBench-Video, GPT-40 using a 1-frame input preserves only 47.8% of its efficacy compared to its performance with an 8-frame input, yielding a normalized score of just 26.0%. This marked difference underscores the temporal importance of MMBench-Video.

4 Experiment

Utilizing MMBench-Video, we assess a diverse array of large vision-language models (LVLMs), encompassing Video-LLMs and image-based LVLMs, both open-source and proprietary. For Video-LLMs, we utilize the default hyperparameters specified in their respective open-source implementations for inference. For image-based LVLMs, we conduct evaluations based on VLMEvalKit [14], employ greedy decoding during inference and cap the maximum number of output tokens at 512.

4.1 Main Results

Open-Source Video-LLMs. We first identify and evaluate representative open-source Video-LLMs using MMBench-Video. Adhering to their default settings, these Video-LLMs process a sequence of video frames, with the number of frames varying from eight to dozens. Interestingly, we observe that all Video-LLMs exhibit comparably subpar performance on MMBench-Video, despite notable performance disparities on other benchmarks. For instance, VideoChat2 surpasses Video-ChatGPT by 18% on the MSVD-QA score (3.9 vs. 3.3), yet the performance gap narrows to just 6% on the MMBench-Video score (0.99 vs. 0.93). All video LLMs attain an average score close to 1 (out of a total of 3), with the top-performing model VideoStreaming [43] reaching a mere 1.12. These findings suggest that the current state of video models' proficiency in understanding MMBench-Video is nascent, underscoring the challenges and emphasizing the necessity for advancements in video LLMs to enhance their capability and effectiveness in interpreting varied video content.

Open-Source LVLMs for Images. A significant number of LVLMs [17, 34, 5, 55, 27, 12, 41, 50] have been developed to comprehend image content and execute visual reasoning tasks. During our evaluation, we focused on LVLMs that support the multi-image inference interface. We assess four prominent open-source LVLMs: Idefics2-8B [27], Qwen-VL-Chat [5], mPLUG-Owl2 [56], and InternVL-Chat-v1.5 [12], using MMBench-Video. To ascertain the models' ability to effectively leverage multiple input frames, we evaluated them under two distinct settings: 1-frame and 8-frame inputs. Results in Tab. 3 indicate that all models, except Qwen-VL-Chat, exhibit a substantial enhancement in performance when utilizing 8 frames compared to a single frame. Notably, InternVL-Chat-v1.5 emerges as the top performer, achieving an impressive average score of 1.26 with 8 frames as inputs, significantly surpassing all other evaluated video LLMs.

Proprietary LVLMs for Images. Unlike their open-source counterparts, most proprietary LVLMs accept arbitrary interleaved images and text as input. However, the context window size still limits the

Madal	Overall		Perception						Rea	soning		
Widdel	Mean	СР	FP-S	FP-C	HL	Mean	LR	AR	RR	CSR	TR	Mean
			Open-S	ource Vid	deo-LLN	1s						
Video-ChatGPT-[100f] [36]	0.93	0.91	0.94	0.81	0.39	0.90	0.70	1.15	1.12	0.84	0.94	0.97
Video-LLaVA-[8f] [32]	1.05	1.14	1.08	0.88	0.50	1.04	0.72	1.23	1.03	0.89	0.97	0.99
Chat-UniVi-[64f] [25]	0.99	1.07	1.00	0.93	0.39	0.98	0.59	1.18	1.14	0.75	0.98	0.97
VideoChat2-[16f] [31]	0.99	1.18	0.94	0.98	0.66	0.98	0.42	1.13	1.24	0.86	0.94	0.95
PLLaVA-7B-[16f] [54]	1.03	1.08	1.06	0.86	0.52	1.02	0.64	1.25	1.17	0.98	1.01	1.03
ShareGPT4Video-8B-[16f*] [11]	1.05	1.20	1.05	1.00	0.32	1.04	0.89	1.06	1.19	1.01	0.99	1.03
VideoStreaming-[64f+] [43]	1.12	1.38	1.13	0.8	0.32	1.13	0.77	1.27	1.11	1.01	1.10	1.09
Open-Source LVLMs for Images												
Idefics2-8B-[1f] [27]	0.95	1.06	0.85	0.81	1.35	0.90	0.73	1.14	1.08	1.09	1.04	1.03
Idefics2-8B-[8f]	1.10	1.23	1.07	0.89	0.77	1.06	0.77	1.27	1.41	1.11	1.14	1.16
Qwen-VL-Chat-[1f] [5]	0.60	0.72	0.59	0.53	1.16	0.63	0.58	0.60	0.54	0.53	0.47	0.53
Qwen-VL-Chat-[8f]	0.52	0.44	0.62	0.33	0.15	0.53	0.45	0.59	0.50	0.36	0.37	0.45
mPLUG-Owl2-[1f] [56]	0.85	1.05	0.79	0.79	0.68	0.83	0.54	1.06	1.05	0.74	0.83	0.86
mPLUG-Owl2-[8f]	1.15	1.34	1.18	0.99	0.27	1.15	0.63	1.33	1.30	1.03	1.11	1.11
InternVL-Chat-v1.5-[1f] [12]	0.84	0.98	0.72	0.78	1.44	0.80	0.57	1.02	1.12	0.83	0.88	0.90
InternVL-Chat-v1.5-[8f]	1.26	1.51	1.22	1.01	1.21	1.25	0.88	1.40	1.48	1.28	1.09	1.22
	,	P	Proprieta	ry LVLM.	s for Im	ages						
Claude-3v-Opus-[4f] [4]	1.19	1.37	1.11	1.00	1.56	1.16	1.12	1.35	1.36	1.17	1.05	1.20
Gemini-Pro-v1.0-[8f] [47]	1.49	1.72	1.50	1.28	0.79	1.49	1.02	1.66	1.58	1.59	1.40	1.45
Gemini-Pro-v1.0-[16f]	1.48	1.61	1.56	1.30	0.65	1.50	1.15	1.57	1.55	1.36	1.33	1.39
Gemini-Pro-v1.5-[8f] [47]	1.30	1.51	1.30	0.98	2.03	1.32	1.06	1.62	1.36	1.25	0.94	1.22
Gemini-Pro-v1.5-[16f]	1.60	1.81	1.59	1.60	2.00	1.61	1.58	1.77	1.69	1.80	1.24	1.55
GPT-4v-[8f] [39]	1.53	1.68	1.45	1.43	1.79	1.51	1.14	1.81	1.70	1.59	1.39	1.52
GPT-4v-[16f]	1.68	1.83	1.65	1.40	1.76	1.66	1.45	1.91	1.86	1.83	1.53	1.69
GPT-4o-[1f] [40]	0.70	0.99	0.61	0.53	2.19	0.73	0.47	0.82	0.63	0.69	0.44	0.59
GPT-4o-[8f]	1.62	1.82	1.59	1.43	1.95	1.63	1.33	1.89	1.60	1.60	1.44	1.57
GPT-4o-[16f]	1.86	2.03	1.88	1.67	2.13	1.89	1.78	1.95	1.78	1.90	1.68	1.80

Table 3: **Evaluation Result of Video Models on MMBench-Video.** CP, FP[S], FP[C], HL stands for four L-2 perception capabilities: Coarse Perception, Single-Instance Finegrained Perception, Cross-Instance Finegrained Perception, and Hallucination. LR, AR, RR, CSR, TR stand for five reasoning capabilities: Logic, Attribute, Relation, Commonsense, and Temporal Reasoning. All scores are based on a 3-grade marking scheme: 0 for worst, 3 for best. -[*N*f] indicates the method take *N* frames uniformly sampled from a video as input. Among *Open-Source Video-LLMs*, ShareGPT4Video-8B-[16f*] follows the IG-VLM [26] strategy and presents 16 frames in a 4×4 grid. VideoStreaming-[64f+] accepts streaming videos and takes at least 64 frames as inputs.

maximum number of images. We evaluate several proprietary LVLMs, including Claude-3v, Gemini-Pro-v[1.0/1.5], GPT-4v, and GPT-4o on MMBench-Video with varying numbers of frames. Claude-3v struggles with 8-frame inputs and is only evaluated under the 4-frame setting. As anticipated, it exhibits the poorest performance among proprietary LVLMs when handling multiple frames. In contrast, other proprietary models demonstrate notably superior performance compared to the stateof-the-art open-source InternVL-Chat. Particularly impressive is GPT-4o, which, when processing 16 frames, achieves an outstanding overall score of **1.86**. This result positioned GPT-4o 66% ahead of the best open-source video LLM and 48% ahead of the best open-source image LVLM.

4.2 Performance of Video-LLMs on Image VQA Benchmarks

Intuitively, a Video-LLM is expected to not only possess all capabilities of an image-based LVLM but also exhibit video-specific competencies, such as future prediction or causal reasoning. In light of the underwhelming performance of Video-LLMs on MMBench-Video, we broaden our evaluation to include image VQA benchmarks to determine if these models have the necessary skills for comprehending static content. We evaluate five Video-LLMs on two extensive image VQA benchmarks: MMBench [35] and MMStar [12]. To accommodate the input format of Video-LLMs, we create pseudo video clips by duplicating static frames, which then serves as the input for the evaluation. In Tab. 4, we list the performance of Video-LLMs alongside several representative image LVLMs for comparative analysis. On both benchmarks, existing Video-LLMs exhibit subpar performance. Notably, top-performing Video-LLMs such as PLLaVA and Video-LLaVA show

Model				MMBen	ch			MMStar						
Model	FP-S	FP-C	СР	LR	AR	RR	Overall	СР	FP	IR	LR	Math	ST	Overall
Open-Source Video-LLMs														
Video-ChatGPT	41.87	27.37	32.87	13.71	53.05	30.46	34.50	40.80	24.80	36.00	26.00	28.00	22.40	29.67
Video-LLaVA	57.44	42.46	62.98	14.52	68.90	43.10	52.32	55.20	20.40	37.60	25.20	25.60	24.00	31.33
Chat-UniVi	47.75	35.75	57.18	9.68	62.19	33.91	45.04	50.00	30.80	42.80	30.40	30.00	24.40	34.73
VideoChat2	42.91	30.72	54.14	7.26	54.88	32.18	41.02	47.60	22.80	32.80	27.20	26.40	13.20	28.33
PLLaVA-7B	59.17	40.78	60.50	17.74	58.54	58.05	52.79	53.60	34.40	40.80	32.40	30.00	17.20	34.73
					Open	-Source L	VLMs for Im	ages						
MiniCPM-V-2	78.89	50.84	72.93	26.61	75.00	65.52	66.02	58.00	32.40	50.00	38.40	32.80	22.80	39.07
LLaVA-v1.5-7B	69.90	56.98	70.17	25.81	67.07	53.45	61.38	57.20	24.40	41.60	28.40	26.40	20.40	33.07
InternVL-Chat-v1.5	88.58	73.18	80.94	58.06	85.98	80.46	79.95	70.40	52.80	65.20	58.40	56.00	39.60	57.07
Idefics2-8B	81.31	65.36	73.20	41.94	80.49	76.44	72.29	66.00	42.40	61.60	49.60	40.00	37.20	49.47
Phi-3-Vision	78.89	61.45	76.80	47.58	79.27	74.14	72.29	60.00	38.80	59.20	45.20	42.40	40.80	47.73

Table 4: **Comparison of Image Models and Video Models on MMBench and MMStar.** We follow the official practice to perform evaluation on these two benchmarks. For MMBench, we report the results on MMBench-DEV-EN-v1.1. We adopt the abbreviations for capabilities that are defined in the original papers.

Model	Subtitle	Overall	Perception						Reasoning						
model	Subtitie	Mean	СР	FP-S	FP-C	HL	Mean	LR	AR	RR	CSR	TR	Mean		
GPT-40-[8f]	×	1.66	1.90	1.63	1.52	1.88	1.68	1.61	1.87	1.50	1.52	1.65	1.63		
	~	1.94	1.98	1.92	1.71	1.72	1.90	2.05	2.07	1.97	2.00	1.99	2.01		
GPT-4o-[16f]	×	1.90	2.13	1.86	1.56	2.20	1.90	2.26	2.04	1.47	2.00	1.85	1.91		
	~	2.05	2.14	2.07	1.79	1.64	2.04	2.31	2.22	1.78	2.33	2.05	2.12		

Table 5: **GPT-4o's performance can be further improved by incorporating YouTube generated subtitles.** We report the performance on a subset of MMBench-Video, for which the auto generated subtitles are available.

performance that is either on par with or inferior to LLaVA-v1.5-7B, a rudimentary baseline for image multimodal understanding, and significantly trail behind the state-of-the-art image LVLM, InternVL-v1.5. This evaluation underscores the current limitations in the spatial understanding capabilities of Video-LLMs.

4.3 Incorporating Speech Further Improves Proprietary LVLMs

Video inherently comprises both visual and audio signals. However, the majority of existing LVLMs for video understanding predominantly focus on visual features, often neglecting the valuable information embedded in audio signals. To explore the potential impact of integrating audio features on video understanding, we conducted experiments using video title tracks (VTT) sourced from YouTube, which are automatically generated through speech recognition techniques. We incorporate these subtitles into the prompt as supplementary context. Experimental results in Tab. 5 reveal that the inclusion of audio/speech information enhances the performance of the state-of-the-art proprietary model, GPT-40. The subtitles offer a rich source of high-density information, facilitating the LLM's ability to accurately address the questions, thereby leading to a comprehensive performance improvement. Nonetheless, the increased information richness also heightens the risk of hallucinations, where the model may produce responses about non-existent content. The effectiveness hinges on the information density and the level of redundancy, necessitating a careful balance in applications.

4.4 The Superior Performance of GPT-4 as a Judge

Due to the discrepancy between the predictions of Video-LLM and the ground truth answers, existing VideoQA benchmarks largely rely on a judge model to assess the model responses. The capability of judge models can significantly influence the final results. To quantitatively study the impact of judge models, we utilize different versions of GPT-3.5 and GPT-4 for evaluation and report the results in Tab. 6 and Fig. 6. We observe that GPT-3.5 tends to assign high scores (typically 2 and 3), potentially leading to inaccuracies. To investigate the alignment with human preferences across different judge models, we conduct study based on a randomly selected subset of 100 questions. Two of the authors manually rate the responses from Video-LLaVA and GPT-40, and we then report the mean absolute error between different judge models and the averaged human ratings. Tab. 7 shows that GPT-3.5 exhibits a significantly larger discrepancy with human preferences and greater inter-version variance.



Figure 6: Rating distribution of different judge models. We report the results of Video-LLaVA and GPT-40 respectively judged by GPT-3.5-Turbo (1106) and GPT-4-Turbo (1106).

Judge Model		Video-LLaVA	GPT-40	Judge Model		Video-LLaVA	GPT-40
CPT 3 5 Turbo	1106	2.09	2.45	CPT 3.5 Turb	1106	0.98	0.815
Gr 1-3.3-10100	0613	1.80	2.11	GI 1-5.5-10100	0613	0.89	0.685
GPT-4-Turbo	1106	1.05	1.62	CPT-4-Turbo	1106	0.36	0.295
	0125	0.90	1.61	01 1-4-10100	0125	0.36	0.255

GPT judges on MMBench-Video. The overall mean scores are reported.

Table 6: Evaluation results obtained with different Table 7: The mean absolute error (MAE) of different GPT Judges with human preferences on a randomly selected subset.

5 Conclusion

This work introduces MMBench-Video, a novel long-form, multi-shot VideoQA benchmark specifically designed to evaluate the capabilities of LVLMs in understanding video content. MMBench-Video encompasses a diverse range of video topics and fine-grained capabilities. Extensive evaluations on MMBench-Video allow us to identify significant performance limitations among existing Video-LLMs in both spatial and temporal understanding.

Additional Experiments A

The Impact of Incorporating Speech over the entire MMBench-Video A.1

In the main paper, we report the quantitative results of speech improvement on the subset of videos with subtitles available from YouTube. In MMBench-Video, approximately half of videos do not include parseable video title tracks. In Tab. 8, we report the impact of incorporating speech information across the entire MMBench-Video dataset. While only half of the VideoQAs are enhanced with speech, the overall performance improvement on the full benchmark remains significant. It is evident that the enhancement in reasoning capabilities surpasses that of perceptual abilities. Speech typically conveys contextual information absent in static visual inputs, facilitating further reasoning by the VLM. Meanwhile, improvements in coarse perception are minimal or remain largely unchanged (for GPT-4o-[16f]). This can be attributable to the fact that perception is predominantly reliant on visual inputs, and speech information does not significantly augment the model's performance in coarse perception.

Model	Subtitle	Overall Mean	Perception						Reasoning						
	Subline		СР	FP-S	FP-C	HL	Mean	LR	AR	RR	CSR	TR	Mean		
GPT-40-[8f]	×	1.62	1.82	1.59	1.43	1.95	1.63	1.33	1.89	1.60	1.60	1.44	1.57		
	~	1.79	1.90	1.82	1.51	1.82	1.79	1.57	1.98	1.81	1.81	1.71	1.78		
GPT-40-[16f]	×	1.86	2.03	1.88	1.67	2.13	1.89	1.78	1.95	1.78	1.90	1.68	1.80		
	~	1.96	2.03	2.00	1.77	1.89	1.97	1.87	1.98	1.92	1.99	1.84	1.90		

Table 8: GPT-40's performance can be further improved by incorporating YouTube generated subtitles even under whole dataset.

A.2 **Detailed Analysis of L-2 Capability**

Based on Tab. 3, it is evident that hallucination is the most significant limitation in L-2 perceptual capabilities for all Video-LLMs, in contrast to the state-of-the-art proprietary LVLMs. This indicates



Figure 7: **Comparison of question type distribution with MSVD and MSRVTT.** MMBench-Video encompasses a more extensive assortment of question types and exhibits a distribution that is more equitably balanced among these various categories.

that existing Video-LLMs are unable to dismiss questions pertaining to videos when uncertain and are inclined to generate answers for questions regarding non-existent visual content.

Regarding LVLMs, the number of frames significantly influences the performance of most L-2 capabilities in MMBench-Video. With an increase in the number of frames, the enhancement in perceptual capabilities becomes more pronounced than that in reasoning capabilities. Owing to a more extensive training corpus and superior safety mechanisms, proprietary LVLMs exhibit superior performance in challenging capabilities such as logical reasoning, commonsense reasoning, and hallucination.

Interestingly, despite Idefics2-8B-[1f] utilizing a single image as input, it still outperforms all Video-LLMs in temporal reasoning tasks. This suggests that Video-LLMs are not effectively leveraging diverse temporal information, underscoring the necessity to enhance the diversity of instruction tuning data for these models.

B Additional Dataset Analysis

In this section, we present more details about the MMBench-Video dataset: including the technique we adopted to filter temporal dispensable questions and some statistics on the linguistic characteristics of questions in MMBench-Video. In Figs. 8 to 10, we display a selection of samples from MMBench-Video, showcasing videos, images, questions, and reference answers for illustrative purposes.

B.1 Temporal Dispensable Data Filtering with LVLM

To ensure that the majority of questions in MMBench-Video are temporally indispensable, we implement an LVLM-based filtering process and subsequently conduct manual verification. Specifically, we employ GPT-4v, one of the most potent LVLMs, to filter out questions exhibiting high temporal irrelevance. Utilizing four distinct random seeds, we sample a single random frame as visual input for each individual VideoQA instance and conduct the inference four times. Subsequently, we utilize GPT-4 to evaluate the responses and compute the average score for each question. Questions with an average score of 2.5 or higher across the four responses were excluded from the benchmark. Based on this approach, we removed a total of 246 temporally dispensable questions from the dataset.

B.2 Question Type Analysis

Given that the majority of existing Video-QA benchmarks are characterized by a limited range of question types, which fail to adequately represent the diverse spectrum of human conversations, the question set within MMBench-Video has been meticulously curated to encompass a wide variety of categories. We visualize the comparison of the question type distribution between MMBench-Video and other popular benchmarks in Fig. 7. In addition to the conventional question archetypes, namely

'*what*', '*who*', '*how*', '*when*', *and* '*where*', MMBench-Video extends its corpus to include additional interrogatives such as '*why*', '*which*', '*is / are*', *and* '*does / do*'. The expansion diversifies the dataset and closely aligns with the style of natural human dialogues. Meanwhile, the question type distribution within MSVD or MSRVTT exhibits a significant skew. The category of 'what' predominates, comprising over 60% of the questions, in stark contrast to the significantly underrepresented categories such as 'when' and 'where', totaling a mere 1%. Nevertheless, the question type distribution within MMBench-Video has been deliberately engineered to achieve a greater equilibrium. While the 'what' category maintains its status as the most prevalent, the remaining question types are evenly distributed across various interrogative forms.

C Prompts Adopted in MMBench-Video

In Sec. 3.1, we outline the LLM-involved evaluation paradigm we employ, utilizing GPT-4 for scoring. The evaluation is conducted through prompts configured with a 3-grade marking (0, 1, 2, 3). In this section, we elaborate on the specific prompts utilized in the evaluation process.

C.1 System Prompt for GPT-based Evaluation

As an AI assistant, your task is to evaluate a candidate answer in comparison to a given correct answer. The question itself, the correct 'groundtruth' answer, and the candidate answer will be provided to you. Your assessment should range from 0 to 3, based solely on the semantic similarity between the groundtruth and the candidate answer, disregarding any grammatical differences. A rating of 0 suggests no similarity, implying the candidate answer is entirely incorrect. A rating of 1 suggests low similarity, meaning the candidate answer is largely incorrect. A rating of 2 suggests high similarity, meaning the candidate answer is largely correct. Lastly, a rating of 3 indicates complete similarity, which means the candidate answer is entirely correct. Your response should be a single integer from 0, 1, 2, or 3. Question: [QUESTION] Groundtruth answer: [ANNOTATED ANSWER] Candidate answer: [CANDIDATE ANSWER] Your response:

C.2 System Prompt for the Inference of LVLMs with Multi-Frame Inputs

```
You will be provided with [FRAME NUM] separate frames uniformly sampled from a
video, the frames are provided in chronological order of the video.
Please analyze these images and provide the answer / answers to the following
question / questions about the video content.
If multiple questions are provided (with indices I1, I2, I3, ...), you should
organize your answers in the following json format:
{
    'I1': 'Answer to Question I1',
    'I2': 'Answer to Question I2',
    . . .
}
Otherwise, please directly reply with your response to the only question.
Even if the information in these separate frames is not enough to give an answer,
PLEASE TRY YOUR BEST TO GUESS A CLEAR OR VAGUE ANSWER WHICH YOU THINK WOULD BE THE
MOST POSSIBLE ONE BASED ON THE QUESTION.
Minimize negative responses such as 'not possible to determine'. STIMULATE YOUR
POTENTIAL AND IMAGINATION!
```







Figure 8: Visualization of Samples in MMBench-Video. Part 1 out of 3.



Figure 9: Visualization of Samples in MMBench-Video. Part 2 out of 3.





Figure 10: Visualization of Samples in MMBench-Video. Part 3 out of 3.

C.3 Input Prompt Template for the Inference of LVLMs with Multi-Frame Inputs

D Limitations and Broader Impacts

Limitations. In this study, we introduce MMBench-Video, a novel long-form multi-shot VideoQA benchmark, and perform a comprehensive evaluation based on this benchmark. In light of budget constraints, our evaluation is focused on a curated selection of representative open-source and proprietary VLMs, which may not encompass all those most recent high-performing models. GPT-4 is adopted as a more advanced judge model for scoring the responses, while further experiments should be conducted in the future to study the feasibility of using state-of-the-art open-source LLMs as the judge. Taking into account the limited capabilities of existing Video-LLMs, we currently set the upper duration limit of videos to 6 minutes, refraining from scaling to tens of minutes or hours. The evaluation results indicate that, even with relatively modest video durations, MMBench-Video presents a significant challenge to existing Video-LLMs.

Broader Impacts. As an evaluation benchmark, MMBench-Video offers detailed insights into the fine-grained capabilities of diverse vision-language models (VLMs) in the domain of video understanding, providing valuable insights for future model optimization. The new benchmark exhibits enhanced quality and enriched diversity, and employs a more precise scoring strategy, which collectively contribute to comprehensive and reliable evaluation outcomes. Leveraging MMBench-Video and other Image VQA benchmarks, we conduct a comprehensive evaluation of existing video-LLMs, revealing their limited capabilities in both spatial and temporal understanding. Additionally, MMBench-Video, being a small-scale benchmark, may not encompass every video topic and fine-grained capability. There is a risk that MMBench-Video may not adequately reflect the video understanding capabilities of VLMs in specific tasks or scenarios. We encourage users to carefully consider the intended use cases of VLMs when utilizing MMBench-Video for evaluation.

References

- [1] 01-ai. Yi-vl. https://huggingface.co/01-ai/Yi-VL-34B, 2023.
- [2] Sami Abu-El-Haija, Nisarg Kothari, Joonseok Lee, Paul Natsev, George Toderici, Balakrishnan Varadarajan, and Sudheendra Vijayanarasimhan. Youtube-8m: A large-scale video classification benchmark, 2016.
- [3] Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. Advances in Neural Information Processing Systems, 35:23716–23736, 2022.
- [4] Anthropic. Introducing the next generation of claude. https://www.anthropic.com/news/claude-3-family, 2024.
- [5] Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen-vl: A frontier large vision-language model with versatile abilities. arXiv preprint arXiv:2308.12966, 2023.
- [6] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. Advances in neural information processing systems, 33:1877–1901, 2020.

- [7] Fabian Caba Heilbron, Victor Escorcia, Bernard Ghanem, and Juan Carlos Niebles. Activitynet: A large-scale video benchmark for human activity understanding. In *Proceedings of the ieee conference on computer vision and pattern recognition*, pages 961–970, 2015.
- [8] Brandon Castellano. Pyscenedetect. Last accessed, 2020.
- [9] David Chen and William B Dolan. Collecting highly parallel data for paraphrase evaluation. In *Proceedings* of the 49th annual meeting of the association for computational linguistics: human language technologies, pages 190–200, 2011.
- [10] Lin Chen, Jisong Li, Xiaoyi Dong, Pan Zhang, Conghui He, Jiaqi Wang, Feng Zhao, and Dahua Lin. Sharegpt4v: Improving large multi-modal models with better captions. arXiv preprint arXiv:2311.12793, 2023.
- [11] Lin Chen, Xilin Wei, Jinsong Li, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Zehui Chen, Haodong Duan, Bin Lin, Zhenyu Tang, et al. Sharegpt4video: Improving video understanding and generation with better captions. arXiv preprint arXiv:2406.04325, 2024.
- [12] Zhe Chen, Weiyun Wang, Hao Tian, Shenglong Ye, Zhangwei Gao, Erfei Cui, Wenwen Tong, Kongzhi Hu, Jiapeng Luo, Zheng Ma, et al. How far are we to gpt-4v? closing the gap to commercial multimodal models with open-source suites. *arXiv preprint arXiv:2404.16821*, 2024.
- [13] Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E Gonzalez, et al. Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality. See https://vicuna.lmsys. org (accessed 14 April 2023), 2023.
- [14] OpenCompass Contributors. Opencompass: A universal evaluation platform for foundation models. https://github.com/open-compass/opencompass, 2023.
- [15] XTuner Contributors. Xtuner: A toolkit for efficiently fine-tuning llm. https://github.com/InternLM/ xtuner, 2023.
- [16] Wenliang Dai, Junnan Li, Dongxu Li, Anthony Meng Huat Tiong, Junqi Zhao, Weisheng Wang, Boyang Li, Pascale Fung, and Steven Hoi. Instructblip: Towards general-purpose vision-language models with instruction tuning. arXiv preprint arXiv:2305.06500, 2023.
- [17] Xiaoyi Dong, Pan Zhang, Yuhang Zang, Yuhang Cao, Bin Wang, Linke Ouyang, Xilin Wei, Songyang Zhang, Haodong Duan, Maosong Cao, Wenwei Zhang, Yining Li, Hang Yan, Yang Gao, Xinyue Zhang, Wei Li, Jingwen Li, Kai Chen, Conghui He, Xingcheng Zhang, Yu Qiao, Dahua Lin, and Jiaqi Wang. Internlm-xcomposer2: Mastering free-form text-image composition and comprehension in vision-language large model. arXiv preprint arXiv:2401.16420, 2024.
- [18] Haodong Duan, Yue Zhao, Yuanjun Xiong, Wentao Liu, and Dahua Lin. Omni-sourced webly-supervised learning for video recognition. In *European conference on computer vision*, pages 670–688. Springer, 2020.
- [19] Christoph Feichtenhofer, Haoqi Fan, Jitendra Malik, and Kaiming He. Slowfast networks for video recognition. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 6202– 6211, 2019.
- [20] Difei Gao, Ruiping Wang, Ziyi Bai, and Xilin Chen. Env-qa: A video question answering benchmark for comprehensive understanding of dynamic environments. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 1675–1685, 2021.
- [21] Noa Garcia, Mayu Otani, Chenhui Chu, and Yuta Nakashima. Knowit vqa: Answering knowledge-based questions about videos. In *Proceedings of the Thirty-Fourth AAAI Conference on Artificial Intelligence*, 2020.
- [22] Rohit Girdhar, Alaaeldin El-Nouby, Zhuang Liu, Mannat Singh, Kalyan Vasudev Alwala, Armand Joulin, and Ishan Misra. Imagebind: One embedding space to bind them all. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15180–15190, 2023.
- [23] Madeleine Grunde-McLaughlin, Ranjay Krishna, and Maneesh Agrawala. Agqa: A benchmark for compositional spatio-temporal reasoning, 2021.
- [24] Yunseok Jang, Yale Song, Youngjae Yu, Youngjin Kim, and Gunhee Kim. Tgif-qa: Toward spatio-temporal reasoning in visual question answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2758–2766, 2017.

- [25] Peng Jin, Ryuichi Takanobu, Caiwan Zhang, Xiaochun Cao, and Li Yuan. Chat-univi: Unified visual representation empowers large language models with image and video understanding. arXiv preprint arXiv:2311.08046, 2023.
- [26] Wonkyun Kim, Changin Choi, Wonseok Lee, and Wonjong Rhee. An image grid can be worth a video: Zero-shot video question answering using a vlm. arXiv preprint arXiv:2403.18406, 2024.
- [27] Hugo Laurençon, Lucile Saulnier, Léo Tronchon, Stas Bekman, Amanpreet Singh, Anton Lozhkov, Thomas Wang, Siddharth Karamcheti, Alexander M. Rush, Douwe Kiela, Matthieu Cord, and Victor Sanh. Obelics: An open web-scale filtered dataset of interleaved image-text documents, 2023.
- [28] Jie Lei, Licheng Yu, Mohit Bansal, and Tamara L Berg. Tvqa: Localized, compositional video question answering. In *EMNLP*, 2018.
- [29] Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. arXiv preprint arXiv:2301.12597, 2023.
- [30] KunChang Li, Yinan He, Yi Wang, Yizhuo Li, Wenhai Wang, Ping Luo, Yali Wang, Limin Wang, and Yu Qiao. Videochat: Chat-centric video understanding. arXiv preprint arXiv:2305.06355, 2023.
- [31] Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu, Guo Chen, Ping Luo, et al. Mvbench: A comprehensive multi-modal video understanding benchmark. arXiv preprint arXiv:2311.17005, 2023.
- [32] Bin Lin, Bin Zhu, Yang Ye, Munan Ning, Peng Jin, and Li Yuan. Video-Ilava: Learning united visual representation by alignment before projection. arXiv preprint arXiv:2311.10122, 2023.
- [33] Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. arXiv preprint arXiv:2310.03744, 2023.
- [34] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *arXiv preprint arXiv:2304.08485*, 2023.
- [35] Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, Kai Chen, and Dahua Lin. Mmbench: Is your multi-modal model an all-around player?, 2023.
- [36] Salman Khan Muhammad Maaz, Hanoona Rasheed and Fahad Khan. Video-chatgpt: Towards detailed video understanding via large vision and language models. *ArXiv* 2306.05424, 2023.
- [37] Jonghwan Mun, Paul Hongsuck Seo, Ilchae Jung, and Bohyung Han. Marioqa: Answering questions by watching gameplay videos. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 2867–2875, 2017.
- [38] OpenAI. Chatgpt. https://openai.com/blog/chatgpt, 2023.
- [39] OpenAI. Gpt-4 technical report, 2023.
- [40] OpenAI. Hello gpt-40. https://openai.com/index/hello-gpt-40, 2024.
- [41] OpenBMB. Minicpm: Unveiling the potential of end-side large language models, 2024.
- [42] Aitor Ormazabal, Che Zheng, Cyprien de Masson d'Autume, Dani Yogatama, Deyu Fu, Donovan Ong, Eric Chen, Eugenie Lamprecht, Hai Pham, Isaac Ong, et al. Reka core, flash, and edge: A series of powerful multimodal language models. arXiv preprint arXiv:2404.12387, 2024.
- [43] Rui Qian, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Shuangrui Ding, Dahua Lin, and Jiaqi Wang. Streaming long video understanding with large language models. arXiv preprint arXiv:2405.16009, 2024.
- [44] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.
- [45] Enxin Song, Wenhao Chai, Guanhong Wang, Yucheng Zhang, Haoyang Zhou, Feiyang Wu, Xun Guo, Tian Ye, Yan Lu, Jenq-Neng Hwang, and Gaoang Wang. Moviechat: From dense token to sparse memory for long video understanding, 2023.
- [46] Makarand Tapaswi, Yukun Zhu, Rainer Stiefelhagen, Antonio Torralba, Raquel Urtasun, and Sanja Fidler. Movieqa: Understanding stories in movies through question-answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4631–4640, 2016.

- [47] Gemini Team, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, et al. Gemini: a family of highly capable multimodal models. arXiv preprint arXiv:2312.11805, 2023.
- [48] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. arXiv preprint arXiv:2302.13971, 2023.
- [49] Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models, 2023.
- [50] Weihan Wang, Qingsong Lv, Wenmeng Yu, Wenyi Hong, Ji Qi, Yan Wang, Junhui Ji, Zhuoyi Yang, Lei Zhao, Xixuan Song, Jiazheng Xu, Bin Xu, Juanzi Li, Yuxiao Dong, Ming Ding, and Jie Tang. Cogvlm: Visual expert for pretrained language models. *ArXiv*, abs/2311.03079, 2023.
- [51] Yi Wang, Kunchang Li, Yizhuo Li, Yinan He, Bingkun Huang, Zhiyu Zhao, Hongjie Zhang, Jilan Xu, Yi Liu, Zun Wang, et al. Internvideo: General video foundation models via generative and discriminative learning. arXiv preprint arXiv:2212.03191, 2022.
- [52] Dejing Xu, Zhou Zhao, Jun Xiao, Fei Wu, Hanwang Zhang, Xiangnan He, and Yueting Zhuang. Video question answering via gradually refined attention over appearance and motion. In *Proceedings of the 25th* ACM international conference on Multimedia, pages 1645–1653, 2017.
- [53] Jun Xu, Tao Mei, Ting Yao, and Yong Rui. Msr-vtt: A large video description dataset for bridging video and language. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 5288–5296, 2016.
- [54] Lin Xu, Yilin Zhao, Daquan Zhou, Zhijie Lin, See Kiong Ng, and Jiashi Feng. Pllava: Parameter-free llava extension from images to videos for video dense captioning. arXiv preprint arXiv:2404.16994, 2024.
- [55] Qinghao Ye, Haiyang Xu, Guohai Xu, Jiabo Ye, Ming Yan, Yiyang Zhou, Junyang Wang, Anwen Hu, Pengcheng Shi, Yaya Shi, Chenliang Li, Yuanhong Xu, Hehong Chen, Junfeng Tian, Qian Qi, Ji Zhang, and Fei Huang. mplug-owl: Modularization empowers large language models with multimodality, 2023.
- [56] Qinghao Ye, Haiyang Xu, Jiabo Ye, Mingshi Yan, Anwen Hu, Haowei Liu, Qi Qian, Ji Zhang, Fei Huang, and Jingren Zhou. mplug-owl2: Revolutionizing multi-modal large language model with modality collaboration. *ArXiv*, abs/2311.04257, 2023.
- [57] Kexin Yi, Chuang Gan, Yunzhu Li, Pushmeet Kohli, Jiajun Wu, Antonio Torralba, and Joshua B. Tenenbaum. Clevrer: Collision events for video representation and reasoning, 2020.
- [58] Zhou Yu, Dejing Xu, Jun Yu, Ting Yu, Zhou Zhao, Yueting Zhuang, and Dacheng Tao. Activitynet-qa: A dataset for understanding complex web videos via question answering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 9127–9134, 2019.
- [59] Renrui Zhang, Jiaming Han, Aojun Zhou, Xiangfei Hu, Shilin Yan, Pan Lu, Hongsheng Li, Peng Gao, and Yu Qiao. Llama-adapter: Efficient fine-tuning of language models with zero-init attention. arXiv preprint arXiv:2303.16199, 2023.
- [60] Yue Zhao, Yuanjun Xiong, Limin Wang, Zhirong Wu, Xiaoou Tang, and Dahua Lin. Temporal action detection with structured segment networks. In *Proceedings of the IEEE international conference on computer vision*, pages 2914–2923, 2017.