Relation Extraction with Fine-Tuned Large Language Models in **Retrieval Augmented Generation Frameworks**

Sefika Efeoglu Freie Universitaet Berlin Berlin, Germany sefika.efeoglu@fu-berlin.de

ABSTRACT

Information Extraction (IE) is crucial for converting unstructured data into structured formats like Knowledge Graphs (KGs). A key task within IE is Relation Extraction (RE), which identifies relationships between entities in text. Various RE methods exist, including supervised, unsupervised, weakly supervised, and rule-based approaches. Recent studies leveraging pre-trained language models (PLMs) have shown significant success in this area. In the current era dominated by Large Language Models (LLMs), fine-tuning these models can overcome limitations associated with zero-shot LLM prompting-based RE methods, especially regarding domain adaptation challenges and identifying implicit relations between entities in sentences. These implicit relations, which cannot be easily extracted from a sentence's dependency tree, require logical inference for accurate identification. This work explores the performance of fine-tuned LLMs and their integration into the Retrieval Augmented-based (RAG) RE approach to address the challenges of identifying implicit relations at the sentence level, particularly when LLMs act as generators within the RAG framework. Empirical evaluations on the TACRED, TACRED-Revisited (TACREV), Re-TACRED, and SemEVAL datasets show significant performance improvements with fine-tuned LLMs, including Llama2-7B, Mistral-7B, and T5 (Large). Notably, our approach achieves substantial gains on SemEVAL, where implicit relations are common, surpassing previous results on this dataset. Additionally, our method outperforms previous works on TACRED, TACREV, and Re-TACRED, demonstrating exceptional performance across diverse evaluation scenarios.

KEYWORDS

Relation Extraction, Language Models, Fine-tuning, Information Extraction

ACM Reference Format:

Sefika Efeoglu and Adrian Paschke. 2024. Relation Extraction with Fine-Tuned Large Language Models in Retrieval Augmented Generation Frame-

© 2024 Copyright held by the owner/author(s). Publication rights licensed to ACM. ACM ISBN 978-x-xxxx-x/YY/MM

Adrian Paschke Freie Universitaet Berlin Berlin, Germany Data Analytic Center (DANA) Fraunhofer Institute FOKUS, Berlin, Germany

INTRODUCTION 1

Information Extraction (IE) is a significant process for representing unstructured data in a structured manner, such as Knowledge Graphs (KGs). One of the main tasks of the IE process is Relation Extraction (RE), which aims to identify (implicit or explicit) relations between entities in a given text data at either sentence or document level [11]. Implicit relations cannot be directly extracted from the sentence's tokens, as illustrated in Figure 1, whereas the explicit relations between entities can easily be identified by taking into account the dependency tree of the sentence, as demonstrated in Figure 2. Identification of implicit relations between entities requires semantic (or logical) inference, and Large Language Models (LLMs), while powerful in many respects, lack the capability for logical inference.



Figure 1: Illustration of an implicit relation, Entity-Origin(e1,e2), between head (e1) and tail (e2) entities in a sentence from the SemEVAL dataset.



Figure 2: Representation of an explicit relation, org:founded, between head and tail entities in a sentence from the TA-CRED dataset.

works. In . ACM, New York, NY, USA, 8 pages. https://doi.org/10.1145/nnnnnn.nnnnnnn identify the relations between entities in the sentence, various approaches, including rule-based, supervised, unsupervised, and weakly supervised RE approaches [3, 23], have been applied so far. Well-performing RE approaches using supervised learning require a large amount of labeled training data. However, they have not achieved better performance compared to pre-trained language model (PLM)-based RE approaches [19, 27, 31]. In the era of LLMs, various approaches using Retrieval-Augmented Generation (RAG) [10, 18], in-context learning [22], and simple vanilla prompting [16] might be applied to extract information from the text corpus without undergoing any model training process.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org. Conference'17, July 2017, Washington, DC, USA

RAG-based prompting approach achieves outstanding results when relations between entities can be easily extracted from sentence tokens [8]. However, the RAG approach fails when relation types are implicit, as illustrated in Figure 1. General-purpose LLMs, e.g., Mistral [15], Llama2 [26] and T5 [5] could not accomplish better performance on implicit relations in [8, 16, 28], since they lack logical inference capabilities and domain knowledge about relation types. Introducing the relation types into the language models might tackle the problems of the RAG4RE approach using generalpurpose LLMs [8]. Therefore, we propose fine-tuning of language models, namely domain adaptation, to address the problem of identifying implicit relations (see Figure 1) between entities at the sentence level.

To evaluate the performance of our approach, we conduct experiments with LLMs, including Llama2-7B [26], Mistral-7b [15] and T5 Large [5], on four different RE benchmark datasets: TA-CRED [30], TACRED-Revisited (TACREV) [2], Re-TACRED [25], and SemEVAL Task-8 [13]. In this work, fine-tuning addresses the performance problem of the zero-shot LLM prompting approach (e.g., RAG4RE [8]) in identifying implicit relations, namely semantic or logical relations, between entities in all the benchmark datasets mentioned above. Our approach's contributions are as follows:

- Fine-tuning mitigates the identification of implicit relation types in the sentence-level RE on SemEVAL.
- Fine-tuning yields substantial enhancements in the performance of language models such as Mistral-7B, T5 Large, and Llama2-7B on the aforementioned benchmark datasets.
- This work also compares the performance of fine-tuned LLMs to RAG4RE [8] using fine-tuned LLMs.
- RAG4RE using our fine-tuned LLMs achieved outstanding performance on TACRED, TACREV and Re-TACRED.

The rest of this paper first summarizes language model-based RE approaches in Section 2 and then introduces our proposed approach ¹ in Section 3. Afterwards, the experimental setup and results are presented and discussed in Section 4. Lastly, all concluding remarks and future works are summarized in Section 5.

2 RELATED WORKS

We categorize recent works into: (i) Relation Extraction and (ii) Fine-Tuning of Large Language Models in this section.

2.1 Relation Extraction

Relation Extraction (RE) is one of the main tasks of IE and plays a significant role among natural language processing tasks. RE aims to identify or classify the relations between head and tail entities in a given text. We mostly focus on sentence-level relation extraction approaches.

RE can be carried out with various types of approaches, including supervised techniques, unsupervised, distant supervision-based, weakly supervised and rule-based RE techniques [23]. Supervised techniques, needing large annotated datasets, are time-consuming and expensive [23]. Distant supervision, relying on existing knowledge bases, tackles the annotated data issue but suffers from wrongly labeled sentences and noise [3]. Weakly supervised RE is errorprone due to semantic drift in pattern sets per iteration [1]. Rulebased RE is limited by predefined rules in relation discovery [23].

With respect to best-performing RE approach, based on finetuning the language models, Cohen et al. [6] introduced a novel approach for relation classification that utilizes span prediction, rather than relying on a single embedding, to represent the relationships between entities. DeepStruct [27] innovates by improving language models' structural comprehension. With a pretrained model boasting 10 billion parameters, it smoothly transfers language models to structure prediction tasks. For RE, it provides structured output (head entity, relation, tail entity) from input text and entity pairs. Zhou et al. [31] focused on tackling two pivotal challenges that impact the effectiveness of current sentence-level RE models: (i) refining Entity Representation and (ii) mitigating the impact of noisy or ambiguously defined labels. Their method extends the pretraining objective of masked language modeling to encompass entities and integrates an advanced entity-aware selfattention mechanism, thus facilitating more precise and resilient RE outcomes. Li et al. [19] devised a label graph technique to assess candidate labels within the top-K prediction set and to discern the connections among them. In their methodology for predicting the correct label, they initially ascertain that the top-K prediction set of a given sample contains valuable insights.

Zhang et al.[16] developed multiple-choice question prompts based on test sentences, featuring entity verbalizations and relation types as choices. Despite falling short of previous rule and ML-based methods, enriching prompt context improved prediction results on datasets like TACRED and Re-TACRED. Melz[21] enhances the RAG approach with Auxiliary Rationale Memory for RE, learning from successes without hefty training costs. Meanwhile, Chen et al. [4] propose a Generative Context-Aware Prompttuning method, addressing prompt template engineering. Their prompt generator extracts context-aware tokens from entity pairs, evaluated on TACRED, TACREV, Re-TACRED, and SemEval datasets. RAG4RE[8] constructs an embedding database from training datasets, regenerates prompts, and inputs them into general-purpose LLMs, especially for RE, evaluated on TACRED, TACREV, Re-TACRED, and SemEVAL benchmark datasets.

2.2 Fine-Tuning of Large Language Models

Undoubtedly, Pretrained Language Models (PLMs) deliver outstanding results across various tasks, including text generation, translation, and question-answering. While zero-shot prompting of Large Language Models (LLMs) often yields impressive outcomes on many downstream tasks, fine-tuning is crucial for adapting LLMs to specific datasets and tasks [12]. Yang et al. [29] conducted single-task fine-tuning with various settings, demonstrating that this approach outperforms zero-shot LLM prompting. However, their results indicate that single-task fine-tuning is prone to catastrophic forgetting. In contrast, Feng et al. [9] proposed a multi-task fine-tuning method that incorporates a mixture of datasets and LoRAs. Their experiments clearly show that multi-task fine-tuning enhances performance over single-task fine-tuning, particularly with datasets from Finance, Medicine, and WebGPT. Additionally, Liu et al. [20]

¹Source code is available at https://github.com/sefeoglu/RAG4RE-extension

applied multi-task fine-tuning to generate code from text data using different code-generation language models, such as StarCode, CodeLLama, and CodeGeex2, demonstrating effectiveness across various coding tasks. In addition to these attempts about LLM finetuning, there are parameter efficient fine-tuning approaches, which are focusing on only target modules of LLMs and freezing its remaining modules, such as Low Rank Adaptation (LoRA) [14], LoRA for quantized language models (QLoRA) [7] and Direct Preference Optimization (DPO) [24]. LoRA fine-tunes models by adding trainable rank decomposition matrices to each transformer layer, reducing parameters and GPU memory needs [14]. This approach maintains or improves performance while keeping pre-trained weights frozen. QLORA [7] introduces innovations to reduce memory use without sacrificing performance, including 4-bit Normal Float for optimal quantization, Double Quantization saving about 0.37 bits per parameter, and Paged Optimizers to manage memory spikes. DPO is a novel algorithm for aligning language models with human preferences without the need for explicit reward modeling or reinforcement learning [24]. By increasing the relative log probability of preferred responses and incorporating dynamic importance weights, DPO effectively prevents model degeneration and simplifies the training process, making it a promising alternative to existing Reinforcement Learning from Human Feedback (RLHF) algorithms. RLHF [17] is a variant of reinforcement learning that learns from human input rather than an engineered reward function, enhancing the performance and alignment of intelligent systems with human values.

3 METHODOLOGY

In this work, we aim to address the issue of identifying implicit relations between entities in the sentence when using RAG with an LLM-based generation approach to identify these relations. We propose applying domain adaptation or transfer learning, specifically fine-tuning, to alleviate the weaknesses of general-purpose LLMs in identifying implicit relations between entities in the sentence. We first introduce our proposed LLM fine-tuning approach for Relation Extraction (RE) in Section 3.1, and then integrate the fine-tuned LLMs into the RAG4RE approach to evaluate whether the fine-tuned LLMs improve its results or not in Section 3.2.

3.1 Fine-tuning Language Models for Relation Extraction

We fine-tune both encoder-decoder, i.e., T5 and decoder only, e.g., Llama2-7B and Mistral-7B, LLMs on datasets by leveraging Supervised Fine-tuning Trainer ² (SFT), which is a crucial step in Reinforcement Learning from Human Feedback (RLHF), so that domain adaptation is applied to general-purpose LLMs. SFT requires labeled training data and is easy to integrate and train.

To leverage only specific parameters of the models for text-totext generation, Low Rank Adaptation for quantized language models (QLoRA) [7] method is also used to fine-tune LLMs on the datasets (see Figure 4). QLoRA not only reduces the parameters of LLMs but also reduces the memory allocation of LLMs on GPU. Therefore, it is necessary when limited GPU memory resources are available. The format of simple query prompts proposed in RAG4RE [8] is used to prepare the training prompt dataset (see Figure 3).

3.1.1 *Prompt Dataset Generation.* The prompt dataset is constructed following the template outlined in a prior work by [8]. This dataset is sourced from a single domain and task supervised dataset, utilizing a specific template depicted in Figure 3 for fine-tuning purposes.

Problem Definition: Relation extraction is to identify the relationship between two entities in a sentence. Question: What is the relation type between tail and head entities according to given relationships below in the following sentence? Query Sentence: {sentence} Head: {head} Tail: {tail } Relation types: {relation_list} output format: relation_type issure 3: A prompt template to create a prompt dataset for

Figure 3: A prompt template to create a prompt dataset for fine-tuning a language model.

3.1.2 Parameter Efficient Fine-Tuning. We leverage QLoRA, one of the parameter-efficient fine-tuning approaches. Firstly, quantization is applied to a pre-trained language model, reducing the high precision floating-point representation into low precision to reduce the memory footprint. This quantization is achieved using "4-bit NormalFloat (NF4)". 4-bit NormalFloat is an informationtheoretically optimal quantization data type, specifically designed for normally distributed data [7]. This innovative format surpasses the performance of traditional 4-bit Integers and 4-bit Floats, delivering superior empirical results in a variety of applications [7]. Afterwards, LoRA, focusing on targeted modules of the pre-trained language model, is added into the 4-bit quantized pre-trained language model. The fine-tuning process is carried out by using the Supervised Fine-Tuning Trainer (SFT). The model is fine-tuned on a single domain and task prompt dataset. Figure 4 illustrates how the pre-trained language model is fine-tuned along with QLoRA and SFT on a prompt dataset.

3.2 Retrieval-Augmented Generation alongside Fine-tuned Language Models

We integrate our fine-tuned LLM on RE prompt dataset into the RAG4RE approach [8] in order to figure out the problem in identification of implicit relation between entities in sentences. In our work, the LLM used in the RAG4RE approach's generation model [8] is exchanged with our fine-tuned LLMs as shown at Figure 5. All other modules in RAG4RE [8] remained same.

²SFT: https://huggingface.co/docs/trl/sft_trainer



Figure 4: Fine-tuning a pre-trained model on a prompt dataset alongside the QLoRA adapter and SFT.



4 EVALUATION

In this section, we present our evaluation process, conducted on four benchmark datasets, in conjunction with several language models. Firstly, we introduce the datasets, metrics, and settings for our approaches, including fine-tuning language models and Retrieval-Augmented Generation along with fine-tuned models separately, in Section 4.1. Subsequently, the results of experiments are presented and discussed alongside previous Relation Extraction (RE) approaches that achieved the highest performance on the datasets used in this work, in Sections 4.2 and 4.3.

4.1 Experimental Setup

Through this section, we initially introduce the datasets utilized for evaluation, followed by a detailed settings used on the finetuning and the RAG4RE framework [8] leveraging our fine-tuned language model within its generation module. All experiments in this work are conducted utilizing 48 GB of GPU memory.

4.1.1 Datasets. To examine the performance of our proposed approaches, we leverage four different RE benchmark datasets detailed in Table 1: TACRED [30], TACREV [2], Re-TACRED [25],

Sefika Efeoglu and Adrian Paschke

and SemEVAL [13]. The prompt datasets listed in Table 1 are generated from validation partition of the original dataset splits and different from the training sentences in TACRED and its variants. The training datasets in Table 1 are utilized in the Embedding DB of RAG4RE [8]. Test splits of all datasets in Table 1 are employed for evaluation. Unfortunately, SemEVAL does not provide an additional dataset split, such as validation or development data, for creating a prompt dataset. As a result, we have to construct the prompt dataset directly from the training split. Consequently, we are unable to evaluate RAG4RE using our fine-tuned language models on SemEVAL. We strictly separate the training and test splits of the datasets in our evaluation.

- TACRED (TAC Relation Extraction Dataset) [30] is a supervised RE dataset created through crowdsourcing, specifically aimed at TAC KBP (Text Analysis Conference Knowledge Base Population) relations. Notably, the dataset does not prescribe a direction for the predefined relations, allowing them to be extracted from the given sentence tokens. We utilized this licensed dataset directly from the Linguistic Data Consortium ⁴ (LDC).
- TACREV is a refined version of TACRED that minimizes noise in sentences labeled as 'no_relation'. We generated this dataset from the original TACRED by utilizing the source codes ⁵ provided at [2].
- Re-TACRED [25] is a re-annotated version of the TACRED dataset designed to enable reliable evaluations of relation extraction (RE) models. To create Re-TACRED, we employed the provided source codes⁶ given at [25] to create this dataset.
- SemEval centers on multi-way classification of semantic relations between entity pairs. The predefined relations, referred to as target relation labels, are directional and cannot be extracted from the tokens of the test or train sentences in SemEVAL ⁷.

Split	TACRED	TACREV	Re-TACRED	SemEVAL
Train	68124	68124	58465	8000
Test	15509	15509	13418	2717
Prompt	22631	22631	19584	8000
Dataset				
# of Relations	42	42	40	19

4.1.2 Evaluation Metrics. The benchmark datasets used in this work, especially TACRED and its variants consisting of mostly 'no_relation' as a target relation [2, 25], are imbalanced, so micro metrics are considered. For instance, there are 12184 'no_relation' out of 15509 relations in TACRED test split. Micro F1-score, precision, and recall metrics have been computed in the evaluation of our experiments alongside LLMs on four different benchmark datasets.

³We changed this figure from the original work [8] for integration of fine-tuned LLMs.

⁴The TAC Relation Extraction dataset catalog is accessible at https://catalog.ldc.upenn.edu/LDC2018T24

⁵The TACKEV source code repository is available at https://github.com/DFKI-NLP/tacrev.

⁶The Re-TACRED source code are at https://github.com/gstoica27/Re-TACRED.

 $^{^7} We \ utilized \ this \ dataset \ from \ Hugging Face: \ https://hugging face.co/datasets/sem_eval_2010_task_8.$

Relation Extraction with Fine-Tuned Large Language Models in Retrieval Augmented Generation Frameworks

4.1.3 Settings for Fine-tuning Language Models. Supervised Finetuning Trainer (SFT) ⁸, based on RLRF [17], is utilized to fine-tune language models, e.g., T5 Large, Mistral-7B, and Llama2-7B on prompt datasets at Table 1. Taking into account previous works using language model for relation extraction [8, 16], we leverage the following language models.

- T5 Large is based on encoder-decoder model architecture [5, 22] with 770 million parameters.
- **Mistral-7B** is a type of decoder only model with 7B parameters [15, 22] and is used for RE task in [8].
- Llama2-7B has only decoder in its architecture [22, 26] and is utilized for identifying relations between entities in a sentence in [8].

Instead of fully fine-tuning language models, we integrate the Low Rank Adaptation (LoRA) approach [14] into the language models and apply 4-bit quantization. In other words, we employ the QLoRA approach [7] for fine-tuning language models. As mentioned in Section 2, LoRA and QLoRA are methods for conducting parameter-efficient fine-tuning and reducing the usage of GPU resources throughout the fine-tuning process. These methods focus solely on targeted modules of pre-trained language models and freeze the remaining modules. The language models are fine-tuned on a single GPU with 48 GB of memory. Throughout the fine-tuning process, parameters listed in Table 2 are utilized.

		Value			
	Parameter	Llama2-7B Mistral-7B	T5		
	Learning Rate	2 <i>e</i> – 4	5e-5		
LLMs	Batch Size	4	8		
	Epoch	1	1		
	Weight Decay	0.001	-		
LoRA	LoRA Alpha	16	32		
	LoRA Dropout	0.1	0.01		
	r	64	4		

Table 2: Parameters and settings are utilized in the finetuning process. *r* in LoRA config refers to the rank of the update matrices.

4.1.4 Setting for Retrieval Augmented Generation-based Relation Extraction. Our language models fine-tuned on the prompt datasets at Table 1, are integrated into RAG4RE [8]. All experimental settings are replicated from RAG4RE [8]. Unfortunately, we are unable to fine-tune T5 XL model used in the original RAG4RE [8] due to limited GPU resources. Therefore, we replicate RAG4RE along with T5 Large and vanilla prompting (or simple query) as defined in [8]. We adhere to the experiments conducted in RAG4RE for our work.

4.2 Results

We evaluated language models fine-tuned on prompt datasets detailed at Table 1 in Section 4.1. Furthermore, we integrated these fine-tuned language models into the RAG4RE [8]. It is worth noting that due to constraints in GPU resources, we opted to utilize T5 Large instead of T5 XL or XXL for fine-tuning. Hence, we chose T5 Large and meticulously replicated the RAG4RE experiments within the confines of our work. In this section, we first introduce the results of our fine-tuned models and then the results of RAG4RE approach using our fine-tuned models.

With regard to evaluation of fine-tuned LLMs alongside LoRA on four different datasets, fine-tuned Mistral-7B models accomplish outstanding performance (see Table 3 and Figure 6). Notably, these fine-tuned Mistral-7B models achieve remarkable F1 scores of 89.64%, 94.61%, and 90.09% on TACRED, TACREV, and Re-TACRED, respectively (see Table 3 and Figure 6). However, its performance on SemEVAL falls short of this excellence. Conversely, the finetuned T5 Large demonstrates the highest F1 with 79.94% (see Table 3) on SemEVAL. The Llama2-7B models fine-tuned on TACRED and TACREV follow the fine-tuned Mistral-7B models with micro-F1 scores of 88.20% and 93.75%. Unfortunately, the fine-tuned Llama2-7B models could not exhibit the same performance on Re-TACRED and SemEVAL at Table 3 and Figure 6. The fine-tuned T5 Large model takes second place with a F1 score of 86.94% on Re-TACRED dataset (see Table 3 and Figure 6). Moreover, fine-tuning LLMs outperformed simple query prompting and the previously introduced RAG4RE method [8].

Additionally, we integrated these fine-tuned LLMs into the RAG4RE approach [8] in order to explore their potential in addressing the limitations of general-purpose LLMs. However, due to the lack of an additional dataset split in SemEVAL, we could not examine whether integrating fine-tuned language models into RAG4RE improves the results of RAG4RE using general-purpose LLMs or not. Remarkably, the integration of fine-tuned models into RAG4RE yielded significant improvements across all three datasets, including TA-CRED, TACREV and Re-TACRED, particularly when leveraging T5 Large (see Table 3 and Figure 6). While we observed enhancements in RAG4RE's performance, as detailed in [8], with the integration of fine-tuned Llama-7B on Re-TACRED, it is noteworthy that this improvement was not observed on TACRED and TACREV. Regrettably, the results indicate that the use of Mistral-7B as the finedtuned LLM did not yield improvements in the results of RE. The reason why the performance of the RAG4RE approach could not be improved when fine-tuned decoder-only models are used as a generator in its architecture (see Figure 5) might be related to catastrophic forgetting. Previous work fine-tuning language models on a single task is also dealing with the same forgetting problem [9].

As a result, the fine-tuned T5 Large models consistently achieved the highest F1 scores among all the experiments conducted in this work, particularly when integrated into the RAG4RE framework proposed in [8]. However, fine-tuned Mistral is slightly better than RAG4RE using fine-tuned T5 on TACREV. In addition to the findings of the experiments using T5 Large, both fine-tuning language models on the dataset and integrating these fine-tuned models into RAG4RE outperformed zero-shot prompting approaches, such as simple queries and RAG4RE [8] (see Table 3).

 $^{^8{\}rm The}$ information about how SFT works are available at https://huggingface.co/docs/trl/sft_trainer.



Figure 6: The results of each dataset when three different language models are used along with different approaches. Each color refers to a language model. Blue, Red, and Green point out T5 Large, Mistral-7B, and Llama2-7B, respectively. In addition, f on the gray curves of each figure points out the F1 score. Note that we could not replicate the experiments for finetuning+RAG4RE on SemEVAL dataset due to small dataset.

Table 3: Results of the ex	periments conducted	on four different	benchmark datasets	alongside different LLMs.

		TACRED		TACREV		Re-TACRED		SemEval					
LLM	Method	P(%)	R(%)	F1(%)	P(%)	R(%)	F1(%)	P(%)	R(%)	F1(%)	P(%)	R(%)	F1(%)
T5 Large	simple query	95.10	03.18	06.16	96.72	06.90	12.89	90.91	00.26	00.51	18.74	09.28	12.40
	RAG4RE	85.99	34.50	49.20	91.28	08.20	15.04	80.77	00.27	00.53	07.39	07.21	07.30
	Fine-tuning (QLoRA)	86.74	86.76	86.74	89.93	90.13	90.03	86.27	87.62	86.94	79.94	79.94	79.94
	RAG4RE+Fine-tuning	89.93	94.17	92.00	95.02	93.66	94.34	92.31	93.73	93.01	-	-	-
Llama2-7B	simple query [8]	84.97	01.21	02.38	74.64	00.44	00.87	80.2	00.94	01.86	05.89	05.08	05.45
	RAG4RE [8]	81.23	55.01	65.59	84.89	54.57	66.43	55.93	03.46	06.52	04.36	04.20	04.28
	Fine-tuning (QLoRA)	88.07	88.34	88.20	90.07	97.73	93.75	87.54	44.58	59.08	57.20	50.13	53.43
	RAG4RE+Fine-tuning	80.29	89.18	84.50	84.10	97.26	90.22	83.53	68.16	75.07	-	-	-
Mistral-7B	simple query [8]	94.67	11.96	21.23	92.34	05.15	09.75	64.64	05.48	10.11	25.50	24.37	24.92
	RAG4RE [8]	87.81	30.10	44.83	93.23	22.59	36.36	60.19	30.08	40.11	24.10	22.75	23.41
	Fine-tuning (QLoRA)	94.73	85.06	89.64	95.79	93.48	94.61	92.40	87.83	90.09	76.99	76.99	76.99
	RAG4RE+Fine-tuning	86.57	82.88	84.68	97.58	79.33	87.50	90.86	85.95	88.33	-	-	-

4.3 Discussion

In this work, we conducted two experiments: firstly, fine-tuning of language models, and secondly, integration of the fine-tuned language models into RAG4RE [8]. Our findings indicate remarkable improvements on results of original RAG4RE [8] on TACRED, TACREV, Re-TACRED at Table 3 when fine-tuned T5 Large models are integrated to RAG4RE approach. Regrettably, extending the same experiment to SemEVAL in conjunction with RAG4RE and fine-tuned language models proved unfeasible, given the absence of additional splits beyond the train and test sets in this dataset. The process of fine-tuning language models, particularly in context of the domain adaptation, demonstrated notable enhancements in the performance of both general-purpose language models and RAG4RE (see Table 3 and Figure 6). However, our fine-tuned language model obtained slightly better F1 score than the RAG4RE using our finetuned language model on TACREV dataset at Table 4.

We analyzed the effectiveness of our fine-tuned language models in Relation Extraction (RE), comparing their F1 scores with both LLM-based methods and state-of-the-art (SoTA) RE techniques in the literature. Our findings reveal that our approach consistently outperforms other LLM-based zero-shot methods [8, 16, 28], as demonstrated in Table 4, across all benchmark datasets. This superior performance can largely be attributed to the lack of domainspecific knowledge used by LLMQA4RE [16] RationaleCL [28] and RAG4RE [8]. The reason why these LLM-based methods could not achieve better performance on these RE datasets, these works rely on zero-shot prompting with general-purpose LLMs, whereas we fine-tuned general-purpose LLMs using QLoRA on small part of datasets. Obviously, our fine-tuned language models outperformed all these zero-shot prompting approaches on all four datasets.

Moreover, we carried out a thorough comparison with existing works achieved remarkable results on these benchmarks in the literature. Remarkably, the best-performing results in our experiments at Table 3 surpassed the SoTA results on the TACRED, TACREV, and Re-TACRED datasets, obtaining F1 scores of 92.00%, 94.61%, and 93.01%, respectively. All these models except for RAG4RE [8] are trained on train splits of these datasets, which means that they have domain knowledge of these datasets. Furthermore, our approach, Fine-tuning+RAG4RE, also outperformed to original RAG4RE using general-purpose LLMs. These achievements are detailed in Table 4.

Consequently, our fine-tuned language models achieved outstanding results on the TACRED, TACREV, and Re-TACRED datasets when integrated into the RAG4RE [8]. Nonetheless, we could not repeat the experiments with RAG4RE using our fine-tuned language models for SemEVAL. However, fine-tuning LLMs on the SemEVAL dataset outperformed all the methods using zero-shot prompting.

 Table 4: A comparison of our best-performing results with those of prior works.

[8]	Method	TACRED	TACREV	Re-TACRED	SemEval
	DeepStruct [27]	76.8%	-	-	-
SoTA	EXOBRAIN [31] KLG [19] SP [6] GAP [4]	75.0% - 74.8% 72.7%	- 84.1% - 82.7%	91.4% - 91.4%	- 90.5% 91.9 % 90.3%
Zero-Shot	LLMQA4RE [16] RationaleCL [28] RAG4RE [8]	52.2% 80.8% 86.6%	53.4% - 88.3%	66.5% - 73.3%	43.5% - 23.41%
	Fine-tuning+ RAG4RE (Ours)	92.00%	94.34%	93.01%	-
	Fine-tuning (Ours)	89.64%	94.61%	90.09%	79.61%

5 CONCLUSION

In this work, we propose to fine-tune Large Language Models (LLMs) to figure out the domain adaptation problem stemming from utilizing general-purpose LLMs, in particular identifying implicit relations between entities in a sentence. To perform this, we conducted two approaches: fine-tuning language models and RAG4RE [8] along with fine-tuned language models on four benchmark datasets, including TACRED, TACREV, Re-TACRED, and SemEVAL, using T5 Large, Mistral-7B, and Llama2-7B. Our fine-tuned LLMs achieved remarkable results and mostly outperformed previous works [8, 28], including the original RAG4RE approach, on TACRED, TACREV and Re-TACRED.

Furthermore, we integrated our fine-tuned LLMs on relation extraction datasets into RAG4RE [8] and evaluated this approach using three benchmark datasets: TACRED, TACREV, and Re-TACRED. We tested three distinct LLMs: Mistral-7B, T5 Large, and Llama2-7B. The results showed that integrating fine-tuned LLMs into the RAG4RE approach improved the original work's performance due to domain adaptation, particularly with T5 Large. However, we did not observe consistent improvements when integrated our finetuned Llama2-7B and Mistral-7B models into RAG4RE. This issue might be related to catastrophic forgetting caused by single-task fine-tuning. Overall, RAG4RE with our fine-tuned models achieved remarkable results compared to RAG4RE using general-purpose LLMs as reported in [8]. Our proposed approach exhibited notable improvements on the benchmarks compared to the original RAG4RE and previous works. Unfortunately, we could not evaluate the performance on SemEVAL dataset, as it is quite small and lacks additional splits not used in the original RAG4RE, unlike TACRED and its variants.

In our future work, we intend to extend our approach with multitask fine-tuning for entity recognition and relation extraction, since single-task fine-tuning might encounter with catastrophic forgetting of learned knowledge and reduce the capabilities of LLMs [9, 20, 29]. Conference'17, July 2017, Washington, DC, USA

REFERENCES

- Eugene Agichtein and Luis Gravano. 2000. Snowball: Extracting Relations from Large Plain-Text Collections. In Proceedings of the Fifth ACM Conference on Digital Libraries (San Antonio, Texas, USA) (DL '00). Association for Computing Machinery, New York, NY, USA, 85–94.
- [2] Christoph Alt, Aleksandra Gabryszak, and Leonhard Hennig. 2020. TA-CRED Revisited: A Thorough Evaluation of the TACRED Relation Extraction Task. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault (Eds.). Association for Computational Linguistics, Online, 1558–1569. https://doi.org/10.18653/v1/2020.acl-main.142
- [3] Mehmet Aydar, Ozge Bozal, and Furkan Ozbay. 2020. Neural relation extraction: a survey.
- [4] Zhenbin Chen, Zhixin Li, Yufei Zeng, Canlong Zhang, and Huifang Ma. 2024. GAP: A novel Generative context-Aware Prompt-tuning method for relation extraction. *Expert Systems with Applications* 248 (2024), 123478. https://doi.org/10.1016/j.eswa.2024.123478
- [5] Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Eric Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, Albert Webson, Shixiang Shane Gu, Zhuyun Dai, Mirac Suzgun, Xinyun Chen, Aakanksha Chowdhery, Sharan Narang, Gaurav Mishra, Adams Yu, Vincent Zhao, Yanping Huang, Andrew Dai, Hongkun Yu, Slav Petrov, Ed H. Chi, Jeff Dean, Jacob Devlin, Adam Roberts, Denny Zhou, Quoc V. Le, and Jason Wei. 2022. Scaling Instruction-Finetuned Language Models. https://doi.org/10.48550/ARXIV.2210.11416
- [6] Amir DN Cohen, Shachar Rosenman, and Yoav Goldberg. 2020. Relation classification as two-way span-prediction. arXiv preprint arXiv:2010.04829 (2020).
- [7] Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. 2023. QLoRA: Efficient Finetuning of Quantized LLMs. arXiv:2305.14314 [cs.LG]
- [8] Sefika Efeoglu and Adrian Paschke. 2024. Retrieval-Augmented Generationbased Relation Extraction. arXiv:2404.13397 [cs.CL]
- [9] Wenfeng Feng, Chuzhan Hao, Yuewei Zhang, Yu Han, and Hao Wang. 2024. Mixture-of-LoRAs: An Efficient Multitask Tuning for Large Language Models. arXiv:2403.03432 [cs.CL]
- [10] Yunfan Gao, Yun Xiong, Xinyu Gao, Kangxiang Jia, Jinliu Pan, Yuxi Bi, Yi Dai, Jiawei Sun, and Haofen Wang. 2023. Retrieval-augmented generation for large language models: A survey. arXiv preprint arXiv:2312.10997 (2023).
- [11] Ralph Grishman. 2015. Information Extraction. *IEEE Expert* 30, 5 (1 Sept. 2015), 8–15.
- [12] Zeyu Han, Chao Gao, Jinyang Liu, Sai Qian Zhang, et al. 2024. Parameterefficient fine-tuning for large models: A comprehensive survey. arXiv preprint arXiv:2403.14608 (2024).
- [13] Iris Hendrickx, Su Nam Kim, Zornitsa Kozareva, Preslav Nakov, Diarmuid Ó Séaghdha, Sebastian Padó, Marco Pennacchiotti, Lorenza Romano, and Stan Szpakowicz. 2010. SemEval-2010 Task 8: Multi-Way Classification of Semantic Relations between Pairs of Nominals. In *Proceedings of the 5th International Workshop on Semantic Evaluation*, Katrin Erk and Carlo Strapparava (Eds.). Association for Computational Linguistics, Uppsala, Sweden, 33–38. https://aclanthology.org/S10-1006
- [14] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. LoRA: Low-Rank Adaptation of Large Language Models. arXiv:2106.09685 [cs.CL]
- [15] Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. 2023. Mistral 7B. arXiv preprint arXiv:2310.06825 (2023).
- [16] Yu Su Kai Zhang, Bernal Jiménez Gutiérrez. 2023. Aligning Instruction Tasks Unlocks Large Language Models as Zero-Shot Relation Extractors. In *Findings* of ACL.
- [17] Nathan Lambert, Louis Castricato, Leandro von Werra, and Alex Havrilla. 2022. Illustrating Reinforcement Learning from Human Feedback (RLHF). *Hugging Face Blog* (2022). https://huggingface.co/blog/rlhf.
- [18] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks. In Proceedings of the 34th International Conference on Neural Information Processing Systems (Vancouver, BC, Canada)

(NIPS'20). Curran Associates Inc., Red Hook, NY, USA, Article 793, 16 pages.

- [19] Bo Li, Wei Ye, Jinglei Zhang, and Shikun Zhang. 2022. Reviewing Labels: Label Graph Network with Top-k Prediction Set for Relation Extraction. arXiv:2212.14270 [cs.CL]
- [20] Bingchang Liu, Chaoyu Chen, Cong Liao, Zi Gong, Huan Wang, Zhichao Lei, Ming Liang, Dajun Chen, Min Shen, Hailian Zhou, Hang Yu, and Jianguo Li. 2023. MFTCoder: Boosting Code LLMs with Multitask Fine-Tuning. arXiv:2311.02303 [cs.LG]
- [21] Eric Melz. 2023. Enhancing LLM Intelligence with ARM-RAG: Auxiliary Rationale Memory for Retrieval Augmented Generation. arXiv e-prints (2023), arXiv-2311.
- [22] Shirui Pan, Linhao Luo, Yufei Wang, Chen Chen, Jiapu Wang, and Xindong Wu. 2024. Unifying large language models and knowledge graphs: A roadmap. IEEE Transactions on Knowledge and Data Engineering (2024).
- [23] Sachin Pawar, Girish K. Palshikar, and Pushpak Bhattacharyya. 2017. Relation Extraction : A Survey.
- [24] Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. 2023. Direct Preference Optimization: Your Language Model is Secretly a Reward Model. arXiv:2305.18290 [cs.LG]
- [25] George Stoica, Emmanouil Antonios Platanios, and Barnabas Poczos. 2021. Re-TACRED: Addressing Shortcomings of the TACRED Dataset. Proceedings of the AAAI Conference on Artificial Intelligence 35, 15 (May 2021), 13843–13850. https://doi.org/10.1609/aaai.v35i15.17631
- Hugo Touvron, Louis Martin, Kevin R. Stone, Peter Albert, Amjad Almahairi, [26] Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Daniel M. Bikel, Lukas Blecher, Cristian Cantón Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony S. Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel M. Kloumann, A. V. Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalvan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, R. Subramanian, Xia Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zhengxu Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023. Llama 2: Open Foundation and Fine-Tuned Chat Models. ArXiv abs/2307.09288 (2023). https://api.semanticscholar.org/CorpusID:259950998
- [27] Chenguang Wang, Xiao Liu, Zui Chen, Haoyun Hong, Jie Tang, and Dawn Song. 2022. DeepStruct: Pretraining of Language Models for Structure Prediction. In *Findings of the Association for Computational Linguistics: ACL 2022*, Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (Eds.). Association for Computational Linguistics, Dublin, Ireland, 803–823. https://doi.org/10.18653/v1/2022.findings-acl.67
- [28] Weimin Xiong, Yifan Song, Peiyi Wang, and Sujian Li. 2023. Rationale-Enhanced Language Models are Better Continual Relation Learners. In Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, Houda Bouamor, Juan Pino, and Kalika Bali (Eds.). Association for Computational Linguistics, Singapore, 15489–15497. https://doi.org/10.18653/v1/2023.emnlp-main.958
- [29] Haoran Yang, Yumeng Zhang, Jiaqi Xu, Hongyuan Lu, Pheng Ann Heng, and Wai Lam. 2024. Unveiling the Generalization Power of Fine-Tuned Large Language Models. arXiv:2403.09162 [cs.CL]
- [30] Yuhao Zhang, Victor Zhong, Danqi Chen, Gabor Angeli, and Christopher D. Manning. 2017. Position-aware Attention and Supervised Data Improve Slot Filling. In Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, Martha Palmer, Rebecca Hwa, and Sebastian Riedel (Eds.). Association for Computational Linguistics, Copenhagen, Denmark, 35– 45. https://doi.org/10.18653/v1/D17-1004
- [31] Wenxuan Zhou and Muhao Chen. 2022. An Improved Baseline for Sentencelevel Relation Extraction. In Proceedings of the 2nd Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 12th International Joint Conference on Natural Language Processing (Volume 2: Short Papers), Yulan He, Heng Ji, Sujian Li, Yang Liu, and Chua-Hui Chang (Eds.). Association for Computational Linguistics, Online only, 161–168. https://aclanthology.org/2022.aacl-short.21