Monte Carlo Planning for Stochastic Control on Constrained Markov Decision Processes

Larkin Liu^{*} Shiqi Liu[†] Matej Jusup[‡]

 25^{th} June, 2024

Abstract

In the world of stochastic control, especially in economics and engineering, Markov Decision Processes (MDPs) can effectively model various stochastic decision processes, from asset management to transportation optimization. These underlying MDPs, upon closer examination, often reveal a specifically constrained causal structure concerning the transition and reward dynamics. By exploiting this structure, we can obtain a reduction in the causal representation of the problem setting, allowing us to solve of the optimal value function more efficiently. This work defines an MDP framework, the SD-MDP, where we disentangle the causal structure of MDPs' transition and reward dynamics, providing distinct partitions on the temporal causal graph. With this stochastic reduction, the SD-MDP reflects a general class of resource allocation problems. This disentanglement further enables us to derive theoretical guarantees on the estimation error of the value function under an optimal policy by allowing independent value estimation from Monte Carlo sampling. Subsequently, by integrating this estimator into well-known Monte Carlo planning algorithms, such as Monte Carlo Tree Search (MCTS), we derive bounds on the simple regret of the algorithm. Finally, we quantify the policy improvement of MCTS under the SD-MDP framework by demonstrating that the MCTS planning algorithm achieves higher expected reward (lower costs) under a constant simulation budget, on a tangible economic example based on maritime refuelling.

1 Introduction

While Markov Decision Processes (MDPs) offer a comprehensive framework for many sequential decision-making problems under uncertainty, certain problem structures and assumptions allow for simplified approaches that avoid the full complexity of an MDP formulation. For instance, in linear quadratic Gaussian control problems, the optimal control policy has a reduced form due to the equivalence principle [AM07]. In finance, under log utility and geometric Brownian motion asset dynamics, the optimal investment strategy has an explicit closed-form solution in some instances of financial derivatives [ZY03]. Economic models with rational expectations and additive components can often leverage the certainty equivalence principle. This means that separating deterministic and stochastic components can simplify the model, and provide an pathways to derive error bounds for Monte Carlo estimation algorithms (later outlined in Section 2.2). Sampling-based approaches that avoid modelling the full probability distribution can be carefully adopted to provide tractable solutions in various stochastic control and economic applications while retaining key problem characteristics [CF12].

From a classical perspective, for the problem of optimal planning, approximation techniques can be applied, such as policy iteration, value iteration, approximate dynamic programming, and deep

^{*}TU München; larkin.liu@tum.de

[†]LÉcole Polytechnique; shiqi.liu@polytechnique.edu

[‡]ETH Zürich; mjusup@ethz.ch

reinforcement learning, etc. [Ber11] [Sil+17] [FSM10] [Ber11]. More recent research has focused on the idea of unravelling the causal structure of the MDP, particularly with respect to each component of the state space and how transitions and rewards are generated as a result of system and agent interaction over time. A system's evolution from state to state, and how rewards are generated resulting from actions taken, can often exhibit a simplified causal structure. When we unfold the causal structure of an MDP, we can apply this knowledge to simplify or get unique properties for any MDP solver [LMT22] [BJS21]. Unfolding and applying the causal structure of an MDP can improve the computational complexity of MDP solvers via separability of the search space [LMT22].

Specifically, focus on the problem of resource allocation over time. Traditionally, resource allocation problems were solved using multi-stage stochastic programming or formulating the problem as an MDP and applying some form of MDP solver, such as approximate dynamic programming, for large-scale problems [WW11] [Pow+05] [DV04] [BDG00]. Nevertheless, these traditional methods are often very specific to the problem setting and do not generalize to a class of similar problems—they often require a full reformulation [Kus90] [Pow+05]. Furthermore, they do not take into account the causal structure of the MDP to obtain computational simplifications [ZBD10]. Similar to energy conservation principles in physics, we impose a construct which we denote as a *resource-utility* exchange model (defined in Section 2.1) [Hau79]. In this model, resources can be converted to utility and vice versa, subject to certain environmental constraints.

The key idea which we introduce is the disentanglement of stochastic environmentally induced state transitions and deterministically action-driven reward functions. When we disentangle these components from an MDP, we are able to independently make optimizations based on components that the agent can model perfectly at a lower fidelity and compute expectations over stochastic outcomes separately, improving efficiency and making it simpler to derive theoretical guarantees on any value approximation [Gen+20] [Tod09]. Namely, this type of construct allows us to obtain theoretical guarantees on value function estimates, which aids us in providing value function estimates when integrating Monte Carlo approximations with MDP solvers utilizing online learning. To shed a new perspective on this family of problems, we formulate an abstraction for a specific class of MDPs, which can be used to flexibly model several types of resource allocation problems. We introduce the SD-MDP (in Section 2.1), which provides a basis for more expressive stochastic modelling for specific problem settings akin to a restless bandit setting, as well as providing a standard pathway to derive important theoretical guarantees.

In this paper, we introduce the SD-MDP framework, a rigorous approach for modelling constrained MDPs through a structured decomposition based on the causal dynamics of the system, as illustrated in Section 2.1. This framework is particularly suited for a wide range of resource-allocation problems. In Section 2.3, we explore how the dynamics of the SD-MDP can inform us about the structure of optimal policy. In Section 3 we describe the integration of this knowledge into well-known Monte Carlo planning algorithms, such as UCT [KS06] and MENTS [Xia+19], and offer theoretical guarantees on the upper bound of simple regret under mild assumptions. In Section 4.1, we present empirical results from the maritime refuelling problem (a.k.a. *bunkering*), demonstrating the practical application of the SD-MDP. These results show that our MCTS methodology, achieves higher expected rewards (or lower costs) under equal simulation budgets compared to vanilla MCTS, and also outperforms the stochastic programming baseline. This may result in positive environmental impact by reducing excess fuel consumption.

2 Problem Definition

Classical MDP: Let a well-defined general discrete time MDP be represented as \mathcal{M}_{θ} , defined by $\mathcal{M} = (\mathbf{x}^1, \mathcal{X}, \mathcal{A}, \mathbb{P}, \mu)$, where the dynamics of the system are governed by parameters θ . To summarize:

- \mathcal{X} is the set of states, $\mathcal{X} = {\mathbf{x}_1, \mathbf{x}_2, ...}$.
- \mathcal{A} is the set of actions, $\mathcal{A} = \{\mathbf{a}_1, \mathbf{a}_2, ...\}.$

- **x**¹ is the initial state of the system.
- \mathbb{P} represents the state transition probabilities, $\mathbb{P}(\mathbf{x}^{t+1} \mid \mathbf{x}, \mathbf{a})$, the probability of transitioning to state \mathbf{x}^{t+1} given action \mathbf{a} in state \mathbf{x} .
- $\mu(\cdot)$ is the reward function, $\mu(\mathbf{x}, \mathbf{a})$, the immediate reward upon taking action \mathbf{a} in state \mathbf{x} at time t.

The objective of our optimization is to obtain a policy π , which maps states to actions, that maximizes the expected cumulative reward,

$$\pi^* = \arg\max_{\pi} \mathbb{E}\left[\sum_{t=1}^{T} \mu(\mathbf{x}^t, \mathbf{a}^t) \,\middle|\, \mathbf{x}^1, \pi\right]$$
(2.1)

This objective aims to identify the policy that maximizes the expected sum of rewards over a finite time horizon over randomness induced by the MDP parameters θ , where the expectation is taken over the randomness in the transition dynamics and policy when it is stochastic. Here, \mathbf{x}^t represents the state at time t, \mathbf{a}^t denotes the action taken at time t, and \mathbf{x}^{t+1} denotes the next state at t+1. It is important to note that negative rewards are also possible, especially in problem settings where minimizing costs is the goal.

2.1 The SD-MDP Framework

We perform a stochastic reduction on the classical MDP, partitioning it into various components driven by the *causal dynamics* and Markovian properties. From the perspective of causal reinforcement learning [LMT22], the SD-MDP partitions the state transition dynamics via the causal relation of the intervening action. This allows the state transition to be modelled separately and independent of the reward dynamics. The *transition separability* characteristic of the SD-MDP isolates the causal effect of actions \mathbf{a}^t on the state transition $\mathbf{x}^t_\eta \to \mathbf{x}^{t+1}_\eta$, as illustrated in Fig. 1.



Figure 1: A visualization of SD-MDP partitioning of stochastic and deterministic causal structure. The SD-MDP splits transition dynamics into stochastic component \mathbf{x}_{η}^{t} and deterministic \mathbf{x}_{d}^{t} . The reward μ^{t} is driven by both partitions, and the action \mathbf{a}^{t} .

The SD-MDP integrates both deterministic (\mathbf{x}_d) and environmentally driven (\mathbf{x}_η) state components, the combination of which defines an MDP state, $\mathbf{x} = [\mathbf{x}_\eta, \mathbf{x}_d]^T$. To standardize notation, $\mathbf{x} \in \mathcal{X}$ is decomposed into $\mathbf{x}_\eta \in \mathcal{X}_\eta$ and $\mathbf{x}_d \in \mathcal{X}_d$. At face value, this model is similar to the restless bandit problem [Git79], aiming to maximize cumulative expected rewards within a finite time frame for environmentally changing state transitions. Unlike a classical restless bandit, due to constraints on \mathbf{x}_d (we later illustrate what such constraints are in Table 1), reward outcomes must be planned over the



Figure 2: A display of norm-capacity dynamics. As the capacity of \mathbf{x}_d shrinks given the constraints of the norm-capacity, the consumption of resource can be transformed into a reward $\langle \phi f(\mathbf{x}_{\eta}^t), \mathbf{a}^t \rangle$. The blue shading represents shrinkage of the the resource capacity, and the orange shading represents the vector space of possible outcomes, the magnitude of this vector (represented by the red arrow) represents the reward.

complete time horizon T, rather than maximizing at each given opportunity, under perfect information or otherwise.

Formally, the SD-MDP is represented as $(\mathcal{X}, \mathcal{A}, \mathcal{R}, \mathcal{T}, \mathbf{x}^1)$, where \mathcal{X} denotes the state space; \mathcal{A} denotes the action space, and is of dimension $D \in \mathbb{Z}^+$ (where \mathbb{Z}^+ denotes the set of integers greater than 0); $\mathcal{R} \subseteq \mathbb{R}$ denotes the reward space; \mathcal{T} is the transition function for $\mathbf{x} \in \mathcal{X}$, and \mathbf{x}^1 is the initial state.

In particular, we divvy up the state vector representation into a deterministic partition, \mathbf{x}_d , and an independent stochastic partition, \mathbf{x}_η , both exhibiting different properties when subject to an intervention (or action) \mathbf{a}^t . To denote the parameters which govern the dynamics of a specific SD-MDP, we use θ . The stochastic transitions governed by $P_{\theta}(\cdot)$ are independent of the action taken.

$$P(\mathbf{x}_d^{t+1}|\mathbf{a}^t, \mathbf{x}^t) \in \{0, 1\}$$

$$(2.2)$$

$$P(\mathbf{x}_{\eta}^{t+1}|\mathbf{a}^{t},\mathbf{x}^{t}) = P_{\theta}(\mathbf{x}_{\eta}^{t+1}|\mathbf{x}_{\eta}^{t})$$
(2.3)

$$P(\mathbf{x}^{t+1}|\mathbf{a}^t, \mathbf{x}^t) = P(\mathbf{x}_d^{t+1}|\mathbf{a}^t, \mathbf{x}^t) P_{\theta}(\mathbf{x}_\eta^{t+1}|\mathbf{x}_\eta^t)$$
(2.4)

Where Eq. (2.2) represents if the future deterministic component \mathbf{x}_d^{t+1} is reached by taking action \mathbf{a}^t . Eq. (2.3) represents the natural transition of the stochastic partition \mathbf{x}_{η}^t independent of \mathbf{a}^t , and Eq. (2.4) represents the combined probability of transition for the SD-MDP.

To allow for a general model of non-linear resource consumption and utility exchange, we use $f(\cdot)$ and $g(\cdot)$ to denote coordinate-wise separable functions composed of a series of smooth positively monotone Lipschitz kernel functions governing the dimension-wise scaling of each dimension when an action is taken by the agent. For example, this can represent the reward and resource consumption dynamics respectively. To be specific $f: \mathbb{R}^D \to \mathbb{R}^D$ and $g: \mathbb{R}^D \to \mathbb{R}^D$ are coordinate wise separable. For a D dimensional vector, f is a monotonic function which,

$$f(\mathbf{x}) \equiv [f_1(\mathbf{x}_1), f_2(\mathbf{x}_2), \dots, f_D(\mathbf{x}_D)]^T, \qquad g(\mathbf{x}) \equiv [g_1(\mathbf{x}_1), g_2(\mathbf{x}_2), \dots, g_D(\mathbf{x}_D)]^T$$
(2.5)

In Table 1, we provide a list of the underlying dynamics that govern the behaviour of the SD-MDP. To begin, an agent may have a particular resource that they are consuming over time (money, fuel, battery etc.). This resource can be converted to rewards for the agent. First, this motivates Dynamic (D1), which ensures a valid representation of multi-dimensional resource capacity consumption over time, as illustrated in Fig. 2. We impose the constraint of a strictly element-wise positive action

Definition	Expression	
(D1) Positive Action & Capacity Space: We assume strictly positive action and capacity spaces.	$\mathbf{a} > 0, \mathbf{x}_d \geq 0$	(2.6)
(D2) General Linear Reward Dynamics: The reward function $\mu(\mathbf{a}^t, \mathbf{x}^t)$ obeys a linear relationship w.r.t. action \mathbf{a}^t and stochastic state partition \mathbf{x}^t .	$\mu(\mathbf{a}^t,\mathbf{x}^t)=\langle \phi f(\mathbf{x}^t_\eta),\mathbf{a}^t angle$	(2.7)
(D3) Incremental Action Dynamics: We define a lin- ear transformation matrix ϕ' , which is anti-parallel to ϕ . To model the expansion and contraction of the capacity	$ \mathbf{x}_d^{t+1} - \mathbf{x}_d^t _p = \underbrace{\Delta_d(t)}_{\text{System}} + \underbrace{\phi' g(\mathbf{a}^t)}_{\text{Agent}} _p$	(2.8)
\mathbf{x}_d , we impose constraints on the transition function acting on \mathbf{x}_d in Eq. (2.8) and Eq. (2.9).	$\underline{\Delta}_{a}(t) \leq \mathbf{x}_{d}^{t+1} - \mathbf{x}_{d}^{t} _{p} \leq \bar{\Delta}_{a}(t), \forall a \in \mathcal{A}$	(2.9)
(D4) Capacity Objective: The accumulation of resources, as measured by $ \phi' g(\mathbf{a}^t) _p$, should meet a predetermined maximum and minimum goals.	$\underline{A} \le \sum_{t=1}^{T} \phi' g(\mathbf{a}^t) _p \le \bar{A}$	(2.10)
(D5) Recency Preference: Ordinal preference of equivalent states w.r.t. to t .	$\mathbf{x}_{\eta}^{t} = \mathbf{x}_{\eta}^{t+\Delta} \implies \mathbf{x}_{\eta}^{t} \succ \mathbf{x}_{\eta}^{t+\Delta}, \Delta \in \mathbb{Z}$	(2.11)

Table 1: Summary of the system dynamics of the SD-MDP.

space, $\mathbf{a} > \mathbf{0}$. Additionally, the capacity space is also subject to a similar constraint, ensuring each component of the capacity vector \mathbf{x}_d is non-negative, i.e., $\mathbf{x}_d \ge \mathbf{0}$.

Dynamic (**D2**) stipulates that the SD-MDP obeys a reward function of a general linear form. Action \mathbf{a}^t , together with the stochastic state partition \mathbf{x}^t_{η} , invokes a deterministic reward outcome with a linear relation, $\mu(\mathbf{a}^t, \mathbf{x}^t)$. Let $\mu(\cdot) : \mathbb{R}^D \times \mathbb{R}^D \mapsto \mathbb{R}$ denote a standard map that yields a scalar in \mathbb{R} when provided with inputs $\mathbf{a} \in \mathcal{A}$ and $\mathbf{x}^t_{\eta} \in \mathcal{X}_{\eta}$, subject to constraints on the system at time t. Next, we employ a linear transformation on $f(\mathbf{x}^t_{\eta})$, with a positive semi-definite matrix ϕ . This homogeneous scaling map allows for both enlargement and shrinking of the vector along the positive dimensions. The reward function results from an inner product between the transformed vector ϕ , $f(\mathbf{x}^t_{\eta})$ and \mathbf{a}^t , as expressed in Eq. (2.7). Furthermore, the dimension of \mathcal{A} is dim $(\mathcal{A}) = D$, which must also be equal to the dimension of $\phi f(\mathbf{x}_{\eta}) \in \phi \mathcal{X}$ where dim $(\phi \mathcal{X}) = D$.

Dynamic (D3) governs resource consumption incrementally. We define a linear transformation matrix ϕ' , which is anti-parallel to ϕ . Similarly, we apply function $g : \mathbb{R}^D \to \mathbb{R}^D$, to model the expansion and contraction of the capacity \mathbf{x}_d . We impose the transition function acting on \mathbf{x}_d in Eq. (2.8). Where $\Delta_d(t) : \{1, ..., T\} \to \mathbb{R}$ is a natural discrete change on \mathbf{x}_d^t as deterministically determined by the system, and $\phi'g(\mathbf{a}^t)$ is the contribution to the expansion or contraction of \mathbf{x}_d^t based on the agent's action taken at \mathbf{a}^t taken at time t. We impose a constraint on the magnitude of capacity change per time interval via Eq. (2.9), where constraints $\underline{\Delta}_a(t)$ and $\overline{\Delta}_a(t)$ are given by the system.

Dynamic (**D4**) enforces a *path constraint* on the action space that restricts the path of the action sequence the agent takes. We constrain the trajectory of actions by limiting the accumulation of actions measured with norms. As defined, the accumulation of resources $\phi'g(\mathbf{a}^t)$ should meet some maximum and minimum goals, as expressed in Eq. (2.10).

Dynamic (D5) posits that the value of receiving the exact same reward sooner is more valuable to the agent than receiving it later without the need for an explicit discount factor. To further expound, using a preference to break any ties should any policy lead to the same reward outcome.

2.2 Value Estimation Properties

We provide an intuitive analysis on the behivour of the optimal policy. In the final state at T, the deterministic property ensures from Dynamic (D2), at the value of the final state final state T, can

be computed via pure exploitation, by taking the maximum allowable action at time T according to the constraints from Dynamic (D3) and (D4). Thus, we express the value function as,

$$V(\mathbf{x}^{T}) = \max_{\mathbf{a} \in \mathcal{A}(T)} \mu(\mathbf{x}^{T}, \mathbf{a})$$
(2.12)

We examine the problem through induction. Consider that the agent is at time T-1 and would like to obtain the value estimate for time T. We express the *conditional value function* $V(\mathbf{x}^T|\mathbf{x}^{T-1})$ as,

$$V(\mathbf{x}^T | \mathbf{x}^{T-1}) = \langle \phi f(\mathbb{E}[\mathbf{x}_{\eta}^T | \mathbf{x}_{\eta}^{T-1}]), \mathbf{a}^* \rangle$$
(2.13)

To obtain the optimal value of \mathbf{a}^* , ideally the agent performs the optimal action to yield the highest reward at time T. This however, depends on the capacity constraints of the action sequence, which must obey constraints Eq. (2.9) and (2.10). We can thus express the value function at T-1, subject to the incremental dynamics, and goal constraints as,

$$V(\mathbf{x}^{T-1}) = \max_{\mathbf{a}\in\mathcal{A}(T-1)} \left\{ \langle \phi f(\mathbf{x}_{\eta}^{T-1}), \mathbf{a} \rangle + \int_{\mathbf{x}^{T}} P_{\theta}(\mathbf{x}^{T} | \mathbf{a}, \mathbf{x}^{T-1}) V(\mathbf{x}^{T}) \, d\mathbf{x} \right\}$$
(2.14)

Assuming capacity is available at time T, given special properties of the problem, we can partition,

$$V(\mathbf{x}^{T-1}) = \max_{\mathbf{a} \in \mathcal{A}^{T-1}} \left\{ \langle \phi f(\mathbf{x}_{\eta}^{T-1}), \mathbf{a} \rangle + \int_{\mathbf{x}^{t}} P_{\theta}(\mathbf{x}_{\eta}^{T} | \mathbf{x}_{\eta}^{T-1}) \left\langle (\mathbf{x}_{d}^{T-1} + \phi' g(\mathbf{a})), \phi f(\mathbf{x}_{\eta}^{T}) \right\rangle d\mathbf{x}_{\eta}^{T} \right\}$$
(2.15)

$$= \max_{\mathbf{a}\in\mathcal{A}^{T-1}} \left\{ \langle \phi f(\mathbf{x}_{\eta}^{T-1}), \mathbf{a} \rangle + \langle (\mathbf{x}_{d}^{T-1} + \phi' g(\mathbf{a})), \int_{\mathbf{x}^{t}} P_{\theta}(\mathbf{x}_{\eta}^{T} | \mathbf{x}_{\eta}^{T-1}) \phi f(\mathbf{x}_{\eta}^{T}) \rangle \, d\mathbf{x}_{\eta}^{T} \right\}$$
(2.16)

$$= \max_{\mathbf{a} \in \mathcal{A}^{T-1}} \left\{ \langle \phi f(\mathbf{x}_{\eta}^{T-1}), \mathbf{a} \rangle + \langle (\mathbf{x}_{d}^{T-1} + \phi' g(\mathbf{a})), \mathbb{E}[\phi f(\mathbf{x}_{\eta}^{T}) | \mathbf{x}_{\eta}^{T-1}] \rangle \right\}$$
(2.17)

For non trivial solutions to Eq. (2.17), we adhere to the *incremental action dynamic* (D3) property of the SD-MDP. The binary structure of the optimal policy becomes apparent at T - 1.

2.3 Structure of the Optimal Policy

Let $\tau_a \equiv (\mathbf{a}^{i=1}, \mathbf{a}^{i=2}, \mathbf{a}^{i=3}, \dots, \mathbf{a}^{i=t})$ denote a sequence of **a** from 1 to *t*. Further, let us denote the operators,

$$\underline{\aleph}^{t}[\tau_{a}] \equiv (T-t+1)||\underline{\Delta}_{a}(t)||_{p} + \sum_{i}^{t-1} ||\phi'g(\mathbf{a}^{i})||_{p} - \bar{A}$$

$$(2.18)$$

$$\overline{\aleph}^{t}[\tau_{a}] \equiv (T-t+1)||\bar{\Delta}_{a}(t)||_{p} + \sum_{i}^{t-1} ||\phi'g(\mathbf{a}^{i})||_{p} - \underline{A}$$
(2.19)

Intuitively, $\overline{\aleph}^t[\tau_a]$ and $\underline{\aleph}^t[\tau_a]$ represent the maximum and minimum allowable consumption under the path constraint in Eq. (2.10) at time t. Moving forward let, $\mathcal{A}(t)$ denote the action set at time t, given the constraints from equations Eq. (2.9) and (2.10), such that the expression $\mathbf{a} \in \mathcal{A}(t)$ encapsulates the constraints from all action dynamics pertaining to the SD-MDP framework.

$$\mathcal{A}(t) \equiv \left\{ \mathbf{a} : \underline{\|\mathbf{a}(t)\|}_{p} \le ||\phi'g(\mathbf{a}^{t})||_{p} \le \overline{\|\mathbf{a}(t)\|}_{p} \right\}$$
(2.20)

$$\left\| \mathbf{a}(t) \right\|_{p} = \max\left\{ \underline{\aleph}^{t}[\tau_{a}], \ \underline{\Delta}_{a}(t) \right\}$$
(2.21)

$$\overline{\|\mathbf{a}(t)\|_{p}} = \min\left\{\overline{\aleph}^{t}[\tau_{a}], \, \|\mathbf{x}_{d}^{t}\|_{p}, \, \bar{\Delta}_{a}(t)\right\}$$
(2.22)

Intuitively, $\underline{\Delta}_a(t)$ and $\overline{\Delta}_a(t)$ constitute the minimum and maximum incremental capacity constraints specified by the system. the *incremental action dynamic* (D3) forms a constraint on the capacity from the deterministic component of the SD-MDP. Along with the goal constraint of the system, $\underline{\aleph}^t[\tau_a]$ and $\overline{\aleph}^t[\tau_a]$ form a bound on the admissible action space at time t, denoted as $\mathcal{A}(t)$.

$$\{\mathbf{a}^+\} = \operatorname*{argmax}_{\mathbf{a}\in\mathcal{A}(t)} ||\mathbf{a}||_p, \qquad \{\mathbf{a}^-\} = \operatorname*{argmin}_{\mathbf{a}\in\mathcal{A}(t)} ||\phi'g(\mathbf{a}^t)||_p$$
(2.23)

Given that ϕ and ϕ' are antiparallel linear maps on \mathbf{a} , the solutions of $\{\mathbf{a}^+\}$ and $\{\mathbf{a}^-\}$ constitute linear a linear optimization problem. $\{\mathbf{a}^+\}$ corresponds to the solution which exploits the maximum achievable reward at time t as expressed in Eq. (2.7), and $\{\mathbf{a}^-\}$ expresses the action conserves the minimizes the consumption of the capacity for the future. Given $\mathcal{A}(t)$, at any time t, there exists two sets $\{\mathbf{a}^+\}$, and $\{\mathbf{a}^-\}$ which either maximizes allowable reward, or maximally reduces consumption of resource \mathbf{x}_d . Let us denote $\mathbf{a}^+[\mathbf{x}_n]$ and $\mathbf{a}^-[\mathbf{x}_n]$ as the following,

$$\mathbf{a}^{+}[\mathbf{x}_{\eta}] = \operatorname*{argmax}_{\mathbf{a} \in \{\mathbf{a}^{+}\}} \langle \phi f(\mathbf{x}_{\eta}), \mathbf{a} \rangle, \qquad \mathbf{a}^{-}[\mathbf{x}_{\eta}] = \operatorname*{argmax}_{\mathbf{a} \in \{\mathbf{a}^{-}\}} \langle \phi f(\mathbf{x}_{\eta}), \mathbf{a} \rangle$$
(2.24)

In Lemma 2.1, we show that the optimal policy consists of a action, represented as a vector, corresponding to one of two sets $\{\mathbf{a}^+\}$ or $\{\mathbf{a}^-\}$, each with dimension D. A continuous action space MDP thereby reduces to a sequential discrete action decision problem, where the action space forms a finite dimension subspace with a maximum cardinality of with at most 2D.

Lemma 2.1. Finite and Bounded Action Space for the SD-MDP: Under the SD-MDP framework, for any action taken in the finite time horizon, optimal policy lies to the union of 2 subspaces, that is $\mathbf{a}^* \subset {\mathbf{a}^+} \cup {\mathbf{a}^-} \subset \mathcal{A}(t) \subseteq \mathcal{A}$, for all time steps t. The cardinality of the dimension of the optimal solution space is upper bounded by 2D. (Proof in Appendix A.1.)

Let $\tau_{\eta} \equiv {\mathbf{x}_{\eta}^{t}, \mathbf{x}_{\eta}^{t+1}, \mathbf{x}_{\eta}^{t+2}, \dots, \mathbf{x}_{\eta}^{T}}$ denote a sequence of stochastic outcomes, the expectation of which is denoted as $\mathbb{E}[\tau_{\eta}] \equiv {\mathbb{E}}[\mathbf{x}_{\eta}^{t}], \mathbb{E}[\mathbf{x}_{\eta}^{t+1}], \mathbb{E}[\mathbf{x}_{\eta}^{t+2}], \dots, \mathbb{E}[\mathbf{x}_{\eta}^{T}]$ }. We define the $\operatorname{Top}_{k}(\mathbb{E}[\tau_{\eta}])$ for a series of multidimensional vectors be defined as,

$$\operatorname{Top}_{k=T}(\tau_{\eta}) = (\mathbb{E}[\mathbf{x}_{\eta}^{k=1}], \mathbb{E}[\mathbf{x}_{\eta}^{k=2}], \mathbb{E}[\mathbf{x}_{\eta}^{k=3}], \dots, \mathbb{E}[\mathbf{x}_{\eta}^{k=T}])$$
(2.25)

Such that,

$$\phi f(\mathbb{E}[\mathbf{x}_{\eta}^{k=1}]) \succ \phi f(\mathbb{E}[\mathbf{x}_{\eta}^{k=2}]) \succ \phi f(\mathbb{E}[\mathbf{x}_{\eta}^{k=3}]) \cdots \succ \phi f(\mathbb{E}[\mathbf{x}_{\eta}^{k=T}])$$
(2.26)

Sketch of Proof: First we demonstrate the separability of $\mathbb{E}[\tau_{\eta}]$ with respect to any deterministic action sequence. The solution is therefore to find a maximizing solution for each $\mathbb{E}[\mathbf{x}_{\eta}^{t}] \in \mathbb{E}[\tau_{\eta}]$, which is possible under full information. Under incremental dynamics, $||\mathbf{a}|| \leq \bar{\Delta}_{a}$ only so many resources can be dedicated to maximizing each $\mathbb{E}[\tau_{\eta}]$, thus this boils down to an allocation problem. We show that when we majorize over $\mathbb{E}[\tau_{\eta}]$, and ϕf is a perfect orthogonal reflection of $\phi' g$, the optimal solution,

(\mathbf{a}^*), to the sequence, $\mathbb{E}[\tau_\eta]$, is an order preserving union of two sequences, one corresponding to a norm maximizing vector $\mathbf{a}^+[\mathbf{x}_\eta]$ and a norm minimizing vector $\mathbf{a}^-[\mathbf{x}_\eta]$.

Lemma 2.2. Solving for Optimal Value via Top K Allocation: Under the SD-MDP framework, the optimal value can be obtained by solving the dual problem, which involves the optimization of the value of k in $Top_k(\mathbb{E}[\tau_n] \text{ over } k \in \{1, ..., T\}$ possibilities. (Proof in Appendix A.2.)

Sketch of Proof: Given the separability of $\mathbb{E}[\tau_{\eta}]$ with respect to any deterministic action sequence. We show that when we majorize over $\mathbb{E}[\tau_{\eta}]$, to produce an ordered set of sequences, we simply select the top k vectors in this ordered list which satisfies the norm maximization constraints for the resource allocation. For the rest of the $\mathbb{E}[\tau_{\eta}]$ we allocate minimum resources within the constraints. The solution involves therefore simply finding the value of k which maximizes the value function in Eq. (2.27) subject to constraints derived from Eq. (2.20).

$$V_k(\mathbf{x}^t) = \sum_k \phi f \odot \operatorname{Top}_k(\mathbb{E}[\tau_\eta]) \odot \mathbf{a}^+[\mathbb{E}[\mathbf{x}_\eta]] + \sum_{T-k} \phi f \odot / \operatorname{Top}_k(\mathbb{E}[\tau_\eta]) \odot \mathbf{a}^-[\mathbb{E}[\mathbf{x}_\eta]]$$
(2.27)

Monte Carlo Value Estimation for the SD-MDP: Theorem 1 states that any value function estimate using N Monte Carlo estimate, will have a best case estimate error on the order of $\mathcal{O}(1/\sqrt{N})$.

Theorem 1. Upper bound on the Monte Carlo Value Estimation for the SD-MDP: For the SD-MDP abstraction partitionable MDP, the optimal policy, where the value function is upper bounded by $|\hat{V}_N - V^*(\mathbf{x})| \leq \mathcal{O}((\delta\sqrt{N})^{-1})$, with probability $1 - \delta$. Where \hat{V}_N is the Monte Carlo simulation estimate of the value function under N iterations. (Proof in Appendix A.4.)

Sketch of Proof: Any naturally evolving time series has an expected outcome which can be computed $\mathbb{E}[\tau_{\eta}]$, and thus the problem reduces to an allocation problem which can be solved using the dual formulation, in solving for $\text{Top}_k(\cdot)$ in Lemma 2.2. Via Hoeffding's inequality, we can upper bound the approximation error from Monte Carlo sampling.

3 Monte Carlo Planning with Value Function Approximation

We consider an algorithm that operates on the SD-MDP framework in the planning setting, using a value function approximator (\hat{V}_N) with a fixed budget N_s . We guarantee that for any $\hat{V}_N(\mathbf{x})$, as $N \to \infty$, the approximation error $|\hat{V}_N(\mathbf{x}) - V^*(\mathbf{x})| \to 0$, as shown by Theorem 1. $\hat{V}_N(\mathbf{x})$ depends on the simulation budget N and the parameters of the SD-MDP, θ . In the planning setting, θ is given.

We apply Monte Carlo Tree Search (MCTS), which performs tree traversal in four phases: Selection, Expansion, Simulation, and Backpropagation. In Selection, actions are chosen based on prior state exploration, guided by a selection policy such as π_{UCT} or π_M . Expansion involves taking an action in the environment and adding a new state-reward node to the tree. When an unexplored node is reached, Simulation or Rollout approximates the Q-function, $\hat{Q}(\cdot)$, based on a rollout policy $\pi_s(\cdot)$. This process continues iteratively until a termination condition is met. Finally, during Backpropagation, value and Q-function estimates are updated and propagated back up the tree, effectively propagating rewards to the root node.

UCT: Leveraging bandit algorithms like UCB, as discussed in [CM07] and [KS06], MCTS efficiently approximates $\pi^*(\mathbf{x}, a)$ by navigating the state-action space via the Upper-Confidence Tree (UCT) metric. Note $\bar{\mu}(t)$ is the reward for a trajectory, prior and after using uniform rollout.

$$\pi_{\text{UCT}}(\mathbf{x}) = \max_{a \in A} \bar{Q}(\mathbf{x}, \mathbf{a}) + c \sqrt{\frac{\log N(\mathbf{x})}{N(\mathbf{x}, \mathbf{a})}}, \quad (3.1) \qquad \bar{Q}(\mathbf{x}^t, \mathbf{a}^t) \leftarrow \bar{Q}(\mathbf{x}^t, \mathbf{a}^t) + \frac{\bar{\mu}(t) - \bar{Q}(\mathbf{x}^t, \mathbf{a}^t)}{N(\mathbf{x}^t, \mathbf{a}^t) + 1}, \quad (3.2)$$

Softmax Entropy Policies (MENTS): Nevertheless, an alternative to UCT are softmax style Boltzmann policies, where the key difference is that a stochastic selection policy is used for action selection versus a deterministic policy. This encourages exploration and has been shown to be faster to converge compared to UCT. [Gri+20] elaborates on the use of AlphaZero and UCT, offering theoretical bounds such as $\hat{\pi} \leq \bar{\pi}$, where $\hat{\pi}$ represents empirical policy, $\bar{\pi}$ is a softmaxed policy balancing an empirical Q function, and π_{θ} denotes the supervised learning policy. The effectiveness of regularized Monte Carlo tree search (MCTS), particularly in low sample count scenarios, is highlighted by [Gri+20].sample efficiency in bandit-based regret minimization algorithms. [Haz11] showed its effectiveness, achieving regret of $O(\log(T))$. The approach utilizes primal-dual space optimization, where the regularizer space simplifies computation compared to the primal space, facilitating learning updates.

Maximum Entropy Monte Carlo Planning (MENTS): [Xia+19] proposes the use of a convex regularizer, which upper-bounds the value function estimate to improve the sampling efficiency of MCTS. In Maximum entropy Monte Carlo Tree Search (MENTS), entropy is used to enhance exploration and convergence to the optimal policy for MDP planning. Furthermore, theoretical guarantees are also provided in [Xia+19] with respect to the suboptimality of the alogrithm over time. Let us define our *approximate Bellman update function*,

$$\mathcal{G}_{\mathcal{T}}(\mathbf{x}, \mathbf{a}, V(\cdot)) = \mu(\mathbf{x}, \mathbf{a}) + \sum_{\mathcal{S}(\mathbf{x}', \mathbf{a})} \left(\frac{N(\mathbf{x}')}{N(\mathbf{x}, \mathbf{a})} V(\mathbf{x}') \right)$$
(3.3)

Given a tree with visited states \mathcal{T} , and a value function estimator based on uniform rollout, $V_s(\cdot)$, in MENTS, there are two modes of updates,

$$Q_{\rm sft}(\mathbf{x}^t, \mathbf{a}^t) = \begin{cases} \mathcal{G}_{\mathcal{T}}(\mathbf{x}, \mathbf{a}, V_{\rm sft}(\cdot)) & \text{if non-terminal in } \mathcal{T} \\ \mathcal{G}_{\mathcal{T}}(\mathbf{x}, \mathbf{a}, V_s(\cdot)) & \text{else} \end{cases}$$
(3.4)

Where $\mathcal{G}_{\mathcal{T}}(\mathbf{x}, \mathbf{a}, V_{\text{sft}}(\cdot))$ represents the softmax value Q-update based on the softmax value function, and $\mathcal{G}_{\mathcal{T}}(\mathbf{x}, \mathbf{a}, V_s(\cdot))$ which is the value function estimate obtained from a uniform rollout policy. The softmax value function, $V_{\text{sft}}(\cdot)$ is updated by a regularized function of the softmax Q function $Q_{\text{sft}}(\cdot)$.

$$V_{\rm sft}(\mathbf{x}^t) \leftarrow \alpha \log \sum_{\mathbf{a} \in \mathcal{A}} \exp\left(\frac{1}{\alpha} Q_{\rm sft}(\mathbf{x}, \mathbf{a})\right) \quad (3.5) \quad \pi_{\rm M}(\mathbf{a} | \mathbf{x}) = (1 - \lambda_s) \frac{1}{\alpha} \left(Q_{\rm sft}(\mathbf{s}, \mathbf{a}) - V_{\rm sft}(\mathbf{s})\right) + \frac{\lambda_s}{|\mathbf{a}|} \tag{3.6}$$

MENTS uses a soft Bellman update for $\hat{Q}_{sft}(\cdot)$, unlike the rollout policy via UCT. [Pai+24] suggests that MENTS is not consistent, meaning it will not always converge, and there exists some MDP's where MENTS fails to converge. Decaying entropy Monte Carlo Tree Search (DENTS) [Pai+24] is an MCTS algorithm that guarantees convergence as $t \to \infty$, but it lacks strong guarantees regarding the probability of taking suboptimal actions ($P(\mathbf{a}^* \neq \mathbf{a})$), which we need for proving Theorem 2.

3.1 Value Clipping

We study the optimization problem of Monte Carlo planning under perfect information. Here we focus on simply the planning setting. From Section 2.2 we can leverage the Monte Carlo estimation properties of the VFA to enhance any MDP solver. As we draw more samples our estimate of the model parameters increases, nevertheless the MC VFA still relies on a simulation budget to estimate the value function. The SD-MDP has theoretical guarantees on its value estimate. \overline{V}^* represents the

maximum value estimate under perfect information, for actions in *hindsight*. \underline{V}^* represents the value estimate for under perfect information for the *anticipative* solution on expectation. Let us define,

$$\Delta_V(\mathbf{x}) = \overline{V}^*(\mathbf{x}) - \underline{V}^*(\mathbf{x}), \quad V^*(\mathbf{x}) \in [\underline{V}^*(\mathbf{x}), \overline{V}^*(\mathbf{x})]$$
(3.7)

Where the true solution $V^*(\mathbf{x})$ belongs somewhere between the optimal value in hindsight and the anticipative solution on expectation. We leverage $\overline{V}(\mathbf{x})^*$ and $\underline{V}(\mathbf{x})^*$ to improve the convergence rate of our planning algorithm. Therefore, given $\Delta_V(\mathbf{x})$ we can clip the outcome of any rollout policy in MCTS by $\Delta_V(\mathbf{x})$. Typically, when a new node is added to the search tree \mathcal{T} , a uniform rollout policy or neural network is implemented to provide an initial estimate of the $V^*(\cdot)$.

Guarantees on Simple Regret: We can provide a guarantee on simple regret, via extension of the work of [Xia+19] for MENTS and [KS06] in combination with the structure of the problem pertaining to the SD-MDP construct. Let simple regret be defined as,

$$\operatorname{reg}(T) = \sup_{\mathbf{x} \in \mathcal{X}} \left(V^*(\mathbf{x}) - V^T(\mathbf{x}) \right)$$
(3.8)

Where $V^T(\mathbf{x})$ is the value estimate of value function estimator after T samples. We provide high probability bounds on the simple regret for MCTS-MENTS, $\operatorname{reg}_M(T)$ and MCTS-UCT $\operatorname{reg}_U(T)$, where there exists some constant $C \in \mathbb{R}^+$ such that,

Theorem 2. Simple Regret: Given a Monte Carlo planning algorithm, \mathcal{M} , where $\tilde{p}(T) = P(\mathbf{a}^* \neq \mathbf{a})$, where $\lim_{T\to\infty} \tilde{p}(T) = 0$ and $\tilde{p}(T)$ is asymptotically bounded above by $\mathcal{O}(\frac{1}{T})$ for T samples, when running \mathcal{M} over the SD-MDP framework, the the simple regret reg(T), as defined in Eq. 3.8, is bounded by $C_k T \tilde{p}(T)$, for some value $C_k \in \mathbb{R}^+$. (Proof in Appendix A.6.)

Sketch of Proof: The proof of the simple regret bounds for MCTS-MENTS and MCTS-UCT in the SD-MDP framework begins with the identification that the optimal action \mathbf{a}^* belongs to a discrete set. The regret reg(T) is then analyzed based on the probability of action swaps, with the worst-case regret per swap denoted by $\tilde{\Delta}_a$. By quantifying the expectation of simple regret, we bound it using binomial probabilities and an upper-bounding polynomial function. As $T \to \infty$, the expectation over simple regret is shown to be upper-bounded by $\mathcal{O}(T^2 \exp(T/\log^3(T)))$ for MENTS and $\mathcal{O}(T^{1-\rho})$ for UCT. This establishes the asymptotic behaviour of simple regret, showing that the regret decreases with increasing time steps.

As a consequence of Theorem 2, when running MCTS-MENTS or MCTS-UCT over the SD-MDP framework, the simple regret, reg(T), is bounded by $\mathcal{O}(T^2 \exp(T/\log^3(T)))$ for MENTS, and $\mathcal{O}(T^{1-\rho})$ for UCT, as expressed in Eq. (3.9) and Eq. (3.10) respectively. Eq. (3.9) is a consequence of Theorem 4 from [Xia+19] and Eq. (3.10) is a consequence of Theorem 5 from [KS06]. A detailed outline of the value clipping implementation in combination with MENTS and UCT can be found in Appendix B.

$$\operatorname{reg}_{\operatorname{MENTS}}(T) \le CT^2 \exp\left(T/\log^3(T)\right) \quad (3.9) \qquad \operatorname{reg}_{\operatorname{MCT}}(T) < CT^{1-\rho} \quad (3.10)$$

4 Empirical Results

We compare the a baseline solution, solved via stochastic programming (details outlined in Appendix D.1), with that of a vanilla MCTS-MENTS and MCTS-UCT, along with that of a the MCTS algorithms enhanced with a value-clipping method as described in Section 3.1. We impose a computational constraint of the power of MCTS, such that the number of MCTS iterations $N \leq K_c (2D)^T$, $K_c = 0.1$, that is it is only possible to explore at most K_c percentage of all possible trajectories using MCTS,



Figure 3: The cost of fuel consumption (left) for various planning algorithms is shown, with the baseline being multiscenario stochastic programming (SP), compared against vanilla MCTS planning and MCTS with value clipping (VC).

before making a decision. Given this constraint, it prevents us from overpowering MCTS in such a way that would allow it to brute force search all possible combinations, and must rely on smart exploration. We solve the MCTS algorithm, with a fixed simulation budget and exploration constants. The price model is governed by a Geometric Brownian Motion. All parameters are specified in Appendix D.2

4.1 Optimal Refuelling - A Maritime Bunkering Example

Bunkering, or maritime refuelling, is a critical issue in transportation logistics focused on finding the optimal policy to refuel ships efficiently. The primary objective is to minimize overall costs, including the price of fuel, transportation costs, and any downtime for refuelling [BKP16]. Mathematical optimization techniques, like mixed integer programming, are often employed to determine the best refuelling strategy, considering factors such as ship capacity, travel distance, fuel availability, and refuelling constraints. This optimization becomes complex due to the uncertainty in fuel prices, necessitating stochastic models to represent cost variability. By addressing these challenges, shipping companies can significantly reduce operational expenses and enhance logistical efficiency. We formulate the problem within the SD-MDP framework, which is suitable for the liner bunkering problem considering stochastic fuel price transitions and deterministic fuel consumption. The capacity constraints, governed by the ship's fuel tank, are covered in (D4). The ship must follow a set route, where the incremental action dynamics from (D3) are determined by the distance between each port-of-call. Ship refuel levels are always positive, and the fuel tank cannot be negative, satisfying (D1). The reward dynamics follow the straightforward linear structure of (D2), with a preference for more immediate cost savings, satisfying (D5) (A detailed description and formulation of this problem is presented in Appendix D).

5 Conclusion

Certain stochastic decision processes in optimal control and economics demonstrate remarkable efficacy when coupled with specific assumptions and advanced approximation techniques, particularly in value approximation. Disentangling the causal structure of Markov Decision Processes (MDP's) not only yields unique insights but also significantly simplifies problem-solving. However, traditional methods for addressing resource allocation problems often struggle to seamlessly integrate with Monte Carlo planning techniques. In response, we propose the innovative SD-MDP framework, offering a versatile modeling approach alongside robust theoretical guarantees. Inspired by fundamental energy conservation principles, we introduce a novel resource-utility exchange model, which not only enhances computational efficiency but also reduces planning problem complexity. Moreover, we showcase the effective disentanglement of Monte Carlo sampling from the planning process within the SD-MDP framework, facilitating the derivation of Monte Carlo value estimates for both upper and lower bounds of the MDP problem at each state. By seamlessly integrating this approach into Monte Carlo Tree Search (MCTS), we not only establish theoretical guarantees but also provide empirical evidence of its efficacy in addressing well-known problems in economic logistics. As future avenues, we envision extending this tool to tackle a broader spectrum of economic problems while delving deeper into the learning setting, where the parameters of the MDP must be learned rather than given.

References

- [AM07] Brian DO Anderson and John B Moore. *Optimal control: linear quadratic methods*. Courier Corporation, 2007.
- [BDG00] Craig Boutilier, Richard Dearden, and Moisés Goldszmidt. "Stochastic dynamic programming with factored representations". In: Artificial intelligence 121.1-2 (2000), pp. 49–107.
- [Ber11] Dimitri P Bertsekas. "Approximate policy iteration: A survey and some new methods". In: Journal of Control Theory and Applications 9.3 (2011), pp. 310–335.
- [BJS21] Ioana Bica, Daniel Jarrett, and Mihaela van der Schaar. "Invariant causal imitation learning for generalizable policies". In: Advances in Neural Information Processing Systems 34 (2021), pp. 3952–3964.
- [BKP16] Berit Dangaard Brouer, Christian Vad Karsten, and David Pisinger. "Big data optimization in maritime logistics". In: Big data optimization: Recent developments and challenges. Springer, 2016, pp. 319–344.
- [CF12] Giuseppe C Calafiore and Lorenzo Fagiano. "Robust model predictive control via scenario optimization". In: *IEEE Transactions on Automatic Control* 58.1 (2012), pp. 219–224.
- [CM07] Pierre-Arnaud Coquelin and Rémi Munos. "Bandit Algorithms for Tree Search". In: CoRR abs/cs/0703062 (2007). arXiv: cs/0703062. URL: http://arxiv.org/abs/cs/0703062.
- [Day72] Peter W Day. "Rearrangement inequalities". In: Canadian Journal of Mathematics 24.5 (1972), pp. 930–943.
- [DV04] Daniela Pucci De Farias and Benjamin Van Roy. "On constraint sampling in the linear programming approach to approximate dynamic programming". In: *Mathematics of operations research* 29.3 (2004), pp. 462–478.
- [Fel91] William Feller. An introduction to probability theory and its applications, Volume 2. Vol. 81. John Wiley & Sons, 1991.
- [FSM10] Amir-massoud Farahmand, Csaba Szepesvári, and Rémi Munos. "Error propagation for approximate policy and value iteration". In: Advances in Neural Information Processing Systems 23 (2010).
- [Gen+20] Sinong Geng et al. "Deep PQR: Solving inverse reinforcement learning using anchor actions". In: International Conference on Machine Learning. PMLR. 2020, pp. 3431–3441.
- [Git79] John C Gittins. "Bandit processes and dynamic allocation indices". In: Journal of the Royal Statistical Society Series B: Statistical Methodology 41.2 (1979), pp. 148–164.
- [Gri+20] Jean-Bastien Grill et al. "Monte-Carlo tree search as regularized policy optimization". en. In: (2020).
- [Hau79] Mark P Haugan. "Energy conservation and the principle of equivalence". In: Annals of Physics 118.1 (1979), pp. 156–186.

- [Haz11] E Hazan. The convex optimization approach to regret minimization, Optimization for Machine Learning (S. Sra, S. Nowozin, and S. Wright, eds.) 2011.
- [HLP52] G.H. Hardy, J.E. Littlewood, and G. Pólya. Inequalities. Cambridge Mathematical Library. Cambridge University Press, 1952. ISBN: 9780521358804. URL: https://books.google. com.au/books?id=t1RCSP8YKt8C.
- [KS06] Levente Kocsis and Csaba Szepesvári. "Bandit Based Monte-Carlo Planning". In: Machine Learning: ECML 2006. Ed. by Johannes Fürnkranz, Tobias Scheffer, and Myra Spiliopoulou. Berlin, Heidelberg: Springer Berlin Heidelberg, 2006, pp. 282–293. ISBN: 978-3-540-46056-5.
- [Kus90] Harold J Kushner. "Numerical methods for stochastic control problems in continuous time". In: SIAM Journal on Control and Optimization 28.5 (1990), pp. 999–1048.
- [LMT22] Yangyi Lu, Amirhossein Meisami, and Ambuj Tewari. "Efficient reinforcement learning with prior causal knowledge". In: Conference on Causal Learning and Reasoning. PMLR. 2022, pp. 526–541.
- [Pai+24] Michael Painter et al. "Monte Carlo Tree Search with Boltzmann Exploration". In: Advances in Neural Information Processing Systems 36 (2024).
- [Pow+05] Warren B Powell et al. "Approximate dynamic programming for high dimensional resource allocation problems". In: *Proceedings. 2005 IEEE International Joint Conference on Neural Networks, 2005.* Vol. 5. IEEE. 2005, pp. 2989–2994.
- [Sil+17] David Silver et al. "Mastering the game of go without human knowledge". In: *Nature* 550.7676 (2017), pp. 354–359.
- [Tod09] Emanuel Todorov. "Efficient computation of optimal actions". In: *Proceedings of the na*tional academy of sciences 106.28 (2009), pp. 11478–11483.
- [WML13] Shuaian Wang, Qiang Meng, and Zhiyuan Liu. "Bunker consumption optimization methods in shipping: A critical review and extensions". In: Transportation Research Part E: Logistics and Transportation Review 53 (2013), pp. 49–62.
- [WW11] Jean-Paul Watson and David L Woodruff. "Progressive hedging innovations for a class of stochastic mixed-integer resource allocation problems". In: *Computational Management Science* 8 (2011), pp. 355–370.
- [Xia+19] Chenjun Xiao et al. "Maximum entropy monte-carlo planning". In: Advances in Neural Information Processing Systems 32 (2019).
- [YNL12] Zhishuang Yao, Szu Hui Ng, and Loo Hay Lee. "A study on bunker fuel management for the shipping liner services". In: Computers & Operations Research 39.5 (2012), pp. 1160– 1172.
- [ZBD10] Brian D Ziebart, J Andrew Bagnell, and Anind K Dey. "Modeling Interaction via the Principle of Maximum Causal Entropy". en. In: (2010).
- [ZY03] Xun Yu Zhou and George Yin. "Markowitz's mean-variance portfolio selection with regime switching: A continuous-time model". In: SIAM Journal on Control and Optimization 42.4 (2003), pp. 1466–1482.

A Proofs and Theory

A.1 Proof of Lemma 2.1

Finite and Bounded Action Space for the SD-MDP: Under the SD-MDP framework, when $\phi f(\cdot)$ is a perfect antisymetric reflection of $\phi f(\cdot)$, the optimal policy belongs to the union of 2 subspaces, that is $\mathbf{a}^* \subset {\mathbf{a}^+} \cup {\mathbf{a}^-} \subset \mathcal{A}$, for all time steps t. The cardinality of the dimension of the optimal solution space is upper bounded by 2D where D is the dimension of \mathbf{a} .

Proof. We use proof by induction. Suppose we start at any time t, and our state is in \mathbf{x}_d^t . The reward function,

$$\mu(\mathbf{x}^t, \langle \mathbf{a} \rangle = \phi f(\mathbf{x}_n^t), \, \mathbf{a} \rangle \tag{A.1}$$

To remind the reader, we denote $\{a^+\}$ and $\{a^-\}$ as the following,

$$\{\mathbf{a}^+\} = \operatorname*{argmax}_{\mathbf{a}\in\mathcal{A}(t)} ||\mathbf{a}||_p, \qquad \{\mathbf{a}^-\} = \operatorname*{argmax}_{\mathbf{a}\in\mathcal{A}(t)} ||\mathbf{x}_d^t + \phi' g(\mathbf{a}^t)||_p$$
(A.2)

Given $\mathcal{A}(t)$, at any time t, there exists two sets $\{\mathbf{a}^+\}$, and $\{\mathbf{a}^-\}$ which either maximizes allowable reward, or maximally reduces consumption of \mathbf{x}_d . Let us denote $\mathbf{a}^+[\mathbf{x}_\eta]$ and $\mathbf{a}^-[\mathbf{x}_\eta]$ as the following,

$$\mathbf{a}^{+}[\mathbf{x}_{\eta}] = \underset{\mathbf{a} \in \{\mathbf{a}^{+}\}}{\operatorname{argmax}} \langle \phi f(\mathbf{x}_{\eta}), \mathbf{a} \rangle, \qquad \mathbf{a}^{-}[\mathbf{x}_{\eta}] = \underset{\mathbf{a} \in \{\mathbf{a}^{-}\}}{\operatorname{argmax}} \langle \phi f(\mathbf{x}_{\eta}), \mathbf{a} \rangle$$
(A.3)

We know that the dimension of $|\mathbf{a}|$, $|\mathbf{x}_d|$, and $|\mathbf{x}_\eta|$ are equal, denoted as D. From the fundamental theorem of linear programming there can be at most D solutions at the vertices of the convex hulls in Eq. (A.3). Depending on the scaling property of $\phi(\cdot)$, the sets $\mathbf{a}^+[\mathbf{x}_\eta]$ and $\mathbf{a}^-[\mathbf{x}_\eta]$ could partially overlap or be disjoint, nevertheless the number of unique solutions would to the either maximixation problem would be at most D.

Given that ϕf and $\phi' g$ are antiparallel homothetic linear transformations on **a**, we presume the solutions of $\{\mathbf{a}^+\}$ and $\{\mathbf{a}^-\}$ to be disjoint sets. Where $\mathbf{a}^+[\mathbf{x}_\eta]$ is the action which myopically maximize the reward obtained at time t, and $\mathbf{a}^-[\mathbf{x}_\eta]$ is the action which maximizes (or conserves) the potential for the future. In fact, when p = 1 the solution to \mathbf{a}^+ is unique due when the feasible region is bounded, and the objective function is linear and convex in the feasible region.

Value function w.r.t. time: Under perfect information, we can naturally compute the expectation over τ_{η} , leading to the expected stochastic outcome at each discrete time step, denoted as $\mathbb{E}[\tau_{\eta}] \equiv \{\mathbf{x}_{\eta}^{t}, \mathbb{E}[\mathbf{x}_{\eta}^{t+1}], \mathbb{E}[\mathbf{x}_{\eta}^{t+2}], \dots, \mathbb{E}[\mathbf{x}_{\eta}^{T}]\}$. This evolution transitions independently w.r.t. to any action sequence $(\mathbf{a}^{t}, \dots, \mathbf{a}^{T})$, due to the properties of the SD-MDP. Thus, for any stochastic trajectory τ_{η} , constituting a single scenario outcome, there exists a solution which optimizes the cumulative rewards from t to T.

Next let us denote the top k elements of $\mathbb{E}[\tau_{\eta}]$ a set of vectors with size k, as $\operatorname{Top}_{k}(\tau_{\eta})$. Should the dimension of \mathbf{x}_{η}^{t} be greater than 1, in order to compare various values of \mathbf{x}_{η}^{t} , we majorize over the sequence provided by $\phi f \odot \mathbb{E}[\tau_{\eta}]$ to ensure a ranking,

$$\operatorname{Top}_{k=T}(\tau_{\eta}) = (\mathbb{E}[\mathbf{x}_{\eta}^{k=1}], \mathbb{E}[\mathbf{x}_{\eta}^{k=2}], \mathbb{E}[\mathbf{x}_{\eta}^{k=3}], \dots, \mathbb{E}[\mathbf{x}_{\eta}^{k=T}])$$
(A.4)

Such that,

$$\phi f(\mathbb{E}[\mathbf{x}_{\eta}^{k=1}]) \succ \phi f(\mathbb{E}[\mathbf{x}_{\eta}^{k=2}]) \succ \phi f(\mathbb{E}[\mathbf{x}_{\eta}^{k=3}]) \cdots \succ \phi f(\mathbb{E}[\mathbf{x}_{\eta}^{k=T}])$$
(A.5)

The $\text{Top}_k(\tau_\eta)$ operator will truncate over this ordered sequence to only include the top k elements. And should we generalize for any $t \in T$, the optimal value function can be expressed as,

$$V_k(\mathbf{x}^t) = \sum_k \phi f \odot \operatorname{Top}_k(\mathbb{E}[\tau_\eta]) \odot \mathbf{a}^+[\mathbb{E}[\mathbf{x}_\eta]] + \sum_{T-k} \phi f \odot / \operatorname{Top}_k(\mathbb{E}[\tau_\eta]) \odot \mathbf{a}^-[\mathbb{E}[\mathbf{x}_\eta]]$$
(A.6)

Let sequence $(\mathbf{a}^+) \equiv (\mathbf{a}^+[\mathbf{x}^1_{\eta}], \dots, \mathbf{a}^+[\mathbf{x}^t_{\eta}])$, and $(\mathbf{a}^-) \equiv (\mathbf{a}^-[\mathbf{x}^1_{\eta}], \dots, \mathbf{a}^-[\mathbf{x}^t_{\eta}])$. Let $\tilde{\mathbf{a}} \equiv (\mathbf{a}^+)\tilde{\cup}(\mathbf{a}^-)$, where $\tilde{\cup}$ represents an order preserving union of sequences. As an aside, we can also express Eq. (A.6) therefore as,

$$V_k(\mathbf{x}^t) = \sum_T \phi f \odot \operatorname{Top}_{k=T}(\mathbb{E}[\tau_\eta]) \odot \tilde{\mathbf{a}}$$
(A.7)

Suppose that the optimal policy consists of the of the expression in Eq. (A.6), we demonstrate that there exists no way of achieving a higher value should k be optimal.

- Under the norm constraints, suppose a reduction in a vector belonging to (\mathbf{a}^+) occurs, and is transferred to a vector in (\mathbf{a}^-) , the maximization of $V_k(\mathbf{x}^t)$ would yield a lesser result. This is due to the explicit assumption that ϕf is a strict orthogonal reflection of $\phi' g$.
- By definition the sequence $\tilde{\mathbf{a}}$ is majorized, and by extension of the Hardy-Littlewold-Polya Theorem [HLP52] [Day72], the sum of Hadmard product of any ranked majorized sequence with another ranked majorized sequence is always maximizing. We can infer that by swapping any element from (\mathbf{a}^+) with (\mathbf{a}^-) would result in a sub-optimal value.

We know that the dimension of $|\mathbf{a}|$, $|\mathbf{x}_d|$, and $|\mathbf{x}_\eta|$ are equal of dimension D, and by Eq. (A.6), the solution over trajectory $\mathbb{E}[\tau_\eta]$ consists of either $\mathbf{a}^+[\mathbf{x}^t_\eta]$ or $\mathbf{a}^-[\mathbf{x}^t_\eta]$ at each time interval t. Therefore the structure of the optimal policy posits that the optimal solution will fall into any of the two sets, $\mathbf{a}^+[\mathbf{x}_\eta] \in {\mathbf{a}^+}$ or $\mathbf{a}^-[\mathbf{x}_\eta] \in {\mathbf{a}^-}$ both with dimension D, and therefore the maximum number of unique solutions is 2D, when ${\mathbf{a}^+}$ and ${\mathbf{a}^-}$ are disjoint.

A.2 Proof of Lemma 2.2

Solving for Optimal Value via Top K Allocation: The optimal value problem can be solved, by solving the dual problem, selecting the value of k in $\text{Top}_k(\mathbb{E}[\tau_n] \text{ over } k \in \{1, \ldots, T\}$ possibilities.

Proof. As the $\operatorname{Top}_k(\tau_\eta)$ operator truncates over an ordered sequence to only include the top k elements, we generalize for any $t \in T$, the optimal value function. Let $||\mathbf{a}^+||_p$ and $||\mathbf{a}^-||_p$ be shorthand for $||\phi'g(\mathbf{a}^+[\mathbf{x}_\eta])||_p$ and $||\phi'g(\mathbf{a}^-[\mathbf{x}_\eta])||_p$ respectively, and these are norm equivalent for any value of \mathbf{x}_η when considering $||\mathbf{a}^+||_p$ or $||\mathbf{a}^-||_p$ specifically. The optimal value function can be expressed as,

$$V^{*}(\mathbf{x}^{t}) = \max_{k \in \{1, \dots, T\}} V_{k}(\mathbf{x}^{t})$$
(A.8)

where,
$$\underline{A} \leq \sum_{k} \left\| \mathbf{a}^{+} \right\|_{p} + (T - K) ||\mathbf{a}^{-}||_{p} \leq \bar{A}$$
 (A.9)

Next, the application of the $\operatorname{Top}_k(\cdot)$ constitutes the *non-anticipative* solution for the planning problem under perfect information. Under unconstrained incremental dynamics, one could set $||\mathbf{a}^+||_p = \overline{A}$, and K = 1, as the trivial solution, which represents the optimal stopping problem. But suppose incremental dynamics do exist, and $\underline{\Delta}_a \leq ||\mathbf{a}||_p \leq \overline{\Delta}_a$, then because $f(\cdot)$ is a strictly monotonic function the optimizing solution to Eq. (A.8) occurs at $\{\mathbf{a}^+\} \cup \{\mathbf{a}^-\}$.

Solving for K: We propose the dual problem from the primal problem in Eq. (A.8). K intuitively controls the maximum capacity allowable. Let us postulate and we seek to maximize K,

$$\frac{\underline{A}}{T} \le \frac{K}{T} (||\mathbf{a}^+||_p - ||\mathbf{a}^-||_p) + T ||\mathbf{a}^-||_p \le \frac{\overline{A}}{T}$$
(A.10)

Given the fixed span $||\mathbf{a}^+||_p - ||\mathbf{a}^-||_p$, we therefore can compute K from Eq. (A.10), where K and $||\mathbf{a}^-||_p$ are free variables subject to certain constraints, and $||\mathbf{a}^+||_p$ and T are given. Next, the application of the $\text{Top}_k(\cdot)$ constitutes the *non-anticipative* solution for the planning problem under perfect information. We propose the dual problem from the primal problem in Eq. (A.8),

$$K^* = \underset{K \in \{1, \dots, T\}}{\operatorname{argmax}} K \tag{A.11}$$

where, $K(||\mathbf{a}^+||_p - ||\mathbf{a}^-||_p) + T^2 ||\mathbf{a}^-||_p \le \bar{A}$ (A.12)

$$K(||\mathbf{a}^+||_p - ||\mathbf{a}^-||_p) + T^2||\mathbf{a}^-||_p \ge \underline{A}$$
(A.13)

To determines the maximizing K, we simply fix K, and search for a maximizing solution to the linear program represented in Eq. (A.11). This LP formulation, assuming the constraints produce a feasible set, will generate one unique solution for $||\mathbf{a}^+||_p$, and $||\mathbf{a}^-||_p$.

A.3 Technical Note on Concentration Bounds

Given any sub-Gaussian random variable X_i , we can express this inequality,

$$P\left(\sum_{i=1}^{n} X_{i} \ge t\right) \le 2\exp\left(-\frac{ct^{2}}{\sum_{i=1}^{n} \|X_{i}\|_{\psi_{2}}^{2}}\right)$$
(A.14)

Where $||X_i||_{\psi_2}$ is the sub-Gaussian norm of X_i , defined as, $||X||_{\psi_2} := \inf \left\{ c \ge 0 : \mathbb{E} \left(e^{X^2/c^2} \right) \le 2 \right\}$. The sub-Gaussian norm of a random variable X is defined as: $|X|_{\psi_2} = \inf \left\{ c > 0 : \mathbb{E} \left[e^{X^2/c^2} \right] \le 2 \right\}$ The sub-Gaussian norm is $|X|_{\psi_2} = \frac{b-a}{2}$ The variance proxy is $\sigma^2 = \frac{(b-a)^2}{4}$

The sub-Gaussian norm is
$$|X|_{\psi_2} = \frac{b-a}{2}$$
 The variance proxy is σ^2
 $\sum_{i=1}^n (b_i - a_i)^2 = 4 \sum_{i=1}^n \sigma_i^2$

Relating Norm and Variance: For a bounded random variable X with $a \le X \le b$, the sub-Gaussian norm is related to the variance proxy $\sigma^2 = \frac{(b-a)^2}{4}$ as 2: $|X|_{\psi_2} = \sqrt{\sigma^2} = \frac{b-a}{2}$.

A.4 Proof of Theorem 1

Upper bound on the Monte Carlo Value Estimation for the SD-MDP: For the SD-MDP abstraction partitionable MDP, the optimal policy, where the value function is upper bounded by $|\hat{V}_N - V^*(\mathbf{x})| \leq O((\delta \sqrt{N})^{-1})$, with probability $1 - \delta$. Where \hat{V}_N is the Monte Carlo simulation estimate of the value function under N iterations.

Proof. For each stochastic trajectory τ_{η} , we denote as as a sequence (\cdot) ,

$$\tau_{\eta} \equiv (\mathbf{x}_{\eta}^{t=1}, \mathbf{x}_{\eta}^{t=2}, ..., \mathbf{x}_{\eta}^{T})$$
(A.15)

We define a sequence of actions as $\tau_{a|\eta}$,

$$\tau_{a|\eta} \equiv (\mathbf{a}^{t=1}, \mathbf{a}^{t=2}, ..., \mathbf{a}^T) \tag{A.16}$$

There must exists at least one optimal solution that for the optimal policy π^* , which we also denote as a sequence $\tau^*_{a|\eta}$, where $\tau^*_{a|\eta}$ is a sequence of deterministic actions, which yield the optimal solution for each trajectory τ_{η} . Given a trajectory runs from $1 \to T$, and as consequence of Lemma 2.1, there exists at most $(2D)^T$ possibly optimal permutations of $\tau^*_{a|\eta}$, where D is the dimension of the action space \mathcal{A} . Let $\tau^*_{a|\eta}$ denote an optimal solution such that,

$$\tau_{a|\eta}^{*} = \operatorname*{argmax}_{a \in \mathcal{A}} \sum_{x_{\eta}^{t} \in \tau_{\eta}} \mathbf{a}^{t} \cdot \phi f(\mathbf{x}_{\eta}^{t}), \quad s.t. \quad \underline{A} \le \sum_{t=1}^{T} ||\mathbf{a}^{t}||_{p} \le \bar{A}$$
(A.17)

Where we know x_{η}^{t} is a stochastic variable belonging to a trajectory τ_{η} . Based on the *recency* preference assumption, illustrated by Eq. (2.10).

$$\mathbf{x}_{\eta}^{t} = \mathbf{x}_{\eta}^{t+\Delta} \implies \mathbf{x}_{\eta}^{t} \succ \mathbf{x}_{\eta}^{t+\Delta}, \quad \Delta \in \mathbb{Z}$$
(A.18)

Under this assumption, for each τ_{η} there must be only one unique $\tau_{a|\eta}^*$, constituting a surjection from $\tau_{\eta} \mapsto \tau_{a|\eta}^*$.

$$\tau_{\eta} \mapsto \tau_{a|\eta}^* \tag{A.19}$$

Since by Lemma 2.1 we have a finite ation space per discrete time period, in finite time the cardinality of $\tau_{a|\eta}^*$ is finite. Nevertheless, the cardinality of τ_{η} is infinite. Thus by the pigeonhole principle, we can conclude that a $\tau_{a|\eta}^*$ can inversely map to potentially more than one τ_{η} , we denote this set of corresponding sequences as $\tilde{\tau}_{\eta}$.

$$\tau_{\eta} \mapsto \tau_{a|\eta}^*, \quad \tilde{\tau}_{\eta} \leftrightarrow \tau_{a|\eta}^*$$
(A.20)

Furthermore, let $\{\tau_{a|\eta}^*\}$ denote all valid sequences of $\tau_{a|\eta}^*$ corresponding to τ_{η} , by consequence of Lemma 2.1, the cardinality of the injective map's image $\{\tau_{a|\eta}^*\}$ bounded by,

$$1 \le \{\tau_{a|\eta}^*\} \le (2D)^T \tag{A.21}$$

Most crucially, $\{\tilde{\tau}_{\eta}\}$ denotes a set of sequences, of which are *indifferent* from each other in terms of their corresponding optimal policy $\tau_{a|\eta}^*$, constituting the optimal solution to the trajectory, for $\mathbf{x}_{\eta} \subset \mathbb{R}^{D}$. Although given parameters of stochastic generator θ , the probability of observing τ_{η} is infinitesimal, the probability of $\tau_{\eta} \in \{\tilde{\tau}_{\eta}\}$ is quantifiable, given the functional form and parameters of the stochastic generator. That is,

$$P_{\theta}(\tau_{\eta} \in \{\tilde{\tau}_{\eta}\} | \mathcal{F}_t) > 0 \tag{A.22}$$

Let the operator $\{\tau_{\eta}\}$ define the set of all sequence of trajectories τ_{η} , we define an operator $\mathcal{Q}(\cdot)$: $\{\tau_{\eta}\} \mapsto \{\tilde{\tau}_{\eta}\}$ which partitions $\{\tau_{\eta}\}$ into into *indifference sets*, $\tilde{\tau}_{\eta}$. In fact, from the relation in Eq. (A.20) and Lemma 2.1 the cardinality of this partition function can be deduced as,

$$1 \le |\mathcal{Q}(\{\tau_{\eta}\})| \le {T \choose k} D^T \le (2D)^T$$
(A.23)

Where $k \leq T$ is the capacity maximizing number governed by solution to the dual problem posed in Eq. (A.8). Let $\{\mathbf{x}_{\eta}^{t \to T}\}$ denote the set of all possible trajectories for \mathbf{x}_{η} between t to T. The expectation thereof for $\mathbb{E}[\{\mathbf{x}_{\eta}^{t \to T}\}]$ can be calculated via stochastic calculus, or approximated by simulation. Given two sequences of vectors, $\mathbf{x}^{t \to T}$ and $\mathbf{y}^{t \to T}$, let us define a an operator $\langle\langle \cdot, \cdot \rangle \rangle$ as,

$$\langle \langle \mathbf{x}^{t \to T}, \mathbf{y}^{t \to T} \rangle \rangle = \sum_{i=1}^{T} \langle \mathbf{x}_i, \mathbf{y}_i \rangle$$
 (A.24)

We can now examine the value function,

$$V^*(\mathbf{x}^t) = \mathbb{E}\Big[\langle\langle \phi f(\mathbf{x}^{t \to T}_{\eta}), \tau^*_{a|\eta} \rangle\rangle\Big]$$
(A.25)

$$= \int_{\tau_{\eta}} P_{\theta}(\tau_{\eta}|\mathcal{F}_{t}) \left\langle \left\langle \phi f(\tau_{\eta}), \tau_{a|\eta}^{*} \right\rangle \right\rangle d\tau_{\eta}, \quad 1 < |\mathcal{Q}(\{\tau_{\eta}\})| < (2D)^{T}$$
(A.26)

$$\leq \sum_{\mathcal{Q}(\{\tau_{\eta}\})} P_{\theta}(\tau_{\eta} \in \{\tilde{\tau}_{\eta}\} | \mathcal{F}_{t}) \ \langle \langle \ \bar{\tau}_{s}, \phi f(\tau_{a|\eta}^{*}) \rangle \rangle, \quad 1 < |\mathcal{Q}(\{\tau_{\eta}\})| < (2D)^{T}$$
(A.27)

Eq. (A.25) represents the optimal value function as the expectation over the reward/cost of the unravelling of the stochastic partition of the SD-MDP, $\phi f(\mathbf{x}_{\eta}^{t \to T})$, assuming an optimal deterministic policy $\tau_{a|\eta}^*$ in adhered to by the agent. Eq. (A.26) expresses the value function as an integral over the probability of each possible outcome $\phi f(\tau_{\eta})$. In principle, $\{\mathbf{x}_{\eta}^{t \to T}\}$ can be partitioned in to indifference sets $\{\tilde{\tau}_{\eta}\}$, via the $\mathcal{Q}(\cdot)$ partition operator, where each indifference maps to a unique $\tau_{a|\eta}^*$. And thus we can make the expectation in Eq. (A.25) decomposable. This presents a key advantage as any upper bounding value function $\bar{V}^*(\mathbf{x}^t) \geq V^*(\mathbf{x}^t)$ can be expressed as the summation of the product of two terms.

$$V^{*}(x^{t}) \leq \bar{V}^{*}(x^{t}) = \sum_{\mathcal{Q}(\{\tau_{\eta}\})} \bar{g}_{\tau_{\eta}}(\{\tilde{\tau}_{\eta}\}) \ \bar{g}_{s}(\tau_{a|\eta}^{*})$$
(A.28)

where,
$$\bar{g}_{\tau_{\eta}}(\cdot) \ge P_{\theta}(\tau_{\eta} \in \{\tilde{\tau}_{\eta}\} | \mathcal{F}_{t}), \quad \forall \tau_{\eta} \in \{\tilde{\tau}_{\eta}\}$$
 (A.29)

$$\bar{g}_s(\cdot) \ge \langle \langle \phi f(\tau_\eta), \tau_{a|\eta}^* \rangle \rangle, \quad \forall \tau_{a|\eta}^* \in \tau_a$$
(A.30)

Finding the upper-bound to $\bar{V}^*(x^t)$ is now decomposed into a problem involving finding an two tight upper bounding functions $\bar{g}_{\tau_{\eta}}(\cdot)$ and $\bar{g}_s(\cdot)$. For *incremental action dynamics* as defined for the SD-MDP framework, there exists a limit on the capacity of actions as defined in Eq. (2.10).

If we define an operator over $\{\tau_{\eta}\}$ such that,

$$\operatorname{Top}_{k}(\tau_{\eta}): \{\tau_{\eta}\} \times K \mapsto \mathbb{R}^{|\mathcal{X}| \times T}, \quad \text{where, } K \in \mathbb{Z}^{+}$$
(A.31)

Where the image, $\operatorname{Im}(\operatorname{Top}_k(\cdot)) \in \mathbb{R}^{|\mathcal{X}| \times T}$. We know that the $\operatorname{Top}_k(\tau_\eta)$ computation can occur with complexity $\mathcal{O}(T)$, as it involves sorting over elements. Therefore, we can denote an expression for

 $\langle \langle \phi f(\tau_{\eta}), \tau_{a|\eta}^* \rangle \rangle$ by writing,

$$\langle\langle \phi f(\tau_{\eta}), \tau_{a|\eta}^{*} \rangle\rangle = \max_{\mathbf{a} \in \{\mathbf{a}^{+}\}} \langle\langle \phi f(\operatorname{Top}_{K}(\{\tau_{\eta}\})), \mathbf{a} \rangle\rangle + \max_{\mathbf{a} \in \{\mathbf{a}^{-}\}} \langle\langle \phi f(/\operatorname{Top}_{K}(\{\tau_{\eta}\})), \mathbf{a} \rangle\rangle, \quad \text{where, } K = \left\lfloor \frac{A}{T} \right\rfloor$$
(A.32)

Note that Eq. (A.32) is equivalent to Eq. (A.6) from Lemma 2.2, and $\tau_{\eta} \in {\tilde{\tau}_{\eta}}$. So now fundamentally, we can express the computation of the value function as a decomposition,

$$V^*(\mathbf{x}^t) = \langle \langle \mathbb{E}[\phi f(\tau_\eta)], \mathbb{E}[\tau^*_{a|\eta}] \rangle \rangle$$
(A.33)

$$= \mathbb{E}[\langle \langle \phi f(\tau_{\eta}), \tau_{a|\eta}^* \rangle \rangle] \tag{A.34}$$

$$= \max_{\mathbf{a} \in \{\mathbf{a}^+\}} \mathbb{E}[\langle \phi f(\operatorname{Top}_K(\{\tau_\eta\})), \mathbf{a} \rangle \rangle] + \max_{\mathbf{a} \in \{\mathbf{a}^-\}} \mathbb{E}[\langle \phi f(/\operatorname{Top}_K(\{\tau_\eta\})), \mathbf{a} \rangle \rangle]$$
(A.35)

From Eq. (A.35) we can see that an approximation of $V^*(\mathbf{x}^t)$ can be computed by simulating over the stochastic trajectory τ_{η} , then applying a deterministic function, $\text{Top}_K(\cdot)$, over it.

Bounding the Approximation Error: To bound the expression on Eq. (A.35) we can take advantage of the $Q(\cdot)$ operator.

$$V^{*}(\mathbf{x}^{t}) = \sum_{\mathcal{Q}(\tau_{\eta})} P_{\theta}(\tau_{\eta} \in \tilde{\tau}_{\eta} | \mathcal{F}_{t}) \left(\max_{\mathbf{a} \in \{\mathbf{a}^{+}\}} \left\langle \left\langle \phi f(\mathbb{E}[\operatorname{Top}_{K}(\tilde{\tau}_{\eta})]), \mathbf{a} \right\rangle \right\rangle + \max_{\mathbf{a} \in \{\mathbf{a}^{-}\}} \left\langle \left\langle \phi f(\mathbb{E}[/\operatorname{Top}_{K}(\tilde{\tau}_{\eta})]), \mathbf{a} \right\rangle \right\rangle \right)$$
(A.36)

The next major challenge likes in the computation of $P_{\theta}(\tau_{\eta} \in {\{\tilde{\tau}_{\eta}\}}|\mathcal{F}_t)$ which is the probability that any trajectory τ_{η} belongs to the indifference set ${\{\tilde{\tau}_{\eta}\}}$, given parameters of the stochastic generator θ and filtration \mathcal{F}_t . Nevertheless, this formulation allow us to separate the reward outcome, which is deterministically computable from the probability of it occurring. To compute the conditional expectation of $\mathbb{E}[\operatorname{Top}_K(\tilde{\tau}_{\eta})]$, we can apply Bayes rule to conditional expectations and obtain a closed from expression for $\mathbb{E}[\operatorname{Top}_K(\tilde{\tau}_{\eta})]$ in Eq. (A.37).

$$\mathbb{E}[\operatorname{Top}_{K}(\tilde{\tau}_{\eta})] = \frac{1}{P(\tau_{\eta} \in \tilde{\tau}_{\eta})} \int_{\tau_{\eta} \in \tilde{\tau}_{\eta}} \operatorname{Top}_{K}(\tilde{\tau}_{\eta}) \ \mathbb{1}[\tau_{\eta} \in \tilde{\tau}_{\eta}] \, d\tau_{\eta}$$
(A.37)

Therefore, we can then apply a Monte Carlo approach to solve the problem of value estimation. But key advantages are imposed, first is *hindsight* optimality. From Eq. (A.36) we can solve an optimal policy using the $\text{Top}_K(\cdot)$ operator over τ_η because there exists no causal relationship between action and state transition, as defined in the SD-MDP dynamic. We also know, that every trajectory has a unique deterministic optimal value outcome by the relation in Eq. (A.20). The same argument applies to $\mathbb{E}[/\text{Top}_K(\tilde{\tau}_\eta)]$. Moving forward, for convienience, let us define,

$$\mathcal{H}(\tilde{\tau}_{\eta}) \equiv \max_{\mathbf{a} \in \{\mathbf{a}^+\}} \left\langle \left\langle \phi f(\mathbb{E}[\operatorname{Top}_K(\tilde{\tau}_{\eta})]), \mathbf{a} \right\rangle \right\rangle + \max_{\mathbf{a} \in \{\mathbf{a}^-\}} \left\langle \left\langle \phi f(\mathbb{E}[/\operatorname{Top}_K(\tilde{\tau}_{\eta})]), \mathbf{a} \right\rangle \right\rangle$$
(A.38)

We can see that $\mathcal{H}(\tilde{\tau}_{\eta})$ serves as a deterministic function for each input $\tilde{\tau}_{\eta}$. As we know that $\mathcal{Q}(\cdot)$ will produce at most $(2D)^T$ partitions of the trajectory space $\{\tau_{\eta}\}$, we can treat this as the approximation of a multinomial distribution via MC. Let our estimator simply be,

$$\hat{P}^{N}_{\theta}(\tau_{\eta} \in \tilde{\tau}_{\eta} | \mathcal{F}_{t}) = \frac{1}{N} \sum_{i}^{N} \mathbb{1}[\tau_{\eta} \sim \theta \in \tilde{\tau}_{\eta}]$$
(A.39)

Secondly, our value approximator would be defined as,

$$\hat{V}_{N}^{*}(\mathbf{x}^{t}) = \sum_{\mathcal{Q}(\{\tau_{\eta}\})} \hat{P}_{\theta}^{N}(\tau_{\eta} \in \tilde{\tau}_{\eta} | \mathcal{F}_{t}) \ \mathcal{H}(\tilde{\tau}_{\eta}), \quad \text{where, } K = \left\lfloor \frac{A}{T} \right\rfloor$$
(A.40)

Convergence: By law of large numbers $||\hat{P}_{\theta}^{N}(\cdot) - P_{\theta}(\cdot)|| \to 0$, and we argue consequently $||\hat{V}_{N}^{*}(\cdot) - V^{*}(\cdot)||$ when $N \to \infty$. To demonstrate convergence, we can apply concentration bounds to quantify the approximation error, via Hoeffding's inequality. Thus we seek the probability that $\tau_{\eta} \in \tilde{\tau}_{\eta}$ by taking N Monte Carlo samples,

$$N(\tilde{\tau}_{\eta}) = \sum^{N} \mathbb{1}[\tau_{\eta} \in \{\tilde{\tau}_{\eta}\}]$$
(A.41)

$$\mathbb{E}[N(\tilde{\tau}_{\eta})] = N \cdot p_{\theta}(\tilde{\tau}_{\eta}) \tag{A.42}$$

Where $p_{\theta}(\tilde{\tau}_{\eta})$ is the finite multinomial probability that the event $\tau_{\eta} \in \tilde{\tau}_{\eta}$ occurs. Thus the total variance of each counts on each $\tau_{\eta} \in \tilde{\tau}_{\eta}$ is,

$$\operatorname{Var}[N(\tilde{\tau}_{\eta})] = N \cdot p_{\theta}(\tau_{\eta} \in \tilde{\tau}_{\eta}) \cdot (1 - p_{\theta}(\tau_{\eta} \in \tilde{\tau}_{\eta}))$$
(A.43)

$$\operatorname{Var}[P(\tilde{\tau}_{\eta})] = p_{\theta}(\tau_{\eta} \in \tilde{\tau}_{\eta}) \cdot (1 - p_{\theta}(\tau_{\eta} \in \tilde{\tau}_{\eta}))$$
(A.44)

We can now apply Hoeffding's inequality, let shorthand $p_{\theta}(\tau_{\eta}) \equiv p_{\theta}(\tau_{\eta} \in \tilde{\tau}_{\eta} | \mathcal{F}_t)$,

$$P\left(\left|\mathbb{E}[\hat{P}_{\theta}^{N}(\tilde{\tau}_{\eta}) - P_{\theta}(\tilde{\tau}_{\eta})]\right| \ge \epsilon\right) \le 2\exp\left(-\frac{2N\epsilon^{2}}{p_{\theta}(\tau_{\eta}) \cdot (1 - p_{\theta}(\tau_{\eta}))}\right)$$
(A.45)

$$P\left(\left|\mathbb{E}[\hat{P}_{\theta}^{N}(\tilde{\tau}_{\eta}) - P_{\theta}(\tilde{\tau}_{\eta})]\right| \ge \epsilon\right) \le 2\exp\left(-\frac{2N\epsilon^{2}}{\sigma^{2}}\right)$$
(A.46)

Therefore, with probability $1 - \delta$,

$$P\left(\left|\mathbb{E}[\hat{P}^{N}_{\theta}(\tilde{\tau}_{\eta}) - P_{\theta}(\tilde{\tau}_{\eta})]\right| \ge \epsilon\right) \le \delta$$
(A.47)

$$2\exp\left(-\frac{2N\epsilon^2}{\sigma^2}\right) \le \delta \tag{A.48}$$

$$\log\left(2\exp\left(-\frac{2N\epsilon^2}{\sigma^2}\right)\right) \le \log\delta \tag{A.49}$$

$$\epsilon \ge \sigma \sqrt{\frac{1}{2N} \log \frac{2}{\delta}} \tag{A.50}$$

Thus we have, with probability $1 - \delta$,

$$\left| \mathbb{E}[\hat{P}_{\theta}^{N}(\tilde{\tau}_{\eta}) - P_{\theta}(\tilde{\tau}_{\eta})] \right| \le \sigma \sqrt{\frac{1}{2N} \log \frac{2}{\delta}} = \epsilon(\tilde{\tau}_{\eta})$$
(A.51)

Therefore, we can express the value function as,

$$V^*(x^t) = \sum_{\mathcal{Q}(\{\tilde{\tau}_\eta\})} P_\theta(\tilde{\tau}_\eta) \ \mathcal{H}(\tilde{\tau}_\eta)$$
(A.52)

Where with probability $1 - \delta$,

$$V^*(x^t) \le \sum_{\mathcal{Q}(\{\tilde{\tau}_\eta\})} \left(P_\theta(\tilde{\tau}_\eta) + \epsilon(\tilde{\tau}_\eta) \right) \mathcal{H}(\tilde{\tau}_\eta)$$
(A.53)

$$= \sum_{\mathcal{Q}(\{\tilde{\tau}_{\eta}\})} P_{\theta}(\tilde{\tau}_{\eta}) \mathcal{H}(\tilde{\tau}_{\eta}) + \sum_{\mathcal{Q}(\{\tilde{\tau}_{\eta}\})} \epsilon(\tilde{\tau}_{\eta}) \mathcal{H}(\tilde{\tau}_{\eta})$$
(A.54)

$$= V^*(x^t) + \sum_{\mathcal{Q}(\{\tilde{\tau}_\eta\})} \epsilon(\tilde{\tau}_\eta) \mathcal{H}(\tilde{\tau}_\eta)$$
(A.55)

Which has the implication that,

$$V^*(x^t) \le \sum_{\mathcal{Q}(\{\tilde{\tau}_\eta\})} \hat{P}^N_{\theta}(\tilde{\tau}_\eta) \ \mathcal{H}(\tilde{\tau}_\eta) \implies \bar{V}^*(x^t) - V^*(x^t) \le \sum_{\mathcal{Q}(\{\tilde{\tau}_\eta\})} \epsilon_{\tau_\eta} \mathcal{H}(\tilde{\tau}_\eta)$$
(A.56)

We can write this also in vector notation as,

$$\Delta_V^+ = \mathbf{C}_{\mathcal{Q}(\cdot)} \cdot \mathcal{H}(\tilde{\tau}_\eta) \tag{A.57}$$

Where, for $q \in \{1, \ldots, |Q|\}$ partitions,

$$\mathbf{C}_{\mathcal{Q}(\cdot)} = [c_1(\tau_\eta, \delta) \dots c_Q(\tau_\eta, \delta)]^T$$
(A.58)

$$c_q(\tau_\eta, \delta) = \sqrt{\frac{p_q(\tilde{\tau}_\eta)(1 - p_q(\tilde{\tau}_\eta))}{2} \log\left(\frac{2}{\delta}\right)}, \quad \forall q \in \mathcal{Q}(\{\tilde{\tau}_\eta\})$$
(A.59)

 Δ_V^+ constitutes the maximum possible over estimation due to misspecification. This is fixed and determined by the properties of the stochastic generator θ , and due to misspecification, the upperbound on the value function decreases with rate $\frac{1}{\sqrt{N}}$. Thus we have an upper bound on the value,

$$\bar{V}^*(x^t) - V^*(x^t) \le \sum_{\mathcal{Q}(\{\tilde{\tau}_\eta\})} \epsilon(\tilde{\tau}_\eta) \,\mathcal{H}(\tilde{\tau}_\eta) = \frac{\Delta_V^+}{\sqrt{N}} \tag{A.60}$$

And without loss of generality, the opposite can be argued for a lower bound, as $\epsilon(\tilde{\tau}_{\eta})$ adheres to a symmetric relation.

$$V^*(x^t) - \underline{V}^*(x^t) \le \frac{\Delta_V^+}{\sqrt{N}} \tag{A.61}$$

A.5 Lemma A.1 and Proof

Lemma A.1. Binomial Sum Simplification: From Feller (1991) (Pg. 151), the following inequality holds,

$$P(\Sigma_i \ge k) = P(\Sigma_i = k) \frac{k(1-p)}{k-Tp}$$
(A.62)

Let X_1, \dots, X_T be a sequence of variables with Bernoulli distribution $X_T \sim B(T, p)$, assuming k > Tp,

$$P(\sum_{i=1}^{T} X_i \ge k) \le P(\sum_{i=1}^{T} X_i = k) \frac{k(1-p)}{k-Tp}$$
(A.63)

Proof.

$$\frac{P(\sum_{i=1}^{T} X_i = k+1)}{P(\sum_{i=1}^{T} X_i = k)} = \frac{\frac{T!}{(k+1)!(T-k-1)!}p^{k+1}(1-p)^{T-k-1}}{\frac{T!}{k!(T-k)!}p^k(1-p)^{T-k}} = \frac{(T-k)p}{(k+1)(1-p)}$$
(A.64)

For $j \ge k$,

$$P(\sum_{i=1}^{T} X_i = j) = \frac{P(\sum_{i=1}^{T} X_i = k+1)}{P(\sum_{i=1}^{T} X_i = k)} \cdots \frac{P(\sum_{i=1}^{T} X_i = j)}{P(\sum_{i=1}^{T} X_i = j-1)} P(\sum_{i=1}^{T} X_i = k)$$
(A.65)

$$\leq P(\sum_{i=1}^{T} X_i = k) \left(\frac{(T-k)p}{(k+1)(1-p)}\right)^{j-k}$$
(A.66)

So we have,

$$P(\sum_{i=1}^{T} X_i \ge k) = \sum_{j=k}^{T} P(\sum_{i=1}^{T} X_i = j) \le P(\sum_{i=1}^{T} X_i = k) \sum_{j=k}^{T} \left(\frac{(T-k)p}{(k+1)(1-p)}\right)^{j-k}$$
(A.67)

$$= P(\sum_{i=1}^{T} X_i = k) \frac{1 - \left(\frac{(T-k)p}{(k+1)(1-p)}\right)^{T-k+1}}{1 - \frac{(T-k)p}{(k+1)(1-p)}}$$
(A.68)

$$\leq P(\sum_{i=1}^{T} X_i = k) \frac{1}{1 - \frac{(T-k)p}{(k+1)(1-p)}} = P(\sum_{i=1}^{T} X_i = k) \frac{(k+1)(1-p)}{k - Tp + 1 - p}$$
(A.69)

$$< P(\sum_{i=1}^{T} X_i = k) \frac{k(1-p)}{k-Tp}$$
 (A.70)

A.6 Proof Theorem 2

Simple Regret: Given a Monte Carlo planning algorithm, \mathcal{M} , where $\tilde{p}(T) = P(\mathbf{a}^* \neq \mathbf{a})$, where $\lim_{T\to\infty} \tilde{p}(T) = 0$ and $\tilde{p}(T)$ is asymptotically bounded above by $\mathcal{O}(\frac{1}{T})$ for T samples, when running \mathcal{M} over the SD-MDP framework, the the simple regret $\operatorname{reg}(T)$, as defined in Eq. 3.8, is bounded by $C_k T \tilde{p}(T)$, for some value $C_k \in \mathbb{R}^+$.

Proof. From Lemma 2.1 we ascertain that as t grows $t \to T$ at each time increment the optimal action \mathbf{a}^* lines in a discrete set $\{\mathbf{a}^+\} \cup \{\mathbf{a}^-\}$. Let $\tilde{p}(t) = P(\mathbf{a}^* \neq \mathbf{a})$, given a trajectory, where the agent has acted perfectly, we first quantify the regret accumulated from making k swaps, that is instead of performing $\mathbf{a}^t = \mathbf{a}^* \in \{\mathbf{a}^-\}$, the agent instead performs $\mathbf{a}^t \in \{\mathbf{a}^+\}$ and (vice-versa). By logic, for k swaps of any given capacity, the agent would play the $\mathbf{a}^t \in \{\mathbf{a}^+\}$ at another point in time. When each of these swaps occur, the worst case instantaneous regret (or gap) is defined as $\tilde{\Delta}_a$,

$$\tilde{\Delta}_{a} = \max_{\mathbf{a} \in \{\mathbf{a}^{+}\}} \langle \phi f(\mathbf{x}_{s}), \mathbf{a} \rangle - \max_{\mathbf{a} \in \{\mathbf{a}^{-}\}} \langle \phi f(\mathbf{x}_{s}), \mathbf{a} \rangle$$
(A.71)

Let us next determine the consequences of each outcome, should i swaps occur.

$$\operatorname{reg}(T|\tau_{\eta}) = \begin{cases} k\tilde{\Delta}_{a}, & k \le i \le T\\ i\tilde{\Delta}_{a}, & i < k \le T \end{cases}$$
(A.72)

Assuming $k > T\tilde{p}$, which is possible as we state that \tilde{p} is asymptotically bounded above by $\mathcal{O}(1/T)$, we can therefore bound the expectation over simple regret as,

$$\mathbb{E}[\operatorname{reg}(T)] \leq \tilde{\Delta}_a \sum_{i=1}^{k-1} i \binom{T}{i} \tilde{p}^i (1-\tilde{p})^{T-i} + k \tilde{\Delta}_a \sum_{i=k}^T \binom{T}{i} \tilde{p}^i (1-\tilde{p})^{T-i}$$
(A.73)

$$=\tilde{\Delta}_a \sum_{i=1}^{k-1} i \binom{T}{i} \tilde{p}^i (1-\tilde{p})^{T-i} + k \tilde{\Delta}_a P(\Sigma_i \ge k)$$
(A.74)

Which we can simplify further as (from Lemma A.1)

$$\mathbb{E}[\operatorname{reg}(T)] \le \tilde{\Delta}_a \sum_{i=1}^{k-1} i \binom{T}{i} \tilde{p}^i (1-\tilde{p})^{T-i} + k \tilde{\Delta}_a P(\Sigma_i = k) \left(\frac{k(1-\tilde{p})}{k-T\tilde{p}}\right)$$
(A.75)

$$= \tilde{\Delta}_{a} \sum_{i=1}^{k-1} i \underbrace{\binom{T}{i} \tilde{p}^{i} (1-\tilde{p})^{T-i}}_{F_{\tilde{p}}^{T}(i)} + k \tilde{\Delta}_{a} \underbrace{\binom{T}{k} \tilde{p}^{k} (1-\tilde{p})^{T-k}}_{F_{\tilde{p}}^{T}(k)} \left(\frac{k(1-\tilde{p})}{k-T\tilde{p}}\right)$$
(A.76)

Taking a close up of the limit on the fractional term, $\frac{k(1-\bar{p})}{k-T\bar{p}}$,

$$\lim_{\tilde{p} \to 0} \frac{k(1 - \tilde{p})}{k - T\tilde{p}} = 1$$
(A.77)

Let $F_{\tilde{p}}^T(x)$ represent the binomial probability, with respect to x successes, give T attempts, and a success probability \tilde{p} .

$$F_{\tilde{p}}^{T}(x) = {T \choose x} \tilde{p}^{x} (1-\tilde{p})^{T-x}$$
(A.78)

We can then represent Eq. (A.76) as,

$$\mathbb{E}[\operatorname{reg}(T)] \le \tilde{\Delta}_a \sum_{i=1}^{k-1} i F_{\tilde{p}}^T(i) + k \tilde{\Delta}_a F_{\tilde{p}}^T(k)$$
(A.79)

From Eq. (A.79) the right hand side is vanishing as $T \to \infty$, while simultaneously $F_{\tilde{p}}^{T}(k) \to 0$. What is more important is we find an upper-bound to the right hand side term, $\tilde{\Delta}_{a} \sum_{i=1}^{k-1} i F_{\tilde{p}}^{T}(i)$. To accomplish this, let us impose an upper-bounding function, $\mathcal{U}^{T}(x, \tilde{p})$ which we define as a polynomial,

$$\mathcal{U}^{T}(x,\tilde{p}) = \alpha x(x-\beta) + \gamma \ge F_{\tilde{p}}^{T}(x), \qquad \forall x \in \mathbb{Z}, \ 1 \le x \le k, \quad \forall \tilde{p} \in [0,1]$$
(A.80)

By adjusting the terms $\alpha, \beta, \gamma \in \mathbb{R}$, we can always construct some upperbounding function which upper-bounds the function $F_{\tilde{p}}^{T}(x)$ on the interval $\forall x \in \mathbb{Z}, 1 \leq x \leq k, \forall \tilde{p} \in [0, 1]$, this is due to the concave nature of $F_{\tilde{p}}^{T}(x)$. That is for any given $T \in [1, \infty)$ we can select some combination of α, β, γ to satisfy Eq. (A.80). Once again we remind the reader that $\tilde{p}(t)$ is actually a dynamic feature of time t, as t increments from $1 \to T$. We can see that α, β are invariant of $\tilde{p}(t)$ for $t \in [1, T]$, should α, β be properly selected. Although we are free to select γ as we desire to form $\mathcal{U}^{T}(x)$, it will become evident later that we must select a $\gamma(T)$ which is a function of T, that approaches 0 as $T \to \infty$. To accomplish this we solve the equation for the polynomial $\mathcal{U}^{T}(x = 0) = 1$,

$$\mathcal{U}^T(x=0,\tilde{p}) = \alpha x(x-\beta) + \gamma(T) = \gamma(T) \ge F_{\tilde{p}}^T(x=1)$$
(A.81)

Given any fixed value of k which is determined by the capacity constraint of the SD-MDP framework, for any arbitrarily large value of T, there exists some α , and β independent of T which, in combination with a properly selected $\gamma(T)$ will serve to upper-bound $F_{\tilde{p}}^T(x=1)$. We enforce the assumption that that $\tilde{p}(T) \to 0$ as $T \to \infty$, we therefore equate $\gamma(T)$ with the binomial coefficient,

$$\gamma(T) = F_{\tilde{p}}^T(x=1) \tag{A.82}$$

$$= \lim_{T \to \infty} \lim_{t \to T} \frac{T!}{1!(T-1)!} \tilde{p}(T)^1 (1-\tilde{p}(T))^{T-1}$$
(A.83)

$$=\lim_{T\to\infty} T\tilde{p}(T)(1-\tilde{p}(T))^{T-1}$$
(A.84)

$$= \lim_{T \to \infty} T \tilde{p}(T) \lim_{T \to \infty} (1 - \tilde{p}(T))^{T-1}$$
(A.85)

$$=\lim_{T\to\infty} T\tilde{p}(T) \tag{A.86}$$

To study simple regret behaviour as $T \to \infty$, we have a return look at Eq. (A.79).

$$\lim_{T \to \infty} \mathbb{E}[\operatorname{reg}(T)] \le \lim_{T \to \infty} \tilde{\Delta}_a \sum_{i=1}^{k-1} i F_{\tilde{p}}^T(i) + k \tilde{\Delta}_a F_{\tilde{p}}^T(k) \frac{k}{T}$$
(A.87)

$$= \lim_{T \to \infty} \tilde{\Delta}_a \sum_{i=1}^{k-1} i F_{\tilde{p}}^T(i)$$
(A.88)

$$\leq \lim_{T \to \infty} \tilde{\Delta}_a \sum_{i=1}^{k-1} i(\alpha_k i(i - \beta_k) + \gamma(T))$$
(A.89)

Where fore any particular value of k, we select $\alpha_k < 0$ and $\beta_k > 0$ such that for some decreasing value $\gamma(T)$, the term $\alpha_k i(i - \beta_k) + \gamma(T)$ upper bounds $F_{\tilde{p}}^T(i)$. We wish to investigate the scenario for large values of T, as $T \to \infty$, therefore, we can assume that the binomial distribution, for any value $F_{\tilde{p}}^T(x > 1) < F_{\tilde{p}}^T(x = 1)$ for sufficiently large values of T, as $F_{\tilde{p}}^T(x)$ enters a regime of monotonically decreasing tail behaviour for increasing values of x > 1, and small values of \tilde{p} . Therefore, in that regime, we can consider $\alpha_k = 0$, and we can upper bound $F_{\tilde{p}}^T(x)$ simply with $\gamma(T)$. Therefore, in this regime, for large values of T, we can say,

$$\lim_{T \to \infty} \mathbb{E}[\operatorname{reg}(T)] \le \lim_{T \to \infty} \tilde{\Delta}_a \sum_{i=1}^{k-1} i\gamma(T))$$
(A.90)

Effectively we have k constants independently of T, which in summation can serve to bound the simple regret in the asymptotic regime. And we can combine the additive terms into some crude upper-bounding additive term C_k .

$$\lim_{T \to \infty} \mathbb{E}[\operatorname{reg}(T)] \le \lim_{T \to \infty} \sum_{i=1}^{k-1} C_i \gamma(T)$$
(A.91)

$$\leq \lim_{T \to \infty} C_k \gamma(T) \tag{A.92}$$

In summary, by coming results from Eq. (A.92) with Eq. (A.86) for large values of $T \to \infty$, we have the following upper-bound on simple regret,

$$\mathbb{E}[\operatorname{reg}(T)] \le C_k T \tilde{p}(T) \tag{A.93}$$

B Algorithms

B.1 MCTS UCT Bellman VC

```
Algorithm 1 MCTS Bellman UCT Value Clipping Algorithm
```

```
1: Input: Initialize state (chance node) \mathbf{x}_0.
  2: Output: Best action a*
  3: Define: \operatorname{clip}(v, \underline{v}, \overline{v}) = \min(\max(v, \underline{v}), \overline{v}), \forall v \in \mathbb{R}
  4: while Max iterations not exceeded. do
          \mathbf{x}_{s} \rightarrow \text{Selection}(\mathbf{x}, \pi_{UCT}(\cdot))
  5:
          v' \gets 0
 6:
          if \alpha_c > \text{Uniform}[0, 1] then
 7:
               for each possible state \mathbf{x}' extending from inducing action \mathbf{a}_s and state \mathbf{x}_s do
 8:
                  v \leftarrow \text{Simulation}(\mathbf{x}', \pi_s(\cdot))
 9:
                  \underline{v} \leftarrow \underline{V}_k(\mathbf{x}') From Eq. (2.27)
10:
                  \bar{v} \leftarrow \text{Hindsight perfect solution.}
11:
                  V(\mathbf{x}') \leftarrow \operatorname{clip}(v, \underline{v}, \overline{v})
12:
                  v' \leftarrow v' + P(\mathbf{x}'|\mathbf{a}, \mathbf{x})V(\mathbf{x}')
13:
              end for
14:
15:
          else
              for each possible state \mathbf{x}' extending from inducing action \mathbf{a}_s and state \mathbf{x}_s do
16:
                  V(\mathbf{x}') \leftarrow \text{Simulation}(\mathbf{x}', \pi_s(\cdot))
17:
                  v' \leftarrow v' + P(\mathbf{x}'|\mathbf{a}, \mathbf{x})V(\mathbf{x}')
18:
              end for
19:
          end if
20:
           Q(\mathbf{x}, \mathbf{a}) \leftarrow \mu(\mathbf{x}, \mathbf{a}) + v'
21:
          Perform Q-Update according to Eq. (3.2).
22:
          Backpropagation(\mathbf{x}_s, Q(\mathbf{x}_s, \mathbf{a}))
23:
24: end while
25: \mathbf{a}^* \leftarrow \operatorname{argmax} Q(\mathbf{x}_0, \mathbf{a})
                    \mathbf{a} \in \mathcal{A}
26: return a*
```

B.2 MCTS MENTS Bellman VC

Algorithm 2 MCTS Bellman MENTS Value Clipping Algorithm

```
1: Input: Initialize state (chance node) \mathbf{x}_0.
  2: Output: Best action a*
  3: Define: \operatorname{clip}(v, \underline{v}, \overline{v}) = \min(\max(v, \underline{v}), \overline{v}), \forall v \in \mathbb{R}
  4: while Max iterations not exceeded. do
          \mathbf{x}_{s} \rightarrow \text{Selection}(\mathbf{x}, \pi_{M}(\cdot))
  5:
          v' \gets 0
 6:
          if \alpha_c > \text{Uniform}[0, 1] then
 7:
               for each possible state \mathbf{x}' extending from inducing action \mathbf{a}_s and state \mathbf{x}_s do
 8:
                   v \leftarrow \text{Simulation}(\mathbf{x}', \pi_s(\cdot))
 9:
                   \underline{v} \leftarrow \underline{V}_k(\mathbf{x}') From Eq. (2.27)
10:
                   \bar{v} \leftarrow \text{Hindsight perfect solution.}
11:
                   V_s(\mathbf{x}') \leftarrow \operatorname{clip}(v, \underline{v}, \overline{v})
12:
                   v' \leftarrow v' + P(\mathbf{x}'|\mathbf{a}, \mathbf{x})V_s(\mathbf{x}')
13:
               end for
14:
          else
15:
               for each possible state \mathbf{x}' extending from inducing action \mathbf{a}_s and state \mathbf{x}_s do
16:
                   V_s(\mathbf{x}') \leftarrow \text{Simulation}(\mathbf{x}', \pi_s(\cdot))
17:
                   v' \leftarrow v' + P(\mathbf{x}'|\mathbf{a}, \mathbf{x})V_s(\mathbf{x}')
18:
               end for
19:
           end if
20:
           Q(\mathbf{x}, \mathbf{a}) \leftarrow \mu(\mathbf{x}, \mathbf{a}) + v'
21:
          Perform Value and Q-Update according to Eq. (3.4) and Eq. (3.5).
22:
           Backpropagation(\mathbf{x}_{s}, Q_{sft}(\mathbf{x}_{s}, \mathbf{a}))
23:
24: end while
25: \mathbf{a}^* \leftarrow \operatorname{argmax} Q_{\operatorname{sft}}(\mathbf{x}_0, \mathbf{a})
26: return \mathbf{a}^{\in \mathcal{A}}
```

C Geometric Brownian Motion (GBM)

The Geometric Brownian Motion (GBM) is a stochastic process used in various fields including finance and physics, to model the random movement of a variable over time. The stochastic differential equation (SDE) is written as ,

$$dS^t = \mu S^t \, dt + \sigma S^t \, dW_t,\tag{C.1}$$

Where S^t as the value of the process at time t, μ as the drift coefficient, σ is the volatility coefficient, and W_t is a standard Brownian motion. The variable evolves with a mean growth rate μ , and volatility σ determining the magnitude of fluctuations. The solution for the above SDE is written as,

$$S^{t} = S^{1} \exp\left(\left(\mu - \frac{1}{2}\sigma^{2}\right)t + \sigma W_{t}\right), \qquad (C.2)$$

where S^1 is the initial value of the process at time t = 0. The term $\left(\mu - \frac{1}{2}\sigma^2\right)$ represents the adjusted drift.

D Maritime Refuelling



Figure 4: Atlantic Pacific Express (APX) liner route. [YNL12]

Maritime refuelling, also known as *bunkering*, is a problem in the field of transportation logistics that involves finding the optimal policy to refuel a fleet of vehicles, such as trucks or ships, while they are in operation. The goal is to minimize the total cost of refuelling, which includes the cost of the fuel itself. It is a common practice in the shipping industry, as ships require large amounts of fuel to power their engines and systems during long voyages. Bunkering is typically done at ports, where the ship can be moored and connected to a fuel supply by hoses or pipelines. Bunkering can also be done at sea, using smaller vessels known as bunker barges to transfer the fuel to the ship. Solving the bunkering problem can allow companies in the transportation industry reduce costs and improve the efficiency of their operations by minimizing fuel costs.

A real-world examples is the Atlantic Pacific Express (APX) liner routes (see Fig. 4). In the liner scenario, a schedule of port visits is prearranged. That is the liner must only determine how much to refuel at each port of call, and at which speed to travel to the next port. But, for simplicity, we omit the speed component. The liner knows which location they are at, how much fuel they possess, how much minimum fuel they need, and the prices of the fuel at all ports in the schedule. We assume that prices follow a known probability distribution. In the normal macroeconomic conditions that is a reasonable assumption since the prices can be estimated from the historical data, while during the turbulent periods designing stress price scenarios might be the best we can do.

One way to approach the bunkering problem is to use mathematical optimization techniques, such as mixed integer programming, to determine the optimal refuelling amounts, given a fixed schedule or flexible schedule¹. This may involve considering factors such as the capacity of the vessel, the distance they need to travel, the availability of fuel at different locations, and any constraints on when and where the vehicles can be refuelled. A liner is a type of shipping vessel that operates on a regular schedule between specified ports, carrying cargo and sometimes passengers. Liner shipping refers to the use of these vessels to transport cargo on a regular basis between predetermined ports of call. Liners are typically owned and operated by shipping companies, and they follow a set route, stopping at a predetermined list of ports to load and unload cargo. Liners are an important part of the global shipping industry, as they provide a reliable and efficient way to transport a wide variety of goods, including consumer goods, raw materials, and manufactured products. They play a vital role in supporting international trade and the movement of goods around the world.

Ship Route (Schedule): In this experiment, we assume that the ship route (i.e. order of the ports) is fixed, and that the fuel is available at all ports on the route. The objective is finding the optimal refuelling policy. Upon arrival at each port, the price is revealed and we need to determine the refuelling amount. In practice, bunkering purchasing problems typically involve big data (i.e., 500 vessels, 40,000 ports of call, governed by 750 contracts [BKP16]).

Fuel prices: Fuel prices can be governed by various stochastic processes – in this work, we assume that the fuel prices obey a discrete time geometric Brownian motion, as described in Section C. We discretize the GBM over many different price outcomes, stemming from realizations of the stochastic process. Therefore, the problem in principle can be solved approximately via stochastic programming, stochastic programming [WML13; YNL12]. Nevertheless, as the scale of the problem increases, i.e. more price scenarios arise, the problem becomes intractable via an increase in stochastic scenarios. Each liner is constrained by predetermined schedules and must ensure that there is enough fuel to travel between each intermediate port of call. The liner can choose the refuel amount and the speed of the ship, which affects fuel consumption.

The maritime bunkering model is subject to the following simplifying model assumptions,

- Fuel prices are subject to global stochastic variation.
- Fuel consumption is deterministic.
- Distance, to and from each port, is fixed and deterministic.
- No possibility of service disruptions.

D.1 Stochastic Programming

 $^{^1\}mathrm{A}$ ship with a flexible schedule is referred to as a tramper.

Notation	Description
Ν	Number of ports of call
S	Number of scenarios
K	Number of stochastic events at each trip step t
$\delta_{n,t}$	Fuel price change change in the port n at the trip step t
β^{s}	Probability of the scenario $s \in S$ occurring
$X_{n,1}^{s}$	Fuel level when arriving at port n in scenario s
$X_{n,2}^{s}$	Fuel level when departing from port n in scenario s
$X_{n,1}$	Fuel level when arriving at port n
$X_{n,2}$	Fuel level when departing from port n
d(n, n+1)	Distance function from the port n until the next port $n+1$
$f_c(n, n+1)$	Fuel consumption function from the port n until the next port $n+1$ given the distance
	d(n, n+1)
\mathcal{N}	Continuous fuel price percentage change probability distribution
P_n^s	Price of fuel at port n in scenario s
P_n	Expected price of fuel at port n
$Y_n^s \in \{0, 1\}$	Indicator for bunkering decision at port n in scenario s
$Y_n \in \{0, 1\}$	Indicator for bunkering decision at port n
B_n^s	Fixed bunkering cost at port n in scenario s
B_n	Fixed bunkering cost at port n
M	Liner fuel tank capacity

Table 2: Notation and variable desciptions.

We formulate the liner bunkering problem as a stochastic program. The stochastic factors affect the price of fuel through the price percentage changes expressed by S scenarios. We optimize the actions to take at each port of call. Concretely, at each port n the liner must decide on a refueling amount, denoted as the amount of fuel leaving port n in scenario s, $X_{n,2}^s$, subtracted by the amount of fuel arriving at port n in scenario s, $X_{n,1}^s$. The fuel consumption, i.e., the difference $X_{n,2}^s - X_{n+1,1}^s$, is deterministic given the distance until the next port d(n, n + 1) which affects a deterministic fuel consumption $f_c(n, n + 1)$. In addition, there is also a fixed bunkering cost B_n^s in case we decide to refuel non-negative amount at port n in scenario s. We indicate the bunkering action by a binary variable Y_n^s . We assume that the liner has the empty fuel tank at the initial port and we constrain its fuel tank capacity by the upper bound M.

Given fuel price percentage change scenarios $s \in S$, which determine the fuel prices P_n^s we have:

$$\min_{X} \qquad C^{SP} = \sum_{s \in S} \beta^{s} \sum_{n \in N} P_{n}^{s} (X_{n,2}^{s} - X_{n,1}^{s}) + B_{n}^{s} Y_{n}^{s} + \tau(T_{n+1}^{k})$$
(D.1a)

subject to

$$X_{n+1,1}^{s} = X_{n,2}^{s} - f_c(n, n+1, V_n^k), n \in N, s \in S$$

$$X_{n+2}^{s} \ge X_{n-1}^{s}, n \in N, s \in S$$
(D.1b)
(D.1c)

$$X_{n,2}^s \ge X_{n,1}^s, n \in N, s \in S$$
 (D.1c)

$$f_c(n, n+1, V_n^k) \ge 0, n \in N \tag{D.1d}$$

$$Y_n^s \in \{0, 1\}, n \in N, s \in S$$
 (D.1e)

$$X_{n,i}^s \ge 0, n \in N, s \in S, i \in \{1, 2\}$$
(D.1f)

$$X_{n,i}^{s} \le M, n \in N, s \in S, i \in \{1, 2\}$$
(D.1g)

$$X_{1,1}^s = 0, s \in S$$
 (D.1h)

We have the stochastic value objective represented by (D.1a), which is the sum of the refuelling costs per port denoted as $P_n^s(X_{n,2}^s - X_{n,1}^s)$, the fixed bunkering costs denoted as $B_n^s Y_n^s$, and the time window

penalties for arriving late or early to the destination denoted as $\tau(T_{n+1}^k)$. (D.1b) is the consumption balance constraint, (D.1c) prevents negative refuelling amounts, (D.1d) states that the consumption is non-negative, (D.1e) is an indicator variable for the fixed bunkering cost, (D.1f) and (D.1g) are lower and upper fuel tank capacities, while (D.1h) imposes the empty fuel tank at the initial port. Each of these constraints hold for every scenario $s \in S$.

D.1.1 Modelling Fuel Price

We simulated $N_{\text{GBM}} = 200,000$ price trajectories using the Geometric Brownian Motion (GBM) model as illustrated in Section C, starting with an initial stock price S_0 . Each trajectory was generated by iterating over T time steps, applying the GBM formula $S^t = S^{t-1} \cdot \exp((\mu - 0.5\sigma^2)\Delta t + \sigma\Delta W_t)$, where ΔW_t represents the increments of a Wiener process. This process involved parameters for drift (μ) , volatility (σ) , under a fixed discrete time increment (Δt) , ensuring the randomness and variability in the simulated price paths. To estimate the probability density function of the simulated prices, we flattened the simulation results and created a histogram with a specified number of bins, and thereafter calculate the probability density for any given price value based on the histogram data. We can this assign probabilities to each simulated price outcome, ensuring a comprehensive probability distribution across the entire range of simulated trajectories.

D.2 Table of Parameters

Config.	Initial Price (S^1)	Price Volatility (σ)	Price Drift (μ)
А	1000	0.9	1.0
В	1000	0.5	1.0
С	100	0.9	1.0
D	1000	0.5	0.5
Ε	1000	0.9	0.5
F	100	0.9	0.5

Table 3: GBM Stochastic price parameters.

Table 4: Shared parameters across	all experimental	configurations.
-----------------------------------	------------------	-----------------

Description	Value
$N_{\rm GBM}$ GBM simulated trajectories. $N_{\rm H}$ Number of histogram bins. $N_{\rm sim}$ MCTS Number of Iterations $N_{\rm depth}$ MCTS Depth Limit λ_s MENTS Decay Rate Number of ports-of-call	200,000 20,000 1 × 105 500 2 × 109 7
Fuel capacity.	50 Units

Fuel consumption rate is simplified to 1 unit of fuel consumed to 1 unit of distance travelled.

Table 6: Static MCTS Solver Parameters.

Description	Value
$N_{\rm GBM}$ GBM simulated trajectories.	200,000

$N_{\rm H}$ Number of histogram bins.	20,000
$N_{\text{depth}} \text{ MCTS Depth Limit}$	500
λ_s MENTS Decay Rate	2×10^9
Number of ports-of-call.	7
Fuel capacity.	50 Units

Table 7:	MCTS	Dynamic	Parameters
----------	------	---------	------------

Config.	$N_{ m sim}$	MCTS Exploration Constant (α)
А	1000	0.9
В	1000	0.5
\mathbf{C}	100	0.9
D	1000	0.5
Ε	1000	0.9
\mathbf{F}	100	0.9

	1	2	3	4	5	6	7
1	0	12	7	15	12	18	3
2	12	0	25	8	10	15	6
3	7	25	0	30	20	16	12
4	15	8	30	0	19	25	30
5	12	10	20	19	0	9	18
6	18	15	16	25	9	0	21
7	3	6	12	30	18	21	0
8	4	14	10	8	13	10	17

Table 5: Distance between each port-of-call represented by a distance matrix.



D.3 Empirical Results - Cost Comparison

Figure 5: Cost performance of the maritime logistics simulation.



D.4 Empirical Results - Value Convergence

Figure 6: Value convergence performance of the maritime logistics simulation.