

AUTOMATING VARIATIONAL DIFFERENTIATION

KANGBO LI* AND ANIL DAMLE†

Abstract. Many problems in Physics and Chemistry are formulated as the minimization of a functional. Therefore, methods for solving these problems typically require differentiating maps whose input and/or output are functions—commonly referred to as variational differentiation. Such maps are not addressed at the mathematical level by the chain rule, which underlies modern symbolic and algorithmic differentiation (AD) systems. Although there are algorithmic solutions such as tracing and reverse accumulation, they do not provide human readability and introduce strict programming constraints that bottleneck performance, especially in high-performance computing (HPC) environments. In this manuscript, we propose a new computer theoretic model of differentiation by combining the pullback of the **B** and **C** combinators from the combinatory logic. Unlike frameworks based on the chain rule, this model differentiates a minimal complete basis for the space of computable functions. Consequently, the model is capable of analytic backpropagation and variational differentiation while supporting complex numbers. To demonstrate the generality of this approach we build a system named CombDiff, which can differentiate nontrivial variational problems such as Hartree-Fock (HF) theory and multilayer perceptrons.

Key word. Differentiation, Electronic Structure, Programming Language

MSC codes. 68V99, 49-04, 15-04

1. Introduction. Variational differentiation (VD) [16] is the differentiation of maps from functions to functions as well as maps from tensors to tensors, which we will refer to as function maps and tensor maps. VD is widely used in the physical sciences and applied mathematics. A classic example is the principle of minimal action [22], where one differentiates the action of a particle $S(r) = \int \mathcal{L}(r(t), \dot{r}(t))dt$ with respect to the trajectory $r(t)$ —yielding Newton’s law for a classical particle. In discretized form, VD becomes the differentiation of tensor maps. An example is to take the gradient of a quadratic loss function x^*Ax , producing $2Ax$ if A is Hermitian.

A more challenging example that is representative of the type of differentiation we aim to automate is the Hartree-Fock (HF) energy [41, 38], which is central to a foundational method in electronic structure theory [29, 32]. Within HF theory the N_e electrons associated with a molecule can be approximately encoded as a matrix $C \in \mathbb{C}^{N_b \times N_e}$ with orthogonal columns (i.e., $C^*C = I$), where N_b is the number of basis functions used to describe each electron. The energy of the system then contains a term of the form

$$(1) \quad \sum_{ij}^{N_e} \sum_{pqrs}^{N_b} C_{pi}^* C_{rj}^* J_{pqrs} C_{sj} C_{qi},$$

where J is a fourth order tensor that encodes the interaction between electrons and has the (time reversal) symmetries $J_{pqrs} = J_{rspq} = J_{qpst}^*$. To build computational methods that minimize the energy, we need to differentiate (1) with respect to C . Moreover, when doing so it is important to take into account the symmetries as they generally reduce the evaluation cost of the gradient by a significant factor (essentially free in the case of (1)). In this paper, we aim to provide a model for automating VD and backpropagation analytically. In addition to producing simplified and human readable results, our approach prevents the differentiation from interfering with numerical computation, which significantly complicates the implementation of differentiation systems while compromising the performance.

*Department of Computer Science, Cornell University (kl935@cornell.edu)

†Department of Computer Science, Cornell University (damle@cornell.edu)

To accomplish this, we present a new pair of differentiation rules for the so-called **B** and **C** combinators from combinatory logic. Our rules serve as an alternative to combining the chain rule with algorithmic mechanisms such as partial evaluation and reverse accumulation. Avoiding algorithmic mechanisms enables the differentiation system to *analytically* backpropagate and perform general VD (even without the discretization). Moreover, our approach makes it possible to optimize for computational efficiency *after* the gradient is analytically known, thus separating differentiability constraints from performance concerns.

The advantage of our approach is rooted in a foundational completeness result from the combinatory logic, which states the **B** and **C** combinators¹ form a minimal complete basis for expressing all computable functions. These combinators and the completeness result were first proposed a century ago by Schröfinkel [37] and Curry [8]. The primary application of the combinators has been to develop the theory of computability [9] as an alternative approach to the more popular lambda calculus [7], but they have also found practical use in building parsers [14, 28], reasoning about data updates [15], and automatic parallelization [27]. Ultimately, our approach scaffolds a (computational) framework for differentiation that is capable of VD and backpropagation, preserves human readability, and enables performance optimization. We use this framework to build the CombDiff system.

1.1. Relation to existing symbolic and computational systems systems.

Differentiating (1) is difficult for existing symbolic differentiation systems such as SymPy [35] and Mathematica, which are typically based on the chain rule and a collection of primitive functions. Nevertheless, symbolic systems can differentiate through univariate functions as well as some “matrix calculus.” This analytical approach has attractive advantages: the result is human readable; the gradient is fast to evaluate; and the system is simple to implement. However, there are several drawbacks that severely limit its applicability. The first is that univariate functions paired with some matrix calculus can only express a limited subset of the tensor maps and does not include (1). The second is that symbolic systems typically do not properly address complex numbers in the context of optimization. Lastly, such methods do not support backpropagation—a necessity for a broad class of problems including machine learning training and ab-initio molecular dynamics.

These problems can be remedied by algorithmic differentiation (AD) systems, but not without hefty compromises. Mathematically, AD systems are also based on the chain rule² and a collection of optimized numerical kernels [3, 10, 20], which alone cannot enable backpropagation. The additional ingredient that enables backpropagation and distinguishes AD systems from symbolic systems is partial evaluation, which often appears in the form of a computation graph traced at runtime [26]. The price of the partial evaluation is steep, with the obvious loss being readability and symbolic processing power. The more subtle downstream impact is in high performance computing (HPC) settings, where one has to develop performance optimizations without seeing the gradient. Furthermore, the differentiability constraints [4] allow only pure user functions, which exclude primitives indispensable to HPC such as mutations and communication. As a result, applying basic HPC methods such as pipelining and

¹or equivalently, the **S** and **K** combinator.

²It is noteworthy that **B** is essentially the composition rule. From this perspective, the chain rule misses the entire dimension of functions spanned by **C**, which is a problem that is partly compensated for by allowing mutations. Moreover, the chain rule only differentiates a composition $f_1(f_2(x))$ with respect to the input x but not functions f_1 and f_2 , so it requires partial evaluations.

recomputation to a problem require major dedicated efforts [25, 11], and sophisticated or problem-specific techniques such as leveraging tensor symmetries and tensor compressions are still open questions. On the positive side, relinquishing readability enables AD systems to differentiate through complex numbers by treating them as 2D real vectors—a solution that is less acceptable for symbolic systems.

There are two partial solutions in AD for addressing tensor maps. The first is to trade immutability and optimized kernels for generality by differentiating low-level mutating statements [26]. Tampering with the immutability constraint can significantly complicate program analysis [5], cause bugs [31], and incur severe performance loss due to the inability to use optimized kernels [2]. A second strategy is to express the tensor maps as a long sequence of matrix and vector operations. This approach is limited to a subset of tensor maps and the performance is sub-optimal compared to tensor contraction engines [1, 17, 13, 24, 2]. The overhead arises from creating an intermediate copy of the tensors for each operation in the sequence, so it is inherent to the method and cannot be easily eliminated. Lastly, it is possible to add higher order functions to the set of primitives of an AD system, which covers a few key types of functionals, but the lack of completeness is a problem [30].

2. Notation. We will employ an “anonymous” notation for tensors and functions, which is less commonly used but is necessary to compactly explain our developments. For example, the Fourier transform can be written in terms of an anonymous function as

$$(2) \quad f \mapsto (\omega \mapsto \int \exp(-i\omega r) f(r) dr),$$

which maps f to another anonymous function that represents the transformed function $\hat{f}(\omega)$. One can apply an anonymous function to an input, which itself can be an anonymous function, and the function application can be evaluated by substitution. For example, we can apply the Fourier transform to an inverse Fourier transform

$$(3) \quad (f \mapsto (\omega \mapsto \int \exp(-i\omega r) f(r) dr)) (r \mapsto \int \exp(i\omega r) g(\omega) d\omega)$$

$$(4) \quad = \omega \mapsto \int \int \exp(-i\omega r) \exp(i\omega' r) g(\omega') d\omega' dr$$

$$(5) \quad = \omega \mapsto \int \delta(\omega - \omega') g(\omega') d\omega' = g(\omega).$$

For our theory to be applicable to tensors, we adopt the same notation and treat tensors as maps from integer indices to the corresponding tensor elements. For example, a vector v can be written as $i \mapsto v_i$, which represents a vector whose i^{th} element is v_i . We will also use the function evaluation notation $v(i)$ interchangeably with v_i for accessing tensor elements.

3. Main Result. We present a pair of differentiation rules as an alternative to the current technology stack for (computational) differentiation, primarily for automating VD. As a demonstration and verification of our framework, we provide an experimental system called CombDiff³ that can perform backpropagation and VD purely symbolically, and produce a human readable gradient. Moreover, it can manipulate the result into the appropriate computational kernels and simplify the result based on tensor symmetries. We illustrate the efficacy of our system by applying it to a variety of objective functions including quadratic loss, conjugate gradient [18, 23], the HF energy, and the Maximally Localized Wannier Function (MLWF) spread metric [39, 34]. In our examples, the symmetry-based simplification produces a gradient

³<https://github.com/kangboli/CombDiff>

that can be evaluated for free as an intermediate of the objective function. This cost reduction appears to be associated with the time reversal symmetry of the models. The documentation page of `CombDiff` contains more sample problems, including analytic backpropagation for a multilayer perceptron.

As an example, the tensor contraction in (1) can be expressed and differentiated with the code in [listing 1](#), a detailed explanation of which is deferred to [section 6](#) and the output is given in (53)

```
1 f, _ = @pct _ ctx (J::T) -> pullback((C::CM) -> sum((i, j, p, q, r, s),
2   C(p, i)' * C(q, i) * C(r, j)' * C(s, j) * J(p, q, r, s))); f
```

LISTING 1
Hartree Fock

4. Background. In this section, we motivate the concept of the pullbacks and the chain rule starting from how some scientists approach VD by hand, from which we introduce pullbacks. We then explain *composition with captures* and the chain rule of pullbacks and go through an example of obtaining derivatives using the formalism.

A common recipe for performing VD is based on “first order perturbation” heuristics: the input of the function is perturbed and we observe the first-order change in the output. For example, when taking the trace of a matrix product $(A, B) \mapsto \text{tr}(AB)$ one can perform VD using the matrix product rules and the trace rule

$$(6) \quad \delta \text{tr}(X) = \text{tr}(\delta X), \quad \delta AB = (\delta A)B + A\delta(B),$$

$$(7) \quad \delta \text{tr}(AB) = \text{tr}((\delta A)B) + \text{tr}(A(\delta B)) = \langle \delta A, B \rangle + \langle A, \delta B \rangle,$$

from which one concludes that $B = 0$ and $A = 0$ are the stationary points. This approach is not suited for symbolic processing because it is hard to express the idea of “evaluating the derivative at a point” without ambiguities. The systematic way to encode the same information in the AD theory is the *pushforward*. We will introduce the pushforwards and pullbacks in our notations; see, e.g., [3, 20] for a review.

The concept of a *pushforward* can be motivated by the Jacobian chain rule for computing the gradient of a composite function $g(x) = f_1(f_2(x))$, where x is a vector, $f_2 : \mathbb{R}^M \rightarrow \mathbb{R}^N$ and $f_1 : \mathbb{R}^N \rightarrow \mathbb{R}$. The gradient of g is

$$(8) \quad \nabla g(x) = \mathcal{J}g(x)^T = \mathcal{J}f_2(x)^T \cdot \mathcal{J}f_1(f_2(x))^T,$$

which is sufficient for deriving the gradient. However, the Jacobian is often $O(N)$ sparse and highly structured, so the $O(N^2)$ time and memory for forming and multiply the Jacobian is unnecessary. This structured sparsity can be captured and leveraged using the pullbacks \mathcal{P} and pushforwards \mathcal{F} , which are the building blocks of AD systems and can be defined as

$$(9) \quad \mathcal{P}f(x, k) \triangleq \mathcal{J}f(x)^T \cdot k = i \mapsto \sum_j k_j \partial f(x)_j / \partial x_i,$$

$$(10) \quad \mathcal{F}f(x, k) \triangleq k \cdot \mathcal{J}f(x)^T = i \mapsto \sum_j k_j \partial f(x)_i / \partial x_j,$$

both of which encode the Jacobian through its action (as a linear map) instead of its entries. A second reason why the pullback/pushforward are preferable to the Jacobian in our context is that they do not rely on the partial derivative notation of the type $\partial f(x)_i / \partial x_j$, which is incompatible with our formulation.⁴

⁴The difficulty is that x_j is supposed to be a independent variable but j is not independent.

To see the connection between the pushforwards and VD rules in (6), one can examine the pushforward of the matrix product following the definition (10)

$$(11) \quad \mathcal{F}((A, B) \mapsto AB)(A, B, K, L)$$

$$(12) \quad = (p, q) \mapsto \sum_{i,j} K_{ij} \frac{\partial \sum_n A_{pn} B_{nq}}{\partial A_{ij}} + \sum_{i,j} L_{ij} \frac{\partial \sum_n A_{pn} B_{nq}}{\partial B_{ij}}$$

$$(13) \quad = (p, q) \mapsto \sum_n K_{pn} B_{nq} + \sum_n A_{pn} L_{nq} = KB + AL.$$

Identifying $K = \delta A$ and $L = \delta B$, this equation corresponds to the product rule in (6). For the rest of this manuscript, we choose to formulate our theory in terms of pullbacks because it is aligned with reverse-mode AD systems, which are more suited for scientific optimization problems.

Given a collection of pullbacks, the chain rule based differentiation is essentially the construction of the pullback of a function composition from the pullbacks of its constituents. The formula can be derived from rewriting (8) in terms of pullbacks.

$$(14) \quad \mathcal{P}g(x, k) = \mathcal{J}f_2(x)^T \cdot (\mathcal{J}f_1(f_2(x)))^T \cdot k = \mathcal{P}f_2(x, \mathcal{P}f_1(f_2(x), k)).$$

The gradient can then be computed as $\nabla g(x) = \mathcal{P}(g)(x, 1)$. A basic chain rule based differentiation system can then be viewed as a two-stage process. First, one breaks down a function into a *composition with captures*. The captures are to be understood as the constants in a function. For example, consider the composition $\exp \circ (x \mapsto w \cdot x)$. The weight w is what one would consider a ‘‘constant,’’ and these constants are called captures in the programming language literature; formally they have to be treated as variables declared in an outer scope. Thus, the full context of our function would be a composition with a capture

$$(15) \quad w \mapsto \exp \circ (x \mapsto w \cdot x).$$

The second stage is to derive the pullback of the composition using the chain rule

$$(16) \quad w \mapsto \mathcal{P}(\exp \circ (x \mapsto w \cdot x))$$

$$(17) \quad = w \mapsto (x, k) \mapsto \mathcal{P}(x \mapsto w \cdot x)(x, \mathcal{P}(\exp)(w \cdot x, k))$$

$$(18) \quad = w \mapsto (x, k) \mapsto ((x, k) \mapsto wk)(x, \mathcal{P}((x, k) \mapsto \exp(x)k)(w \cdot x, k))$$

$$(19) \quad = w \mapsto (x, k) \mapsto w \exp(w \cdot x)k,$$

where the pullback of the multiplication and exponential are assumed given. The gradient is then obtained as $w \exp(w \cdot x)$ by setting $k = 1$.

5. Model. In the section, we introduce the **B** and **C** combinators, then we contribute the differentiation rules for the combinators and a procedure for applying them to VD. Heuristically speaking, the **C** combinator converts a function that returns a function to a composition with captures. For tensor problems, it converts the differentiation of tensor maps to the differentiation of parametrized univariate functions. The differentiation rule for the **B** combinator yields two terms: one term serves the role of the chain rule, and the other term does the backpropagation. We will not discuss the derivation of the rules, but we will show how they work by walking through examples and verifying the correctness through implementation. Lastly, we show that complex numbers can be treated by extending the definition of pullback, and the **B** and **C** rules still apply.

5.1. The Combinators. In combinatory logic, the composition of two functions f_1 and f_2 can be modeled with the **B** combinator as $\mathbf{B}(f_1)(f_2) = (\mathbf{B}(f_1))(f_2)$, where the function evaluation is left associative and the **B** combinator is defined as

$$(20) \quad \mathbf{B} = f \mapsto (g \mapsto (x \mapsto f(g(x)))).$$

From this perspective, the AD process can be viewed as decomposing a function in terms of the **B** combinator and a collection of primitive functions. The composition can be differentiated by assembling the pullbacks of the primitive functions using the chain rule. The drawback of this approach is that it cannot backpropagate or express more general functions such as functions that return functions.

To differentiate functions that return functions, we need the **C** combinator, which is defined as

$$(21) \quad \mathbf{C} = f \mapsto (x \mapsto (y \mapsto f(y)(x))).$$

To see what **C** does, we rewrite a function returning a function in terms of **C**

$$(22) \quad w \mapsto (x \mapsto \exp(w \cdot x)) = \mathbf{C}(x \mapsto \mathbf{B}(\exp)(w \mapsto w \cdot x)),$$

where the function inside **C** is a composition with a capture x —a case we know how to differentiate from (15). In abstract, the **C** combinator converts a function that returns a function into a composition with a captures. More generally, the process of decomposing a function into the combinators and a small number of primitives, which are listed in Table 1, is known as abstraction elimination.

primitive	definition	pullback
B -combinator	$f \mapsto g \mapsto x \mapsto f(g(x))$	See Eq. (27)
C -combinator	$g \mapsto x \mapsto b \mapsto g(b)(x)$	See Eq. (23)
conjugate	$x \mapsto x^*$	$(x, k) \mapsto k^*$
multiply	$x \mapsto vx$	$(x, k) \mapsto v^*k$
add	$x \mapsto v + x$	$(x, k) \mapsto k$
contract	Σ	$(x, k) \mapsto i \mapsto k$

TABLE 1

The primitive functions and their pullbacks.

5.2. Differentiating the Combinators. We have reduced a function that return functions to the **C** combinator and a composition with captures. To differentiate the **C** combinator, we need a new rule call the **C** rule, which can be written in terms of the pullbacks as

$$(23) \quad \mathcal{P}(\mathbf{C}(g)) = (x, k) \mapsto \Sigma(b \mapsto \mathcal{P}(g(b))(x, k(b))),$$

where Σ denotes a polymorphic contraction. Polymorphic means that its definition depends on the type of its input. In the case of our rule (23), if b is a real number or a function, then Σ is an integral over the real line or the corresponding function space. We will use the notation $\Sigma_b g(b)$ as a shorthand for $\Sigma(b \mapsto g(b))$ to be familiar and concise, but conceptually Σ maps a function to a number. As an example of the **C** rule, applying it to the previous example in (22) gives

$$(24) \quad \mathcal{P}(\mathbf{C}(x \mapsto \mathbf{B}(\exp)(w \mapsto w \cdot x)))(x, k)$$

$$(25) \quad = \Sigma_b \mathcal{P}(x \mapsto \mathbf{B}(\exp)(x \mapsto x \cdot b)(x))(x, k(b))$$

$$(26) \quad = \Sigma_b b \exp(b \cdot x)k(b),$$

The right hand side involves an inner product between k and $b \mapsto b \exp(b \cdot x)$, which seems unclear how to compute. However, the contraction generally does not need to be computed. Instead, k typically turns out to contain a polymorphic delta function that meets the contraction due to the **B** rule that we will introduce next. The two polymorphic objects then subtly combine into a simple substitution, an example of which will be shown in (31).

The differentiation rules for the **B** combinator may appear to be just (14). However, this does not account for the crucial case where x is captured by f or g , which is required for the backpropagation. For example, $f \mapsto f(i)$ can be written as $f \mapsto \mathbf{B}(f)(\mathbf{I})(i)$, where \mathbf{I} is the identity map and the first input of \mathbf{B} is dependent on the input variable f . This necessitates an adaptation to the chain rule, which we refer to as the **B** rule

$$(27) \quad \begin{aligned} \mathcal{P}(x \mapsto \mathbf{B}(f)(g)(x)) &= (x, k) \mapsto \\ &\mathcal{P}(x \mapsto g(x))(x, \mathcal{P}(f)(g(x), k)) + \mathcal{P}(x \mapsto f)(x, i \mapsto \delta(g(x), i, k)), \end{aligned}$$

where δ is a polymorphic delta function similar to the polymorphic contraction. $\delta(i, j, k)$ is k if $i = j$ but 0 otherwise. If i, j are integers, real numbers, or functions, δ represents a Kronecker delta, a Dirac delta, or a delta function on the function space. We have chosen to write delta functions as function calls instead of superscripts/subscripts to avoid abusing the notation for the Dirac/Kronecker delta. The first term in the rule reproduces the chain rule, and the second term is responsible for backpropagating, which includes a function returning a function $x \mapsto f$, necessitating the **C** combinator. The delta function will meet the contraction that appears when applying the **C** rule from (23) and will result in a substitution.

5.3. Examples. To illustrate the significance of the backpropagation part of the **B** rule, we consider differentiating the solution of a system of equations $g(x) = 0$. When g arises from a gradient $g = \nabla R$ this corresponds to differentiating a stationary point of R , which models a broad class of problems including molecular dynamics and sensitivity analysis [12]. Consider the procedure ρ that maps g to one of its roots, where the condition $g \mapsto g(\rho(g)) = g \mapsto 0$ is satisfied. Differentiating both sides yields

$$(28) \quad 0 = \mathcal{P}(g \mapsto \rho(g))(g, \mathcal{P}g(\rho(g), k)) + \mathcal{P}(g \mapsto g)(g, i \mapsto \delta(i, \rho(g), k))$$

$$(29) \quad = \mathcal{P}(\rho)(g, H(k)) + i \mapsto \delta(i, \rho(g), k), \quad H(k) = \mathcal{P}g(\rho(g), k)$$

$$(30) \quad \mathcal{P}(\rho) = (g, k) \mapsto i \mapsto \delta(i, \rho(g), -H^{-1}(k)),$$

where $H(k)$ is a linear map on k that represents multiplying by the Hessian of R if $g = \nabla R$. This example essentially differentiates the function `argmin` [19], which is typically performed after g is concretely known and $g(x) = 0$ has been solved.

The backpropagating part of the **B** rule also enables us to decompose any explicit function in terms of only univariate functions. For example, $x \mapsto f(x) \cdot g(x)$ can be decomposed using only multiplication by a constant as $x \mapsto (v \mapsto f(x) \cdot v)(x)$ because the $(v \mapsto f(x) \cdot v)$ is allowed to capture x . This implies that multivariate calculus of static dimensions is already handled through the **B** rule and that multivariate primitives such as adding or multiplying two numbers are unnecessary. The differentiation

of $x \mapsto f(x) \cdot g(x)$ proceeds as

$$\begin{aligned}
(31) \quad & \mathcal{P}(x \mapsto (v \mapsto f(x) \cdot v)(g(x)))(x, k) \\
(32) \quad & = \mathcal{P}(g)(x, \mathcal{P}(v \mapsto f(x) \cdot v)(g(x), k)) \\
(33) \quad & \quad + \mathcal{P}(x \mapsto (v \mapsto f(x) \cdot v))(x, i \mapsto \delta(i, g(x), k)) \\
(34) \quad & = \mathcal{P}(g)(x, f(x)^*k) + \Sigma_v \mathcal{P}(x \mapsto (t \mapsto t \cdot v)(f(x)))(x, \delta(v, g(x), k)) \\
(35) \quad & = \mathcal{P}(g)(x, f(x)^*k) + \Sigma_v \mathcal{P}(f)(x, \mathcal{P}(t \mapsto t \cdot v)(f(x), \delta(v, g(x), k))) \\
(36) \quad & = \mathcal{P}(g)(x, f(x)^*k) + \mathcal{P}(f)(x, \Sigma_v v^* \delta(v, g(x), k)) \\
(37) \quad & = \mathcal{P}(g)(x, f(x)^*k) + \mathcal{P}(f)(x, g(x)^*k),
\end{aligned}$$

which is the product rule for pullbacks (note the conjugates). From (35) to (37), the contraction met the delta function and resulted in a substitution of v into $g(x)$, and no polymorphic object is present in the final result.

5.4. Complex Numbers. The primitive operations we listed in Table 1 contain mysterious complex conjugates. We now explain our treatment of complex numbers, which leads to the complex conjugates in primitive pullbacks. The main difficulty in dealing with complex numbers is that the standard complex analysis does not prescribe a useful gradient for optimization. For example, minimizing $z \mapsto |z|^2$ is evidently equivalent to minimizing $(a, b) \mapsto a^2 + b^2$, but a Cauchy-Riemann argument shows that $|z|^2$ is nowhere analytic, so the pullback makes no sense. For a real and scalar valued function, this problem is partly resolved through the Wirtinger derivative [21]

$$(38) \quad \partial f(z)/\partial z = \partial f(z)/\partial a + i \partial f(z)/\partial b, \quad z = a + ib,$$

which can be used for, e.g., gradient descent.

This formalism is insufficient for symbolic automation because it does not handle the case where $f(z)$ is complex and requires splitting z into its real and imaginary parts. Differentiating a complex function $f(z)$ may seem unnecessary when the objective function to optimize is always a real scalar. However, we differentiate $f(z)$ by differentiating its constituents, which are complex-valued functions. Moreover, representing a complex gradient in terms of the real and imaginary parts of z is not acceptable for symbolic purposes, and it is preferable to avoid splitting a complex variable to begin with (rather than trying to reassemble them from the real and imaginary parts in the end).

These problems can be resolved by extending the definition of pullback to complex numbers. We start by proposing the operators \mathcal{V} and \mathcal{W}

$$(39) \quad \mathcal{V}(z) \triangleq [\operatorname{Re}(z_1) \quad \operatorname{Im}(z_1) \quad \dots \quad \operatorname{Re}(z_n) \quad \operatorname{Im}(z_n)]^T,$$

$$(40) \quad \mathcal{W}(f) \triangleq v \mapsto \mathcal{V}(f(\mathcal{V}^{-1}(v))).$$

\mathcal{V} and \mathcal{V}^{-1} establish an isomorphism between \mathbb{C}^N and \mathbb{R}^{2N} so that we can convert a complex problem to a real one that is equivalent. Analogously, \mathcal{W} converts between $\mathbb{C}^N \rightarrow \mathbb{C}^M$ and $\mathbb{R}^{2N} \rightarrow \mathbb{R}^{2M}$. One can check that the following identities hold

$$(41) \quad \forall f \in \mathbb{C}^N \rightarrow \mathbb{C}^M, \quad \mathcal{V}(f(z)) = (\mathcal{W}(f))(\mathcal{V}(z)),$$

$$(42) \quad \forall f \in \mathbb{C}^N \rightarrow \mathbb{R}, \quad f(z) = \mathcal{V}(1)^T \cdot (\mathcal{W}(f))(\mathcal{V}(z)).$$

To minimize a scalar-valued function $f(z)$ over z , we can equivalently minimize the real function $u \mapsto \mathcal{V}(1)^T \cdot (\mathcal{W}(f))(u)$ and convert u to the corresponding complex number with $z = \mathcal{V}^{-1}(u)$. The gradient of the real function can be written as $(\mathcal{J}(\mathcal{W}(f)))(u)^T \cdot \mathcal{V}(1)$. Transforming this vector back into the complex space gives the complex gradient $\mathcal{V}^{-1}((\mathcal{J}(\mathcal{W}(f)))(u)^T \cdot \mathcal{V}(1))$. Therefore, we write the Wirtinger gradient as

$$(43) \quad \nabla f(z) \triangleq \mathcal{V}^{-1}(\mathcal{J}(\mathcal{W}(f))(\mathcal{V}(z))^T \cdot (\mathcal{V}(1))).$$

To be able to find the gradient through the pullback as $\nabla f(z) = \mathcal{P}(f)(z, 1)$, we suggest to define the complex pullbacks as

$$(44) \quad \mathcal{P}(f) \triangleq (z, k) \mapsto \mathcal{V}^{-1}(\mathcal{J}(\mathcal{W}(f))(\mathcal{V}(z))^T \cdot \mathcal{V}(k)).$$

Since the pullback remains a vector Jacobian product just like (9), the **B** and **C** rules are not affected by the change. Therefore, the only modification to the theory is to derive the pullbacks of the univariate primitives listed in Table 1 using (44) instead of (9). As an example, writing $z = x + iy$ and $k = a + ib$, the pullback of the complex conjugate can be derived as

$$(45) \quad \mathcal{W}(z \mapsto z^*) = (x, y) \mapsto (x, -y),$$

$$(46) \quad \mathcal{P}(z \mapsto z^*) = (z, k) \mapsto \mathcal{V}^{-1} \left(\begin{bmatrix} 1 & 0 \\ 0 & -1 \end{bmatrix} \cdot \begin{bmatrix} a \\ b \end{bmatrix} \right) = (z, k) \mapsto k^*.$$

5.5. Equivalence Graph. The two combinator rules introduced contractions and delta functions that have to be combined into substitutions. This can be implemented in many ways, but we choose to adapt a technique called the equivalence graph (e-graph) [36], which has found applications in compiler optimization [40, 44] and symbolic math [6]. We will use it primarily to combine contractions with delta functions and perform a number of simplifications including combining terms that are identical due to tensor symmetries. The details of the e-graph is outside the scope of differentiation and will be covered in a separate manuscript.

6. Results. We now show four examples of increasing difficulty that can be easily handled by `CombDiff`. The simplest problem can only be symbolically automated with dedicated rules for the matrix calculus, whereas the harder problems are challenging even for experts to differentiate by hand. In our examples, the domains of the functions and the ranges of the sums do not affect the differentiation but complicate the presentation—so we will assume them to be infinite.

6.1. Quadratic Functions. We introduce the syntax of `CombDiff` by differentiating the quadratic form x^*Ax with $A \in \mathbb{C}^{N \times N}$ being Hermitian. Many symbolic systems can handle this, but typically through a dedicated implementation of the “matrix calculus.” Our system produces the same result without rules for matrices or vectors except for post-differentiation optimization.

```
1 f, _ = @pct (A::Her) -> pullback((x::CV) ->
2   sum((i, j), x(i)'*A(i,j)*x(j)))
3
4 df = redux(vdiff(f), settings=symmetry_settings) |> blaserize
```

LISTING 2
Quadratic functions

The syntax of CombDiff is identical to that of Julia since it is implemented as a Julia DSL through its macro system, which gives a different semantic to same syntax. To obtain the derivative of $x \mapsto x^*Ax$, one write it in terms of its mathematical definition, as shown in [listing 2](#). The result of the definition is a function `f` with a context, the latter of which is discarded for this example. The `vdiff` function performs the differentiation on `f` and produces the correct but unsimplified gradient, which the `redux` function takes as input and simplifies. The `blaserize` function then rewrites the result in terms of linear algebra operations to improve readability and computational efficiency by leveraging BLAS. The final result is shown in [\(47\)](#), whose latex code is generated by the system.

$$(47) \quad A \mapsto x \mapsto 2.0 \cdot A \cdot x.$$

The factor of two is a consequence of the symmetry of A . The mechanism for encoding and exploiting the symmetry will be illustrated in [subsection 6.3](#).

This example, although simple, demonstrates many of the benefits of our approach that persist into the complex examples: there is no need to complicate the implementation with partial evaluation, matrix calculus, or memory mutations; the $2Ax$ is in a form that can be directly fed to BLAS, but it would not be necessary here because the evaluation is essentially free as an intermediate of evaluating x^*Ax thanks to the symmetry.

6.2. Conjugate Gradient. The conjugate gradient (CG) algorithm [\[23, 43\]](#) is a widely used algorithm. We give a conceptually simple derivation of CG by minimizing $R = x \mapsto \frac{1}{2}x^T Ax - b^T x$, whose stationary condition yields $Ax = b$. We consider a general optimization step parametrized by the step sizes $x + \alpha(r + \beta p)$, where $x \in \mathbb{R}^N$ is the current iterate, $p \in \mathbb{R}^N$ is the previous step direction and $r \in \mathbb{R}^N$ is the current gradient. The residual as a function of the parameters after taking the gradient step is $(\alpha, \beta) \mapsto R(x + \alpha(r + \beta p))$, which we minimize with respect to α and β .

In [listing 3](#), we first differentiate the residual without substituting the objective function R to obtain an abstract theory that is generally applicable. Then we show that replacing R with the quadratic form gives the CG coefficients.

```

1 f, _ = @pct (A::Sym, r::RV, p::RV, b::RV, x::RV) -> begin
2   R = (x::RV) ->
3     sum((i, j), 0.5 * x(i) * A(i, j) * x(j)) - sum(i, x(i) * b(i))
4   pullback((alpha::R, beta::R) ->
5     R((i::N) -> x(i) + alpha * (r(i) + beta * p(i))))
6 end;
7 blaserize(f)
8
9 df = vdiff(f) |> blaserize
10
11 df = redux(vdiff(eval_all(f)); settings=symmetry_settings) |> blaserize

```

LISTING 3
Conjugate gradient

The result of line 9 of [listing 3](#) is shown in [\(48\)](#), which gives a vector of two components. This shows that we can differentiate through unknown functions as a consequence of

avoiding the partial evaluation.

$$\begin{aligned}
& (A, r, p, b, x) \mapsto \text{let} \\
& \quad R = x \mapsto (-1.0 \cdot x^T \cdot b + 0.5 \cdot x^T \cdot A \cdot x) \\
(48) \quad & (\alpha, \beta) \mapsto (\nabla(R)((\alpha \cdot (\beta \cdot p + r) + x))^T \cdot (\beta \cdot p + r), \\
& \quad \nabla(R)((\alpha \cdot (\beta \cdot p + r) + x))^T \cdot p \cdot \alpha) \\
& \text{end}
\end{aligned}$$

If we write $p_k = r + \beta p$, $\nabla R(\alpha p_k + x)^T \cdot p_k = 0$ has the interpretation that the gradient at the next iterate should be orthogonal to the current step direction. Combined with $\nabla R(\alpha p_k + x)^T \cdot p \cdot \alpha = 0$, we have a nonlinear system of two equations for α and β , the coefficients and thus the solutions of which depends on R .

Once we substitute the quadratic form for R in line 11 of [listing 3](#), the gradient reduces to

$$\begin{aligned}
& (A, r, p, b, x) \mapsto (\alpha, \beta) \mapsto \\
(49) \quad & (((\beta \cdot p + r)^T \cdot A \cdot (\alpha \cdot (\beta \cdot p + r) + x) - 1.0 \cdot (\beta \cdot p + r)^T \cdot b), \\
& \alpha \cdot (p^T \cdot A \cdot (\alpha \cdot (\beta \cdot p + r) + x) - 1.0 \cdot b^T \cdot p)).
\end{aligned}$$

Using the fact that the gradient $r = Ax - b$ is orthogonal to the previous step direction p , the two nonlinear equations can be solved by hand to get

$$(50) \quad \alpha = \frac{p_k^T \cdot (b - Ax)}{p_k^T A p_k} = -\frac{(r + \beta p)^T r}{p_k^T A p_k} = -\frac{r^T \cdot r}{p_k^T A p_k},$$

$$(51) \quad \beta = \frac{(b^T - x^T \cdot A) \cdot p - \alpha r^T \cdot A \cdot p}{\alpha p^T A p} = \frac{r^T A p}{p^T A p},$$

which can be recognized as the parameters that produce the conjugate gradient method.

6.3. Hartree Fock. We now return to the HF problem motivating this work, which is a contraction between a fourth order complex tensor $J \in \mathbb{C}^{N \times N \times N \times N}$ and a complex matrix $C \in \mathbb{C}^{N \times N_e}$

$$(52) \quad J \mapsto C \mapsto \sum_{i,j,p,q,r,s} C_{p,i}^* C_{r,j}^* J_{p,q,r,s} C_{s,j} C_{q,i}.$$

Similar to how the gradient of $x^* A x$ can be simplified when A is Hermitian, the gradient of the HF energy can be simplified based on the symmetries of the electron repulsion integral tensor J , which are encoded through the type system. For example, the first symmetry in line 4 of [listing 4](#) specifies that $J_{pqr s} = J_{qp s r}^*$, and the second symmetry specifies that $J_{pqr s} = J_{r s p q}$.

```

1 _, ctx = @pct begin
2   @space T begin
3     type = (N, N, N, N) -> C
4     symmetries = (((2, 1, 4, 3), :conj), ((3, 4, 1, 2), :id))
5   end
6 end;
7 f, _ = @pct _ ctx (J::T) -> pullback((C::CM) -> sum((i, j, p, q, r, s),
8   C(p, i)' * C(q, i) * C(r, j)' * C(s, j) * J(p, q, r, s))); f
9
10 df = redux(vdiff(f); settings=symmetry_settings)

```

```

11
12 df |> get_body |> decompose |> pp |> simplify |> first
      LISTING 4
      Hartree Fock

```

The gradient can be obtained as usual in line 10 of [listing 4](#) and the result is

$$(53) \quad J \mapsto C \mapsto (\mathbf{d}, \mathbf{d}_1) \mapsto \left(\sum_{j,p,r,s} J_{r,s,p,d}^* C_{s,j}^* C_{p,d_1} C_{r,j} \right) 4.0.$$

If one writes $\hat{J}(\mathbf{d}, \mathbf{p}) = \sum_{r,s} J_{r,s,p,d}^* \sum_j C_{s,j}^* C_{r,j}$, then (53) can be written as a matrix multiplication $\hat{J} \cdot C$, and \hat{J} can be recognized as the Coulomb contribution to the Fock matrix [41, 29]. In terms of the performance, this result is in the form that the tensor contraction engines expect; the factor of 4 represents a $4\times$ saving due to the symmetries, but the evaluation is again free as an intermediate of evaluating the objective. Getting the gradient for free currently requires manual effort, but this is made possible by the readability of the result.

As an illustration of the differentiation process, we find the Hessian vector product using lower level operations of the system. In line 12 of [listing 4](#), the gradient first goes through the `decompose` function, which breaks down the map in (53) into the **B** and **C** combinators. `pp` then applies the **B** and **C** rules to obtain the pullback, which encodes the Hessian vector product. The result is then simplified into

$$(54) \quad (C, \mathbf{k}) \mapsto (\mathbf{a}_2, \mathbf{a}_3) \mapsto \left(\sum_{\mathbf{d}, \mathbf{d}_1, p, s} C_{p, \mathbf{d}_1}^* J_{\mathbf{a}_2, s, p, \mathbf{d}} \mathbf{k}_{\mathbf{d}, \mathbf{d}_1} C_{s, \mathbf{a}_3} + \sum_{\mathbf{d}, \mathbf{d}_1, p, r} J_{r, \mathbf{a}_2, p, \mathbf{d}}^* \mathbf{k}_{\mathbf{d}, \mathbf{d}_1}^* C_{p, \mathbf{d}_1} C_{r, \mathbf{a}_3} + \sum_{\mathbf{d}, j, r, s} C_{r, j}^* J_{r, s, \mathbf{a}_2, \mathbf{d}} \mathbf{k}_{\mathbf{d}, \mathbf{a}_3} C_{s, j} \right) 4.0.$$

6.4. Localized Wannier Functions. Lastly, we examine the theory of localized Wannier functions [34, 33]. The gradient used in the standard codebase `Wannier90` is technically the projected gradient [34], which is partly the reason why `Wannier90` requires a dedicated optimizer. A derivation that produces the usual gradient can be found in [42].

The optimization objective for this problem is a complex tensor contraction similar to the HF energy

$$(55) \quad U \mapsto \sum_{n,b} w(b) |\hat{\rho}(n, b)|^2,$$

$$(56) \quad \hat{\rho}(n, b) = \sum_{k,p,q} U(p, n, k)^* S(p, q, k, k+b) U(q, n, k+b),$$

where $S \in \mathbb{C}^{N \times N \times N_k \times N_k}$ is known as the overlap matrix and $U \in \mathbb{C}^{N \times N \times N_k}$ is known as the gauge. Similar to the HF case, S has a symmetry $S(p, q, k, k+b) = S(q, p, k+b, k)^*$, which has to be leveraged to simplify the result. The difference from the HF problem is that the index k is on a periodic domain; one has to consider arithmetic in the indices, and b is on a symmetric domain.

For our system to fully simplify the gradient, all of the above assumptions have to be encoded in the types, and these assumptions themselves are subtle enough that one needs an expert to identify them. One can proceed without these assumptions and get a suboptimal but nevertheless correct gradient, but we will encode these assumptions in [listing 5](#) to show that this is possible in principle.

```

1 _, ctx = @pct begin
2   @domain BZ begin
3     base = I
4     periodic = true

```

```

5   end
6
7   @domain X begin
8     symmetric = true
9     contractable = false
10  end
11
12  @space Mmn begin
13    type = (N, N, BZ, BZ) -> C
14    symmetries = ((2, 1, 4, 3), :conj),)
15  end
16
17  @space SV begin
18    type = (I,) -> C
19    symmetries = ((1,), :ineg),)
20  end
21
22  @space Gauge begin
23    type = (N, N, BZ) -> C
24  end
25 end;
26 f, _ = @pct _ ctx (S::Mmn, w::SV) -> pullback((U::Gauge) ->
27   begin
28     rho = (n::N, b::X) -> sum((k::BZ, p, q), U(p, n, k)' *
29     S(p, q, k, k + b) * U(q, n, k + b))
30     sum((n, b::X), w(b) * rho(n, b)' * rho(n, b))
31   end); f
32
33 df = redux(vdiff(eval_all(f)); settings=symmetry_settings)

```

LISTING 5

Localized Wannier functions

The result of the code is

$$(57) \quad (S, w) \mapsto U \mapsto (\mathbf{d}, \mathbf{d}_1, \mathbf{d}_2) \mapsto 4.0 \cdot (\sum_{b,p,k,p,q} U(\mathbf{p}, \mathbf{d}_1, (b+k))^* \cdot w(b) \cdot U(\mathbf{q}, \mathbf{d}_1, k) \cdot U(\mathbf{p}, \mathbf{d}_1, (\mathbf{d}_2 + b)) \cdot S(\mathbf{d}, p, \mathbf{d}_2, (\mathbf{d}_2 + b)) \cdot S(\mathbf{p}, q, (b+k), k)).$$

This result requires one further step of simplification to be recognized as similar to the gradient derived by hand in [39]

$$(58) \quad (S, w) \mapsto U \mapsto (\mathbf{d}, \mathbf{d}_1, k) \mapsto 4.0 \cdot (\sum_{b,p,q} w(b) \cdot \hat{\rho}(\mathbf{d}_1, b))^* U(\mathbf{p}, \mathbf{d}_1, (k+b)) \cdot S(\mathbf{d}, p, k, (k+b)).$$

Once again, the gradient is free as a byproduct of evaluating the objective function, although it is more subtle to see. However, due to the arithmetics on the indices, neither the objective nor the gradient can be fed directly into a tensor contraction engine.

7. Conclusion. We have developed a novel framework for automating variational differentiation based on the combinatory logic. We proposed a pair of differentiation rules for the **B** and **C** combinators, which spans the space of computable functions. Our differentiation framework is then completed with a generalization to complex numbers through a redefinition of the pullbacks. Our approach enables VD and backpropagation while staying free from any numerical evaluations. Consequently, we are able to keep the gradients human readable, minimize code complexity, and avoid performance losses inherent to conflating differentiating with performance optimizations.

The main theoretical limitation of our method is the performance of the e-graph search when tensor symmetries are involved. Although the hardest example in the paper (MLWF) requires less than ten seconds on a M1 Pro Processor, which is acceptable for interactive use, the time complexity can grow rapidly with larger problems. This issue can be mitigated by guiding the search on the graph with the compressibility of the ASTs, which also has the benefit of improving the numerical performance.

Acknowledgements. K.L. and A.D. were supported by the SciAI Center, and funded by the Office of Naval Research (ONR), under Grant Number N00014-23-1-2729. We like to thank Dr. Guido Falk von Rudorff for the discussion on differentiating the stationary points.

REFERENCES

- [1] *cutensor: A high-performance cuda library for tensor primitives*, <https://docs.nvidia.com/cuda/cutensor/latest/index.html> (accessed 2024-06-01).
- [2] M. ABBOTT, D. ALUTHGE, N3N5, V. PURI, C. ELROD, S. SCHAUB, C. LUCIBELLO, J. BHATTACHARYA, J. CHEN, K. CARLSSON, AND M. GELBRECHT, *mcabbott/tullio.jl: v0.3.7*, Oct. 2023, <https://doi.org/10.5281/zenodo.10035615>, <https://github.com/mcabbott/Tullio.jl/blob/f7d4cbab5a8e3cfd259deb06aab4c64934606c0a/README.md> (accessed 2024-06-01).
- [3] A. G. BAYDIN, B. A. PEARLMUTTER, A. A. RADUL, AND J. M. SISKIND, *Automatic differentiation in machine learning: a survey*, (2015), <http://arxiv.org/abs/1502.05767v4>, <https://arxiv.org/abs/1502.05767v4>. Atilim Gunes Baydin, Barak A. Pearlmutter, Alexey Andreyevich Radul, Jeffrey Mark Siskind. Automatic differentiation in machine learning: a survey. The Journal of Machine Learning Research, 18(153):1–43, 2018.
- [4] J. BRADBURY, R. FROSTIG, P. HAWKINS, M. J. JOHNSON, C. LEARY, D. MACLAURIN, G. NECULA, A. PASZKE, J. VANDERPLAS, S. WANDERMAN-MILNE, AND Q. ZHANG, *JAX: composable transformations of Python+NumPy programs*, 2018, <http://github.com/google/jax>.
- [5] J. BRADBURY, R. FROSTIG, P. HAWKINS, M. J. JOHNSON, C. LEARY, D. MACLAURIN, G. NECULA, A. PASZKE, J. VANDERPLAS, S. WANDERMAN-MILNE, AND Q. ZHANG, *JAX: composable transformations of Python+NumPy programs*, 2018, https://github.com/google/jax/blob/be1e40dc2e1777d83b870afa31e178123f2a1366/docs/notebooks/Common_Gotchas_in_JAX.md (accessed 2024-06-01).
- [6] A. CHELI, *Metatheory.jl: Fast and elegant algebraic computation in julia with extensible equality saturation*, Journal of Open Source Software, 6 (2021), p. 3078, <https://doi.org/10.21105/joss.03078>, <https://doi.org/10.21105/joss.03078>.
- [7] A. CHURCH, *A set of postulates for the foundation of logic*, The Annals of Mathematics, 33 (1932), p. 346, <https://doi.org/10.2307/1968337>, <http://dx.doi.org/10.2307/1968337>.
- [8] H. B. CURRY, *Grundlagen der kombinatorischen logik*, American Journal of Mathematics, 52 (1930), pp. 509–536, <http://www.jstor.org/stable/2370619> (accessed 2024-05-31).
- [9] H. B. CURRY, R. FEYS, W. CRAIG, J. R. HINDLEY, AND J. P. SELDIN, *Combinatory logic*, vol. 1, North-Holland Amsterdam, 1958.
- [10] C. ELLIOTT, *The simple essence of automatic differentiation*, Proceedings of the ACM on Programming Languages, 2 (2018), pp. 1–29, <https://doi.org/10.1145/3236765>, <http://dx.doi.org/10.1145/3236765>.
- [11] J. FENG AND D. HUANG, *Optimal gradient checkpoint search for arbitrary computation graphs*, (2018), <http://arxiv.org/abs/1808.00079v6>, <https://arxiv.org/abs/1808.00079v6>.
- [12] A. V. FIACCO AND G. P. MCCORMICK, *Nonlinear programming: sequential unconstrained minimization techniques*, SIAM, 1990.
- [13] M. FISHMAN, S. R. WHITE, AND E. M. SToudenMIRE, *The itensor software library for tensor network calculations*, (2020), <https://doi.org/10.21468/SciPostPhysCodeb.4>, <http://arxiv.org/abs/2007.14822v2>, <https://arxiv.org/abs/2007.14822v2>. SciPost Phys. Codebases 4 (2022).
- [14] J. FOKKER, *Functional parsers*, in Advanced Functional Programming: First International Spring School on Advanced Functional Programming Techniques Båstad, Sweden, May 24–30, 1995 Tutorial Text 1, Springer, 1995, pp. 1–23.
- [15] J. N. FOSTER, M. B. GREENWALD, J. T. MOORE, B. C. PIERCE, AND A. SCHMITT, *Combinators for bidirectional tree transformations*, ACM Transactions on Programming Lan-

- guages and Systems, 29 (2007), p. 17, <https://doi.org/10.1145/1232420.1232424>, <http://dx.doi.org/10.1145/1232420.1232424>.
- [16] I. M. GELFAND, *Calculus of variations*, Dover Publications, 2000.
- [17] E. GEORGANAS, D. KALAMKAR, S. AVANCHA, M. ADELMAN, D. AGGARWAL, C. ANDERSON, A. BREUER, J. BRUESTLE, N. CHAUDHARY, A. KUNDU, D. KUTNICK, F. LAUB, V. MD, S. MISRA, R. MOHANTY, H. PABST, B. RETFORD, B. ZIV, AND A. HEINECKE, *Tensor processing primitives: A programming abstraction for efficiency and portability in deep learning & hpc workloads*, (2021), <https://doi.org/10.1145/3458817.3476206>, <http://arxiv.org/abs/2104.05755v4>, <https://arxiv.org/abs/2104.05755v4>.
- [18] G. H. GOLUB AND C. F. V. LOAN, *Matrix Computations*, Johns Hopkins University Press, 2013.
- [19] S. GOULD, B. FERNANDO, A. CHERIAN, P. ANDERSON, R. S. CRUZ, AND E. GUO, *On differentiating parameterized argmin and argmax problems with application to bi-level optimization*, ArXiv, abs/1607.05447 (2016), <https://api.semanticscholar.org/CorpusID:7186854>.
- [20] A. GRIEWANK AND A. WALTHER, *Evaluating Derivatives*, Society for Industrial and Applied Mathematics, 1 2008, <https://doi.org/10.1137/1.9780898717761>, <http://dx.doi.org/10.1137/1.9780898717761>.
- [21] R. GUNNING AND H. ROSSI, *Analytic Functions of Several Complex Variables*, Ams Chelsea Publishing, Prentice-Hall, 1965, <https://books.google.com/books?id=L0zJmamx5AAC>.
- [22] J. S. HERBERT GOLDSTEIN CHARLES POOLE, H. GOLDSTEIN, C. P. POOLE, AND J. L. SAFKO, *Classical Mechanics (3rd Edition)*, Addison Wesley, 2002.
- [23] M. HESTENES AND E. STIEFEL, *Methods of conjugate gradients for solving linear systems*, Journal of Research of the National Bureau of Standards, 49 (1952), p. 409, <https://doi.org/10.6028/jres.049.044>, <http://dx.doi.org/10.6028/jres.049.044>.
- [24] S. HIRATA, *Tensor contraction engine: abstraction and automated parallel implementation of configuration-interaction, coupled-cluster, and many-body perturbation theories*, The Journal of Physical Chemistry A, 107 (2003), pp. 9887–9897, <https://doi.org/10.1021/jp034596z>, <http://dx.doi.org/10.1021/jp034596z>.
- [25] Y. HUANG, Y. CHENG, A. BAPNA, O. FIRAT, M. X. CHEN, D. CHEN, H. LEE, J. NGIAM, Q. V. LE, Y. WU, AND Z. CHEN, *Gpipe: Efficient training of giant neural networks using pipeline parallelism*, (2018), <http://arxiv.org/abs/1811.06965v5>, <https://arxiv.org/abs/1811.06965v5>.
- [26] M. INNES, *Don't unroll adjoint: Differentiating ssa-form programs*, (2018), <http://arxiv.org/abs/1810.07951v4>, <https://arxiv.org/abs/1810.07951v4>.
- [27] Y. LAFONT, *Interaction combinators*, Information and Computation, 137 (1997), pp. 69–101, <https://doi.org/10.1006/inco.1997.2643>, <http://dx.doi.org/10.1006/inco.1997.2643>.
- [28] D. LEIJEN AND E. MEIJER, *Parsec: Direct style monadic parser combinators for the real world*, (2001).
- [29] L. LIN AND J. LU, *Mathematical Introduction to Electronic Structure Theory - Iterative Solution of Symmetric Quasi-Definite Linear Systems*, Society for Industrial and Applied Mathematics, 2019.
- [30] M. LIN, *Automatic functional differentiation in jax*, (2023), <http://arxiv.org/abs/2311.18727v2>, <https://arxiv.org/abs/2311.18727v2>.
- [31] J. H. LUKAS DEVOS, MAARTEN VAN DAMME AND CONTRIBUTORS, *Tensoroperations.jl: Fast tensor operations using a convenient einstein index notation*, 10 2023, <https://doi.org/10.5281/zenodo.3245496>, <https://github.com/Jutho/TensorOperations.jl/blob/f047345fa3b76f81db3394b14bb0beac108dab22/docs/src/man/autodiff.md> (accessed 2024-06-01).
- [32] R. M. MARTIN, *Electronic Structure: Basic Theory And Practical Methods*, Cambridge Univ Press, 2004.
- [33] N. MARZARI, A. A. MOSTOFI, J. R. YATES, I. SOUZA, AND D. VANDERBILT, *Maximally localized wannier functions: Theory and applications*, Reviews of Modern Physics, 84 (2012), p. 1419.
- [34] N. MARZARI AND D. VANDERBILT, *Maximally localized generalized wannier functions for composite energy bands*, Physical Review B, 56 (1997), pp. 12847–12865, <https://doi.org/10.1103/physrevb.56.12847>, <http://dx.doi.org/10.1103/physrevb.56.12847>.
- [35] A. MEURER, C. P. SMITH, M. PAPROCKI, O. ČERTÍK, S. B. KIRPICHEV, M. ROCKLIN, A. KUMAR, S. IVANOV, J. K. MOORE, S. SINGH, ET AL., *Sympy: symbolic computing in python*, PeerJ Computer Science, 3 (2017), p. e103.
- [36] C. G. NELSON, *Techniques for program verification*, PhD thesis, Stanford University, Stanford, CA, USA, 1980. AAI8011683.
- [37] M. SCHÖNFINKEL, *Über die bausteine der mathematischen logik*, Mathematische Annalen,

- 92 (1924), pp. 305–316, <https://doi.org/10.1007/bf01448013>, <http://dx.doi.org/10.1007/bf01448013>.
- [38] J. C. SLATER, *A simplification of the hartree-fock method*, Physical Review, 81 (1951), pp. 385–390, <https://doi.org/10.1103/physrev.81.385>, <http://dx.doi.org/10.1103/physrev.81.385>.
- [39] M. STENDEL AND N. A. SPALDIN, *Accurate polarization within a unified wannier function formalism*, Physical Review B, 73 (2006), <https://doi.org/10.1103/physrevb.73.075121>, <http://dx.doi.org/10.1103/physrevb.73.075121>.
- [40] R. TATE, M. STEPP, Z. TATLOCK, AND S. LERNER, *Equality saturation: a new approach to optimization*, SIGPLAN Not., 44 (2009), p. 264–276, <https://doi.org/10.1145/1594834.1480915>, <https://doi.org/10.1145/1594834.1480915>.
- [41] J. THIJSEN, *Computational Physics*, Cambridge University Press, 2012.
- [42] K. S. THYGESEN, L. B. HANSEN, AND K. W. JACOBSEN, *Partly occupied wannier functions: Construction and applications*, Phys. Rev. B, 72 (2005), p. 125119, <https://doi.org/10.1103/PhysRevB.72.125119>, <https://link.aps.org/doi/10.1103/PhysRevB.72.125119>.
- [43] L. N. TREFETHEN, *Numerical Linear Algebra*, Society for Industrial and Applied Mathematics, 2022.
- [44] M. WILLSEY, C. NANDI, Y. R. WANG, O. FLATT, Z. TATLOCK, AND P. PANCHEKHA, *egg: Fast and extensible equality saturation*, Proc. ACM Program. Lang., 5 (2021), <https://doi.org/10.1145/3434304>, <https://doi.org/10.1145/3434304>.