Blind Baselines Beat Membership Inference Attacks for Foundation Models

Debeshee Das

Jie Zhang

Florian Tramèr

ETH Zurich

Abstract

Membership inference (MI) attacks try to determine if a data sample was used to train a machine learning model. For foundation models trained on unknown Web data, MI attacks can be used to detect copyrighted training materials, measure test set contamination, or audit machine unlearning. Unfortunately, we find that evaluations of MI attacks for foundation models are flawed, because they sample members and non-members from different distributions. For 8 published MI evaluation datasets, we show that *blind* attacks—that distinguish the member and non-member distributions without looking at any trained model—outperform state-of-the-art MI attacks. Existing evaluations thus tell us nothing about membership leakage of a foundation model's training data.

1 Introduction

Many foundation models (Bommasani et al., 2021) such as GPT-4 (OpenAI, 2023), Gemini (Gemini Team, 2023) and DALL-E (Ramesh et al., 2021) are trained on unknown data. There is great interest in methods that can determine if a piece of data was used to train these models. Such methods—called *membership inference attacks* (Shokri et al., 2017)—have been studied for foundation models in many recent works (Shi et al., 2023; Duan et al., 2024; Ko et al., 2023; Dubiński et al., 2024; Zhang et al., 2024; Meeus et al., 2023). Applications include privacy attacks (Carlini et al., 2021), demonstrating the use of copyrighted material (Meeus et al., 2024), detecting test data contamination (Oren et al., 2023), or auditing the efficacy of methods to "unlearn" training data (Bourtoule et al., 2021).

To evaluate the performance of a membership inference attack, it is common to train a model on a random subset of a larger dataset, and then ask the attacker to distinguish these *members* from the remaining *non-members* by interacting with the model. Emulating this setup for foundation models is hard, since we often do not have access to a held out set sampled from the *same distribution* as the training set.

Existing MI evaluations thus create member and non-member datasets *a posteriori*, typically by picking members from sources known or suspected to be in the targeted foundation model's training set, and then attempting to emulate the distribution of these sources to sample non-members.

Unfortunately, we show these strategies are severely flawed, and create easily distinguishable member and non-member distributions. As a special case of this flaw, concurrent work of Duan et al. (2024) and Maini et al. (2024) finds a temporal shift between members and non-members in the Wiki-MIA dataset (Shi et al., 2023). We show this issue is persistent by identifying significant distribution shifts (beyond temporal shifts) in 8 MI evaluation datasets for foundation models, for both text and vision. Worse, we show that existing MI attacks perform "worse than chance" on these datasets. Specifically, we design "blind" attacks, *which completely ignore the target model*, and outperform all reported results from state-of-the-art MI attacks (see Table 1).

Our methods are naive: for some datasets with a temporal shift, we just apply a threshold to specific dates extracted from each sample; for other text or text-vision datasets, we build simple bag-of-words or n-gram classifiers on captions.

Current MI attacks for foundation models thus cannot be relied on, as we cannot rule out that they are (poorly) inferring membership based on data *features*, without extracting any actual membership

MI dataset	Metric	Best Reported	Ours
WikiMIA ¹	TPR@5%FPR	$43.2\%^{2}$	94.4%
$\operatorname{BookMIA^1}$	AUC ROC	$88.0\%^{1}$	90.5%
Temporal Wiki ³	AUC ROC	$79.6\%^3$	$\mathbf{79.9\%}$
Temporal arXiv ³	AUC ROC	$72.3\%^{3}$	73.1%
$ArXiv-1 month^6$	TPR@1%FPR	$5.9\%^6$	13.4%
$Multi-Webdata^4$	TPR@1%FPR	$40.3\%^{4}$	83.5%
$LAION-MI^5$	TPR@1%FPR	$2.5\%^5$	9.9%
$\operatorname{Gutenberg}^6$	TPR@1%FPR	$18.8\%^6$	59.6%

Table 1: **MI evaluation datasets for foundation models are flawed.** Our *blind* attacks distinguish members from non-members better than existing attacks, without looking at any model.

¹(Shi et al., 2023) ²(Zhang et al., 2024) ³(Duan et al., 2024) $\frac{1}{4}(V_{2,2} + z_{1,2}) = \frac{5}{2}(Duh)(z_{1,2}) + \frac{1}{2}(Duh)(z_{1,2}) + \frac{$

 4 (Ko et al., 2023) 5 (Dubiński et al., 2024) 6 (Meeus et al., 2023)

leakage from the model. Future MI attacks should be evaluated on models with a clear train-test split, e.g., using the Pile (Gao et al., 2020) or a random subset of DataComp (Gadre et al., 2024) or DataComp-LM (Li et al., 2024).

2 Background and Related Work

Web-scale training datasets. Foundation models are often trained on massive datasets collected from web crawls, such as C4 (Raffel et al., 2020), the Pile (Gao et al., 2020) or LAION (Schuhmann et al., 2022). However, there has been a trend towards using undisclosed training sets for models like GPT-2 to GPT-4 (Radford et al., 2019; OpenAI, 2023), Gemini (Gemini Team, 2023) or DALL-E (Ramesh et al., 2021). Even recent open models like LLaMA (Touvron et al., 2023) do not release information about their training dataset. Some datasets have been released for research purposes, such as RedPajama (Together, 2023), Dolma (Soldaini et al., 2024) or LAION (Schuhmann et al., 2022). Notably, these datasets lack a designated test set.

Membership inference attacks. Membership inference attacks aim to determine whether a given data point was used to train a machine learning model (Shokri et al., 2017). Early attacks applied a *global* decision function to all samples (e.g., by thresholding the model's loss (Yeom et al., 2018)). Current state-of-the-art attacks calibrate the attack threshold to the difficulty of each sample (Carlini et al., 2022).

Membership inference for foundation models. Membership inference attacks have been applied to LLMs (Shi et al., 2023; Duan et al., 2024; Zhang et al., 2024; Meeus et al., 2023), diffusion models (Dubiński et al., 2024), CLIP (Ko et al., 2023), and other foundation models. The motivations for these attacks include using them as a component of a privacy attack (Carlini et al., 2021), for evaluating unlearning methods (Shi et al., 2023), or for data provenance tests to detect the use of copyrighted data (Meeus et al., 2024). Due to the lack of a dedicated test set (and possibly even an unknown training set) for the targeted models, many of these works design custom evaluation datasets for membership inference attacks, by collecting sources of data that were likely used (respectively not used) for training.

Evaluating membership inference. Membership inference attacks were originally evaluated with average-case metrics such as the ROC AUC on a balanced set of members and non-members (Shokri et al., 2017). More recent work advocates for evaluating the attack's performance in the *worst-case*, typically by reporting the true-positive rate (TPR) at low false-positive rates (FPR) (Carlini et al., 2022).

Membership inference evaluations are usually set up so that a baseline attack (which does not query the target model) achieves 50% AUC (or equal TPR and FPR). Some authors have also considered cases where the attacker has a non-uniform prior (Jayaraman et al., 2020). In either case, the goal of a MI attack is to extract information from the model to beat a baseline inference without access to the model.

Many MI evaluation datasets for foundation models introduce distribution shifts between members and non-members, which allows for baseline attacks with non-trivial success. In concurrent work, Duan et al. (2024) and Maini et al. (2024) identify a temporal shift between members and non-members in one

dataset—WikiMIA (Shi et al., 2023)—and demonstrate that some attacks fail when temporal shifts are removed. Our work shows that this issue is much broader: virtually all evaluation sets proposed for membership inference on foundation models are flawed. We further show that existing attacks do not just exploit distribution shifts, but they do so *sub-optimally* and are easily beat by blind baselines. These attacks thus perform "worse than chance".

3 Blindly Inferring Membership

3.1 Distribution Shifts in MI Evaluation Datasets

MI evaluations measure the ability to distinguish a model's training set members from non-members. A baseline attack (with no knowledge of the model) should do no better than random guessing—i.e., an AUC of 50% or equal TPR and FPR. For current MI evaluations sets for foundation models, this is not the case, due to intrinsic differences between members and non-members. We discuss the most common reasons for this discrepancy below.

Temporal shifts. MI evaluation sets based on a hard data cutoff for some evolving Web source (e.g., Wikipedia or arXiv) introduce a temporal shift between members and non-members. We can thus blindly distinguish members from non-members if we can answer a question of the form: "is this data from before or after 2023?"

Biases in data replication. Even if we know how the training set was sampled, building an indistinguishable dataset of non-members is challenging (Recht et al., 2019). Slight variations in the procedures used to create the two datasets (Engstrom et al., 2020) could be exploited by a blind attack.

Distinguishable tails. Some works filter and process the data to maximally align the member and non-member distributions (e.g., by matching linguistic characteristics). However, distributions that are hard to distinguish *on average* may still be easy to distinguish for *data outliers*.

3.2 Blind Attack Techniques

In this section, we introduce simple "blind" attack techniques to distinguish members from non-members in MI evaluations. The datasets we consider consist of either text, or images and text. For simplicity, we focus only on the text modality in both cases. We do not aim for our blind attacks to be optimal. We prioritize simple and interpretable methods to show that existing evaluation datasets suffer from large distribution shifts. Our blind attacks typically aim to achieve a high TPR at a low FPR (i.e., very confident predictions of membership for as many samples as possible).

Date detection. Some text samples (e.g., from Wikipedia, arXiv, etc.) might contain specific dates. Heuristically, it is unlikely that a text contains specific dates referencing the future. Thus, to place an upper-bound on the date at which a text was written, we simply extract all dates present in the text (using simple regular expressions). We then predict that a sample is a member if all referenced dates fall before some threshold. Such an approach can have false positives when a text sample only references dates far in the past.

Bag-of-words classification. Explicit dates are just one textual feature we can use. More generally, we can aim to predict membership from arbitrary words in the text. To this end, we train a simple bag-of-words classifier. Here we have to guard against overfitting, since we can always find some word combinations that appear in members and not in non-members (e.g., the exact text of the member samples). So we train our classifier on 80% of the members and non-members, and then evaluate the blind attack on the remaining 20%. As some of the evaluation datasets are small, we aggregate results over a 10-fold cross-validation.

Greedy rare word selection. The above classifier should work well on average, but might not be optimal at low FPRs. Here, we take a simple greedy approach: we extract all n-grams (for $n \in [1, 5]$) and sort them by their TPR-to-FPR ratio on part of the data (i.e., for each n-gram, we compute the fraction of members and non-members that contain this n-gram). We then pick the n-gram with the best

MI dataset	Metric	Best attack	Ours
	Temporal shi	fts	
WikiMIA	TPR@5%FPR AUC ROC	$43.2\%\ 83.9\%$	${94.4\%^{\dagger}}\ {98.7\%^{\dagger}}$
BookMIA	TPR@5%FPR AUC ROC	- 88.0%	$egin{array}{c} 60.8\%^{\dagger}\ 90.5\%^{\dagger} \end{array}$
Temporal Wiki	TPR@1%FPR AUC ROC	79.6%	$egin{array}{c} 33.5\%^{\ddagger}\ 79.9\%^{\dagger} \end{array}$
Temporal arXiv	TPR@1%FPR AUC ROC	-74.5%	$egin{array}{c} 10.8\%^{\ddagger} \ 75.6\%^{\dagger} \end{array}$
ArXiv-1 month	TPR@1%FPR AUC ROC	$5.9\% \\ 67.8\%$	$egin{array}{c} 13.4\%^* \ 68.4\%^\dagger \end{array}$
	Biased replicat	tion	
Multi-Webdata	TPR@1%FPR AUC ROC	$40.3\%\ 81.7\%$	$83.5\%^{\ddagger}\ 96.9\%^{\dagger}$
LAION-MI	$\mathrm{TPR}@1\%\mathrm{FPR}$	2.5%	$9.9\%^{\ddagger}$
Gutenberg	TPR@1%FPR AUC ROC	$\frac{18.8\%}{85.6\%}$	$59.6\%^{\ddagger}\ 96.4\%^{\dagger}$

Table 2: Extended version of Table 1, with the results from our blind attacks compared to the best reported MI attack on each evaluation set. We report the same metrics as used in prior work, and add TPR at 1% FPR if no prior results are reported.

* Date detection † Bag-of-words ‡ Greedy rare words

ratio, and repeat this procedure. Given a set of selected n-grams, we evaluate our attack on a held-out set by predicting that a sample is a member if it contains any of these n-grams.

4 Case Studies

We now study 8 membership inference datasets proposed for large language models and diffusion models. Table 2 summarizes our results: for each dataset, we create blind attacks that outperform existing MI attacks that have access to a trained model. We average the results from multiple runs and report for the same metric used in prior work, either AUC ROC or TPR at low FPR. Whenever possible, we use the exact datasets released by the authors to ensure that no biases are introduced. For datasets that are not publicly available (arXiv-1 month and Gutenberg (Meeus et al., 2023)), we follow the specific collection steps outlined in the respective work to create similar datasets.

4.1 Temporal Shifts

4.1.1 WikiMIA

The dataset and evaluation. The WIKIMIA dataset (Shi et al., 2023) selects members from Wikipedia event pages from before 01/01/2017 and non-members from after 01/01/2023. It thus serves as an MI evaluation set for any LLM trained in between those dates. The best reported prior MI attack on this evaluation set is from the Min-K%++ method of Zhang et al. (2024).

Our attack. We first apply our naive date detection attack. We extract all dates in the snippet and check if the latest one is from before 2023. Using this, we obtain a 52.3% TPR at 5% FPR. This already beats the state-of-the-art MI attack evaluated on this dataset (see Table 2). To obtain an even stronger

blind attack, we train a bag-of-words classifier on 80% of the dataset, and evaluate on the remaining 20%. This classifier achieves a near perfect TPR of 94.4%.

4.1.2 BookMIA

The dataset and evaluation. This dataset (Shi et al., 2023) is constructed from 512-token length text snippets from various books. Members are selected from books in the Books3 corpus that have been shown to be memorized by GPT-3. Non-members are taken from books that were first published in or after 2023. In the evaluation of Shi et al. (2023), their Min-K% method obtains the highest AUC against GPT-3.

Our attack. We train a bag-of-words classifier on 80% of the dataset, and evaluate on the remaining 20%. As shown in Table 2, a bag-of-words classifier achieves a 90.5% AUC ROC and beats state-of-the-art MI attacks against GPT-3.¹

4.1.3 Temporal Wiki & arXiv

The datasets and evaluations. Duan et al. (2024) hypothesize that some MI attacks evaluated on Wiki-MIA may indvertently exploit temporal shifts between members and non-members. To show-case this, they create datasets that sample members from the Wikipedia and arXiv snippets in the Pile (Gao et al., 2020) and non-members from the same sources at a later date.

In more detail, in the Temporal arXiv Dataset, members are snippets from arXiv papers posted prior to July 2020 and contained in the Pile training data, while the non-members are sampled from arXiv papers from successively different time ranges after the Pile cutoff of July 2020. The Temporal Wikipedia dataset is also constructed based on the same principle as the WikiMIA dataset, but selects non-member articles from RealTimeData WikiText data created after August 2023 while members are from The Pile from before 03/01/2020. The authors show that existing MI attacks applied to Pythia models improve as the temporal shift increases, with the MI attack of Carlini et al. (2022) performing best.

Our attacks. We show that even if existing attacks do rely on some temporal features in the Temporal Wikipedia and Temporal arXiv datasets, they do so sub-optimally. As for the prior datasets, we train a bag-of-words classifier which outperforms prior MI results on these datasets. Specifically, we focus on the "2020-08" split (where non-members are taken from arXiv articles in August 2020, right after the Pile cutoff). There, our blind attack slightly outperforms the AUC and TPR at 1% FPR of the best reported MI attack on both datasets (see Table 2).

4.1.4 One-month arXiv

The dataset and evaluation. Meeus et al. (2023) also note that naively re-collecting data from arXiv causes a large temporal shift. Instead, they thus pick the non-members as close after the model's cutoff date as possible. They build an MI evaluation set by taking all arXiv articles from the RedPajama dataset (Together, 2023) as members, and all articles from March 2023 (right after the dataset's cutoff date) as non-members. In contrast to the Temporal arXiv dataset we looked at previously, this dataset uses full arXiv articles rather than just snippets. The authors propose a new MI attack that relies on textual feature extractors, and evaluate it on the OpenLLaMA model (Geng & Liu, 2023) which was trained on RedPajama.

Our attack. As this dataset is not public, we replicate a similar setup by taking all articles before March 2023 in RedPajama as the members, and all articles from March 2023 as the non-members. The issue with this dataset is that the distributions of members and non-members are still incredibly easy to distinguish at one end: papers that are *much older* than the cutoff date are guaranteed to be members. And since this dataset uses the full LaTex body of each article, determining a paper's approximate date is very easy: we just look at the paper's citations. We use a regex to find all \cite commands, and extract the year in the citation keyword if it exists. We guess that a paper is a member if it only cites

 $^{^{1}}$ To control for book- and author-specific features (such as character names), we repeat the experiment with no author appearing in both our classifier's train and test sets. This still results in a significantly above chance AUC ROC of 80.3%.

papers from before 2022. This trivial baseline yields 13.4% TPR without any false positives, over twice as high as the TPR at 1% FPR obtained by the best MI attack in (Meeus et al., 2023).

4.2 Biases in Data Replication and Distinguishable Tails

4.2.1 Multi-Webdata

The dataset and evaluation. To evaluate MI attacks on diffusion models, Ko et al. (2023) collect multiple web-scale datasets of captioned images: CC3M (Sharma et al., 2018), CC12M (Changpinyo et al., 2021), (LAION (Schuhmann et al., 2022) and MS-COCO (Lin et al., 2014)). They argue that since these datasets are sampled from a common global source (i.e., captioned images from the Web), they can serve as a natural evaluation set for MI attacks. Specifically, the authors train a diffusion model on CC12M (the members), and sample the non-members from the union of the other three datasets.² Ko et al. (2023) evaluate the performance of three newly proposed MI attacks on target models from the ViT (Dosovitskiy et al., 2020) and ResNet (He et al., 2016) families trained on CC12M.

Our attack. For simplicity, we focus only on the image captions and ignore the visual content. We train a bag-of-words binary classifier on the captions, achieving a TPR of 75.7% at a 1% FPR, far superior to the best MI attack methods evaluated on these datasets (see Table 2). It is likely that incorporating visual features into the classifier could lead to an even stronger blind attack.

4.2.2 LAION-MI

The dataset. Dubiński et al. (2024) explicitly try to control for and minimize biases in data replication. However, their techniques still leave distinguishable tails. To create an evaluation dataset for a model trained on LAION (Schuhmann et al., 2022), they rely on the multilingual-LAION dataset (Schuhmann et al., 2022) to sample non-members. This dataset was sampled from the Web in a similar way to LAION, except that the captions are not in English and the images were not filtered for quality.

To align the two distributions, the authors first apply the same selection process that was used to select images in LAION: (1) they discard all images from multilingual LAION with an "aesthetics score" below some threshold; (2) they translate the non-member captions to English, using Facebook's M2M100 1.2B They then train a distinguisher on top of image captions, and select a subset of the data where members and non-members are hard to distinguish *on average*. The authors use a PCA visualization to confirm that the two distributions closely match.

The authors evaluate multiple MI attacks in white-box, grey-box and black-box settings, obtaining a best score of 2.5% TPR@1%FPR on their LAION-MI dataset.

Our attack. We posit that *outlier* members would still be easy to distinguish from non-members. To provide some intuition, we started by looking for individual *characters* that appear much more frequently in members than in non-members. We show the five characters with the highest distinguishing power in Table 3.

We note that there are non-English characters (Russian 'o' and 'T') that appear predominantly in *members*. This is likely because the original LAION captions were selected on the basis of being *primarily* in English. In contrast, since the captions from the non-members were output by a translation model, they are unlikely to contain non-English characters. The presence of special characters such as xa0 (a non-breaking space) are similarly due to biases in translation: this character is not part of the translation model's output vocabulary.

To boost the power of this approach, we apply our greedy selection algorithms to all n-grams of up to 5 characters. We use 80% of the data to pick the n-grams with the highest TPR-to-FPR ratio until we hit a 1% FPR. At that point, we obtain a 9.9% TPR on the evaluation set—surpassing the best MI attack.

 $^{^{2}}$ Wu et al. (2023) use a similar approach, and choose members and non-members from different text-vision datasets.

Character	Members	Non-members
	0.60%	0.00%
xa0	0.30%	0.00%
	0.21%	0.00%
0	0.23%	0.03%
Т	0.15%	0.03%

Table 3: Characters with the highest distinguishing power among members and non-members for LAION-MI.

4.2.3 Project Gutenberg

The dataset and evaluation. This dataset (Meeus et al., 2023) consists of books from Project Gutenberg. The members are books contained in the RedPajama dataset (Together, 2023), more specifically the set of "PG-19" books collected by Rae et al. (2019) which were all originally published before 1919. The non-members consist of books added to the Project Gutenberg repository after the creation of the PG-19 corpus in February 2019. To mitigate the obvious distribution shift in the publication years of members and non-members, Meeus et al. (2023) filter both the members and non-members to only contain books published between 1850 and 1910 (i.e., members are books published between 1850 and 1910, which were added to Project Gutenberg before February 2019. Non-members are books that were originally published in the same period, but added to Project Gutenberg after February 2019). The authors evaluate a new MI attack (see Section 4.1.4 for details) against the OpenLLaMA model (Geng & Liu, 2023) trained on RedPajama.

Our attack. While the publication dates of the members and non-members are similarly distributed, we find that *the date on which a book is added to Project Gutenberg* still introduces a noticeable distribution shift. Indeed, it appears that the format of the preface metadata that Project Gutenberg adds to books has changed at some point between the collection of PG-19 and the non-member corpus (e.g., the link to the HTML version of a book used to have a .htm file extension, and this was changed to a .html extension for books added after a certain date). By exploiting such small discrepancies, our greedy n-gram attack applied to the first 1,000 characters of a book achieves 59.6% TPR at a 1% FPR, 3 times higher than the best MI attack evaluated on this dataset.

Of course, it may be possible to preprocess this particular dataset to get rid of these formatting discrepancies. Nevertheless, we believe our results illustrate how brittle the process of re-collecting an identically distributed non-member set can be. Moreover, even if we ignore any formatting information, and apply our attack directly to the book text, we can still distinguish members and non-members far better than chance, with a TPR of 16.6% at a 1% FPR.

5 A Path Forward: the Pile, DataComp and DataComp-LM

As we have seen, building MI evaluation datasets *a posteriori* is incredibly challenging, due to the many possibilities for distribution shift. It may be possible to apply more rigorous filtering techniques to minimize these shifts, so that even strong blind attacks cannot reliably distinguish members and non-members. Any MI attack's performance should then be compared against these strong blind baselines.

An alternative avenue is to forego MI evaluations on arbitrary foundation models, and focus on those models for which identically distributed sets of members and non-members are available. A prime example is the Pile (Gao et al., 2020), which has an official test set. Models trained on the Pile training set—e.g., Pythia (Biderman et al., 2023) or GPT-NeoX-20B citeblack2022gpt—are thus a popular target for MI attack evaluations (see e.g., (Duan et al., 2024; Maini et al., 2024; Li et al., 2023)). Unfortunately, the Pile only contains text, and is too small to train state-of-the-art language models.

A more recent and broadly applicable alternative is to use models trained on the DataComp (Gadre et al., 2024) and DataComp-LM (Li et al., 2024) benchmarks. These benchmarks contribute multiple models (ViTs and LLMs) trained on data *sampled randomly* from a larger dataset. More precisely, these benchmarks introduce two datasets, CommonPool and DCLM-POOL, which contain respectively 12.8 billion image-text pairs and 240 trillion text tokens sampled from Common Crawl. To enable experiments at

Table 4: Models trained on datasets with *random* train-test splits for Data-Comp (Gadre et al., 2024) and DataComp-LM (Li et al., 2024). For each dataset pool, we report the pool's absolute size (in image-text pairs, respectively tokens) and its relative size compared to the global pool that it was randomly sampled from. Gadre et al. (2024) and Li et al. (2024) have pretrained ViTs and LLMs on each pool size.

Modality	Pool Name	Pool Size	Models
Vision+Text	CommonPool Large CommonPool Medium CommonPool Small	$\begin{array}{c} 1.280 \mathrm{B} \ (10\%) \\ 0.128 \mathrm{B} \ (1\%) \\ 0.013 \mathrm{B} \ (0.1\%) \end{array}$	ViT-B/16 ViT-B/32 ViT-B/32
Text	DCLM 400M-1x DCLM 1B-1x DCLM 1B-5x DCLM 7B-1x DCLM 7B-5x	0.47T (0.2%) 1.64T (0.2%) 8.20T (3.4%) 7.85T (3.3%) 15.7T (6.5%)	412M LLM 1.4B LLM 1.4B LLM 6.9B LLM 6.9B LLM

smaller budgets, the authors produce smaller data pools sampled randomly from the full pool. They then train a variety of models on each pool (see Table 4).^{3,4}

A minor complication is that most models in the DataComp and DataComp-LM benchmarks are not trained on the entirety of a pool. Rather, the benchmarks encourage models to be trained on *filtered* datasets: given a pool of data \mathcal{P} and a binary filter $f : \mathcal{X} \mapsto \{0, 1\}$, models are trained on the filtered pool $\{x \in \mathcal{P} \mid f(x)\}$. This training set is thus no longer a random subset of the full dataset. But this is easily remedied by applying exactly the same filter f to select the non-members.

We encourage future work on MI attacks for foundation models to evaluate their methods on these models and datasets.

As part of their experiments, Gadre et al. (2024) and Li et al. (2024) trained CLIP models of various sizes and a 1B parameter language model on *random* subsets of these datasets. These models and datasets might thus form an ideal testbed for MI evaluations on web-scale text and vision models.

Future web-scale dataset and model developers could similarly release an official IID split to enable rigorous MI evaluations for a wider variety of models and modalities.

6 Conclusion

We have shown that current evaluations of MI attacks for foundation models cannot be trusted, as members and non-members can be reliably distinguished by simple blind attacks with no knowledge of the model. State-of-the-art MI attacks may thus be ineffective at extracting any actual membership information, and cannot be relied on for applications such as copyright detection or auditing unlearning methods. The MI evaluation datasets we investigated should likely be discarded due to the large distribution shifts between members and non-members, and replaced by datasets with a random train-test split—e.g., the Pile or DataComp.

References

Biderman, S., Schoelkopf, H., Anthony, Q. G., Bradley, H., O'Brien, K., Hallahan, E., Khan, M. A., Purohit, S., Prashanth, U. S., Raff, E., et al. Pythia: A suite for analyzing large language models across training and scaling. In *International Conference on Machine Learning*, pp. 2397–2430. PMLR, 2023.

Bommasani, R., Hudson, D. A., Adeli, E., Altman, R., Arora, S., von Arx, S., Bernstein, M. S., Bohg, J.,

³https://github.com/mlfoundations/datacomp

⁴https://github.com/mlfoundations/dclm.

Bosselut, A., Brunskill, E., et al. On the opportunities and risks of foundation models. arXiv preprint arXiv:2108.07258, 2021.

- Bourtoule, L., Chandrasekaran, V., Choquette-Choo, C. A., Jia, H., Travers, A., Zhang, B., Lie, D., and Papernot, N. Machine unlearning. In 2021 IEEE Symposium on Security and Privacy (SP), pp. 141–159. IEEE, 2021.
- Carlini, N., Tramer, F., Wallace, E., Jagielski, M., Herbert-Voss, A., Lee, K., Roberts, A., Brown, T., Song, D., Erlingsson, U., et al. Extracting training data from large language models. In 30th USENIX Security Symposium (USENIX Security 21), pp. 2633–2650, 2021.
- Carlini, N., Chien, S., Nasr, M., Song, S., Terzis, A., and Tramer, F. Membership inference attacks from first principles. In 2022 IEEE Symposium on Security and Privacy (SP), pp. 1897–1914. IEEE, 2022.
- Changpinyo, S., Sharma, P., Ding, N., and Soricut, R. Conceptual 12m: Pushing web-scale image-text pre-training to recognize long-tail visual concepts. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 3558–3568, June 2021.
- Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., et al. An image is worth 16x16 words: Transformers for image recognition at scale. arXiv preprint arXiv:2010.11929, 2020.
- Duan, M., Suri, A., Mireshghallah, N., Min, S., Shi, W., Zettlemoyer, L., Tsvetkov, Y., Choi, Y., Evans, D., and Hajishirzi, H. Do membership inference attacks work on large language models? arXiv preprint arXiv:2402.07841, 2024.
- Dubiński, J., Kowalczuk, A., Pawlak, S., Rokita, P., Trzciński, T., and Morawiecki, P. Towards more realistic membership inference attacks on large diffusion models. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 4860–4869, 2024.
- Engstrom, L., Ilyas, A., Santurkar, S., Tsipras, D., Steinhardt, J., and Madry, A. Identifying statistical bias in dataset replication. In *International Conference on Machine Learning*, pp. 2922–2932. PMLR, 2020.
- Gadre, S. Y., Ilharco, G., Fang, A., Hayase, J., Smyrnis, G., Nguyen, T., Marten, R., Wortsman, M., Ghosh, D., Zhang, J., et al. DataComp: In search of the next generation of multimodal datasets. *Advances in Neural Information Processing Systems*, 36, 2024.
- Gao, L., Biderman, S., Black, S., Golding, L., Hoppe, T., Foster, C., Phang, J., He, H., Thite, A., Nabeshima, N., et al. The Pile: An 800GB dataset of diverse text for language modeling. arXiv preprint arXiv:2101.00027, 2020.
- Gemini Team. Gemini: a family of highly capable multimodal models. arXiv preprint arXiv:2312.11805, 2023.
- Geng, X. and Liu, H. OpenLLaMA: An open reproduction of LLaMA, May 2023. URL https://github.com/openlm-research/open_llama.
- He, K., Zhang, X., Ren, S., and Sun, J. Deep residual learning for image recognition. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 770–778, 2016.
- Jayaraman, B., Wang, L., Knipmeyer, K., Gu, Q., and Evans, D. Revisiting membership inference under realistic assumptions. arXiv preprint arXiv:2005.10881, 2020.
- Ko, M., Jin, M., Wang, C., and Jia, R. Practical membership inference attacks against large-scale multimodal models: A pilot study. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4871–4881, 2023.
- Li, J., Fang, A., Smyrnis, G., Ivgi, M., Jordan, M., Gadre, S., Bansal, H., Guha, E., Keh, S., Arora, K., et al. DataComp-LM: In search of the next generation of training sets for language models. arXiv preprint arXiv:2406.11794, 2024.
- Li, M., Wang, J., Wang, J., and Neel, S. MoPe: Model perturbation-based privacy attacks on language models. arXiv preprint arXiv:2310.14369, 2023.

- Lin, T.-Y., Maire, M., Belongie, S., Hays, J., Perona, P., Ramanan, D., Dollár, P., and Zitnick, C. L. Microsoft COCO: Common objects in context. In *Computer Vision–ECCV 2014: 13th European Conference, Zurich, Switzerland, September 6-12, 2014, Proceedings, Part V 13*, pp. 740–755. Springer, 2014.
- Maini, P., Jia, H., Papernot, N., and Dziedzic, A. LLM dataset inference: Did you train on my dataset?, 2024.
- Meeus, M., Jain, S., Rei, M., and de Montjoye, Y.-A. Did the neurons read your book? Document-level membership inference for large language models. arXiv preprint arXiv:2310.15007, 2023.
- Meeus, M., Shilov, I., Faysse, M., and de Montjoye, Y.-A. Copyright traps for large language models. arXiv preprint arXiv:2402.09363, 2024.
- OpenAI. GPT-4 technical report. arXiv preprint arXiv:2303.08774, 2023.
- Oren, Y., Meister, N., Chatterji, N., Ladhak, F., and Hashimoto, T. B. Proving test set contamination in black box language models. arXiv preprint arXiv:2310.17623, 2023.
- Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., Sutskever, I., et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.
- Rae, J. W., Potapenko, A., Jayakumar, S. M., and Lillicrap, T. P. Compressive transformers for longrange sequence modelling. arXiv preprint arXiv:1911.05507, 2019.
- Raffel, C., Shazeer, N., Roberts, A., Lee, K., Narang, S., Matena, M., Zhou, Y., Li, W., and Liu, P. J. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of machine learning research*, 21(140):1–67, 2020.
- Ramesh, A., Pavlov, M., Goh, G., Gray, S., Voss, C., Radford, A., Chen, M., and Sutskever, I. Zero-shot text-to-image generation. In *International Conference on Machine Learning*, 2021.
- Recht, B., Roelofs, R., Schmidt, L., and Shankar, V. Do ImageNet classifiers generalize to ImageNet? In *International conference on machine learning*, pp. 5389–5400. PMLR, 2019.
- Schuhmann, C., Beaumont, R., Vencu, R., Gordon, C., Wightman, R., Cherti, M., Coombes, T., Katta, A., Mullis, C., Wortsman, M., et al. LAION-5B: An open large-scale dataset for training next generation image-text models. Advances in Neural Information Processing Systems, 35:25278–25294, 2022.
- Sharma, P., Ding, N., Goodman, S., and Soricut, R. Conceptual Captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning. In *Proceedings of the 56th Annual Meeting of* the Association for Computational Linguistics, 2018.
- Shi, W., Ajith, A., Xia, M., Huang, Y., Liu, D., Blevins, T., Chen, D., and Zettlemoyer, L. Detecting pretraining data from large language models. arXiv preprint arXiv:2310.16789, 2023.
- Shokri, R., Stronati, M., Song, C., and Shmatikov, V. Membership inference attacks against machine learning models. In 2017 IEEE symposium on security and privacy (SP), pp. 3–18. IEEE, 2017.
- Soldaini, L., Kinney, R., Bhagia, A., Schwenk, D., Atkinson, D., Authur, R., Bogin, B., Chandu, K., Dumas, J., Elazar, Y., et al. Dolma: An open corpus of three trillion tokens for language model pretraining research. arXiv preprint arXiv:2402.00159, 2024.
- Together. RedPajama: an open dataset for training large language models, 2023. URL https://github.com/togethercomputer/RedPajama-Data.
- Touvron, H., Lavril, T., Izacard, G., Martinet, X., Lachaux, M.-A., Lacroix, T., Rozière, B., Goyal, N., Hambro, E., Azhar, F., et al. LLaMA: Open and efficient foundation language models. arXiv preprint arXiv:2302.13971, 2023.
- Wu, Y., Yu, N., Li, Z., Backes, M., and Zhang, Y. Membership inference attacks against text-to-image generation models, 2023. URL https://openreview.net/forum?id=J41IW8Z7mE.
- Yeom, S., Giacomelli, I., Fredrikson, M., and Jha, S. Privacy risk in machine learning: Analyzing the connection to overfitting. In 2018 IEEE 31st computer security foundations symposium (CSF), pp. 268–282. IEEE, 2018.

Zhang, J., Sun, J., Yeats, E., Ouyang, Y., Kuo, M., Zhang, J., Yang, H., and Li, H. Min-K%++: Improved baseline for detecting pre-training data from large language models. *arXiv preprint arXiv:2404.02936*, 2024.