Greedy Gray Codes for some Restricted Classes of Binary Words

Nathanaël Hassler

Vincent Vajnovszki

Laboratoire d'Informatique de Bourgogne Dijon, France

nathanael.hassler@ens-rennes.fr vincent.vajnovszki@u-bourgogne.fr

Dennis Wong

Macao Polytechnic University Macao, China cwong@uoguelph.ca

We investigate the existence of greedy Gray codes, based on the choice of the first element in the code, for two classes of binary words: generalized Fibonacci words and generalized Dyck words.

1 Introduction

1.1 Constrained binary words

1's run constrained binary words

Let $n, p \in \mathbb{N}$, $p \ge 2$, and $F_n(p)$ be the set of length *n* binary words with no *p* consecutive 1's. $F_n(2)$ is counted by the Fibonacci numbers f_n , and in general, $F_n(p)$ is counted by the *p*-order Fibonacci numbers $f_n^{(p)}$. Now let $k \in \mathbb{N}$, and $F_n(p,k)$ be the subset of words in $F_n(p)$ of weight *k* (i.e., with exactly *k* 1's). $F_n(p,k)$ is counted by the univariate *p*-nomial coefficient.

Prefix constrained binary words

Let $k, n, p \in \mathbb{N}$ with $(p+1)k \le n$, and $C_n(p,k)$ be the set of length *n* binary words of weight *k* with the property that any prefix contains at least *p* times as many 0's as 1's. In particular:

- $C_n(0,k)$ is the set of length *n* binary words of weight *k* (combinations in binary word representation),
- $C_{2n}(1,n)$ is the set of length 2n Dyck words, and it is counted by the Catalan numbers $\binom{2n}{n} \binom{2n}{n-1} = \frac{1}{n+1} \binom{2n}{n}$,
- $C_{3n}(2,n)$ is in bijection with size 3n ternary trees (see A001764 in [4]).

More generally, $C_{(p+1)n}(p,n)$ is counted by $\frac{1}{pn+1}\binom{(p+1)n}{n}$, known as the Pfaff–Fuss–Catalan numbers, and the cardinality of $C_n(p,k)$ is established for instance in [5, Equation (2)], using generating functions:

$$|C_n(p,k)| = \binom{n}{k} - p\binom{n}{k-1}.$$
(1)

S. Brlek and L. Ferrari (Eds.): GASCom 2024 EPTCS 403, 2024, pp. 108–112, doi:10.4204/EPTCS.403.23 © N. Hassler, V. Vajnovszki, D. Wong This work is licensed under the Creative Commons Attribution License.

1.2 Gray codes and greedy algorithms

A Gray code for a class of combinatorial objects is a list that contains each object from the class exactly once such that any two consecutive objects in the list differ only by a 'small change' [3]. In this paper we restrict ourselves to Gray codes for restricted classes of same length and same weight binary words (the weight of a binary word being its number of 1's). The 'small changes' we consider here are homogeneous transpositions: two binary words differ by a *homogeneous* transposition if one can be obtained from the other by transposing a 1 with a 0, and there are no 1's between the transposed bits. A Gray code is called homogeneous if consecutive words differ in a such a way. A list of words is *suffix partitioned* if words with the same suffix are consecutive in the list.

The next definition of the *greedy Gray code algorithm* is a specialisation of that introduced in [6] to particular cases of binary words, see also [7].

Definition 1.1. For a set *S* of same length and same weight binary words the *greedy Gray code algorithm* to obtain a Gray code list \mathcal{L} for the set *S* is:

- 1. Initialize \mathscr{L} with a particular word in *S*.
- 2. For the last word in \mathcal{L} , homogeneously transposes the leftmost possible 1 with the leftmost possible 0, such that the obtained word is in *S* but not in \mathcal{L} .
- 3. If at point 2. a new word is obtained, then append it to the list \mathscr{L} and return to point 2.

In the following we will say that the list \mathcal{L} is obtained by applying the greedy algorithm for *S* to α , where α is the initial word of \mathcal{L} . Depending on the choice of α , it can happen that the obtained list \mathcal{L} is not an exhaustive one for *S*.

2 Tail partitioned lists

The tail of a binary word is its unique suffix of the form $011\cdots 1$, and the only words with no tail have the form $11\cdots 1$. Note that 0 is also a tail, for the words ending by 0.

A list of binary words is *increasing (decreasing) tail partitioned* if words with tails of length ℓ appear before (after) words with tail of length $\ell + 1$, for any $\ell \ge 1$.

Definition 2.1. A list \mathscr{L} of same length binary words is *recursive tail partitioned* if it is empty, or

- it is increasing or decreasing tail partitioned, and
- for any tail t, the list obtained by: (i) considering the sublist of \mathscr{L} of words with tail t, then (ii) erasing the tail t in each word of this sublist, is in turn recursive tail partitioned.

In the following \cdot denotes the concatenation (of two words, or of each word in a list with a word) and the comma appends lists. With this notation, \mathscr{L} is a recursive tail partitioned list if it is empty or has the form

$$\mathscr{L} = \mathscr{L}_1 \cdot 01^u, \mathscr{L}_2 \cdot 01^{u+1}, \mathscr{L}_3 \cdot 01^{u+2}, \cdots, \mathscr{L}_{\ell+1} \cdot 01^{u+\ell}$$

$$\tag{2}$$

or the form

$$\mathscr{L} = \mathscr{L}_1 \cdot 01^{u+\ell}, \mathscr{L}_2 \cdot 01^{u+\ell-1}, \mathscr{L}_3 \cdot 01^{u+\ell-2}, \cdots, \mathscr{L}_{\ell+1} \cdot 01^u$$
(3)

for some $u, \ell \ge 0$, and each list \mathcal{L}_i , is in turn recursive tail partitioned.

We remark that the list in (2) is not necessarily the reverse of that in (3). Clearly, a recursive tail partitioned list (r-t partitioned list for short) is a suffix partitioned list.

Theorem 2.2. If the list \mathcal{L} is a homogeneous and suffix partitioned Gray code for a set of (same length and same weight) binary words, then \mathcal{L} is an r-t partitioned list.

3 Main results

3.1 Fibonacci words $F_n(2,k)$

In this subsection we show that for any $\alpha \in F_n(2,k)$, by applying the greedy algorithm for $F_n(2,k)$ to α , a suffix partitioned list is obtained, and we characterize the words α such that the greedy algorithm yields an exhaustive list for $F_n(2,k)$. Moreover, for every $\alpha \in F_n(2,k)$ we characterize the last word in the obtained list.

For n < 2k - 1, $F_n(2,k)$ is empty and in two particular cases $F_n(2,k)$ is a singleton set.

Fact 3.1. If k = 0, then $F_n(2,k) = \{0^n\}$, and if n = 2k - 1, then $F_n(2,k) = \{1(01)^{k-1}\}$.

For $\alpha \in F_n(2,k)$ we denote by $\mathscr{F}(\alpha)$ the list obtained by applying the greedy algorithm for $F_n(2,k)$ to α .

For n, k with $n \ge 2k$, let $\alpha_{n,k}^i = 0^i 1(01)^{k-1} 0^{n-2k+1-i}$, for $0 \le i \le n-2k+1$. Furthermore, let $\gamma_{n,k} := \alpha_{n,k}^{n-2k+1} = 0^{n-2k} (01)^k$. We denote by GenF(n,k) the set of words $\alpha \in F_n(2,k)$ such that $\mathscr{F}(\alpha)$ is a homogeneous Gray code for $F_n(2,k)$. Equivalently, $\alpha \in GenF(n,k)$ if and only if $\mathscr{F}(\alpha)$ contains every word of $F_n(2,k)$.

Theorem 3.2. Let $n \in \mathbb{N}^*$. Then for all k with $n \ge 2k$, we have

- 1. $\alpha_{n,k}^i \in GenF(n,k)$ for all $0 \le i \le n-2k$, and $\mathscr{F}(\alpha_{n,k}^i)$ is a suffix partitioned list, with $\gamma_{n,k}$ as last word.
- γ_{n,k} ∈ GenF(n,k), 𝔅(γ_{n,k}) is a suffix partitioned list and its last word is

 α⁰_{n,k} if k is even,
 α^{n-2k}_{n,k} if k is odd.

In the next lemma, we extend the result of 1. in Theorem 3.2 concerning the last element of $\mathscr{F}(\alpha)$ to each $\alpha \in F_n(2,k)$.

Lemma 3.3. Let $n \ge 2k$. For any $\alpha \in F_n(2,k)$ with $\alpha \neq \gamma_{n,k}$, the last word of $\mathscr{F}(\alpha)$ is $\gamma_{n,k}$.

Now we generalise the property for $\mathscr{F}(\alpha)$ to be suffix partitioned to each word of $F_n(2,n)$.

Lemma 3.4. Let $n \ge 2k - 1$. For any $\alpha \in F_n(2,k)$, $\mathscr{F}(\alpha)$ is a suffix partitioned list.

Now we are able to completely describe the set GenF(n,k).

Proposition 3.5. Let $n \ge 2k - 1$. Then

$$GenF(n,k) = \{0^{i}1(01)^{k-1}0^{n-2k+1-i} \mid 0 \le i \le n-2k+1\}.$$

In particular, |GenF(n,k)| = n - 2k + 2.

3.2 $C_n(p,k)$

For n, p, k such that $n \ge (p+1)k$ and $\alpha \in C_n(p, k)$, we denote by $\mathscr{D}_p(\alpha)$ the list obtained by applying the greedy algorithm for $C_n(p,k)$ to α . Let also $Gen_p(n,k)$ be the set of words $\alpha \in C_n(p,k)$ such that $\mathscr{D}_p(\alpha)$ is a homogeneous Gray code for $C_n(p,k)$. Equivalently, $\alpha \in Gen_p(n,k)$ if and only if $\mathscr{D}_p(\alpha)$ contains every word of $C_n(p,k)$. Since the situation is a bit more complicated than the one for Fibonacci words, for clarity we first investigate the case $p \in \mathbb{N}$, explaining every details of the proofs. Then we explain how the results are generalised to any $p \in \mathbb{R}$, not necessarily describing each proof.

3.2.1 $p \in \mathbb{N}$

We start by investigating the case $p \in \mathbb{N}$. We fix such a p throughout this section. For $n \ge (p+1)k$, let $\alpha_{n,k}^{i,j} := 0^{pj-i}1^{j-1}0^i1(0^p1)^{k-j}0^{n-(p+1)k}$ (resp. $\alpha_{n,k} = 1^k0^{n-k}$) for $i = 0, \ldots, p-1$ and $j = 1, \ldots, k$ if $p \ge 1$ (resp. if p = 0), and $\beta_{n,k}^i := 0^i1^k0^{n-i-k}$ for $i = pk+1, \ldots, n-k$. Because it plays a special role, we will use different notation for $\beta_{n,k}^{n-k}$, so we set $\gamma_{n,k} := \beta_{n,k}^{n-k} = 0^{n-k}1^k$.

Theorem 3.6. *Let* $n \ge (p+1)k$ *, with* $k \ge 1$ *.*

- 1. For all $0 \le i \le p-1$ and $1 \le j \le k$, we have $\alpha_{n,k}^{i,j} \in Gen_p(n,k)$ (resp. $\alpha_{n,k} \in Gen_0(n,k)$), and $\mathscr{D}_p(\alpha_{n,k}^{i,j})$ (resp. $\mathscr{D}_0(\alpha_{n,k})$) is a suffix partitioned list with $\gamma_{n,k}$ as last word.
- 2. For all j, $pk+1 \leq j \leq n-k-1$, we have $\beta_{n,k}^j \in Gen_p(n,k)$, and $\mathscr{D}_p(\beta_{n,k}^j)$ is a suffix partitioned list with $\gamma_{n,k}$ as last word.
- 3. $\gamma_{n,k} \in Gen_p(n,k)$, $\mathscr{D}_p(\gamma_{n,k})$ is a suffix partitioned list and its last word is
 - (i) $0^{p}1$ if (n,k) = (p+1,1), (ii) $\beta_{n,k}^{n-k-1} = 0^{n-k-1}1^{k}0$ if k is odd and $n \neq (p+1)k$, (iii) $\alpha_{n,k}^{1,k-1} = 0^{(k-1)p-1}1^{k-2}010^{p}1$ if $k \ge 3$ is odd and n = (p+1)k (resp. $\alpha_{n,k} = 1^{k}$ if p = 0), (iv) $\alpha_{n,k}^{1,k} = 0^{kp-1}1^{k-1}010^{n-(p+1)k}$ if k is even (resp. $\alpha_{n,k} = 1^{k}0^{n-k}$ if p = 0).

Lemma 3.7. Let $n \ge (p+1)k$. For all $\alpha \in C_n(p,k)$, with $\alpha \neq \gamma_{n,k}$, $\mathscr{D}_p(\alpha)$ ends with $\gamma_{n,k}$.

Lemma 3.8. Let $n \ge 1$. Then for all k with $n \ge (p+1)k$, and for each $\alpha \in C_n(p,k)$, $\mathcal{D}_p(\alpha)$ is a suffix partitioned list.

Proposition 3.9. Let $n \ge (p+1)k$. If $p \ge 1$ then

$$Gen_p(n,k) = \bigcup_{j=1}^{k} \{0^{pj-i} 1^{j-1} 0^i 1 (0^p 1)^{k-j} 0^{n-(p+1)k} \mid 0 \le i \le p-1 \\ \cup \{0^i 1^k 0^{n-i-k} \mid pk+1 \le i \le n-k\}.$$

}

If p = 0 *then* $Gen_0(n,k) = \{0^i 1^k 0^{n-i-k} \mid 0 \le i \le n-k\}$. *In particular,*

$$|Gen_p(n,k)| = n - k + 1 - p.$$

Remark 3.10. Propositions 3.5 and 3.9 highlight the fact that the choice of the first element for the greedy algorithm is crucial. Indeed, only a few elements will produce a Gray code for $F_n(2,k)$ or $C_n(p,k)$ with this algorithm.

3.2.2 $p \in \mathbb{R}_+$

The previous results can be generalized to $C_n(p,k)$ for any $p \in \mathbb{R}_+$. In particular we have the following result:

Theorem 3.11. Let $p \in \mathbb{R}_+$ and $n \ge (p+1)k$. Then

$$|Gen_p(n,k)| = n - k + 1 - \lceil p \rceil.$$

3.3 Algorithmic considerations

Building on the previous results, the last part presents CAT algorithms that greedily generate Gray code for $C_n(p,k)$ and $F_n(2,k)$, which we omit in this abstract.

References

- [1] A. Bultena & F. Ruskey (1998): An Eades-McKay algorithm for well-formed parentheses strings. Information Processing Letters 68, pp. 255–259, doi:10.1016/S0020-0190(98)00171-9.
- [2] P. Eades & B. McKay (1984): An algorithm for generating subsets of fixed size with a strong minimal change property. Information Processing Letters 19, pp. 131–133, doi:10.1016/0020-0190(84)90091-7.
- [3] Torsten Mütze (2023): *Combinatorial Gray codes an updated survey*. Electronic Journal of Combinatorics 30(3):DS26, doi:10.37236/11023.
- [4] N.J.A. Sloane: The On-Line Encyclopedia of Integer Sequences. Available at http://oeis.org/.
- [5] V. Vajnovszki & T. Walsh (2006): A loop-free two-close Gray code algorithm for listing k-ary Dyck words. Journal of Discrete Algorithms 4(4), pp. 633–648, doi:10.1016/j.jda.2005.07.003.
- [6] A. Williams (2013): *The greedy Gray code algorithm*. In: Proceedings of the 13th international conference on Algorithms and Data Structures, p. 525–536, doi:10.1007/978-3-642-40104-6_46.
- [7] D. Wong & V. Vajnovszki (2023): Greedy Gray codes for Dyck words and ballot sequences. In: Computing and Combinatorics. COCOON 2023, Lecture Notes in Computer Science 14423, Springer, pp. 29–40, doi:10. 1007/978-3-031-49193-1_3.