EVALALIGN: Supervised Fine-Tuning Multimodal LLMs with Human-Aligned Data for Evaluating Text-to-Image Models

Zhiyu Tan¹ Xiaomeng Yang¹ Luozheng Qin¹ Mengping Yang¹ Cheng Zhang² Hao Li³

¹ Shanghai Academy of AI for Science ² Carnegie Mellon University ³ Fudan University

https://github.com/SAIS-FUXI/EvalAlign

Abstract

The recent advancements in text-to-image generative models have been remarkable. Yet, the field suffers from a lack of evaluation metrics that accurately reflect the performance of these models, particularly lacking fine-grained metrics that can guide the optimization of the models. In this paper, we propose EVALALIGN, a metric characterized by its accuracy, stability, and fine granularity. Our approach leverages the capabilities of Multimodal Large Language Models (MLLMs) pre-trained on extensive datasets. We develop evaluation protocols that focus on two key dimensions: image faithfulness and text-image alignment. Each protocol comprises a set of detailed, fine-grained instructions linked to specific scoring options, enabling precise manual scoring of the generated images. We Supervised Fine-Tune (SFT) the MLLM to align closely with human evaluative judgments, resulting in a robust evaluation model. Our comprehensive tests across 24 text-to-image generation models demonstrate that EVALALIGN not only provides superior metric stability but also aligns more closely with human preferences than existing metrics, confirming its effectiveness and utility in model assessment.

1 Introduction

Text-to-image models, such as DALL·E series [38, 37, 3], Imagen [43], and Stable Diffusion [33], have significantly impacted various domains such as entertainment, design, and education, by enabling high-quality image generation. These technologies not only advance the field of text-to-image generation but also enhance related applications such as video generation [4, 60], image editing [46, 18, 59], and personalized image generation [13, 42]. Despite this prevalence, in the practical use of generative models, we still lack evaluation methods to accurately evaluate existing text-to-image models.

Existing benchmarks for text-to-image generation models are neither comprehensive nor accurate enough to meet current evaluation needs. The reasons for this include: (1) Limited model parameters: Current evaluation models have too few parameters, which restricts their ability to accurately represent images, leading to significant discrepancies compared to human evaluations. (2) Training data limitations: Some evaluation methods, such as Inception Score (IS) [44], Frechet Inception Distance (FID) [15], and CLIP Score [14], use models that have not been trained with synthesized images, which may introduce training bias and flaws the evaluation. (3) High annotation costs: Some methods, such as ImageReward [56], HPS [55] and HPS v2 [54], rely heavily on extensive human annotations, which significantly increases the cost of labeling. (4) Lack of detailed evaluation metric: The evaluation metrics do not provide fine-grained interpretability, preventing them from guiding model

optimization effectively. (5) Computational inefficiency: The evaluation models require substantial computational resources, making them inefficient.

To address these issues, we propose EVALALIGN, which offers low-cost, accurate, and efficient model evaluations while providing fine-grained, interpretable metrics. Specifically, we Supervised Fine-Tune (SFT) a Multimodal Large Language Model (MLLM) to align it with human annotations. Our focus is on two key evaluation aspects: image faithfulness and text-image alignment.

Due to its pre-training on large-scale datasets and a large number of model parameters, the MLLM demonstrates excellent understanding and generalization capabilities for images and instructions. This makes it possible to design evaluation instruction based on MLLM to evaluate text-to-image models. However, since the pre-trained datasets do not include model-generated images (such as distorted body structures and human hands) or evaluation-related text instructions, using MLLM directly for model evaluation does not yield optimal results. Therefore, we employ SFT on a small amount of manually annotated data to align MLLM with human annotations for text-to-image generation. In summary, our main contributions can be summarized as follows:

- We introduce a dataset specifically designed to address the evaluation challenges of text-to-image models. This dataset, derived from multiple data sources, has been thoroughly cleaned and systematically annotated by human. It enables precise evaluation of text-image alignment and image faithfulness.
- We propose the EVALALIGN evaluation metric, which accurately aligns evaluation metrics with human preferences. This method is cost-effective in terms of annotation and training, computationally efficient, and provides interpretable metrics.
- We conduct evaluations over 24 text-to-image models and compare EVALALIGN with existing evaluation methods. Extensive experiments demonstrate that EVALALIGN outperforms other methods in evaluating model performance.

2 Related Work

Evaluations and benchmarks of text-to-image generation. Despite the incredible progress achieved by text-to-image generation, evaluations and benchmarks in this area are far from flawless and contain critical limitations. For example, the most commonly used metrics, IS [44], FID [15], and CLIPScore [14] are broadly recognized as inaccurate for their inconsistency with human perception. To address, HPS series [55, 54], PickScore [20], and ImageReward [56] introduced human preference prior on image assessing to the benchmark, thereby allowing better correlation with image quality. However, with varying source and size of training data, these methods merely score the evaluated images in a coarse and general way, which cannot serve as an indication for model evolution. Meanwhile, HEIM [21] combined automatic and human evaluation and holistically evaluated text-toimage generation in 12 aspects, such as alignment, toxicity, and so on. As a consequence, HEIM relies heavily on human labour, limiting its application within budget-limited research groups severely. [30] standardized the protocol and settings of human evaluation, ensuring its verifiable and reproducible. There are also some works bear a resemble with us. For instance, TIFA [16], Gecko [53] and LLMScore [27] also formulate the evaluation as a set of visual question answering procedure and use LLMs as evaluation models. However, while they all mainly focus on text-image alignment, our approach takes both text-image alignment and image faithfulness into consideration. Moreover, the evaluation of LLMScore requires an object detection stage, which introduces significantly extra inference latency to the evaluation pipeline.

As illustrated in Table 1, existing text-to-image evaluation methods contains various limitations, making them incapable to serve as a fine-grained, comprehensive, and human-preference aligned automatic benchmark. While our work fills in this gap economically, and can be employed to indicate evolution direction and support thorough analysis of text-to-image generation models.

Multimodal Large Language Models (MLLMs). Pretrained on massive text-only and image-text data, MLLMs have exhibited exceptional image-text joint understanding and generalization abilities, facilitating a large spectrum of downstream applications. Among the works major in MLLMs, LLaVA [26, 24] and MiniGPT4 [61, 5] proposed to conduct visual instruction tuning during SFT, so that MLLMs can be easily aligned to human preference and precisely answer fine-grained questions on visual content. Meanwhile, Video-LLaMA [58] and VideoChat [22] utilized MLLMs for video

Table 1: **Comparison of different evaluation metrics and frameworks for text-to-image generation.** EVALALIGN focuses on two key evaluation aspects, i.e., image faithfulness and text-image alignment, and supports human-aligned, fine-grained, and automatic evaluations. P: Prompt. I: Image. A: Annotation.

Mathad	Vanua	Benc	hmark Feature		Da	ataset Si	ze	Evaluation	n Aspect
Method	venue	Human-aligned	Fine-grained	Automatic	Р	Ι	А	Faithfulness	Alignment
Inception Score [44]	NeurIPS 2016	×	×	✓	_	1.3M	-	1	X
FID [15]	NeurIPS 2017	×	×	1	-	1.3M	-	1	×
CLIP-score [14]	EMNLP 2021	×	×	1	400M	400M	-	×	1
HPS [55]	ICCV 2023	1	×	1	25K	98K	25K	-	-
TIFA [16]	ICCV 2023	1	1	1	4K	-	25K	×	1
TVRHE [30]	CVPR 2023	1	×	×	-	-	-	1	×
ImageReward [56]	NeurIPS 2023	1	×	1	8.8K	68K	137K	-	-
PickScore [20]	NeurIPS 2023	1	×	1	35K	1M	500K	-	-
HPS v2 [54]	arXiv 2023	1	×	1	107K	430K	645K	-	-
HEIM [21]	NeurIPS 2023	1	1	×	-	-	-	1	1
Gecko [53]	arXiv 2024	1	1	1	2K	-	108K	×	1
LLMScore [27]	arXiv 2024	✓	\checkmark	\checkmark	-	-	-	×	\checkmark
EVALALIGN (ours)	-	 ✓ 	\checkmark	~	3K	21K	132K	✓	\checkmark

understanding. VILA [23] quantitatively proved that involving text-only instruction-tuning data during SFT can further ameliorate model performance on text-only and multimodal downstream tasks. LLaVA-NeXT [25] extracted visual tokens for both the resized input image and the segmented sub-images to provide more detailed visual information for MLLMs, achieving significant performance bonus on tasks with high-resolution input images.

In this paper, we manually annotate a minimal amount of high-quality visual instruction-tuning data to adapt MLLMs to perform human preference aligned and fine-grained evaluation. Owing to the generalization and multimodal understanding abilities of MLLMs, our experiments demonstrated that the finetuned MLLMs can accurately assess text-to-image generation models by following instructions regarding various fine-grained criteria of synthesised image.

3 EVALALIGN Dataset Construction

To train, validate and test the effectiveness of our evaluation models, we build EVALALIGN benchmark. Specifically, EVALALIGN dataset is a meticulously annotated collection featuring fine-grained annotations for images generated from text prompts. This dataset comprises 21k images, each accompanied by detailed instructions. The compilation process for the EVALALIGN Dataset encompasses prompt collection, image generation, and precise instruction-based annotation.

3.1 Prompts and Images Collection

Prompt collection. To assess the capabilities of our model in terms of text-image alignment and image faithfulness, we collect, filter, and clean prompts from existing evaluation datasets and generated prompts based on LLM. These prompts encompass a diverse range from real-world user prompts, prompts generated through rule-based templates with LLM, to manually crafted prompts. Specifically, the utilized prompts are sourceed from HPS [55], HRS-Bench [2], HPSv2 [54], TIFA [16], DSG [7], T2I-Comp [17], Winoground [50], DALL-EVAL [8], DiffusionDB [52], PartiPrompts [57], DrawBench [43], and JourneryDB [49].

Prompt curation. The prompts are collected for facilitating fine-grained and comprehensive evaluation on text-to-image models in terms of image faithfulness and text-image alignment. Considering some of the collected prompt are unsuitable for these two evaluation tasks, we filter the collected prompts to ensure their quantity, quality and diversity. For the image faithfulness evaluation task, we prioritize prompts related to human, animals, and other tangible objects, as prompts depicting sci-fi scenarios are less suitable for this type of assessment. Our filtering process initially selects prompts that describe human, animals, and other real objects. After deduplicating these prompts, we carefully selected 1,500 distinct prompts with varying topic, background and style for further evaluation. The selected prompts encompass 10k subjects across 15 categories. For the text-image alignment task, we refined our selection based on descriptions of style, color, quantity, and spatial relationships in the



Figure 1: **Overview of EVALALIGN.** We collect, filter and clean prompts from various sources to ensure their quantity, quality and diversity. We use 8 state-of-the-art text-to-image models to the generate images for evaluation. These synthesized images are then delegated to human annotators for thorough multi-turn annotation. Finally, the annotated data are used to SFT train a MLLM to align it with fine-grained human preference, thereby adapting the model to perform fine-grained human-aligned text-to-image evaluations.

prompts. Only those prompts containing relevant descriptions and exceeding 15 words in length were considered, culminating in a final set of 1,500 prompts for evaluation.

Image generation. To train and evaluate the MLLM, we use a diverse set of images generated by various models using the aforementioned prompts, allowing for detailed human annotation. For each prompt, multiple images are generated across different models. The dataset is enriched by images synthesized by models with varying architectures and scales, enhancing the diversity essential for a comprehensive evaluation.

This variety not only tests the MLLM generalization capabilities but also aids in developing a model with broader applicability. The training dataset incorporates images from 8 models, whereas the test dataset spans 24 models. The inclusion of 16 unseen models in the test set is crucial for evaluating the MLLM to generalize beyond its training data. For detailed information on the inference setting of each model, please refer to the supplementary material. This structured approach ensures a robust framework for training and validating the MLLM, positioning it as a versatile and adaptive tool in the field of image generation from textual descriptions.

3.2 Data Annotation

Prompt annotation. For text prompts focused on text-image alignment, we begin by annotating the entities and their attributes within the text, as illustrated in Figure 1. Our annotators extract the entities mentioned in the prompts and label each entity with corresponding attributes, including quantity, color, spatial relationships, and actions. During the annotation, we also ask the annotators annotate the overall style of the image if described in the corresponding prompt and report prompts that contain toxic and NSFW content. These high-quality and detailed annotations facilitate the subsequent SFT training and evaluation of the MLLM. This meticulous annotation procedure ensures that the MLLM can accurately align and respond to the nuanced details specified in the prompts, enhancing both the training process and the model's performance in generating images that faithfully reflect the described attributes and style.

Image annotation. The images generated by text-to-image models often present challenges such as occluded human body parts, which can impede the effectiveness of SFT training and evaluation of

the MLLM. Therefore, to address these challenges and enhance the model's training and evaluative capabilities, specific annotations are applied to all images depicting human and animals. These annotations include: presence of human or animal faces; visibility of hands; visibility of limbs. By implementing these annotations, we ensure that the MLLM can more effectively learn from and assess the completeness and faithfulness of the generated images. This structured approach to annotation not only aids in identifying common generation errors but also optimizes the model's ability to generate more accurate and realistic images, thereby improving both training outcomes and the model's overall performance in generating coherent and contextually appropriate visual content.

Instruction-Fine-tuning data annotation. To align the MLLM with human preference prior on fine-grained image assessing, we can train the model on a minimal amount of fine-grained human preference data through SFT training. As a consequence, we devise two sets of questions, each is concentrated on a specific fine-grained aspect of image faithfulness and image-text alignment, and ask human annotators to answer these questions to acquire the fine-grained human preference data. To aid the human annotators to understand the meaning of each question and its available answer options, thereby ensuring high annotation quality, we employ a thorough and comprehensive procedure of annotation preparation. First, we write a detailed annotation guideline and conduct a training for the annotators to explain the annotation guideline and answer their questions about the annotation (see supplementary materials for the annotation guideline). Then, we conduct a multi-turn trial annotation on another 50 synthesized images. After each trial, we calculate the Cohen's kappa coefficient and interpret annotation guidelines for our annotators. In total, we conduct nine turns of trial annotation, and in the last turn of the trial, the Cohen's kappa coefficient of our annotators reaches 0.681, indicating high inter-annotator reliability and high annotation quality. More results about the trial annotation will be included in the supplementary materials.

After completing the aforementioned preparations, we delegate the images filtered during image annotation to 10 annotators and ask them to complete the annotation just as how they did in the trial annotation. Furthermore, during the whole annotation procedure, four text-to-image generation experts conduct random sampling quality inspection on the present annotated results, causing a second and a third re-annotation on 423 and 112 inspection-failed samples. Overall, owing to the valuable work of our human annotators and our fastidious annotation procedure, we get quality-sufficient instruction-tuning data required for the SFT training of the MLLM. More details of the annotation procedure will be introduced in the supplementary files.

3.3 Dataset Statistics

To summarize, we generate 24k images from 3k prompts based on 8 text-to-image models, which includes DeepFloyd IF [1], SD15 [40], LCM [28], SD21 [40], SDXL [33], Wuerstchen [32], Pixart [6], and SDXL-Turbo [48]. After data filtering, 4.5k images were selected as annotation data for task of text-image alignment. Subsequently, these images were carefully annotated to generate 13.5k text-image pairs, where 11.4k were used to the training dataset and 2.1k to the validation dataset. For the image faithfulness task, we select 12k images for annotate, producing 36k text-image pairs, with 30k are used to the training dataset and 6.2k to the validation dataset. Additionally, we employed 24 text-to-image models to generate 2.4k images from 100 prompts. After annotation, these images were used as testing dataset. Figure 2 and Figure 3 show the distribution of objects in different categories within our prompts, demonstrating the diversity and balance of our prompts.

4 Training and Evaluation Methods

4.1 Supervised Fine-Tuning the MLLM

As we mentioned above, we use MLLMs as the evaluation models and let it to answer a set of carefully-designed instructions, thereby achieving quantitative measurement of fine-grained text-to-image generation skills. Due to training bias, zero-shot MLLMs perform poorly when it comes to fine-grained evaluation on synthesized images, particularly in term of image faithfulness. To address, we conduct SFT training on the annotated data to align the MLLM with human preference prior on fine-grained image assessing. Formally, the SFT training sample can be denoted as a triplet, i.e., (Q, M, A), where Q, M, A denotes the question (or the instruction), the multimodal input and the answer, respectively. Specifically, Q is a question about a fine-grained aspect of the



Figure 2: Statistics of prompts on evaluating textto-image alignment. Prompts in our text-to-image alignment benchmark covers a broad range of concepts commonly used in text-to-image generation.



Figure 3: Statistics of prompts on evaluating image faithfulness. Prompts in our image faithfulness benchmark covers a broad range of objects and categories that related to image faithfulnes.

generated image as well as the available answer options, M is mainly the image and necessary textual description, while A is the specific answer chosen from the given options and annotated by human. Notably, we expand each given option to a more detailed and descriptive version, benefiting the SFT performance by allowing the MLLM to understand the meaning of each option. During SFT training, the optimization objective is the original autoregressive loss function utilized to train LLMs, but calculated only on A. Specifically, the loss function can be formulated as follows, where N is the length of the ground truth answer:

$$L(\theta) = \sum_{i=1}^{N} \log p(A_i | Q, M, A_{\langle i \rangle}; \theta).$$
(1)

4.2 Evaluation and Metrics

During inference, the MLLM, parameterized by θ , is required to generate the appropriate response R, given the specific question Q and the multimodal input M in an autoregressive way:

$$R_i = f(Q, M, R_{
⁽²⁾$$

This autoregressive generation procedure is considered complete once the model generates a EOS token or the generated response exceeds the preset maximum generation length. After the generation, we use rule-based filtering and regular expression to extract the option chosen by the MLLM, where each option has an exclusive predefined score to quantitatively measure a fine-grained skill specified by the question Q:

$$Score(Q) = g(R) = g(f(Q, M; \theta)),$$
(3)

where $g(\cdot)$ represents the procedure of option extraction and score searching. We devise two holistic and detailed question sets, S_f and S_a , that encompass every aspect of image faithfulness and text-image alignment, respectively. Consequently, Our metric EvalAlign can be defined by simply summing the scores of the two question sets:

$$\operatorname{EvalAlign}_{\mathrm{f}} = \sum_{Q_i \in S_f} \operatorname{Score}(Q_i) \quad \operatorname{EvalAlign}_{\mathrm{a}} = \sum_{Q_j \in S_a} \operatorname{Score}(Q_j), \tag{4}$$

where EvalAlign_f and EvalAlign_a indicates the image faithfulness score and image-text alignment score evaluated by EVALALIGN.

4.3 Implementation Details

We leverage the LLaVA-NeXT model and applied the LoRA fine-tuning method to align it with the training dataset as described previously. The entire training process was conducted on 32 NVIDIA A100 GPUs with 10 hours, using a learning rate of 5×10^{-5} . Additionally, we restricted the LoRA fine-tuning to the Q and K weights of the attention module, as extending the fine-tuning to the ViT and projection modules was found to cause overfitting. Importantly, our method does not necessitate any modifications to the MLLM, rendering it compatible with any MLLM model. For the ablation

Table 2: Results on image faithfulness.

Table 3: Results on text-to-image alignment.

Model	Human	EVALALIGN	Model	Human	EVALALIGN
PixArt XL2 1024 MS [6]	2.2848 1	1.6415 ¹	IF-I-XL v1.0 [1]	5.4500 ¹	5.5300 ¹
Dreamlike Photoreal v2.0 [11]	2.0070^{-2}	1.4522 4	IF-I-L v1.0 [1]	5.2300 ²	5.4500 ²
SDXL Refiner v1.0 [47]	1.9229 ³	1.6072 ²	SDXL Refiner v1.0 [47]	5.2100 ³	5.4000 ³
SDXL v1.0 [33]	1.8136 4	1.4675 ³	LCM SDXL [28]	5.1800 4	5.3300 ⁵
Wuerstchen [32]	1.7837 ⁵	1.4279 ⁵	PixArt XL2 1024 MS [6]	5.1100 ⁵	5.3100 ⁶
LCM SDXL [28]	1.6910 ⁶	1.3391 7	IF-I-M v1.0 [1]	5.0800 ⁶	5.2200 ⁸
Openjourney [34]	1.6667 7	1.1750 10	LCM LORA SDXL [28]	5.0600 7	5.2700 ⁷
Safe SD MAX [31]	1.6491 ⁸	1.2175 ⁸	SDXL v1.0 [33]	5.0300 ⁸	5.3500 ⁴
LCM LORA SDXL [28]	1.6387 ⁹	1.3833 ⁶	Wuerstchen [32]	4.8700 ⁹	5.1700 ⁹
Safe SD STRONG [31]	1.6308 10	1.1466 11	Openjourney [34]	4.8300 10	4.9200 15
Safe SD MEDIUM [31]	1.6275 11	1.1298 15	SD v2.1 [40]	4.8000 11	5.0700 11
Safe SD WEAK [31]	1.6078 12	1.1188 17	MultiFusion [29]	4.6800 12	4.8000 18
SD v2.1 [40]	1.5524 13	1.1094 18	Dreamlike Diffusion v1.0 [10]	4.6600 13	5.1500 10
SD v2.0 [40]	1.5277 14	1.1300 14	SD v2.0 [40]	4.6400 14	5.0100 ¹²
Openjourney v2 [35]	1.5000 15	0.9956 20	Vintedois Diffusion v0.1 [51]	4.6200 15	4.9500 14
Redshift diffusion [39]	1.4733 16	1.1382 12	Safe SD STRONG [31]	4.6000 16	4.8300 17
Dreamlike Diffusion v1.0 [10]	1.4652 17	1.2052 ⁹	Dreamlike Photoreal v2.0 [11]	4.5600 17	4.9800 13
SD v1.5 [40]	1.4417 ¹⁸	1.1362 13	Safe SD WEAK [31]	4.5300 18	4.7100 ²⁰
IF-I-XL v1.0 [1]	1.3808 19	0.9221 22	SD v1.4 [40]	4.5200 19	4.7600 19
SD v1.4 [40]	1.3592 ²⁰	0.9511 21	SD v1.5 [40]	4.4500 ²⁰	4.9000 16
Vintedois Diffusion v0.1 [51]	1.3562 21	1.0797 ¹⁹	Safe SD MEDIUM [31]	4.4000 21	4.5600 ²⁴
IF-I-L v1.0 [1]	1.2635 22	0.8814 23	Redshift diffusion [39]	4.3500 ²²	4.6700 ²¹
MultiFusion [29]	1.2372 ²³	1.1298 16	Safe SD MAX [31]	4.3100 ²³	4.5900 ²³
IF-I-M v1.0 [1]	1.0135 ²⁴	0.7928 24	Openjourney v2 [35]	4.1500 24	4.6500 22

study, we evaluated the LLaVA-NeXT 13B model on the validation dataset. In the final experiment, we apply supervised fine-tuning to the LLaVA-NeXT 34B model on the testing dataset and compare against different evaluation metrics.

5 Experimental Results

In this section, we show results of EVALALIGN on benchmarking 24 text-to-image generative models. We also compare with popular text-to-image metrics and frameworks, including Inception Score (IS) [44], Frechet Inception Distance (FID) [15], CLIP-score [14], and HPS v2 [54]. Please refer to supplementary materials for detailed results and analyses.

5.1 Main Results

Evaluation on image faithfullness. We conducted the image faithfullness evaluation on the testing dataset, as detailed in Table 2. Our evaluation metric, EVALALIGN, demonstrates close alignment with human preferences Specifically, the rankings of the top and bottom 10 models by both EVALALIGN and human evaluation scores show remarkable consistency, confirming that our metric closely mirrors human evaluation. Importantly, most of the images from the 24 generative models were not present during training, showcasing the robust generalization capability of our evaluation method.

Evaluation on text-image alignment. The evaluation of text-image alignment on the testing dataset was conducted follow the same manner of image faithfullness evaluation. Table 3 reveals that the rankings based on the EVALALIGN metric and human evaluation metric for the 24 models are generally consistent. This consistency likely stems from the proximity of MLLM's pre-training tasks to the text-image alignment evaluation tasks, resulting in better performance on text-image alignment evaluation task.

Table 4: Results of different prompt categories for eval- Table 5: Results of different prompt categories for evaluat-

uating image faithfulness. Baseline is the vanilla LLaVA- ing text-to-image alignment. Baseline is the vanilla LLaVA-NeXT model without find-tuning with human-aligned data. NeXT model without find-tuning with human-aligned data.

Method	Body	Hand	Face	Object	Common	Method	Object	Count	Color	Style	Spatial	Action
Human Baseline EVALALIGN	1.6701 3.9950 1.7305	1.0278 3.9932 0.9490	1.4107 3.9867 1.4393	2.2968 2.6734 2.3565	1.0637 3.3476 1.0903	Human Baseline EVALALIGN	1.6947 1.5602 1.6807	1.2032 1.0742 1.2516	1.8551 1.9275 1.8696	1.9796 1.1837 1.9592	1.5608 1.4118 1.5882	1.8015 1.1838 1.8382
	1						1					

Table 6: Ablation study on the size of training data. Results are reported on image faithfulness under different training data scale. We observe that a small number of annotated training data is sufficient for optimal results.

Method	Data Size	SDXL	Pixart	Wuerstchen	SDXL-Turbo	IF	SD v1.5	SD v2.1	LCM
Human	-	2.1044	1.8606	1.7839	1.3854	1.3822	1.3818	1.1766	1.0066
EvalAlign	200 500 800	1.7443 1.8890 2.0443	1.8898 1.9161 1.9199	1.9278 1.8586 1.8012	1.1261 1.2141 1.3353	1.2977 1.3109 1.296	1.5254 1.3926 1.4702	1.4309 1.3815 1.3221	1.1204 0.9485 1.0305

5.2 Ablations and Analyses of EVALALIGN

Results on different prompt categories. SFT significantly enhances the performance of MLLMs on evaluation tasks. We conducted experiments comparing the LLava-Next 13B model with and without SFT. As shown in Table 4 and Table 5, the results demonstrate that SFT considerably improves performance across all prompt categories in both image faithfulness and text-to-image alignment, closely aligning the MLLM's predictions with human evaluations. Note that Table 4 shows that the baseline method without SFT performs poorly on the image faithfulness task, which suggests the necessity of SFT.

Effect of dataset size for vision-language model training. In order to explore the effects of data size, we train model on image faithfulness evaluation task under three different data size: 200, 500 and 800. As illustrated in Table 6, performance generally enhances with more training data. Notably, training with just 500 data nearly maximizes accuracy, with further increases to 800 data yielding only slight improvements. This result suggests that our method requires only a small amount of annotated data to achieve good performance, highlighting the cost-effectiveness of our approach.

Effect of model size. Transformers have demonstrated a strong capacity to scale effectively across a variety of tasks, as noted in key studies [9, 36]. In Table 7, we illustrate the advantages of scaling up the MLLM for image faithfulness evaluation. Specifically, increasing the MLLM model size from 7B to 34B results in notable improvements in performance.

Comparison with Existing Evaluation Methods 5.3

SFT with human-aligned data outperforms vanilla MLLMs. To validate the effectiveness of the MLLM after SFT, we use vanilla LLaVA-NeXT 13B as the baseline model for comparison. As shown in Table 4 and Table 5, the results of vanilla model suggest some correlations with human-annotated data. However, the alignment of the vanilla MLLM is relatively low due to the absence of images generated by model (such as distorted bodies and hands images) and issues related to evaluation in the MLLM's pre-training dataset. After applying SFT on the LLaVA-Next 13B model using human annotated data, the model's predictions on various fine-grained evaluation metrics are almost align to the human-annotated data and significantly surpass the evaluation results of all MLLM models that were not fine-tuned. This experimental results confirms that our SFT training enables the MLLM to be successfully applied to the task of evaluating text-to-image models.

Comparison with state-of-the-art methods. To verify the human preference alignment of our model, especially when compared with other baseline methods, we calculate Kendall rank [19] and Pearson [12] correlation coefficient and summarize the results in Table 8. This comparison experiment encompasses images generated by 24 text-to-image models, covering an extensive range of synthesized image distribution.

Table 7: Ablation study on the size vision-language model. Results are reported on image faithfulness under different model scales of LLaVA-NeXT. We observe that model size is critical for reliable evaluation.

Method	Model Size	SDXL	Pixart	Wuerstchen	SDXL-Turbo	IF	SD v1.5	SD v2.1	LCM
Human		2.1044	1.8606	1.7839	1.3854	1.3822	1.3818	1.1766	1.0066
EvalAlign	7B 13B 34B	1.9959 2.0443 2.1131	1.8615 1.9199 1.8621	1.8228 1.8012 1.8083	1.1708 1.3353 1.3906	1.2704 1.2960 1.3076	1.4031 1.4702 1.3921	1.3063 1.3221 1.2037	1.0145 1.0305 1.0143

As can be concluded, compared with baseline methods, EVALALIGN achieves significant higher alignment with fine-grained human preference on image faithfulness and image-text consistency, showcasing robust generalization ability. Although HPS v2 roughly aligns with human preference in some extent, the relative small model capacity and coarse ranking training limits its generalization to the fine-grained

Table 8: Comparison with existing methods.

Method	Faithf	ulness	Alignment			
Method	Kendall↑	Pearson↑	Kendall↑	Pearson↑		
CLIP-score HPSv2	0.1304 0.4203	0.1765 0.5626	0.6956 0.5217	0.8800 0.7113		
EVALALIGN	0.7464	0.8730	0.8043	0.9356		

annotated data. Besides, since CLIP-s only cares the CLIP similarity of the generated image and its corresponding prompt, it behaves poorly in image faithfulness evaluation. The per-question alignment and the leaderboard of EVALALIGN will be introduced in the supplementary materials.

6 Conclusion and Discussion

In this work, we design an economic and efficient evaluation method that offers high accuracy, strong generalization capabilities, and provides fine-grained, interpretable metrics. We develop a comprehensive data annotation and cleaning process tailored for evaluation tasks, and established the EVALALIGN benchmark for training and evaluating models on supervised fine-tuning tasks for MLLMs. Experimental results across 24 text-to-image models demonstrate that our evaluation metrics surpass the accuracy of all the state-of-art evaluation method. Additionally, we conduct a detailed empirical study on how MLLMs can be applied to model evaluation tasks. There are still many opportunities for further advancements and expansions based on our EVALALIGN. We hope that our work can inspire and facilitate future research in this field.

References

- Misha Konstantinov Alex Shonenkov and et al. Deepfloyd if. https://github.com/deep-floyd/IF, 2023.
- [2] Eslam Mohamed Bakr, Pengzhan Sun, Xiaogian Shen, Faizan Farooq Khan, Li Erran Li, and Mohamed Elhoseiny. Hrs-bench: Holistic, reliable and scalable benchmark for text-to-image models. In *Proceedings* of the IEEE/CVF international conference on computer vision, pages 20041–20053, 2023.
- [3] James Betker, Gabriel Goh, Li Jing, Tim Brooks, Jianfeng Wang, Linjie Li, Long Ouyang, Juntang Zhuang, Joyce Lee, Yufei Guo, et al. Improving image generation with better captions. *https://openai.com/dall-e-3*, 2023.
- [4] Andreas Blattmann, Tim Dockhorn, Sumith Kulal, Daniel Mendelevitch, Maciej Kilian, Dominik Lorenz, Yam Levi, Zion English, Vikram Voleti, Adam Letts, et al. Stable video diffusion: Scaling latent video diffusion models to large datasets. arXiv preprint arXiv:2311.15127, 2023.
- [5] Jun Chen, Deyao Zhu, Xiaoqian Shen, Xiang Li, Zechun Liu, Pengchuan Zhang, Raghuraman Krishnamoorthi, Vikas Chandra, Yunyang Xiong, and Mohamed Elhoseiny. Minigpt-v2: Large language model as a unified interface for vision-language multi-task learning. arXiv preprint arXiv:2310.09478, 2023.
- [6] Junsong Chen, Jincheng Yu, Chongjian Ge, Lewei Yao, Enze Xie, Yue Wu, Zhongdao Wang, James Kwok, Ping Luo, Huchuan Lu, et al. Pixart-alpha: Fast training of diffusion transformer for photorealistic text-to-image synthesis. arXiv preprint arXiv:2310.00426, 2023.
- [7] Jaemin Cho, Yushi Hu, Jason Michael Baldridge, Roopal Garg, Peter Anderson, Ranjay Krishna, Mohit Bansal, Jordi Pont-Tuset, and Su Wang. Davidsonian scene graph: Improving reliability in fine-grained evaluation for text-image generation. In *International conference on learning representations*, 2023.

- [8] Jaemin Cho, Abhay Zala, and Mohit Bansal. Dall-eval: Probing the reasoning skills and social biases of text-to-image generation models. In *Proceedings of the IEEE/CVF international conference on computer* vision, pages 3043–3054, 2023.
- [9] Mostafa Dehghani, Josip Djolonga, Basil Mustafa, Piotr Padlewski, Jonathan Heek, Justin Gilmer, Andreas Peter Steiner, Mathilde Caron, Robert Geirhos, Ibrahim Alabdulmohsin, et al. Scaling vision transformers to 22 billion parameters. In *International conference on machine learning*, pages 7480–7512. PMLR, 2023.
- [10] Dreamlike-diffusion v1.0. https://huggingface.co/dreamlike-art/dreamlike-diffusion-1. 0, 2022.
- [11] Dreamlike-photoreal. https://huggingface.co/dreamlike-art/dreamlike-photoreal-2.0, 2023.
- [12] David Freedman, Robert Pisani, and Roger Purves. Statistics (international student edition). *Pisani, R. Purves, 4th edn. WW Norton & Company, New York*, 2007.
- [13] Rinon Gal, Yuval Alaluf, Yuval Atzmon, Or Patashnik, Amit Haim Bermano, Gal Chechik, and Daniel Cohen-or. An image is worth one word: Personalizing text-to-image generation using textual inversion. In International conference on learning representations, 2022.
- [14] Jack Hessel, Ari Holtzman, Maxwell Forbes, Ronan Le Bras, and Yejin Choi. CLIPScore: A reference-free evaluation metric for image captioning. In *Proceedings of the conference on empirical methods in natural language processing*, pages 7514–7528, November 2021.
- [15] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *Advances in neural information processing systems*, 30, 2017.
- [16] Yushi Hu, Benlin Liu, Jungo Kasai, Yizhong Wang, Mari Ostendorf, Ranjay Krishna, and Noah A Smith. Tifa: Accurate and interpretable text-to-image faithfulness evaluation with question answering. In Proceedings of the IEEE/CVF international conference on computer vision, pages 20406–20417, 2023.
- [17] Kaiyi Huang, Kaiyue Sun, Enze Xie, Zhenguo Li, and Xihui Liu. T2i-compbench: A comprehensive benchmark for open-world compositional text-to-image generation. *Advances in neural information* processing systems, 36:78723–78747, 2023.
- [18] Lianghua Huang, Di Chen, Yu Liu, Yujun Shen, Deli Zhao, and Jingren Zhou. Composer: Creative and controllable image synthesis with composable conditions. *arXiv preprint arXiv:2302.09778*, 2023.
- [19] M. G. KENDALL. A new measure of rank correlation. Biometrika, 30(1-2):81-93, 1938.
- [20] Yuval Kirstain, Adam Polyak, Uriel Singer, Shahbuland Matiana, Joe Penna, and Omer Levy. Pick-apic: An open dataset of user preferences for text-to-image generation. Advances in neural information processing systems, 36, 2024.
- [21] Tony Lee, Michihiro Yasunaga, Chenlin Meng, Yifan Mai, Joon Sung Park, Agrim Gupta, Yunzhi Zhang, Deepak Narayanan, Hannah Teufel, Marco Bellagente, et al. Holistic evaluation of text-to-image models. Advances in neural information processing systems, 36, 2024.
- [22] KunChang Li, Yinan He, Yi Wang, Yizhuo Li, Wenhai Wang, Ping Luo, Yali Wang, Limin Wang, and Yu Qiao. Videochat: Chat-centric video understanding. *arXiv preprint arXiv:2305.06355*, 2023.
- [23] Ji Lin, Hongxu Yin, Wei Ping, Yao Lu, Pavlo Molchanov, Andrew Tao, Huizi Mao, Jan Kautz, Mohammad Shoeybi, and Song Han. Vila: On pre-training for visual language models. arXiv preprint arXiv:2312.07533, 2023.
- [24] Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. *arXiv preprint arXiv:2310.03744*, 2023.
- [25] Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. Llava-next: improved reasoning, ocr, and world knowledge, January 2024.
- [26] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. Advances in neural information processing systems, 36, 2024.
- [27] Yujie Lu, Xianjun Yang, Xiujun Li, Xin Eric Wang, and William Yang Wang. Llmscore: Unveiling the power of large language models in text-to-image synthesis evaluation. Advances in neural information processing systems, 36, 2024.
- [28] Simian Luo, Yiqin Tan, Longbo Huang, Jian Li, and Hang Zhao. Latent consistency models: Synthesizing high-resolution images with few-step inference. *arXiv preprint arXiv:2310.04378*, 2023.
- [29] Bellagente Marco, Brack Manuel, Teufel Hannah, Friedrich Felix, and et al. Multifusion: fusing pre-trained models for multi-lingual, multi-modal image generation. *arXiv preprint arXiv:2305.15296*, 2023.

- [30] Mayu Otani, Riku Togashi, Yu Sawai, Ryosuke Ishigami, Yuta Nakashima, Esa Rahtu, Janne Heikkilä, and Shin'ichi Satoh. Toward verifiable and reproducible human evaluation for text-to-image generation. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition, pages 14277–14286, 2023.
- [31] Schramowski Patrick, Brack Manuel, and et al. Safe latent diffusion: Mitigating inappropriate degeneration in diffusion models. *arXiv preprint arXiv:2211.05105*, 2022.
- [32] Pablo Pernias, Dominic Rampas, and Marc Aubreville. Wuerstchen: Efficient pretraining of text-to-image models. arXiv preprint arXiv:2306.00637, 2023.
- [33] Dustin Podell, Zion English, Kyle Lacey, Andreas Blattmann, Tim Dockhorn, Jonas Müller, Joe Penna, and Robin Rombach. Sdxl: Improving latent diffusion models for high-resolution image synthesis. arXiv preprint arXiv:2307.01952, 2023.
- [34] Openjourney. https://huggingface.co/prompthero/openjourney, 2022.
- [35] Openjourneyv2. https://huggingface.co/ilkerc/openjourney-v2, 2023.
- [36] Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. Improving language understanding by generative pre-training. *OpenAI*, 2018.
- [37] Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.
- [38] Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. In *International conference on machine learning*, pages 8821–8831. PMLR, 2021.
- [39] redshift-diffusion. https://huggingface.co/nitrosocke/redshift-diffusion, 2022.
- [40] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer* vision and pattern recognition, pages 10684–10695, 2022.
- [41] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer* vision and pattern recognition, pages 10684–10695, 2022.
- [42] Nataniel Ruiz, Yuanzhen Li, Varun Jampani, Yael Pritch, Michael Rubinstein, and Kfir Aberman. Dreambooth: Fine tuning text-to-image diffusion models for subject-driven generation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 22500–22510, 2023.
- [43] Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily L Denton, Kamyar Ghasemipour, Raphael Gontijo Lopes, Burcu Karagol Ayan, Tim Salimans, et al. Photorealistic text-toimage diffusion models with deep language understanding. Advances in neural information processing systems, 35:36479–36494, 2022.
- [44] Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. *Advances in neural information processing systems*, 29, 2016.
- [45] Christoph Schuhmann, Romain Beaumont, Richard Vencu, Cade Gordon, Ross Wightman, Mehdi Cherti, Theo Coombes, Aarush Katta, Clayton Mullis, Mitchell Wortsman, et al. Laion-5b: An open large-scale dataset for training next generation image-text models. *Advances in neural information processing systems*, 35:25278–25294, 2022.
- [46] Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International conference on learning representations*, 2021.
- [47] Sdxl-refiner. https://huggingface.co/stabilityai/stable-diffusion-xl-refiner-1.0, 2023.
- [48] Sdxl-turbo. https://stability.ai/research/adversarial-diffusion-distillation, 2023.
- [49] Keqiang Sun, Junting Pan, Yuying Ge, Hao Li, Haodong Duan, Xiaoshi Wu, Renrui Zhang, Aojun Zhou, Zipeng Qin, Yi Wang, et al. Journeydb: A benchmark for generative image understanding. Advances in neural information processing systems, 36, 2024.
- [50] Tristan Thrush, Ryan Jiang, Max Bartolo, Amanpreet Singh, Adina Williams, Douwe Kiela, and Candace Ross. Winoground: Probing vision and language models for visio-linguistic compositionality. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 5238–5248, 2022.
- [51] vintedois-diffusion v0.1. https://huggingface.co/22h/vintedois-diffusion-v0-1, 2023.
- [52] Zijie J Wang, Evan Montoya, David Munechika, Haoyang Yang, Benjamin Hoover, and Duen Horng Chau. Diffusiondb: A large-scale prompt gallery dataset for text-to-image generative models. In *Proceedings of the annual meeting of the association for computational linguistics*, pages 893–911, 2023.

- [53] Olivia Wiles, Chuhan Zhang, Isabela Albuquerque, Ivana Kajić, Su Wang, Emanuele Bugliarello, Yasumasa Onoe, Chris Knutsen, Cyrus Rashtchian, Jordi Pont-Tuset, et al. Revisiting text-to-image evaluation with gecko: on metrics, prompts, and human ratings. arXiv preprint arXiv:2404.16820, 2024.
- [54] Xiaoshi Wu, Yiming Hao, Keqiang Sun, Yixiong Chen, Feng Zhu, Rui Zhao, and Hongsheng Li. Human preference score v2: A solid benchmark for evaluating human preferences of text-to-image synthesis. arXiv preprint arXiv:2306.09341, 2023.
- [55] Xiaoshi Wu, Keqiang Sun, Feng Zhu, Rui Zhao, and Hongsheng Li. Human preference score: Better aligning text-to-image models with human preference. In *Proceedings of the IEEE/CVF international* conference on computer vision, pages 2096–2105, 2023.
- [56] Jiazheng Xu, Xiao Liu, Yuchen Wu, Yuxuan Tong, Qinkai Li, Ming Ding, Jie Tang, and Yuxiao Dong. Imagereward: Learning and evaluating human preferences for text-to-image generation. Advances in neural information processing systems, 36, 2024.
- [57] Jiahui Yu, Yuanzhong Xu, Jing Yu Koh, Thang Luong, Gunjan Baid, Zirui Wang, Vijay Vasudevan, Alexander Ku, Yinfei Yang, Burcu Karagol Ayan, et al. Scaling autoregressive models for content-rich text-to-image generation. *Transactions on machine learning research*, 2022.
- [58] Hang Zhang, Xin Li, and Lidong Bing. Video-Ilama: An instruction-tuned audio-visual language model for video understanding. *arXiv preprint arXiv:2306.02858*, 2023.
- [59] Lvmin Zhang, Anyi Rao, and Maneesh Agrawala. Adding conditional control to text-to-image diffusion models. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 3836–3847, 2023.
- [60] Shiwei Zhang, Jiayu Wang, Yingya Zhang, Kang Zhao, Hangjie Yuan, Zhiwu Qin, Xiang Wang, Deli Zhao, and Jingren Zhou. I2vgen-xl: High-quality image-to-video synthesis via cascaded diffusion models. arXiv preprint arXiv:2311.04145, 2023.
- [61] Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. Minigpt-4: Enhancing vision-language understanding with advanced large language models. arXiv preprint arXiv:2304.10592, 2023.

A Limitations

Multimodal LLMs. Since EVALALIGN evaluation models are fine-tuned MLLMs, they also suffer from multimodal hallucination, where models may generate content that seems plausible but actually incorrect or fabricated, and cannot be inferred from the input images and texts. Moreover, due to the possible harmful content in the pretraining data of the utilized base MLLMs, the model may inherit these biases and generate inappropriate response. Although we carefully curate the SFT training data of the EVALALIGN evaluation models, the problems of hallucination and biased pre-training is alleviated but not fully addressed. Other than the these issues, EVALALIGN evaluation models also suffer from opacity and interpretability, context limitation, as well as sensitivity to input formatting, like most multimodal LLMs.

Human Annotations. Human annotation is naturally subjective and influenced by individual perspectives, biases, and preferences. During the annotation, annotators can make mistakes, leading to incorrect or noisy labels. Regarding these challenges, we conduct 9 rounds of trial annotation and 2 rounds of random sampling quality inspection to ensure the inter-annotator consistency and overall annotation quality. We also design easy-to-understand annotation guidelines, instructions and platform to lower the annotation difficulty and benefit the annotation accuracy. Despite all these efforts, conducting human annotation with different annotators, user interface and annotation guidelines may lead to different result, making our annotation somewhat limited. Furthermore, human annotation can be time-consuming and resource-intensive, limiting the scale at which we can afford.

B Ethical and Social Impacts

Similar with other MLLMs, EVALALIGN may potentially generate responses contain offensive, inappropriate, or harmful content. Since the base MLLMs of EVALALIGN are pretrained on large datasets scraped from the web that might contain private information and harmful content, they may inadvertently generate or expose sensitive information, raising ethical and privacy concerns. MLLMs are also susceptible to adversarial attacks, where inputs are intentionally crafted to deceive the model. This vulnerability can be exploited to manipulate model outputs, posing security and ethic risks. To alleviate these safety limitation, we create dedicated evaluation sets for bias detection and mitigation, and conducted adversarial testing through hours of redteaming. Besides, EVALALIGN is designed for fine-grained, human-aligned automatic text-to-image evaluations. We believe that with appropriate use, it could provide users with interesting experiences for detailed synthesized image evaluation, and inspires more appealing research works about text-to-image generation.

C Annotation Details

Before performing the final human annotation, we made a series of efforts to guarantee its quantity, quality and efficiency. To begin with, we select appropriate candidates to perform the annotation and hold a training meeting for them. Then, we design a user-friendly user interface and a comprehensive annotation procedure. We write a detailed annotation guidelines to explain every aspect and precaution of the annotation. As mentioned above, we conduct 9 rounds of trial annotation on another 50 synthesized images and 2 turns of random sampling quality inspection to further ensure inter-annotator consistency and annotation accuracy.

Annotator selection. The accuracy and reliability of the annotated data depend heavily on the capabilities of the human annotators involved in the annotation process. As a consequence, at the beginning of the annotation, We first conduct annotator selection to build an appropriate and unbiased annotation team, and train this annotation team with our meticulously prepared annotation guidelines. For annotator selection, we let the candidates to accomplish a test concentrating on 10 factors, domain expertise, resistance to visually disturbing content, attention to detail, communication skills, reliability, cultural and linguistic competence, technical skills, ethical considerations, aesthetic cognition, and motivation. Notably, since the evaluated models may generate images with uncomfortable and inappropriate visual content, the candidates are notified with this inconvenience before the test. Only those agreed with this inconvenience are eligible to participate in the test, and they are welcome to withdraw at any time if they choose to do so. Based on the test results and candidate backgrounds, We try our best to ensure that the selected annotators are well-balanced in background and have

No.4512 Prompt: A woman wearing a red dress is gently cradling a small, white puppy in her arms.



Figure 4: Demonstration of our user interface. Each time, our specially designed user interface will provide one sample to the annotators. We incorporated four distinct icons to signify various functionalities of the user interface.

a generally competitive abilities of the 10 mentioned factors. To summarize, our annotation team includes 10 annotators carefully selected from 29 candidates, 5 males and 5 females, all have a bachelor's degree. We interview the annotators and ensure they are adequate for the annotation.

Annotation training and guidelines. After the selection, we conduct a training meeting over our comprehensive user guidelines to make the annotation team aware of our purpose and standard. During the training meeting, we explain the purpose, precaution, standard, workload and wage of the annotation. Besides, we have formally informed the annotators that the human annotation is solely for research purposes, and the data they have annotated may potentially be released to the public in the future. We, and the annotators reached consensus on the standard, workload, wage and intended usage of the annotated data. The rules for recognising image faithfulness and text-image are universal, and thus each individual's standards should not differ significantly. As a consequence, we annotate a few samples using our meticulously developed annotation platform for the annotators to ensure inter-annotator consistency. The overall snapshot of the developed annotation paltform is exhibited in fig. 4. With this training, we also equip the annotators with necessary knowledge for unbiased detailed human evaluation on image faithfulness and text-image alignment. Specifically, the employed annotation guidelines involve the instructions for using the annotation platform and detailed guidelines about the annotation procedure, and we demonstrate them in Table 9.

Trial Annotation Even with the above preparation, there is no quantitative evidence to verify the quality, the efficiency, and the inter-annotator consistency of the human annotation. Additionally, the standard for assessing image faithfulness and text-image are universal, which further emphasize the significant role of high inter-annotator consistency. Considering that, we conduct a multi-turn trial annotation on another 50 synthesized images. After each trial, we calculate the Cohen's kappa coefficient and conduct a meeting for our annotators to explain annotation standards, rules and guidelines, thereby ensuring high inter-annotator reliability. In total, we conduct nine turns of trial annotation, and in the last turn of the trial, the Cohen's kappa coefficient of our annotators reaches 0.681, indicating high inter-annotator reliability.

Random Sampling Quality Inspection Upon reaching the milestone percentages of 25%, 50%, 75%, and 100% in the annotation progress, we conducted a series of random sampling quality inspections on the present annotation results at each milestone, totally four turns of random sampling quality inspection. The random sampling quality inspection by four experts in text-to-image generation selected from our group on 1,000 randomly sampled annotated images. For the first two turn of

quality inspection, there are totally 423 and 112 annotated samples that failed the inspection. The failed samples are re-annotated and re-inspected. As for the last two turns of quality inspection, they both revealed zero failed samples due to the thoughtful and rigorous annotation preparation.

D Additional Details of the Evaluated Models

In this section, we introduce the details of the evaluated text-to-image generative models in this work.

• Stable Diffusion {v1.4, v1.5, v2 base, v2.0, v2.1}. Stable Diffusion (SD) is a series of 1B text-toimage generative models based on latent diffusion model [41] and is trained on LAION-5B [45]. Specifically, the SD series includes SD v1.1, SD v1.2, SD v1.4, SD v1.5, SD v2 base, SD v2.0, and SD v2.1 respectively. Among them, we choose the most commonly-employed SD v1.4, SD v1.5, SD v2.0 and SD v2.1 for EVALALIGN evaluation.

SD v1.1 was trained at a resolution of 256x256 on laion2B-en for 237k steps, followed by training at a resolution of 512x512 on laion-high-resolution ((170M examples from LAION-5B with resolution >= 1024x1024) for the subsequent 194k steps. While, SD v1.2 was initialized from v1.1 and further finetuned for 515k steps at resolution 512x512 on laion-aesthetics v2 5+ (a subset of laion2B-en, filtered to images with an original size >= 512x512, estimated aesthetics score > 5.0, and an estimated watermark probability < 0.5). **SD v1.4** is initialized from v1.2 and subsequently finetuned for 225k steps at resolution 512x512 on laion-aesthetics v2 5+. This version incorporates a 10% dropping of the text-conditioning to improve classifier-free guidance sampling. Similar to SD v1.4, **SD v1.5** is resumed from SD v1.2 and trained 595k steps at resolution 512x512 on laion-aesthetics v2 5+, with 10% dropping of the text-conditioning.

SD v2 base is trained from scratch for 550k steps at resolution 256x256 on a subset of LAION-5B filtered for explicit pornographic material, using the LAION-NSFW classifier with punsafe = 0.1 and an aesthetic score >= 4.5. Then it is further trained for 850k steps at resolution 512x512 on the same dataset on images with resolution >= 512x512. **SD v2.0** is resumed from stable-diffusion v2 base and trained for 150k steps using a v-objective on the same dataset. After that, it is further finetuned for another 140k steps on 768x768 images. **SD v2.1** is finetuned from SD v2.0 with an additional 55k steps on the same dataset (with punsafe=0.1), and then finetuned for another 155k extra steps with punsafe=0.98.

- Stable Diffusion XL {v1.0, Refiner v1.0}. Stable Diffusion XL (SDXL) is a powerful text-toimage generation model that iterates on the previous Stable Diffusion models in three key ways: (1) its UNet is 3x larger and SDXL combines a second text encoder (OpenCLIP ViT-bigG/14) with the original text encoder to significantly increase the number of parameters; (2) it introduces size and crop-conditioning to preserve training data from being discarded and gain more control over how a generated image should be cropped; (3) it introduces a two-stage model process; the base model (can also be run as a standalone model) generates an image as an input to the refiner model which adds additional high-quality details.
- **Pixart-Alpha.** Pixart-Alpha is a model that can be used to generate and modify images based on text prompts. It is a Transformer Latent Diffusion Model that uses one fixed, pretrained text encoders (T5)) and one latent feature encoder (VAE).
- Latent Consistency Model Stable Diffusion XL Latent Consistency Model Stable Diffusion XL (LCM SDXL) [28] enables SDXL for swift inference with minimal steps. Viewing the guided reverse diffusion process as solving an augmented probability flow ODE (PF-ODE), LCMs are designed to directly predict the solution of such ODE in latent space, mitigating the need for numerous iterations and allowing rapid, high-fidelity sampling.
- **Dreamlike Diffusion 1.0.** Dreamlike Diffusion 1.0 [10] is a SD v1.5 model finetuned on highquality art images by dreamlike.art.
- **Dreamlike Photoreal 2.0.** Dreamlike Photoreal 2.0 [11] is a photorealistic text-to-image latent diffusion model resumed from SD v1.5 by dreamlike art. This model was finetuned on 768x768 images, it works pretty good with resolution 768x768, 640x896, 896x640 and higher resolution such as 768x1024.
- **Openjourney v1, v2.** Openjourney [34] is an open-source text-to-image generation model resumed from SD v1.5 and finetuned on Midjourney images by PromptHero. Openjourney v2 [35] was

further finetuned using another 124000 images for 12400 steps, about 4 epochs and 32 training hours.

- **Redshift Diffusion**. Redshift Diffusion [39] is a Stable Diffusion model finetuned on high-resolution 3D artworks.
- Vintedois Diffusion. Vintedois Diffusion [51] is a Stable Diffusion v1.5 model finetuned on a large number of high-quality images with simple prompts to generate beautiful images without a lot of prompt engineering.
- Safe Stable Diffusion {Weak, Medium, Strong, Max}. Safe Stable Diffusion [31] is an enhanced version of the SD v1.5 model by mitigating inappropriate degeneration caused by pretraining on unfiltered web-crawled datasets. For instance SD may unexpectedly generate nudity, violence, images depicting self-harm, and otherwise offensive content. Safe Stable Diffusion is an extension of Stable Diffusion that drastically reduces this type of content. Specifically, it has an additional safety guidance mechanism that aims to suppress and remove inappropriate content (hate, harassment, violence, self-harm, sexual content, shocking images, and illegal activity) during image generation. The strength levels for inappropriate content removal are categorized as: {Weak, Medium, Strong, Max}.
- **MultiFusion.** MultiFusion [29] is a multimodal, multilingual diffusion model that extends the capabilities of SD v1.4 by integrating various modules to transfer capabilities to the downstream model. This combination results in novel decoder embeddings, which enable prompting of the image generation model with interleaved multimodal, multilingual inputs, despite being trained solely on monomodal data in a single language.
- **DeepFloyd-IF { M, L, XL } v1.0.** DeepFloyd-IF [1] is a novel state-of-the-art open-source textto-image model with a high degree of photorealism and language understanding. It is a modular composed of a frozen text encoder and three cascaded pixel diffusion modules: a base model that generates 64x64 image based on text prompt and two super-resolution models, each designed to generate images of increasing resolution: 256x256 and 1024x1024, respectively. All stages of the model utilize a frozen text encoder based on the T5 transformer to extract text embeddings, which are then fed into a UNet architecture enhanced with cross-attention and attention pooling. Besides, it underscores the potential of larger UNet architectures in the first stage of cascaded diffusion models and depicts a promising future for text-to-image synthesis. The model is available in three different sizes: M, L, and XL. M has 0.4B parameters, L has 0.9B parameters, and XL has 4.3B parameters.

Throughout all of the conducted experiments, we use the default inference settings for each evaluated models.

Table 9: User Guidelines of the Human Annotation. Considering that our annotators are native Chinese speakers while our readers may not be, each user is actually provided with a copy of Chinese version of the user guidelines. Meanwhile, we demonstrate its translated English version as follows.

User Guidelines

Part I Introduction

Welcome to the annotation platform. This platform is designed to simplify the annotation process and enhance annotation efficiency. Before the detailed introduction, we want to claim again that you may feel inconvenient as the evaluated models may generate images with uncomfortable and inappropriate visual content. Now, you are still welcomed if you want to withdraw your consent The annotation process is conducted on a sample-by-sample basis, with a question-by-question approach. Thus, you are supposed to answer all the questions raised for the present sample to accomplish its annotation. Once all the delegated samples are accomplished, your job is finished and we are thankful for your contribution to the project.

Part II Guidelines of the User Interface

1.User Login: To access the annotation platform, you are required to login as a user. Please navigate to the login page, enter the username and password provided by us, and click the "Login" button.

2.Dashboard: Once you complete the login, you will be jumped into the dashborad page. The dashboard will list the overview of the samples assigned to you to annotate. Besides, we list the status of each sample for you to freely check your annotation progress (e.g., pending, completed).

3.Annotation Interface: Click on the "Start" button or an assigned image through the dashboard interface, you will jump into the annotation interface. annotation interface is made up of three components: 1) Image Display: View the image to be annotated and its conditioned prompts; 2) Question Panel: List of single-choice questions related to the image; 3) Navigation Buttons: "Next" and "Previous" buttons to navigate through questions and images.

4.Answering Questions: Each time, the annotation interface will provide you a sample for annotation, please view the image and read the associated question, select the appropriate answer from the available options, and repeat the processs for all questions related to the question.

5.Saving and Submitting Annotations: To save progress and submit completed annotations, you can click the "Save" button to save your progress. If you finish the assigned sample and ensure the accuracy and confidence of its, you can click the "Submit" button to submit this annotation.

6.Review and Edit Annotations: If you want to review and edit your submission, you can navigate the completed tasks section, and select the image to review. You will jump into its annotation interface with the previously submitted annotations and are allowed to do any modification.

7.Report and contact: If you find any problem about the assigned sample, such as witnessing NSFW or biased content, assigned visually abnormal sample, feel free to click the "Report" button and fill a form to report this sample. If you have any question about the standard of the annotation or have suggestions for improvement, please do not hesitate to contact us through phone, we will be glad to help you.

Part III General Guidelines of the Human Annotation

1.In general, you are supposed to answer all the questions raised for the present sample to accomplish its annotation. This annotation only involves single-choice question.

2.Before answering the question, please ensure that the question is applicable to this prompt. If it is not applicable, please select option 0 directly—this is the predefined option for this particular scenario.

3.If you are answering a question about the image faithfulness, you may find the question is applicable to multiple objects within the image. you need to answer the question regarding to every applicable object and its role in the image. A straightforward way for this is to solely score every applicable object and choose the option closest to the calculated weighted average score.

4.If you are answering the object faithfulness question on the image faithfulness annotation, you need to drop and report for the encountered image with no clear main object.

5. If you are answering the commonsense question on the image faithfulness annotation, you need to drop and report for the encountered surreal and sci-fi image.

6. You are required to first annotate 30 samples to form a stable and reasonable assessment standard. Then, accomplish the annotation in progress.

7. This annotation is for evaluating image faithfulness and text-image alignment, as a consequence, the standard of the annotation is universal.

8. If you feel confused at anything about the human annotation, feel free to contact us through phone, we will be glad to help you.

9. Once you have submitted your annotation results, we are very thankful to inform you that you have finished your job. Thank you once again for your contribution to our project.

10.If you have submitted your annotation but want to withdraw your submission and review the annotation results, you can contact us through phone, we will send it back to you.

E Instruction Templates

Here, we present every instruction used for EVALALIGN evaluation on image faithfuleness and text-image alignment. The templates contain some placeholders set for filling in the corresponding attributes of the input images during the evaluation. For example, a specific "<ObjectHere>" and "<NumberHere>" can be "people, laptop, scissors." and "plate: 1, turkey sandwich: 3, lettuce: 1.", respectively.

For EVALALIGN evaluation on image faithfulness, we devise 5 questions concentrate on the faithfulness of the generated body structure, generated face, generated hand, generated objects, as well as generation adherence to commonsense and logic. The instruction templates for these fine-grained criteria are as follows:

[Q1]:Are there any issues with the [human/animals] body structure in the image, such as multiple arms, missing limbs or legs when not obscured, multiple heads, limb amputations, and etc?

[OPTIONS]: 0. There are no human or animal body in the picture; 1. The body structure of the people or animals in the picture has a very grievous problem that is unbearable; 2. The body structure of the people or animals in the picture has some serious problems and is not acceptable; 3. The body structure of the people or animals in the picture has a slight problem that does not affect the senses; 4. The body structure of the people or animals in the picture is basically fine, with only a few flaws; 5. The body structure of the people or animals in the picture is completely fine and close to reality.

[Q2]:Are there any issues with the [human/animals] hands in the image, such as having more or less than five fingers when not obscured, broken fingers, disproportionate finger sizes, abnormal nail size proportions, and etc?

[OPTIONS]: 0.No human or animal hands are shown in the picture; 1.The hand in the picture has a very grievous problem that is unbearable; 2.The hand in the picture has some serious problems and is not acceptable; 3.The hand in the picture has a slight problem that does not affect the senses; 4.The hand in the picture is basically fine, with only a few flaws; 5.The hands in the picture are completely fine and close to reality.

[Q3]:Are there any issues with [human/animals] face in the image, such as facial distortion, asymmetrical faces, abnormal facial features, unusual expressions in the eyes, and etc? **[OPTIONS]**: 0.There is no face of any person or animal in the picture; 1.The face of the person or animal in the picture has a very grievous problem that is unbearable; 2.The face of the person or animal in the picture has some serious problems and is not acceptable; 3.The face of the person or animal in the picture has a slight problem that does not affect the senses; 4.The face of the person or animal in the picture is basically fine, with only a few flaws; 5.The face of the person or animal in the picture is completely fine and close to reality.

[Q4]: Are there any issues or tentative errors with objects in the image that do not correspond with the real world, such as distortion of items, and etc?

[OPTIONS]: 0. There are objects in the image that completely do not match the real world, which is very serious and intolerable; 1. There are objects in the image that do not match the real world, which is quite serious and unacceptable; 2. There are slightly unrealistic objects in the image that do not affect the senses; 3. There are basically no objects in the image that do not match the real world, only some flaws; 4. All objects in the image match the real world, no problem.

[Q5]:Does the generated image contain elements that violate common sense or logical rules, such as animal/human with inconsistent anatomy, object-context mismatch, impossible physics, scale and proportion issues, temporal and spatial inconsistencies, hybrid objects, and etc?

[OPTIONS]: 0.The image contains elements that violate common sense or logical rules, which is very grievous and intolerable; 1.The presence of elements in the image that seriously violate common sense or logical rules is unacceptable; 2.The image contains elements that violate common sense or logical rules, which is slightly problematic and does not affect the senses; 3.There are basically no elements in the image that violate common sense or logical rules, which is slightly problematic and sense or logical rules, only some flaws; 4.There are no elements in the image that violate common sense or logical rules, and they are close to reality.

The templates of EVALALIGN evaluation on text-image alignment are as follows. We select 6 common aspects of text-image alignment, object, number, color, style, spatial relationship and action. For images that do not involve the specified attribute, the corresponding question template is not filled in and subsequently input into EVALALIGN.

[Q1]:Does the given image contain all the objects (<ObjectHere>) presented in the corresponding prompts?

[OPTIONS]: 1.None objects are included; 2.Some objects are missing; 3.All objects are included.

[Q2]:Does the given image correctly reflect the numbers (<NumberHere>) of each object presented in the corresponding prompts?

[OPTIONS]: 1.All counting numbers are wrong; 2.Some of them are wrong; 3.All counting numbers are right.

[Q3]:Does the given image correctly reflect the colors of each object (<ColorHere>) presented in the corresponding prompts?

[OPTIONS]: 1.All colors are wrong; 2.Some of them are wrong; 3.All corresponding colors numbers are right.

[Q4]:Does the given image correctly reflect the style (<StyleHere>) described in the corresponding prompts?

[OPTIONS]: 1.All styles are wrong; 2.Some of them are wrong; 3.All styles are right.

[Q5]:Does the given image correctly reflect the spatial relationship (<SpatialHere>) of each object described in the corresponding prompts?

[OPTIONS]: 1.All spatial relationships are wrong; 2.Some of them are wrong; 3.All spatial relationships are right.

[Q6]:Does the given image correctly reflect the action of each object (<ActionHere>) described in the corresponding prompts?

[OPTIONS]: 1.All actions are wrong; 2.Some of them are wrong; 3.All actions are right.

F Additional Quantitative Analysis

F.1 Generalization Experiments

To verify the generalization capability of our evaluation model, We compared MLLM's SFT using different training datasets: one with images generated by all 8 text-to-image models and another

with images generated by only 4 of these models, while the final evaluation was conducted on images generated by the other 4 models. As shown in Table 10 and Table 11, We observed that MLLMs trained on images from a subset of text-to-image models can effectively generalize to images generated by unseen text-to-image models.

Table 10: Ablation study on the number of different text-to-image models used to generate the training data for evaluating image faithfulness. We observe that EVALALIGN exhibits strong generalization capability.

Method	T2I models	body	hand	face	object	common	MAE
Human	-	1.4988	0.8638	1.1648	2.2096	0.8710	0
EVALALIGN	8 4	1.6058 1.6522	0.7901 0.9588	1.1974 1.2355	2.2783 2.3032	0.8871 0.9516	0.0596 0.0987

Table 11: Ablation study on the number of different text-to-image models used to generate the training data for evaluating text-to-image alignment. We observe that EVALALIGN exhibits strong generalization capability.

Method	T2I models	Object	Count	Color	Style	Spatial	Action	MAE
Human	-	1.7373	1.3131	2.0000	1.9333	1.5952	1.8837	0
EVALALIGN	84	1.7203 1.7832	1.3232 1.3526	1.9565 1.9637	1.9333 1.9876	1.6547 1.6891	1.8605 1.8954	0.0256 0.0469

F.2 Instruction Enhancement Experiments

Providing more contextual information for instructions enhances the performance of MLLMs. To further improve MLLM evaluation performance, we enhanced the prompts for both SFT and inference stages. As shown in Table 12, our experiments demonstrate that the enhanced prompts significantly increase evaluation accuracy. Specifically, the evaluation using enhanced instructions reduced the MAE metric by half, from 0.120 to 0.006, compared to the original instructions. Additionally, this approach consistently improved evaluation performance across different text-to-image models.

F.3 Mulit-scaling Resolutions Experiments

In the design of LLaVA-Next, using multi-scale resolution images as input helps address the issue of detail information loss, which significantly impacts the evaluation of image faithfulness, such as assessing deformations in hands and faces. We conducted a multi-scale image training comparison experiment to validate this approach. The baseline was the 13B LLaVA model with 336×336 resolution input, while the comparison model used images at three resolutions (336×336 , 672×672 , 1008×1008) as input. As shown in Table 13, training with multi-scale inputs significantly enhanced the model's understanding of image and achieved better evaluation performance.

F.4 Full Comparison with Existing Evaluation Methods

Table 14 and Table 15 present the comparison results between our proposed method and existing alternatives. Owing to the powerful aligned understanding of images and text by MLLMs, our model achieves the best alignment with human performance across all tested benchmarks for 24 text-to-image models, along with a significant improvement in image faithfulness. This indicates that our model excels in both comprehending and evaluating the intricate details of generated images, closely mirroring human judgment and setting a new standard for image-text alignment and faithfulness.

G Qualitative Analysis

As shown in Figure 5, we present a comparison of different evaluation metrics on images generated by four models, including human annotated scores, EVALALIGN, ImageReward [56], HPSv2 [54], and PickScore [20]. The digits in the figure represent the ranking for each evaluation metric, with darker

Table 12: Ablation study on the enhancement of instructions. Results are reported on image faithfulness under different instructions. We observe that enhanced instructions can significantly improves the evaluation metrics. MAE: mean absolute error.

Method	Instruction	SDXL	Pixart	Wuerstchen	SDXL-Turbo	IF	SD v1.5	SD v2.1	LCM	MAE
Human	-	2.1044	1.8606	1.7839	1.3854	1.3822	1.3818	1.1766	1.0066	0
EVALALIGN	×	1.9565 2.0443	1.9286 1.9199	1.8565 1.8012	1.1818 1.3353	1.3419 1.2960	1.4801 1.4702	1.4078 1.3221	1.1051 1.0305	0.1201 0.0064

Table 13: Ablation study on multi-scale input. Results are reported on image faithfulness under different input strategy. We observe that input with multi-scale resolution images can improve the evaluation metrics. MAE: mean absolute error.

Method	Multi Scale	SDXL	Pixart	Wuerstchen	SDXL-Turbo	IF	SD v1.5	SD v2.1	LCM	MAE
Human	-	2.1044	1.8606	1.7839	1.3854	1.3822	1.3818	1.1766	1.0066	0
EVALALIGN	✓	1.8105 2.0443	1.9238 1.9199	1.9325 1.8012	1.2078 1.3353	1.2247 1.296	1.4540 1.4702	1.3012 1.3221	1.0554 1.0305	0.1358 0.0064

colors indicating higher rankings. From the figure, it is evident that our proposed EvalAlign metric closely matches the human rankings across two evaluation dimensions, demonstrating excellent consistency.

Furthermore, Figure 6 showcases the EVALALIGN evaluation metric across different fine-grained results. The numbers in the figure represent EVALALIGN scores for the corresponding evaluation aspect, with darker colors indicating higher scores and better generation performance. Note that if the text prompt does not specify a particular style, the style consistency score defaults to 0. From these results, it is evident that the same text-to-image model exhibits significant performance variation across different evaluation aspects.

Model	Human	EVALALIGN	HPS v2	CLIP-score	mageReward	PickScore	IS
PixArt XL2 1024 MS [6]	2.2848 1	1.6415 ¹	31.6226 1	0.8580 1	0.9696 1	22.1335 ¹	5.2583 ²¹
Dreamlike Photoreal v2.0 [11]	2.0070 ²	1.4522 4	29.2322 ⁶	0.8286 12	0.1886 13	21.2271 ⁸	5.6452 14
SDXL Refiner v1.0 [47]	1.9229 ³	1.6072^{-2}	29.8197 ³	0.8566 2	0.7245 2	22.0492 ²	5.3985 ¹⁶
SDXL v1.0 [33]	1.8136 ⁴	1.4675 ³	29.0620 ⁷	0.8467 4	0.7043 ³	21.8106 ³	5.3774 ¹⁸
Wuerstchen [32]	1.7837 ⁵	1.4279 ⁵	30.6622 ²	0.8199 14	0.3212 11	21.3720 ⁶	5.9751 ⁴
LCM SDXL [28]	1.6910 ⁶	1.3391 7	29.3588 ⁵	0.8335 10	0.5304 6	21.6532 ⁴	5.9874 ³
Openjourney [34]	1.6667 7	1.1750 10	26.3475 13	0.8196 15	0.1478 16	20.8637 10	5.7368 ¹⁰
Safe SD MAX [31]	1.6491 ⁸	1.2175 ⁸	25.7396 ¹⁷	0.7555 24	-0.0507 ²²	20.4594 21	5.5428 ¹⁵
LCM LORA SDXL [28]	1.6387 ⁹	1.3833 ⁶	27.3299 10	0.8364 8	0.4959 7	21.4824 5	5.6575 ¹²
Safe SD STRONG [31]	1.6308 10	1.1466 11	25.5764 ¹⁸	0.8165 18	-0.1022 ²³	20.6211 18	5.8643 ⁶
Safe SD MEDIUM [31]	1.6275 11	1.1298 15	26.2798 14	0.8101 20	0.2042 12	20.7880 12	6.1760 ¹
Safe SD WEAK [31]	1.6078 12	1.1188 ¹⁷	26.1180 15	0.7809 ²³	-0.1264 ²⁴	20.3873 ²⁴	5.3861 ¹⁷
SD v2.1 [40]	1.5524 13	1.1094 18	26.5823 12	0.8377 7	0.4116 9	21.0502 ⁹	5.3073 ¹⁹
SD v2.0 [40]	1.5277 14	1.1300 14	25.3481 ²¹	0.8170 17	0.0872 18	20.7529 ¹³	5.9060 ⁵
Openjourney v2 [35]	1.5000 15	0.9956 20	24.6984 ²³	0.7958 22	-0.0415 ²¹	20.4088 ²²	5.1995 ²²
Redshift diffusion [39]	1.4733 ¹⁶	1.1382 12	25.1572 ²²	0.8101 21	0.0218 20	20.6155 19	5.7657 ⁸
Dreamlike Diffusion v1.0 [10]	1.4652 17	1.2052 9	29.6506 ⁴	0.8543 ³	0.6508 4	21.2664 7	5.6614 11
SD v1.5 [40]	1.4417 ¹⁸	1.1362 13	25.4972 ¹⁹	0.8214 13	0.1686 14	20.7143 ¹⁶	6.0535 ²
IF-I-XL v1.0 [1]	1.3808 ¹⁹	0.9221 22	27.4512 ⁹	0.8449 5	0.6087 5	20.7474 14	5.3012 ²⁰
SD v1.4 [40]	1.3592 ²⁰	0.9511 21	25.3697 ²⁰	0.8190 16	0.1050 17	20.6535 17	5.8571 ⁷
Vintedois Diffusion v0.1 [51]	1.3562 21	1.0797 19	26.5901 11	0.8341 9	0.3562 10	20.8358 11	5.0181 ²³
IF-I-L v1.0 [1]	1.2635 ²²	0.8814 23	27.4836 ⁸	0.8384 6	0.4463 8	20.7170 15	5.6502 13
MultiFusion [29]	1.2372 ²³	1.1298 16	23.8133 ²⁴	0.8151 19	0.0695 19	20.4780 ²⁰	4.3824 ²⁴
IF-I-M v1.0 [1]	1.0135 ²⁴	0.7928 24	25.9522 16	0.8329 11	0.1637 15	20.4035 ²³	5.7451 ⁹

Table 14: Results on faithfulness.

Image Faithfulness: A man is drinking water from a glass while another man is observing a dog nearby.



HPS v2 :

Human :

HPS v2 :

PickScore :

ImageReward: 1

ImageReward:

PickScore : 2

Image Faithfulness: A farmer wearing a hat feeds a cow with a bell grazing in a field.



Text-Image Alignment: A young child wearing a bright yellow raincoat joyfully jumps in the puddles, while their playful dog, adorned with a green collar, eagerly chases after them.

SDXL Pixart Openjourney Dreamlike EvalAlign :

Text-Image Alignment : The purple-haired girl sitting on the car, night, city background.



Figure 5: Qualitative results of EVALALIGN benchmark. As can be concluded, EVALALIGN is consistently aligned with fine-grained human preference in terms of image faithfulness and text-image alignment, while other methods fail to do so.

Model	Human	EvalAlign	HPS v2	CLIP-score I	mageReward	PickScore	IS
IF-I-XL v1.0 [1]	5.4500 ¹	5.5300 ¹	32.5477 10	0.8579 ²	0.4391 ³	21.1998 10	7.1864 ⁵
IF-I-L v1.0 [1]	5.2300 ²	5.4500 ²	32.7140 ⁹	0.8538 4	0.3820 6	21.1284 12	6.6571 ²⁰
SDXL Refiner v1.0 [47]	5.2100 ³	5.4000 ³	35.6465 ³	0.8528 5	0.4738 ²	22.3532 ²	7.1101 ⁸
LCM SDXL [28]	5.1800 ⁴	5.3300 ⁵	33.8011 ⁶	0.8512 6	0.3833 5	21.9620 4	7.0067 14
PixArt XL2 1024 MS [6]	5.1100 ⁵	5.3100 ⁶	37.0493 ¹	0.8634 1	0.6542 1	22.3926 ¹	6.9293 ¹⁶
IF-I-M v1.0 [1]	5.0800 ⁶	5.2200 ⁸	31.0951 14	0.8434 8	0.0499 10	20.8270 20	7.2586 ³
LCM LORA SDXL [28]	5.0600 7	5.2700 7	32.7752 ⁸	0.8349 10	0.1618 9	21.7627 ⁶	6.8389 ¹⁹
SDXL v1.0 [33]	5.0300 ⁸	5.3500 4	35.1593 ⁴	0.8540 ³	0.4322 4	22.1291 ³	7.2762 ¹
Wuerstchen [32]	4.8700 ⁹	5.1700 ⁹	36.4632 ²	0.8381 9	0.2513 7	21.7779 ⁵	7.1280 7
Openjourney [34]	4.8300 10	4.9200 15	31.1495 12	0.8173 16	-0.0867 14	21.1163 ¹³	6.2729 ²²
SD v2.1 [40]	4.8000 11	5.0700 11	31.1017 13	0.8278 14	-0.0453 12	21.2093 ⁹	7.0767 ⁹
MultiFusion [29]	4.6800 12	4.8000 18	28.7957 ²⁴	0.8264 15	-0.1337 ¹⁵	20.9625 17	4.9593 ²⁴
Dreamlike Diffusion v1.0 [10]	4.6600 13	5.1500 10	34.8196 ⁵	0.8493 7	0.2295 8	21.5550 7	6.8581 ¹⁸
SD v2.0 [40]	4.6400 14	5.0100 12	30.6153 ¹⁷	0.8298 13	-0.1424 ¹⁶	21.1905 11	7.0124 13
Vintedois Diffusion v0.1 [51]	4.6200 15	4.9500 14	31.9503 11	0.8319 12	-0.0222 11	21.1141 14	6.1987 ²³
Safe SD STRONG [31]	4.6000 16	4.8300 17	30.6615 ¹⁶	0.7751 ²³	-0.5028 ²²	20.7491 ²¹	7.2743 ²
Dreamlike Photoreal v2.0 [11]	4.5600 17	4.9800 13	33.7712 ⁷	0.8344 11	-0.0859 ¹³	21.4832 ⁸	6.9363 ¹⁵
Safe SD WEAK [31]	4.5300 18	4.7100 ²⁰	30.5644 18	0.8140 18	-0.2728 ¹⁸	20.9899 ¹⁶	6.4238 ²¹
SD v1.4 [40]	4.5200 19	4.7600 19	29.9149 ²⁰	0.8048 20	-0.3438 ¹⁹	20.8462 19	7.0150 12
SD v1.5 [40]	4.4500 20	4.9000 16	30.1673 ¹⁹	0.8142 17	-0.2213 17	20.8640 18	7.1642 ⁶
Safe SD MEDIUM [31]	4.4000 21	4.5600 24	30.7820 15	0.7974 21	-0.3591 ²⁰	21.0257 15	7.0709 10
Redshift diffusion [39]	4.3500 ²²	4.6700 21	29.2865 ²²	0.8066 19	-0.4172 ²¹	20.6327 ²³	7.0610 11
Safe SD MAX [31]	4.3100 ²³	4.5900 ²³	29.8126 ²¹	0.7601 24	-0.6095 ²⁴	20.7046 ²²	7.2273 4
Openjourney v2 [35]	4.1500 ²⁴	4.6500 ²²	29.2389 ²³	0.7851 22	-0.6051 ²³	20.5973 ²⁴	6.8613 17

Table 15: Results on text-to-image alignment.



Image Faithfulness: A man is drinking water from a glass while another

Image Faithfulness: A farmer wearing a hat feeds a cow with a bell grazing in a field.



Text-Image Alignment : The purple-haired girl sitting on the car, night, city background.

colla	ar, eagerly chas	ses after them.						
	SDXL	Pixart	Openjourney	Dreamlike	SDXL	Pixart	Openjourney	Dreamlike
Object :	3	3	2	2	3	2	3	3
Count :	3	3	3	3	3	3	3	3
Color	3	2	2	2	3	3	1	3
Style	0	0	0	0	0	0	0	0
Spatial :	3	2	2	1	3	3	3	3
Action :	3	3	3	3	3	3	3	3

Figure 6: **Qualitative results of EVALALIGN benchmark.** As can be inferred, EVALALIGN distinctively provides multiple fine-grained scores covering every aspect of image faithfulness and text-image alignment. Additionally, we noticed that, in general, a model cannot perform well on every fine-grained aspect, which is consistent with [21].