An elementary approach based on variational inequalities for modelling a friction-based locomotion problem

Panyu Chen¹, Álvaro Mateos González^{2,3}, and Laurent Mertz⁴

¹Department of Computer Science, Duke University

²University of Michigan-Shanghai Jiao Tong University Joint Institute, Shanghai Jiao Tong University, Shanghai, 200240, China

³Modeling, Data Analysis & Computational Tools for Biology Research Group,

Biomathematics Unit, Department of Biodiversity, Ecology & Evolution, Faculty of

Biological Sciences, Complutense University of Madrid, 28040 Madrid, Spain

⁴Department of Mathematics, City University of Hong Kong, Kowloon, Hong Kong, China

July 8, 2024

Abstract

We propose an elementary proof based on a penalization technique to show the existence and uniqueness of the solution to a system of variational inequalities modelling the friction-based motion of a two-body crawling system. Here for each body, the static and dynamic friction coefficients are equal.

1 Introduction

The ability of a living organism to move from one place to another is essential to its survival. Indeed, it makes it possible to meet many needs such as finding food, a habitat and a mate, or escaping predators and danger. Living organisms use a broad class of locomotion strategies such as swimming in the water, flying through the air or running, crawling, and slithering using friction between their body and the ground on land [1]. The understanding and simulation of the mechanisms underlying these locomotion strategies have promising applications in robotics [5, 10, ?] by biomimetics. In the present work, we propose a system of variational inequalities to model friction-based locomotion for multibody systems using friction forces between their bodies and a surface.

1.1 Physical formulation of a two-body crawling system using dry friction

We consider a setting similar to that of [17]: a system composed of two bodies with masses m_1 and m_2 lying on a flat surface. We assume all motion of the system is uni-dimensional along a single axis, thus we can represent the positions of masses m_1 and m_2 by two real numbers x_1 and x_2 . The velocity and the acceleration of mass m_i , $i \in \{1, 2\}$, are respectively denoted by $\dot{x}_i = \frac{dx_i}{dt}$ and \ddot{x}_i . A mechanism (linkage) connects the two bodies and imposes the temporal variation of their distance $\ell(t) \triangleq x_2(t) - x_1(t)$. For instance, if ℓ is a given oscillating function, it corresponds to an alternation between extension phases in which the bodies are pushed apart and contraction phases in which they are pulled closer. In this way, an overall motion of the system can be generated by the dry friction forces. The motion of the two-body system is described by Newton's second law: for each i = 1, 2, we have $m_i \ddot{x}_i + \mathbb{F}_i = G_i$, where G_i is a contact force (push or pull) applied to the body of mass m_i which is induced by ℓ and the body with mass $m_j, j \neq i$ and \mathbb{F}_i is a dry friction force described by Coulomb's model. The two forces \mathbb{F}_i and G_i are coupled and described as follows:

$$\mathbb{F}_i \triangleq \begin{cases} G_i, & \text{when } \dot{x}_i = 0 \text{ and } |G_i| \leq f_i, \\ \sigma_i f_i, & \text{when } \dot{x}_i \neq 0 \text{ or } (\dot{x}_i = 0 \text{ and } |G_i| > f_i) \end{cases}$$

where $\sigma_i \triangleq \operatorname{sign}(\dot{x}_i)$ when $\dot{x}_i \neq 0$ or $\sigma_i \triangleq \operatorname{sign}(G_i)$ when $\dot{x}_i = 0$. Here f_i is the dry friction coefficient associated with the mass m_i . See Figure 1 for illustration. Newton's third law implies that $G_1 = -G_2$, and then using $x_2 = x_1 + \ell$ to reduce the aforementioned equations of motion we obtain

$$G_2 = \frac{m_1 m_2}{M} \left(\ddot{\ell} + \frac{\mathbb{F}_2}{m_2} - \frac{\mathbb{F}_1}{m_1} \right)$$

where $M \triangleq m_1 + m_2$. As a consequence, the equations of motion can be formulated as

(1)
$$M\ddot{x}_1 + \mathbb{F}_1 = -m_2\ddot{\ell} - \mathbb{F}_2, \qquad M\ddot{x}_2 + \mathbb{F}_2 = m_1\dot{\ell} - \mathbb{F}_1.$$

Note that the equation of x_2 is redundant since x_2 is entirely determined by $x_2 = x_1 + \ell$, where ℓ is a known input. Thus, we are concerned with clarifying the dynamics of x_1 in order to represent the whole system.



Figure 1: Bodies of masses m_1 and m_2 at respective positions x_1 and x_2 . The linkage $\ell = x_2 - x_1$ imposes contact forces $G_1 = -G_2$ on the bodies. The directions of friction forces \mathbb{F}_1 and \mathbb{F}_2 oppose the body movements. Left: contraction phase. Right: extension phase.

1.2 Review of methods for friction-based locomotion

The dry friction forces in our paper describing solid-solid friction are rather standard, see chapter 10 of [14]. In a simple setting, the response of a single mass subjected to dry friction and external forces with appropriate regularity (possibly random) is well understood in terms of standard variational inequalities or differential inclusions [4, 12, 13]. Here, our setting with two masses is inspired by the work [17], where the authors prove that locomotion can occur in the framework introduced above provided the dry friction coefficients f_1 and f_2 are distinct. The time-variation of the body-body separation varies periodically, but asymmetrically in time. The authors study stick and slip phases separately and provide numerical simulations and asymptotic interpretations of their results. Models related to ours have recurrently been used in robotics inspired by biology, particularly for modular snake robots able to navigate complex environments. This ability spurred a theoretical and practical interest in modeling, building and potentially using such robots in impractical terrain. Starting in the 70s, Hirose and coauthors designed models for the biomechanics of snake locomotion, focusing on the coordination of contraction/extension of a chain of modular segments and the management of dry friction forces necessary for effective locomotion on rough surfaces [10, 15]. A survey on snake robot models can be found in [?]. More recently, several research groups have built experimental prototypes to study settings very closely related to ours. In [2], the authors model the 1-dimensional motion of a system of three connected masses on the dry frictional plane, enabled by periodic changes in inter-mass distances. Those distances are explicitly defined as continuous piece-wise parabolic periodic functions. The motion equations are solved for those analytic expressions and implemented in a prototype. In [3], the authors model a two-body crawler on an inclined plane under dry friction. Again, the system is actuated by periodic changes in distance masses. They analyze numerically and empirically the range of inclination angles and excitation laws that enable the system to crawl upwards. Beyond the case of unidimensional motion, several works have been focused on modeling 2- or 3-dimensional motion. In [5], the quasi-static motion of a twolink system on a frictional 2d plane is investigated. In [11], the development of a snake-inspired robot with active control of friction showcases practical applications of such models, enabling efficient movement across diverse terrains. On the theoretical analysis side, Gidoni and coauthors have studied abstract rateindependent systems motivated by applications to soft and elastic crawlers [6, 7, 9]. Their work in [8] is more general than ours, but their setup is more complex. In our work, we remain in the setup of [17], allowing for an elementary approach based on a penalization technique to obtain the existence uniqueness of a solution to Equation (1).

1.3 Our contribution: a system of variational inequalities modelling a two-body crawling system

For i = 1, 2, we define the functions $\varphi_i(y) = f_i|y|$, for $y \in \mathbb{R}$. Given $\ell(.)$ twice continuously differentiable on $[0, \infty)$ and $y_0 \in \mathbb{R}$, we consider the mathematical problem of finding three functions $y, k_1, k_2 : [0, \infty) \to \mathbb{R}$ such that

$$(\mathcal{S}_2)$$

(i)
$$y \in \mathcal{C}([0,\infty);\mathbb{R}), y(0) = y_0,$$

(*ii*)
$$k_1, k_2 \in \mathcal{C}([0, \infty); \mathbb{R}) \cap \mathcal{BV}_{loc}([0, \infty); \mathbb{R}), \text{ with } k_1(0) = 0$$

$$\begin{array}{ll} (ii) & \forall t \ge 0, \ My(t) + k_1(t) + k_2(t) = -m_2\dot{\ell}(t), \\ (iii) & \forall t \ge 0, \ My(t) + k_1(t) + k_2(t) = -m_2\dot{\ell}(t), \\ (iii) & \forall t \ge 0, \ \forall 0 \le c \le t, \ \forall t \in C([c, t]; \mathbb{P}). \end{array}$$

$$(iv) \quad \forall t \ge 0, \, \forall \, 0 \le s \le t, \, \forall \mathfrak{z} \in \mathcal{C}([s,t];\mathbb{R}),$$

$$\int_{s}^{t} [\mathfrak{z}(r) - y(r)] dk_{1}(r) + \int_{s}^{t} \varphi_{1}(y(r)) dr \leqslant \int_{s}^{t} \varphi_{1}(\mathfrak{z}(r)) dr,$$

(v) $\forall t \ge 0, \forall 0 \leqslant s \leqslant t, \forall \mathfrak{z} \in \mathcal{C}([s, t]; \mathbb{R}),$
 $\int_{s}^{t} [\mathfrak{z}(r) - y(r) - \dot{\ell}(r)] dk_{2}(r) + \int_{s}^{t} \varphi_{2}\left(y(r) + \dot{\ell}(r)\right) dr \leqslant \int_{s}^{t} \varphi_{2}(\mathfrak{z}(r)) dr.$

Due to the presence of a variational parameter \mathfrak{z} , the fourth and fifth conditions are also called variational inequalities (VI). Using the notation of [13], the first VI above corresponds to the differential inclusion $dk_1(t) \in \partial \varphi_1(y(t))(dt)$ whereas the second one correspond to $dk_2(t) \in \partial \varphi_2(y(t) + \dot{\ell}(t))(dt)$. Here we have $\partial \varphi_i(y) = \{f_i \operatorname{sign}(y)\}$ if $y \neq 0$ or $[-f_i, f_i]$ if y = 0. As a consequence, the problem above clarifies the sense of the following nonstandard multivalued equation $Mdy + \partial \varphi_1(y)(dt) + \partial \varphi_2(y + \dot{\ell})(dt) \ni -m_2\dot{\ell}dt$. Then the definition of x_1 becomes straightforward

$$\forall t \ge 0, \ x_1(t) = x_{1,0} + \int_0^t y(r) \mathrm{d}r.$$

Theorem 1. The problem (S_2) has a unique solution.

Remark 1. Our first theorem above resolves a nonstandard problem of Skorokhod. If we remove $\partial \varphi_1(y + \ell)(dt)$ in the multivalued equation above then it corresponds to a standard Skorokhod problem as shown on page 231 of [13] for instance. In terms of friction forces, roughly speaking, $\partial \varphi_1(y)$ and $\partial \varphi_2(y + \ell)$ corresponds to \mathbb{F}_1 and \mathbb{F}_2 respectively. It is worth mentioning that the same physical problem with $p \ge 2$ aligned masses can be treated in our mathematical framework with a straightforward generalization of the case p = 2.

2 Proof of Theorem 1

The proof is composed of four steps. The first step consists in studying a regularised version of (S_2) using the Moreau-Yosida regularization with two parameters n_1 and n_2 . The regularized equation whose state variable is y^n with $n = (n_1, n_2)$ can be analyzed using standard method of ODEs. In the second step, we show the sequence y^n has the Cauchy property with respect to the supremum norm $||y|| := \sup_{t \in \mathbb{R}_+} |y(t)|$. As a consequence, a limit exists. Then, in the third step, we identify the limit as a solution to a system of variational inequalities. Finally, in the last step, we prove the uniqueness of the limit.

2.1 Moreau-Yosida regularisation

The Moreau-Yosida regularisation of φ_i , which is a standard tool in non-smooth convex analysis in [4, Chap.2], is defined as follows: for each $n_i \in \mathbb{N}^*$, for each $y \in \mathbb{R}$,

$$\varphi_{i,n_i}(y) \triangleq \inf_{y' \in \mathbb{R}} \left\{ \frac{n_i}{2} (y - y')^2 + \varphi_i(y') \right\} = \begin{cases} f_i \frac{n_i}{2} y^2, & \text{if } n_i |y| \leq f_i, \\ f_i \left(|y| - \frac{1}{2n_i} \right), & \text{if } n_i |y| > f_i. \end{cases}$$

Thus, $\lim_{n_i\to\infty}\varphi_{i,n_i}(y) = \varphi_i(y)$. For each $n_i \in \mathbb{N}^*$, $\varphi_{i,n_i}(y)$ is differentiable and $\varphi'_{i,n_i}(y) = \operatorname{proj}_{[-f_i,f_i]}(n_iy)$. In this context, a regularisation of the problem (\mathcal{S}_2) consists in replacing φ_i by φ_{i,n_i} . Here given $\ell(.)$ twice continuously differentiable on $[0,\infty)$ and $y_0 \in \mathbb{R}$, we want to find a function $y^n \in C([0,\infty);\mathbb{R})$ where $n \triangleq (n_1, n_2)$ such that

(2)
$$\forall t \ge 0, \ My^{n}(t) + \int_{0}^{t} \varphi'_{1,n_{1}}(y^{n}(s)) \mathrm{d}s + \int_{0}^{t} \varphi'_{2,n_{2}}(y^{n}(s) + \dot{\ell}(s)) \mathrm{d}s = -m_{2}\dot{\ell}(t).$$

In turn, y^n is continuously differentiable and satisfies

(3)
$$\forall t \ge 0, \ M\dot{y}^n(t) + \varphi'_{1,n_1}(y^n(t)) + \varphi'_{2,n_2}(y^n(t) + \dot{\ell}(t)) = -m_2\ddot{\ell}(t).$$

Thus, the regularised problem boils down to an ordinary differential equation with Lipschitz nonlinear terms depending on n_1 and n_2 . For each $n = (n_1, n_2)$, applying Picard's theorem yields a unique solution y^n .

2.2 Cauchy convergence of the regularised solutions

For all $t \in \mathbb{R}_+$, for all $n \in N^{*2}$ we denote $k_1^n(t) := \int_0^t \varphi'_{1,n_1}(y^n(s)) ds$ and $k_2^n(t) := \int_0^t \varphi'_{2,n_2}(y^n(s) + \dot{\ell}(s)) ds + c_2$, with $c_2 = -My_0 - m_2\dot{\ell}(0)$ for compatibility with *(iii)* in (\mathcal{S}_2) . Hereafter, we simply refer to two-indexed sequences as sequences. We say the multi-index n tends to infinity when $\min(n)$ tends to infinity, and that a sequence indexed by n converges if it tends to a limit when $\min n \to \infty$.

Proposition 1. For all $t \ge 0$,

- (i) The sequence $(y^n)_n$ converges uniformly over [0,t] to a continuous function y.
- (ii) Up to extraction, k_1^n and k_2^n converge pointwise over [0, t] to continuous functions k_1, k_2 .
- (iii) y, k_1, k_2 satisfy the first three lines of system (\mathcal{S}_2) over [0, t].

Proof of (i). Fix $t \ge 0$. Let us start by proving that the set of solutions $\{y^{n_1,n_2} \mid n_1, n_2 \in \mathbb{N}\}$ satisfies the Cauchy condition: for all $\varepsilon > 0$ there exists N > 0 such that for all $n_1, n_2, r_1, r_2 \in \mathbb{N}^*$, if $\min(n_1, n_2, r_1, r_2) > N$, then $\|y_1^{n_1,n_2} - y_1^{r_1,r_2}\|_{L^{\infty}([0,t])} < \varepsilon$. First note that for any function f differentiable over an interval [0, t], we have

$$f(t)^{2} = f(0)^{2} + \int_{0}^{t} 2f(r) \frac{\mathrm{d}f(r)}{\mathrm{d}r} \,\mathrm{d}r$$

by the fundamental theorem of calculus. Take arbitrary positive naturals r_1, r_2, n_1, n_2 , and set $n = (n_1, n_2)$, $r = (r_1, r_2)$. Since $y^n(0) = y^r(0)$, injecting equation (3) into the above gives us

$$(y^{n}(t) - y^{r}(t))^{2} = -\frac{2}{M} \int_{0}^{t} (y^{n}(s) - y^{r}(s)) \left[\varphi'_{1,n_{1}}(y^{n}(s)) - \varphi'_{1,r_{1}}(y^{r}(s)) \right] ds - \frac{2}{M} \int_{0}^{t} (y^{n}(s) - y^{r}(s)) \left[\varphi'_{1,n_{2}}(y^{n}(s) + \dot{\ell}(s)) - \varphi'_{1,r_{2}}(y^{r}(s) + \dot{\ell}(s)) \right] ds,$$

which we can recast into

$$(y^{n}(t) - y^{r}(t))^{2} = -\frac{2}{M} \int_{0}^{t} (y^{n}(s) - y^{r}(s)) \left[\varphi'_{1,n_{1}}(y^{n}(s)) - \varphi'_{1,r_{1}}(y^{r}(s)) \right] ds - \frac{2}{M} \int_{0}^{t} \left((y^{n}(s) + \dot{\ell}(s)) - (y^{r}(s) + \dot{\ell}(s)) \right) \left[\varphi'_{1,n_{2}}(y^{n}(s) + \dot{\ell}(s)) - \varphi'_{1,r_{2}}(y^{r}(s) + \dot{\ell}(s)) \right] ds.$$

This allows us to apply the following inequality, a consequence of Equation (6.28.b) page 552 in [13]. Lemma 1. $\forall y_1, y_2 \in \mathbb{R}$, for $i \in \{1, 2\}$ and for all $n_i, r_i \in \mathbb{N}^*$, we have

$$-(y_1 - y_2)(\varphi'_{i,n_i}(y_1) - \varphi'_{i,r_i}(y_2)) \le (f_i)^2 \left(\frac{1}{n_i} + \frac{1}{r_i}\right).$$

Hence, for all $t \ge 0$,

$$\sup_{s \in [0,t]} |y^n(s) - y^r(s)|^2 \leq f_1^2 \left(\frac{1}{n_1} + \frac{1}{r_1}\right) t + f_2^2 \left(\frac{1}{n_2} + \frac{1}{r_2}\right) t.$$

This means that for all $\varepsilon > 0$ there exists $N_{\varepsilon} \ge \frac{2(f_1^2 + f_2^2)t}{\varepsilon^2}$ such that for all $r_1, r_2, n_1, n_2 \ge N_{\varepsilon}$,

$$\sup_{s \in [0,t]} |y^n(s) - y^r(s)|^2 \le \varepsilon^2,$$

meaning that $\{y^n | n_1, n_2 \in \mathbb{N}^*\}$ satisfies the Cauchy property. It follows that y^n converges uniformly over compact sets to $y \in C^0$ as n tends to ∞ , concluding the proof of (i).

Proof of (ii). Fix $t \ge 0$. For all $n \in \mathbb{N}^{*2}$, by definition of φ'_{1,n_1} and φ'_{2,n_1} , the absolute values of the integrands of k_1^n and k_2^n are bounded by f_1 and f_2 respectively. Hence $(\varphi'_{1,n_1}(y^n))_n$ and $(\varphi'_{2,n_1}(y^n + \dot{\ell}))_n$ are two sequences bounded in $L^2([0,t])$ by f_1^2t and f_2^2t respectively, uniformly in n. It follows that $(\varphi'_{1,n_1}(y^n))_n$ and $(\varphi'_{2,n_1}(y^n + \dot{\ell}))_n$ converge weakly up to extraction to $\delta_1, \delta_2 \in L^2([0,t])$. We may take the same extraction for both sequences by extracting first for one, then for the other. Since δ_1 and δ_2 are in L^2 , the functions defined by $k_1(t) := \int_0^t \delta_1(s) \, ds$ and $k_2(t) := \int_0^t \delta_2(s) \, ds$ are continuous.

Proof of (iii). For all n, equation (2) is satisfied. For any test function $\phi \in L^2$, up to extraction,

$$\int_0^t \varphi_{1,n_1}'(y^n(s))\phi(s)\mathrm{d}s + \int_0^t \varphi_{2,n_2}'(y^n(s) + \dot{\ell}(s))\phi(s)\mathrm{d}s \xrightarrow[n \to \infty]{} \int_0^t \delta_1(s)\phi(s) \,\mathrm{d}s + \int_0^t \delta_2(s)\phi(s) \,\mathrm{d}s.$$

So $\phi \equiv 1$ yields, up to extraction, $\int_0^t \varphi'_{1,n_1}(y^n(s)) ds + \int_0^t \varphi'_{2,n_2}(y^n(s) + \dot{\ell}(s)) ds \rightarrow k_1(t) + k_2(t)$. Since y^n converges uniformly in C^0 , it follows that the equality (2) passes to the limit in n up to extraction, and we recover, for all $t \ge 0$, $My(t) + k_1(t) + k_2(t) = -m_2\dot{\ell}(t)$, concluding the proof of Proposition 1.

2.3 Identification of the limit as a system of variational inequalities

Proposition 2. Let $t \ge 0$. The functions y, k_1, k_2 from Proposition 1 satisfy the last two lines of system (S_2) over [0, t].

Proof. Let $n \in (\mathbb{N}^*)^2$. We first prove that the fourth line of system (\mathcal{S}_2) is satisfied by working on φ_1 . It is known, see 4. page 550 in [13], that for all $\xi \in \mathbb{R}$, for $J_{1,n_1}(\xi) \triangleq \xi - \frac{1}{n_1} \varphi'_{1,n_1}(\xi)$.

(4)
$$\varphi_{1,n_1}'(\xi) \in \partial \varphi_1(J_{1,n_1}(\xi)).$$

Writing out the inclusion (4) at $\xi = y^n(r)$ for some $r \in [0, t]$, we recover, for any $v \in \mathbb{R}$,

$$\varphi_{1,n_1}(y^n(r))[v - J_{1,n_1}(y^n(r))] + \varphi_1(J_{1,n_1}(y^n(r))) \le \varphi_1(v).$$

Furthermore, if v is a continuous function on [s, t], we can integrate the equation above over [s, t]:

(5)
$$\int_{s}^{t} \varphi_{1,n_{1}}(y^{n}(r))[v(r) - J_{1,n_{1}}(y^{n}(r))] \, \mathrm{d}r + \int_{s}^{t} \varphi_{1}(J_{1,n_{1}}(y^{n}(r))) \, \mathrm{d}r \leqslant (t-s) \int_{s}^{t} \varphi_{1}(v(r)) \mathrm{d}r.$$

To pass to the limit as $n \to \infty$, we rewrite the first term on the left-hand side

$$\int_{s}^{t} \varphi_{1,n_{1}}(y^{n}(r))[v - J_{1,n_{1}}(y^{n}(r))] \, \mathrm{d}r = \int_{s}^{t} \varphi_{1,n_{1}}(y^{n}(r))[v - y(r)] \, \mathrm{d}r + \int_{s}^{t} \varphi_{1,n_{1}}(y^{n}(r))[y(r) - J_{1,n_{1}}(y^{n}(r))] \, \mathrm{d}r.$$

Since y^n converges uniformly to $y \in C^0$, φ_{1,n_1} is bounded over compact sets, and $J_{1,n_1}(y^n)$ converges uniformly over compact sets to y, it follows that the second right-hand side term tends to 0, and the first converges to

$$\int_{s}^{t} \left[v(r) - y(r) \right] \mathrm{d}k_{1}(r),$$

by definition of k_1 . Since φ_1 is continuous and $J_{1,n_1}(y^n)$ converges uniformly over compact sets to y, we have, for all $r \in [s, t]$,

$$\varphi_1(y(r)) \leq \lim_{n \to \infty} \inf \varphi_1(J_{1,n_1}(y^n(r))).$$

Integrating over [s, t] and applying Fatou's lemma – since $\varphi \ge 0$ – yields

$$\int_{s}^{t} \varphi_{1}(y(r)) \, \mathrm{d}r \leqslant \int_{s}^{t} \lim_{n \to \infty} \inf \varphi_{1}(J_{1,n_{1}}(y^{n}(r))) \, \mathrm{d}r \leqslant \lim_{n \to \infty} \inf \int_{s}^{t} \varphi_{1}(J_{1,n_{1}}(y^{n}(r))) \, \mathrm{d}r.$$

Taking the limit inferior of equation (5) and considering the bounds above gives us the fourth line of system (S_2), and an analogous reasoning on φ_2 allows us to recover the fifth line.

2.4 Uniqueness of the solution

Assume two triples of functions (y, k_1, k_2) and $(\tilde{y}, \tilde{k_1}, \tilde{k_2})$ satisfy (S_2) . Then all six functions are continuous, and also \mathcal{BV}_{loc} thanks to the third line of the system, hence differentiable almost everywhere. Let $0 = s \leq t \in \mathbb{R}$. We can take the variational test function \mathfrak{z} equal to \tilde{y} in $(S_2).(iv)$ for y and get

$$\int_0^t [\tilde{y}(r) - y(r)] \mathrm{d}k_1(r) + \int_0^t \varphi_1(y(r)) \mathrm{d}r \leqslant \int_0^t \varphi_1(\tilde{y}(r)) \mathrm{d}r$$

Conversely, injecting $\mathfrak{z} = y$ in in $(\mathcal{S}_2).(iv)$ for \tilde{y} ,

$$\int_0^t [y(r) - \tilde{y}(r)] \mathrm{d}\tilde{k_1}(r) + \int_0^t \varphi_1(\tilde{y}(r)) \mathrm{d}r \leqslant \int_0^t \varphi_1(y(r)) \mathrm{d}r$$

By addition,

(6)
$$\int_0^t (\tilde{y} - y)(r)(k_1' - \tilde{k_1}')(r) \, \mathrm{d}r \leqslant 0$$

where the derivatives of k_1 and $\tilde{k_1}$ are defined weakly. Taking \mathfrak{z} equal to $\tilde{y} + \dot{\ell}$ or $y + \dot{\ell}$ in the fifth lines of (\mathcal{S}_2) applied to y and \tilde{y} respectively then summing like above, we get

(7)
$$\int_0^t (\tilde{y} - y)(r)(k_2' - \tilde{k_2}')(r) \, \mathrm{d}r \leqslant 0.$$

Expressing $\tilde{y} - y$ from $(S_2).(iii)$ gives us $\tilde{y} - y = \frac{1}{M} \left[(k_1 + k_2) - (\tilde{k_1} + \tilde{k_2}) \right]$, which we inject into the sum of (6) and (7). Since M > 0, we get

$$\int_{0}^{t} \left[(k_1 + k_2) - (\tilde{k_1} + \tilde{k_2}) \right] (r) \left[(k_1 + k_2) - (\tilde{k_1} + \tilde{k_2}) \right]' (r) \, \mathrm{d}r \leqslant 0,$$

hence $\left[k_1(t) + k_2(t) - \tilde{k_1}(t) - \tilde{k_2}(t)\right]^2 \leq 0$, since the expression above vanishes at t = 0 thanks to $(\mathcal{S}_2).(iii)$. It follows that $k_1 + k_2 = \tilde{k_1} + \tilde{k_2}$ at every time, so $\tilde{y} = y$ thanks to $(\mathcal{S}_2).(iii)$. Hence, subtracting line 4 of (\mathcal{S}_2) for \tilde{y} from the same row for y gives us, for any $0 \leq s \leq t$ and any continuous function $\mathfrak{z} = y + v$,

$$\int_{s}^{t} v(r)(k_{1}'(r) - \tilde{k_{1}}'(r)) \, \mathrm{d}r \leq 0$$

equality resulting from taking -v instead of v. And since $k_1(0) = \tilde{k_1}(0)$, we have $k_1 = \tilde{k_1}$, hence $k_2 = \tilde{k_2}$.

Acknowledgement

L.M. is thankful for support through NSFC Grant No. 12271364 and GRF Grant No. 11302823.

References

- [1] R McNeill Alexander. Principles of animal locomotion. Princeton University Press, 2003.
- [2] C Behn, F Schale, I Zeidis, K Zimmermann, and N Bolotnik. Dynamics and motion control of a chain of particles on a rough surface. <u>Mechanical Systems and Signal Processing</u>, 89:3–13, 2017.
- [3] N Bolotnik, P Schorr, I Zeidis, and K Zimmermann. Periodic locomotion of a two-body crawling system along a straight line on a rough inclined plane. <u>ZAMM-Journal of Applied Mathematics and</u> Mechanics/Zeitschrift f
 ür Angewandte Mathematik und Mechanik, 98(11):1930–1946, 2018.
- [4] H. Brézis. Opérateurs maximaux monotones et semi-groupes de contractions dans les espaces de Hilbert. North-Holland Mathematics Studies, No. 5. North-Holland Publishing Co., Amsterdam-London; American Elsevier Publishing Co., Inc., New York, 1973.
- [5] Tatiana Figurina. Quasi-static motion of a two-link system along a horizontal plane. <u>Multibody System</u> Dynamics, 11:251–272, 2004.
- [6] Paolo Gidoni. Rate-independent soft crawlers. <u>The Quarterly Journal of Mechanics and Applied</u> Mathematics, 71(4):369–409, 2018.
- [7] Paolo Gidoni and Antonio DeSimone. Stasis domains and slip surfaces in the locomotion of a bio-inspired two-segment crawler. Meccanica, 52(3):587–601, 2017.
- [8] Paolo Gidoni, Alessandro Margheri, and Carlota Rebelo. Limit cycles for dynamic crawling locomotors with periodic prescribed shape. <u>Zeitschrift für angewandte Mathematik und Physik</u>, 74(2), February 2023.
- [9] Paolo Gidoni and Filippo Riva. A vanishing-inertia analysis for finite-dimensional rate-independent systems with nonautonomous dissipation and an application to soft crawlers. <u>Calc. Var. Partial Differential</u> Equations, 60(5):Paper No. 191, 54, 2021.
- [10] Shigeo Hirose. <u>Biologically Inspired Robots: Snake-like Locomotors and Manipulators</u>. Oxford science publications. Oxford University Press, 1993.

- [11] Hamidreza Marvi, Gregory Meyers, Geoffrey Russell, and David L Hu. Scalybot: a snake-inspired robot with active control of friction. In <u>Dynamic Systems and Control Conference</u>, volume 54761, pages 443–450, 2011.
- [12] Jean Jacques Moreau. Application of convex analysis to some problems of dry friction. In <u>Trends in</u> applications of pure mathematics to mechanics, pages 263–280. Pitman, 1977.
- [13] Etienne Pardoux and Aurel Râșcanu. <u>Stochastic differential equations</u>, Backward SDEs, Partial differential equations, volume 69. Springer, 2014.
- [14] Valentin L. Popov. Contact Mechanics and Friction. Springer Berlin Heidelberg, 2010.
- [15] Paolo Serafini, Elisabeth Guazzelli, Bernhard Schrefler, Friedrich Pfeiffer, Franz G Rammerstorfer, Yoji Umetani, and Sigeo Hirose. Biomechanical study of serpentine locomotion. <u>On Theory and Practice of</u> <u>Robots and Manipulators: Volume I, pages 171–184, 1974.</u>
- [16] Aksel Andreas Transeth, Kristin Ytterstad Pettersen, and Pal Liljeback. A survey on snake robot modeling and locomotion. <u>Robotica</u>, 27(7):999–1015, 2009.
- [17] Gregory L. Wagner and Eric Lauga. Crawling scallop: Friction-based locomotion with one degree of freedom. Journal of Theoretical Biology, 324:42–51, 2013.