


# An Earth Rover dataset recorded at the ICRA@40 party

Qi Zhang

Zhihao Lin

Arnoud Visser 

**Abstract**—The ICRA conference is celebrating its 40<sup>th</sup> anniversary in Rotterdam in September 2024, with as highlight the Happy Birthday ICRA Party at the iconic Holland America Line Cruise Terminal. One month later the IROS conference will take place, which will include the Earth Rover Challenge. In this challenge open-world autonomous navigation models are studied truly open-world settings.

As part of the Earth Rover Challenge several real-world navigation sets in several cities world-wide, like Auckland, Australia and Wuhan, China. The only dataset recorded in the Netherlands is the small village Oudewater. The proposal is to record a dataset with the robot used in the Earth Rover Challenge in Rotterdam, in front of the Holland America Line Cruise Terminal, before the festivities of the Happy Birthday ICRA Party start.

## I. INTRODUCTION

Recent developments in visual SLAM have shown that it is possible to generate detailed reconstructions of the surroundings (e.g. [1] and [2]), although those reconstructions require depth-cameras. Creating navigation maps from a single front camera is more challenging, with the first successful attempt called MonoSLAM [3], followed by several more advanced methods like LDSO, ORB-SLAM, Droid-slam and Sni-slam [4], [5], [6], [7]. Some more advanced approaches, which integrate multi-view information and use neural networks to replace depth sensors for depth estimation [8], [9], applying more constraints with additional features such as lines or planes [10], [11], or extracting more general features [12], [13], have shown promising prospects for real-time monocular SLAM methods.

The robot used for this challenge is the Earth Rover Zero from FrodoBot<sup>1</sup> (see Fig. 1). It is a small four-wheel drive robot, with a camera at the front and rear. The front camera has a resolution of resolution of 1024x576, and the rear camera's resolution is 540x360. In addition, the FrodoBot has an IMU, GPS and 4G SIM card onboard. The 4G SIM card provides a wireless interface, which allows teams all over the world to drive the robot around.

Part of the challenge is creating a real-world dataset ( $> 2k$  hours), collected in several cities. Such large datasets are the way forward, as demonstrated with foundations models for robotics [14].

Such a dataset could be used in two ways. One solution would be to use it to train the robot to navigate with an end-to-end algorithm [15], [16], as demonstrated recently in the OpenDriveLab challenge by the team of Nvidia [17]. Yet, in that challenge, six high-resolution cameras provided a surround view, while the Earth Rover has to rely mostly on its front camera.



Fig. 1. The FrodoBot Earth Rover Zero.

The front camera can also be used for situation awareness, by perceiving the features that provide information for safe navigation. For safety, it is for instance important that pedestrians, bicycles and other traffic are detected [18]. For a first demonstration, a robust object-detection model such as YoloV8 would be a good choice [19]. Rich semantic priors can eliminate the interference of dynamic objects in pose estimation [20], [21]. In contrast, richer semantic methods, instance segmentation, multi-object tracking or more complex networks, further combine the estimation of the poses of dynamic objects and the robot itself [22], [23], [24]. In addition, the front camera can be used for visual odometry, to get an estimate of the Earth Rover's movement, independent from the IMU estimates [25]. We can also integrate IMU and visual information to achieve more robust tracking and reconstruction [26], [27].

The next level would be to create a visual map of the surroundings, in this case, the Holland America Line Cruise Terminal (see Fig. 2). The ORB-SLAM algorithm [5] would be a good choice for a first demonstration<sup>2</sup>, which can be extended in a later stage with more advanced methods [7].

Once a visual map is generated, it can be combined with satellite maps and street maps to Scene Action Maps [28]. The behavior learned to navigate on the Scene Action Maps, can be ported to other robots with cross-embodiment approaches [29], [30].

We have many interesting ideas how to extend the autonomous driving capabilities of the robot, but also realize that well ahead of the Earth Rover Challenge only the basic navigational and safety functionality will be active. For instance, dynamic-obstacle avoidance is hard, but it demonstrating this in a real-world setting will give insight in the strength and weaknesses. With human supervision this

<sup>1</sup><https://www.frodobots.ai/>

<sup>2</sup><https://github.com/SlamMate/vSLAM-on-FrodoBots-2K>



Fig. 2. Holland America Line Cruise Terminal in Rotterdam.

will be enough to record an interesting dataset.

## II. CONCLUSION

This paper outlines plans to record a new dataset for the Earth Rover Challenge at ICRA@40 in Rotterdam using the Earth Rover Zero robot. The dataset will enrich the current collection<sup>3</sup> further which will allow to train SLAM and navigation algorithms on data collected in the real world. This recording will be unique due to the public (the visitors of the Happy Birthday ICRA Party) and the waterfront nearby. As a bonus, it will be fun for the ICRA participants to see a live dataset recording in action during their party.

## REFERENCES

- [1] L. Liso, E. Sandström, V. Yugay, L. Van Gool, and M. R. Oswald, "Loopy-slam: Dense neural slam with loop closures," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, Feb. 2024, pp. 20 363–20 373.
- [2] V. Yugay, Y. Li, T. Gevers, and M. R. Oswald, "Gaussian-slam: Photo-realistic dense slam with gaussian splatting," preprint arXiv:2312.10070, Mar 2024.
- [3] A. J. Davison, I. D. Reid, N. D. Molton, and O. Stasse, "Monoslam: Real-time single camera slam," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 29, no. 6, pp. 1052–1067, 2007.
- [4] X. Gao, R. Wang, N. Demmel, and D. Cremers, "Ldso: Direct sparse odometry with loop closure," in *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2018, pp. 2198–2204.
- [5] C. Campos, R. Elvira, J. J. G. Rodríguez, J. M. Montiel, and J. D. Tardós, "Orb-slam3: An accurate open-source library for visual, visual-inertial, and multimap slam," *IEEE Transactions on Robotics*, vol. 37, no. 6, pp. 1874–1890, 2021.
- [6] Z. Teed and J. Deng, "Droid-slam: Deep visual slam for monocular, stereo, and rgb-d cameras," *Advances in neural information processing systems*, vol. 34, pp. 16 558–16 569, 2021.
- [7] S. Zhu, G. Wang, H. Blum, J. Liu, L. Song, M. Pollefeys, and H. Wang, "Sni-slam: Semantic neural implicit slam," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024, pp. 21 167–21 177.
- [8] G. Zhang, E. Sandström, Y. Zhang, M. Patel, L. V. Gool, and M. R. Oswald, "Glorie-slam: Globally optimized rgb-only implicit encoding point cloud slam," 2024. [Online]. Available: <https://arxiv.org/abs/2403.19549>
- [9] E. Sandström, K. Tateno, M. Oechsle, M. Niemeyer, L. V. Gool, M. R. Oswald, and F. Tombari, "Splat-slam: Globally optimized rgb-only slam with 3d gaussians," 2024. [Online]. Available: <https://arxiv.org/abs/2405.16544>
- [10] A. Pumarola, A. Vakhitov, A. Agudo, A. Sanfeliu, and F. Moreno-Noguer, "Pl-slam: Real-time monocular visual slam with points and lines," in *2017 IEEE International Conference on Robotics and Automation (ICRA)*, 2017, pp. 4503–4508.
- [11] W. Zhao, H. Sun, X. Zhang, and Y. Xiong, "Visual slam combining lines and structural regularities: Towards robust localization," *IEEE Transactions on Intelligent Vehicles*, pp. 1–18, 2023.
- [12] L. Liu and J. M. Aitken, "Hfnet-slam: An accurate and real-time monocular slam system with deep features," *Sensors*, vol. 23, no. 4, 2023. [Online]. Available: <https://www.mdpi.com/1424-8220/23/4/2113>
- [13] H. M. S. Bruno and E. L. Colombini, "Lift-slam: A deep-learning feature-based monocular visual slam method," *Neurocomputing*, vol. 455, pp. 97–110, 2021.
- [14] A. Padalkar, A. Pooley, A. Jain, A. Bewley, A. Herzog, A. Irpan, A. Khazatsky, A. Rai, A. Singh, A. Brohan, et al., "Open x-embodiment: Robotic learning datasets and rt-x models," preprint arXiv:2310.08864, 2023.
- [15] X. Zhou, Z. Wang, H. Ye, C. Xu, and F. Gao, "Ego-planner: An esdf-free gradient-based local planner for quadrotors," *IEEE Robotics and Automation Letters*, vol. 6, no. 2, pp. 478–485, 2021.
- [16] F. Yang, C. Cao, H. Zhu, J. Oh, and J. Zhang, "Far planner: Fast, attemptable route planner using dynamic visibility update," in *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2022, pp. 9–16.
- [17] Z. Li, K. Li, S. Wang, S. Lan, Z. Yu, Y. Ji, Z. Li, Z. Zhu, J. Kautz, Z. Wu, Y.-G. Jiang, and J. M. Alvarez, "Hydra-mdp: End-to-end multimodal planning with multi-target hydra-distillation," 2024.
- [18] J. Cao, Y. Pang, J. Xie, F. S. Khan, and L. Shao, "From handcrafted to deep features for pedestrian detection: A survey," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 44, no. 9, pp. 4913–4934, 2022.
- [19] D. Kumar and N. Muhammad, "Object detection in adverse weather for autonomous driving through data merging and yolov8," *Sensors*, vol. 23, no. 20, p. 8471, 2023.
- [20] Z. Lin, Q. Zhang, Z. Tian, P. Yu, and J. Lan, "Dpl-slam: Enhancing dynamic point-line slam through dense semantic methods," *IEEE Sensors Journal*, vol. 24, no. 9, pp. 14 596–14 607, 2024.
- [21] X. Hu, Y. Zhang, Z. Cao, R. Ma, Y. Wu, Z. Deng, and W. Sun, "Cfp-slam: A real-time visual slam based on coarse-to-fine probability in dynamic environments," in *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2022, pp. 4399–4406.
- [22] B. Bescós, C. Campos, J. D. Tardós, and J. Neira, "Dynaslam ii: Tightly-coupled multi-object tracking and slam," *IEEE Robotics and Automation Letters*, vol. 6, pp. 5191–5198, 2020.
- [23] H. Zhang, H. Uchiyama, S. Ono, and H. Kawasaki, "Motslam: Mot-assisted monocular dynamic slam using single-view depth estimation," in *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2022, pp. 4865–4872.
- [24] W. Ye, X. Lan, S. Chen, Y. Ming, X. Yu, H. Bao, Z. Cui, and G. Zhang, "Pvo: Panoptic visual odometry," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2023, pp. 9579–9589.
- [25] L. Kneip, M. Chli, and R. Siegwart, "Robust real-time visual odometry with a single camera and an imu," in *Proceedings of the British Machine Vision Conference 2011*. British Machine Vision Association, 2011.
- [26] A. Azimi, A. Hosseinaveh Ahmadabadian, and F. Remondino, "Pks: A photogrammetric key-frame selection method for visual-inertial systems built on orb-slam3," *ISPRS Journal of Photogrammetry and Remote Sensing*, vol. 191, pp. 18–32, 2022.
- [27] Y. Ren, B. Xu, C. L. Choi, and S. Leutenegger, "Visual-inertial multi-instance dynamic slam with object-level relocalisation," in *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2022, pp. 11 055–11 062.
- [28] J. Loo and D. Hsu, "Scene action maps: Behavioural maps for navigation without metric information," preprint arXiv:2405.07948, May 2024.
- [29] J. Yang, C. Glossop, A. Bhorkar, D. Shah, Q. Vuong, C. Finn, D. Sadigh, and S. Levine, "Pushing the limits of cross-embodiment learning for manipulation and navigation," preprint arXiv:2402.19432, Feb. 2024.
- [30] A. Loquercio, E. Kaufmann, R. Ranftl, M. Müller, V. Koltun, and D. Scaramuzza, "Learning high-speed flight in the wild," *Science Robotics*, vol. 6, no. 59, 2021.

<sup>3</sup><https://huggingface.co/datasets/frodobots/FrodoBots-2K>