MATTEO BELENCHIA, FLAVIO CORRADINI, MICHELA QUADRINI, and MICHELE LORETI, Uni-

versity of Camerino, Italy

Graph neural networks form a class of deep learning architectures specifically designed to work with graph-structured data. As such, they share the inherent limitations and problems of deep learning, especially regarding the issues of explainability and trustworthiness. We propose $\mu \mathcal{G}$, an original domain-specific language for the specification of graph neural networks that aims to overcome these issues. The language's syntax is introduced, and its meaning is rigorously defined by a denotational semantics. An equivalent characterization in the form of an operational semantics is also provided and, together with a type system, is used to prove the type soundness of $\mu \mathcal{G}$. We show how $\mu \mathcal{G}$ programs can be represented in a more user-friendly graphical visualization, and provide examples of its generality by showing how it can be used to define some of the most popular graph neural network models, or to develop any custom graph processing application.

CCS Concepts: • Computing methodologies \rightarrow Neural networks; Parallel programming languages; • Mathematics of computing \rightarrow Graph theory; • Theory of computation \rightarrow Program semantics; Type theory; • Software and its engineering \rightarrow Formal methods; Formal language definitions.

Additional Key Words and Phrases: Graph Neural Networks, Domain-Specific Language, Graph Deep Learning

ACM Reference Format:

Matteo Belenchia, Flavio Corradini, Michela Quadrini, and Michele Loreti. 2018. The μG Language for Programming Graph Neural Networks. J. ACM 37, 4, Article 111 (August 2018), 32 pages. https://doi.org/XXXXXXXXXXXXXXXXX

1 INTRODUCTION

Deep learning models are at the forefront of artificial intelligence research today. Among them, artificial neural networks are the most commonly used class of models for a wide range of different tasks, including natural language processing, computer vision, software engineering, and many more [29]. For applications where the inputs can be represented as graphs, the graph neural network [10] (GNN) model has been the architecture of choice, and has achieved state-of-the-art performance on many tasks.

Despite these promising advancements, deep learning models, including graph neural networks, face a number of issues. These systems are difficult to engineer with, and are notoriously harder to debug and interpret compared to traditional software systems [23]. Another issue is the lack of guarantees that these systems offer regarding their outputs, which time and again have been shown to be easily foolable, not only using so-called "adversarial examples" [17], but also more generally in unpredictable and surprising ways [3, 12]. Furthermore, these systems act like a black-box and are opaque, in the sense that human users are unable to understand how they have reached their conclusions [4].

Authors' address: Matteo Belenchia, matteo.belenchia@unicam.it; Flavio Corradini, flavio.corradini@unicam.it; Michela Quadrini, michela.quadrini@ unicam.it; Michele Loreti, michele.loreti@unicam.it, University of Camerino, Via Andrea D'Accorso 16, Camerino, Macerata, Italy, 62032.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org. © 2018 Copyright held by the owner/author(s). Publication rights licensed to ACM.

Finally, there is a very strong bias in deep learning research against the usage of prior knowledge even when such usage is warranted, and even then, it is difficult to figure out how to integrate such knowledge in these systems [24].

In this paper, we tackle all these issues by proposing a new graph neural network specification language, called μG (pronounced as "mee-gee"). A graph neural network in μG is built up as a composition of simpler GNNs following the formal rules of the language. These GNNs are built up from the base terms, specifying functions to be applied to the single nodes in terms of themselves and/or their neighbors, which can then be composed sequentially, in parallel, selected according to a Boolean condition, or iterated.

The language's syntax is introduced using a context-free grammar, and the meaning of each term is formally and rigorously defined by a denotational semantics. Later on, we also introduce a structural operational semantics, and prove that both semantics are equivalent, i.e., they define the same graph neural network operations. Using the operational semantics and after having defined a type system for μG , we prove the type soundness of the language. The type soundness of μG guarantees that every well-typed μG program properly defines a GNN with the correct output type.

The language can be used both in textual form and in graphical form. The graphical representation of μG programs is introduced as a more user-friendly approach to use the language, as it keeps the flow of information and the type of labels easier to follow and reason about.

Our language is framework and hardware-agnostic, as μG could be implemented in different ways. We opted to implement μG in TensorFlow so that it can use its automatic differentiation capabilities and allow the GNNs we program to be executable on CPUs, GPUs, or TPUs without changing their implementation. Furthermore, these GNNs can interoperate with any other TensorFlow feature as if they were TensorFlow models themselves.

We claim that $\mu \mathcal{G}$ helps with the aforementioned problems of deep learning. For the matter of explainability and interpretability, using $\mu \mathcal{G}$ helps by making the computations performed more explicit, by taking the form of a $\mu \mathcal{G}$ expression which has clearly definite semantics and types. Indeed, the user might even define functions and computations using the same terminology of the specific domain in which the GNN is going to be used in, making the purpose of each term easier to understand. Some, or all, parts of the GNN can be defined to be inherently interpretable, by virtue of being defined explicitly based on the available domain knowledge. Furthermore, determining the nodes, edges, or labels that contributed to a specific prediction becomes amenable to static analysis techniques [7].

As for the issues of trustworthiness, the use of a formal language like μG allows the formal verification of GNNs similarly to that of other programming languages, e.g., by abstract interpretation, symbolic execution, data-flow analysis, and so on. In particular, we are interested in the problem of formally verifying safety properties of GNNs, e.g. output reachability properties [18]. The verification of an output reachability property for a function f given an input region X and an output region Y consists in checking whether for all inputs $x \in X$, $f(x) \in Y$. As far as we know, no solution for this problem has been proposed for graph neural networks specifically [33]. The verification of properties of this kind can be used to prove the robustness of a GNN against adversarial examples, which is critical when such models are deployed in safety-critical systems, where guarantees of correct functioning are paramount.

Finally, it is easy to include prior knowledge when defining a GNN in μG . The basic terms of the language need not make use of neural network layers as is typically the case for the more popular graph neural network models, but can in general use any kind of function, not necessarily depending on trainable parameters. This way is also possible to define a GNN which does not require training at all, as we did in a previous work where we used μG for model checking [6]. Prior, or innate, knowledge can be freely mixed with optimizable function in order to build hybrid, neural-symbolic systems [22, 25, 32].

Contributions. Our main contributions are:

- We define the syntax μG language, and provide its denotational and operational semantics.
- We prove the equivalence of the denotational and operational semantics of μG .
- We define the typing rules of μG and prove its type soundness.
- We show how μG programs can be represented graphically.
- We demonstrate how to use μG to program some of the most popular graph neural network models.

Structure of the paper. We survey the related work in Section 2, while we introduce the necessary notation and preliminary information in Section 3 and 4. Then the μG language is described in detail in Section 5 by showing its syntax and semantics. A proof of equivalence of the denotational and operational semantics of μG is in Section 6, followed by a proof of type soundness in Section 7. The graphical representation of μG programs is introduced in Section 8. A brief discussion on the implementation of μG is in Section 9. Finally, we evaluate μG by showing its application in CTL model checking and its usage to define some graph neural network models in Section 10, and delineate the future direction of our work in the conclusions.

2 RELATED WORK

Many domain specific languages (DSL) have been developed over the years to ease the development of machine learning applications [28]. Far from being a complete survey, we will discuss here only the most recent ones or those that are most relevant for our work.

DeepDSL [37] is a language based on Scala that allows the definition of neural networks through variable assignments. Variables can be assigned computational modules such as convolutional layers, pooling layers, activation functions and so on. Neural networks are defined by variable assignments where the right-hand side is the function composition of other computational modules. The code is compiled to Java and uses JCuda to communicate with CUDA and cuDNN. AiDSL [13] is a language for the specification of supervised feed-forward neural networks using a model driven engineering approach. The code is compiled into Encog, a machine learning framework in Java. SEMKIS-DSL [19] is another language developed using a model driven engineering approach, where the main focus is shifted from the specification of the neural network architecture to the requirements that the input dataset and the neural network's outputs must satisfy. For the time being there are no compilation targets for the language, so it is not possible to automatically produce a neural network from specification. On the other hand, Diesel [11] acts at a finer level of detail, allowing the specification of common linear algebra and neural network computations that are typically implemented by libraries such as cuBLAS and cuDNN. It uses a polyhedral model to schedule operations and perform optimizations, and the source code is compiled directly into CUDA code. So far, none of these languages take into consideration the definition of graph-structured inputs or the typical operations that characterize graph neural networks.

A DSL where graphs are first-class objects is OptiML [31], which supports the specification of machine learning models to be run on heterogenous hardware (i.e. the CPU or GPU). The language can be used to implement any machine learning model that can be expressed using the Statistical Query Model [20], and the code can be compiled to Scala, C++, or CUDA code. Graph objects in OptiML support operations expressed in terms of vertices and edges, and graph operations are specified in terms of vertices and their neighbours in the graph. Furthermore, OptiML has a fixed point operator with a customizable threshold value just like μG . Another DSL that supports graphs is StreamBrain [27], which is a language for the specification of Bayesian Confidence Propagation Neural Networks. This model takes in input a graph where every node is a random variable and edges represent the dependencies between variables. StreamBrain Manuscript submitted to ACM

has a Python interface and its syntax is similar to that of Keras, where the model is seen as a stack of layers, and it can compile to OpenMP, OpenCL, and CUDA. Streambrain is based on NumPy and supports CPUs, GPUs and FPGAs.

Despite the native support for graphs, neither OptiML nor StreamBrain fully support the graph neural network model, with the first being limited to statistical inference problems, and the latter to a specific kind of neural architecture and graph labeling. Therefore, we can conclude that, at the time of writing, no domain specific language has been developed specifically for graph neural network models and tasks.

3 BACKGROUND AND NOTATION

Graphs and their labelings. A directed graph is a pair $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ where \mathcal{V} is a collection of vertices (which we also refer to as nodes) and \mathcal{E} is a collection of ordered pairs of vertices, called *edges*. For any $u, v \in \mathcal{V}$, whenever $(u, v) \in \mathcal{E}$ we say that u is a predecessor of v and that v is a successor of u. We also say that (u, v) is an incoming edge for v and an outgoing edge for u. Moreover, let $\widetilde{N}_{\mathcal{G}}(v)$ denote the set of predecessors of v, formally $\widetilde{N}_{\mathcal{G}}(v) = \{u \mid (u, v) \in \mathcal{E}\}$, while $\overrightarrow{N}_{\mathcal{G}}(u)$ denotes the set of successors of u, namely $\overrightarrow{N}_{\mathcal{G}}(u) = \{v \mid (u, v) \in \mathcal{E}\}$. Similarly, let $I_{\mathcal{G}}(v)$ denote the set of incoming edges for v, formally $I_{\mathcal{G}}(v) = \{(u, v) \mid u, v \in \mathcal{V}\}$, and let $O_{\mathcal{G}}(u)$ denote the set of outgoing edges for u, formally $O_{\mathcal{G}}(u) = \{(u, v) \mid u, v \in \mathcal{V}\}$.

Sometimes it is useful to associate nodes and edges with values. Given a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, we can consider its *node-labeling* and *edge-labeling*. The former is a function $\eta : \mathcal{V} \to T_{\mathcal{V}}$ associating each node $v \in \mathcal{V}$ with a value in the set $T_{\mathcal{V}}$. Similarly, an *edge-labeling* is a function $\xi : \mathcal{E} \to T_{\mathcal{E}}$ that maps an edge to its label in the set $T_{\mathcal{E}}$. Let $V \subseteq \mathcal{V}$ (resp. $E \subseteq \mathcal{E}$), we let $\eta(V)$ (resp. $\xi(E)$) denote the *multi-set* of labels associated to the elements of V (resp. E) by η (resp. ξ). Likewise, we let $(\eta, \xi)(E)$ denote the *multi-set* of tuples $(\eta(u), \xi((u, v)), \eta(v))$ for each $(u, v) \in E$.

Encoding of graphs and labels. One way to represent graphs and their labeling functions on a computer is in the form of a matrix of node features **X**, an adjacency matrix **A** and a matrix of edge features **E**. The node features matrix **X** stores the features associated with each node in the graph. The *i*-th row of the matrix contains a value $x_i \in T_V$ that represents the information associated with the *i*-th vertex of the graph in a given ordering. The adjacency matrix **A** encodes the architecture of the graph, with each non-zero element $a_{ij} \in \mathbb{R}$ denoting the presence of an edge from a node *i* to a node *j*. The edge features matrix **E** stores the features associated with each edge, like the node features matrix. The *i*-th row of **E** is a value $e_i \in T_E$ that represents the information associated with the *i*-th edge in the row-major (or any other) ordering of the edges in **A**.

Graph Neural Networks. A graph neural network is a deep learning model that operates on graph-structured data. Introduced by Scarselli et al. [30], it emerged to overcome the limitations of graph kernel methods [26]. GNNs generalize many other classes of deep learning architectures, as other deep learning models can be seen as a particular case of graph neural networks [8]. Convolutional Neural Networks (CNNs), for example, can be seen as a graph neural networks where inputs can only be 1-dimensional sequences (such as texts) or 2-dimensional grids (such as images), which are both particular instances of graphs. Graph neural networks, more generally, can learn on any non-Euclidean structure representable as graphs, which contrary to grids such as images, can have differing shapes, number of nodes and connectivity properties.

Graph neural networks can be used for many tasks, which can be roughly categorized according to the subject of prediction: nodes, edges, or entire graphs. As with other machine learning models, there are two main kinds of tasks, namely classification and regression, where the goal is to predict the class or some numerical quantity associated with the nodes in the graph, edges, or the entire graph.

5

Over the years, many types of graph neural network variants have been developed [38]. Among these, we mention Graph Convolutional Networks [21], Graph Isomorphism Networks [36], and Graph Attention Networks [34]. Graph neural networks have been applied to the most disparate domains [38], spanning computer vision, natural language processing, particle physics, chemistry, combinatorial optimization, recommender systems, traffic forecasting and graph mining.

The most general form of graph neural network, which subsumes most of the GNN variants that have been developed over the years [8], is the message passing neural network [5, 14] (MPNN). A typical MPNN comprises a fixed number of convolutional layers stacked in sequence, each of them updating the labels of the nodes. A convolution operation computes the new node labels x'_i from the current node labels x_i according to the following equation:

$$x_i' = \psi\left(x_i, \sigma_{j \in N_G(i)}\varphi(x_j, e_{ji}, x_i)\right) \tag{1}$$

where $N_{\mathcal{G}}(i)$ is the set of neighbors of node *i*, σ is a permutation-invariant function and ψ , φ are (usually) optimizable functions. The function φ generates the message sent from node *j* to node *i*, which in the simplest case might simply be x_j . The function σ aggregates the multiset of messages obtained by φ in a way that is independent of the order they are evaluated and is usually a non-learnable function such as the sum, product or mean, but, more generally, it can also be defined as a neural network. The function ψ updates the label of node *i* by considering both the current label x_i and the value computed by σ .

Graph neural networks composed by layers described by Equation 1 are permutation-equivariant functions that take in input a graph \mathcal{G} , an edge-labeling ξ , and a node-labeling η to return a new node-labeling η' . This characterization leaves out some types of graph neural networks, namely, the graph neural networks that use pooling layers (which therefore change the architecture of the graph by removing elements from \mathcal{V} and \mathcal{E}) and the graph neural networks that learn edge features rather than node features (which therefore produce a new edge-labeling ξ' instead). At any rate, the standard graph neural network model we have just described is general enough to encompass these two special cases as well. A graph neural network that uses pooling layers can be represented by allowing the node-labeling function to label each node with an additional Boolean value that specifies whether the node has been deleted or not and by ruling that an edge is valid if and only if both the source and destination nodes have not been deleted. A graph neural network that learns edge features can instead be modeled by reifying edges into nodes and by having the graph's node-labeling function label each node with an additional Boolean value that specifies whether the node represents an edge or a node of the original graph.

4 THE DOMAIN OF GRAPH NEURAL NETWORKS

In this section, we introduce the necessary definitions and theorems that characterize graph neural networks in our work. We elaborate further on the notion of node-labeling function and formalize the graph neural network as a transformation between node-labeling functions, then move on to prove that the set of graph neural networks is a chain complete partially ordered set.

4.1 Node-labeling functions

We denote the set of all labeling functions with co-domain T as H[T], and we say that this set specifies its *type*. As examples, labeling functions of type $H[\mathbb{B}]$ map vertices to Boolean values, while functions of type $H[\mathbb{N}^k]$ with $k \in \mathbb{N}$ map vertices to k-tuples of natural numbers. Each type also includes a bottom node-labeling function $\perp_H = \lambda v$.undef Manuscript submitted to ACM

that is undefined for every node. Then $(H[T], \sqsubseteq_H)$ is a partially ordered set, where \perp_H is the bottom element and \sqsubseteq_H is the pointwise ordering relation such that, for all $v \in \mathcal{V}$

$$\eta_1 \sqsubseteq_H \eta_2 \iff \eta_1(v) = t \implies \eta_2(v) = t$$

We also consider the parallel composition of node-labeling functions η_1 and η_2 , and we denote it as $\eta_1|\eta_2$, to specify the node-labeling function $\lambda v.(\eta_1(v), \eta_2(v))$ that maps vertices to (possibly nested) pairs of node labels. The inverse operation is given by the projection functions $\pi_L, \pi_R : H[T \times T] \to H[T]$ such that

$$\pi_L(\eta_1|\eta_2) = \eta_1$$
$$\pi_R(\eta_1|\eta_2) = \eta_2$$

We call π_L the *left projection* and π_R the *right projection*. Adequate composition of these two projection functions can be used to obtain any nested node-labeling function.

4.2 Graph neural networks

Given a graph \mathcal{G} together with its edge-labeling function ξ , we define a graph neural network to be a function $\phi_{\mathcal{G},\xi} : H[T_1] \to H[T_2]$ that maps a node-labeling function to another node-labeling function. We denote the set of such graph neural networks as $\Phi_{\mathcal{G},\xi}[T_1, T_2]$ or, more succinctly, as $\Phi_{\mathcal{G},\xi}$. The subscript \mathcal{G}, ξ indicates that each graph neural network is parametrized by a graph and an edge-labeling function. Likewise for the node-labeling functions, the set of graph neural networks $\Phi_{\mathcal{G},\xi}[T_1, T_2]$ is a partially ordered set with a point-wise ordering relation $\sqsubseteq_{\Phi_{\mathcal{G},\xi}}[T_1, T_2]$ such that, for all $\eta \in H[T_1]$

$$\phi_1 \sqsubseteq_{\Phi_{G,\mathcal{E}}[T_1,T_2]} \phi_2 \iff \phi_1(\eta) = \eta' \implies \phi_2(\eta) = \eta'$$

When the types are clear from the context or not revelant, we drop the subscript and simply write $\Box_{\Phi_{G,F}}$.

Next, we define the underlying *relation* of a GNN as the set of input-output tuples which characterize the GNN. Building on this concept, we also specify their *sequential* and *parallel composition*.

Definition 4.1. Given a graph neural network $\phi : \Phi_{G,\xi}[T_1, T_2]$ we define its underlying *relation*, denoted by $rel(\phi)$, as

$$rel(\phi) = \{(\eta_1, \eta_2) \in H[T_1] \times H[T_2] \mid \phi(\eta_1) = \eta_2\}$$

The sequential composition, or simply composition, of relations $A : H[T_1] \times H[T_2]$ and $B : H[T_2] \times H[T_3]$, denoted by A * B, is defined as

$$A * B = \{ (\eta_1, \eta_3) \mid \exists \eta_2 \in H[T_2] : (\eta_1, \eta_2) \in A \land (\eta_2, \eta_3) \in B \}$$

The *parallel composition*, or *concatenation*, of relations $A : H[T_1] \times H[T_2]$ and $B : H[T_1] \times H[T_3]$, denoted by $A \frown B$, is defined as

$$A \frown B = \{ (\eta_1, (\eta_2, \eta_3)) \mid (\eta_1, \eta_2) \in A \land (\eta_1, \eta_3) \in B \}$$

The following lemma defines the relationship between the relations and the ordering of GNNs.

LEMMA 4.2. Given two GNNs ϕ_1, ϕ_2 we have

$$\phi_1 \sqsubseteq_{\Phi_{G,\mathcal{E}}} \phi_2 \iff rel(\phi_1) \subseteq rel(\phi_2)$$

PROOF. First we show that $\phi_1 \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_2 \implies rel(\phi_1) \subseteq rel(\phi_2)$. Since $\phi_1(\eta) = \eta' \implies \phi_2(\eta) = \eta'$, any $(\eta, \eta') \in rel(\phi_1)$ is also a member of $rel(\phi_2)$.

From the other direction, suppose that $rel(\phi_1) \subseteq rel(\phi_2)$. Since $(\eta, \eta') \in rel(\phi_1) \implies (\eta, \eta') \in rel(\phi_2)$, we have that $\forall (\eta, \eta') \in rel(\phi_1), \phi_1(\eta) = \eta' \implies \phi_2(\eta) = \eta'$.

As was the case for the node-labeling functions, we consider the parallel composition of graph neural networks $\phi_1 : \Phi_{\mathcal{G},\xi}[T, T_1]$ and $\phi_2 : \Phi_{\mathcal{G},\xi}[T, T_2]$, and we denote it as $\phi_1 \times \phi_2$, to define the graph neural network

$$\lambda e.\lambda v.(\phi_1(e)(v),\phi_2(e)(v))$$

with type $\Phi_{\mathcal{G},\xi}[T, T_1 \times T_2]$ that concatenates the node-labelings generated by ϕ_1 and ϕ_2 . Then the relationship between the parallel composition of labeling functions and the parallel composition of graph neural networks is highlighted by the equation:

$$\phi_1 \times \phi_2(\eta) = \phi_1(\eta) |\phi_2(\eta)|$$

Next, we prove that the set of graph neural networks of a given type $\Phi_{\mathcal{G},\xi}[T_1, T_2]$ with the ordering relation $\sqsubseteq_{\Phi_{\mathcal{G},\xi}}$ is a chain complete partially ordered set (ccpo).

THEOREM 4.3. The set of graph neural networks is a chain complete partially ordered set $(\Phi_{\mathcal{G},\xi}, \sqsubseteq_{\Phi_{\mathcal{G},\xi}})$, with least element $\bot_{\Phi_{\mathcal{G},\xi}} : H[T_1] \to H[T_2]$ defined by

$$\perp_{\Phi_{GF}}(\eta) = undef$$

PROOF. First we show that $\sqsubseteq_{\Phi_{\mathcal{G},\xi}}$ fulfils the requirements to a partial order. We have that $\phi \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi$ because $\phi(\eta) = \eta'$ implies $\phi(\eta) = \eta'$, therefore we satisfy the reflexivity requirement. Then to prove transitivity, we assume that $\phi_1 \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_2$ and $\phi_2 \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_3$ and show that $\phi_1 \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_3$. If $\phi_1(\eta) = \eta'$, we get that $\phi_2(\eta) = \eta'$ from $\phi_1 \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_2$. Then we also have $\phi_3(\eta) = \eta'$ from $\phi_2 \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_3$. Lastly, to prove that the ordering is anti-symmetric, we assume that $\phi_1 \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_2$ and $\phi_2 \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_1$ and we need to show that $\phi_1 = \phi_2$. If $\phi_1(\eta) = \eta'$, then by $\phi_1 \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_2$ we have that $\phi_2(\eta) = \eta'$. Likewise if $\phi_1(\eta)$ is undefined, then $\phi_2(\eta)$ must be undefined as well, otherwise $\phi_2(\eta) = \eta'$ and $\phi_2 \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_1$ are in contradiction. Therefore ϕ_1 and ϕ_2 are equal on any η .

To see that $(\Phi_{\mathcal{G},\xi}, \sqsubseteq_{\Phi_{\mathcal{G},\xi}})$ is a ccpo, we need to show that for all chains *Y*, the least upper bound $\bigsqcup Y$ exists. Let $rel(\bigsqcup Y) = \bigcup \{rel(\phi) \mid \phi \in Y\}$. We first show that $\bigcup \{rel(\phi) \mid \phi \in Y\}$ indeed specifies a graph neural network. That is, whenever (η, η') and (η, η'') are members of $X = \bigcup \{rel(\phi) \mid \phi \in Y\}$, then $\eta' = \eta''$. If $(\eta, \eta') \in X$, then there must be a $\phi \in Y$ such that $\phi(\eta) = \eta'$, and similarly for $(\eta, \eta'') \in X$, there must be a $\phi' \in Y$ such that $\phi'(\eta) = \eta''$. Since *Y* is a chain, then either $\phi \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi'$ or $\phi' \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi$. In any case, this means that $\phi(\eta) = \phi'(\eta)$ and $\eta' = \eta''$. Next we show that $\bigsqcup Y$ as we defined it is an upper bound of *Y*. Let ϕ be a member of *Y*. Clearly, $\phi \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \bigsqcup Y$, because $rel(\phi) \subseteq rel(\bigsqcup Y)$. Lastly, we prove that $\bigsqcup Y$ is the least upper bound of *Y*. Let ϕ_1 be an upper bound of *Y*. By definition, $\phi \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_1$ for all $\phi \in Y$, and $rel(\phi) \subseteq rel(\phi_1)$. Then it must also be the case that $\bigcup \{rel(\phi) \mid \phi \in Y\} \subseteq rel(\phi_1)$, and therefore $rel(\bigsqcup Y) \subseteq rel(\phi_1)$. Then $\bigsqcup Y \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \phi_1$ and it is the least upper bound of *Y*.

The last step of the proof is to show that $\perp_{\Phi_{G,\xi}}$ is the least element of $\Phi_{G,\xi}$. It is indeed a member of $\Phi_{G,\xi}$ and $\perp_{\Phi_{G,\xi}} \sqsubseteq_{\Phi_{G,\xi}} \phi$ for all ϕ , since $\perp_{\Phi_{G,\xi}} (\eta) = \eta'$ implies (vacuously) that $\phi(\eta) = \eta'$.

5 THE μG LANGUAGE FOR GRAPH NEURAL NETWORKS

In this section, we introduce the syntax of μG as a programming language for the definition of graph neural networks. After specifying its syntax (Definition 5.1), we show its denotational semantics (Definition 5.2), and structural operational semantics (Definition 5.8). Definition 5.1 (Syntax of μG). Given a set S of function symbols, we define an algebra of graph neural networks with the following abstract syntax:

$$\mathcal{N} ::= \iota \mid \psi \mid \triangleleft_{\sigma}^{\varphi} \mid \triangleright_{\sigma}^{\varphi} \mid \mathcal{N}_{1}; \mathcal{N}_{2} \mid \mathcal{N}_{1} \mid \mid \mathcal{N}_{2} \mid \mathcal{N}_{1} \oplus \mathcal{N}_{2} \mid \mathcal{N}^{\star}$$

with $\varphi, \sigma, \psi \in S$. The operator precedence rules given by $\star >$; > || > \oplus and parentheses are introduced to the syntax to make the meaning of expressions unambiguous.

Given a graph \mathcal{G} and an edge-labeling ξ , the meaning of a $\mu \mathcal{G}$ expression is a graph neural network, a function between node-labeling functions. The term ι represents the application of the *identity* GNN that leaves the node labels unaltered. Another of the basic $\mu \mathcal{G}$ terms is the *function application* ψ . This represents the GNN that applies the function referenced by ψ . Moreover, the *pre-image* term $\triangleleft_{\sigma}^{\varphi}$ and the *post-image* term $\triangleright_{\sigma}^{\varphi}$ define a GNN that computes the labeling of a node in terms of the labels of its predecessors and successors, respectively. Two GNNs can be composed by *sequential composition* N_1 ; N_2 and *parallel composition* $N_1 || N_2$. The *choice* operator $N_1 \oplus N_2$ allows to run different GNNs according to the values of a node-labeling function. Finally, the *star* operator N^{\star} is used to program recursive behavior.

5.1 Denotational semantics

Having defined the syntax, we are now ready to introduce the denotational semantics of μG .

Definition 5.2. (Denotational semantics) Given a graph \mathcal{G} and an edge-labeling function ξ , we define the semantic interpretation function $\mathcal{S}_{ds}[[\cdot]]^{\mathcal{G},\xi} : \mathcal{N} \to \Phi_{\mathcal{G},\xi}$ on $\mu \mathcal{G}$ formulas \mathcal{N} by induction in the following way:

$$\begin{split} & \mathcal{S}_{ds}[[\iota]]^{\mathcal{G},\xi} = id \\ & \mathcal{S}_{ds}[[\psi]]^{\mathcal{G},\xi}(\eta) = \lambda v.f_{\psi}(\eta(\mathcal{V}), \eta(v)) \\ & \mathcal{S}_{ds}[[\triangleleft_{\sigma}^{\varphi}]]^{\mathcal{G},\xi}(\eta) = \lambda v.f_{\sigma}(f_{\varphi}((\eta,\xi)(I_{\mathcal{G}}(v))), \eta(v)) \\ & \mathcal{S}_{ds}[[\vdash_{\sigma}^{\varphi}]]^{\mathcal{G},\xi}(\eta) = \lambda v.f_{\sigma}(f_{\varphi}((\eta,\xi)(O_{\mathcal{G}}(v))), \eta(v)) \\ & \mathcal{S}_{ds}[[\mathcal{N}_{1};\mathcal{N}_{2}]]^{\mathcal{G},\xi} = \mathcal{S}_{ds}[[\mathcal{N}_{2}]]^{\mathcal{G},\xi} \circ \mathcal{S}_{ds}[[\mathcal{N}_{1}]]^{\mathcal{G},\xi} \\ & \mathcal{S}_{ds}[[\mathcal{N}_{1}||\mathcal{N}_{2}]]^{\mathcal{G},\xi} = \mathcal{S}_{ds}[[\mathcal{N}_{1}]]^{\mathcal{G},\xi} \times \mathcal{S}_{ds}[[\mathcal{N}_{2}]]^{\mathcal{G},\xi} \\ & \mathcal{S}_{ds}[[\mathcal{N}_{1}||\mathcal{N}_{2}]]^{\mathcal{G},\xi} = cond(\pi_{L},\mathcal{S}_{ds}[[\mathcal{N}_{1}]]^{\mathcal{G},\xi} \circ \pi_{R},\mathcal{S}_{ds}[[\mathcal{N}_{2}]]^{\mathcal{G},\xi} \circ \pi_{R}) \\ & \mathcal{S}_{ds}[[\mathcal{N}^{\star}]]^{\mathcal{G},\xi} = FIX(\lambda\phi.cond(\lambda e.\lambda v.\mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}(e)(v) \simeq_{\epsilon} e(v), id, \phi \circ \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi})) \end{split}$$

for any $\psi, \varphi, \sigma \in S$. The functions *cond* and *FIX* are defined as:

$$cond(t, f_1, f_2)(\eta) = \begin{cases} f_1(\eta) & \text{if } t(\eta) = \lambda v. \text{True} \\ f_2(\eta) & \text{otherwise} \end{cases}$$

$$FIX(f) = \bigsqcup \{ f^n(\bot_{\Phi_{\mathcal{G},\xi}}) \mid n \ge 0 \}$$

where $f^0 = id$ and $f^{n+1} = f \circ f^n$. For any label type T and any real value $\epsilon \in \mathbb{R}$, we define a binary predicate \simeq_{ϵ} such that

$$x \simeq_{\epsilon} y \iff |x - y| \le \epsilon$$

Additionally, we provide the semantics for a term of the form $N_1 \otimes N_2$ which will be useful later in the proof of the equivalence with the structural operational semantics

$$\mathcal{S}_{ds}[[\mathcal{N}_1 \otimes \mathcal{N}_2]]^{\mathcal{G},\xi} = (\mathcal{S}_{ds}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \circ \pi_L) \times (\mathcal{S}_{ds}[[\mathcal{N}_2]]^{\mathcal{G},\xi} \circ \pi_R)$$

In the following paragraphs, we clarify the meaning of μG expressions.

Identity application. The term *i* is evaluated as the identity graph neural network that returns the input node-labeling function as is.

Function application. A function symbol $\psi_1, \psi_2, \ldots \in S$ is evaluated as the graph neural network that maps a node-labeling to a new node-labeling by applying the corresponding function f_1, f_2, \ldots on both local and global node information. The local information is the label of each individual node, while the global information is the multiset of the labels of all the nodes in the graph. The graph neural network we obtain applies a (possibly trainable) function f to these two pieces of information. Two particular cases arise if the function ignores either of the two inputs. If f ignores the global information, the GNN returns a node-labeling function η_l , a purely local transformation of the node labels. On the other hand, if f ignores the local information, the GNN returns a node-labeling function η_g that assigns to each node a label that summarizes the entire graph, emulating what in the GNN literature is known as a *global pooling* operator [16].

Pre-image and Post-Image. The pre-image \triangleleft and the post-image \triangleright , together with function symbols $\varphi, \sigma \in S$ are evaluated as the graph neural networks $S_{ds}[[\triangleleft_{\sigma}^{\varphi}]]^{\mathcal{G},\xi}$ and $S_{ds}[[\triangleright_{\sigma}^{\varphi}]]^{\mathcal{G},\xi}$. In the case of the pre-image, for any symbol $\varphi \in S$ the corresponding function f generates a message from tuples $(\eta(u), \xi((u, v)), \eta(v))$ for each $(u, v) \in I_{\mathcal{G}}(v)$. Then for any symbol $\sigma \in S$ the corresponding function g generates a new label for a node v from the multiset of incoming messages for v obtained from f and the current label $\eta(v)$. The functions f and g may be trainable. The case of the post-image is analogous, with the difference that f is applied to tuples $(\eta(v), \xi((v, u)), \eta(u))$ for each $(v, u) \in O_{\mathcal{G}}(v)$ instead.

Sequential composition. An expression of the form $N_1; N_2$ is evaluated as the graph neural network resulting from the function composition of $S_{ds}[[N_2]]^{\mathcal{G},\xi}$ and $S_{ds}[[N_1]]^{\mathcal{G},\xi}$.

Parallel composition. An expression of the form $N_1||N_2$ is evaluated as the graph neural network that maps a node-labeling function to the node-labeling function obtained from the parallel composition of $S_{ds}[[N_1]]^{\mathcal{G},\xi}$ and $S_{ds}[[N_2]]^{\mathcal{G},\xi}$.

Choice. The choice operator $N_1 \oplus N_2$ applied to $\mu \mathcal{G}$ formulas N_1, N_2 is evaluated as the graph neural network $S_{ds}[[N_1]]^{\mathcal{G},\xi}$ if the left projection of the input node-labeling $\eta' = \pi_L(\eta)$ is a node-labeling function such that $\forall v \in \mathcal{G}, \eta'(v) = \text{True}$. Otherwise, it is evaluated as the graph neural network $S_{ds}[[N_2]]^{\mathcal{G},\xi}$. In any case, the selected GNN is given in input the right projection of the input node-labeling function.

Fixed points. The *star* operator N^* , or the *fixed point* operator, applied to a μG formula N is evaluated as the graph neural network that that maps a node-labeling function η to a new node-labeling function η' that is the fixed point of N computed starting by η . In other words, the sequence

$$\begin{split} \eta_0 &= \eta \\ \eta_1 &= \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}(\eta_0) \\ \eta_2 &= \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}(\eta_1) \\ &\vdots \\ \eta_i &= \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}(\eta_{i-1}) \end{split}$$

is computed until we obtain a labeling η' such that $S_{ds}[[N]]^{\mathcal{G},\xi}(\eta') = \eta'$. The *FIX* function used in the definition requires that the input functional is a continuous function. In order to prove that, we first have to show that function composition \circ and the function *cond* are continuous. Later, in Section 6, we will also require the continuity of parallel composition \times to prove the equivalence of the denotational and operational semantics. The following lemmas prove all these results.

LEMMA 5.3. Function composition \circ is continuous in both its arguments.

PROOF. We prove that \circ is continuous in the first argument. The proof of continuity in the second argument is analogous. Let ϕ_0 be a graph neural network and let $F(\phi) = \phi \circ \phi_0$. We start by proving that F is monotone. If $\phi_1 \sqsubseteq_{\Phi_{G,\xi}} \phi_2$, then $rel(\phi_1) \subseteq rel(\phi_2)$, and we can conclude that

$$rel(\phi_0) * rel(\phi_1) \subseteq rel(\phi_0) * rel(\phi_2)$$

and therefore $F(\phi_1) \sqsubseteq_{\Phi_{G,\xi}} F(\phi_2)$.

Next we prove the continuity of *F*. Let *Y* be a non-empty chain, then

$$rel(F(\bigsqcup Y)) = rel((\bigsqcup Y) \circ \phi_0)$$
$$= rel(\phi_0) * rel(\bigsqcup Y)$$
$$= rel(\phi_0) * \bigcup \{rel(\phi) \mid \phi \in Y\}$$
$$= \bigcup \{rel(\phi_0) * rel(\phi) \mid \phi \in Y\}$$
$$= rel(\bigsqcup \{F(\phi) \mid \phi \in Y\})$$

Thus $F(\bigsqcup Y) = \bigsqcup \{F(\phi) \mid \phi \in Y\}.$

LEMMA 5.4. Parallel composition \times is continuous in both its arguments.

PROOF. We prove that × is continuous in the first argument. The proof of continuity in the second argument is analogous. Let ϕ_0 be a graph neural network and let $F(\phi) = \phi \times \phi_0$. We start by proving that F is monotone. If $\phi_1 \sqsubseteq_{\phi,\xi} \phi_2$, then $rel(\phi_1) \subseteq rel(\phi_2)$, and we can conclude that

$$rel(\phi_0) \frown rel(\phi_1) \subseteq rel(\phi_0) \frown rel(\phi_2)$$

Manuscript submitted to ACM

10

and therefore $F(\phi_1) \sqsubseteq_{\Phi_{G,\xi}} F(\phi_2)$. Next, we prove the continuity of *F*. Let *Y* be a non-empty chain, then

$$rel(F(\bigsqcup Y)) = rel((\bigsqcup Y)|\phi_0)$$
$$= rel(\bigsqcup Y) \frown rel(\phi_0)$$
$$= \bigcup \{rel(\phi) \mid \phi \in Y\} \frown rel(\phi_0)$$
$$= \bigcup \{rel(\phi) \frown rel(\phi_0) \mid \phi \in Y\}$$
$$= rel(\bigsqcup \{F(\phi) \mid \phi \in Y\})$$

Thus $F(\bigsqcup Y) = \bigsqcup \{F(\phi) \mid \phi \in Y\}.$

LEMMA 5.5. The function cond is continuous in its first argument.

PROOF. Let ϕ_0, ϕ_1 be GNNs, and let $F(\phi) = cond(\phi, \phi_0, \phi_1)$. We start by proving that *F* is monotone. We have to show that if $\phi_2 \sqsubseteq_{\Phi_G F} \phi_3$, then $F(\phi_2) \sqsubseteq F(\phi_3)$. We consider an arbitrary node-labeling function η and show that

$$F(\phi_2)(\eta) = \eta' \implies F(\phi_3)(\eta) = \eta'$$

If $\phi_2(\eta) = \lambda v$. True, then $F(\phi_2)(\eta) = \phi_0(\eta)$, and from $\phi_2 \equiv_{\phi_{G,\xi}} \phi_3$, we get that $F(\phi_3)(\eta) = \phi_0(\eta)$. Let's consider the case $\phi_2(\eta) \neq \lambda v$. True. Then $F(\phi_2)(\eta) = \phi_1(\eta)$ and the same is true for $F(\phi_3)(\eta)$ so the result is immediate.

To prove the continuity of *F*. Let *Y* be a non-empty chain, and we will only show that $F(\bigsqcup Y) \sqsubseteq_{\Phi_{G,\xi}} \bigsqcup \{F(\phi) \mid \phi \in Y\}$ since from the monotonicity of *F* we just proved we can conclude $\bigsqcup \{F(\phi) \mid \phi \in Y\} \sqsubseteq_{\Phi_{G,\xi}} F(\bigsqcup Y)$.

Then let's assume $F(\bigsqcup Y)(\eta) = \eta'$ and we have to determine a $\phi \in Y$ such that $F(\phi)(\eta) = \eta'$. If $(\bigsqcup Y)(\eta) = \lambda v$. True, we have $F(\bigsqcup Y)(\eta) = \phi_1(\eta)$ and it must be the case that $(\eta, \lambda v$. True) $\in rel(\bigsqcup Y)$. But since $rel(\bigsqcup Y) = \bigcup \{rel(\phi) \mid \phi \in Y\}$ there must exist a $\phi \in Y$ such that $\phi(\eta) = \lambda v$. True and $F(\phi)(\eta) = \phi_1(\eta)$. The case where $(\bigsqcup Y)(\eta) \neq \lambda v$. True is analogous.

LEMMA 5.6. The function cond is continuous in its second and third arguments.

PROOF. We prove that *cond* is continuous in the second argument. The proof of continuity in the third argument is analogous. Let ϕ_t , ϕ_0 be GNNs, and let $F(\phi) = cond(\phi_t, \phi, \phi_0)$. We start by proving that *F* is monotone.

If $\phi_t(\eta) = \lambda v$. True, then $F(\phi_1)(\eta) = \phi_1(\eta)$, and from $\phi_1 \sqsubseteq_{\phi_{G,\xi}} \phi_2$, we get that $\phi_1(\eta) = \eta' \implies \phi_2(\eta) = \eta'$. Therefore $F(\phi_2)(\eta) = \phi_2(\eta) = \eta'$ proves our result. Let's consider the case $\phi_t(\eta) \neq \lambda v$. True. Then $F(\phi_1)(\eta) = \phi_0(\eta)$ and the same is true for $F(\phi_2)(\eta)$ so the result is immediate.

To prove the continuity of *F*. Let *Y* be a non-empty chain, and we will only show that $F(\bigsqcup Y) \sqsubseteq_{\Phi_{G,\xi}} \bigsqcup \{F(\phi) \mid \phi \in Y\}$ since from the monotonicity of *F* we just proved we can conclude $\bigsqcup \{F(\phi) \mid \phi \in Y\} \sqsubseteq_{\Phi_{G,\xi}} F(\bigsqcup Y)$.

Then let's assume $F(\bigsqcup Y)(\eta) = \eta'$ and we have to determine a $\phi \in Y$ such that $F(\phi)(\eta) = \eta'$. If $\phi_t(\eta) \neq \lambda v$. True, we have $F(\bigsqcup Y)(\eta) = \phi_0(\eta)$ and for all $\phi \in Y$ we have $F(\phi)(\eta) = \phi_0(\eta)$. If $\phi_t(\eta) = \lambda v$. True, we have $F(\bigsqcup Y)(\eta) = (\bigsqcup Y)(\eta) = \eta'$ and therefore $(\eta, \eta') \in rel(\bigsqcup Y)$. But then, since $rel(\bigsqcup Y) = \bigcup \{rel(\phi) \mid \phi \in Y\}$, there must exist a $\phi \in Y$ such that $\phi(\eta) = \eta'$ and then $F(\phi)(\eta) = \eta'$.

Finally, we can show that the functional we pass to *FIX* is indeed a continuous function.

THEOREM 5.7. The functional $F(\phi) = cond(\lambda e.S_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}(e) \cong e, id, \phi \circ S_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi})$ is continuous.

Manuscript submitted to ACM

PROOF. We can see F as the composition of two functions

$$F = \lambda f.cond(\lambda e.S_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}(e) \cong e, f, id) \circ \lambda f.f \circ S_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}$$

and since the function composition of continuous functions is itself continuous, we conclude its continuity from the continuity of function composition (Lemma 5.3) and *cond* (Lemma 5.6). \Box

5.2 Operational semantics

For the structural operational semantics, we consider computations of the form

$$\langle N, \eta \rangle$$

where N is a $\mu \mathcal{G}$ expression and η is a node-labeling function. The transition rules are shown in Table 1. For any label type T and any real value $\epsilon \in \mathbb{R}$, the function $f_{\simeq_{\epsilon}} : (T \times T)^* \times (T \times T) \to \mathbb{B}$ associated to $\psi_{\simeq_{\epsilon}}$ in Table 1 is defined as

$$f_{\simeq_{\epsilon}}(X, x) = \pi_L(x) \simeq_{\epsilon} \pi_R(x)$$

Finally, we can define the semantic interpretation function on the structural operational semantics.

Definition 5.8 (Structural operational semantics). Given a graph \mathcal{G} and an edge-labeling function ξ , we define the semantic interpretation function $\mathcal{S}_{sos}[[\cdot]]^{\mathcal{G},\xi} : \mathcal{N} \to \Phi_{\mathcal{G},\xi}$ such that

$$S_{sos}[[\mathcal{N}]]^{\mathcal{G},\xi}(\eta) = \begin{cases} \eta' & \text{if } \langle \mathcal{N},\eta\rangle \to^{\star}_{\mathcal{G},\xi} \eta' \\ \text{undef otherwise} \end{cases}$$

The rules PAR_1 and PAR_2 in Table 1 make the evaluation of μG expressions non-deterministic. The next theorem shows that no matter the order of application of the structural semantics rules, the obtained GNN is the same.

THEOREM 5.9 (CONFLUENCE). If $\langle N, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle N_1, \eta_1 \rangle$ and $\langle N, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle N_2, \eta_2 \rangle$, then either $N_1 = N_2$ and $\eta_1 = \eta_2$ or there exists a term N' and a labeling function η' such that $\langle N_1, \eta_1 \rangle \rightarrow_{\mathcal{G}, \xi} \langle N', \eta' \rangle$ and $\langle N_2, \eta_2 \rangle \rightarrow_{\mathcal{G}, \xi} \langle N', \eta' \rangle$.

PROOF. By induction on the structure of N. The only interesting case is that for expressions of the form $N_1 \otimes N_2$, where rules PAR₁ and PAR₂ can be applied in any order. Suppose that $\langle N_1 \otimes N_2, \eta \rangle \rightarrow_{\mathcal{G},\xi} \langle N'_1 \otimes N_2, \eta_1 | \pi_R(\eta) \rangle$ by rule PAR₁ and that $\langle N_1 \otimes N_2, \eta \rangle \rightarrow_{\mathcal{G},\xi} \langle N_1 \otimes N'_2, \pi_L(\eta) | \eta_2 \rangle$ by rule PAR₂. Then the required term is $N' = N'_1 \otimes N'_2$ and the labeling function is $\eta' = \eta_1 | \eta_2$, because $\langle N_1 \otimes N'_2, \pi_L(\eta) | \eta_2 \rangle \rightarrow_{\mathcal{G},\xi} \langle N'_1 \otimes N'_2, \eta_1 | \eta_2 \rangle$ by rule PAR₁ and $\langle N'_1 \otimes N_2, \eta_1 | \pi_R(\eta) \rangle \rightarrow_{\mathcal{G},\xi} \langle N'_1 \otimes N'_2, \eta_1 | \eta_2 \rangle$ by rule PAR₂.

5.3 Language macros

We can enrich $\mu \mathcal{G}$ with a number of macros that simplifies the job of programming a graph neural network. In this section, we describe the means to define variables, functions, and shortcuts for the definition of if-then-else and while loop expressions. Some of these extensions require us to introduce a set of variable symbols $X := X | Y | Z | \cdots$ to the language's syntax. We will also use function symbols p_L and p_R to denote left and right projections.

Variable assignments. It is useful sometimes to assign an entire expression to a single label, so that whenever that label occurs in a program, the referred expression is substituted to it. For this purpose, we introduce variable assignments in the form of let expressions. A let expression has the form let X = N in N'. The intuitive meaning of such expression is that all occurrences of the variable symbol X in the expression N' are substituted with the expression Manuscript submitted to ACM

[ID]	$\langle \iota,\eta angle ightarrow_{{\cal G},\xi}\eta$		
[APPLY]	$\langle \psi, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \iota, \lambda v. f_{\psi}([\eta(u) \mid u \in \mathcal{V}], \eta(v)) \rangle$		
[PREIMG]	$ \langle \triangleleft_{\sigma}^{\varphi}, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \iota, \lambda v. f_{\sigma}([f_{\varphi}(\eta(u), \xi((v, u)), \eta(v)) \mid u \in \overrightarrow{N}(v)], \eta(v)) \rangle $		
[POSTIMG]	$ \langle \rhd_{\sigma}^{\varphi}, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \iota, \lambda v. f_{\sigma}([f_{\varphi}(\eta(u), \xi((u, v)), \eta(v)) \mid u \in \overleftarrow{N}(v)], \eta(v)) \rangle $		
$[SEQ_1]$	$\frac{\langle \mathcal{N}_{1},\eta\rangle \rightarrow_{\mathcal{G},\xi} \langle \mathcal{N}_{1}',\eta'\rangle}{\langle \mathcal{N}_{1};\mathcal{N}_{2},\eta\rangle \rightarrow_{\mathcal{G},\xi} \langle \mathcal{N}_{1}';\mathcal{N}_{2},\eta'\rangle}$		
$[SEQ_2]$	$\langle \iota; \mathcal{N}_2, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}_2, \eta \rangle$		
[SPLIT]	$\langle \mathcal{N}_1 \mathcal{N}_2, \eta angle ightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}_1 \otimes \mathcal{N}_2, \eta \eta angle$		
$[PAR_1]$	$\frac{\langle \mathcal{N}_{1}, \pi_{L}(\eta) \rangle \rightarrow_{\mathcal{G},\xi} \langle \mathcal{N}_{1}', \eta' \rangle}{\langle \mathcal{N}_{1} \otimes \mathcal{N}_{2}, \eta \rangle \rightarrow_{\mathcal{G},\xi} \langle \mathcal{N}_{1}' \otimes \mathcal{N}_{2}, \eta' \pi_{R}(\eta) \rangle}$		
[PAR ₂]	$\frac{\langle \mathcal{N}_{2}, \pi_{R}(\eta) \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}_{2}', \eta' \rangle}{\langle \mathcal{N}_{1} \otimes \mathcal{N}_{2}, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}_{1} \otimes \mathcal{N}_{2}', \pi_{L}(\eta) \eta' \rangle}$		
[MERGE]	$\langle \iota \otimes \iota, \eta \rangle \to_{\mathcal{G}, \xi} \langle \iota, \eta \rangle$		
[CHOICE ₁]	$\langle \mathcal{N}_1 \oplus \mathcal{N}_2, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}_1, \pi_R(\eta) \rangle \text{ if } \pi_L(\eta) = \lambda v. \text{True}$		
$[CHOICE_2]$	$\langle \mathcal{N}_1 \oplus \mathcal{N}_2, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}_2, \pi_R(\eta) \rangle \text{ if } \pi_L(\eta) = \lambda v. True$		
[STAR]	$\langle \mathcal{N}^{\star}, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle ((\iota \mathcal{N}); \psi_{\simeq_{\epsilon}} \iota); (\iota \oplus \mathcal{N}; \mathcal{N}^{\star}), \eta \rangle$		

Table 1. Structural operational semantics of μG

N. This substitution is purely syntactical, and let expressions are simply rewritten as $N'_{[N/X]}$. Clearly, multiple let expressions can be chained, so that we can write let $X_1 = N_1, X_2 = N_2, \ldots, X_k = N_k$ in N as a shorthand for let $X_1 = N_1$ in (let $X_2 = N_2$ in (... (let $X_k = N_k$ in N)...)).

Function definitions. Similarly to variable assignments, we also consider the definition of functions. A def expression has the form def $\mathcal{X}(\mathcal{X}_1, \ldots, \mathcal{X}_k) \{\mathcal{N}\}$ in \mathcal{N}' . Its intuitive meaning is that whenever the variable symbol \mathcal{X} followed by a parenthesized list of values $(\mathcal{N}_1, \ldots, \mathcal{N}_k)$ (which from now on we refer to as a call expression) occurs in \mathcal{N}' the entire call expression is substituted with the expression \mathcal{N} in which each variable symbol $\mathcal{X}_1, \ldots, \mathcal{X}_k$ has been substituted with the corresponding expression $\mathcal{N}_1, \ldots, \mathcal{N}_k$. As in the case of variables, this substitution is purely syntactical is rewritten as

$$\mathcal{N}'_{[\mathcal{X}(\mathcal{N}_1,...,\mathcal{N}_k)/\text{let }\mathcal{X}_1=\mathcal{N}_1,...,\mathcal{X}_k=\mathcal{N}_k \text{ in }\mathcal{N}]}$$

If-then-else selection. A typical programming language construct is the *if-then-else* selection operator that evaluates a Boolean condition and executes one out of two branches accordingly. In $\mu \mathcal{G}$ this operator can be implemented as a macro using the choice operator. We consider a graph neural network $\phi_1 : \Phi_{\mathcal{G},\xi}[T_1, \mathbb{B}]$ denoted by an expression \mathcal{N}_1 to provide a Boolean node-labeling function, and then execute the graph neural network denoted by \mathcal{N}_2 if the Boolean labeling is True for every node, otherwise the GNN denoted by \mathcal{N}_3 is executed instead. Then we can introduce the term if \mathcal{N}_1 then \mathcal{N}_2 else \mathcal{N}_3 as a shorthand for $(\mathcal{N}_1||\iota); (\mathcal{N}_2 \oplus \mathcal{N}_3)$.

Fixpoints with variables. Oftentimes we might want to include constant terms in our fixpoint computations, that is, include GNNs whose outputs do not depend on the current iterate solution, but only on the initial node labels as received by the star operator. To this end, we introduce a macro expression fix X = N, let $\mathcal{Y}_1 = N_1, \ldots, \mathcal{Y}_k = N_k$ in N' where the variable symbol X is the fixpoint variable and N is the GNN that computes the initial value for the fixpoint computation. The variables \mathcal{Y}_i for $i \in 1, \ldots, k$ denote the values we want to pre-compute and stay constant during the computation. To clarify this behavior formally, we show how this macro can be expressed in the language. We restrict the placement of variable symbols X, \mathcal{Y} to not appear on the right-hand side of a sequential composition expression. Then, this macro can be implemented as

$$((\mathcal{N}_1||\mathcal{N}_2||\cdots||\mathcal{N}_k)||\mathcal{N});$$

$$((p_1||p_2||\cdots||p_k)||\mathcal{N}'_{[p_1/\mathcal{Y}_1,\dots,p_k/\mathcal{Y}_k,p_R/\mathcal{X}]})^{\star};$$

$$p_R$$

where the terms p_i denote a composition of left and right projections functions to obtain the node-labeling produced by $S_{ds}[[N_i]]^{\mathcal{G},\xi}$ in the parallel composition of N_i for $i \in 1, ..., k$. Indeed, it is even possible to statically infer the largest possible set of sub-expressions N_i that can be pre-computed, and therefore we can simply write fix X = N in N' to have the same effect. This macro then essentially implements μ -calculus style fixpoint computations, with the added flexibility of being able to set any initial value for the fixpoint computation.

In the case there is no such sub-expression N_i , the macro reduces to

$$N; N^{\star}_{[\iota/X]}$$

Fixed iteration loops. The basic fixpoint operator iterates until the output labeling is considered equal to the input labeling. At times the programmer might want to instead iterate for a fixed number of steps, that is, execute the body of the fixpoint expression only for $k \ge 1$ steps. For this purpose, we expand on the previous macro to introduce repeat X = N in N' for k with $k \in \mathbb{N}^+$ that is a shorthand for the $\mu \mathcal{G}$ expression

(fix
$$X = zero||N$$
 in
if $X; p_L; <_k$ then
 $(X; p_L; succ)||N'_{[X; p_R/X]}$
else
 $X); p_R$

where *zero* denotes a constant function that maps all node labels to $0, <_k$ denotes a Boolean function that maps nodes to True if their (integer) label is smaller than k, and *succ* denotes the successor function over natural numbers. Clearly, Manuscript submitted to ACM

we can also have a repeat macro without having to specify a variable and an initial condition: repeat N' for k can be rewritten as repeat $X = \iota$ in N' for k.

6 EQUIVALENCE OF OPERATIONAL AND DENOTATIONAL SEMANTICS

Both the denotational semantics and operational semantics of μG define a mapping from node-labeling functions to node-labeling functions, i.e., a graph neural network. In the next theorem, we show that they define the *same* graph neural network.

THEOREM 6.1 (EQUIVALENCE OF DENOTATIONAL AND STRUCTURAL OPERATIONAL SEMANTICS). For any μG expression N, any graph G and any edge-labeling function ξ , we have that

$$\mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi} = \mathcal{S}_{sos}[[\mathcal{N}]]^{\mathcal{G},\xi}$$

PROOF. Since both functions return GNNs, which are members of a partially ordered set $\Phi_{\mathcal{G},\xi}$ with ordering relation $\Box_{\Phi_{\mathcal{G},\xi}}$, it is sufficient to show that for any $\mu \mathcal{G}$ expression \mathcal{N} :

- $S_{sos}[[\mathcal{N}]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} S_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}$
- $S_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} S_{sos}[[\mathcal{N}]]^{\mathcal{G},\xi}$

Lemma 6.2 and Lemma 6.3 prove that both these conditions are satisfied by the semantics of μG .

LEMMA 6.2. For every expression \mathcal{N} of $\mu \mathcal{G}$, we have $\mathcal{S}_{sos}[[\mathcal{N}]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}$.

PROOF. We shall prove that for any expression N and any node-labeling function η , η'

$$\langle \mathcal{N}, \eta \rangle \to_{G,\xi}^{\star} \eta' \implies \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}(\eta) = \eta'$$
 (2)

In order to do that, we will show that

$$\langle \mathcal{N}, \eta \rangle \to_{\mathcal{G}, \xi} \eta' \implies \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G}, \xi}(\eta) = \eta'$$
(3)

$$\langle \mathcal{N}, \eta \rangle \to_{\mathcal{G}, \xi} \langle \mathcal{N}', \eta' \rangle \implies \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G}, \xi}(\eta) = \mathcal{S}_{ds}[[\mathcal{N}']]^{\mathcal{G}, \xi}(\eta') \tag{4}$$

If Equation 3 and Equation 4 hold, the proof of Equation 2 is a straightforward induction on the length *k* of the derivation sequence $\langle N, \eta \rangle \rightarrow^{k}_{\mathcal{G},\xi} \eta'$. The proof of Equation 3 and Equation 4 is by induction on the shape of the derivation trees.

The case ID: We have $\langle \iota, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \eta$, and since $\mathcal{S}_{ds}[[\iota]]^{\mathcal{G}, \xi}(\eta) = \eta$, the result follows. **The case APPLY:** We have $\langle \psi, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \iota, \lambda v. f_{\psi}([\eta(u) \mid u \in \mathcal{V}], \eta(v)) \rangle$, and since

$$\begin{aligned} \mathcal{S}_{ds}[[\psi]]^{\mathcal{G},\xi}(\eta) &= \lambda v. f_{\psi}([\eta(u) \mid u \in \mathcal{V}], \eta(v)) \\ &= \mathcal{S}_{ds}[[\iota]]^{\mathcal{G},\xi}(\lambda v. f_{\psi}([\eta(u) \mid u \in \mathcal{V}], \eta(v))) \end{aligned}$$

the result follows.

The case PREIMG: Analogous to case APPLY.

The case POSTIMG: Analogous to case APPLY.

The case SEQ₁: Assume that $\langle \mathcal{N}_1; \mathcal{N}_2, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}'_1; \mathcal{N}_2, \eta' \rangle$ because $\langle \mathcal{N}_1, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}'_1, \eta' \rangle$. By induction hypothesis we have that $\mathcal{S}_{ds}[[\mathcal{N}_1]]^{\mathcal{G}, \xi}(\eta) = \mathcal{S}_{ds}[[\mathcal{N}'_1]]^{\mathcal{G}, \xi}(\eta')$. Then we get

$$S_{ds}[[\mathcal{N}_1; \mathcal{N}_2]]^{\mathcal{G}, \xi}(\eta) = S_{ds}[[\mathcal{N}_2]]^{\mathcal{G}, \xi}(S_{ds}[[\mathcal{N}_1]]^{\mathcal{G}, \xi}(\eta))$$
$$= S_{ds}[[\mathcal{N}_2]]^{\mathcal{G}, \xi}(S_{ds}[[\mathcal{N}_1']]^{\mathcal{G}, \xi}(\eta'))$$
$$= S_{ds}[[\mathcal{N}_1'; \mathcal{N}_2]]^{\mathcal{G}, \xi}(\eta')$$

The case SEQ₂: We have that $\langle \iota; \mathcal{N}_2, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}_2, \eta \rangle$. Then we get

$$\begin{split} \mathcal{S}_{ds}[[\iota;\mathcal{N}_2]]^{\mathcal{G},\xi}(\eta) &= \mathcal{S}_{ds}[[\mathcal{N}_2]]^{\mathcal{G},\xi}(\mathcal{S}_{ds}[[\iota]]^{\mathcal{G},\xi}(\eta)) \\ &= \mathcal{S}_{ds}[[\mathcal{N}_2]]^{\mathcal{G},\xi}(\eta) \end{split}$$

The case SPLIT: We have $\langle \mathcal{N}_1 || \mathcal{N}_2, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}_1 \otimes \mathcal{N}_2, \eta | \eta \rangle$. Then we get

$$\begin{split} S_{ds}[[\mathcal{N}_{1}||\mathcal{N}_{2}]]^{\mathcal{G},\xi}(\eta) &= S_{ds}[[\mathcal{N}_{1}]]^{\mathcal{G},\xi} \times S_{ds}[[\mathcal{N}_{2}]]^{\mathcal{G},\xi}(\eta) \\ &= (S_{ds}[[\mathcal{N}_{1}]]^{\mathcal{G},\xi} \circ \pi_{L}) \times (S_{ds}[[\mathcal{N}_{2}]]^{\mathcal{G},\xi} \circ \pi_{R})(\eta|\eta) \\ &= S_{ds}[[\mathcal{N}_{1} \otimes \mathcal{N}_{2}]]^{\mathcal{G},\xi}(\eta|\eta) \end{split}$$

The case PAR₁: We have $\langle \mathcal{N}_1 \otimes \mathcal{N}_2, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}'_1 \otimes \mathcal{N}_2, \eta' | \pi_R(\eta) \rangle$ because $\langle \mathcal{N}_1, \pi_L(\eta) \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}'_1, \eta' \rangle$. By induction hypothesis we have that $\mathcal{S}_{ds}[[\mathcal{N}_1]]^{\mathcal{G}, \xi}(\pi_L(\eta)) = \mathcal{S}_{ds}[[\mathcal{N}'_1]]^{\mathcal{G}, \xi}(\eta')$. Then we get

$$\begin{split} \mathcal{S}_{ds}[[\mathcal{N}_{1}\otimes\mathcal{N}_{2}]]^{\mathcal{G},\xi}(\eta) &= (\mathcal{S}_{ds}[[\mathcal{N}_{1}]]^{\mathcal{G},\xi}\circ\pi_{L})\times(\mathcal{S}_{ds}[[\mathcal{N}_{2}]]^{\mathcal{G},\xi}\circ\pi_{R})(\eta) \\ &= \mathcal{S}_{ds}[[\mathcal{N}_{1}]]^{\mathcal{G},\xi}(\pi_{L}(\eta))|\mathcal{S}_{ds}[[\mathcal{N}_{2}]]^{\mathcal{G},\xi}(\pi_{R}(\eta)) \\ &= \mathcal{S}_{ds}[[\mathcal{N}_{1}']]^{\mathcal{G},\xi}(\eta')|\mathcal{S}_{ds}[[\mathcal{N}_{2}]]^{\mathcal{G},\xi}(\pi_{R}(\eta)) \\ &= (\mathcal{S}_{ds}[[\mathcal{N}_{1}']]^{\mathcal{G},\xi}\circ\pi_{L})\times(\mathcal{S}_{ds}[[\mathcal{N}_{2}]]^{\mathcal{G},\xi}\circ\pi_{R})(\eta'|\pi_{R}(\eta)) \\ &= \mathcal{S}_{ds}[[\mathcal{N}_{1}'\otimes\mathcal{N}_{2}]]^{\mathcal{G},\xi}(\eta'|\pi_{R}(\eta)) \end{split}$$

The case PAR₂**:** Analogous to case PAR₁.

The case MERGE: We have that $\langle \iota \otimes \iota, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \iota, \eta \rangle$. Then we get:

$$\begin{split} \mathcal{S}_{ds}[[\iota \otimes \iota]]^{\mathcal{G},\xi}(\eta) &= (\mathcal{S}_{ds}[[\iota]]^{\mathcal{G},\xi} \circ \pi_L) \times (\mathcal{S}_{ds}[[\iota]]^{\mathcal{G},\xi} \circ \pi_R)(\eta) \\ &= \mathcal{S}_{ds}[[\iota]]^{\mathcal{G},\xi}(\pi_L(\eta)) |\mathcal{S}_{ds}[[\iota]]^{\mathcal{G},\xi}(\pi_R(\eta)) \\ &= \pi_L(\eta) |\pi_R(\eta) \\ &= \eta \\ &= \mathcal{S}_{ds}[[\iota]]^{\mathcal{G},\xi}(\eta) \end{split}$$

The case CHOICE₁: We have $\langle \mathcal{N}_1 \oplus \mathcal{N}_2, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}_1, \pi_R(\eta) \rangle$ because $\pi_L(\eta) = \lambda v$. True. Then we get

$$\begin{split} \mathcal{S}_{ds}[[\mathcal{N}_1 \oplus \mathcal{N}_2]]^{\mathcal{G},\xi}(\eta) &= cond(\pi_L, \mathcal{S}_{ds}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \circ \pi_R, \mathcal{S}_{ds}[[\mathcal{N}_2]]^{\mathcal{G},\xi} \circ \pi_R)(\eta) \\ &= \mathcal{S}_{ds}[[\mathcal{N}_1]]^{\mathcal{G},\xi}(\pi_R(\eta)) \end{split}$$

The case CHOICE₂: Analogous to CHOICE₁.

The case STAR: We have

$$\langle \mathcal{N}^{\star}, \eta \rangle \rightarrow_{G \not\in} \langle ((\iota || \mathcal{N}); \psi_{\simeq_{\epsilon}} || \iota); (\iota \oplus \mathcal{N}; \mathcal{N}^{\star}), \eta \rangle$$

Let $F = \lambda \phi.cond(\lambda e.\lambda v.S_{ds}[[N]]^{\mathcal{G},\xi}(e)(v) \simeq_{\epsilon} e(v), id, \phi \circ S_{ds}[[N]]^{\mathcal{G},\xi})$, then we get

$$\begin{split} \mathcal{S}_{ds}[[\mathcal{N}^{\star}]]^{\mathcal{G},\xi}(\eta) &= FIX(F)(\eta) \\ &= F(FIX(F))(\eta) \\ &= cond(\lambda e.\lambda v.S_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}(e)(v) \simeq_{\epsilon} e(v), id, FIX(F) \circ \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi})(\eta) \\ &= cond(\lambda e.\lambda v.S_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}(e)(v) \simeq_{\epsilon} e(v), id, \mathcal{S}_{ds}[[\mathcal{N}^{\star}]]^{\mathcal{G},\xi} \circ \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi})(\eta) \\ &= cond(\lambda e.\lambda v.S_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi}(e)(v) \simeq_{\epsilon} e(v), id, \mathcal{S}_{ds}[[\mathcal{N}^{\star}]]^{\mathcal{G},\xi} \circ \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi})(\eta) \\ &= cond(\mathcal{S}_{ds}[[(\mathcal{N}||\iota);\psi_{\simeq_{\epsilon}}]]^{\mathcal{G},\xi}, \mathcal{S}_{ds}[[\iota]]^{\mathcal{G},\xi}, \mathcal{S}_{ds}[[\mathcal{N};\mathcal{N}^{\star}]]^{\mathcal{G},\xi}) \\ &= cond(\pi_{L},\mathcal{S}_{ds}[[\iota]]^{\mathcal{G},\xi} \circ \pi_{R}, \mathcal{S}_{ds}[[\mathcal{N};\mathcal{N}^{\star}]]^{\mathcal{G},\xi} \circ \pi_{R}) \circ \mathcal{S}_{ds}[[(\mathcal{N}||\iota);\psi_{\simeq_{\epsilon}}||\iota]]^{\mathcal{G},\xi}(\eta) \\ &= \mathcal{S}_{ds}[[\iota \in \mathcal{N};\mathcal{N}^{\star}]]^{\mathcal{G},\xi} \circ \mathcal{S}_{ds}[[((\iota||\mathcal{N});\psi_{\simeq_{\epsilon}}||\iota)]]^{\mathcal{G},\xi}(\eta) \\ &= \mathcal{S}_{ds}[[((\iota||\mathcal{N});\psi_{\simeq_{\epsilon}}||\iota);(\iota \in \mathcal{N};\mathcal{N}^{\star})]]^{\mathcal{G},\xi}(\eta) \end{split}$$

This completes our proof of Lemma 6.2.

LEMMA 6.3. For every expression \mathcal{N} of $\mu \mathcal{G}$, we have $\mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \mathcal{S}_{sos}[[\mathcal{N}]]^{\mathcal{G},\xi}$.

PROOF. We proceed by structural induction on the expression N.

The case *i*: Immediate, as $S_{ds}[[\iota]]^{\mathcal{G},\xi}(\eta) = S_{sos}[[\iota]]^{\mathcal{G},\xi}(\eta)$.

The case ψ : This case is simple as well, since $S_{ds}[[\psi]] \mathcal{G}^{\xi}(\eta) = S_{sos}[[\psi]] \mathcal{G}^{\xi}(\eta)$ by applying rule APPLY followed by rule ID.

The case $\triangleleft_{\sigma}^{\varphi}$: Analogous to case ψ , but instead using the rules PREIMG and ID.

The case $\triangleright_{\sigma}^{\varphi}$: Analogous to case ψ , but instead using the rules POSTIMG and ID.

The case $\mathcal{N}_1; \mathcal{N}_2$: By induction hypothesis we have $\mathcal{S}_{ds}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \mathcal{S}_{sos}[[\mathcal{N}_1]]^{\mathcal{G},\xi}$ and $\mathcal{S}_{ds}[[\mathcal{N}_2]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \mathcal{S}_{sos}[[\mathcal{N}_2]]^{\mathcal{G},\xi}$. By the monotonicity of \circ in both its arguments (Lemma 5.3) and the induction hypothesis we get that

$$S_{ds}[[\mathcal{N}_1; \mathcal{N}_2]]^{\mathcal{G}, \xi} = S_{ds}[[\mathcal{N}_2]]^{\mathcal{G}, \xi} \circ S_{ds}[[\mathcal{N}_1]]^{\mathcal{G}, \xi}$$
$$\sqsubseteq_{\Phi_{\mathcal{G}, \xi}} S_{sos}[[\mathcal{N}_2]]^{\mathcal{G}, \xi} \circ S_{sos}[[\mathcal{N}_1]]^{\mathcal{G}, \xi}$$

To continue the proof, we need to prove that if $\langle N_1, \eta \rangle \rightarrow_{\mathcal{G},\xi}^k \eta'$ then $\langle N_1; N_2, \eta \rangle \rightarrow_{\mathcal{G},\xi}^k \langle N_2, \eta' \rangle$. The proof is by induction on the derivation length k. For k = 1 we have $\langle N_1, \eta \rangle \rightarrow_{\mathcal{G},\xi} \eta'$, which means that $N_1 = \iota$ and $\eta = \eta'$. Therefore, by applying rule SEQ₂ we get $\langle \iota; N_2, \eta \rangle \rightarrow_{\mathcal{G},\xi} \langle N_2, \eta' \rangle$. For the inductive step, let's assume the lemma holds for k and prove that it holds for k + 1. We assume that $\langle N_1, \eta \rangle \rightarrow_{\mathcal{G},\xi}^{k+1} \eta'$, which means that $\langle N_1, \eta \rangle \rightarrow_{\mathcal{G},\xi} \langle N'_1, \eta_1 \rangle$ for some N'_1, η_1 , and $\langle N'_1, \eta_1 \rangle \rightarrow_{\mathcal{G},\xi}^k \eta'$. Therefore the first rule we can apply for the sequential composition of N_1 and N_2 is SEQ₁ with $\langle N_1, \eta \rangle \rightarrow_{\mathcal{G},\xi} \langle N'_1, \eta_1 \rangle$ as its premise, and we get the transition $\langle N_1; N_2, \eta \rangle \rightarrow_{\mathcal{G},\xi} \langle N'_1; N_2, \eta_1 \rangle$. Now we apply the induction hypothesis $\langle N'_1, \eta_1 \rangle \rightarrow_{\mathcal{G},\xi}^k \eta' \implies$ $\langle N'_1; N_2, \eta_1 \rangle \rightarrow_{\mathcal{G},\xi}^k \langle N_2, \eta' \rangle$ to obtain the desired result, having performed k + 1 steps in total. Using this result,

Manuscript submitted to ACM

we can conclude that

$$\mathcal{S}_{sos}[[\mathcal{N}_2]]^{\mathcal{G},\xi} \circ \mathcal{S}_{sos}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \mathcal{S}_{sos}[[\mathcal{N}_1;\mathcal{N}_2]]^{\mathcal{G},\xi}$$

as required.

The case $\mathcal{N}_1||\mathcal{N}_2$: By induction hypothesis we have $\mathcal{S}_{ds}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \mathcal{S}_{sos}[[\mathcal{N}_1]]^{\mathcal{G},\xi}$ and $\mathcal{S}_{ds}[[\mathcal{N}_2]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \mathcal{S}_{sos}[[\mathcal{N}_2]]^{\mathcal{G},\xi}$. By the monotonicity of × in both its arguments (Lemma 5.4) and the induction hypothesis, we get that

$$S_{ds}[[\mathcal{N}_1||\mathcal{N}_2]]^{\mathcal{G},\xi} = S_{ds}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \times S_{ds}[[\mathcal{N}_2]]^{\mathcal{G},\xi}$$
$$\sqsubseteq_{\Phi_{\mathcal{G},\xi}} S_{sos}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \times S_{sos}[[\mathcal{N}_2]]^{\mathcal{G},\xi}$$

To continue the proof, we have to show that if $\langle N_1, \eta_1 \rangle \rightarrow_{\mathcal{G},\xi}^{k_1} \eta'_1$ and $\langle N_2, \eta_2 \rangle \rightarrow_{\mathcal{G},\xi}^{k_2} \eta'_2$, then $\langle N_1 \otimes N_2, \eta_1 | \eta_2 \rangle \rightarrow_{\mathcal{G},\xi}^{k_1+k_2} \eta'_1 | \eta'_2$. For $k_1 = k_2 = 1$, we have that $N_1 = N_2 = \iota$, $\eta_1 = \eta'_1$ and $\eta_2 = \eta'_2$. Hence, we get $\langle \iota \otimes \iota, \eta_1 | \eta_2 \rangle \rightarrow_{\mathcal{G},\xi} \langle \iota, \eta_1 | \eta_2 \rangle \rightarrow_{\mathcal{G},\xi} \langle \iota, \eta_1 | \eta_2 \rangle \rightarrow_{\mathcal{G},\xi} \eta_1 | \eta_2$ by applying rule MERGE followed by rule ID and performing 1 + 1 = 2 steps. For the inductive step, let's assume the implication holds for k_1, k_2 and prove it for $k_1 + 1, k_2 + 1$. We have $\langle N_1, \eta_1 \rangle \rightarrow_{\mathcal{G},\xi} \langle N'_1, \eta''_1 \rangle \rightarrow_{\mathcal{G},\xi}^{k_1} \eta'_1$ and $\langle N_2, \eta_2 \rangle \rightarrow_{\mathcal{G},\xi} \langle N'_2, \eta''_2 \rangle \rightarrow_{\mathcal{G},\xi}^{k_2} \eta'_2$ for some $N'_1, N'_2, \eta''_1, \eta''_2$. Then we can perform two steps $\langle N_1 \otimes N_2, \eta_1 | \eta_2 \rangle \rightarrow_{\mathcal{G},\xi} \langle N'_1 \otimes N_2, \eta''_1 | \eta_2 \rangle \rightarrow_{\mathcal{G},\xi} \langle N'_1 \otimes N_2, \eta''_1 | \eta'_2 \rangle$ by applying rules [PAR_1] and [PAR_2]. Then by applying the induction hypothesis we get our result $\langle N'_1 \otimes N'_2, \eta''_1 | \eta''_2 \rangle \rightarrow_{\mathcal{G},\xi}^{k_1+k_2} \eta'_1 | \eta'_2$ in $2 + k_1 + k_2 = (k_1 + 1) + (k_2 + 1)$ steps. Using this result, we can conclude that

$$S_{sos}[[\mathcal{N}_2]]^{\mathcal{G},\xi} \times S_{sos}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} S_{sos}[[\mathcal{N}_1 \otimes \mathcal{N}_2]]^{\mathcal{G},\xi} \circ (id \times id)$$
$$= S_{sos}[[\mathcal{N}_1||\mathcal{N}_2]]^{\mathcal{G},\xi}$$

as required.

The case $\mathcal{N}_1 \otimes \mathcal{N}_2$: By induction hypothesis we have $\mathcal{S}_{ds}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \mathcal{S}_{sos}[[\mathcal{N}_1]]^{\mathcal{G},\xi}$ and $\mathcal{S}_{ds}[[\mathcal{N}_2]]^{\mathcal{G},\xi} \sqsubseteq_{\Phi_{\mathcal{G},\xi}} \mathcal{S}_{sos}[[\mathcal{N}_2]]^{\mathcal{G},\xi}$. By the monotonicity of \circ (Lemma 5.3) and that of \times in both its arguments (Lemma 5.4), and the induction hypothesis, we get that

$$S_{ds}[[\mathcal{N}_{1} \otimes \mathcal{N}_{2}]]^{\mathcal{G},\xi} = (S_{ds}[[\mathcal{N}_{1}]]^{\mathcal{G},\xi} \circ \pi_{L}) \times (S_{ds}[[\mathcal{N}_{1}]]^{\mathcal{G},\xi} \circ \pi_{R})$$
$$\equiv_{\Phi_{\mathcal{G},\xi}} (S_{sos}[[\mathcal{N}_{1}]]^{\mathcal{G},\xi} \circ \pi_{L}) \times (S_{sos}[[\mathcal{N}_{2}]]^{\mathcal{G},\xi} \circ \pi_{R})$$
$$= S_{sos}[[\mathcal{N}_{1} \otimes \mathcal{N}_{2}]]^{\mathcal{G},\xi}$$

The case $N_1 \oplus N_2$: We have that $S_{ds}[[N_1 \oplus N_2]]^{\mathcal{G},\xi} = cond(\pi_L, S_{ds}[[N_1]]^{\mathcal{G},\xi} \circ \pi_R, S_{ds}[[N_2]]^{\mathcal{G},\xi} \circ \pi_R)$. By induction hypothesis we have that $S_{ds}[[N_1]]^{\mathcal{G},\xi} \equiv_{\Phi_{\mathcal{G},\xi}} S_{sos}[[N_1]]^{\mathcal{G},\xi}$ and $S_{ds}[[N_2]]^{\mathcal{G},\xi} \equiv_{\Phi_{\mathcal{G},\xi}} S_{sos}[[N_2]]^{\mathcal{G},\xi}$. By the monotonicity of \circ (Lemma 5.3) and that of *cond* in its second and third arguments (Lemma 5.6), and the induction hypothesis we have that

$$S_{ds}[[\mathcal{N}_1 \oplus \mathcal{N}_2]]^{\mathcal{G},\xi} = cond(\pi_L, S_{ds}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \circ \pi_R, S_{ds}[[\mathcal{N}_2]]^{\mathcal{G},\xi} \circ \pi_R)$$
$$\sqsubseteq_{\Phi_{\mathcal{G},\xi}} cond(\pi_L, S_{sos}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \circ \pi_R, S_{sos}[[\mathcal{N}_2]]^{\mathcal{G},\xi} \circ \pi_R)$$

Now from the rules CHOICE_1 and CHOICE_2 it follows that

$$S_{sos}[[\mathcal{N}_1 \oplus \mathcal{N}_2]]^{\mathcal{G},\xi}(\eta) = S_{sos}[[\mathcal{N}_1]]^{\mathcal{G},\xi}(\pi_R(\eta)) \text{ if } \pi_L(\eta) = \lambda v.\text{True}$$
$$S_{sos}[[\mathcal{N}_1 \oplus \mathcal{N}_2]]^{\mathcal{G},\xi}(\eta) = S_{sos}[[\mathcal{N}_2]]^{\mathcal{G},\xi}(\pi_R(\eta)) \text{ if } \pi_L(\eta) \neq \lambda v.\text{True}$$

therefore

$$cond(\pi_L, \mathcal{S}_{sos}[[\mathcal{N}_1]]^{\mathcal{G},\xi} \circ \pi_R, \mathcal{S}_{sos}[[\mathcal{N}_2]]^{\mathcal{G},\xi} \circ \pi_R) = \mathcal{S}_{sos}[[\mathcal{N}_1 \oplus \mathcal{N}_2]]^{\mathcal{G},\xi}$$

The case \mathcal{N}^{\star} : We have that $\mathcal{S}_{ds}[[\mathcal{N}^{\star}]]^{\mathcal{G},\xi} = FIX(F)$, where

$$F = \lambda \phi. cond(\lambda e. \lambda v. \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G}, \xi}(e)(v) \simeq_{\epsilon} e(v), id, \phi \circ \mathcal{S}_{ds}[[\mathcal{N}]]^{\mathcal{G}, \xi})$$

We start by proving that if $f : D \to D$ is a continuous function on a ccpo (D, \sqsubseteq) and if $d \in D$ is such that $f(d) \sqsubseteq d$, then $FIX(f) \sqsubseteq d$. To prove this, we recall that by the monotonicity of f it must be the case that $f(f(d)) \sqsubseteq f(d)$, and more generally, that $f^{n+1}(d) \sqsubseteq f^n(d), \forall n \ge 0$. Therefore d is an upper bound of the chain $\{f^n(d) \mid n \ge 0\}$. Then, since $\bot \sqsubseteq d$, we have that $f^n(\bot) \sqsubseteq f^n(d), \forall n \ge 0$ and d is also an upper bound for the chain $\{f^n(\bot) \mid n \ge 0\}$. Then $FIX(f) = \bigsqcup \{f^n(\bot) \mid n \ge 0\} \sqsubseteq d$ since the least fixed point of f is the least upper bound of that chain.

This result proves that $FIX(F) \subseteq S_{sos}[[N^*]]^{\mathcal{G},\xi}$, on the condition that we show that $F(S_{sos}[[N^*]]^{\mathcal{G},\xi}) \subseteq S_{sos}[[N^*]]^{\mathcal{G},\xi}$. We can prove this by first showing that

$$S_{sos}[[\mathcal{N}^{\star}]]^{\mathcal{G},\xi} = S_{sos}[[((\mathcal{N}||\iota);\psi_{\simeq_{e}}||\iota);(\iota \oplus \mathcal{N};\mathcal{N}^{\star})]]^{\mathcal{G},\xi}$$

$$\exists S_{sos}[[(\iota \oplus \mathcal{N};\mathcal{N}^{\star})]]^{\mathcal{G},\xi} \circ S_{sos}[[((\mathcal{N}||\iota);\psi_{\simeq_{e}}||\iota)]]^{\mathcal{G},\xi}$$

$$= cond(\pi_{L}, S_{sos}[[\iota]]^{\mathcal{G},\xi} \circ \pi_{R}, S_{sos}[[\mathcal{N};\mathcal{N}^{\star}]]^{\mathcal{G},\xi} \circ \pi_{R}) \circ S_{sos}[[(((\mathcal{N}||\iota);\psi_{\simeq_{e}}||\iota)]]^{\mathcal{G},\xi}$$

$$= cond(S_{sos}[[(\mathcal{N}||\iota);\psi_{\simeq_{e}}]]^{\mathcal{G},\xi}, S_{sos}[[\iota]]^{\mathcal{G},\xi}, S_{sos}[[\mathcal{N};\mathcal{N}^{\star}]]^{\mathcal{G},\xi})$$

$$\equiv cond(S_{sos}[[(\mathcal{N}||\iota);\psi_{\simeq_{e}}]]^{\mathcal{G},\xi}, S_{sos}[[\iota]]^{\mathcal{G},\xi}, S_{sos}[[\mathcal{N}^{\star}]]^{\mathcal{G},\xi} \circ S_{sos}[[\mathcal{N}]]^{\mathcal{G},\xi})$$

The induction hypothesis gives us that $S_{ds}[[N]]^{\mathcal{G},\xi} \subseteq S_{sos}[[N]]^{\mathcal{G},\xi}$, and by the monotonicity of \circ (Lemma 5.3) and *cond* (Lemmas 5.5 and 5.6) we get

$$S_{sos}[[\mathcal{N}^{\star}]]^{\mathcal{G},\xi} \supseteq cond(S_{sos}[[(\mathcal{N}||\iota);\psi_{\simeq_{\epsilon}}]]^{\mathcal{G},\xi}, S_{sos}[[\iota]]^{\mathcal{G},\xi}, S_{sos}[[\mathcal{N}^{\star}]]^{\mathcal{G},\xi} \circ S_{sos}[[\mathcal{N}]]^{\mathcal{G},\xi})$$
$$\supseteq cond(S_{ds}[[(\mathcal{N}||\iota);\psi_{\simeq_{\epsilon}}]]^{\mathcal{G},\xi}, id, S_{sos}[[\mathcal{N}^{\star}]]^{\mathcal{G},\xi} \circ S_{ds}[[\mathcal{N}]]^{\mathcal{G},\xi})$$
$$= F(S_{sos}[[\mathcal{N}^{\star}]]^{\mathcal{G},\xi})$$

This completes our proof of Lemma 6.3.

7 TYPE SOUNDNESS

We say that a μG term is *well-typed* whenever it can be typed with the rules of Table 2. These rules guarantee that any *well-typed* μG term defines a graph neural network. Next, we will be using these typing rules to prove the type soundness of the operational semantics of μG . Proving the type safety of μG ensures that the GNNs we program with it handle the data types correctly and produce results of the expected type. Concretely, this means that well-typed GNNs can always progress to the next step of computation and that after each step the type of the output is preserved.

$$[\mathsf{T}-\mathsf{ID}] \qquad \qquad \iota: \Phi_{\mathcal{G},\xi}[T,T]$$

[T-PSI]
$$\frac{\Gamma \vdash f_{\psi} : T_1^* \times T_1 \to T_2}{\psi : \Phi_{G, \varepsilon}[T_1, T_2]}$$

$$[\mathsf{T}-\mathsf{PRE}] \qquad \frac{\Gamma \vdash f_{\varphi} : T_1 \times T_e \times T_1 \to T_2 \qquad \Gamma \vdash f_{\sigma} : T_2^* \times T_1 \to T_3}{\sigma^{\varphi} \cdot \Phi = [T, T]}$$

$$[\mathsf{T}-\mathsf{POST}] \qquad \frac{\Gamma \vdash f_{\varphi} : T_1 \times T_e \times T_1 \to T_2 \qquad \Gamma \vdash f_{\sigma} : T_2^* \times T_1 \to T_3}{\frac{\sigma}{\sigma}}$$

 $\cdot \Phi \sim [T, T_{\rm e}]$

[T T]

SEQ]
$$\overset{\varphi_{\sigma}}{\sim} : \Phi_{\mathcal{G},\xi}[T_1, T_3]$$
$$\underbrace{N_1 : \Phi_{\mathcal{G},\xi}[T_1, T_2] \quad N_2 : \Phi_{\mathcal{G},\xi}[T_2, T_3]}_{N_1 : N_2 : \Phi_{\mathcal{G},\xi}[T_1, T_3]}$$

$$[\mathsf{T}-\mathsf{PAR}] \qquad \qquad \frac{\mathcal{N}_1 : \Phi_{\mathcal{G},\xi}[T,T_1] \quad \mathcal{N}_2 : \Phi_{\mathcal{G},\xi}[T,T_2]}{\mathcal{N}_1 || \mathcal{N}_2 : \Phi_{\mathcal{G},\xi}[T,T_1 \times T_2]}$$

$$\begin{bmatrix} \mathsf{T}\text{-}\mathsf{PROD} \end{bmatrix} \qquad \frac{\mathcal{N}_1 : \Phi_{\mathcal{G},\xi}[T_1, T_1'] \qquad \mathcal{N}_2 : \Phi_{\mathcal{G},\xi}[T_2, T_2']}{\mathcal{N}_1 \otimes \mathcal{N}_2 : \Phi_{\mathcal{G},\xi}[T_1 \times T_2, T_1' \times T_2']} \\ \begin{bmatrix} \mathsf{T}\text{-}\mathsf{CHOICE} \end{bmatrix} \qquad \frac{\mathcal{N}_1 : \Phi_{\mathcal{G},\xi}[T_1, T_2] \qquad \mathcal{N}_2 : \Phi_{\mathcal{G},\xi}[T_1, T_2]}{\mathcal{N}_1 \oplus \mathcal{N}_2 : \Phi_{\mathcal{G},\xi}[\mathbb{B} \times T_1, T_2]} \end{bmatrix}$$

$$[\mathsf{T}-\mathsf{STAR}] \qquad \qquad \frac{\mathcal{N}:\Phi_{\mathcal{G},\xi}[T,T]}{\mathcal{N}^{\star}:\Phi_{\mathcal{G},\xi}[T,T]}$$

Table 2. Typing rules of μG .

Theorem 7.1 (Type soundness). If $\mathcal{N} : \Phi_{\mathcal{G},\xi}[T_1, T_2], \eta : H[T_1] \text{ and } \langle \mathcal{N}, \eta \rangle \rightarrow^{\star}_{\mathcal{G},\xi} \eta', \text{ then } \eta' : H[T_2].$

PROOF. Follows from Lemma 7.2 (Progress) and Lemma 7.3 (Preservation).

LEMMA 7.2 (PROGRESS). Suppose that N is a well-typed term $N : \Phi_{\mathcal{G},\xi}[T_1, T_2]$ and that $\eta : H[T_1]$, then either $N = \iota$ or there exists \mathcal{N}', η' such that $\langle \mathcal{N}, \eta \rangle \rightarrow_{\mathcal{G}, \xi} \langle \mathcal{N}', \eta' \rangle$.

PROOF. By induction on typing derivations. It suffices to show that either $N = \iota$ or there exists an operational rule that can be applied.

Case T-ID: Immediate, as $\mathcal{N} = \iota$.

[T-

Case T-PSI: We have $\mathcal{N} = \psi$ and therefore can use rule APPLY.

Case T-PRE: We have $\mathcal{N} = \triangleleft_{\sigma}^{\varphi}$ and therefore can use rule PREIMG.

- **Case T-POST:** We have $\mathcal{N} = \triangleright_{\sigma}^{\varphi}$ and therefore can use rule POSTIMG.
- **Case T-SEQ:** We have $\mathcal{N} = \mathcal{N}_1$; \mathcal{N}_2 where $\mathcal{N}_1 : \Phi_{\mathcal{G},\xi}[T_1,T]$ and $\mathcal{N}_2 : \Phi_{\mathcal{G},\xi}[T,T_2]$. By induction hypothesis \mathcal{N}_1 is either i or it is possible to apply a transition rule. In the former case, we can apply rule SEQ₂, while in the latter case we can apply rule SEQ_1 .
- **Case T-PAR:** We have $\mathcal{N} = \mathcal{N}_1 || \mathcal{N}_2$ where $\mathcal{N}_1 : \Phi_{\mathcal{G},\xi}[T,T_1]$ and $\mathcal{N}_2 : \Phi_{\mathcal{G},\xi}[T,T_2]$. In this case, we can use rule SPLIT.

Case T-PROD: We have $\mathcal{N} = \mathcal{N}_1 \otimes \mathcal{N}_2$ where $\mathcal{N}_1 : \Phi_{\mathcal{G},\xi}[T_1, T_1']$ and $\mathcal{N}_2 : \Phi_{\mathcal{G},\xi}[T_2, T_2']$. By induction hypothesis \mathcal{N}_1 and \mathcal{N}_2 are either ι or is it possible to apply a transition rule. Then,

- if $N_1 = \iota$ and $N_2 = \iota$, we can apply rule MERGE.
- if $N_1 \neq i$ and $N_2 = i$, we can apply rule PAR₁.
- if $N_1 = \iota$ and $N_2 \neq \iota$, we can apply rule PAR₂.
- if $N_1 \neq i$ and $N_2 \neq i$, we can apply either rule PAR₁ or rule PAR₂.

Case T-CHOICE: We have $\mathcal{N} = \mathcal{N}_1 \oplus \mathcal{N}_2 : \Phi_{\mathcal{G},\xi}[\mathbb{B} \times T_1, T_2]$ where $\mathcal{N}_1 : \Phi_{\mathcal{G},\xi}[T_1, T_2]$ and $\mathcal{N}_2 : \Phi_{\mathcal{G},\xi}[T_1, T_2]$. Furthermore, we have that $\eta : H[\mathbb{B} \times T_1]$. If $\pi_L(\eta)$ is the constant node-labeling function that maps every node to True, we apply rule CHOICE₁. In any other case we apply rule CHOICE₂.

Case T-STAR: We have $\mathcal{N} = \mathcal{N}_1^*$ where $\mathcal{N}_1 : \Phi_{\mathcal{G},\xi}[T,T]$. We can apply rule STAR.

LEMMA 7.3 (PRESERVATION). If $\mathcal{N} : \Phi_{\mathcal{G},\xi}[T_1, T_2], \eta : H[T_1], and \langle \mathcal{N}, \eta \rangle \rightarrow_{\mathcal{G},\xi} \gamma$

- if $\gamma = \langle \mathcal{N}', \eta' \rangle$, then $\mathcal{N}' : \Phi_{\mathcal{G}, \xi}[T', T_2]$ and $\eta' : H[T']$.
- if $\gamma = \eta'$, then $\eta' : H[T_2]$.

PROOF. By induction on typing derivations.

Case T-ID: We have $\mathcal{N} = \iota : \Phi_{\mathcal{G},\xi}[T,T]$ and $\eta : H[T]$. The only applicable rule is ID by which $\langle \iota, \eta \rangle \to_{\mathcal{G},\xi} \eta : H[T]$. **Case T-PSI:** We have $\psi : \Phi_{\mathcal{G},\xi}[T_1,T_2]$ and $\eta : H[T_1]$. The only rule that can be applied is APPLY which gives $\mathcal{N}' = \iota$ and $\eta' = \lambda v. f_{\psi}([\eta(u) \mid u \in \mathcal{V}], \eta(v))$. Then η' has type $H[T_2]$ and ι has type $\Phi_{\mathcal{G},\xi}[T_2,T_2]$ by rule T-ID.

Case T-PRE: We have $\triangleleft_{\sigma}^{\varphi} : \Phi_{\mathcal{G},\xi}[T_1, T_3]$ and $\eta : H[T_1]$. The only rule that can be applied is PREIMG which gives $\mathcal{N}' = \iota$ and $\eta' = \lambda v.f_{\sigma}([f_{\varphi}(\eta(u), \xi((v, u)), \eta(v)) \mid u \in \overrightarrow{\mathcal{N}}(v)], \eta(v))$. Then η' has type $H[T_3]$ and ι has type $\Phi_{\mathcal{G},\xi}[T_3, T_3]$ by rule T-ID.

Case T-POST: Analogous to T-PRE, but using rule POSTIMG instead.

Case T-SEQ: We have $N_1; N_2 : \Phi_{\mathcal{G},\xi}[T_1, T_3]$ and $\eta : H[T_1]$. We also have sub-derivations with conclusions that $N_1 : \Phi_{\mathcal{G},\xi}[T_1, T_2]$ and $N_2 : \Phi_{\mathcal{G},\xi}[T_2, T_3]$. There are two possible rules that can be applied, SEQ₁ and SEQ₂.

- In the case of SEQ₁, we have N' = N'₁; N₂. By applying the induction hypothesis on N₁ we get that η' : H[T] and N'₁ : Φ_{G,ξ}[T, T₂] for some node-labeling type H[T]. Then we can apply rule T-SEQ on N'₁; N₂ to get its type Φ_{G,ξ}[T, T₃].
- In the case of SEQ₂, then $N_1 = \iota$, $T_2 = T_1$ and we have $N' = N_2$ which we know has type $\Phi_{\mathcal{G},\xi}[T_1, T_3]$, and $\eta' = \eta$ which we know has type $H[T_1]$.
- **Case T-PAR:** We have $N_1||N_2: \Phi_{\mathcal{G},\xi}[T, T_1 \times T_2]$ and $\eta: H[T]$. We also have sub-derivations with conclusions that $N_1: \Phi_{\mathcal{G},\xi}[T, T_1]$ and $N_2: \Phi_{\mathcal{G},\xi}[T, T_2]$. The only rule that can be applied is SPLIT. Then $\eta' = \eta | \eta: H[T \times T]$ and $N' = N_1 \otimes N_2$ which by rule T-PROD has type $\Phi_{\mathcal{G},\xi}[T \times T, T_1 \times T_2]$.
- **Case T-PROD:** We have $N_1 \otimes N_2 : \Phi_{\mathcal{G},\xi}[T_1 \times T_2, T'_1 \times T'_2]$ and $\eta : H[T_1 \times T_2]$. We also have sub-derivations with conclusions that $N_1 : \Phi_{\mathcal{G},\xi}[T_1, T'_1]$ and $N_2 : \Phi_{\mathcal{G},\xi}[T_2, T'_2]$. There are three possible rules that can be applied, PAR₁, PAR₂, and MERGE.
 - In the case of PAR₁, we have $\mathcal{N}' = \mathcal{N}'_1 \otimes \mathcal{N}_2$ and $\eta' = \eta_1 | \pi_R(\eta)$. By applying the induction hypothesis on \mathcal{N}_1 we get that $\eta_1 : H[T]$ and $\mathcal{N}'_1 : \Phi_{\mathcal{G},\xi}[T, T'_1]$ for some node-labeling type H[T]. Then we can apply rule T-Prod on $\mathcal{N}'_1 \otimes \mathcal{N}_2$ to get its type $\Phi_{\mathcal{G},\xi}[T \times T_2, T'_1 \times T'_2]$, and $\eta' : H[T \times T_2]$.
 - The case of PAR₂ is analogous to that of PAR₁.

- In the case of MERGE, we have $\mathcal{N}' = \iota$ and $\eta' = \eta$. Furthermore, this rule could have been applied only if $\mathcal{N}_1 = \mathcal{N}_2 = \iota$, which means that $T_1 = T'_1$ and $T_2 = T'_2$. Then by rule T-ID we get that $\iota : \Phi_{\mathcal{G},\xi}[T'_1 \times T'_2, T'_1 \times T'_2]$.
- **Case T-CHOICE:** We have $N_1 \oplus N_2 : \Phi_{\mathcal{G},\xi}[\mathbb{B} \times T_1, T_2]$ and $\eta : H[\mathbb{B} \times T_1]$. We also have sub-derivations with conclusions that $N_1 : \Phi_{\mathcal{G},\xi}[T_1, T_2]$ and $N_2 : \Phi_{\mathcal{G},\xi}[T_1, T_2]$. There are two possible rules that can be applied, CHOICE₁ and CHOICE₂.
 - In case CHOICE₁, we have $\eta' = \pi_R(\eta) : H[T_1]$ and $\mathcal{N}' = \mathcal{N}_1$ which we know to have type $\Phi_{\mathcal{G},\xi}[T_1, T_2]$.
 - In case CHOICE₂, we have $\eta' = \pi_R(\eta) : H[T_1]$ and $\mathcal{N}' = \mathcal{N}_2$ which we know to have type $\Phi_{G,\xi}[T_1, T_2]$.
- **Case T-STAR:** We have $\mathcal{N}^{\star} : \Phi_{\mathcal{G},\xi}[T,T]$ and $\eta : H[T]$. We also have a subderivation with the conclusion that $\mathcal{N} : \Phi_{\mathcal{G},\xi}[T,T]$. The only rule that can be applied is STAR. Then $\eta' = \eta : H[T]$ and $\mathcal{N}' = ((\iota||\mathcal{N}); \psi_{\cong}||\iota); (\iota \oplus \mathcal{N}; \mathcal{N}^{\star})$. By applying the typing rules we can conclude that this term also has type $\Phi_{\mathcal{G},\xi}[T,T]$.

8 A GRAPHICAL REPRESENTATION

In this section, we present a graphical representation for $\mu \mathcal{G}$ programs and expressions. Using such graphical notation makes it easier to understand and communicate the structure and purpose of a $\mu \mathcal{G}$ program, as the programmer might easily lose track of label types and sizes when developing in textual form. The basic terms of $\mu \mathcal{G}$ can be represented graphically as boxes, as shown in Figure 1, while the composite terms of the language are shown in Figure 2. Each term has exactly one input node-labeling and one output node-labeling, and the graphical representation is built top-down starting from the main (usually composite) term and substituting each box with either a basic term or a composite one; in this last case, this procedure is repeated recursively until all boxes in the figure are basic terms. As an illustrative example, let $\psi_1, \psi_2, \psi_3, \varphi, \sigma$ be function symbols. Figure 3 shows how we can represent graphically the $\mu \mathcal{G}$ expression $(\psi_1 || \psi_2); \psi_3; \triangleleft_{\sigma}^{\varphi}$.



Fig. 1. Graphical representation of basic μG expressions.

In the graphical representation for μG expressions we have used some auxiliary functions which we describe in turn:

- The function : *H*[*T*₁] → *H*[*T*₁] × *H*[*T*₁], •(η) = (η, η) maps a node-labeling function to a tuple containing two copies of itself.
- The function $\circ : H[T_1] \times H[T_2] \rightarrow H[T_1 \times T_2],$

$$\circ(\eta_1, \eta_2) = \begin{cases} \eta_1 & \text{if } \eta_2 = \eta_\perp \\ \eta_2 & \text{if } \eta_1 = \eta_\perp \\ \eta_1 | \eta_2 & \text{otherwise} \end{cases}$$

maps two node-labeling functions to a new node-labeling function which labels each node with the concatenation of their labels. If one of the input labeling functions is the empty labeling, \circ simply returns the other function.

Manuscript submitted to ACM



(a) The sequential composition of graph neural networks ϕ_1 and ϕ_2 .

(b) The parallel composition of graph neural networks ϕ_1 and ϕ_2 .



(c) The choice operator for the graph neural networks ϕ_1 and $\phi_2.$



(d) The star graph neural network that computes the fixed point of ϕ_1 .

Fig. 2. Graphical representation of the possible compositions of μG expressions.



Fig. 3. Example graphical representation of the $\mu \mathcal{G}$ expression $(\psi_1 || \psi_2); \psi_3; \triangleleft_{\sigma}^{\varphi}$.

• The function $\diamond: H[\mathbb{B} \times T_1] \to H[T_1] \times H[T_1],$

$$\diamond(\eta) = \begin{cases} (\pi_R(\eta), \eta_\perp) & \text{if } \pi_L(\eta) = \lambda v. \text{True} \\ (\eta_\perp, \pi_R(\eta)) & \text{otherwise} \end{cases}$$

takes a Boolean node-labeling function and another labeling function and propagates it in output as the first or second element of a tuple. If the Boolean labeling function maps every node to a true value, the other labeling function is propagated as the first element of the tuple (to be received in input by the GNN to be executed when the test is satisfied), otherwise it is returned as the second element of the tuple.

9 IMPLEMENTATION

The $\mu \mathcal{G}$ language has been implemented as a Python library called LIBMG, which we described in detail in a previous work [7]. The library was developed on top of Spektral [15], a graph neural network library based on Tensorflow [1]. The main advantage of using a framework such as TensorFlow is that $\mu \mathcal{G}$ programs are compiled to graph neural networks that can be executed seamlessly on CPUs, GPUs, or in a distributed setting without changing the source code.

The functionalities of LIBMG include the typical language support tools in the form of a parser, unparser and normalizer for $\mu \mathcal{G}$ expressions. The main functionality that is provided consists in the $\mu \mathcal{G}$ compiler that transforms a $\mu \mathcal{G}$ program into a TensorFlow Model instance. The compiler can be set up to automatically memoize sub-expressions that occur multiple times in the same program. The library also implements basic graph visualization functions, that allows to view in any web browser the input or output graphs, or intermediate representation produced by a $\mu \mathcal{G}$ model. Finally, a simple explanatory algorithm is provided that computes the sub-graph that was used by a $\mu \mathcal{G}$ model to compute the label of a given node.

Using LIBMG, the ψ, φ , and σ functions are defined by instantiating the corresponding classes and are stored in dictionaries. These dictionaries, which contain a mapping between function names and the functions themselves, are used to create a $\mu \mathcal{G}$ compiler instance. The $\mu \mathcal{G}$ compiler can then parse $\mu \mathcal{G}$ programs containing the function names defined in its dictionaries.

The models generated by the compiler can be trained by TensorFlow as usual. Only in the case of the star operator, the corresponding layer implements a custom gradient computation. In that case implicit differentiation is used as to make the computation of the gradient tractable.

10 EVALUATION

We evaluate μG both in terms of its expressiveness, meaning that it can be used to define most, if not all, of the graph neural network architectures that have been developed over the years, and also as a specification language for the development of graph neural networks for specific tasks. In Section 10.1 we describe an updated version of the CTL model checker developed using μG introduced in our previous work [6, 7]. Then, in Section 10.2, we show how to define some of the more well-known GNN architectures using our language.

10.1 Model Checking

We evaluated μG in a previous work by using it to define a GNN that performs CTL model checking on Kripke structures. For that use case, the set of functions that we used is shown in Table 3, while in Table 4 we show the translation function from CTL to the μG expression denoting the GNN that verifies it.

The $\mu \mathcal{G}$ model checker implementation was compared to two other explicit-state model checkers, pyModelChecking¹ and mCRL2 [9]. We used some of the benchmarks from the Model Checking Contest 2022 [2], namely those for which we could explicitly generate the reachability graph on our machine, shown in Table 5. The $\mu \mathcal{G}$ model checker was set up to either verify all the formulas in parallel (the *full* setup), or one by one as would have been the case for the other model checkers (the *split* setup). In the former case, there would have been additional advantages due to the memoization of common sub-formulas across multiple formulas. The experimental results are shown in Figure 4, and we notice that for the larger Kripke structures there is an evident speed advantage of $\mu \mathcal{G}$ compared to the other model checkers (in some instances, by an order of magnitude).

¹https://github.com/albertocasagrande/pyModelChecking

Manuscript submitted to ACM

$$\begin{split} \psi_{p} : (2^{AP})^{\star} \times 2^{AP} \to \mathbb{B} \qquad \psi_{p}(X, x) = \begin{cases} \text{True} & \text{if } p \in x \\ \text{False} & \text{otherwise} \end{cases} \\ \forall p \in AP) \\ \psi_{tt} : (2^{AP})^{\star} \times 2^{AP} \to \mathbb{B} \qquad \psi_{tt}(X, x) = \text{True} \\ \psi_{ff} : (2^{AP})^{\star} \times 2^{AP} \to \mathbb{B} \qquad \psi_{ff}(X, x) = \text{False} \\ \psi_{\gamma} : (\mathbb{B})^{\star} \times \mathbb{B} \to \mathbb{B} \qquad \psi_{\gamma}(X, x) = -x \\ \psi_{\wedge} : (\mathbb{B}^{2})^{\star} \times \mathbb{B}^{2} \to \mathbb{B} \qquad \psi_{\wedge}(X, x) = x_{1} \wedge x_{2} \\ \psi_{\vee} : (\mathbb{B}^{2})^{\star} \times \mathbb{B}^{2} \to \mathbb{B} \qquad \psi_{\vee}(X, x) = x_{1} \vee x_{2} \\ \varphi_{id} : \mathbb{B} \times () \times \mathbb{B} \to \mathbb{B} \qquad \varphi_{id}(i, e, j) = i \\ \sigma_{\vee} : \mathbb{B}^{\star} \times \mathbb{B} \to \mathbb{B} \qquad \sigma_{\vee}(M, x) = \bigvee_{i} M_{i} \end{split}$$

Table 3. The ψ, φ , and σ functions used for CTL model checking. The subscripts indicate the function symbols that will be used in the $\mu \mathcal{G}$ expressions. For each $p \in AP$, we consider a corresponding function ψ_p .

$$\begin{split} \mathcal{M}(p) &= p \\ \mathcal{M}(\neg \phi) &= \mathcal{M}(\phi); \neg \\ \mathcal{M}(\phi_1 \land \phi_2) &= (\mathcal{M}(\phi_1) || \mathcal{M}(\phi_2)); \land \\ \mathcal{M}(\mathsf{EX} \ \phi) &= \mathcal{M}(\phi); \triangleright^{id}_{\vee} \\ \mathcal{M}(\mathsf{EG} \ \phi) &= \mathsf{fix} \ X = tt \ \mathsf{in} \ (\mathcal{M}(\phi) || X; \triangleright^{id}_{\vee}); \land \\ \mathcal{M}(\mathsf{E} \ \phi_1 \cup \phi_2) &= \mathsf{fix} \ X = ff \ \mathsf{in} \ (\mathcal{M}(\phi_2) || (\mathcal{M}(\phi_1) || X; \triangleright^{id}_{\vee}); \lor); \land \end{split}$$

Table 4. Recursive definition of the translation function $\mathcal{M}: \phi \to \mathcal{N}$.

ID	Petri Net	#nodes in RG	#edges in RG
1	RobotManipulation-PT-00001	110	274
2	TokenRing-PT-005	166	365
3	Philosophers-PT-000005	243	945
4	RobotManipulation-PT-00002	1430	5 500
5	Dekker-PT-010	6144	171 530
6	BART-PT-002	17 424	53 328
7	ClientsAndServers-PT-N0001P0	27 576	113 316
8	Philosophers-PT-000010	59 049	459 270
9	Referendum-PT-0010	59 050	393 661
10	SatelliteMemory-PT-X00100Y0003	76 358	209 484
11	RobotManipulation-PT-00005	184 756	1 137 708
12	Dekker-PT-015	278 528	16 834 575
13	HouseConstruction-PT-00005	1 187 984	7 191 110

Table 5. Petri net models used for the experiments, for which we reported here the number of nodes and edges in the reachability graph (RG).

10.2 Specification of Graph Neural Networks

In this section, we show how to define some of the most popular graph neural network models in μG . As is the case for any programming language, there are many different ways to obtain the same result, therefore the implementations Manuscript submitted to ACM



Fig. 4. Execution times of $\mu \mathcal{G}$ (split and full setups), pyModelChecking, and mCRL2 across 13 Petri net models from the Model Checking Contest 2022. The y-axis is on a logarithmic scale. On the twelfth Petri net, the red bar indicates that the $\mu \mathcal{G}$ model ran out of memory after the pre-processing (tracing) step.

that we show here are only intended to highlight the generality of the language. For specific use cases, it is up to the programmer to choose the most useful μG implementation.

Graph Convolutional Networks. A Graph Convolutional Network [21] (GCN) performs a graph convolution by multiplying the node features with a matrix of weights, normalized according to the degree of the nodes and assigning greater importance to the features received from nodes with fewer neighbors. The new node labels $x'_i \in \mathbb{R}^m$ are computed from the current node labels $x_i \in \mathbb{R}^n$ according to the equation

$$x'_{i} = f\left(\sum_{j \in N_{\mathcal{G}}(i) \cup \{i\}} \frac{x_{j}\Theta}{\sqrt{deg(i)}\sqrt{deg(j)}}\right)$$

where deg(i) is the degree of node i, $\Theta \in \mathbb{R}^{n \times m}$ is a matrix of trainable weights, and f is an activation function. The set of neighbors of a node include both the predecessors and the successors, as the GCN was originally thought for the case of undirected graphs. To implement the GCN, we make use of the functions shown in Table 6. We start by defining a $\mu \mathcal{G}$ expression to compute the degree of each node. We recall that the degree of a node is the number of its outgoing edges (the *outdegree*) plus the number of incoming edges (the *indegree*), with self loops counting as both. It is easy to compute this number in $\mu \mathcal{G}$: we use \triangleleft_1^4 to compute the indegree and \triangleright_1^4 to compute the outdegree, then we add them.

 $(\triangleleft^{1}_{+}|| \triangleright^{1}_{+});+_{2}$

$$\begin{split} \psi_{NN} &: (\mathbb{R}^n)^{\star} \times \mathbb{R}^n \to \mathbb{R}^m & \psi_{NN}(X, x) = f(x^T \Theta) \\ \psi_{+_2} &: (\mathbb{R}^2)^{\star} \times \mathbb{R}^2 \to \mathbb{R} & \psi_{+_2}(X, x) = x_1 + x_2 \\ \psi_{+_{2n}} &: (\mathbb{R}^{2n})^{\star} \times \mathbb{R}^{2n} \to \mathbb{R}^n & \psi_{+_{2n}}(X, x) = x_1 + x_2 \\ \varphi_{1} &: \mathbb{R}^n \times \mathbb{R} \times \mathbb{R}^n \to \mathbb{R} & \varphi_{1}(i, e, j) = 1 \\ \varphi_{dgn} &: \mathbb{R}^{n+1} \times \mathbb{R} \times \mathbb{R}^{n+1} \to \mathbb{R}^n & \varphi_{dgn}(i, e, j) = \frac{i_2}{\sqrt{i_1}\sqrt{j_1}} \\ \sigma_{+} &: \mathbb{R}^{\star} \times \mathbb{R}^n \to \mathbb{R} & \sigma_{+}(M, x) = 1 + \sum_i M_i \\ \sigma_{dg+} &: (\mathbb{R}^n)^{\star} \times \mathbb{R}^{n+1} \to \mathbb{R}^n & \sigma_{dg+}(M, x) = \frac{x_2}{x_1} + \sum_i M_i \\ \text{Table 6. Functions used in the definition of the GCN. } \end{split}$$

In the steps that follow, we need the degree of nodes but also the original labels, therefore we use parallel composition with ι to have both these values.

$$(\triangleleft^{1}_{+}|| \triangleright^{1}_{+});+_{2}||_{l}$$

Then we compute $\sum_{j \in N_{\mathcal{G}}(i) \cup \{i\}} \frac{x_j}{\sqrt{deg(i)}\sqrt{deg(j)}}$ by summing the pre-image and the post-image using dgn and dg+

$$((\triangleleft_{+}^{1}|| \bowtie_{+}^{1});+_{2}||_{\iota});(\triangleleft_{dg+}^{dgn}|| \bowtie_{dg+}^{dgn});+_{2n}$$

Note that both φ_{dgn} and σ_{dg+} expect node labels $l \in \mathbb{R}^{n+1}$, where $l_1 \in \mathbb{R}$ is the degree of the node and $l_2 \in \mathbb{R}^n$ is the actual label of the node. Finally, we multiply the node labels with the weight matrix Θ followed by the application of the activation function f, i.e., the classic dense neural network layer. Putting all of this together, the $\mu \mathcal{G}$ expression that implements a GCN layer is

$$((\triangleleft^{1}_{+}|| \rhd^{1}_{+});+_{2}|| \iota);(\triangleleft^{dgn}_{dg+}|| \rhd^{dgn}_{dgr+});+_{2n};NN$$

Graph Attention Networks. A Graph Attention Network [34] (GAT), like the GCN, transforms the node labels using a learnable weight matrix $\Theta \in \mathbb{R}^{n \times m}$. Then it employs a self-attention mechanism $a : \mathbb{R}^m \times \mathbb{R}^m \to \mathbb{R}$, shared by all the nodes, that given the labels of node j and node i such that $(j, i) \in \mathcal{E}$, it indicates the importance of node j's labels to node i. This value is then normalized using the softmax function. In the original formulation, the attention mechanism is a single-layer feedforward neural network which uses a weight vector $\mathbf{a} \in \mathbb{R}^{2m}$ and the LeakyReLU activation function. Therefore, the attention coefficients α_{ji} are given by

$$\alpha_{ji} = \frac{exp\left(LeakyReLU\left(\mathbf{a}^{T}(x_{i}\Theta, x_{j}\Theta)\right)\right)}{\sum_{k \in \widetilde{N}_{G}(i) \cup \{i\}} exp\left(LeakyReLU\left(\mathbf{a}^{T}(x_{i}\Theta, x_{k}\Theta)\right)\right)}$$

Given these attention coefficients, the GAT layer computes the new node labels $x'_i \in \mathbb{R}^m$ from the current labels $x_i \in \mathbb{R}^n$ according to the equation

$$x_i' = f\left(\sum_{j \in \overleftarrow{N}_{\mathcal{G}}(i) \cup \{i\}} \alpha_{ji} x_j \Theta\right)$$

where f is the activation function. The authors then extend this basic mechanism by employing multi-head attention, that is, they define K independent attention heads and weight matrices whose outputs are then concatenated. Thus, we get

$$x_i' = \left\|_{k=1}^K f\left(\sum_{j \in \widetilde{N}_{\mathcal{G}}(i) \cup \{i\}} \alpha_{ji}^k x_j \Theta^k\right)\right.$$

Belenchia et al.

$$\begin{split} & \psi_{NN_i} : (\mathbb{R}^n)^{\star} \times \mathbb{R}^n \to \mathbb{R}^m & \psi_{NN_i}(X, x) = f(x\Theta^i) \\ & \psi_{j} : (\mathbb{R}^{n+1})^{\star} \times \mathbb{R}^{n+1} \to \mathbb{R}^n & \psi_{j}(X, x) = \frac{x_1}{x_2} \\ & \varphi_{att*_i} : \mathbb{R}^n \times \mathbb{R} \times \mathbb{R}^n \to \mathbb{R}^n & \varphi_{att*_i}(i, e, j) = exp(LeakyReLU(\mathbf{a}_i \cdot (i^T\Theta^i, j^T\Theta^i))) \cdot i \\ & \varphi_{att_i} : \mathbb{R}^n \times \mathbb{R} \times \mathbb{R}^n \to \mathbb{R} & \varphi_{att_i}(i, e, j) = exp(LeakyReLU(\mathbf{a}_i \cdot (i^T\Theta^i, j^T\Theta^i))) \\ & \sigma_{t-att_i} : \mathbb{R}^{\star} \times \mathbb{R}^n \to \mathbb{R} & \sigma_{t-att_i}(M, x) = exp(LeakyReLU(\mathbf{a}_i \cdot (x^T\Theta^i, x^T\Theta^i))) + \sum_j M_j \\ & \sigma_{n-att_i} : (\mathbb{R}^n)^{\star} \times \mathbb{R}^n \to \mathbb{R}^n & \sigma_{n-att_i}(M, x) = exp(LeakyReLU(\mathbf{a}_i \cdot (x^T\Theta^i, x^T\Theta^i))) \cdot x + \sum_j M_j \\ & \text{Table 7. Functions used in the definition of GAT convolutions.} \end{split}$$

The functions needed to implement the GAT layer are shown in Table 7. First, we compute the unnormalized attention coefficients and multiply them with the node labels, using the term $\triangleleft_{n-att_1}^{att*_1}$. Then to normalize them, we compute in parallel the total attention values for incoming edges at each node using $\triangleleft_{t-att_1}^{att_1}$, and divide the labels of the first expression by this expression

$$(\triangleleft_{n-att_1}^{att*_1} || \triangleleft_{t-att_1}^{att_1}); /$$

At this point, we simply have to multiply by the weight matrix and apply the activation function to get the basic GAT layer

$$(\triangleleft_{n-att_{1}}^{att*_{1}} || \triangleleft_{t-att_{1}}^{att_{1}}); /; NN_{1}$$

Now we show how to use multi-head attention. We save the previous expression in k different variables using let expressions, such that each expression gets its own attention mechanism and weight matrix. Then the body of the let expression is simply the parallel composition of these variables

let
$$GAT_1 = (\triangleleft_{n-att_1}^{att_{n-1}} || \triangleleft_{t-att_1}^{att_1}); /; NN_1,$$

$$\vdots$$
 $GAT_k = (\triangleleft_{n-att_k}^{att_{k-att_k}} || \triangleleft_{t-att_k}^{att_k}); /; NN_k \text{ in }$
 $GAT_1 || GAT_2 || \cdots || GAT_k$

Graph Isomorphism Networks. A Graph Isomorphism Network [36] (GIN) generalizes the Weisfeiler-Lehman test [35] and thus has the greatest discriminative power among GNNs for determining whether two graphs are not isomorphic. The GIN convolution consists in multiplying each node label by $(1+\epsilon)$, where $\epsilon \in \mathbb{R}$ is a trainable parameter, then adding the sum of the labels of the neighbor nodes. The obtained values are then passed in input to a multilayer perceptron (MLP), that is, it gets multiplied with a learnable weight matrix Θ^i followed by the application of an activation function f_i two or more times in sequence. Formally, the GIN computes the new node labels $x'_i \in \mathbb{R}^m$ from the current labels $x_i \in \mathbb{R}^n$ as

$$x'_i = MLP((1 + \epsilon) \cdot x_i + \sum_{j \in \overleftarrow{N}_{\mathcal{G}}(i)} x_j)$$

In Table 8 we show the functions we need to implement the GIN layer in μG . We use parallel composition to compute the product of the node labels with 1 + ϵ and the sum of the labels of the neighbors of each node, then we add them using +.

$$(*\epsilon || \triangleleft^{id}_{+}); +$$

Finally, we put in sequence two dense neural network layers with weight matrices $\Theta^1 \in \mathbb{R}^{n \times n'}, \Theta^2 \in \mathbb{R}^{n' \times m}$ and activation functions f_1, f_2 , as in the case of the original GIN article. Therefore, the $\mu \mathcal{G}$ expression that implements a Manuscript submitted to ACM

28

$$\begin{split} \psi_{NN_1} &: (\mathbb{R}^n)^{\star} \times \mathbb{R}^n \to \mathbb{R}^{n'} & \psi_{NN_1}(X, x) = f_1(x\Theta^1) \\ \psi_{NN_2} &: (\mathbb{R}^{n'})^{\star} \times \mathbb{R}^{n'} \to \mathbb{R}^m & \psi_{NN_2}(X, x) = f_2(x\Theta^2) \\ \psi_{*\epsilon} &: (\mathbb{R}^n)^{\star} \times \mathbb{R}^n \to \mathbb{R}^n & \psi_{*\epsilon}(X, x) = (w_{\epsilon} + 1) \cdot x \\ \psi_{+} &: (\mathbb{R}^{2n})^{\star} \times \mathbb{R}^{2n} \to \mathbb{R}^n & \psi_{+}(X, x) = x_1 + x_2 \\ \varphi_{id} &: \mathbb{R}^n \times \mathbb{R} \times \mathbb{R}^n \to \mathbb{R}^n & \varphi_{*}(i, e, j) = i \\ \sigma_{+} &: (\mathbb{R}^n)^{\star} \times \mathbb{R}^n \to \mathbb{R}^n & \sigma_{+}(M, x) = \sum_i M_i \\ \text{Table 8. Functions used in the definition of GIN convolutions.} \end{split}$$

$$\begin{split} \psi_{MLP_2} &: (\mathbb{R}^{n+k})^{\star} \times \mathbb{R}^{n+k} \to \mathbb{R}^m \qquad \psi_{MLP_2}(X, x) = f_4(f_3(x\Theta^3)\Theta^4) \\ \psi_0 &: (\mathbb{R}^n)^{\star} \times \mathbb{R}^n \to \mathbb{R}^k \qquad \psi_0(X, x) = \mathbf{0}_k \\ \varphi_{MLP_1} &: \mathbb{R}^{n+k} \times \mathbb{R} \times \mathbb{R}^{n+k} \to \mathbb{R}^k \qquad \varphi_{MLP_1}(i, e, j) = f_2(f_1((\pi_L(j), e, i)\Theta^1)\Theta^2) \\ \sigma_+ &: (\mathbb{R}^k)^{\star} \times \mathbb{R}^k \to \mathbb{R}^k \qquad \sigma_+(M, x) = \sum_i M_i \\ \text{Table 9. Functions used in the definition of the original GNN convolution.} \end{split}$$

GIN is

$$(*\epsilon || \triangleleft_+^{id}); +; NN_1; NN_2$$

The Original Graph Neural Network Model. The graph neural network model was first introduced by Scarselli et al. [30]. The new node labels $x'_i \in \mathbb{R}^m$ of the original GNN model are computed as a two-step process. In the first step the new "state" $s'_i \in \mathbb{R}^k$ of each node is computed from the current node labels $x_i \in \mathbb{R}^n$, the edge labels $e_{ji} \in \mathbb{R}^l$, and the neighbor nodes' labels $x_i \in \mathbb{R}^n$ and states $s_i \in \mathbb{R}^k$ as the fixed point of the equation

$$s_i = \sum_{j \in \overleftarrow{N}_{\mathcal{G}}(i)} h(x_i, e_{ji}, x_j, s_j)$$

where *h* is typically a two-layer perceptron with weight matrices $\Theta^1 \in \mathbb{R}^{(2n+l+k)\times n'}, \Theta^2 \in \mathbb{R}^{n'\times k}$ and activation functions f_1, f_2 . Then, the second step consists in the application of a function *g* to the state and labels of each node to obtain the final node labels

$$x_i' = g(x_i, s_i)$$

where in this case too *g* is a two-layer perceptron, with weight matrices $\Theta^3 \in \mathbb{R}^{(n+k) \times m'}, \Theta^4 \in \mathbb{R}^{m' \times m}$ and activation functions f_3, f_4 . In Table 9 we show the functions required to implement this GNN layer. The first step consists in initializing the node states. For this example, we initialize the node states to an array of *k* zeros and we append it to the current node labels using the identity term and parallel composition

$$(\iota || 0)$$

After this step, we compute the fixed point of the states using a two-layer perceptron to generate messages and aggregating them through summation

$$(\iota || 0); (\iota || \triangleleft_{+}^{MLP_1})^{\star}$$

Once a fixed point for the states is reached, we use another multi-layer perceptron to obtain the final node labels and obtain

$$(\iota || 0); (\iota || \triangleleft_+^{MLP_1})^{\star}; MLP_2$$

11 CONCLUSION

We presented the syntax and semantics of $\mu \mathcal{G}$, a novel programming language for the definition of graph neural networks, where a graph neural network is characterized as a higher-order function $\phi : H[T_1] \rightarrow H[T_2]$. We proved the type soundness of $\mu \mathcal{G}$ and shown a graphical formalism for the representation of $\mu \mathcal{G}$ programs. The language was implemented as a Python library built on the TensorFlow framework. We evaluated $\mu \mathcal{G}$ on the application of CTL model checking and as a means to specify some of the most popular graph neural network models.

In future implementations, we plan to expand the language in a number of ways. A typical graph neural network operation that is still overlooked in μG is pooling. A pooling operator changes the underlying graph by reducing the number of nodes, producing a coarsened version of a graph. Graph pooling operators can be generally described in terms of the operations of selection, reduction, and connection [16]. The selection operator groups nodes together, the reduction operator aggregates the nodes in each group into a single node, and finally the connection operator generates the edges to link the newly generated nodes. The introduction of pooling operators requires careful consideration of how they can be composed with the existing terms, but it would allow μG to tackle graph-level tasks explicitly.

The main purpose for developing μG is to be eventually able to perform formal verification of graph neural networks and generate explanations for their outputs. For the time being, there are still no procedures that allow the verification of output reachability properties of GNNs [33]. In the future, we aim to define an abstract interpretation approach for these tasks.

REFERENCES

- [1] Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dandelion Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. 2015. TensorFlow: Large-Scale Machine Learning on Heterogeneous Systems. https://www.tensorflow.org/ Software available from tensorflow.org.
- [2] Elvio Amparore, Bernard Berthomieu, Gianfranco Ciardo, Silvano Dal Zilio, Francesco Gallà, Lom Messan Hillah, Francis Hulin-Hubard, Peter Gjøl Jensen, Loïg Jezequel, Fabrice Kordon, Didier Le Botlan, Torsten Liebke, Jeroen Meijer, Andrew Miner, Emmanuel Paviot-Adet, Jiří Srba, Yann Thierry-Mieg, Tom van Dijk, and Karsten Wolf. 2019. Presentation of the 9th Edition of the Model Checking Contest. In *Tools and Algorithms for the Construction and Analysis of Systems*, Dirk Beyer, Marieke Huisman, Fabrice Kordon, and Bernhard Steffen (Eds.). Springer International Publishing, Cham, 50–68. https://doi.org/10.1007/978-3-030-17502-3_4
- [3] Anish Athalye, Logan Engstrom, Andrew Ilyas, and Kevin Kwok. 2018. Synthesizing Robust Adversarial Examples. arXiv:1707.07397 [cs.CV]
- [4] Enrico Barbierato and A. Gatti. 2024. The Challenges of Machine Learning: A Critical Review. ELECTRONICS 13 (2024), 1–30. https://doi.org/10. 3390/electronics13020416
- [5] Peter W. Battaglia, Jessica B. Hamrick, Victor Bapst, Alvaro Sanchez-Gonzalez, Vinicius Zambaldi, Mateusz Malinowski, Andrea Tacchetti, David Raposo, Adam Santoro, Ryan Faulkner, Caglar Gulcehre, Francis Song, Andrew Ballard, Justin Gilmer, George Dahl, Ashish Vaswani, Kelsey Allen, Charles Nash, Victoria Langston, Chris Dyer, Nicolas Heess, Daan Wierstra, Pushmeet Kohli, Matt Botvinick, Oriol Vinyals, Yujia Li, and Razvan Pascanu. 2018. Relational inductive biases, deep learning, and graph networks. https://doi.org/10.48550/arXiv.1806.01261 arXiv:1806.01261 [cs, stat].
- [6] Matteo Belenchia, Flavio Corradini, Michela Quadrini, and Michele Loreti. 2023. Implementing a CTL Model Checker with μG, a Language for Programming Graph Neural Networks. In Formal Techniques for Distributed Objects, Components, and Systems (Lecture Notes in Computer Science), Marieke Huisman and António Ravara (Eds.). Springer Nature Switzerland, Cham, 37–54. https://doi.org/10.1007/978-3-031-35355-0_4
- [7] Matteo Belenchia, Flavio Corradini, Michela Quadrini, and Michele Loreti. 2024. LIBMG: a Python Library for Programming Graph Neural Networks in μG. (2024). Accepted with minor revisions for publication to Science of Computer Programming.
- [8] Michael M. Bronstein, Joan Bruna, Taco Cohen, and Petar Veličković. 2021. Geometric Deep Learning: Grids, Groups, Graphs, Geodesics, and Gauges. arXiv:2104.13478 [cs.LG]
- [9] Olav Bunte, Jan Friso Groote, Jeroen J. A. Keiren, Maurice Laveaux, Thomas Neele, Erik P. de Vink, Wieger Wesselink, Anton Wijs, and Tim A. C. Willemse. 2019. The mCRL2 Toolset for Analysing Concurrent Systems. In Tools and Algorithms for the Construction and Analysis of Systems, Tomáš Vojnar and Lijun Zhang (Eds.). Springer International Publishing, Cham, 21–39. https://doi.org/10.1007/978-3-030-17465-1_2

- [10] Gabriele Corso, Hannes Stark, Stefanie Jegelka, Tommi Jaakkola, and Regina Barzilay. 2024. Graph neural networks. Nature Reviews Methods Primers 4, 1 (07 Mar 2024), 17. https://doi.org/10.1038/s43586-024-00294-7
- [11] Venmugil Elango, Norm Rubin, Mahesh Ravishankar, Hariharan Sandanagobalane, and Vinod Grover. 2018. Diesel: DSL for linear algebra and neural net computations on GPUs. In Proceedings of the 2nd ACM SIGPLAN International Workshop on Machine Learning and Programming Languages (MAPL 2018). Association for Computing Machinery, New York, NY, USA, 42–51. https://doi.org/10.1145/3211346.3211354
- [12] Kevin Eykholt, Ivan Evtimov, Earlence Fernandes, Bo Li, Amir Rahmati, Chaowei Xiao, Atul Prakash, Tadayoshi Kohno, and Dawn Song. 2018. Robust Physical-World Attacks on Deep Learning Models. arXiv:1707.08945 [cs.CR]
- [13] Vicente García Díaz, Jordán Espada, B. Pelayo García-Bustelo, and Juan Cueva Lovelle. 2015. Towards a Standard-based Domain-specific Platform to Solve Machine Learning-based Problems. International Journal of Artificial Intelligence and Interactive Multimedia 3 (Jan. 2015), 6–12. https: //doi.org/10.9781/ijimai.2015.351
- [14] Justin Gilmer, Samuel S. Schoenholz, Patrick F. Riley, Oriol Vinyals, and George E. Dahl. 2017. Neural message passing for Quantum chemistry. In Proceedings of the 34th International Conference on Machine Learning - Volume 70 (ICML'17). JMLR.org, Sydney, NSW, Australia, 1263–1272.
- [15] Daniele Grattarola and Cesare Alippi. 2020. Graph Neural Networks in TensorFlow and Keras with Spektral. IEEE Comput. Intell. Mag. 16 (2020), 99–106. https://doi.org/10.1109/mci.2020.3039072
- [16] Daniele Grattarola, Daniele Zambon, Filippo Maria Bianchi, and Cesare Alippi. 2022. Understanding Pooling in Graph Neural Networks. IEEE Transactions on Neural Networks and Learning Systems 35, 2 (July 2022), 2708–2718. https://doi.org/10.1109/TNNLS.2022.3190922 Conference Name: IEEE Transactions on Neural Networks and Learning Systems.
- [17] Sicong Han, Chenhao Lin, Chao Shen, Qian Wang, and Xiaohong Guan. 2023. Interpreting Adversarial Examples in Deep Learning: A Review. ACM Comput. Surv. 55, 14s, Article 328 (jul 2023), 38 pages. https://doi.org/10.1145/3594869
- [18] Xiaowei Huang, Daniel Kroening, Wenjie Ruan, James Sharp, Youcheng Sun, Emese Thamo, Min Wu, and Xinping Yi. 2020. A Survey of Safety and Trustworthiness of Deep Neural Networks: Verification, Testing, Adversarial Attack and Defence, and Interpretability. http://arxiv.org/abs/1812.08342 arXiv:1812.08342 [cs].
- [19] Benjamin Jahić, Nicolas Guelfi, and Benoît Ries. 2023. SEMKIS-DSL: A Domain-Specific Language to Support Requirements Engineering of Datasets and Neural Network Recognition. *Information* 14, 4 (April 2023), 213. https://doi.org/10.3390/info14040213 Number: 4 Publisher: Multidisciplinary Digital Publishing Institute.
- [20] Michael Kearns. 1998. Efficient noise-tolerant learning from statistical queries. J. ACM 45, 6 (Nov. 1998), 983–1006. https://doi.org/10.1145/293347. 293351
- [21] Thomas N. Kipf and Max Welling. 2017. Semi-Supervised Classification with Graph Convolutional Networks. arXiv:1609.02907 [cs.LG]
- [22] Luís C. Lamb, Artur d'Avila Garcez, Marco Gori, Marcelo O.R. Prates, Pedro H.C. Avelar, and Moshe Y. Vardi. 2020. Graph Neural Networks Meet Neural-Symbolic Computing: A Survey and Perspective. In Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, IJCAI-20, Christian Bessiere (Ed.). International Joint Conferences on Artificial Intelligence Organization, Yokohama, Yokohama, Japan, 4877–4884. https://doi.org/10.24963/ijcai.2020/679 Survey track.
- [23] Gary Marcus. 2018. Deep Learning: A Critical Appraisal. arXiv:1801.00631 http://arxiv.org/abs/1801.00631
- [24] Gary Marcus. 2018. Innateness, AlphaZero, and Artificial Intelligence. arXiv:1801.05667 [cs.AI]
- [25] Gary Marcus. 2020. The Next Decade in AI: Four Steps Towards Robust Artificial Intelligence. https://arxiv.org/abs/2002.06177v3 arXiv: 2002.06177.
- [26] Christopher Morris, Matthias Fey, and Nils Kriege. 2021. The Power of the Weisfeiler-Leman Algorithm for Machine Learning with Graphs. In Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence. ijcai.org, Montreal, Canada, 4543–4550. https://doi.org/10.24963/ ijcai.2021/618 Conference Name: Thirtieth International Joint Conference on Artificial Intelligence {IJCAI-21} ISBN: 9780999241196 Place: Montreal, Canada Publisher: International Joint Conferences on Artificial Intelligence Organization.
- [27] Artur Podobas, Martin Svedin, Steven W. D. Chien, Ivy B. Peng, Naresh Balaji Ravichandran, Pawel Herman, Anders Lansner, and Stefano Markidis. 2021. StreamBrain: An HPC Framework for Brain-like Neural Networks on CPUs, GPUs and FPGAs. In *Proceedings of the 11th International Symposium on Highly Efficient Accelerators and Reconfigurable Technologies* (Online, Germany) (*HEART '21*). Association for Computing Machinery, New York, NY, USA, Article 8, 6 pages. https://doi.org/10.1145/3468044.3468052
- [28] Ivens Portugal, Paulo Alencar, and Donald Cowan. 2016. A Preliminary Survey on Domain-Specific Languages for Machine Learning in Big Data. In 2016 IEEE International Conference on Software Science, Technology and Engineering (SWSTE). IEEE, Beer Sheva, Israel, 108–110. https: //doi.org/10.1109/SWSTE.2016.23
- [29] Iqbal H. Sarker. 2021. Deep Learning: A Comprehensive Overview on Techniques, Taxonomy, Applications and Research Directions. SN Computer Science 2, 6 (18 Aug 2021), 420. https://doi.org/10.1007/s42979-021-00815-1
- [30] Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. 2009. The Graph Neural Network Model. IEEE Transactions on Neural Networks 20, 1 (Jan. 2009), 61–80. https://doi.org/10.1109/TNN.2008.2005605 Conference Name: IEEE Transactions on Neural Networks.
- [31] Arvind K. Sujeeth, HyoukJoong Lee, Kevin J. Brown, Hassan Chafi, Michael Wu, Anand R. Atreya, Kunle Olukotun, Tiark Rompf, and Martin Odersky. 2011. OptiML: an implicitly parallel domain-specific language for machine learning. In Proceedings of the 28th International Conference on International Conference on Machine Learning (ICML'11). Omnipress, Madison, WI, USA, 609–616.
- [32] Zachary Susskind, Bryce Arden, Lizy K. John, Patrick Stockton, and Eugene B. John. 2021. Neuro-Symbolic AI: An Emerging Class of AI Workloads and their Characterization. arXiv:2109.06133 https://arxiv.org/abs/2109.06133

- [33] Marco Sälzer and Martin Lange. 2022. Fundamental Limits in Formal Verification of Message-Passing Neural Networks. https://openreview.net/ forum?id=WlbG820mRH-
- [34] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. 2018. Graph Attention Networks. arXiv:1710.10903 [stat.ML]
- [35] Boris Yulievich Weisfeiler and Andrey Aleksandrovich Leman. 1968. The Reduction of a Graph to Canonical Form and the Algebra which Appears therein. Nauchno-Technicheskaya Informatsia 9 (1968), 12 – 16.
- [36] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. 2019. How Powerful are Graph Neural Networks? arXiv:1810.00826 [cs.LG]
- [37] Tian Zhao, Xiaobing Huang, and Yu Cao. 2017. DeepDSL: A Compilation-based Domain-Specific Language for Deep Learning. arXiv:1701.02284 [cs.PL]
- [38] Jie Zhou, Ganqu Cui, Shengding Hu, Zhengyan Zhang, Cheng Yang, Zhiyuan Liu, Lifeng Wang, Changcheng Li, and Maosong Sun. 2020. Graph neural networks: A review of methods and applications. AI Open 1 (Jan. 2020), 57–81. https://doi.org/10.1016/j.aiopen.2021.01.001

Received 20 February 2007; revised 12 March 2009; accepted 5 June 2009