A novel multi-threaded web crawling model

Author: Weijie Jiang Institution: Shanghai Maritime University

July 16, 2024

Abstract

This paper proposes a novel model for web crawling suitable for large-scale web data acquisition. This model first divides web data into several sub-data, with each sub-data corresponding to a thread task. In each thread task, web crawling tasks are concurrently executed, and the crawled data are stored in a buffer queue, awaiting further parsing. The parsing process is also divided into several threads. By establishing the model and continuously conducting crawler tests, it is found that this model is significantly optimized compared to single-threaded approaches.

1 INTRODUCTION

With the rapid development of the Internet, the volume of online information is experiencing explosive growth. Consequently, the demand for effective acquisition and management of online information is becoming increasingly urgent.

Web crawlers can automatically retrieve various types of information from the Internet. For individual users, web crawlers help users quickly access and integrate massive information resources. For enterprises, the role of web crawlers enables them to obtain product information from competitors, allowing for more effective market strategies. For governments, web crawlers assist in detecting trends in online public opinion and maintaining cybersecurity. Meanwhile, academic researchers can also use web crawlers to crawl academic resources and data, which aids in the advancement of scientific research.

Therefore, web crawlers, as an automated data acquisition tool, are becoming increasingly important in this context.

2 MOTIVATION

Traditional single-threaded web crawlers may encounter efficiency issues in large-scale data retrieval tasks due to their performance limitations. Therefore, to enhance the performance and efficiency of web crawlers, introducing multi-threading technology is a common solution. Multi-threaded web crawlers allow simultaneous processing of multiple tasks, with each task executed in an independent thread, thus fully utilizing computational resources and accelerating data retrieval speed.

Although multi-threaded web crawler technology is relatively mature today, often we only need to extract specific data from web pages after crawling. Based on this, this paper aims to develop a multi-threaded web crawler and a web page information extraction model, enabling users to retrieve large amounts of truly needed information in a short period.

3 MODEL ARCHITECTURE

Figure [1](#page-1-0) illustrates the model I constructed. Initially, the large text data is divided into several segments, each processed by a dedicated thread. Within these threads, URL data from the large text is concurrently crawled. The crawling process remains concurrent throughout. Subsequently, the crawled webpage text is stored in a web data queue, awaiting targeted data extraction. The targeted data extraction process also operates concurrently. Finally, the extracted data is written into targeted data sets. Each targeted data set is ultimately integrated into a result data set and returned. The writing process is concurrent as well.

Figure 1: Model Structure.

4 EXPERIMENT

Firstly, we test the efficiency of the crawler under single-threaded conditions. Here, we crawl URL datasets with data sizes of 100, 500, and 1000 respectively, recording the time taken for each singlethreaded execution. Each task size experiment is repeated ten times (Table [1\)](#page-1-1).

Experiment	Data Size 100	Data Size 500	Data Size 1000
1	17.562s	92.442s	247.962s
2	15.809s	91.730s	252.434s
3	18.474s	94.995s	248.887s
4	15.934s	100.061s	251.991s
5	16.210s	95.860s	250.444s
6	16.759s	93.467s	255.241 _s
	15.475s	91.966s	252.567s
8	16.006s	104.441 _s	246.241 _s
9	16.273s	95.511s	255.124s
10	16.567s	93.426s	256.342s
Average Time	16.507s	95.391s	251.724s

Table 1: Crawler Time Cost under Single-threaded Conditions

Here we plot a line graph of data size against average time (Figure [2\)](#page-2-0), showing an overall linear relationship between data size and average time. It can be observed that as the data size increases, the time taken by the single-threaded crawler program exceeds linear growth. One possible reason for this is that with larger data sizes, the impact of network fluctuations becomes more significant.

Next, we proceed with executing multi-threaded crawling operations. Here, we maintain a constant number of channels in each thread, with $m=5$ and $k=5$. To simplify the experiment, we only test the scenario with a data size of 500. We conduct multiple experiments (10 in each group) to obtain the average values for text segmentation n of 1, 5, 10, and 20 (Table [2\)](#page-2-1).

We observe that when $m=5$ and $k=5$, the shortest execution time is achieved when the thread count is set to 10, followed by 20. Due to the relatively small difference in time between thread counts 10 and 20, we speculate that the system's execution time stabilizes when the thread count is 10 or greater.

Table [3](#page-2-2) records the start, end, and duration of each thread in a concurrent experiment $(n = 10,$ $m = 5, k = 5$. The timestamp is May 8, 2024, at 18:55 Beijing time. In this experiment, there are 10 threads with 5 crawler channels and 5 data parsing channels.

Figure 2: Crawler Efficiency under Single-threaded Conditions.

Experiment	Thread Count 1	Thread Count 5	Thread Count 10	Thread Count 20
	23.589s	21.307s	19.189s	18.891s
$\overline{2}$	24.145s	22.013s	19.616s	18.762s
3	23.988s	21.921s	19.652s	19.306s
4	23.892s	21.340s	18.965s	19.441 _s
5	23.784s	22.552s	18.798s	19.351s
6	24.185s	22.498s	19.987s	20.534s
7	24.812s	21.093s	19.445s	19.675s
8	25.009s	22.062s	19.213s	18.321s
9	23.512s	21.402s	18.872s	20.001s
10	23.902s	22.512s	19.765s	19.842s
Average Time	24.082s	21.870s	19.350s	19.412s

Table 2: Average Time for Different Thread Counts When $n = 10$, $m = k = 5$

Thread ID	Start Time	End Time	Duration
T0	18:55:03.7s	18:55:23.1s	19.358s
T1	18:55:03.7s	18:55:23.2s	19.419s
T2	18:55:03.7s	18:55:23.0s	19.238s
T3	18:55:03.8s	18:55:23.2s	19.395s
T4	18:55:03.8s	18:55:23.1s	19.339s
Т5	18:55:03.8s	18:55:23.2s	19.363s
T6	18:55:03.8s	18:55:23.1s	19.3s
T7	18:55:04.0s	18:55:23.0s	18.965s
T8	18:55:04.0s	18:55:22.7s	18.611s
T9	18:55:04.1s	18:55:23.0s	18.886s

Table 3: Thread Execution Time

The line graph in Figure [3](#page-3-0) visualizes the duration of each thread as recorded in Table [3.](#page-2-2) Next,

Figure 3: Thread Duration When $n = 10$, $m = 5$, $k = 5$

we change the value of m and k to 10 and proceed with the same experiment. When $n = 10$, the time remains the smallest among the others. With the increase in the number of crawler and parsing channels, the overall program execution time reduces. However, it is worth noting that when $n = 20$, the time unexpectedly increases. Analyzing the reasons behind this, it is found that it may be due to the significant overhead of thread creation and switching, which reduces overall performance (Table [2\)](#page-2-1).

Experiment	Thread Count 1	Thread Count 5	Thread Count 10	Thread Count 20
-	19.092s	18.676s	18.543s	23.346s
$\overline{2}$	19.324s	18.523s	17.752s	23.607s
3	18.984s	17.982s	17.635s	20.087s
4	20.102s	18.002s	18.032s	19.652s
5	19.767s	17.613s	17.424s	20.142s
6	19.324s	17.982s	18.432s	19.542s
7	19.645s	18.654s	17.733s	21.421s
8	19.426s	18.768s	18.032s	20.442s
9	19.816s	18.982s	17.998s	22.421s
10	20.042s	19.112s	18.692s	19.884s
Average Time	19.552s	18.429s	18.027s	21.054s

Table 4: Average Time for Different Thread Counts When $n = 10$, $m = k = 10$

5 SUMMARY

After multiple experiments, it was found that when the number of URLs is 500, and $n = m = k = 10$, the least time is consumed, indicating the best scenario, with a time of 18.027 seconds. Comparing this to the single-threaded crawler time for the same dataset, the time is reduced by 77.364 seconds, optimizing by 81.11%.

Comparison of Single-threaded and Optimal

Figure 4: Comparison of Single-threaded and Optimal Multi-threading Times

6 FUTURE WORK

Obviously, this experiment is not yet fully completed. The preliminary conclusions drawn only provide guidance for our subsequent experiments. Next, we need to conduct controlled variable experiments multiple times, obtaining datasets with different numbers of URLs, and varying the values of n, m , and k . By continuously adjusting the thread numbers in the model, we aim to determine the optimal thread settings applicable to all URL dataset sizes.

References

- [1] H.-J. Kim, J.-Y. Lee, and S.-S. Shin, "Multi-threaded web crawling design using queues," Journal of Convergence for Information Technology, vol. 7, no. 2, pp. 43–51, 2017.
- [2] K. Vayadande, R. Shaikh, T. Narnaware, S. Rothe, N. Bhavar, and S. Deshmukh, "Designing web crawler based on multi-threaded approach for authentication of web links on internet," in 2022 6th International Conference on Electronics, Communication and Aerospace Technology. IEEE, 2022, pp. 1469–1473.
- [3] A. K. Sharma, V. Shrivastava, and H. Singh, "Experimental performance analysis of web crawlers using single and multi-threaded web crawling and indexing algorithm for the application of smart web contents," Materials Today: Proceedings, vol. 37, pp. 1403–1408, 2021.
- [4] P. Bedi, A. Thukral, H. Banati, A. Behl, and V. Mendiratta, "A multi-threaded semantic focused crawler," Journal of Computer Science and Technology, vol. 27, pp. 1233–1242, 2012.