# Q-Sparse: All Large Language Models can be Fully Sparsely-Activated

### Hongyu Wang<sup>∗</sup> Shuming Ma<sup>∗</sup> Ruiping Wang Furu Wei<sup>⋄</sup> <https://aka.ms/GeneralAI>

## Abstract

We introduce, Q-Sparse, a simple yet effective approach to training sparselyactivated large language models (LLMs). Q-Sparse enables full sparsity of activations in LLMs which can bring significant efficiency gains in inference. This is achieved by applying top- $K$  sparsification to the activations and the straightthrough-estimator to the training. We also introduce Block Q-Sparse for batch training and inference. The key results from this work are, (1) Q-Sparse can achieve results comparable to those of baseline LLMs while being much more efficient at inference time; (2) We present an inference-optimal scaling law for sparselyactivated LLMs; (3) Q-Sparse is effective in different settings, including trainingfrom-scratch, continue-training of off-the-shelf LLMs, and finetuning; (4) Q-Sparse works for both full-precision and 1-bit LLMs (e.g., **BitNet b1.58** [\[WMD](#page-13-0)<sup>+</sup>23]). Particularly, the synergy of BitNet b1.58 and Q-Sparse (can be equipped with MoE) provides the cornerstone and a clear path to revolutionize the efficiency, including cost and energy consumption, of future LLMs.

<span id="page-0-0"></span>

Figure 1: Q-Sparse achieves a superior inference-optimal scaling law than the dense models. It saves significant compute of matrix multiplication by top- $K$  sparsification of the activations.

<sup>∗</sup> Equal contribution. ⋄ Corresponding author. S. Ma, F. Wei are with Microsoft Research. H. Wang and R. Wang are with University of Chinese Academy of Sciences.

# 1 Fully Sparsely-Activated LLMs

Large language models (LLMs) have achieved remarkable performance on a wide range of natural language processing (NLP) tasks. However, the deployment of LLMs in real-world applications is challenging due to their high computational cost and memory footprint, especially during the inference stage. To address this challenge, recent works  $[MWM+24, WMD+23, SXZ+24, XGZC23,$  $[MWM+24, WMD+23, SXZ+24, XGZC23,$ [LKM23\]](#page-12-0) have focused on improving the efficiency of LLMs with various approaches, including quantization  $[MWM<sup>+</sup>24$  $[MWM<sup>+</sup>24$ ,  $WMD<sup>+</sup>23$  $WMD<sup>+</sup>23$ , [FAHA23\]](#page-12-1), pruning [\[XGZC23\]](#page-14-0), distillation [\[GDWH23\]](#page-12-2), better decoding [\[LKM23\]](#page-12-0), and so on. One promising approach is to use sparsity to reduce the number of activated parameters in LLMs.

Sparsity contributes two factors to the efficiency of LLMs. First, sparsity can reduce the amount of computation of the matrix multiplication as zero elements are not computed. Second, sparsity can reduce the amount of input/output (I/O) that transfers the parameters between the memory and the computation units. The I/O transfer serves as the major bottleneck in the inference stage of LLMs.

One common approach to sparsity in LLMs is to use weight sparsity, which prunes the model weights to save the computation. However, unstructured weight sparsity is difficult to parallelize in GPU devices, while structured weight sparsity has a large impact to the accuracy of the model.

Another approach is to use activation sparsity, which reduces the number of activated elements in the activation tensors. Activation sparsity can be achieved by using the mixture-of-experts (MoE) mechanism [\[LLX](#page-12-3)+21, [FZS21\]](#page-12-4), modifying the activation function [\[MAM](#page-13-3)+23, [SXZ](#page-13-2)+24], or predicting the position to be sparsed  $[LWD^{\dagger}23]$  $[LWD^{\dagger}23]$ . However, these approaches do not enable full sparsity of activations in LLMs, which can limit the efficiency gains during the inference stage. Moreover, compared to the dense models, the scaling laws for the sparsely-activated LLMs have not been well studied.

To explore the full potential of sparsity in LLMs, we introduce Q-Sparse, a simple yet effective approach to enable full sparsity of activations in LLMs. The major modification on LLMs is in the linear projection (i.e., matrix multiplication). As shown in Figure [1,](#page-0-0) for each linear projection, it has a top-K sparsification function that selects the top-K activations in the input tensor. For the backprogation, we use the straight through estimator to compute the gradients of the activations. We also introduce a squared ReLU function for the feed-forward layers to further improve the sparsity of the activations. Q-Sparse can be used with both full-precision and quantized LLMs. Furthermore, we introduce, Block Q-Sparse, a block sparsity implementation to make Q-Sparse compatible with batch training and inference.

To study the scaling law of sparsely-activated LLMs, we conduct a series of scaling experiments and derive an inference-optimal scaling law for sparsely-activated LLMs. We summarize the findings from the scaling experiments and the implications of the scaling law as below:

- The performance of the sparsely-activated models is better than the dense baselines with the same inference compute budget (i.e., activated parameters or FLOPs).
- $\bullet$  As the parameters  $N$  scales, the performance gap between the sparsely-activated models and the dense baselines decreases.
- The performance of the sparsely-activated models with around 40% sparsity ratio can match the performance of the dense baselines with the same model size and training tokens.
- Given the same inference budget  $N_a$ , a sparsely-activated full-precision model with a sparsity ratio of 45.58% (or  $1.84N_a$  parameters) can achieve the best performance. For the 1.58-bit models, the optimal sparsity ratio is 61.25%.

We also conduct experiments to evaluate the effectiveness of O-Sparse in different settings, including training-from-scratch, continue-training of off-the-shelf LLMs, and finetuning. We show that Q-Sparse can achieve results comparable to those of baseline LLMs with the same training cost while being much more efficient at inference time.

# 2 Q-Sparse

#### 2.1 Architecture

The Q-Sparse architecture is based on the Transformer architecture  $[VSP^+17, TLI^+23]$  $[VSP^+17, TLI^+23]$  $[VSP^+17, TLI^+23]$  $[VSP^+17, TLI^+23]$  with modifications to enable sparsity in the activations.

# Top-K Sparsity

The Transformer architecture uses *nn.Linear* to perform the projection in both attention and feedforward layers, which can be written as:

$$
\mathbf{Y} = \mathbf{X} \cdot \mathbf{W}^T \tag{1}
$$

where  $\mathbf{X} \in \mathbb{R}^{N \times D}$  is the input tensor,  $\mathbf{W} \in \mathbb{R}^{M \times D}$  is the weight tensor, and  $\mathbf{Y} \in \mathbb{R}^{N \times M}$  is the output tensor. The *nn.Linear* operation is equivalent to the matrix multiplication operation.

We introduce a top-K sparsity function on top of the matrix multiplication operation. The top-K sparsity function is defined as:

$$
\mathbf{Y} = (\mathbf{X} \odot \mathbf{M}) \cdot \mathbf{W}^T \tag{2}
$$

$$
\mathbf{M} = \text{Top}_k(|\mathbf{X}|) \tag{3}
$$

where  $\mathbf{M} \in \mathbb{R}^{N \times D}$  is the mask tensor that indicates the top-K activations in the input tensor X in terms of the absolute values,  $\odot$  is the element-wise multiplication operation, and Top<sub>k</sub> is the function that selects the top-K elements in the tensors.

To reduce the interval around zero, we re-scale the tensor by its  $L_2$  norm after performing the top-K sparsity function.

#### Quantized Top-K Sparsity

Recent works [\[WMD](#page-13-0)<sup>+</sup>23] have shown that quantization can be used to reduce the memory footprint and computational cost of LLMs without the loss of performance. We introduce a quantized version of the top-K sparsity function. The quantized top-K sparsity function is defined as:

$$
\mathbf{Y} = (\mathbf{Q}(\mathbf{X}) \odot \mathbf{M}) \cdot \mathbf{W}^T
$$
 (4)

where  $O(\cdot)$  is the quantization function that quantizes the input tensor **X** to a 8-bit representation:

$$
Q(X) = \text{RoundClip}(\frac{127}{\gamma + \epsilon} \mathbf{X}, -128, 127)
$$
\n<sup>(5)</sup>

$$
\gamma = \max(|\mathbf{X}|) \tag{6}
$$

$$
RoundClip(X, a, b) = min(max(round(X), a), b)
$$
\n(7)

where  $\epsilon$  is a small constant to avoid division by zero, and  $\gamma$  is the maximum absolute value in the input tensor X.

Q-Sparse can be used with both full-precision and quantized LLMs. Specifically, the quantized version of Q-Sparse is compatible with 1-bit LLMs, such as BitNet b1.58 [\[WMD](#page-13-0)<sup>+</sup>23]. When using Q-Sparse with 1-bit LLMs, the quantization function is performed on the weight tensor  $W$ :

$$
\mathbf{Y} = (\mathbf{Q}(\mathbf{X}) \odot \mathbf{M}) \cdot \mathbf{Q}_w(\mathbf{W})^T
$$
 (8)

where  $Q_w(\cdot)$  is the quantization function that quantizes the weight tensor W to a 1.58-bit representation:

$$
Q_w(W) = \text{RoundClip}(\frac{W}{\alpha + \epsilon}, -1, 1)
$$
\n(9)

where  $\alpha$  is the mean absolute value in the weight tensor **W**:

$$
\alpha = \text{mean}(|\mathbf{W}|) \tag{10}
$$

#### Squared ReLU

To further improve the sparsity of the activations, we use the squared ReLU function  $[SML^+21]$  $[SML^+21]$  for the feed-forward layers. The squared ReLU function is defined as  $ReLU(X)^2$ .

Following the LLaMA architecture, we use the gated linear unit (GLU) for the feed-forward layers. The squared ReLU function is applied with the GLU function into a ReLU<sup>2</sup>GLU function. The  $ReLU<sup>2</sup>GLU$  function is defined as:

$$
ReLU^{2}GLU(X) = \mathbf{XW}_{up}^{T} \odot RelU^{2}(\mathbf{XW}_{gate}^{T})
$$
\n(11)

#### Block Q-Sparse

While the top-k sparsification can be used in the single-sample mode, it is not friendly with the batch mode for the current GPU devices. Recent work  $[ZMZ^+21, LZW^+23]$  $[ZMZ^+21, LZW^+23]$  $[ZMZ^+21, LZW^+23]$  $[ZMZ^+21, LZW^+23]$  shows that N:M sparsity, where N out of M consecutive elements to be zero, is more hardware friendly and can be used in the batch mode with an optimized GPU kernel. To leverage this feature of the modern GPU devices, we introduce Block Q-Sparse. The key idea of Block Q-Sparse is to apply the top-K sparsity function on the activations in the block level, and the block size is set to M so that there are always  $M - K$ zeros out of M consecutive values. The top-K sparsity function is applied to the activations in each block independently. The block level sparsity can be used to reduce the memory footprint and computational cost of the LLMs in the batch mode.

#### 2.2 Training

Most of the existing works  $[MAM<sup>+</sup>23]$  $[MAM<sup>+</sup>23]$  on training sparsely-activated models use the vanilla backpropagation algorithm to compute the gradient through the sparsity function:

$$
\frac{\partial \mathbf{Y}}{\partial \mathbf{X}} = \frac{\partial \mathbf{Y}}{\partial (\mathbf{X} \odot \mathbf{M})} \odot \mathbf{M}
$$
 (12)

where M is the mask tensor that indicates the top-K activations in the input tensor X, and  $\odot$  is the element-wise multiplication operation.

The vanilla back-propagation algorithm has a limitation. It zero-outs the gradients of the non-activated elements, which can lead to the vanishing gradient problem, especially when the sparsity ratio is high. In this work, we propose to use the straight-through estimator [\[BLC13\]](#page-12-5) to back-propagate the gradients through the sparsity function. In this way, the gradients are passed through the sparsity function without being zeroed-out. The straight-through estimator is defined as:

$$
\frac{\partial \mathbf{Y}}{\partial \mathbf{X}} = \frac{\partial \mathbf{Y}}{\partial (\mathbf{X} \odot \mathbf{M})}
$$
(13)

We visualize the average  $l2$  norm of each projection's gradient across different layers for dense model, Q-Sparse with and without STE. We adopt top-K as 50% for Q-Sparse. Without STE, the gradient is much smaller at the bottom layers, while STE can preserve the magnitude of the gradients. As shown in Figure [2,](#page-4-0) STE estimator significantly eases the issue of gradient vanishing, especially at the bottom of the layers. We present more visualizations for each components in the Appendix [A.](#page-14-2)

## 2.3 Q-Sparse for Continue-Train and Finetuning Settings

Q-Sparse can be used in different settings, including training-from-scratch, continue-training, and finetuning. In the continue-train and finetuning settings, we use the same architecture and training procedure as in the training-from-scratch setting. The only difference is that we initialize the model with the pre-trained weights and continue training with the sparsity function enabled.

For the pre-trained models that do not have the squared ReLU function in the feed-forward layers, we apply the top-K sparsity function after the activated function (e.g., SiLU) in the feed-forward layers. It can improve the sparsity of the activations without changing the model architecture.

<span id="page-4-0"></span>

Figure 2: The average magnitude of each projection's gradient of dense baseline, Q-Sparse with and without STE across different layers. The visualization is conducted with 300M model size on a subset of the valid set of C4  $[RSR^+19]$  $[RSR^+19]$ . It shows that the gradient vanishes without STE.

## 3 Scaling Laws

Recent work on large language models has shown that the performance of LLMs scales with the model size and the amount of training data.  $[HBM+22]$  $[HBM+22]$  argues that the converged performance of a dense Transformer model with  $N$  parameters follows a power-law scaling law, which can be written as:

$$
L(N) \triangleq E + \frac{A}{N^{\alpha}} \tag{14}
$$

where  $L(N)$  is the performance of the model with N parameters, E is the performance of the model with infinite parameters, A is a constant, and  $\alpha$  is the scaling exponent. Note that the number of training tokens are fixed in this setting, which is part of the constant  $E$ .

In this work, we investigate the scaling law of sparsely-activated LLMs. We find that the performance of sparsely-activated LLMs also follows a power-law scaling law, which can be written as:

$$
L(N, S) \triangleq E + \frac{A(S)}{N^{\alpha}}
$$
\n(15)

$$
A(S) = B + C \exp\left(\frac{\beta}{1 - S}\right) \tag{16}
$$

where  $L(N, S)$  is the performance of the sparsely-activated model with N parameters and a sparsity ratio of S, and  $\alpha$  and  $\beta$  are the scaling exponents.

In the following part, we will introduce how we derive the scaling law and the corresponding findings.

#### 3.1 Scaling Experiments and Findings

To determine the form of the scaling law of sparse-activated LLMs, we begin with a series of scaling experiments. In the experiments, we train a series of language models with Q-Sparse of various scales, ranging from 300M to 7B. The models are trained on the Redpajama dataset [\[Com23\]](#page-12-7). We use the Sentencepiece tokenizer from LLaMA to preprocess data. Besides Q-Sparse, we also train the dense baselines with the same datasets and settings. More details can be found in the Appendix [B.](#page-14-3)

<span id="page-5-0"></span>

Figure 3: The scaling curves of the sparsely-activated models regrading to the model size given a fixed sparsity ratio  $S$  (Left), and regrading to the sparsity ratio given a fixed model size  $N$  (Right).

The observed losses of the sparsely-activated models and the dense baselines are shown in Figure [3.](#page-5-0) We summarize the findings as below:

- The performance of the sparsely-activated models scales with the model size and the sparsity ratio.
- Given a fixed sparsity ratio  $S$ , the performance of the sparsely-activated models follows a power-law scaling law with regards to the model size  $N$ .
- Given a fixed parameters  $N$ , the performance of the sparsely-activated models follows an exponential-law scaling law with regards to the sparsity ratio S.
- As the parameters  $N$  scales, the performance gap between the sparsely-activated models and the dense baselines decreases.

According to these findings, our main hypothesis is that the performance of the sparsely-activated models follows a combination of a power-law scaling law with regards to the model size  $N$  and an exponential-law scaling law with regards to the sparsity ratio S.

#### 3.2 Power Law in the Model Size  $N$

With a fixed sparsity ratio S, the scaling law should follows  $[KMH^+20]$  $[KMH^+20]$ 's scaling law, which can be written as:

$$
L(N, S) \triangleq E + \frac{A(S)}{N^{\alpha(S)}}\tag{17}
$$

where  $\alpha(S)$  is the scaling exponent, and the scaling factor  $A(S)$  is a function of the sparsity ratio S. Given any model size N, the function  $L(N, S)$  should follow the Lipschitz continuity with regards to the sparsity ratio S. Therefore, the scaling exponent  $\alpha(S)$  should be a non-decreasing function. Given any model size N, the function  $L(N, S)$  is increasing with the sparsity ratio S, so  $\alpha(S)$  should be a non-increasing function. Above all, the scaling exponent  $\alpha(S)$  should be a constant, and the scaling function can be written as:

$$
L(N, S) \triangleq E + \frac{A(S)}{N^{\alpha}}
$$
\n(18)

#### 3.3 Exponential Law in the Sparsity Ratio S

According to the above finding, the performance of the sparsely-activated models follows an exponential-law scaling law with regards to the sparsity ratio S. Therefore, the scaling factor  $A(S)$  should also follow an exponential law. Besides, given any model size N, the scaling function is increasing with the sparsity ratio  $S$ . Therefore, the scaling factor  $A(S)$  should be a non-decreasing function. The scaling factor  $A(S)$  can be written as:

$$
A(S) = B + C \exp\left(\frac{\beta}{1 - S}\right) \tag{19}
$$

<span id="page-6-0"></span>

Figure 4: The inference-optimal scaling curves of the sparsely-activated models with full-precision (Top) and 1.58-bit (Bottom) weight. It shows that a sparisty of 45.58% for full-precision models and 61.25% for 1.58-bit models can achieve the best performance with the same inference compute budget (i.e., activated parameters or FLOPs).

where  $B$  is the scaling factor for extremely sparse LLMs,  $C$  is the scaling factor for dense LLMs, and  $\beta$  is the scaling exponent of the scaling factor  $A(S)$  with regards to the sparsity ratio S.

#### 3.4 Fitting the Parameters

We fit the parameters of the scaling law to the observed losses of the sparsely-activated models. We use the L-BFGS algorithm [\[Noc80\]](#page-13-10) to minimize the Huber loss [\[Hub92\]](#page-12-9) between the predicted and observed log loss.

$$
\min_{E,B,C,\beta,\alpha} \sum_{\text{Runs }i} \text{Huber}_{\delta} \left( \log \hat{L}(N_i, S_i) - \log L_i \right) \tag{20}
$$

Following [\[HBM](#page-12-6)<sup>+</sup>22],  $\delta$  is set as 10<sup>-3</sup>. We select the best fit from a grid of initialisations around possible local optimas. E, B, C,  $\alpha$  and  $\beta$  are estimated as 1.86, 0.01, 1.89, 0.10 and 0.05, respectively.

#### 3.5 Diminishing Gap between Sparsely-Activated Models and Dense Baselines

Given the above scaling law, we can derive the performance of the sparsely-activated models and the dense baselines with the same model size  $N$  and the same sparsity ratio  $S$ . The performance gap between the sparsely-activated models and the dense baselines decreases as the model size N scales. The performance gap can be written as:

$$
L(N, S) - L(N, 0) = \frac{A(S)}{N^{\alpha(S)}} - \frac{A(0)}{N^{\alpha(0)}}
$$
\n(21)

$$
=\frac{A(0)}{N^{\alpha}}(\frac{A(S)}{A(0)}-1)
$$
\n(22)

Since  $\alpha$  is a constant that satisfies  $\alpha > 0$ , the performance gap decreases as the model size N scales. It means that given a large enough model size  $N$ , the performance of the sparsely-activated models can eventually match the performance of the dense baselines with the same model size.

<span id="page-7-0"></span>

Figure 5: The training loss curve of O-Sparse and the baseline with full-precision. We adopt top- $K$ as 70% for Q-Sparse, resulting in 40% overall sparsity.

#### 3.6 Inference-Optimal Scaling Law

The scaling law can also be transformed into a form that is dependent on the activated parameters  $N_a$ , which reflects the effective compute (i.e., FLOPs) of the model during inference:

$$
L(N_a, S) \triangleq E + A(S) \left(\frac{1 - S}{N_a}\right)^{\alpha} \tag{23}
$$

where  $N_a$  is the number of activated parameters in the model, which is equal to  $N \times (1 - S)$ . Since  $A(S)$  is an increasing function and  $(1 - S)^{\alpha}$  is a decreasing function, there exists a sparsity ratio  $S^* > 0$  that minimizes the loss of the sparsely-activated models. This leads to the inference-optimal scaling law of the sparsely-activated models:

$$
L(N_a) \triangleq E + A(S^*) \left(\frac{1 - S^*}{N_a}\right)^\alpha \tag{24}
$$

It shows that the performance of the sparsely-activated models is better than the dense baselines with the same inference compute budget. We further solve the optimal sparsity ratio  $S^*$ , finding that  $S^* \approx 45.58\%$ . It means that a sparsely-activated model with a sparsity ratio of 45.58% (or 1.84 $N_a$ ) parameters) can achieve the best performance with the same inference budget  $N_a$ . We follow the same process to estimate the inference-optimal scaling law for 1.58-bit Q-Sparse models. We find that the optimal sparsity ratio is  $61.25\%$  (or  $2.58N_a$  parameters). Figure [4](#page-6-0) shows the inference-optimal scaling curves of the sparsely-activated models with full-precision and 1.58-bit weight. It shows that with the same performance, the sparsely-activated models can achieve a significant reduction in the number of activated parameters or FLOPs during inference.

The inference-optimal scaling law shows that the performance of the sparsely-activated models can be optimized by adjusting the sparsity ratio  $S$ . It can be used to guide the training of the sparsely-activated models and to optimize the performance of the models during inference.

# 4 Experiments

We conduct experiments to evaluate the effectiveness of Q-Sparse in different settings, including training-from-scratch, continue-training of off-the-shelf LLMs, and finetuning.

#### 4.1 Training-from-Scratch

Setting We train a series of language models with Q-Sparse in both full-precision and 1.58 bits. The models are trained with 50B tokens on the Redpajama dataset [\[Com23\]](#page-12-7). We compare Q-Sparse with the dense baselines with the same datasets and settings.

<span id="page-8-0"></span>

Figure 6: The training loss curve of O-Sparse and the baseline with 1.58-bit weight. We adopt top- $K$ as 70% for Q-Sparse, resulting in 40% overall sparsity.

<span id="page-8-1"></span>

Figure 7: The training loss curves for Q-Sparse and Block Q-Sparse. It shows that Block Q-Sparse has a similar convergence to Q-Sparse with the same sparsity.

Results The observed losses of the sparsely-activated models and the dense baselines are shown in Figure [5.](#page-7-0) It shows that Q-Sparse with 40% sparsity ratio can match the performance of the dense baselines with the same model size and training tokens.

BitNet b1.58 + Q-Sparse We further evaluate the effectiveness of Q-Sparse on 1-bit LLMs. We train a series of BitNet b1.58 models with Q-Sparse of various scales. We plot the training loss curves of both Q-Sparse and the BitNet b1.58 baseline. Figure [6](#page-8-0) shows that the performance of the sparsely-activated BitNet b1.58 models is better than the dense baselines with the same inference compute budget. It demonstrates that Q-Sparse is compatible to 1-bit LLMs and their synergy can be used to optimize the performance of the models during inference.

Block Q-Sparse We evaluate the effectiveness of Block Q-Sparse. We compare it with Q-Sparse of the same sparsity ratio. The sparsity ratio is 50%, and the block size is set to 32 (i.e., N:M=16:32). The experiments are performed with the model sizes of 300M and 700M. The training loss curves of Q-Sparse and Block Q-Sparse are shown in Figure [7.](#page-8-1) It shows that Block Q-Sparse has a similar convergence to Q-Sparse with the same sparsity. It demonstrates that Block Q-Sparse can match the performance of Q-Sparse when training from scratch.

Ablation Study of top-K Sparisty and STE To evaluate the effect of the top-K sparsity function, we compare the performance of the sparsely-activated models with the top-K sparsity function and

<span id="page-9-0"></span>

Figure 8: The training loss curves (Left) and the overall sparsity ratio (Right) of different sparsity functions. All models are trained with 300M size and 50B tokens.

<span id="page-9-1"></span>

Figure 9: The sparsity ratio of each model's component of different sparsity functions.

the ReLU sparsity function. Moreover, we study the effect of the STE by comparing the models with and without STE. Figure [8](#page-9-0) illustrates the results. It shows that either removing STE or replacing with ReLU function significantly hurt the performance. Besides, the sparsity ratio of the models with the ReLU function decreases as the training processes. In constrast, the sparisty ratio remains unchanged with the top-K sparisty function. As shown in Figure [9,](#page-9-1) we break down the contribution of the sparsity ratio from different components, finding that the decreasing sparisty is mainly from the QKV projection, the gating projection and the up projection of the feed-forward layers. This proves the superior of top-K over ReLU function.

#### 4.2 Continue-Training

**Setting** We continue-train the Mistral 7B model  $[BBC + 23]$  $[BBC + 23]$  for 40B tokens on the FineWeb-Edu dataset [\[LBAvWW24\]](#page-12-10). We use the Sentencepiece tokenizer from Mistral to preprocess data. We use the batch size of 4M tokens and the learning rate of 5e-5. We use the Adam optimizer with the weight decay of 0.01. More training details can be found in Appendix [B.](#page-14-3)

Results For a fair comparison, we continue-train the Mistral 7B model with the same recipe as the dense baseline. We compare O-Sparse with the ReLUfication  $[MAM<sup>+</sup>23]$  $[MAM<sup>+</sup>23]$  and dReLU Sparsification  $[SXZ^+24]$  $[SXZ^+24]$  methods, which sparsify the model by changing the activation function. Following the origin paper  $[MAM+23]$  $[MAM+23]$ , we adopt a two-stage training strategy that first replaces the non-ReLU activation and then adds the ReLU functions. For the dReLU Sparsification method, we implement the dReLU sparsification method following the origin paper  $[SXZ^+24]$  $[SXZ^+24]$ . We evaluate these models on a range of language tasks, including ARC-Challenge [\[YBS19\]](#page-14-4), HellaSwag [\[ZHB](#page-14-5)+19], Wino-

<span id="page-10-0"></span>

<b>Models</b>	<b>Activated</b>	<b>ARC</b>	<b>HS</b>	<b>MMLU</b>	WG	TOA	Avg.
Dense Baseline	7.0B	61.8	81.4	59.8	77.5	42.7	64.6
ReLUfication $[MAM+23]$	5.0B	57.2	78.8	54.7	74.7	38.8	60.8
dReLU Sparsification $[SXZ^+24]$	5.4B	59.2	78.0	54.0	75.8	38.3	61.0
Q-Sparse (this work)	2.9B	59.0	79.0	55.6	74.0	41.0	61.7
	3.8B	60.5	80.7	58.0	75.9	43.5	63.7

Table 1: The results of the continue-training for Q-Sparse and the baselines on the end tasks.

<span id="page-10-1"></span>

Table 2: The activated parameters and the sparsity ratio of the continue-training for Q-Sparse and the baselines on the test set of Wikitext2.

grande [\[SBBC20\]](#page-13-11), MMLU [\[HBB](#page-12-11)+21] and TruthfulQA [\[LHE22\]](#page-12-12). Results are shown in Table [1.](#page-10-0) It shows that Q-Sparse achieves comparable performance to the dense baseline while being much more efficient at inference time. Moreover, Q-Sparse outperforms the ReLUfication and dReLU Sparsification methods in terms of the performance and the sparsity ratio.

To break down the sparsity of each component in the model, we present the sparsity ratio of the query, key, value, output, up, down, and gate tensors in Table [2.](#page-10-1) It shows that Q-Sparse achieves a higher sparsity ratio than the ReLUfication and dReLU Sparsification methods. The sparsity ratio of the query, key, value, output, up, and down tensors is higher than 40%, and the sparsity ratio of the gate tensor is higher than 60%. It demonstrates that Q-Sparse can achieve full sparsity of activations in LLMs.

#### <span id="page-10-2"></span>4.3 Supervised Finetuning

**Setting** We finetune the base model of Mistral 7B  $[JSM^+23]$  $[JSM^+23]$  and Qwen1.5 7B  $[BBC^+23]$  $[BBC^+23]$  on Open-Orca dataset  $[LGP^{+}23]$  $[LGP^{+}23]$  for both the dense baselines and Q-Sparse. The batch size is set as 128. The learning rates are selected from {3e-6, 5e-6, 7e-6}. All models are trained with 1 epoch for a fair comparison. The hyper-parameters are detailed in Appendix [B.](#page-14-3) We conduct the evaluation for these models on a range of language tasks, including ARC-Challenge [\[YBS19\]](#page-14-4), HellaSwag [\[ZHB](#page-14-5)<sup>+</sup>19], Winogrande [\[SBBC20\]](#page-13-11), MMLU [\[HBB](#page-12-11)<sup>+</sup>21] and TruthfulQA [\[LHE22\]](#page-12-12).

Results The results are shown in Table [3.](#page-11-1) It shows that Q-Sparse with 3.6B activated parameters achieves significant better performance than the Qwen1.5 4B dense model. Moreover, Q-Sparse with around 4B activated parameters achieves comparable performance to the Mistral 7B model and the Qwen1.5 7B model. It demonstrates that Q-Sparse can be used to finetune a dense pretrained model to a much more efficient sparse model with almost no loss at accuracy.

## 4.4 Evaluation of Block Q-Sparse

**Setting** We finetune the base model of Mistral 7B  $[JSM^+23]$  $[JSM^+23]$  and Qwen1.5 7B  $[BBC^+23]$  $[BBC^+23]$  on Open-Orca dataset  $[LGP^+23]$  $[LGP^+23]$  for Block Q-Sparse. The block size is set as 32, which is recommended by the previous work [\[LZW](#page-13-8)<sup>+</sup>23] on N:M sparse kernels. The other hyper-parameters are consistent with the experiments shown in Section [4.3.](#page-10-2)

Results Table [4](#page-11-2) summarizes the results for Block Q-Sparse. Similar to the results of Q-Sparse, Block Q-Sparse achieves comparable performance to the dense baselines with much fewer activated

<span id="page-11-1"></span>

<b>Models</b>	<b>Activated</b>	ARC	<b>HS</b>	MMLU	WG	TOA	Avg.
Owen $1.5 - 4B$	3.2B	42.8	68.2	53.6	67.1	47.9	55.9
$Qwen1.5-7B$	6.5B	47.7	74.6	61.5	71.4	50.7	61.2
Q-Sparse	3.6B	46.3	72.6	59.1	67.5	50.3	59.2
	4.1B	47.9	73.2	59.2	69.4	51.1	60.1
Mistral-7B	7.0B	62.5	82.6	61.2	77.6	50.3	66.8
<b>Q-Sparse</b>	3.8B	60.5	81.5	60.0	77.1	50.5	65.9
	4.3B	61.4	81.6	60.6	77.6	50.7	66.4

<span id="page-11-2"></span>Table 3: The results of the supervised fine-tuning for Q-Sparse and the dense baselines on the end tasks.



Table 4: The results of the supervised fine-tuning for Block Q-Sparse and the dense baselines on the end tasks.

parameters. It demonstrates that Block Q-Sparse can be used for a much more efficient sparse model while supporting the batch mode.

# 5 Discussion and Future Work

## Scaling BitNet b1.58 + Q-Sparse + YOCO

We have shown promising results of combining 1-bit LLMs (i.e., BitNet b1.58) and fully sparse activations (i.e.,  $\overline{Q}$ -Sparse). We are working on scaling up the training in terms of both model size and training tokens. Furthermore, we will incorporate YOCO [\[SDZ](#page-13-12)+24] to address the issue of KV cache for LLM inference. The integration of BitNet, Q-Sparse, and YOCO provides a comprehensive approach to optimizing all data types in LLM inference and deployment, which includes systematic optimization of model weights, activations, and KV cache.

## Q-Sparse + MoE

Mixture-of-Experts has been the most widely method to achieve sparse activations in LLMs. Q-Sparse is orthogonal and can be seamlessly integrated with MoE.

## References

<span id="page-11-0"></span>[BBC<sup>+</sup>23] Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, Binyuan Hui, Luo Ji, Mei Li, Junyang Lin, Runji Lin, Dayiheng Liu, Gao Liu, Chengqiang Lu, Keming Lu, Jianxin Ma, Rui Men, Xingzhang Ren, Xuancheng Ren, Chuanqi Tan, Sinan Tan, Jianhong Tu, Peng Wang, Shijie Wang, Wei Wang, Shengguang Wu, Benfeng Xu, Jin Xu, An Yang, Hao Yang, Jian Yang, Shusheng Yang, Yang Yao, Bowen Yu, Hongyi Yuan, Zheng Yuan, Jianwei Zhang, Xingxuan Zhang, Yichang Zhang, Zhenru Zhang, Chang Zhou, Jingren Zhou, Xiaohuan Zhou, and Tianhang Zhu. Qwen technical report. *CoRR*, abs/2309.16609, 2023.

- <span id="page-12-5"></span>[BLC13] Yoshua Bengio, Nicholas Léonard, and Aaron C. Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *CoRR*, abs/1308.3432, 2013.
- <span id="page-12-7"></span>[Com23] Together Computer. Redpajama: an open dataset for training large language models, 2023.
- <span id="page-12-1"></span>[FAHA23] Elias Frantar, Saleh Ashkboos, Torsten Hoefler, and Dan Alistarh. OPTQ: accurate quantization for generative pre-trained transformers. In *The Eleventh International Conference on Learning Representations*, 2023.
- <span id="page-12-4"></span>[FZS21] William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *CoRR*, abs/2101.03961, 2021.
- <span id="page-12-2"></span>[GDWH23] Yuxian Gu, Li Dong, Furu Wei, and Minlie Huang. Knowledge distillation of large language models. *arXiv preprint arXiv:2306.08543*, 2023.
- <span id="page-12-11"></span>[HBB+21] Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021.
- <span id="page-12-6"></span>[HBM<sup>+</sup>22] Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, Tom Hennigan, Eric Noland, Katie Millican, George van den Driessche, Bogdan Damoc, Aurelia Guy, Simon Osindero, Karen Simonyan, Erich Elsen, Jack W. Rae, Oriol Vinyals, and Laurent Sifre. Training compute-optimal large language models. *CoRR*, abs/2203.15556, 2022.
	- [Hub92] Peter J Huber. Robust estimation of a location parameter. In *Breakthroughs in statistics: Methodology and distribution*, pages 492–518. Springer, 1992.
- <span id="page-12-13"></span><span id="page-12-9"></span>[JSM<sup>+</sup>23] Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de Las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mistral 7b. *CoRR*, abs/2310.06825, 2023.
- <span id="page-12-8"></span>[KMH<sup>+</sup>20] Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *CoRR*, abs/2001.08361, 2020.
- <span id="page-12-14"></span><span id="page-12-12"></span><span id="page-12-10"></span><span id="page-12-3"></span><span id="page-12-0"></span>[LBAvWW24] Anton Lozhkov, Loubna Ben Allal, Leandro von Werra, and Thomas Wolf. Finewebedu, May 2024.
	- [LGP<sup>+</sup>23] Wing Lian, Bleys Goodson, Eugene Pentland, Austin Cook, Chanvichet Vong, and "Teknium". Openorca: An open dataset of gpt augmented flan reasoning traces. <https://https://huggingface.co/Open-Orca/OpenOrca>, 2023.
	- [LHE22] Stephanie Lin, Jacob Hilton, and Owain Evans. Truthfulqa: Measuring how models mimic human falsehoods. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2022, Dublin, Ireland, May 22-27, 2022*, pages 3214–3252. Association for Computational Linguistics, 2022.
	- [LKM23] Yaniv Leviathan, Matan Kalman, and Yossi Matias. Fast inference from transformers via speculative decoding. In *International Conference on Machine Learning, ICML 2023, 23-29 July 2023, Honolulu, Hawaii, USA*, 2023.
	- $[LLX+21]$  Dmitry Lepikhin, HyoukJoong Lee, Yuanzhong Xu, Dehao Chen, Orhan Firat, Yanping Huang, Maxim Krikun, Noam Shazeer, and Zhifeng Chen. Gshard: Scaling giant models with conditional computation and automatic sharding. In *ICLR 2021*, 2021.
- <span id="page-13-4"></span>[LWD+23] Zichang Liu, Jue Wang, Tri Dao, Tianyi Zhou, Binhang Yuan, Zhao Song, Anshumali Shrivastava, Ce Zhang, Yuandong Tian, Christopher Ré, and Beidi Chen. Deja vu: Contextual sparsity for efficient llms at inference time. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett, editors, *International Conference on Machine Learning, ICML 2023, 23-29 July 2023, Honolulu, Hawaii, USA*, volume 202 of *Proceedings of Machine Learning Research*, pages 22137–22176. PMLR, 2023.
- <span id="page-13-8"></span>[LZW+23] Bin Lin, Ningxin Zheng, Lei Wang, Shijie Cao, Lingxiao Ma, Quanlu Zhang, Yi Zhu, Ting Cao, Jilong Xue, Yuqing Yang, and Fan Yang. Efficient GPU kernels for N: m-sparse weights in deep learning. In Dawn Song, Michael Carbin, and Tianqi Chen, editors, *Proceedings of the Sixth Conference on Machine Learning and Systems, MLSys 2023, Miami, FL, USA, June 4-8, 2023*. mlsys.org, 2023.
- <span id="page-13-3"></span>[MAM+23] Iman Mirzadeh, Keivan Alizadeh, Sachin Mehta, Carlo C. Del Mundo, Oncel Tuzel, Golnoosh Samei, Mohammad Rastegari, and Mehrdad Farajtabar. Relu strikes back: Exploiting activation sparsity in large language models. *CoRR*, abs/2310.04564, 2023.
- <span id="page-13-12"></span><span id="page-13-11"></span><span id="page-13-10"></span><span id="page-13-9"></span><span id="page-13-7"></span><span id="page-13-1"></span>[MWM<sup>+</sup>24] Shuming Ma, Hongyu Wang, Lingxiao Ma, Lei Wang, Wenhui Wang, Shaohan Huang, Li Dong, Ruiping Wang, Jilong Xue, and Furu Wei. The era of 1-bit llms: All large language models are in 1.58 bits. *CoRR*, abs/2402.17764, 2024.
	- [Noc80] Jorge Nocedal. Updating quasi-newton matrices with limited storage. *Mathematics of computation*, 35(151):773–782, 1980.
	- [RSR<sup>+</sup>19] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *CoRR*, abs/1910.10683, 2019.
	- [SBBC20] Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Wino-Grande: an adversarial winograd schema challenge at scale. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence*, pages 8732–8740, 2020.
	- [SDZ<sup>+</sup>24] Yutao Sun, Li Dong, Yi Zhu, Shaohan Huang, Wenhui Wang, Shuming Ma, Quanlu Zhang, Jianyong Wang, and Furu Wei. You only cache once: Decoder-decoder architectures for language models. *CoRR*, abs/2405.05254, 2024.
	- [SML<sup>+</sup>21] David R. So, Wojciech Manke, Hanxiao Liu, Zihang Dai, Noam Shazeer, and Quoc V. Le. Primer: Searching for efficient transformers for language modeling. *CoRR*, abs/2109.08668, 2021.
	- [SXZ<sup>+</sup>24] Yixin Song, Haotong Xie, Zhengyan Zhang, Bo Wen, Li Ma, Zeyu Mi, and Haibo Chen. Turbo sparse: Achieving llm sota performance with minimal activated parameters. *arXiv preprint arXiv:2406.05955*, 2024.
	- [TLI<sup>+</sup>23] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. LLaMA: open and efficient foundation language models. *CoRR*, abs/2302.13971, 2023.
	- [VSP<sup>+</sup>17] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 5998–6008, 2017.
- <span id="page-13-6"></span><span id="page-13-5"></span><span id="page-13-2"></span><span id="page-13-0"></span>[WMD<sup>+</sup>23] Hongyu Wang, Shuming Ma, Li Dong, Shaohan Huang, Huaijie Wang, Lingxiao Ma, Fan Yang, Ruiping Wang, Yi Wu, and Furu Wei. Bitnet: Scaling 1-bit transformers for large language models. *CoRR*, abs/2310.11453, 2023.
- <span id="page-14-4"></span><span id="page-14-0"></span>[XGZC23] Mengzhou Xia, Tianyu Gao, Zhiyuan Zeng, and Danqi Chen. Sheared llama: Accelerating language model pre-training via structured pruning. *CoRR*, abs/2310.06694, 2023.
	- [YBS19] Vikas Yadav, Steven Bethard, and Mihai Surdeanu. Quick and (not so) dirty: Unsupervised selection of justification sentences for multi-hop question answering. In Kentaro Inui, Jing Jiang, Vincent Ng, and Xiaojun Wan, editors, *EMNLP-IJCNLP*, 2019.
- <span id="page-14-5"></span>[ZHB+19] Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. HellaSwag: can a machine really finish your sentence? In *Proceedings of the 57th Conference of the Association for Computational Linguistics*, pages 4791–4800, 2019.
- <span id="page-14-1"></span>[ZMZ+21] Aojun Zhou, Yukun Ma, Junnan Zhu, Jianbo Liu, Zhijie Zhang, Kun Yuan, Wenxiu Sun, and Hongsheng Li. Learning N: M fine-grained structured sparse neural networks from scratch. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021.



# <span id="page-14-2"></span>A Visualizations

Figure 10: The gradient magnitude of each linear projection of dense baseline, Q-Sparse with and without STE estimator across different layers.

# <span id="page-14-3"></span>B Hyperparameters

Size	Hidden Size GLU Size #Heads #Layers				<b>Seq Length</b>
300M	1024	2730	16	24	2048
700M	1536	4096	24	24	2048
1.3B	2048	5460	32	24	2048
7B	4096	11008	32	32	2048

Table 5: Model configurations for the scaling experiments of both BitNet b1.58 and LLaMA LLM with Q-Sparse.



Table 6: Hyper-parameters for the scaling experiments of both BitNet b1.58 and LLaMA LLM with Q-Sparse.



Table 7: Hyper-parameters for the continue-training of Mistral 7B with Q-Sparse on Findweb Edu dataset.

<b>Hyperparameters</b>	Value			
Training epoch				
<b>Batch Size</b>	128			
Adam $\beta$	(0.9, 0.95)			
Learning rate	${3e-6, 5e-6, 7e-6}$			
Learning rate schedule	Cosine decay			
Warmup ratio	0.03			
Dropout	x			
Attention dropout	х			
Weight decay				

Table 8: Hyper-parameters for the supervised fine-tuning of Mistral 7B and Qwen-1.5 7B with Q-Sparse on OpenOrca dataset.