NUMERICAL EIGENVALUE OPTIMIZATION BY SHAPE-VARIATIONS FOR MAXWELL'S EIGENVALUE PROBLEM

CHRISTINE HERTER, SEBASTIAN SCHÖPS, AND WINNIFRIED WOLLNER

ABSTRACT. In this paper we consider the free-form optimization of eigenvalues in electromagnetic systems by means of shape-variations with respect to small deformations. The objective is to optimize a particular eigenvalue to a target value. We introduce the mixed variational formulation of the Maxwell eigenvalue problem introduced by Kikuchi (1987) in function spaces of $H(\operatorname{curl}; \Omega)$ and $H^1(\Omega)$. To handle this formulation, suitable transformations of these spaces are utilized, e.g., of Piola-type for the space of $H(\operatorname{curl}; \Omega)$. This allows for a formulation of the problem on a fixed reference domain together with a domain mapping. Local uniqueness of the solution is obtained by a normalization of the the eigenfunctions. This allows us to derive adjoint formulas for the derivatives of the eigenvalues with respect to domain variations. For the solution of the resulting optimization problem, we develop a particular damped inverse BFGS method that allows for an easy line search procedure while retaining positive definiteness of the inverse Hessian approximation. The infinite dimensional problem is discretized by mixed finite elements and a numerical example shows the efficiency of the proposed approach.

1. INTRODUCTION

In this paper, we consider a numerical eigenvalue optimization by shape-variations for Maxwell's eigenvalue problem. This work is motivated by particle accelerator cavities, where an accurate geometry is essential for the acceleration of the particles. Eigenvalue optimization of resonating structures, e.g., in context of electromagnetic cavities, is a challenging area of research because the therein resulting eigenmodes are easily effected to small deformations of the domain. The goal of electromagnetic cavities is to achieve an acceleration eigenmode for the particles. The most relevant eigenmode is the fundamental Transverse Magnetic (TM) mode, shown in Figure 1. For a detailed description of such a cavity as well as its associated components, we refer to the paper about Superconducting TESLA cavities by [8].



FIGURE 1. Electric field of the TM_{010} , also called π -mode

The analytic sensitives of eigenpairs of Maxwell's eigenvalue problem have been considered in isogeometric analysis, e.g., in work of [54], where the sensitivities of the eigenpair have been computed with respect to a scalar parameter. The therein parameter optimization has been done with a simplified formulation of Maxwell's eigenvalue problem excluding the divergence-free constraint on the eigenfunction.

²⁰²⁰ Mathematics Subject Classification. 49M41, 49M37, 49Q10.

Key words and phrases. shape optimization, Maxwell eigenvalue, adjoint calculus, damped inverse BFGS method.

Due to the formulation, care has to be taken in removing spurious solutions. Further, the deformation and its derivatives are expressed in terms of parameters explicitly dependent on weights and control points. Further work of optimizing resonant structures on this approach has been seen in, e.g., [39]. Goals for the optimization of these cavities are uncertainty quantification, see, e.g., [20], and mode tracking, see e.g., [31]. In context of cavities, there already exists several references to multiobjective optimization, e.g., [35, 52] as well as parameter optimization, e.g., [48]. Further, for solving multi-objective optimization problems, we refer to [36] for the use of an evolutionary algorithm, and to [46], addressing a stochastic Maxwell's eigenvalue problem.

In this paper, we consider a free-form eigenvalue optimization problem with respect to a mixed variational formulation of Maxwell's eigenvalue problem by [33], i.e., for a certain eigenvalue λ of the Maxwell operator

$$\nabla \times (\nabla \times u) = \lambda u \qquad \text{in } \Omega,$$

$$\nabla \cdot u = 0 \qquad \text{in } \Omega,$$

$$\nu \times u = 0 \qquad \text{on } \partial\Omega$$

$$\|u\|^2 = 1,$$

which governs the field distribution of the eigenmodes and their associated frequency. In this setup the eigenvalue, and corresponding eigenfunctions u, are to be optimized by choice of the physical domain Ω . The results and formulation have been announced in [28]. As detailed in, e.g., [14], this mixed formulation prohibits spurious eigenvalues. To allow for a larger variety in admissible domains, we consider the method of mappings allowing arbitrary, sufficiently regular and injective, deformations of a reference domain $\widehat{\Omega} \subset \mathbb{R}^d$, $d \in \{2, 3\}$. For the method of mappings is based on kinematic statements from continuum mechanics, where the actual physical domain Ω_q is then given by a deformation $q: \widehat{\Omega} \to \mathbb{R}^d$ by defining $\Omega_q = F(\widehat{\Omega}) = (I+q)\widehat{\Omega}$. For details, we refer to, e.g., [42, 41].

The method of mappings is already applied to several shape optimization problems to derive Fréchet derivatives with respect to shape-variations. For example, we refer to [19], where properties of Fréchet differentiability are derived in the context of Navier-Stokes problems. Due to the, infinite, dimension of the control space standard sensitivity based approaches for derivatives of the eigenvalues, e.g., [38, 5] are no longer applicable. Hence, as announced in [28], we utilize the adjoint approach to calculate eigenvalue derivatives. The origin of the adjoint approach is explained in [43], and perspective of Lagrange multiplier is introduced in [15]. For the adjoint approach in context of optimization problems governed by partial differential equations, we refer to, e.g., [51, 30]. Moreover, the adjoint method has already been applied to many applications of control problems as well as shape and topology optimization problems, e.g., in the domain of structural optimization of solid bodies, see [2, 1, 3, 4], or in fluid mechanics, see, e.g., [25]. Further, optimization problems where the functionals depend on the eigenvalues are studied in, e.g., [34] and discussed in [50]. The particular formulation of the eigenvalue problem and its adjoint are inspired by [29, 47], where this approach is applied to a posteriori error estimation for elliptic eigenvalue problems. For more literature for the computation of shape derivatives in context of PDE constrained optimization, we refer to [18, 49, 24].

In order the concerning optimization problem, we consider a damped inverse BFGS method for infinite dimensional problems. The damping is based on an idea of [45] for the standard BFGS method, see also [44]. Our implementation of the damped inverse BFGS method is already used in [13].

This paper is structured as follows. In Section 2, we model the optimization problem of Maxwell's eigenvalue problem. Therefore, we consider the method of mappings in Section 2.1. Based on this method, we derive the shape optimization problem depending on domain variations in Section 2.2. Afterwards, we discuss the adjoint calculus for a generalized eigenvalue optimization problem in Section 3. where we consider an adjoint representation for the derivatives in Section 3.1 and derive the formulas for Maxwell's eigenvalue optimization problem with domain transformations in Section 3.2. In Section 4, we discuss the optimization method used for the solution of the Maxwell eigenvalue optimization problem. In particular, we will introduce a damped inverse BFGS method. Here, the damping is utilized to allow the use of an Armijo backtracking linesearch within the optimization while still guaranteeing positive definiteness of the approximate inverse Hessian. Finally, in Section 5, we provide the details of the finite element discretization using a mixed finite element method utilizing Lagrange and Nédélec elements to obtain conforming subspaces of $H_0^1(\widehat{\Omega})$ and $H_0(\operatorname{curl}; \widehat{\Omega})$, see, e.g., Monk [40]. Further, several numerical examples show the correctness and efficiency of our implementation.

2. Modeling the Optimization Problem of Maxwell's Eigenvalue Problem

2.1. **Mapping.** Let d = 2, 3, we denote by $\widehat{\Omega} \subset \mathbb{R}^d$ the, simply connected, reference domain. To map this domain to the physical domain $\Omega_q \subset \mathbb{R}^d$ on which the Maxwell eigenvalue problem is to be posed, we define a deformation depending on a displacement q which we consider as our control variable. The transformation of a point $\widehat{x} \subset \widehat{\Omega}$ to a corresponding point $x \subset \Omega_q$ is defined by

$$x = \mathcal{F}_q(\widehat{x}) = q(\widehat{x}) + \widehat{x}.$$

To ensure invertibility of this mapping, as well as invertibility of induced maps between function spaces on $\widehat{\Omega}$ and Ω_q , we require that $q \in Q^{\mathrm{ad}} \subset Q := H^1(\widehat{\Omega}; \mathbb{R}^d)$. More precisely, defining the deformation gradient

(1)
$$DF_q = I + \nabla q,$$

where I denotes the $d \times d$ identity matrix, and $J_q = \det(DF_q)$ the corresponding determinant, we require that for each $q \in Q^{ad}$ it holds

$$\mathrm{DF}_q \in L^{\infty}(\widehat{\Omega}; \mathbb{R}^{d \times d}), \qquad \mathrm{J}_q > 0.$$

Based on these mappings, we need to define suitable transformations to assert the needed function spaces on $\hat{\Omega}$ and Ω are isomorphic. Here, we need to consider the function spaces

$$H_0(\operatorname{curl};\Omega) = \left\{ v \in L^2(\Omega)^d : \nabla \times v \in L^2(\Omega)^n; \ v \times \nu = 0 \text{ on } \partial\Omega \right\},$$
$$H_0^1(\Omega) = \left\{ v \in H^1(\Omega) : v = 0 \text{ on } \partial\Omega \right\},$$

where n = 1 for d = 2 and n = 3 for d = 3 and ν denotes the outward unit normal on $\partial \Omega$.

To this end, see, e.g., [14], we transform a scalar function $\hat{p} \in H_0^1(\widehat{\Omega})$ to a scalar function $p = \mathcal{H}_q(\widehat{p}) \in H_0^1(\Omega_q)$ by

$$p \circ \mathbf{F}_q = \widehat{p}$$
 on $\overline{\Omega}$.

Over and above that, $H_0^1(\widehat{\Omega})$ and $H_0^1(\Omega_q)$ are isomorphic and for any such pair $\widehat{p} \in H_0^1(\widehat{\Omega})$ and $p \in H_0^1(\Omega_q)$, it holds

$$\nabla p \circ \mathbf{F}_q = \mathbf{D} \mathbf{F}_q^{-T} \widehat{\nabla} \widehat{p} \qquad \text{on } \widehat{\Omega}$$

where $\widehat{\nabla}$ and ∇ denote the gradient with respect to the reference coordinates \widehat{x} and the physical coordinates x.

For $H_0(\operatorname{curl}; \Omega)$ we need to apply the covariant Piola mapping. Therefore, for $\widehat{u} \in H_0(\operatorname{curl}; \widehat{\Omega})$ we associate a function $u = \mathcal{G}_q(\widehat{u}) \in H_0(\operatorname{curl}; \Omega_q)$ by the mapping

$$u \circ \mathbf{F}_q = \mathbf{D} \mathbf{F}_q^{-T} \widehat{u}$$
 on $\widehat{\Omega}$

Then for $u \in H_0(\operatorname{curl}; \Omega_q)$ and corresponding $\widehat{u} \in H_0(\operatorname{curl}; \widehat{\Omega})$, it holds that in the three-dimensional case

$$abla imes u \circ \mathbf{F}_q = \frac{1}{\mathbf{J}_q} \mathbf{D} \mathbf{F}_q \widehat{\nabla} \times \widehat{u} \qquad \text{on } \widehat{\Omega}.$$

In the two-dimensional case it holds that

$$\nabla \times u \circ \mathbf{F}_q = \frac{1}{\mathbf{J}_q} \widehat{\nabla} \times \widehat{u} \qquad \text{on } \widehat{\Omega}.$$

In addition, the local volume change between the two domains satisfies

$$dx = J_{\alpha} d\hat{x}.$$

For further details we refer to, e.g., [40, 16].

2.2. Shape Optimization Problem. Based on the domain mapping introduced in Section 2.1. We define the following shape optimization problem of Maxwell's eigenvalue problem. We look for the solution of the problem

(2)

$$\begin{array}{c} \min J(q,\lambda(q)) \\ \text{s.t. } \nabla \times (\nabla \times u) = \lambda u & \text{ in } \Omega_q \\ \nabla \cdot u = 0 & \text{ in } \Omega_q \\ \nu \times u = 0 & \text{ on } \partial \Omega_q \\ \|u\|_{\Omega_q}^2 = 1, \end{array}$$

where a particular eigenvalue, e.g., smallest, is selected from the possible solutions of (2). Here, and following, $\|\cdot\|$ and (\cdot, \cdot) are the usual L^2 norm and scalar product on $\widehat{\Omega}$ while an index Ω_q refers to the respective quantity on Ω_q . Furthermore, ν is the outer unit normal vector to the boundary $\partial\Omega_q$. The generalized eigenvalue problem of (2) is reformulated in weak form using the variational formulation by Kikuchi [33], also seen in [14]. It is to find an eigenvalue $\lambda \in \mathbb{R}$ and corresponding eigenvector $0 \neq u \in H_0(\operatorname{curl}; \Omega_q)$ such that, for some $\psi \in H_0^1(\Omega_q)$,

(3)
$$(\nabla \times u, \nabla \times v)_{\Omega_q} + (\nabla \psi, v)_{\Omega_q} = \lambda(u, v)_{\Omega_q} \quad \forall \ v \in H_0(\operatorname{curl}; \Omega_q) \\ (u, \nabla \varphi)_{\Omega_q} = 0 \qquad \forall \ \varphi \in H_0^1(\Omega_q)$$

Considering now (3) on the reference domain $\widehat{\Omega}$ and applying the domain mapping introduced in Section 2.1, we derive the following transformed equations on the reference domain. Let $u, v \in H_0(\operatorname{curl}; \Omega_q), \varphi \in H_0^1(\Omega_q)$ and corresponding $\widehat{u}, \widehat{v} \in H_0(\widehat{\operatorname{curl}}; \widehat{\Omega}), \widehat{\varphi} \in H_0^1(\widehat{\Omega})$ be arbitrary. In case of d = 3 the curl-equation is given by

$$a(q; \hat{u}, \hat{v}) \stackrel{d=3}{\coloneqq} \int_{\Omega_q} \left(\nabla \times u, \nabla \times v \right) \mathrm{dx} \qquad = \int_{\widehat{\Omega}} \frac{1}{\mathrm{J}_{\mathrm{q}}} \left(\mathrm{DF}_q \, \nabla \times \hat{u}, \mathrm{DF}_q \, \nabla \times \hat{v} \right) \mathrm{d}\hat{\mathbf{x}}$$

while for d = 2, it is

$$a(q; \widehat{u}, \widehat{v}) \stackrel{d=2}{\coloneqq} \int_{\Omega_q} \left(\nabla \times u, \nabla \times v \right) \mathrm{dx} \qquad = \int_{\widehat{\Omega}} \frac{1}{\mathrm{J}_q} \left(\nabla \times \widehat{u}, \nabla \times \widehat{v} \right) \mathrm{d}\widehat{x}.$$

Independent of d = 2, 3, the remaining terms are transformed as follows.

$$b(q; \hat{u}, \hat{\varphi}) \coloneqq \int_{\Omega_q} (u, \nabla \varphi) \, \mathrm{dx} \qquad \qquad = \int_{\widehat{\Omega}} \mathcal{J}_q \left(\mathrm{DF}_q^{-T} \, \hat{u}, \mathrm{DF}_q^{-T} \, \nabla \hat{\varphi} \right) \, \mathrm{d}\hat{\mathbf{x}},$$
$$m(q; \hat{u}, \hat{v}) \coloneqq \int_{\Omega_q} (u, v) \, \mathrm{dx} \qquad \qquad = \int_{\widehat{\Omega}} \mathcal{J}_q \left(\mathrm{DF}_q^{-T} \, \hat{u}, \mathrm{DF}_q^{-T} \, \hat{v} \right) \, \mathrm{d}\hat{\mathbf{x}}.$$

Hence the weak formulation of the eigenvalue problem becomes find

$$(\lambda, u, \psi) \in \mathbb{R} \times H_0(\widehat{\operatorname{curl}}; \widehat{\Omega}) \times H_0^1(\widehat{\Omega})$$

such that

$$a(q; u, v) + b(q; v, \psi) = \lambda m(q; u, v) \qquad \forall v \in H_0(\widehat{\operatorname{curl}}; \widehat{\Omega}),$$
$$b(q; \varphi, u) = 0 \qquad \forall \varphi \in H_0^1(\widehat{\Omega}).$$

We introduce the form $k: Q^{\mathrm{ad}} \times (H_0(\widehat{\mathrm{curl}}; \widehat{\Omega}) \times H_0^1(\widehat{\Omega}))^2 \to \mathbb{R}$ for notational convenience, by

$$k(q;(u,\psi),(v,\varphi)) := a(q;u,v) + b(v,\psi) + b(u,\varphi).$$

The variational form (3) can be written as find $(\lambda, u, \psi) \in \mathbb{R} \times H_0(\widehat{\operatorname{curl}}; \widehat{\Omega}) \times H_0^1(\widehat{\Omega})$ solving

(4)
$$k(q;(u,\psi),(v,\varphi)) = \lambda m(q;u,v) \quad \forall (v,\varphi) \in H_0(\widehat{\operatorname{curl}};\widehat{\Omega}) \times H_0^1(\widehat{\Omega}).$$

We obtain the discretized formulation of (4) straight forward by utilization of the Galerkin method.

3. Adjoint Calculus for a Generalized Eigenvalue Optimization Problem

3.1. An Adjoint Representation for the Derivatives. We consider a general eigenvalue optimization problem

(5)
$$\min_{q,\lambda,u} J(q,\lambda(q))$$
$$k(q;\mathbf{u},\mathbf{v}) = \lambda(q) m(q;\mathbf{u},\mathbf{v}) \quad \forall \mathbf{v} \in \mathbf{U}$$
$$m(q;\mathbf{u},\mathbf{u}) = 1,$$
$$\mathbf{u} \in \mathbf{U},$$
$$\lambda \in \mathbb{R},$$
$$q \in Q^{\mathrm{ad}}.$$

Here Q^{ad} is the set of admissible controls and **U** is the space, where we search for eigenfunctions. In the example considered in Section 2.2, it is $\mathbf{U} = H_0(\widehat{\mathrm{curl}}; 0, \widehat{\Omega}) \times H_0^1(\widehat{\Omega})$ and functions can be decomposed as $\mathbf{u} = (u, \psi)$, $\mathbf{v} = (v, \varphi)$. Further, we assume the cost functional $J : Q \times \mathbb{R} \to \mathbb{R}$ to be continuously differentiable on $Q^{\mathrm{ad}} \times \mathbb{R}$. The forms $k, m : Q \times \mathbf{U} \times \mathbf{U} \to \mathbb{R}$ are linear in the last two arguments. Moreover, m is assumed to be symmetric with respect to the last two arguments. Further, they are both differentiable on $Q^{\mathrm{ad}} \times \mathbf{U} \times \mathbf{U}$. Here, differentiability on Q^{ad} is to be understood in terms of sufficiently regular perturbations $p \in \widetilde{Q}$ such that smallness of p implies that the forms k, m remain well-defined.

For each $q \in Q^{\text{ad}}$, we assume that the eigenvalue problem $k(q, u) = \lambda(q) m(q, u)$ admits, a sequence $\lambda_0(q) \leq \lambda_1(q) \leq \ldots$ of real eigenvalues, which holds true for the considered Maxwell eigenvalue problem, see, e.g., [40, Chapter 4.7]. To apply adjoint calculus, we assume that, after normalization, the selected eigenvalue and eigenfunction pair (λ, \mathbf{u}) to be locally unique; and thus in particular the eigenvalue to be simple. Moreover, we assume a gap of real eigenvalues between the chosen eigenvalue $\lambda_i(q)$ and the others, i.e., without crossing, which implies that there exists $\rho > 0$, independent of q, such that

$$|\lambda_i(q) - \lambda_j(q)| \ge \rho$$
 for all $j \ne i$.

The selection rule, e.g., $\lambda(q) = \lambda_0(q)$, is understood implicitly defining a solution operator $S: Q^{\mathrm{ad}} \to \mathbb{R} \times \mathbf{U}$ by defining $q \mapsto S(q) = (\lambda(q), \mathbf{u}(q)) = (\lambda, \mathbf{u})$ to be the particularly chosen eigenvalue-eigenfunction pair.

With the help of the solution operator, we can define the reduced problem

(6)
$$\min_{q \in Q^{\mathrm{ad}}} j(q) := J(q, \lambda(q)).$$

We can now utilize standard Lagrange techniques, see, e.g., [51, 12], to obtain a representation of the derivative $j'(q) \in Q^*$ and the Q-gradient $\nabla_Q j(q) \in Q$. To this end, we introduce the Lagrangian

$$\mathcal{L}: Q^{\mathrm{ad}} \times (\mathbb{R} \times \mathbf{U}) \times (\mathbb{R} \times \mathbf{U})$$

of problem (6) as

(7)
$$\mathcal{L}(q, (\lambda, \mathbf{u}), (\mu, \mathbf{z})) = J(q, \lambda) - k(q; \mathbf{u}, \mathbf{z}) + \lambda m(q; \mathbf{u}, \mathbf{z}) + \mu (m(q; \mathbf{u}, \mathbf{u}) - 1)$$

where $\mathbf{z} \in \mathbf{U}$ will be the adjoint state and μ is the multiplier for the normalization of the eigenfunction condition.

Then as usual, we can recover the state equation (eigenvalue/eigenfunction) from the condition

$$0 = \mathcal{L}'_{(\mu,\mathbf{z})}(q,(\lambda,\mathbf{u}),(\mu,\mathbf{z}))(\tau,\mathbf{v}) \qquad \forall (\tau,\mathbf{v}) \in \mathbb{R} \times \mathbf{U}$$
$$= -k(q;\mathbf{u},\mathbf{v}) + \lambda m(q;\mathbf{u},\mathbf{v})$$
$$+ \tau(m(q;\mathbf{u},\mathbf{u}) - 1)$$

using linearity of k, m in the last argument. The adjoint state is then defined by

$$\begin{split} 0 &= \mathcal{L}'_{(\lambda,\mathbf{u})}(q,(\lambda,\mathbf{u}),(\mu,\mathbf{z}))(\tau,\mathbf{v}) & \forall (\tau,\mathbf{v}) \in \mathbb{R} \times \mathbf{U} \\ &= J'_{\lambda}(q,\lambda)\tau + \tau \, m(q;\mathbf{u},\mathbf{z}) \\ &- k(q;\mathbf{v},\mathbf{z}) + \lambda \, m(q;\mathbf{v},\mathbf{z}) + 2\mu m(q;\mathbf{u},\mathbf{v}), \end{split}$$

where τ is the test function of the eigenvalue and **v** is the test function of the eigenfunction. using linearity of k, m in the last two arguments and symmetry of m. Setting $\mu = 0$ and considering variations in **v**, we see that **z** solves the adjoint eigenvalue problem

$$k(q; \mathbf{v}, \mathbf{z}) = \lambda m(q; \mathbf{v}, \mathbf{z}) \qquad \forall \mathbf{v} \in \mathbf{U}.$$

Variations in τ yield a normalization of the adjoint eigenfunction

$$m(q; \mathbf{u}, \mathbf{z}) = -J'_{\lambda}(q, \lambda).$$

We obtain the derivative of the reduced cost functional with the thus computed values for $(\lambda, \mathbf{u}, \mu, \mathbf{z})$

$$j'(q)p = \mathcal{L}'_{q}(q, (\lambda, u), (\mu, z))p \quad \forall p \in \widetilde{Q}.$$

Assuming $\widetilde{Q} \subset Q$ to be dense and j'(q) to be extendable to a functional on Q, and not just on \widetilde{Q} , we can compute the Q-gradient $\nabla_Q j(q)$ by inverting the Riesz isomorphism, i.e., solving

$$(\nabla_Q j(q), p)_Q = j'(q)p \qquad \forall p \in Q.$$

3.2. **Derivative Formulas for the Domain Transformation.** In the previous Section 3.1, we derived an adjoint representation for the reduced gradient of a generalized eigenvalue optimization problem. For the shape optimization problem of Maxwell's eigenvalue problem (2), we consider the following cost functional

$$J(q,\lambda) = \frac{1}{2} |\lambda - \lambda_*|^2 + \frac{\alpha}{2} \left(\|q\|^2 + \|\nabla q\|^2 \right) - \beta \int_{\widehat{\Omega}} \ln(\mathbf{J}_q - \varepsilon) \,\mathrm{d}\widehat{x},$$

where $\lambda_* \in \mathbb{R}$ is a target eigenvalue and $\alpha, \beta \in \mathbb{R}$ are given parameters adding some regularization terms to the objective functional. We apply a quadratic penalty regularization using the H^1 -norm to guarantee the existence of q and ∇q . In addition, the deformation gradient DF_q , defined in (1), needs to be invertible and its determinant to be non-negative. To ensure this, we apply a barrier term enforcing $J_q = \det(DF_q) \geq \varepsilon$ for some $\varepsilon > 0$.

Here, the state and adjoint needed simply coincide with the constraining eigenvalue problem for (λ, \mathbf{u}) and the corresponding adjoint eigenvalue problem for \mathbf{z} with a particular normalization, i.e., in the setting of Section 2.2, the state variables are

$$(\lambda, \mathbf{u}) = (\lambda, (u, \psi)) \in \mathbb{R} \times (H_0(\widehat{\operatorname{curl}}; \widehat{\Omega}) \times H_0^1(\widehat{\Omega})).$$

solving

(8)
$$a(q; u, v) + b(q; v, \psi) = \lambda m(q; u, v) \quad \forall v \in H_0(\operatorname{curl}; \Omega),$$
$$b(q; u, \varphi) = 0 \qquad \forall \varphi \in H_0^1(\widehat{\Omega}),$$
$$m(q; u, u) = 1,$$

while the adjoint is

$$\mathbf{z} = (z, \chi)) \in H_0(\widehat{\operatorname{curl}}; \widehat{\Omega}) \times H_0^1(\widehat{\Omega})$$

solving

(9)
$$a(q; v, z) + b(q; v, \chi) = \lambda m(q; v, z) \quad \forall v \in H_0(\operatorname{curl}; \widehat{\Omega})$$
$$b(q; z, \varphi) = 0 \qquad \forall \varphi \in H_0^1(\widehat{\Omega}),$$
$$2m(q; u, z) = \lambda - \lambda_*,$$

where we had defined

$$a(q; u, v) = (\nabla \times \mathcal{G}_q(u), \nabla \times \mathcal{G}_q(v))_{\Omega_q}$$

$$b(q; u, \varphi) = (\mathcal{G}_q(u), \nabla \mathcal{H}_q(\varphi))_{\Omega_q},$$

$$m(q, u, v) = (\mathcal{G}_q(u), \mathcal{G}_q(v))_{\Omega_q},$$

where $\mathcal{H}_q, \mathcal{G}_q$ are the isomorphisms between reference and physical function spaces as defined in Section 2.1.

More tedious is the calculation of the derivatives with respect to the domain transformation. In view of the integral transformations at the end of Section 2.2 it is clear that the, directional, derivatives of the deformation gradient DF_q , its inverse DF_q^{-T} , and its determinant $J_q = \det(J_q)$ are needed, i.e., for $q \in Q^{\text{ad}}$ and direction p, one needs

$$\mathrm{DF}'_q d = \nabla d, \quad (\mathrm{F}_q^{-T})d, \quad \mathrm{J}'_q d.$$

As previously shown, the derivative of the reduced cost functional is given as

(10)
$$\begin{aligned} j'(q) &= \mathcal{L}'_q(q, (\lambda, (u, \psi)), (0, (z, \chi)))p \\ &= J'_q(q)p - a'_q(q; u, z)p - b'_q(q; z, \psi)p - b'_q(q; u, \chi)p + \lambda m'_q(q; u, z)p \end{aligned}$$

already inserting $\mu = 0$. The first term is

$$J_q'(q,\lambda)p = \alpha\left((q,p) + (\nabla q,\nabla p)\right) - \beta \int_{\widehat{\Omega}} \frac{1}{\mathbf{J}_q} (\mathbf{J}_q)' p \,\mathrm{d}\widehat{x},$$

For the remaining terms, the derivatives follow from the respective formulas in Section 2.2, i.e., for d=2

$$\mathbf{a}_{q}'(q; u, z) p \stackrel{d=2}{=} \int_{\widehat{\Omega}} \frac{-1}{\mathbf{J}_{q}^{2}} \mathbf{J}_{q}' p\left(\nabla \times u, \nabla \times z\right) \mathrm{d}\widehat{\mathbf{x}},$$

while for d = 3

8

$$\begin{split} a_q'(q; u, z) p &\stackrel{d=3}{=} \int_{\widehat{\Omega}} \frac{-1}{J_q^2} J_q' p \ (\mathrm{DF}_q \, \nabla \times u, \mathrm{DF}_q \, \nabla \times z) \, \mathrm{d}\widehat{\mathbf{x}} \\ &+ \int_{\widehat{\Omega}} \frac{1}{J_q} \ \left(\mathrm{DF}_q' p \, \nabla \times u, \mathrm{DF}_q \, \nabla \times z \right) \mathrm{d}\widehat{\mathbf{x}} \\ &+ \int_{\widehat{\Omega}} \frac{1}{J_q} \ \left(\mathrm{DF}_q \, \nabla \times u, \mathrm{DF}_q' p \, \nabla \times z \right) \mathrm{d}\widehat{\mathbf{x}}. \end{split}$$

The remaining terms are independent of the dimension

$$\begin{split} b_q'(q;z,\psi) &= \int_{\widehat{\Omega}} \mathcal{J}_q' p\left(\mathrm{DF}_q^{-T} z, \mathrm{DF}_q^{-T} \nabla \psi \right) \mathrm{d}\widehat{\mathbf{x}} \\ &+ \int_{\widehat{\Omega}} \mathcal{J}_q \left((\mathrm{DF}_q^{-T})' p \, z, \mathrm{DF}_q^{-T} \nabla \psi \right) \mathrm{d}\widehat{\mathbf{x}} \\ &+ \int_{\widehat{\Omega}} \mathcal{J}_q \left(\mathrm{DF}_q^{-T} \, z, (\mathrm{DF}_q^{-T}) p \, \nabla \psi \right) \mathrm{d}\widehat{\mathbf{x}}, \\ m_q'(q,u,z) p &= \int_{\widehat{\Omega}} \mathcal{J}_q' p \left(\mathrm{DF}_q^{-T} \, u, \mathrm{DF}_q^{-T} \, z \right) \mathrm{d}\widehat{\mathbf{x}} \\ &+ \int_{\widehat{\Omega}} \mathcal{J}_q \left((\mathrm{DF}_q^{-T})' p \, u, \mathrm{DF}_q^{-T} \, z \right) \mathrm{d}\widehat{\mathbf{x}} \\ &+ \int_{\widehat{\Omega}} \mathcal{J}_q \left(\mathrm{DF}_q^{-T} \, u, (\mathrm{DF}_q^{-T})' p \, z \right) \mathrm{d}\widehat{\mathbf{x}}. \end{split}$$

4. A DAMPED INVERSE BFGS METHOD

In order to solve the reduced optimization problem (6), we consider a damped inverse Broyden-Fletcher-Goldfarb-Shanno (BFGS) method. The damping was introduced for an update for the Hessian approximation by [45], here we show that an analogous approach can be utilized for the approximation of the inverse Hessian. The resulting damped inverse BFGS method is given in Algorithm 1, where it is assumed that the problem is such that a Q-gradient of the reduced objective can be computed.

Remark 1. Note, that to assert global convergence, a check of the angle between d^k and $\nabla_Q j(q^k)$ could be added in the algorithm. However, in our numerical tests convergence to near stationarity was achieved without such safeguards.

Remark 2. In the implementation of Algorithm 1 the operator B_k is never stored but the action $B_k \nabla_Q j(q^k)$ is evaluated using the recursive definition of B_k given by the update formula. To this end, the functions $\tilde{d}, B_k y^k \in Q$ and the scalars $(\tilde{d}^k, y^k)_Q$ and $(\tilde{d}^k - B_k y^k, y^k)$ are stored. To avoid unwanted increase in memory usage, the implementation allows to specify the number m of previous iterates to be kept. The recursive definition then uses the definition $B_{k-m} = B_0$. To ensure compactness of $B_0 - \nabla^2 j(q)$, we choose by default $B_0 = 1/\alpha I$, where I denotes the identity on Q. Hence, the BFGS method guarantees fast convergence, see [23, Theorem 5.2], [32, Theorem 2.5].

In the following lemma, we show that the damping step ensures that positive definiteness of B_k is sufficient to assert positive definiteness of B_{k+1} .

Lemma 1. Let \tilde{d}^k, y^k be given and assume that $B_0 \in \mathcal{L}(Q, Q)$ is a symmetric, positive definite operator. Then the damping step in Algorithm 1 ensures that $\langle y^k, \tilde{d}^k \rangle > 0$. By induction B_k , and thus B_{k+1} , remains positive definite.

Proof. First, we verify the claim, that $\langle y^k, \tilde{d}^k \rangle > 0$ is sufficient to assert positive definiteness of B_{k+1} . The proof of this is almost analog to the finite dimensional case, see, e.g., [53]. To this end, let $p \in Q \setminus \{0\}$, then the update formula asserts

$$(p, B_{k+1}p)_Q = (p, B_k p)_Q + \frac{(p, \tilde{d}^k - B_k y^k)_Q (\tilde{d}^k, p)_Q + (p, \tilde{d}^k)_Q (\tilde{d}^k - B_k y^k, p)_Q}{(\tilde{d}^k, y^k)_Q} - (p, \tilde{d}^k)_Q \frac{(\tilde{d}^k - B_k y^k, y^k)_Q}{(\tilde{d}^k, y^k)_Q^2} (\tilde{d}^k, p)_Q.$$

By expanding the second and third summand, it equals to

$$= (p, B_k p)_Q + 2 \frac{(p, \tilde{d}^k)_Q^2 - (p, B_k y^k)_Q (p, \tilde{d}^k)_Q}{(\tilde{d}^k, y^k)_Q} - (p, \tilde{d}^k)_Q^2 \frac{(\tilde{d}^k, y^k)_Q - (B_k y^k, y^k)_Q}{(\tilde{d}^k, y^k)_Q^2}$$

Again, expanding and re-sort terms provides

$$= (p, B_k p)_Q + \frac{(p, d^k)_Q^2}{(\tilde{d^k}, y^k)_Q} - 2\frac{(p, B_k y^k)_Q (p, d^k)_Q}{(\tilde{d^k}, y^k)_Q} + (p, \tilde{d^k})_Q^2 \frac{(B_k y^k, y^k)_Q}{(\tilde{d^k}, y^k)_Q^2}$$

By adding $\pm \frac{(B_k y^k, \tilde{d}^k)_Q^2}{(y^k, B_k y^k)_Q}$, we obtain

$$= (p, B_k p)_Q + \frac{(p, \tilde{d}^k)_Q^2}{(\tilde{d}^k, y^k)_Q} - \frac{(B_k y^k, \tilde{d}^k)_Q^2}{(y^k, B_k y^k)_Q} + \frac{(B_k y^k, \tilde{d}^k)_Q^2}{(y^k, B_k y^k)_Q} - 2\frac{(p, B_k y^k)_Q (p, \tilde{d}^k)_Q}{(\tilde{d}^k, y^k)_Q} + (p, \tilde{d}^k)_Q^2 \frac{(B_k y^k, y^k)_Q}{(\tilde{d}^k, y^k)_Q^2}$$

where we consider by binomial formula

$$= (p, B_k p)_Q + \frac{(p, d^k)_Q^2}{(\tilde{d}^k, y^k)_Q} - \frac{(B_k y^k, d^k)_Q^2}{(y^k, B_k y^k)_Q} + (B_k y^k, y^k)_Q \left[\frac{(B_k y^k, \tilde{d}^k)_Q}{(B_k y^k, y^k)_Q} - \frac{(p, \tilde{d}^k)_Q}{(\tilde{d}^k, y^k)_Q} \right]^2$$

Under the assumption that B_k is positive definite, only the third summand can be negative, using a square root $B_k^{1/2}$ of the positive definite operator B_k , see, e.g., [37], and Cauchy-Schwarz inequality one obtains

$$(p, B_{k+1}p)_Q \ge (p, B_k p)_Q + \frac{(p, d^k)_Q^2}{(\tilde{d^k}, y^k)_Q} - \frac{(B_k y^k, d^k)_Q^2}{(y^k, B_k y^k)_Q} \\ \ge \|B_k^{1/2}p\|_Q + \frac{(p, \tilde{d^k})_Q^2}{(\tilde{d^k}, y^k)_Q} - \frac{\|B_k^{1/2}y^k\|_Q^2 \|B_k^{1/2}\tilde{d^k}\|_Q^2}{\|B_k^{1/2}y^k\|_Q^2} \ge \frac{(p, \tilde{d^k})_Q^2}{(\tilde{d^k}, y^k)_Q} \ge 0.$$

Now, either, $B_k^{1/2}y^k$ and $B_k^{1/2}\tilde{d}^k$ are linear independent, then the second inequality coming from Cauchy-Schwarz inequality is strict, or there is some $t \neq 0$ such that

$$B_k^{1/2}p = tB_k^{1/2}\widetilde{d}^k$$

and then

10

$$\frac{(p,\tilde{d}^k)_Q^2}{(\tilde{d}^k,y^k)_Q} = \frac{(B_k^{-1/2}B_k^{1/2}p,\tilde{d}^k)_Q^2}{(\tilde{d}^k,y^k)_Q} = t^2 \frac{(B_k^{-1/2}B_k^{1/2}\tilde{d}^k,\tilde{d}^k)_Q^2}{(\tilde{d}^k,y^k)_Q} = t^2 \frac{(\tilde{d}^k,\tilde{d}^k)_Q^2}{(\tilde{d}^k,y^k)_Q} > 0$$

implying positive definiteness of B_{k+1} .

Now, it remains to show that $(y_k, \tilde{d}^k)_Q > 0$. In the case $\theta = 1$, clearly, with $\xi \in (0, 1)$,

$$(y^k, \widetilde{d}^k)_Q \ge \xi \, (y^k, B_k y^k)_Q > 0$$

Otherwise, if $\theta \neq 1$, it is

(y')

$$\begin{split} {}^{k}, \widetilde{d}^{k})_{Q} &= (y^{k}, \theta_{k}\widetilde{d}^{k} + (1 - \theta_{k})B_{k}y^{k})_{Q} \\ &= (1 - \xi)\frac{(y^{k}, B_{k}y^{k})_{Q}}{(y^{k}, B_{k}y^{k})_{Q} - (y^{k}, \widetilde{d}^{k})_{Q}} (y^{k}, \widetilde{d}^{k})_{Q} \\ &+ \left(1 - (1 - \xi)\frac{(y^{k}, B_{k}y^{k})_{Q}}{(y^{k}, B_{k}y^{k})_{Q} - (y^{k}, d^{k})_{Q}}\right) (y^{k}, B_{k}y^{k})_{Q} \\ &= (1 - \xi)\frac{(y^{k}, B_{k}y^{k})_{Q}}{(y^{k}, B_{k}y^{k})_{Q} - (y^{k}, \widetilde{d}^{k})_{Q}} (y^{k}, B_{k}y^{k})_{Q} \\ &+ \frac{(y^{k}, B_{k}y^{k})_{Q} - (y^{k}, \widetilde{d}^{k})_{Q} - (1 - \xi)(y^{k}, B_{k}y^{k})_{Q}}{(y^{k}, B_{k}y^{k})_{Q} - (y^{k}, \widetilde{d}^{k})_{Q}} \\ &= \frac{(y^{k}, B_{k}y^{k})_{Q} \cdot \left((1 - \xi)(y^{k}, \widetilde{d}^{k})_{Q} - (y^{k}, \widetilde{d}^{k})_{Q} + \xi(y^{k}, B_{k}y^{k})_{Q}\right)}{(y^{k}, B_{k}y^{k})_{Q} - (y^{k}, \widetilde{d}^{k})_{Q}} \\ &= \frac{(y^{k}, B_{k}y^{k})_{Q} - \xi(y^{k}, \widetilde{d}^{k})_{Q} + \xi(y^{k}, B_{k}y^{k})_{Q}}{(y^{k}, B_{k}y^{k})_{Q} - (y^{k}, \widetilde{d}^{k})_{Q}} \\ &= \xi(y^{k}, B_{k}y^{k})_{Q} > 0. \end{split}$$

Similar to the finite dimensional damping, see [53], we choose $\xi = 0.2$. Thus the assertion is shown.

5. NUMERICAL EXAMPLES ON A 5-CELL CAVITY

In this section, we show numerical results of the damped inverse BFGS algorithm from Algorithm 1 using adjoint calculus in order to solve the eigenvalue optimization problem (2). We consider a two-dimensional planar 5-cell cavity geometry inspired by a low β cavity design from [17, Chapter 6.4] on a model for the Superconducting-DArmstadt-LINear-ACcelerator (S-DALINAC)¹. Moreover, we consider to optimize the first (smallest) eigenvalue λ_0 to a target eigenvalue λ_* . We clarify here, that the chosen eigenvalue to optimize is not necessary the first one. The only restriction to the theory is that we choose a simple eigenvalue.

We discretize the function spaces with a mixed finite element method. We discretize the space of $H_0^1(\Omega)$ with Lagrange elements. To ensure the tangential continuity of the $H_0(\operatorname{curl}; \Omega)$, we discretize the function space with Nédélec elements. For more details for finite elements and their properties, we refer to, e.g., [40, 14]. For the numerical computation, we use the C++-based optimization library DOpElib [22], which bases on the finite element library deal.II [7, 6]. Further, the eigenvalue problems within the optimization are solved by the Krylov Schur eigenvalue solver with a shift-invert spectral transformation provided in the SLEPc library version 3.18.2 [26, 27] which bases on the PETSc library version 3.18.5 [10, 11, 9]. The convergence tolerance for the eigenvalue solver is set to 10^{-5} . The eigenvalue solver

¹http://www.ikp.tu-darmstadt.de/sdalinac_ikp/

Algorithm 1 Damped inverse BFGS method for an eigenvalue shape optimization problem

- **Input:** Let $q^0 \in Q$ be an initial guess for the control and the initial inverse Hessian approximation be $B_0 \in \mathcal{L}(Q, Q)$ (symmetric, positive definite). We choose the parameter TOL > 0, $k_{\text{max}} \in \mathbb{N}$, and $\gamma \in (0, 0.5)$.
- While $\|\nabla_Q j(q^k)\|_Q > \text{TOL do}$ 1:
- Solve the state eigenvalue problem (8) to obtain $\lambda, u \in \mathbb{R} \times U$. 2:
- Solve the adjoint eigenvalue problem (9) to obtain $\overline{\lambda}, z \in \mathbb{R} \times Z$. 3:
- Compute the gradient $\nabla_Q j(q^k)$, using (10). 4:
- Compute the search direction 5:

$$d^k = -B_k \nabla_Q j(q^k).$$

Set $q_{k+1} = q^k + t_k d^k$, where t_k is computed by backtracking line search, i.e., 6: $t_k = \max(1, \rho, \rho^2, \ldots)$ for some $\rho \in (0, 1)$ such that

$$j(q^k - t_k d^k) \le j(q^k) + \gamma t_k (\nabla_Q j(q^k), d^k)_Q$$

holds.

- Set $\widetilde{d^k} = t_k d^k = q^{k+1} q^k$ and $y^k = \nabla_Q j(q^{k+1}) \nabla_Q j(q^k)$. 7:
- Damping step: 8:
- If $(y^k, \tilde{d}^k)_Q > = \xi(y^k, B_k y^k)_Q$ then 9:
- $\theta_k = 1$ 10:
- else 11:
- $\begin{aligned} \theta_k &= (1-\xi) \frac{(y^k, B_k y^k)_Q}{(y^k, B_k y^k)_Q (\tilde{d}^k, y^k)_Q} \\ \underset{\widetilde{\gamma}_k}{\text{end If}} & \underset{\sim}{\text{in }} \end{aligned}$ 12:
- 13:

14:
$$d^k = \theta_k d^k + (1 - \theta_k) B_k y^k$$

Update $B_{k+1} \in \mathcal{L}(Q, Q)$ such that for any $p \in Q$ it holds 15:

$$B_{k+1}p = B_{k}p + \frac{(d^{k} - B_{k}y^{k})(d^{k}, p)_{Q} + d^{k}(d^{k} - B_{k}y^{k}, p)_{Q}}{(d^{k}, y^{k})_{Q}} - d^{k}\frac{(d^{k} - B_{k}y^{k}, y^{k})_{Q}}{(d^{k}, y^{k})_{Q}^{2}}(d^{k}, p)_{Q}$$

Set $k \leftarrow k+1$. 16: 17: end While

applies a Richardson Krylov solver and the Cholesky preconditioner chosen with the default properties of the SLEPc- and PETSc-libraries for the first example, whereas in the second example, we set the relative convergence tolerance of the Richardson Krylov solver to 10^{-5} and allow this method to automatically determine optimal scaling at each iteration to minimize the 2-norm of the preconditioned residual.

In the following, we consider the starting design of a so-called low β cavity, where the cells get longer in order to take into account the increasing speed of the particle bunch. The geometry is described with the parameters shown in Table 1 and the initial domain of the 5-cell cavity is shown in Figure 2. The meshes of the geometries are created with GMSH [21] and shown in Figure 3. Further, we set the maximum number of iterations of the BFGS method to 100, the termination tolerance is set to TOL $= 10^{-7}$. For the Armijo line search, we set the maximum number of iterations to 10 and $\gamma = \rho = 0.1$. Furthermore, we set the target value $\lambda_* = 6017$ and the regularization parameters $\alpha = 100, \beta = 10^{-6}$ and $\varepsilon = 10^{-4}$. The results in Table 2 show that by a discretization with 22103 DoFs or higher, the



FIGURE 2. Geometry of a Cavity.

TABLE 1. Cavity design parameters for the different cells, see [17]. All dimensions are given in mm.

Cavity Shape Parameter	Cell 1	Cell 2	Cell 3	Cell 4	Cell 5
Equator radius $R_{\rm eq}$	43.44542	43.44542	43.44542	43.44542	43.44542
Iris radius $R_{\rm iris}$	16.5627	16.5627	16.5627	16.5627	16.5627
Horizontal half axis at iris a_1	3.2	3.7184	4.32	5.0208	5.8336
Vertical half axis at iris b_1	3.0592	3.0592	3.0592	3.0592	3.0592
Horizontal half axis at equator	21.98	25.54076	29.673	34.48662	40.06954
a_2					
Vertical half axis at equator b_2	23.82352	23.82352	23.82352	23.82352	23.82352
Length L	25.18	29.25916	33.993	39.50742	45.90314



FIGURE 3. Mesh of the 5-cell Cavity

BFGS method converges after 16 iterations. For a setting with 5438 DoFs, it takes 12. The values of J_q are slightly smaller than 1, which means that we obtain a small shrinkage of the domain. The deformation of a 5-cell cavity after optimization is shown in Figure 4.

6. CONCLUSION

In this paper, we considered an eigenvalue optimization problem with respect to shape-variations in electromagnetic systems motivated by particle accelerator cavities, such as superconducting TESLA or low β cavities, see [8, 17, 20]. We formulated an optimization problem with the mixed formulation by Kikuchi and a domain mapping, where we distinguished between the function spaces of $H_0(\text{curl})$ and H_0^1 . We discussed the approach of adjoint calculus for general eigenvalue optimization problems and we applied adjoint calculus to the concrete problem. In

12

TABLE 2. Results of a freeform optimization with target value $\lambda_* = 6017$ using the BFGS method from algorithm 1 with $\alpha = 100$ and $\beta = 10^{-6}$ on a 5-cell cavity. The initial first (numerical) eigenvalue is given by λ_0 . We show the eigenvalue λ_{it} after termination of the method and the resulting value of the cost functional J, the relative residual of the gradient of the cost functional as well as the minimum and maximum value of the determinant of the deformation gradient J_q .

DoFs	ref.	Lagr.	Néd.	λ_0	it.	$\lambda_{\mathrm{it.}}$	J	r _{rel}	$\mathrm{J}_{q,\mathrm{min}}$	$J_{q,\max}$
5438	0	1	0	6018.47	12	6017	1.728e-10	7.846e-07	0.99998	0.99999
22103	0	2	1	6022.89	16	6017	2.691e-09	9.067e-07	0.99987	0.99999
22103	1	1	0	6021.91	16	6017	1.878e-09	7.243e-07	0.99993	0.99998
86723	2	1	0	6024.65	16	6017	4.532e-09	9.520e-07	0.99991	0.99998



FIGURE 4. Deformation of a 5-cell cavity after optimization of the first eigenvalue to target value $\lambda_* = 6017$ using the BFGS method from algorithm 1 with regularization parameters $\alpha = 100$ and $\beta = 10^{-6}$. The chosen refinement level is 2, the number of DoFs is 86723. Lagrange elements of order 1 and lowest order Nédélec elements are used.

order to solve this optimization problem, we discussed a damped inverse BFGS method for infinite dimensional problems. We proved the preservation of the positive definiteness property of the updating operator which ensures that the curvature condition is fulfilled. Finally, we showed the functionality of this method on a numerical example of an optimization of a cavity domain.

References

- G. Allaire and F. Jouve. Minimum stress optimal design with the level set method. *Engineering Analysis with Boundary Elements*, 32(11):909–918, 2008. doi:10.1016/j.enganabound.2007.05.007.
- [2] G. Allaire, F. Jouve, and A.-M. Toader. Structural optimization using sensitivity analysis and a level-set method. *Journal of Computational Physics*, 194 (1):363–393, 2004. doi:10.1016/j.jcp.2003.09.032.
- [3] G. Allaire, F. Jouve, and N. Van Goethem. Damage and fracture evolution in brittle materials by shape optimization methods. *Journal of Computational Physics*, 230(12):5010–5044, 2011. doi:10.1016/j.jcp.2011.03.024.

- 14 CHRISTINE HERTER, SEBASTIAN SCHÖPS, AND WINNIFRIED WOLLNER
- [4] G. Allaire, C. Dapogny, and P. Frey. Shape optimization with a level set based mesh evolution method. *Computer Methods in Applied Mechanics and Engineering*, 282:22–53, 2014. doi:10.1016/j.cma.2014.08.028.
- [5] A. L. Andrew, K.-W. E. Chu, and P. Lancaster. Derivatives of eigenvalues and eigenvectors of matrix functions. SIAM J. Matrix Anal. Appl., 14(4):903–926, 1993. doi:10.1137/0614061.
- [6] D. Arndt, W. Bangerth, T. C. Clevenger, D. Davydov, M. Fehling, D. Garcia-Sanchez, G. Harper, T. Heister, L. Heltai, M. Kronbichler, R. M. Kynch, M. Maier, J.-P. Pelteret, B. Turcksin, and D. Wells. The deal.II library, version 9.1. *Journal of Numerical Mathematics*, 27(4):203–213, 2019. doi:10.1515/jnma-2019-0064.
- [7] D. Arndt, W. Bangerth, B. Blais, T. C. Clevenger, M. Fehling, A. V. Grayver, T. Heister, L. Heltai, M. Kronbichler, M. Maier, P. Munch, J.-P. Pelteret, R. Rastak, I. Thomas, B. Turcksin, Z. Wang, and D. Wells. The deal.II library, version 9.2. *Journal of Numerical Mathematics*, 28(3):131–146, 2020. doi:10.1515/jnma-2020-0043.
- [8] B. Aune, R. Bandelmann, D. Bloess, B. Bonin, A. Bosotti, M. Champion, C. Crawford, G. Deppe, B. Dwersteg, D. A. Edwards, H. T. Edwards, M. Ferrario, M. Fouaidy, P.-D. Gall, A. Gamp, A. Gössel, J. Graber, D. Hubert, M. Hüning, M. Juillard, T. Junquera, H. Kaiser, G. Kreps, M. Kuchnir, R. Lange, M. Leenen, M. Liepe, L. Lilje, A. Matheisen, W.-D. Möller, A. Mosnier, H. Padamsee, C. Pagani, M. Pekeler, H.-B. Peters, O. Peters, D. Proch, K. Rehlich, D. Reschke, H. Safa, T. Schilcher, P. Schmüser, J. Sekutowicz, S. Simrock, W. Singer, M. Tigner, D. Trines, K. Twarowski, G. Weichert, J. Weisend, J. Wojtkiewicz, S. Wolff, and K. Zapfe. Superconducting TESLA cavities. *Phys. Rev. ST Accel. Beams*, 3:092001, 2000. doi:10.1103/PhysRevSTAB.3.092001.
- [9] S. Balay, W. D. Gropp, L. C. McInnes, and B. F. Smith. Efficient management of parallelism in object oriented numerical software libraries. In E. Arge, A. M. Bruaset, and H. P. Langtangen, editors, *Modern Software Tools in Scientific Computing*, pages 163–202. Birkhauser Press, 1997. doi:10.1007/978-1-4612-1986-6_8.
- [10] S. Balay, S. Abhyankar, M. F. Adams, J. Brown, P. Brune, K. Buschelman, L. Dalcin, A. Dener, V. Eijkhout, W. D. Gropp, D. Kaushik, M. G. Knepley, D. A. May, L. C. McInnes, R. T. Mills, T. Munson, K. Rupp, P. Sanan, B. F. Smith, S. Zampini, H. Zhang, and H. Zhang. PETSc users manual. Technical Report ANL-95/11 - Revision 3.15, Argonne National Laboratory, 2021.
- [11] S. Balay, S. Abhyankar, M. F. Adams, J. Brown, P. Brune, K. Buschelman, L. Dalcin, A. Dener, V. Eijkhout, W. D. Gropp, D. Kaushik, M. G. Knepley, D. A. May, L. C. McInnes, R. T. Mills, T. Munson, K. Rupp, P. Sanan, B. F. Smith, S. Zampini, H. Zhang, and H. Zhang. PETSc Web page, 2021. URL https://petsc.org/.
- [12] R. Becker, D. Meidner, and B. Vexler. Efficient numerical solution of parabolic optimization problems by finite element methods. *Optim. Methods Softw.*, 22 (5):813–833, 2007. doi:10.1080/10556780701228532.
- [13] M. Bezbaruah, M. Maier, and W. Wollner. Shape optimization of optical microscale inclusions. SIAM J. Sci. Comput., 46(4):B377–B402, 2024. doi:10.1137/23M158262.
- [14] D. Boffi. Finite element approximation of eigenvalue problems. Acta Numer., 19:1–120, 2010. doi:10.1017/S0962492910000012.
- [15] J. Cea. Conception optimale ou identification de formes, calcul rapide de la dérivée directionnelle de la fonction coût. *RAIRO Modélisation mathématique*

et analyse numérique, 20(3):371–402, 1986. doi:10.1051/m2an/1986200303711. [16] G. Cohen. Higher-Order Numerical Methods for Transient Wave Equations.

- Scientific computation. Springer, 2002. doi:10.1007/978-3-662-04823-8.
- [17] J. Corno. Numerical Methods for the Estimation of the Impact of Geometric Uncertainties on the Performance of Electromagnetic Devices. PhD thesis, Technische Universität, Darmstadt, 2017. URL http://tuprints.ulb. tu-darmstadt.de/7038/.
- [18] M. C. Delfour and J. P. Zolésio. Shapes and Geometries. Society for Industrial and Applied Mathematics, second edition, 2011. doi:10.1137/1.9780898719826.
- [19] M. Fischer, F. Lindemann, M. Ulbrich, and S. Ulbrich. Fréchet differentiability of unsteady incompressible Navier–Stokes flow with respect to domain variations of low regularity by using a general analytical framework. *SIAM Journal on Control and Optimization*, 55(5):3226–3257, 2017. doi:10.1137/16M1089563.
- [20] N. Georg, W. Ackermann, J. Corno, and S. Schöps. Uncertainty quantification for Maxwell's eigenproblem based on isogeometric analysis and mode tracking. *Computer Methods in Applied Mechanics and Engineering*, 350:228–244, 2019. doi:10.1016/j.cma.2019.03.002.
- [21] C. Geuzaine and J.-F. Remacle. Gmsh: A 3-d finite element mesh generator with built-in pre- and post-processing facilities. *International Journal for Numerical Methods in Engineering*, 79(11):1309–1331, 2009. doi:10.1002/nme.2579.
- [22] C. Goll, T. Wick, and W. Wollner. DOpElib: Differential equations and optimization environment; A goal oriented software library for solving pdes and optimization problems with pdes. Archive of Numerical Software, 5(2):1–14, 2017. doi:10.11588/ans.2017.2.11815.
- [23] A. Griewank. The local convergence of Broyden-like methods on Lipschitzian problems in Hilbert spaces. SIAM J. Numer. Anal., 24(3):684–705, 1987. doi:10.1137/07240.
- [24] J. Haslinger and R. A. E. Mäkinen. Introduction to Shape Optimization. Society for Industrial and Applied Mathematics, 2003. doi:10.1137/1.9780898718690.
- [25] J. Heners, L. Radtke, M. Hinze, and A. Düster. Adjoint shape optimization for fluid-structure interaction of ducted flows. *Computational Mechanics*, 61 (3):259–276, 2018. doi:10.1007/s00466-017-1465-5.
- [26] V. Hernandez, J. E. Roman, and V. Vidal. Slepc: Scalable library for eigenvalue problem computations. In J. M. L. M. Palma, A. A. Sousa, J. Dongarra, and V. Hernández, editors, *High Performance Computing for Computational Science — VECPAR 2002*, volume 2565 of *Lecture Notes in Computer Science*, pages 377–391. Springer, 2003. doi:10.1007/3-540-36569-9 25.
- [27] V. Hernandez, J. E. Roman, and V. Vidal. SLEPc: A scalable and flexible toolkit for the solution of eigenvalue problems. ACM Trans. Math. Software, 31(3):351–362, 2005. doi:10.1145/1089014.108901.
- [28] C. Herter, S. Schöps, and W. Wollner. Eigenvalue optimization with respect to shape-variations in electromagnetic cavities. *PAMM*, 22(1):e202200122, 2023. doi:10.1002/pamm.202200122.
- [29] V. Heuveline and R. Rannacher. A posteriori error control for finite approximations of elliptic eigenvalue problems. Adv. Comput. Math., 15:107–138, 2001. doi:10.1023/A:1014291224961.
- [30] M. Hinze, R. Pinnau, M. Ulbrich, and S. Ulbrich. Optimization with PDE Constraints, volume 23 of Mathematical Modelling: Theory and Applications. Springer, 2009. doi:10.1007/978-1-4020-8839-1.

- 16 CHRISTINE HERTER, SEBASTIAN SCHÖPS, AND WINNIFRIED WOLLNER
- [31] P. Jorkowski and R. Schuhmann. Mode tracking for parametrized eigenvalue problems in computational electromagnetics. In 2018 International Applied Computational Electromagnetics Society Symposium (ACES), pages 1–2, 2018. doi:10.23919/ROPACES.2018.8364147.
- [32] C. T. Kelley and E. W. Sachs. A new proof of superlinear convergence for Broyden's method in Hilbert space. SIAM J. Optim., 1(1):146–150, 1991. doi:10.1137/0801011.
- [33] F. Kikuchi. Mixed and penalty formulations for finite element analysis of an eigenvalue problem in electromagnetism. *Computer Methods in Applied Mechanics and Engineering*, 64(1):509–521, 1987. doi:10.1016/0045-7825(87)90053-3.
- [34] N. Kikuchi, H.-C. Cheng, and Z.-D. Ma. Optimal Shape and Topology Design of Vibrating Structures. Springer Netherlands, Dordrecht, 1995. doi:10.1007/978-94-011-0453-1 6.
- [35] M. Kranjčević, S. Gorgi Zadeh, A. Adelmann, P. Arbenz, and U. van Rienen. Constrained multiobjective shape optimization of superconducting rf cavities considering robustness against geometric perturbations. *Phys. Rev. Accel. Beams*, 22:122001, 2019. doi:10.1103/PhysRevAccelBeams.22.122001.
- [36] M. Kranjčević, A. Adelmann, P. Arbenz, A. Citterio, and L. Stingelin. Multiobjective shape optimization of radio frequency cavities using an evolutionary algorithm. Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment, 920:106– 114, 2019. ISSN 0168-9002. doi:10.1016/j.nima.2018.12.066.
- [37] C. S. Kubrusly. Spectral Theorem, chapter 3, pages 55–89. Birkhäuser Boston, Boston, 2012. ISBN 978-0-8176-8328-3. doi:10.1007/978-0-8176-8328-3 3.
- [38] P. Lancaster. On eigenvalues of matrices dependent on a parameter. Numerische Mathematik, 6:377–387, 1964. doi:10.1007/BF01386087.
- [39] A. S. Lewis. The mathematics of eigenvalue optimization. Mathematical Programming, 97:155–176, 2003. doi:10.1007/s10107-003-0441-3.
- [40] P. Monk. Finite element methods for Maxwell's equations. Numerical Mathematics and Scientific Computation. Oxford University Press, New York, 2003. doi:10.1093/acprof:oso/9780198508885.001.0001.
- [41] F. Murat and J. Simon. Sur le contrôle par un domaine géométrique. Laboratoire d'Analyse Numérique de l'Université de Paris VI, 1976. URL https://api.semanticscholar.org/CorpusID:124497750.
- [42] F. Murat and J. Simon. Etude de problemes d'optimal design. In J. Cea, editor, Optimization Techniques Modeling and Optimization in the Service of Man Part 2, volume 41 of Lecture Notes in Computer Science, pages 54–62. Springer Berlin Heidelberg, 1976. doi:10.1007/3-540-07623-9_279.
- [43] F. Murat and L. Tartar. Calculus of Variations and Homogenization, volume 31 of Progress in Nonlinear Differential Equations and Their Applications, chapter 6, pages 139–173. Birkhäuser Boston, Boston, MA, 1997. doi:10.1007/978-1-4612-2032-9 6.
- [44] J. Nocedal and S. J. Wright. Numerical Optimization. Springer, New York, NY, USA, 2e edition, 2006. doi:10.1007/978-0-387-40065-5.
- [45] M. J. D. Powell. A fast algorithm for nonlinearly constrained optimization calculations. In Numerical analysis (Proc. 7th Biennial Conf., Univ. Dundee, Dundee, 1977), volume 630 of Lecture Notes in Math., pages 144–157, 1978. doi:10.1007/BFb0067703.
- [46] P. Putek, S. G. Zadeh, and U. van Rienen. Multi-objective shape optimization of TESLA-like cavities: Addressing stochastic Maxwell's eigenproblem constraints. *Journal of Computational Physics*, 513:113125, 2024.

doi:10.1016/j.jcp.2024.113125.

- [47] R. Rannacher, A. Westenberger, and W. Wollner. Adaptive finite element solution of eigenvalue problems: Balancing of discretization and iteration error. *Journal of Numerical Mathematics*, 18(4):303–327, 2010. doi:10.1515/JNUM.2010.015.
- [48] V. Shemelin. Optimal choice of cell geometry for a multicell superconducting cavity. *Phys. Rev. ST Accel. Beams*, 12:114701, 2009. doi:10.1103/PhysRevSTAB.12.114701.
- [49] J. Sokolowski and J.-P. Zolesio. Introduction to shape optimization. Springer Berlin Heidelberg, Berlin, Heidelberg, 1992. doi:10.1007/978-3-642-58106-9 1.
- [50] A.-M. Toader and C. Barbarosie. 6. Optimization of eigenvalues and eigenmodes by using the adjoint method. In M. Bergounioux, Édouard Oudet, M. Rumpf, G. Carlier, T. Champion, and F. Santambrogio, editors, *Topological Optimization and Optimal Transport*, volume 17 of *Radon Ser. Comput. Appl. Math.*, pages 142–158. De Gruyter, Berlin, Boston, 2017. doi:10.1515/9783110430417-006.
- [51] F. Tröltzsch. Optimal control of partial differential equations, volume 112 of Graduate Studies in Mathematics. American Mathematical Society, Providence, RI, 2010. doi:10.1090/gsm/112.
- [52] S.-A. Udongwo, S. G. Zadeh, R. Calaga, and U. van Rienen. Design and optimisation of an 800 MHz 5-cell elliptical SRF cavity for T⁻t working point of the future circular Electron-Positron Collide. In *Proc. IPAC'23*, number 14 in International Particle Accelerator Conference, pages 764–767. JACoW Publishing, Geneva, Switzerland, 2023. doi:10.18429/JACoW-IPAC2023-MOPL089.
- [53] M. Ulbrich and S. Ulbrich. Nichtlineare Optimierung. Mathematik Kompakt. Birkhäuser Basel, 2012. doi:10.1007/978-3-0346-0654-7.
- [54] A. Ziegler, M. Merkel, P. Gangl, and S. Schöps. On the computation of analytic sensitivities of eigenpairs in isogeometric analysis. *Computer Methods in Applied Mechanics and Engineering*, 409:115961, 2023. doi:10.1016/j.cma.2023.115961.

UNIVERSITÄT HAMBURG, FACHBEREICH MATHEMATIK, BUNDESSTR. 55, 20146 HAMBURG *Email address*: christine.herter@uni-hamburg.de

Schlossgartenstr. 8 64289 Darmstadt Email address: sebastian.schoeps@tu-darmstadt.de

UNIVERSITÄT HAMBURG, FACHBEREICH MATHEMATIK, BUNDESSTR. 55, 20146 HAMBURG *Email address*: winnifried.wollner@uni-hamburg.de