# A Unified Model of Congestion Games with Priorities: Two-Sided Markets with Ties, Finite and Non-Affine Delay Functions, and Pure Nash Equilibria

Kenjiro Takazawa\*

July 2024

#### Abstract

The study of equilibrium concepts in congestion games and two-sided markets with ties has been a primary topic in game theory, economics, and computer science. Ackermann, Goldberg, Mirrokni, Röglin, Vöcking (2008) gave a common generalization of these two models, in which a player more prioritized by a resource produces an infinite delay on less prioritized players. While presenting several theorems on pure Nash equilibria in this model, Ackermann et al. posed an open problem of how to design a model in which more prioritized players produce a large but finite delay on less prioritized players. In this paper, we present a positive solution to this open problem by combining the model of Ackermann et al. with a generalized model of congestion games due to Bilò and Vinci (2023). In the model of Bilò and Vinci, the more prioritized players produce a finite delay on the less prioritized players, while the delay functions are of a specific kind of affine function, and all resources have the same priorities. By unifying these two models, we achieve a model in which the delay functions may be finite and non-affine, and the priorities of the resources may be distinct. We prove some positive results on the existence and computability of pure Nash equilibria in our model, which extend those for the previous models and support the validity of our model.

# 1 Introduction

The study of equilibrium concepts in noncooperative games is a primary topic in the fields of game theory, economics, and computer science. In particular, the models of *congestion games* and *two-sided markets with ties* have played important roles in the literature.

Congestion games, introduced by Rosenthal [35] in 1973, represent the human behaviour of avoiding congestion. Each *player* chooses a strategy, which is a set of *resources*. If a resource is shared by many players, then much delay is imposed on those players. The objective of a player is to minimize the total delay of the resources in her strategy. Rosenthal [35] proved that every congestion game is a *potential game*. A noncooperative game is called a potential game if it admits a *potential function*, the existence of which guarantees the existence of a pure Nash equilibrium. Moreover, Monderer and Shapley [32] proved the converse: every potential game can be represented as a congestion game. On the basis of these results, congestion games are recognized as a fundamental model in the study of pure Nash equilibria in noncooperative games (see, e.g., [7, 36]).

<sup>\*</sup>Department of Industrial and Systems Engineering, Faculty of Science and Engineering, Hosei University, Tokyo 184-8584, Japan. takazawa@hosei.ac.jp. Supported by JSPS KAKENHI Grant Numbers JP20K11699, 24K02901, JP24K14828, Japan.

Table 1: Results of Ackermann et al. [1]. "NPS" stands for "Non-Player-Specific," while "PS" stands for "Player-Specific." "Polynomial BR Dynamics" means that there exists a sequence of a polynomial number of best responses reaching a pure Nash equilibrium.

	<b>Consistent Priorities</b>	Inconsistent Priorities
NPS	<b>Polynomial BR Dynamics</b> - Singleton Game (Theorem 2.6) - Matroid Game (Theorem 2.10)	<b>Potential Function</b> - Singleton Game (Theorem 2.7) - Matroid Game (Theorem 2.11)
PS	_	<ul> <li>Potential Function</li> <li>Two-Sided Singleton Market (Theorem 2.9)</li> <li>Two-Sided Matroid Market (Theorem 2.13)</li> <li>Polynomial Algorithm</li> <li>Singleton Game (Theorem 2.8)</li> <li>Matroid Game (Theorem 2.12)</li> </ul>

A two-sided market consists of agents and markets, which have preferences over the other side. Each agent chooses a set of markets. On the basis of the choices of the agents, the markets determine an assignment of the players to the markets according to their preferences over the agents. The objective of a player is to maximize her payoff, which is determined by the assignment. Typical special cases of a two-sided market are the stable matching problem and the Hospitals/Residents problem. Since the pioneering work of Gale and Shapley [14], analyses on equilibria have been a primary topic in the study of two-sided markets, and a large number of generalized models have been proposed. In particular, a typical generalization of allowing *ties* in the preferences [24] critically changes the difficulty of the analyses (see [16, 29]), and attracts intensive interests [15, 17, 21, 22, 25, 26, 27, 30, 42].

In 2008, Ackermann, Goldberg, Mirrokni, Röglin, and Vöking [1] introduced a model which commonly generalizes congestion games and two-sided markets with ties, and is referred to as *congestion games with priorities*. This model is briefly described as follows. Each resource ehas priorities (preferences) with ties over the players. Among the players choosing e in their strategies, only the players most prioritized by e receive a finite delay from e, and the other players receive an infinite delay. In other words, only the most prioritized players are accepted. It is clear that this model generalizes congestion games, and it also generalizes a certain model of two-sided markets with ties, *correlated two-sided markets with ties*.

For several classes of their model, Ackermann et al. [1] presented some positive results on the existence and computability of pure Nash equilibria. These results are summarized in Table 1 and will be formally described in Section 2.2. In *player-specific congestion games*, each resource e has a specific delay function  $d_{i,e}$  for each player i. In a singleton congestion game, every strategy of every player consists of a single resource. In a matroid congestion game, the strategies of each player are the bases of a matroid.

Meanwhile, Ackermann et al. [1] posed an open question of how to design a model in which the less prioritized players receive a finite delay caused by the more prioritized players. We appreciate the importance of this question because such a model can include the many-to-many models of the stable matching problem [4, 5, 9, 12, 38, 39] (see also [29]). In congestion games, the fact that each resource accepts multiple players is essential, since the number of those players determine the cost of the resource. In the models of stables matchings in which each market accepts multiple agents, the preferences of the markets indeed affect the stability of the matchings, but it is not the case that only the most preferred agents are accepted. Thus, such a generalization of congestion games with priorities suggested in [1] is crucial to attain a more reasonable generalization of the stable matching problem. Table 2: Summary of Our Results. "NPS" stands for "Non-Player-Specific," while "PS" stands for "Player-Specific." "Polynomial BR Dynamics" means that there exists a sequence of a polynomial number of better responses reaching a pure Nash equilibrium. "PNE" stands for "Pure Nash Equilibrium."

	<b>Consistent Priorities</b>	Inconsistent Priorities
NPS	<ul> <li>Polynomial BR Dynamics</li> <li>Singleton Game (Theorem 4.1)</li> <li>Matroid Game (Theorem 6.2)</li> <li>Existence of a PNE</li> <li>General Game (Theorem 6.7)</li> </ul>	<b>Potential Function</b> - Singleton Game (Theorem 4.4) - Matroid Game (Theorem 6.3)
PS	<b>Polynomial BR Dynamics</b> - Singleton Game (Theorem 4.1) - Matroid Game (Theorem 6.2)	<ul> <li>Potential Function</li> <li>Two-Sided Singleton Market (Theorem 5.3)</li> <li>Two-Sided Matroid Market (Theorem 6.5)</li> <li>Existence of a PNE</li> <li>Singleton Game (Theorem 4.5)</li> <li>Matroid Game (Theorem 6.4)</li> </ul>

The contributions of the paper are described as follows. We first point out that a generalized model of congestion games by Bilò and Vinci [6] partially answers to the question posed by Ackermann et al. [1]. In their model, the players more prioritized by a resource indeed produce a finite delay on the less prioritized players. Meanwhile, this model only covers a special case of the model of Ackermann et al. [1] in which the delay functions are of a specific kind of affine functions and all resources have the same priorities over the players. We refer to the model of [6] as a *priority-based affine congestion game with consistent priorities*.

A main contribution of this paper is to design a model which gives a positive and full answer to the open problem of Ackermann et al. [1]. By unifying the models of Ackermann et al. [1] and Bilò and Vinci [6], we present a model of congestion games with priorities in which the more prioritized players produce a finite delay on the less prioritized players, the delay function may be non-affine, and the priorities of the resources may be inconsistent. We refer to our model as a *priority-based congestion games with (in)consistent priprities*. We then prove some positive results on the existence and computability of pure Nash equilibria in our model, which extend those for the previous models [1, 6] and support the validity of our model. Our technical results are summarized in Table 2.

The rest of the paper is organized as follows. We review previous results in Section 2. Emphases are put on a formal description of the model and results of congestion games with priorities [1]. In Section 3, we describe our model of priority-based congestion games. In Section 4, we present some positive results on pure Nash equilibria in priority-based singleton congestion games. Section 5 is devoted to a description of how correlated two-sided markets with ties are generalized in our model. Finally, in Section 6, we deal with priority-based congestion games which are not singleton games.

## 2 Preliminaries

Let  $\mathbb{Z}$  denote the set of the integers, and  $\mathbb{R}$  that of the real numbers. Subscripts + and ++ represent that the set consists of nonnegative numbers and positive numbers, respectively. For instance,  $\mathbb{R}_+$  denotes the set of the nonnegative real numbers and  $\mathbb{Z}_{++}$  that of the positive integers.

#### 2.1 Congestion Games

A congestion game is described by a tuple

$$(N, E, (\mathcal{S}_i)_{i \in N}, (d_e)_{e \in E}).$$

Here,  $N = \{1, \ldots, n\}$  denotes the set of the players and E that of the resources. Each player  $i \in N$  has her strategy space  $S_i \subseteq 2^E$ , and chooses a strategy  $S_i \in S_i$ . The collection  $(S_1, \ldots, S_n)$  of the chosen strategies is called a strategy profile. For a resource  $e \in E$  and a strategy profile  $S = (S_1, \ldots, S_n)$ , let  $N_e(S) \subseteq N$  denote the set of players whose strategy includes e, and let  $n_e(S) \in \mathbb{Z}_+$  denote the size of  $N_e(S)$ , i.e.,

$$N_e(S) = \{i \in N : e \in S_i\}, \quad n_e(S) = |N_e(S)|.$$

Each resource  $e \in E$  has its *delay function*  $d_e \colon \mathbb{Z}_{++} \to \mathbb{R}_+$ . In a strategy profile S, the function value  $d_e(n_e(S))$  represents the delay of a resource  $e \in E$ . The objective of each player is to minimize her cost, which is the sum of the delays of the resources in her strategy. Namely, the cost  $\gamma_i(S)$  imposed on a player  $i \in N$  in a strategy profile S is defined as  $\gamma_i(S) = \sum_{e \in S_i} d_e(n_e(S))$ , which is to be minimized.

For a strategy profile  $S = (S_1, \ldots, S_n)$  and a player  $i \in N$ , Let  $S_{-i}$  denote a collection of the strategies in S other than  $S_i$ , namely  $S_{-i} = (S_1, \ldots, S_{i-1}, S_{i+1}, \ldots, S_n)$ . A better response of a player in a strategy profile is a change of her strategy so that her cost strictly decreases. Namely, when  $i \in N$  changes her strategy from  $S_i$  to  $S'_i$  in a strategy profile S, it is a better response if  $\gamma_i(S_{-i}, S'_i) < \gamma_i(S)$ . In particular, a better response from  $S_i$  to  $S'_i$  is a best response if  $S'_i$  minimizes  $\gamma_i(S_{-i}, S'_i)$ . A pure Nash equilibrium is a strategy profile in which no player has a better response. Namely, a strategy profile S is a pure Nash equilibrium if

 $\gamma_i(S) \leq \gamma_i(S_{-i}, S'_i)$  for each player  $i \in N$  and each of her strategy  $S'_i \in \mathcal{S}_i$ .

A potential function  $\Phi$  is one which is defined on the set of the strategy profiles and satisfies

$$\Phi(S_{-i}, S'_i) - \Phi(S) = \gamma_i(S_{-i}, S'_i) - \gamma_i(S)$$

for each strategy profile S, each player  $i \in N$ , and each strategy  $S'_i \in S$ . The existence of a potential function implies the existence of a pure Nash equilibrium, because a strategy profile minimizing the potential function must be a pure Nash equilibrium. A game admitting a potential function is referred to as a *potential game*. The following theorem is a primary result on congestion games, stating that each congestion game is a potential game and vice versa.

**Theorem 2.1** ([32, 35]). A congestion game is a potential game, and hence possesses a pure Nash equilibrium. Moreover, every potential game is represented as a congestion game.

Hereafter, we assume that each delay function  $d_e$   $(e \in E)$  is monotonically nondecreasing, i.e.,  $d_e(x) \leq d_e(x')$  if x < x'.

Study on congestion games from the viewpoint of *algorithmic game theory* [7, 34, 36] has appeared since around 2000. For singleton congestion games, Ieong, McGrew, Nudelman, Shoham, and Sun [23] proved that a pure Nash equilibrium in a singleton congestion game can be attained after a polynomial number of better responses.

**Theorem 2.2** ([23]). In a singleton congestion game, starting from an arbitrary strategy profile, a pure Nash equilibrium is attained after a polynomial number of better (hence, best)responses. This theorem is followed by a large number of extensions. Recall that a *player-specific* congestion game is one in which each resource  $e \in E$  has a delay function  $d_{i,e} \colon \mathbb{Z}_{++} \to \mathbb{R}_+$  specific to each player  $i \in N$ . Milchtaich [31] proved the following theorem for player-specific singleton congestion games.

**Theorem 2.3** ([31]). In a player-specific singleton congestion game, there exists a sequences of polynomial number of best responses starting from an arbitrary strategy profile and reaching a pure Nash equilibrium.

Note that Theorem 2.3 differs from Theorem 2.2 in that not any sequence of best responses reaches to a pure Nash equilibrium.

A significant work along this line is due to Ackermann, Röglin, and Vöking [2, 3], who employed the discrete structure of *matroids* into congestion games. For a finite set E and its subset family  $S \subseteq 2^E$ , the pair (E, S) is a *matroid* if  $S \neq \emptyset$  and

for  $S, S' \in \mathcal{S}$  and  $e \in S \setminus S'$ , there exists  $e' \in S' \setminus S$  such that  $(S \setminus \{e\}) \cup \{e'\} \in \mathcal{S}$ . (1)

A set in S is referred to as a *base*. It follows from (1) that all bases in S has the same cardinality, which is referred to as the *rank* of the matroid (E, S).

A congestion game  $(N, E, (S_i)_{i \in N}, (d_e)_{e \in E})$  is referred to as a matroid congestion game if  $(E, S_i)$  is a matroid for every player  $i \in N$ . It is straightforward to see that a singleton congestion game is a spacial case of a matroid congestion game. Ackermann, Röglin, and Vöking [2, 3] proved the following extensions of Theorems 2.2 and 2.3 to matroid congestion games.

**Theorem 2.4** ([2]). In a matroid congestion game, starting from an arbitrary strategy profile, a pure Nash equilibrium is attained after a polynomial number of best responses.

**Theorem 2.5** ([3]). In a player-specific matroid congestion game, there exists a sequence of polynomial number of better responses starting from an arbitrary strategy profile and reaching a pure Nash equilibrium.

Since these works, matroid congestion games have been recognized as a well-behaved class of congestion games, and study on more generalized and related models followed. In the models of congestion games with mixed objectives [11] and congestion games with complementarities [10, 41], the cost on a player is not necessarily the sum of the delays in her strategy. A budget game [8] is a variant of a congestion game, and their common generalization is proposed in [28]. A resource buying game [19, 40] is another kind of a noncooperative game in which the players share the resources. In all of the above models, the fact that  $(E, S_i)$  is a matroid for each player *i* plays a key role to guaranteeing the existence of a pure Nash equilibrium. A further generalized model in which the strategy space is represented by a polymatroid is studied in [18, 20]. A different kind of relation between matroids and congestion games is investigated in [13].

#### 2.2 Congestion Games with Priorities

Ackermann et al. [1] offered a model which commonly generalizes congestion games and a certain class of two-sided markets with ties. This model is described by a tuple

$$(N, E, (\mathcal{S}_i)_{i \in N}, (p_e)_{e \in E}, (d_e)_{e \in E}),$$

in which the player set N, the resource set E, the strategy spaces  $S_i \subseteq 2^E$   $(i \in N)$ , and the delay functions  $d_e: \mathbb{Z}_{++} \to \mathbb{R}_+$   $(e \in E)$  are the same as those in the classical model in Section 2.1.

What is specific to this model is that each resource  $e \in E$  has a priority function  $p_e \colon N \to \mathbb{Z}_{++}$ . If  $p_e(i) < p_e(j)$  for players  $i, j \in N$ , then the resource e prefers i to j.

In a strategy profile  $S = (S_1, \ldots, S_n)$ , the delay of e imposed on each player in  $N_e(S)$  is determined in the following way. Define  $p_e^*(S) \in \mathbb{Z}_{++} \cup \{+\infty\}$  by

$$p_e^*(S) = \begin{cases} \min\{p_e(i) \colon i \in N_e(S)\} & \text{if } N_e(S) \neq \emptyset, \\ +\infty & \text{if } N_e(S) = \emptyset. \end{cases}$$

For a positive integer q, define  $n_e^q(S) \in \mathbb{Z}_+$  by

$$n_e^q(S) = |\{i \in N_e(S) \colon p_e(i) = q\}|.$$
(2)

Now the delay imposed on a player  $i \in N_e(S)$  by the resource e is defined as

$$\begin{cases} d_e \left( n_e^{p_e^*(S)}(S) \right) & \text{if } p_e(i) = p_e^*(S), \\ +\infty & \text{if } p_e(i) > p_e^*(S). \end{cases}$$

This model is referred to as a *congestion game with priorities*. A special case in which all resources have the same priority function is called a *congestion game with consistent priorities*. The general model is often referred to as a *congestion game with inconsistent priorities*.

It is straightforward to see that the model of congestion games with priorities includes congestion games. An instance  $(N, E, (S_i)_{i \in N}, (d_e)_{e \in E})$  of a congestion game reduces to a congestion game  $(N, E, (S_i)_{i \in N}, (d_e)_{e \in E})$  reduces to a congestion game  $(N, E, (S_i)_{i \in N}, (p_e)_{e \in E}, (d_e)_{e \in E})$ with priorities in which all resources have the same constant priority function. As mentioned above, the model of congestion games with priorities also includes *correlated two-sided markets* with ties. See Section 2.2.2 for details.

#### 2.2.1 Singleton Games

For singleton congestion games with consistent priorities, Ackermann et al. [1] proved the following theorem on the basis of Theorem 2.2.

**Theorem 2.6** ([1]). In a singleton congestion game with consistent priorities, there exists a sequence of a polynomial number of best responses starting from an arbitrary strategy profile and reaching a pure Nash equilibrium.

To the best of our knowledge, an extension of Theorem 2.3 to player-specific delay functions is missing in the literature, and will be discussed in a more generalized form in Section 4.1.

Ackermann et al. [1] further proved that every singleton congestion game with inconsistent priorities is a potential game.

**Theorem 2.7** ([1]). A singleton congestion game with inconsistent priorities is a potential game, and hence possesses a pure Nash equilibrium.

We remark that the potential function establishing Theorem 2.7 obeys a generalized definition of potential functions. It maps a strategy profile to a sequence of vectors, which lexicographically decreases by a better response. The details will appear in our proof of Theorem 4.4, which extends Theorem 2.7 to priority-based singleton congestion games.

For player-specific congestion games with inconsistent priorities, Ackermann et al. [1] designed a polynomial-time algorithm for constructing a pure Nash equilibrium. Let n denote the number of the players and m that of the resources.

**Theorem 2.8** ([1]). A player-specific singleton congestion game with inconsistent priorities possesses a pure Nash equilibrium, which can be computed in polynomial time with  $O(n^3m)$ strategy changes.

#### 2.2.2 Correlated Two-Sided Markets with Ties

Here we describe a *correlated to two-sided market with ties* [1], and see that it can be represented as a player-specific congestion game with inconsistent priorities. For unity, we apply the terminology of congestion games to two-sided markets. For example, we use the terms players and resources instead of agents and markets. We also assume that the objective of a player is to minimize her delay, instead of to maximize her payoff.

A correlated two-sided market with ties is represented by a tuple

$$(N, E, (\mathcal{S}_i)_{i \in N}, (c_{i,e})_{i \in N, e \in E}, (d_e)_{e \in E}).$$

For each pair (i, e) of a player  $i \in N$  and a resource  $e \in E$ , a cost  $c_{i,e} \in \mathbb{R}_+$  is associated. The costs implicitly determine the preferences of the players, since the objective of a player is to minimize her cost. Moreover, each resource e also prefer players with smaller costs, and in particular only accepts the players with smallest cost, which is formally described in the following way.

Let  $S = (S_1, \ldots, S_n)$  be a strategy profile, and let  $e \in E$  be a resource. Let  $c_e^*(S) \in \mathbb{R}_+$  be the minimum cost associated with a player in  $N_e(S)$  and e, i.e.,  $c_e^*(S) = \min\{c_{i,e}: i \in N_e(S)\}$ . Let  $N_e^*(S) \subseteq N_e(S)$  denote the set of the players in  $N_e(S)$  with cost  $c_e^*(S)$ , and let  $|N_e^*(S)| = n_e^*(S)$ . Namely,

$$c_e^*(S) = \min\{c_{i,e} \colon i \in N_e(S)\}, \quad N_e^*(S) = \{i \in N_e(S) \colon c_{i,e} = c_e^*(S)\}, \quad n_e^*(S) = |N_e^*(S)|.$$

Each player in  $N_e(S) \setminus N_e^*(S)$  receives an infinite cost from e. The cost on a player  $i \in N_e^*(S)$ satisfies that it is nonincreasing with respect to  $n_e^*(S)$  and is equal to  $c_e^*(S)$  if  $n_e^*(S) = 1$ , i.e., i is the only player in  $N_e^*(S)$ . This is represented by a bivariate delay function  $d_e : \mathbb{R}_+ \times \mathbb{Z}_{++} \to \mathbb{R}_+$ such that, for each  $x \in \mathbb{R}_+$ ,  $d_e(x, 1) = x$  and  $d_e(x, y)$  is nondecreasing with respect to y. In summary, the cost imposed on a player  $i \in N_e(S)$  by e is equal to

$$\begin{cases} d_e(c_e^*(S), n_e^*(S)) & (i \in N_e^*(S)), \\ +\infty & (i \in N_e(S) \setminus N_e^*(S)). \end{cases}$$
(3)

A correlated two-sided market  $(N, E, (S_i), (c_{i,e}), (d_e))$  with ties reduces to a player-specific congestion game with inconsistent priorities. For a resource  $e \in E$ , construct a priority function  $p_e \colon N \to \mathbb{Z}_{++}$  satisfying that

$$p_e(i) < p_e(j)$$
 if and only if  $c_{i,e} < c_{j,e}$  for each  $i, j \in N$ . (4)

Then, for each pair (i, e) of a player  $i \in N$  and a resource  $e \in E$ , define a player-specific delay function  $d'_{i,e} \colon \mathbb{Z}_{++} \to \mathbb{R}_+$  by

$$d'_{i,e}(y) = d_e(c_{i,e}, y) \quad (y \in \mathbb{Z}_{++})$$

We refer to a correlated two-sided markets with ties in which each strategy of each player is a singleton as a *correlated two-sided singleton markets with ties*. It follows from the above reduction that Theorem 2.8 applies to a correlated two-sided singleton markets with ties. Ackermann et al. [1] proved a stronger result that a correlated two-sided singleton markets with ties has a potential function.

**Theorem 2.9** ([1]). A correlated two-sided singleton market with ties is a potential game, and hence possesses a pure Nash equilibrium.

#### 2.2.3 Extension to Matroid Games

Finally, Ackermann et al. [1] provided the following extensions of Theorems 2.6–2.9 from singleton games to matroid games. For a matroid game, define its rank r as the the maximum rank of the matroids forming the strategy spaces of all players.

A better response of a player  $i \in N$  in a strategy profile S from a strategy  $S_i$  to another strategy  $S'_i$  is referred to as a *lazy better response* if if there exists a sequence  $(S_i^0, S_i^1, ..., S_i^k)$ of strategies of i such that  $S_i^0 = S_i$ ,  $S_i^k = S'_i$ ,  $|S_i^{k'+1} \setminus S_i^{k'}| = 1$  and the cost on i in a strategy profile  $(S_{-i}, S_i^{k'+1})$  is strictly smaller than that in  $(S_{-i}, S_i^{k'})$  for each k' = 0, 1, ..., k - 1. A potential game with respect to lazy better responses is a game admitting a potential function which strictly decreases by a lazy better response.

**Theorem 2.10** ([1]). In a matroid congestion game with consistent priorities, there exists a sequence of a polynomial number of best responses starting from an arbitrary strategy profile and reaching a pure Nash equilibrium.

**Theorem 2.11** ([1]). A matroid congestion game with inconsistent priorities is a potential game with respect to lazy better responses, and hence possesses a pure Nash equilibrium.

**Theorem 2.12** ([1]). A player-specific matroid congestion game with inconsistent priorities possesses a pure Nash equilibrium, which can be computed in polynomial time with  $O(n^3mr)$  strategy changes.

**Theorem 2.13** ([1]). A correlated two-sided matroid market with ties is a potential game with respect to lazy better responses, and hence possesses a pure Nash equilibrium.

#### 2.3 Priority-Based Affine Congestion Games

In this subsection, we describe the model of priority-based affine congestion games with consistent priorities [6], by using the terminology of congestion games with priorities. A priority-based affine congestion game with consistent priorities is described by a tuple

$$(N, E, (\mathcal{S}_i)_{i \in N}, p, (\alpha_e, \beta_e)_{e \in E}).$$

Again, N and E denote the set of the players and that of the resources, respectively, and  $S_i \subseteq 2^E$  is the strategy space of a player  $i \in N$ . Note that all resources have the same priority function  $p: N \to \mathbb{Z}_{++}$ . Each resource  $e \in E$  is associated with two nonnegative real numbers  $\alpha_e, \beta_e \in \mathbb{R}_+$ , which determine the delay function of e in the following manner.

Let S be a strategy profile,  $e \in E$  be a resource, and  $q \in \mathbb{Z}_+$  a positive integer. Define  $n_e^q(S) \in \mathbb{Z}_+$  as in (2), in which  $p_e$  is replaced by p. Similarly, define  $n_e^{\leq q}(S) \in \mathbb{Z}_+$  by

$$n_e^{
(5)$$

Now the delay imposed on a player  $i \in N_e(S)$  by e is defined as

$$\alpha_e \cdot \left( n_e^{$$

which is interpreted in the following way. The delay imposed on player  $i \in N_e(S)$  by  $e \in E$ is affected by the  $n_e^{\langle p(i)}(S)$  players in  $N_e(S)$  more prioritized than *i*. It is also affected by the  $n_e^{p(i)}(S)$  players with the same priority as *i*, which is reflected to  $(n_e^{p(i)}(S) + 1)/2$  in (6). This value is the expected number of the players more or equally prioritized than *i* when the ties of the  $n_e^{p(i)}(S)$  players are broken uniformly at random. Bilò and Vinci [6] proved that every priority-based affine congestion game with consistent priorities has a pure Nash equilibrium, and that it can be constructed by finding a pure Nash equilibrium of the most prioritized players, and then inductively extending the pure Nash equilibrium of the players with up to the k-th priority to those with up to the (k + 1)-st priority. In each step, the game restricted to the players with the (k + 1)-st priority is a potential game.

**Theorem 2.14** ([6]). A priority-based affine congestion game with consistent priorities possesses a pure Nash equilibrium.

We should remark that Bilò and Vinci [6] further conducted an elaborated analysis on the price of anarchy and the price of stability of the pure Nash equilibria of this model, which might be a main contribution of their paper.

# 3 Our Model

We first point out that the model of Bilò and Vinci [6] described in Section 2.3 partially answers to the open question of Ackermann et al. [1]. Indeed, the delay (6) of a player  $i \in N_e(S)$  is finitely affected by the more prioritized players in  $N_e(S)$ . Meanwhile, compared to the model of Ackermann et al. [1], the delay (6) is specific in that it is a particular affine function of  $n_e^{< p(i)}(S)$ and  $n_e^{p(i)}(S)$ , and the priorities of the resources are consistent. Below we resolve these points by providing a common generalization of the two models, which provides a full answer to the open question in [1].

Our model is represented by a tuple

$$(N, E, (\mathcal{S}_i)_{i \in N}, (p_e)_{e \in E}, (d_e)_{e \in E}),$$

which is often abbreviated as  $(N, E, (\mathcal{S}_i), (p_e), (d_e))$ . Again, N and E denote the sets of players and resources, respectively, each player  $i \in N$  has her strategy space  $\mathcal{S}_i \subseteq 2^E$ , and each resource  $e \in E$  has a priority function  $p_e \colon N \to \mathbb{Z}_{++}$ .

Let  $S = (S_1, \ldots, S_n)$  be a strategy profile,  $i \in N$ , and  $e \in S_i$ . Reflecting the delay function (6), our delay function  $d_e : \mathbb{Z}_+ \times \mathbb{Z}_{++} \to \mathbb{R}_+$   $(e \in E)$  is a bivariate function with variables  $n_e^{<p_e(i)}(S)$  and  $n_e^{p_e(i)}(S)$ . Namely, the delay imposed on i by e is described as

$$d_e\left(n_e^{
(7)$$

We assume that each delay function  $d_e$  ( $e \in E$ ) has the following properties:

$$d_e(x,y) \le d_e(x',y) \qquad (\text{if } x < x'), \tag{8}$$

$$d_e(x, y) \le d_e(x, y') \qquad (\text{if } y < y'), \tag{9}$$

$$d_e(x,y) \le d_e(x+y-1,1) \quad \text{(for each } x \in \mathbb{Z}_+ \text{ and } y \in \mathbb{Z}_{++}\text{)}. \tag{10}$$

Property (8) and (9) mean that the delay function  $d_e$  is nondecreasing with respect to  $n_e^{\langle p_e(i)}(S)$ and  $n_e^{p_e(i)}(S)$ , respectively. These properties reflect the monotonicity of the delay functions in the previous models. Property (10) means that the cost on *i* increases if the  $n_e^{p_e(i)}(S) - 1$  players in  $N_e(S)$  with the same priority as *i* are replaced by the same number of more prioritized players. This property captures the characteristic of the models of [1, 6] that prioritized players produce more delays than those with the same priority.

We refer to our model as a priority-based congestion game with inconsistent priorities, or priority-based congestion game for short. If the resources have the same priority function, then the game is referred to as a priority-based congestion game with consistent priorities.

A priority-based affine congestion game  $(N, E, (S_i)_{i \in N}, p, (\alpha_e, \beta_e)_{e \in E})$  with consistent priority [6] is represented as a priority-based congestion game with consistent priorities p and delay function  $d_e: \mathbb{Z}_+ \times \mathbb{Z}_{++} \to \mathbb{R}_+$   $(e \in E)$  defined as in (6), namely

$$d_e\left(n_e^{
(11)$$

It is not difficult to see that the delay function  $d_e$  in (11) satisfies the properties (8)–(10).

A congestion game with inconsistent priorities [1] is also a special case of a priority-based congestion game. Given a congestion game  $(N, E, (\mathcal{S}_i)_{i \in N}, (p_e)_{e \in E}, (d_e)_{e \in E})$  with priorities, define a delay function  $d'_e: \mathbb{Z}_+ \times \mathbb{Z}_{++} \to \mathbb{R}$  of a priority-based congestion game by

$$d'_e(x,y) = \begin{cases} +\infty & (x \ge 1), \\ d_e(y) & (x = 0). \end{cases}$$
(12)

Again, the delay function  $d'_e$  in (12) satisfies the properties (8)–(10) if  $d_e$  is a nondecreasing function. The properties (8) and (9) are directly derived. The property (10) follows from the fact that  $d'_e(x + y - 1, 1) \neq +\infty$  only if (x, y) = (0, 1), and in that case both  $d'_e(x, y)$  and  $d'_e(x + y - 1, 1)$  is equal to  $d'_e(0, 1) = d_e(1)$ .

# 4 Priority-Based Singleton Congestion Games

In this section, we present some theorems on pure Nash equilibria in singleton games in our model.

### 4.1 Consistent Priorities

In this subsection, we present a theorem on pure Nash equilibria in priority-based player-specific singleton congestion games with consistent priorities (Theorem 4.1). This theorem is not only an extension of Theorems 2.2 and 2.6, which concern pure Nash equilibria in non-player-specific singleton congestion games, but also implies the existence of pure Nash equilibria in player-specific congestion games with consistent priorities (Corollary 4.2), which is missing in the literature.

Hereafter, some theorems are marked with  $(\star)$ , meaning that their proofs appear in Appendix.

**Theorem 4.1** (\*). In a priority-based player-specific singleton congestion game  $G = (N, E, (S_i), p, (d_{i,e}))$ with consistent priorities, there exists a sequence of polynomial number of better responses starting from an arbitrary strategy profile and reaching a pure Nash equilibrium.

The following corollary is a direct consequence of Theorem 4.1.

**Corollary 4.2.** In a player-specific singleton congestion game with consistent priorities, there exists a sequences of polynomial number of better responses starting from an arbitrary strategy profile and reaching a pure Nash equilibrium.

**Remark 4.3.** Corollary 4.2 does not imply that a pure Nash equilibrium in a priority-based singleton congestion games which is not player-specific is obtained from an *arbitrary* sequence of best responses. This is because, as described in the proof for Theorem 4.1, the order of the players in the sequence is specified by the priority function.

#### 4.2 Inconsistent Priorities

In this subsection, we investigate priority-based singleton congestion games with inconsistent priorities. We first prove the following extension of Theorem 2.7.

**Theorem 4.4.** A priority-based singleton congestion game  $(N, E, (S_i), (p_e), (d_e))$  with inconsistent priorities is a potential game, and hence possesses a pure Nash equilibrium.

*Proof.* For each strategy profile  $S = (e_1, \ldots, e_n)$ , define its potential  $\Phi(S) \in (\mathbb{R}_+ \times \mathbb{Z}_{++})^n$  as follows. Let  $e \in E$  be a resource, and let  $Q_e(S) = \{q_1, \ldots, q_{k^*}\}$  be a set of integers such that  $Q_e(S) = \{q: n_e^q(S) > 0\}$  and  $q_1 < \cdots < q_{k^*}$ . The resource  $e \in E$  contributes the following  $n_e(S)$  vectors in  $\mathbb{R}_+ \times \mathbb{Z}_{++}$  to  $\Phi(S)$ :

$$(d_{e}(0,1), q_{1}), \dots, (d_{e}(0, n_{e}^{q_{1}}(S)), q_{1}), (d_{e}(n_{e}^{q_{1}}(S), 1), q_{2}), \dots, (d_{e}(n_{e}^{q_{1}}(S), n_{e}^{q_{2}}(S)), q_{2}), \dots, (d_{e}(n_{e}^{< q_{k}}(S), 1), q_{k}), \dots, (d_{e}(n_{e}^{< q_{k}}(S), n_{e}^{q_{k}}(S)), q_{k}), \dots, (d_{e}(n_{e}^{< q_{k}*}(S), 1), q_{k}^{*}), \dots, (d_{e}(n_{e}^{< q_{k}*}(S), n_{e}^{q_{k}*}(S)), q_{k}^{*}).$$
(13)

For two vectors  $(x, y), (x', y') \in \mathbb{R}_+ \times \mathbb{Z}_{++}$ , we define a lexicographic order  $(x, y) \preceq_{\text{lex}} (x', y')$  if

$$x < x'$$
, or  $x = x'$  and  $y \le y'$ .

The strict relation  $(x, y) \prec_{\text{lex}} (x', y')$  means that  $(x, y) \preceq_{\text{lex}} (x', y')$  and  $(x, y) \neq (x', y')$  hold.

The potential  $\Phi(S)$  is obtained by ordering the *n* vectors contributed by all resources in the lexicographically nondecreasing order. We remark that the order in (13) is lexicographically nondecreasing, which can be derived from (8)–(10) as follows. It follows from (9) that

$$d_e(n_e^{< q_k}(S), y) \le d_e(n_e^{< q_k}(S), y+1) \quad (k = 1, \dots, k^*, y = 1, \dots, q_{k-1}),$$
(14)

and from (8) and (10) that

$$d_e\left(n_e^{< q_k}(S), n_e^{q_k}(S)\right) \le d_e\left(n_e^{< q_{k+1}}(S) - 1, 1\right) \le d_e\left(n_e^{< q_{k+1}}(S), 1\right) \quad (k = 1, \dots, k^* - 1).$$
(15)

We then define a lexicographic order over the potentials. For strategy profiles S and S', where

$$\Phi(S) = ((x_1, y_1), \dots, (x_n, y_n)), \quad \Phi(S') = ((x'_1, y'_1), \dots, (x'_n, y'_n)),$$

define  $\Phi(S') \preceq_{\text{lex}} \Phi(S)$  if there exists an integer  $\ell$  with  $1 \leq \ell \leq n$  such that

$$(x'_{\ell'}, y'_{\ell'}) = (x_{\ell'}, y_{\ell'})$$
 for each  $\ell' < \ell$ , and  $(x'_{\ell}, y'_{\ell}) \prec_{\text{lex}}(x_{\ell}, y_{\ell})$ .

The strict relation  $\Phi(S') \prec_{\text{lex}} \Phi(S)$  means that  $\Phi(S') \preceq_{\text{lex}} \Phi(S)$  and  $\Phi(S') \neq \Phi(S)$  hold.

Suppose that a player *i* has a better response in a strategy profile *S*, which changes her strategy from *e* to *e'*. Let  $S' = (S_{-i}, e')$ . Below we show that  $\Phi(S') \prec_{\text{lex}} \Phi(S)$ , which completes the proof.

Let  $p_e(i) = q$  and  $p_{e'}(i) = q'$ . Since the delay imposed on *i* becomes smaller due to the better response, it holds that

$$d_{e'}(n_{e'}^{\leq q'}(S), n_{e'}^{q'}(S) + 1) < d_e(n_e^{\leq q}(S), n_e^{q}(S)).$$
(16)

Note that e' contributes a vector

$$(d_{e'}(n_{e'}^{\leq q'}(S), n_{e'}^{q'}(S) + 1), q')$$
(17)

to  $\Phi(S')$  but not to  $\Phi(S)$ . To prove  $\Phi(S') \prec_{\text{lex}} \Phi(S)$ , it suffices to show that a vector belonging to  $\Phi(S)$  but not to  $\Phi(S')$  is lexcographically larger than the vector (17).

First, consider the vectors in  $\Phi(S)$  contributed by e. Let  $Q_e(S) = \{q_1, \ldots, q_{k^*}\}$ , where  $q_1 < \cdots < q_{k^*}$ . The better response of i changes the vectors in  $\Phi(S)$  whose second component is larger than q, because the first argument of the delay function  $d_e$  decreases by one. If  $q = q_{k^*}$ , then those vectors do not exist and thus we are done. Suppose that  $q = q_k$  for some  $k < k^*$ . Among those vectors, the lexicographically smallest one is

$$\left(d_e\left(n_e^{< q_{k+1}}(S), 1\right), q_{k+1}\right).$$

Recall (15), saying that

$$d_e\left(n_e^{< q_k}(S), n_e^{q_k}(S)\right) \le d_e\left(n_e^{< q_{k+1}}(S), 1\right),$$

and thus

$$d_{e'}\left(n_{e'}^{< q'}(S), n_{e'}^{q'}(S) + 1\right) < d_e\left(n_e^{< q_{k+1}}(S), 1\right)$$

follows from (16). Hence, we conclude that

$$\left(d_{e'}\left(n_{e'}^{< q'}(S), n_{e'}^{q'}(S) + 1\right), q'\right) \prec_{\text{lex}} \left(d_e\left(n_e^{< q_{k+1}}(S), 1\right), q_{k+1}\right).$$

Next, consider the vectors in  $\Phi(S)$  contributed by e'. Without loss of generality, suppose that there exists a positive integer q'' such that  $q'' \in Q_{e'}(S)$  and q'' > q'. Let q'' be the smallest integer satisfying these conditions. The lexicographically smallest vector in  $\Phi(S)$  contributed by e' and changed by the better response of i is

$$\left(d_{e'}\left(n_{e'}^{< q''}(S), 1\right), q''\right).$$

It follows from the property (10) that

$$d_{e'}\left(n_{e'}^{< q'}(S), n_{e'}^{q'}(S) + 1\right) \le d_{e'}\left(n_{e'}^{< q''}(S), 1\right),$$

and thus

$$\left(d_{e'}\left(n_{e'}^{< q'}(S), n_{e'}^{q'}(S) + 1\right), q'\right) \prec_{\text{lex}} \left(d_{e'}\left(n_{e'}^{< q''}(S), 1\right), q''\right),$$

completing the proof.

We next show the following theorem, which corresponds to Theorem 2.8 but does not include a polynomial bound on the number of strategy changes.

**Theorem 4.5**  $(\star)$ . A priority-based player-specific singleton congestion game with inconsistent priorities possesses a pure Nash equilibrium, which can be computed with a finite number of strategy changes.

# 5 Generalized Correlated Two-Sided Markets with Ties

In this section, we introduce the model of generalized correlated two-sided markets with ties, which generalizes correlated two-sided markets with ties described in Section 2.2.2. We show that this model is a special class of priority-based player-specific congestion games with inconsistent priorities, and it includes priority-based congestion games with inconsistent priorities. This is in contrast to the situation of correlated two-sided markets with ties, in which it is unclear whether correlated two-sided markets with ties include congestion games with inconsistent priorities. We then prove that a generalized correlated two-sided market with ties is a potential game, which extends Theorem 2.9.

### 5.1 Model

A generalized correlated two-sided market with ties is described by a tuple

$$(N, E, (\mathcal{S}_i)_{i \in N}, (c_{i,e})_{i \in N, e \in E}, (d_e)_{e \in E}).$$

Again, N and E denote the sets of the players and resources, respectively. For each player  $i \in N$  and each resource  $e \in E$ , a nonnegative real number  $c_{i,e} \in \mathbb{R}_+$  is associated, which implies the preferences of i and e, and are reflected in the delay function  $d_e$  of e in the following way.

Let  $S = (S_1, \ldots, S_n)$  be a strategy profile and  $e \in E$  be a resource. In the same way as (2) and (5), for a nonnegative number  $q \in \mathbb{R}_+$ , define  $n_e^q(S), n_e^{\leq q}(S) \in \mathbb{Z}_+$  by

$$n_e^q(S) = |\{i \in N_e(S) : c_{i,e} = q\}|, n_e^{$$

Note that  $n_e^{c_{i,e}}(S) > 0$  if  $e \in S_i$ . The delay function  $d_e$  is a trivariate function  $d_e \colon \mathbb{R}_+ \times \mathbb{Z}_+ \times \mathbb{Z}_+ \times \mathbb{Z}_+ \to \mathbb{R}_+$ . The cost imposed by e on a player  $i \in N_e(S)$  is

$$d_e\left(c_{i,e}, \, n_e^{< c_{i,e}}(S), \, n_e^{c_{i,e}}(S)\right)$$

Here, the delay functions  $d_e$   $(e \in E)$  have the following properties:

 $d_e(c, x, y) \le d_e(c', x, y) \qquad (\text{if } c < c'), \tag{18}$  $d_e(c, x, y) \le d_e(c, x', y) \qquad (\text{if } x < x'). \tag{19}$ 

$$d_e(c, x, y) \le d_e(c, x', y) \qquad (\text{if } x < x'), \tag{19}$$

$$d_e(c, x, y) \le d_e(c, x, y') \qquad (\text{if } y < y') \tag{20}$$

$$d_e(c, x, y) \le d_e(c, x, y) \qquad (\text{if } y < y), \qquad (20)$$

 $d_e(c, x, y) \le d(c, x + y - 1, 1) \qquad (\text{for each } x \in \mathbb{Z}_+ \text{ and } y \in \mathbb{Z}_{++}). \tag{21}$ 

The properties (18)–(20) represent the monotonicity of  $d_e$ , while (19)–(21) corresponds to the properties (8)–(10) of the delay functions in priority-based congestion games. We also remark that  $d_e(c, 0, 1)$  is not necessarily equal to c, whereas  $d_e(c, 1) = c$  in correlated two-sided markets with ties.

### 5.2 Relation to Other Models

A correlated two-sided market with ties  $(N, E, (\mathcal{S}_i), (c_{i,e}), (d_e))$  is represented as a generalized correlated two-sided market with ties  $(N, E, (\mathcal{S}_i), (c_{i,e}), (d'_e))$  by defining the trivariate function  $d'_e : \mathbb{R}_+ \times \mathbb{Z}_+ \times \mathbb{Z}_+ \to \mathbb{R}_+$  by

$$d'_e(c, x, y) = \begin{cases} d_e(c, y) & \text{if } x = 0, \\ +\infty & \text{if } x \ge 1 \end{cases}$$

for each resource  $e \in E$ .

The following propositions show that generalized correlated two-sided markets with ties lie between priority-based congestion games with inconsistent priorities and priority-based playerspecific congestion games with inconsistent priorities.

**Proposition 5.1** ( $\star$ ). A priority-based congestion games with inconsistent priorities is represented as a generalized correlated two-sided market with ties.

**Proposition 5.2** ( $\star$ ). A generalized correlated two-sided market with ties is represented as a priority-based player-specific congestion games with inconsistent priorities.

### 5.3 Pure Nash Equilibria and Potential

From Proposition 5.2 and Theorem 4.5, it follows that a generalized correlated singleton twosided market has a pure Nash equilibrium and it can be computed with a finite number of strategy changes. What is more, the proof for Theorem 4.4 applies to a generalized correlated singleton two-sided market, and hence it is indeed a potential game.

**Theorem 5.3** (\*). A generalized correlated two-sided singleton market  $(N, E, (S_i), (c_{i,e}), (d_e))$  with ties is a potential game, and hence possesses a pure Nash equilibrium.

# 6 Extension Beyond Singleton Games

In this section, we discuss extensions of the above results on priority-based singleton congestion games into larger classes with respect to the strategy spaces. We present extensions of Theorems 4.1, 4.4, 4.5, and 5.3 into matroid games, followed by an investigation of priority-based congestion games with consistent priorities without any assumption on the strategy spaces of the players.

### 6.1 Matroid Games

The following is a fundamental property of matroids, which is essential to the extension of our arguments for singleton games to matroid games.

**Lemma 6.1** (see, e.g., [33, 37]). Let (E, S) be a matroid,  $S \in S$  be a base, and  $w_e \in \mathbb{R}$  be a weight for each  $e \in E$ . If there exists a base  $S' \in S$  such that  $\sum_{e \in S'} w_e < \sum_{e \in S} w_e$ , then there exists an element  $e \in S$  and  $e' \in E \setminus S$  such that  $(S \setminus \{e\}) \cup \{e'\} \in S$  and  $w_{e'} < w_e$ .

It follows from Lemma 6.1 that we can implement an arbitrary better response of a player in a matroid game as a lazy better response. On the basis of this fact, the proofs for Theorems 4.1, 4.4, 4.5, and 5.3 can be adapted to matroid games.

**Theorem 6.2.** In a priority-based player-specific matroid congestion game with consistent priorities, there exists a sequences of polynomial number of better responses starting from an arbitrary strategy profile and reaching a pure Nash equilibrium.

**Theorem 6.3.** A priority-based matroid congestion game with inconsistent priorities is a potential game, and hence possesses a pure Nash equilibrium.

**Theorem 6.4.** A priority-based player-specific matroid congestion game with inconsistent priority possesses a pure Nash equilibrium, which can be computed with a finite number of strategy changes.

**Theorem 6.5.** A generalized correlated two-sided matroid market with ties is a potential game, and hence possesses a pure Nash equilibrium.

#### 6.2 Arbitrary Strategy Spaces

For a priority-based congestion game  $(N, E, (S_i)_{i \in N}, p, (d_e)_{e \in E})$  with consistent priorities, let  $N^q$  denote the set of the players with priority-function value q, namely  $N^q = \{i \in N : p(i) = q\}$ .

**Lemma 6.6** (\*). Let  $G = (N, E, (S_i)_{i \in N}, p, (d_e)_{e \in E})$  be a priority-based congestion game with consistent priorities. Let  $S = (S_1, \ldots, S_n)$  be its strategy profile and let  $q \in \mathbb{Z}_+$ . Fix the strategy of each player  $j \in N \setminus N^q$  to  $S_j$ , and let  $G^q$  denote the game restricted to the players in  $N^q$ . Then, the game  $G^q$  is a potential game with potential function

$$\Phi(S^q) = \sum_{e \in E} \sum_{k=1}^{n_e(S^q)} d_e(n_e^{< q}(S), k) \quad (S^q = (S_i)_{i \in N^q}).$$

It directly follows from Lemma 6.6 that a pure Nash equilibrium of a priority-based congestion game G with consistent priorities can be constructed by combining pure Nash equilibria  $S^q$  of a game  $G^q$  for each priority-function value q, where  $G^q$  is defined by fixing the strategies of the players in  $N^{q'}$  to form a pure Nash equilibrium of  $G^{q'}$  for each q' < q.

**Theorem 6.7.** A priority-based congestion game with consistent priorities possesses a pure Nash equilibrium.

# 7 Conclusion

We have presented a common generalization of the models of congestion games by Ackermann et al. [1] and Bilò and Vinci [6]. This generalization gives a positive and full answer to the open question posed by Ackermann et al. [1]. We then proved some theorems on the existence of pure Nash equilibria, extending those in [1] and [6].

Once the existence of pure Nash equilibria is established, a possible direction of future work is to design an efficient algorithm for finding a pure Nash equilibrium in our model. Analyses on the price of anarchy and the price of stability in our model is also of interest, as is intensively done for the model of Bilò and Vinci [6].

# References

- [1] H. Ackermann, P. W. Goldberg, V. S. Mirrokni, H. Röglin, and B. Vöcking. A unified approach to congestion games and two-sided markets. *Internet Math.*, 5(4):439–457, 2008.
- [2] H. Ackermann, H. Röglin, and B. Vöcking. On the impact of combinatorial structure on congestion games. J. ACM, 55(6):25:1–25:22, 2008.
- [3] H. Ackermann, H. Röglin, and B. Vöcking. Pure Nash equilibria in player-specific and weighted congestion games. *Theor. Comput. Sci.*, 410(17):1552–1563, 2009.
- [4] M. Baïou and M. Balinski. Many-to-many matching: stable polyandrous polygamy (or polygamous polyandry). Discret. Appl. Math., 101(1-3):1–12, 2000.
- [5] V. Bansal, A. Agrawal, and V. S. Malhotra. Polynomial time algorithm for an optimal stable assignment with multiple partners. *Theor. Comput. Sci.*, 379(3):317–328, 2007.
- [6] V. Bilò and C. Vinci. Congestion games with priority-based scheduling. *Theor. Comput. Sci.*, 974:114094, 2023.

- [7] V. Bilò and C. Vinci. Coping with Selfishness in Congestion Games—Analysis and Design via LP Duality. Monographs in Theoretical Computer Science. An EATCS Series. Springer, 2023.
- [8] M. Drees, M. Feldotto, S. Riechers, and A. Skopalik. Pure Nash equilibria in restricted budget games. J. Comb. Optim., 37(2):620–638, 2019.
- [9] P. Eirinakis, D. Magos, I. Mourtos, and P. Miliotis. Finding all stable pairs and solutions to the many-to-many stable matching problem. *INFORMS J. Comput.*, 24(2):245–259, 2012.
- [10] M. Feldotto, L. Leder, and A. Skopalik. Congestion games with complementarities. In D. Fotakis, A. Pagourtzis, and V. T. Paschos, editors, 10th International Conference on Algorithms and Complexity, CIAC 2017, volume 10236 of Lecture Notes in Computer Science, pages 222–233, 2017.
- [11] M. Feldotto, L. Leder, and A. Skopalik. Congestion games with mixed objectives. J. Comb. Optim., 36(4):1145–1167, 2018.
- [12] T. Fleiner. On the stable b-matching polytope. Math. Soc. Sci., 46(2):149–158, 2003.
- [13] S. Fujishige, M. X. Goemans, T. Harks, B. Peis, and R. Zenklusen. Congestion games viewed from M-convexity. Oper. Res. Lett., 43(3):329–333, 2015.
- [14] D. Gale and L. Shapley. College admissions and the stability of marriage. Am. Math. Mon., 69:9–15, 1962.
- [15] H. Goko, K. Makino, S. Miyazaki, and Y. Yokoi. Maximally satisfying lower quotas in the hospitals/residents problem with ties. In P. Berenbrink and B. Monmege, editors, 39th International Symposium on Theoretical Aspects of Computer Science, STACS 2022, volume 219 of LIPIcs, pages 31:1–31:20, 2022.
- [16] D. Gusfield and R. W. Irving. The Stable Marriage Problem—Structure and Algorithms. Foundations of computing series. MIT Press, 1989.
- [17] K. Hamada, S. Miyazaki, and H. Yanagisawa. Strategy-proof approximation algorithms for the stable marriage problem with ties and incomplete lists. In P. Lu and G. Zhang, editors, 30th International Symposium on Algorithms and Computation, ISAAC 2019, volume 149 of LIPIcs, pages 9:1–9:14, 2019.
- [18] T. Harks, M. Klimm, and B. Peis. Sensitivity analysis for convex separable optimization over integral polymatroids. SIAM J. Optim., 28(3):2222–2245, 2018.
- [19] T. Harks and B. Peis. Resource buying games. In A. S. Schulz, M. Skutella, S. Stiller, and D. Wagner, editors, *Gems of Combinatorial Optimization and Graph Algorithms*, pages 103–111. Springer, 2015.
- [20] T. Harks and V. Timmermans. Uniqueness of equilibria in atomic splittable polymatroid congestion games. J. Comb. Optim., 36(3):812–830, 2018.
- [21] C.-C. Huang, K. Iwama, S. Miyazaki, and H. Yanagisawa. A tight approximation bound for the stable marriage problem with restricted ties. In N. Garg, K. Jansen, A. Rao, and J. D. P. Rolim, editors, *Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques, APPROX/RANDOM 2015*, volume 40 of *LIPIcs*, pages 361– 380, 2015.

- [22] C.-C. Huang and T. Kavitha. Improved approximation algorithms for two variants of the stable marriage problem with ties. *Math. Program.*, 154(1-2):353–380, 2015.
- [23] S. Ieong, R. McGrew, E. Nudelman, Y. Shoham, and Q. Sun. Fast and compact: A simple class of congestion games. In M. M. Veloso and S. Kambhampati, editors, 20th Annual AAAI Conference on Artificial Intelligence, AAAI 2005, pages 489–494, 2005.
- [24] R. W. Irving. Stable marriage and indifference. Discret. Appl. Math., 48(3):261–272, 1994.
- [25] N. Kamiyama. Stable matchings with ties, master preference lists, and matroid constraints. In M. Hoefer, editor, 8th International Symposium, SAGT 2015, volume 9347 of Lecture Notes in Computer Science, pages 3–14. Springer, 2015.
- [26] N. Kamiyama. Many-to-many stable matchings with ties, master preference lists, and matroid constraints. In E. Elkind, M. Veloso, N. Agmon, and M. E. Taylor, editors, 18th International Conference on Autonomous Agents and MultiAgent Systems, AAMAS 2019, pages 583–591. IFAAMAS, 2019.
- [27] T. Kavitha. Stable matchings with one-sided ties and approximate popularity. In A. Dawar and V. Guruswami, editors, 42nd IARCS Annual Conference on Foundations of Software Technology and Theoretical Computer Science, FSTTCS 2022, volume 250 of LIPIcs, pages 22:1–22:17, 2022.
- [28] F. Kiyosue and K. Takazawa. A common generalization of budget games and congestion games. In P. Kanellopoulos, M. Kyropoulou, and A. A. Voudouris, editors, 15th International Symposium on Algorithmic Game Theory, SAGT 2022, volume 13584 of Lecture Notes in Computer Science, pages 258–274. Springer, 2022.
- [29] D. F. Manlove. Algorithmics of Matching Under Preferences, volume 2 of Series on Theoretical Computer Science. WorldScientific, 2013.
- [30] D. Marx and I. Schlotter. Parameterized complexity and local search approaches for the stable marriage problem with ties. *Algorithmica*, 58(1):170–187, 2010.
- [31] I. Milchtaich. Congestion games with player-specific payoff functions. Game. Econ. Behav., 13:111–124, 1996.
- [32] D. Monderer and L. S. Shapley. Potential games. Games Econ. Behav., 14:124–143, 1996.
- [33] K. Murota. *Discrete Convex Analysis*. Society for Industrial and Applied Mathematics, Philadelphia, 2003.
- [34] N. Nisan, T. Roughgarden, É. Tardos, and V. V. Vazirani, editors. Algorithmic Game Theory. Cambridge University Press, 2007.
- [35] R. W. Rosenthal. A class of games possessing pure-strategy Nash equilibria. Int. J. Game Theory, 2:65–67, 1973.
- [36] T. Roughgarden. Twenty Lectures on Algorithmic Game Theory. Cambridge University Press, 2016.
- [37] A. Schrijver. Combinatorial Optimization—Polyhedra and Efficiency. Springer, 2003.
- [38] M. Sotomayor. The lattice structure of the set of stable outcomes of the multiple partners assignment game. Int. J. Game Theory, 28(4):567–583, 1999.

- [39] M. Sotomayor. Three remarks on the many-to-many stable matching prblem. Math. Soc. Sci., 38(1):55–70, 1999.
- [40] K. Takazawa. Generalizations of weighted matroid congestion games: pure Nash equilibrium, sensitivity analysis, and discrete convex function. J. Comb. Optim., 38(4):1043–1065, 2019.
- [41] K. Takazawa. Pure Nash equilibria in weighted congestion games with complementarities and beyond. In M. Dastani, J. S. Sichman, N. Alechina, and V. Dignum, editors, Proceedings of the 23rd International Conference on Autonomous Agents and Multiagent Systems, AAMAS 2024, pages 2495–2497. ACM, 2024.
- [42] Y. Yokoi. An approximation algorithm for maximum stable matching with ties and constraints. In H. Ahn and K. Sadakane, editors, 32nd International Symposium on Algorithms and Computation, ISAAC 2021, volume 212 of LIPIcs, pages 71:1–71:16, 2021.

### A Omitted Proof

### A.1 Proofs from Section 4

In a singleton game, a strategy  $\{e\}$  is simply denoted by e. We use a term *state* to refer to a collection of the strategies of some of the players in N, and let N(S) denote the set of the players contributing a state S. In other words, a strategy profile is a special case of a state Sfor which N(S) = N. For a state S and a resource  $e \in E$ , let  $N_e(S)$  denote the set of players choosing e as the strategy, and let  $|N_e(S)| = n_e(S)$ .

Proof of Theorem 4.1. Let  $\{q_1, q_2, \ldots, q_k\}$  denote the set of the priority-function values of all players, i.e.,

$$\{q_1, q_2, \dots, q_k\} = \{p(i) : i \in N\}, \text{ where } q_1 < q_2 < \dots < q_k$$

For each k' = 1, 2, ..., k, define  $N^{k'} \subseteq N$  by  $N^{k'} = \{i \in N : p(i) = q_{k'}\}.$ 

Let  $S = (e_1, \ldots, e_n)$  be an arbitrary strategy profile of G, and let  $S^{k'}$  be a state of G consisting of the strategies of the players in  $N^{k'}$  in S for each  $k' = 1, 2, \ldots, k$ . We prove the theorem by induction on k'. First, define a player-specific singleton congestion game

$$G^{1} = (N^{1}, E, (\mathcal{S}_{i})_{i \in N^{1}}, (d'_{i,e})_{i \in N^{1}, e \in E})$$

in which the delay function  $d'_{i,e} \colon \mathbb{Z}_{++} \to \mathbb{R}_+$   $(i \in N^1, e \in E)$  is defined by

$$d'_{i,e}(y) = d_{i,e}(0,y) \quad (y \in \mathbb{Z}_{++}).$$

It then follows from Theorem 2.3 that  $G^1$  has a pure Nash equilibrium  $\hat{S}^1$ , which is attained by a polynomial number of best responses from  $S^1$ .

Now let  $k' \in \{1, \ldots, k-1\}$  and suppose that we have a state  $\hat{S}^{k'}$  of the players in  $\bigcup_{\ell=1}^{k'} N^{\ell}$  in which no player has an incentive to change her strategy. Then construct a player-specific singleton congestion game

$$G^{k'+1} = (N^{k'+1}, E, (\mathcal{S}_i)_{i \in N^{k'+1}}, (d'_{i,e})_{i \in N^{k'+1}, e \in E})$$

in which

$$d'_{i,e}(y) = d_{i,e}(n_e(\hat{S}^{k'}), y) \quad (y \in \mathbb{Z}_{++})$$

for each  $e \in E$ . It again follows from Theorem 2.3 that the game  $G^{k'+1}$  has a pure Nash equilibrium and it is attained by a polynomial number of best responses from an arbitrary strategy profile.

By induction, we have proved that a pure Nash equilibrium of a player-specific priority-based singleton congestion game can be attained through a polynomial number of best responses from an arbitrary strategy profile.  $\hfill \Box$ 

Proof of Theorem 4.5. We prove this theorem by presenting an algorithm for computing a pure Nash equilibrium of a priority-based player-specific singleton congestion game  $(N, E, (S_i), (p_e), (d_{i,e}))$ . The algorithm constructs a sequence  $S_0, S_1, \ldots, S_k$  of states in which  $N(S_0) = \emptyset$ ,  $N(S_k) = N$ , and

each player in  $N(S_{k'})$  has no incentive to change her strategy (22)

for each k' = 0, 1, ..., k, implying that  $S_k$  is a pure Nash equilibrium.

It is clear that (22) is satisfied for k' = 0. Below we show how to construct  $S_{k'+1}$  from  $S_{k'}$  under an assumption that  $S_{k'}$  satisfies (22) and  $N(S_{k'}) \subsetneq N$ .

Take a player  $i \in N \setminus N(S_{k'})$ , and let *i* choose a resource  $e \in E$  imposing the minimum cost on *i* if *i* is added to  $N_e(S_{k'})$ . We construct the new state  $S_{k'+1}$  by changing the strategy of each player  $j \in N_e(S_{k'})$  in the following way. The other players do not change their strategies.

For the players in  $N_e(S_{k'})$ , we have the following cases A and B.

**Case A.** No player in  $N_e(S_{k'})$  comes to have a better response when *i* is added to  $N_e(S_{k'})$ .

**Case B.** Some players in  $N_e(S_{k'})$  comes to have a better response when *i* is added to  $N_e(S_{k'})$ .

In Case A, we do not change the strategies of the players in  $N_e(S_{k'})$ . In Case B, if a player  $j \in N_e(S_{k'})$  comes to have a better response, it must hold that  $p_e(j) \ge p_e(i)$ . We further separate Case B into the following two cases.

**Case B1.** There exists a player  $j \in N_e(S_{k'})$  having a better response and satisfying  $p_e(j) = p_e(i)$ .

**Case B2.** Every player  $j \in N_e(S_{k'})$  having a better response satisfies  $p_e(j) > p_e(i)$ .

In each case, the strategies are changed as follows.

**Case B1.** Only one player  $j \in N_e(S_{k'})$  having a better response and  $p_e(j) = p_e(i)$  changes her strategy by discarding her strategy. Namely,  $j \notin N(S_{k'+1})$ . The other players do not change their strategies.

**Case B2.** Every player  $j \in N_e(S_{k'})$  having a better response discards her strategy.

We have now constructed the new state  $S_{k'+1}$ . It is straightforward to see that the state  $S_{k'+1}$  satisfies (22). We complete the proof by showing that this algorithm terminates within a finite number of strategy changes.

For a resource  $e \in E$ , let  $q_e^* = \max\{p_e(i) : i \in N\}$ . For each state  $S_{k'}$  appearing in the algorithm, define its potential  $\Phi(S_{k'}) \in \left( \times_{e \in E} \mathbb{Z}_+^{q_e^*} \right) \times \mathbb{Z}_{++}$  in the following manner. For each resource  $e \in E$ , define a vector  $\phi_e \in \mathbb{Z}_+^{q_e^*}$  by

$$\phi_e(q) = n_e^q(S_{k'}) \quad (q = 1, 2, \dots, q_e^*),$$

which is a contribution of e to the first component of  $\Phi(S_{k'})$ . The first component of  $\Phi(S_{k'})$  is constructed by ordering the vectors  $\phi_e$  ( $e \in E$ ) in the lexicographically nondecreasing order. For a resource  $e \in E$  and a player  $i \in N_e(S_{k'})$ , define  $tol(i, S_{k'}) \in \mathbb{Z}_{++}$  as the maximum number  $y \in \mathbb{Z}_{++}$  such that e is an optimal strategy for i if i shares e with y players having the same priority as e, i.e.,

$$d_{i,e}(n_e^{$$

for each e' with  $e' \neq e$  and  $\{e'\} \in S_i$ . Note that *i* herself is counted in *y*, and hence  $\operatorname{tol}(i, S_{k'}) \geq 1$  for each  $i \in N(S_{k'})$ . Now the second component of the potential  $\Phi(S_{k'})$  is defined as  $\sum_{i \in N(S_{k'})} \operatorname{tol}(i, S_{k'})$ .

We prove that the potential  $\Phi(S_{k'})$  increases lexicographically monotonically during the algorithm. Let a state  $S_{k'+1}$  is constructed from  $S_{k'}$  and the involvement of a player  $i \in N \setminus N(S_{k'})$  choosing a resource  $e \in E$ . It is straightforward to see that  $\phi_{e'}$  is unchanged for each  $e' \in E \setminus \{e\}$ . Consider how the vector  $\phi_e$  changes.

**Case A.** The unique change of  $\phi_e$  is that  $\phi_e(p_e(i))$  increases by one, implying that the first component of  $\Phi(S_{k'+1})$  is lexicographically larger than that of  $\Phi(S_{k'})$ .

**Case B1.** Let  $j^* \in N_e(S_{k'})$  denote the unique player who discard her strategy. Recall that  $p_e(j^*) = p_e(i)$ . It follows that  $\phi_e$  is unchanged, and hence the first component of  $\Phi(S_{k'+1})$  is the same as that of  $\Phi(S_{k'})$ . The second component of  $\Phi(S_{k'+1})$  is strictly larger than that of  $\Phi(S_{k'})$ , because

$$N(S_{k'+1}) = (N(S_{k'}) \cup \{i\}) \setminus \{j^*\},$$
  

$$tol(j, S_{k'+1}) = tol(j, S_{k'}) \quad \text{for each } j \in N(S_{k'}) \setminus \{i, j^*\},$$
  

$$tol(i, S_{k'+1}) \ge n_e^{p_e(i)}(S_{k'}) + 1,$$
  

$$tol(j^*, S_{k'}) = n_e^{p_e(i)}(S_{k'}).$$

**Case B2.** It holds that  $n_e^q(S_{k'+1}) = n_e^q(S_{k'})$  for each  $q < p_e(i)$  and  $n_e^{p_e(i)}(S_{k'+1}) = n_e^{p_e(i)}(S_{k'}) + 1$ . Thus, the first component of  $\Phi$  lexicographically increases.

### A.2 Proofs from Section 5

Proof of Proposition 5.1. Given a priority-based congestion game  $(N, E, (\mathcal{S}_i), (p_e), (d_e))$  with inconsistent priorities, construct a generalized correlated two-sided market  $(N, E, (\mathcal{S}_i), (c_{i,e}), (d'_e))$  with ties by defining

$$c_{i,e} = p_e(i) \qquad (i \in N, e \in E), d'_e(c, x, y) = d_e(x, y). \quad (e \in E, c \in \mathbb{R}_+, x \in \mathbb{Z}_+, y \in \mathbb{Z}_{++}).$$

It is straightforward to see that the delay function  $d'_e$  ( $e \in E$ ) satisfy (18)–(21) in which  $d_e$  is replaced by  $d'_e$ , if the original delay function  $d_e$  satisfies (8)–(10).

Proof of Proposition 5.2. Given a generalized correlated two-sided market  $(N, E, (\mathcal{S}_i), (c_{i,e}), (d_e))$ with ties, construct a priority-based player-specific congestion game  $(N, E, (\mathcal{S}_i), (p_e), (d'_{i,e}))$  with inconsistent priorities as follows. For each resource  $e \in E$ , construct its priority function  $p_e: N \to \mathbb{Z}_+$  in the same way as in (4), and define its delay function  $d'_{i,e}: \mathbb{Z}_+ \times \mathbb{Z}_{++} \to \mathbb{R}_+$ specific to a player  $i \in N$  by

$$d'_{i,e}(x,y) = d_e(p_e(i), x, y) \quad (x \in \mathbb{Z}_+, y \in \mathbb{Z}_{++}).$$

It is straightforward to see that the delay function  $d'_{i,e}$   $(i \in N, e \in E)$  satisfies (8)–(10) in which  $d_e$  is replaced by  $d'_{i,e}$ , if the original delay function  $d_e$  satisfies (18)–(21).

Proof of Theorem 5.3. For each strategy profile  $S = (e_1, \ldots, e_n)$ , define its potential  $\Phi(S) \in (\mathbb{R}_+ \times \mathbb{Z}_{++})^n$  as follows. Let  $e \in E$  be a resource, and let  $Q_e(S) = \{q_1, \ldots, q_{k^*}\}$  be a set of integers such that  $Q_e(S) = \{q: n_e^q(S) > 0\}$  and  $q_1 < \cdots < q_{k^*}$ . The resource  $e \in E$  contributes the following  $n_e(S)$  vectors in  $\mathbb{R}_+ \times \mathbb{Z}_{++}$  to  $\Phi(S)$ :

$$(d_e(q_1, 0, 1), q_1), \dots, (d_e(q_1, 0, n_e(S, q_1)), q_1), (d_e(q_2, n_e^{q_1}(S), 1), q_2), \dots, (d_e(q_2, n_e^{q_1}(S), n_e^{q_2}(S)), q_2), \dots, (d_e(q_k, n_e^{< q_k}(S), 1), q_k), \dots, (d_e(q_k, n_e^{< q_k}(S), n_e^{q_k}(S)), q_k), \dots, (d_e(q_{k^*}, n_e^{< q_{k^*}}(S), 1), q_{k^*}), \dots, (d_e(q_{k^*}, n_e^{< q_{k^*}}(S), n_e^{q_{k^*}}(S)), q_{k^*}))$$

The potential  $\Phi(S)$  is obtained by ordering the *n* vectors contributed by all resources in the lexicographically nondecreasing order. We can observe that the order of the  $n_e(S)$  vectors shown above is lexicographically nondecreasing in the following way. It follows from the property (20) that

$$d_e(q_k, n_e^{< q_k}(S), y) \le d_e(q_k, n_e^{< q_k}(S), y+1)$$

for each  $k = 1, ..., k^*$  and for each  $y = q_1, ..., q_{k-1}$ . It further follows from the properties (18), (19) and (21) that

$$d_e(c, x, y) \le d_e(c, x + y - 1, 1) \le d_e(c', x + y, 1)$$
(23)

if c < c', and in particular

$$d_e(q_k, n_e^{< q_k}(S), n_e^{q_k}(S)) \le d_e(q_{k+1}, n_e^{< q_{k+1}}(S), 1) \quad \text{for each } k = 1, \dots, k^* - 1.$$
(24)

Suppose that a player *i* has a better response in a strategy profile *S*, which changes her strategy from *e* to *e'*, and let  $S' = (S_{-i}, e')$ . Below we show that  $\Phi(S') \prec_{\text{lex}} \Phi(S)$ , which completes the proof.

Let  $c_{i,e} = q$  and  $c_{i,e'} = q'$ . Since the delay imposed on *i* becomes smaller due to the better response, it holds that

$$d_{e'}(q', n_{e'}^{\leq q'}(S), n_{e'}^{q'}(S) + 1) < d_e(q, n_e^{\leq q}(S), n_e^{q}(S)).$$
(25)

Note that e' contributes a vector

$$(d_{e'}(q', n_{e'}^{< q'}(S), n_{e'}^{q'}(S) + 1), q')$$
(26)

to  $\Phi(S')$  but not to  $\Phi(S)$ . To prove  $\Phi(S') \prec_{\text{lex}} \Phi(S)$ , it suffices to show that a vector belonging to  $\Phi(S)$  but not to  $\Phi(S')$  is lexcographically larger than the vector (26).

First, consider the vectors in  $\Phi(S)$  contributed by e. Let  $Q_e(S) = \{q_1, \ldots, q_{k^*}\}$ , where  $q_1 < \cdots < q_{k^*}$ . Due to the better response of i, the vectors in  $\Phi(S)$  whose second component is larger than q changes, because the second argument of the delay function  $d_e$  decreases by one. If  $q = q_{k^*}$ , then those vectors do not exist and thus we are done. Suppose that  $q = q_k$  for some  $k < k^*$ . Among those vectors, the lexicographically smallest one is

$$(d_e(q_{k+1}, n_e^{< q_{k+1}}(S), 1), q_{k+1})$$

It follows from (24) and (25) that

$$d_{e'}(q', n_{e'}^{\leq q'}(S), n_{e'}^{q'}(S) + 1) < d_e(q, n_e^{\leq q}(S), n_e^q(S)) \le d_e(q_{k+1}, n_e^{\leq q_{k+1}}(S), 1).$$

Hence, it holds that

$$(d_{e'}(q', n_{e'}^{< q'}(S), n_{e'}^{q'}(S) + 1), q') \prec_{\text{lex}} (d_e(q_{k+1}, n_e^{< q_{k+1}}(S), 1), q_{k+1}).$$

Next, consider the vectors in  $\Phi(S)$  contributed by e'. Without loss of generality, suppose that there exists a positive integer q'' such that  $q'' \in Q_{e'}(S)$  and q'' > q'. Let q'' be the smallest integer satisfying these conditions. The lexicographically smallest vector in  $\Phi(S)$  contributed by e' and changed by the better response of i is

$$(d_{e'}(q'', n_{e'}^{< q''}(S), 1), q'').$$

It then follows from the properties (18) and (21) that

$$d_{e'}(q', n_{e'}^{< q'}(S), n_{e'}^{q'}(S) + 1) \le d_{e'}(q'', n_{e'}^{< q'}(S), n_{e'}^{q'}(S) + 1) \le d_{e'}(q'', n_{e'}^{< q''}(S), 1)$$

and thus

$$(d_{e'}(q', n_{e'}^{< q'}(S), n_{e'}^{q'}(S) + 1), q') \prec_{\text{lex}} (d_{e'}(q'', n_{e'}^{< q''}(S), 1), q''),$$

completing the proof.

### A.3 Proof from Section 6

Proof of Lemma 6.6. Let i be a player in  $N^q$ , and  $S_i \in S_i$  be an arbitrary strategy of i. For each  $S'_i \in S_i$ , it holds that

$$\begin{split} \Phi(S_{-i}^{q}, S_{i}') - \Phi(S^{q}) &= \sum_{e \in S_{i}' \setminus S_{i}} d_{e}(n_{e}^{< q}(S), n_{e}(S^{q}) + 1) - \sum_{e \in S_{i} \setminus S_{i}'} d_{e}(n_{e}^{< q}(S), n_{e}(S^{q})) \\ &= \gamma_{i}(S_{-i}^{q}, S_{i}') - \gamma_{i}(S^{q}), \end{split}$$

and hence the function  $\Phi$  is a potential function of  $G^q$ .