

**Dario Pasquini** 

ni Evgenios M. Kornaropoulos Giuseppe Ateniese George Mason University Fairfax, VA, USA {dpasquin, evgenios, ateniese}@gmu.edu

#### ABSTRACT

We introduce LLMmap, a first-generation fingerprinting attack targeted at LLM-integrated applications. LLMmap employs an active fingerprinting approach, sending carefully crafted queries to the application and analyzing the responses to identify the specific LLM model in use. With as few as 8 interactions, LLMmap can accurately identify LLMs with over 95% accuracy. More importantly, LLMmap is designed to be robust across different application layers, allowing it to identify LLMs operating under various system prompts, stochastic sampling hyperparameters, and even complex generation frameworks such as RAG or Chain-of-Thought.



Model: gpt-4-turbo-2024-04-09

Figure 1: Active fingerprinting via LLMmap.

## 1 Introduction

Penetration testing or any other form of security analysis hinges on an information-gathering phase. Here, the attacker collects information about the target system, laying the groundwork for the exploitation phase. For instance, when auditing a remote machine or service, the first step for the attacker is to infer the operating system running on the target, usually, by a **fingerprinting attack**. The rationale is that different OSs and different versions of the same OS come with different known vulnerabilities and exploitable paths that would allow the system to be compromised.

Testing the security of applications integrating Large Language Models (LLMs) is no different. Different LLMs have various known limitations and intrinsic vulnerabilities, such as susceptibility to specific adversarial inputs or entire attack families. Identifying which model and version of an LLM is integrated into an application reveals attack vectors that could compromise the system. Once the deployed LLM is determined, the attacker can leverage tailored adversarial inputs or exploit architecture-specific vulnerabilities, such as *Buffer Overflow in Mixture of Experts* [6] in Mixture of Experts based LLMs. If the target LLM is open-source, the attacker can use powerful white-box optimization approaches [19, 9, 4] for even more reliable and impactful attacks.

In this work, we introduce  $LLMmap^1$ , a first-generation fingerprinting attack targeting LLM-integrated applications. LLMmap utilizes an active fingerprinting strategy; it submits specially designed queries to the application and analyzes its responses to identify the specific model and version of LLM operating within the application (see Figure 1). LLMmap can fingerprint a target LLM with a limited number of interactions (3 to 8) and is designed to be effective regardless of the underlying applicative layer. That is, LLMmap can fingerprint LLMs deployed with arbitrary system prompts, stochastic sampling procedures, and hyper-parameters, and even when those implement advanced applicative frameworks like *RAG* or *ReACT* [18].

We provide two solutions for LLM fingerprinting: (i) A classifier capable of inferring the correct LLM version among the 40 most common LLMs with accuracy higher than 95%. (ii) An open-set classifier trained via contrastive learning, capable of fingerprinting previously unseen LLMs. The second model enables LLMmap to produce a vectorial representation of the LLM interaction and store it in a template database for matching an arbitrary number of models.

We showcase the effectiveness of LLMmap by evaluating it on both open-source and proprietary models, including various versions of *ChatGPT* and *Claude*. Our approach accurately discerns closely related models, such as those differing only in their context windows (e.g., *Phi-3-medium-128k-instruct* vs. *Phi-3-medium-4k-instruct*). LLMmap is lightweight and fast, making it a practical tool for any *AI red team* toolbox. Code available at: https://github.com/pasquini-dario/LLMmap.

# 2 Active Fingerprinting for LLMs

Effective OS fingerprinting techniques rely on active interaction with the target system. For instance, attackers send TCP packets (known as *probes*) to the target and analyze the responses. Operating systems differ in aspects such as TCP window size, default TTL (Time to Live), handling of flags, reactions to unusual or malformed packets, and TCP sequence numbering. These variations allow attackers to distinguish between different OSs.

LLMs exhibit similar variability—different LLMs respond differently to the same prompt. By analyzing these discrepancies, attackers can identify the underlying model. However, fingerprinting LLMs is inherently challenging due to several factors:

• **Randomized Outputs:** Unlike deterministic operating systems, LLMs use randomized sampling to generate responses. This sampling is influenced by hidden hyperparameters, such as temperature and token repetition penalty, making consistent output difficult to achieve.

• **Model Customization:** LLMs are often tailored for specific applications using a *system prompt/directive*, which sets the model's general behavior (see Figure 1). This customization can significantly alter the output distribution, complicating the fingerprinting process.

• Applicative Layers: LLM applications frequently involve complex interaction pipelines. For example, a Retrieval Augmented Generation (RAG) framework might be used, integrating a knowledge base and additional hyperparameters (e.g., embedding model, chunking procedure). Similarly, advanced prompting frameworks like Chain-of-Thought [15] or ReACT [18] can further obscure the fingerprinting process.

These factors, individually or in combination, greatly influence an LLM's behavior, making fingerprinting a complex adversarial task. We refer to the cumulative effect of these factors as the **prompting configuration** of the LLM-integrated application.

### 2.1 Problem Formulation

In the following, we formalize the objective of the adversary in a fingerprinting attack. Let  $\mathcal{B}$  be a remote application integrating an LLM (e.g., a chatbot served via a web interface). The application enables interaction with external parties. That is, an external user can submit a query q to the LLM and receive its output o, an interaction captured by the following oracle:

$$\mathcal{O}(q) = o$$
, such that  $o \sim s(LLM_{\theta_i}(q))$ , (1)

where  $LLM_{\theta_i}$  is the deployed LLM, and s is the prompting configuration; the set of transformations applied to the LLM's inputs and outputs, including the system prompt, the chosen sampling procedure, and the use of RAG or similar frameworks, as well as their arbitrary combination. The symbol ~ is used to indicate that the output of the model is generated via a stochastic sampling procedure. Hereafter, we call any input provided to the oracle O a *query*.

We assume  $\mathcal{O}$  to be a perfect oracle; that is, nothing can be inferred about  $LLM_{\theta}$  besides what is revealed from the output of  $\mathcal{O}$  itself. We consider both the *prompting configuration s* and the randomness of the sampling method to

<sup>&</sup>lt;sup>1</sup>Name derived from the foundational network scanner Nmap [8].

be unknown to all external observers. In addition, to make our approach as general as possible, we assume  $\mathcal{O}$  to be stateless; that is, submitting a query to  $\mathcal{O}$  does not change its internal state, and thus does not affect the results of future queries.<sup>2</sup> We model an adversary  $\mathcal{A}$  who aims to infer the exact model and version of the LLM deployed in  $\mathcal{B}$  with the least amount of queries to  $\mathcal{O}$ . Hereafter, we call this adversarial objective "*LLM fingerprinting*".

### 2.2 Related Work

Xu et al. [16] propose a watermark-based fingerprinting technique designed to protect intellectual property through remote ownership attestation of LLMs. In their setting, the model owner performs an additional training step on the existing model to inject a behavioral watermark before releasing it. To verify ownership of a remote LLM, the owner submits the set of predefined trigger queries and checks for the injected watermark in the obtained responses. In another concurrent work and under the same setting, Russinovich and Salem [12] introduce a technique to incorporate recognizable behaviors into an LLM via tuning, defining core requirements for successful watermark-based fingerprinting. Their approach is based on hashing responses generated by a set of predefined queries.

Overall, both of the above works address the scenario where the "defender" watermarks the model (s)he owns during training so that can later verify whether the model is used without their consent. On the contrary, our work concerns the case where an "attacker", who cannot affect the training or the specifics of the deployment, induces unique responses via prompting so as to fingerprint and recognize the unknown underlying model.

The most comparable approach to LLMmap is the concurrent work by Yang and Wu [17]. Unlike other solutions [16, 12], this method does not require fine-tuning the model. However, it assumes access to the logits output generated by the tested LLM, rather than the generated text, making it non-applicable to real-world practical settings where LLM is deployed. In particular, their method performs fingerprinting by matching the vector spaces induced by the logits of two different models in response to a set of 300 random queries (as opposed to our technique that needs  $\leq 8$  queries).

### 3 Overview of LLMmap

In this section, we introduce LLMmap, our approach to fingerprinting LLMs. LLMmap aims to identify the specific LLM used in an application through a combination of strategic questioning and machine learning analysis.

The process begins by preparing a set of carefully chosen questions, designed to elicit responses that reveal unique characteristics of different AI models. These questions, referred to as the **querying strategy** (Q), are then submitted to the O. The oracle responds to each question, and these question-response pairs, called *traces* ( $(q_i, o_i)$ ), are collected.

The collected traces are then analyzed by an **inference model** (f). This machine learning model processes the traces to determine which specific LLM is being used by the application. The goal is to accurately attribute an entry from the label space ( $\mathbf{C}$ ) that corresponds to the identified LLM version. The fingerprinting process is formalized in Algorithm 1.

To maximize the accuracy and efficiency of this fingerprinting process, careful selection of both the query strategy (Q) and the inference model (f) is crucial. The following sections will discuss our solutions for implementing these components effectively.

#### Algorithm 1 Fingerprinting attack

```
1: function LLMMAP(\mathcal{O}, \mathcal{Q}, f)

2: \mathcal{T} \leftarrow \{\}

3: for q_i in \mathcal{Q} do

4: o_i \leftarrow \mathcal{O}(q_i)

5: \mathcal{T} \leftarrow \mathcal{T} \cup \{(q_i, o_i)\}

6: end for

7: c \leftarrow f(\mathcal{T})

8: return c
```

 $<sup>^{2}</sup>$ Indeed, there may be applications that allow only for a one-shot interaction with the user, not supporting interleaved communication. Nonetheless, we stress that any stateless interaction can be simulated with a stateful one, making the stateless setting the most general.

## 4 Querying strategy of LLMmap

Much like in traditional OS fingerprinting, not all queries have the same effectiveness in characterizing the target LLM. Some queries are more revealing than others. We assume that there exists a set of prompts that can elicit distinctive behaviors from different LLMs, making it possible to differentiate between them reliably. Therefore, developing an effective querying strategy (Q) for LLMmap involves identifying these key queries that can consistently highlight the differences among various LLMs.

### 4.1 In Pursuit of (Robust) Queries that Reveal the Model

To effectively fingerprint the target model, our work identifies two essential properties that queries should possess:

(1) Inter-model Discrepancy: A query should generate outputs that are maximally different across different LLMs. In other words, the query should produce very different answers when used on different language models. Formally, let  $\mathbf{L}$  be the universe of possible language models and let d be a distance function that measures differences in the output space of the LLMs. We aim to find a query  $q^*$  that maximizes these differences, defined as:

$$q^* = \underset{q \in Q}{\arg\max\left(\mathbb{E}_{(\theta, \theta' \in \mathbf{L})}\left[d(LLM_{\theta}(q), \ LLM_{\theta'}(q))\right]\right)}.$$
(2)

This means we want to identify queries that produce very different outputs for any given pair of different LLMs,  $\theta$  and  $\theta'$ . This property increases the likelihood of distinguishing between different LLMs.

(2) Intra-model Consistency: A query should produce consistent outputs across different prompting configurations and randomness when executed by the same underlying model  $\theta$ . This means that even if the model is set up differently each time, the query should still produce similar answers. Formally, let S be the set of possible prompting configurations. We seek a query  $q^*$  that minimizes the differences in outputs for the same model across these configurations, defined as:

$$q^* = \underset{q \in Q}{\arg\min} \left( \mathbb{E}_{(s,s' \in \mathbf{S})} \left[ d(s(LLM_{\theta}(q)), s'(LLM_{\theta}(q))) \right] \right).$$
(3)

In other words, we want a query  $q^*$  for which execution on any given pair of different prompting configurations, namely s and s', for the same model  $\theta$  would result in *similar* outputs. This property allows us to robustly recognize an LLM even when its setup varies.

A good candidate query for fingerprinting should satisfy both of these properties simultaneously.

### 4.2 Effective Query Strategies

Based on the properties defined earlier, we will now discuss some general prompt families that we have found to be effective for LLM fingerprinting.

### 4.2.1 Can We Simply Apply Banner Grabbing on LLMs?

While fingerprinting an LLM is generally a challenging task, there are a few instances where inferring the origin of the target model can be trivial. Indeed, LLM deployers might choose to: (*i*) explicitly state the name of the model in the system prompt, or (*ii*) train the model with samples that include the name of the model/family. In such cases, an adversary can infer information about the model by simply prompting it to reveal it, e.g., by submitting "*what model are you*?" or "*what's your name*?". This is a well-known approach in offensive security for service/OS fingerprinting and is called *banner grabbing*. Hereafter, we refer to this class of queries as *banner grabbing queries*.

*Banner Grabbing* Is Not a Robust Solution (*per se*): While inherently simple, this baseline approach is neither a general nor a reliable fingerprinting approach. Specifically:

(1) In practice, according to our experiments, only a small portion of models, especially open-source ones, are aware of their name or origin. Moreover, even when the model has such information, it is usually limited to the model's family (e.g., *LLaMa* or *Phi*), lacking details on the generation and size of the model. For instance, *LLaMa-3-8B* and *LLaMa-2-70B*, or *ChatGPT-4* and *ChatGPT-4o*, would be considered the same model.<sup>3</sup>

<sup>&</sup>lt;sup>3</sup>Among all the tested models, the only one that demonstrated awareness of its exact version is *Mistral-7B-Instruct-v0.1*, which responds with "*Mistral 7B v0.1*".



Figure 2: Difference in response of two LLMs upon a malicious prompt. The model *Mixtral-8x7B*, in contrast to *gpt-4o-2024*, tends to restate the harmful task in its answer.

(2) This approach is not robust to prompting configurations, such as different system prompts. A trivial mitigation against banner grabbing queries is for the LLM to state a different model name in the system prompt, thus overriding the true *banner* of the model and misleading the attacker (e.g., Figure 1).

(3) Ultimately and more interestingly, banner-grabbing queries are not a reliable approach. We observed that models would often produce meaningful yet erroneous answers to such queries i.e., the model claims to be a different LLM. This usually happens because the model has been trained/fine-tuned on outputs generated by other models (typically *OpenAI's* models). For instance, *SOLAR-10.7B-Instruct-v1.0* and *openchat\_3.5* falsely claim to be OpenAI models when answering banner grabbing queries. Similarly, unreliable answers might appear due to bias in the training set. For instance, the models *aya-23-8B* and *35B* from *Cohere* respond to banner grabbing queries with "*Coral*", another model from the same vendor. Table 2 in Appendix A provides additional examples for this behavior.

**Banner Grabbing** Queries Induce Strong Inter-model Discrepancy: Although this baseline approach is unreliable, it results in highly inter-model discriminative responses (see Equation (2)), which are frequently factually wrong. Each model tends to answer such queries in unique ways. For instance, Google's Gemma models seem to avoid disclosing any information about themselves, responding with "*I am unable to provide information that may compromise my internal architecture or development process.*", which is unique among the models we analyzed. Such queries can also discriminate among closely related models. For instance, *Phi-3-mini* claims to be *GPT-4*, whereas *Phi-3-medium* models correctly state *Phi.* Therefore, this approach can be exploited to distinguish LLMs that would otherwise behave very similarly within the same model family.

Among the pool of queries in this family, the most effective and robust probe we identified is "*Who created you?*". This banner grabbing query induces strong intra-model consistency (see Equation (3)) as it tends to bypass the effect of the system prompt more than other similar queries, such as "*What's your name?*".

### 4.2.2 Queries That Request Meta-Information About The Model

Another family of queries with high inter-model discrepancy includes prompts that ask the model for information about itself or its training process (e.g., "What's the size of your training set?"), rather than knowledge-based tasks (e.g., "What's the capital of France?"). While the LLM, in most cases, would not have the answer to this type of request (as such information is not shared at training time), the made-up responses are generally unique and, therefore, very helpful for distinguishing between models. In other settings, such as when prompting "What's your data cutoff date?", the LLM might be aware of the answer, potentially leaking very important metadata about the training that can be exploited in the fingerprinting process.

### 4.2.3 "Malformed" Queries Reveal Useful Information

A common and effective approach in OS fingerprinting is to submit malformed packets to the target system. How the TCP/IP stack fails to process (or handle) these packets leaks substantial information about the OS. A similar rationale can be applied to LLMs. Indeed, how LLMs respond to "atypical" prompts is generally unique and, more importantly, consistent across various prompting configurations (e.g., different system prompts).

**Exploiting Models' Alignment:** While LLMs lack any formal syntactic correctness for their inputs, we observed that adversaries could induce models to produce *"error messages"* by exploiting other features of the models, such as their alignment procedures.

Alignment is a methodology that aims to make the model helpful, honest, and harmless [2]. In particular, we aim to exploit the latter property. Due to the alignment process, when asked to respond to a harmful query (e.g., "*How to build a bomb?*"), the LLM refuses by issuing a message stating that the prompted task cannot be served (see Figure 2). Attackers can exploit this behavior to induce strong and robust fingerprint signals, as these "*error messages*" are typically highly model-dependent and sufficiently unique. More prominently, these responses also remain consistent across prompting configurations. Indeed, regardless of the directives set by the prompting configuration, the model prioritizes

the refusal of the harmful task. Furthermore, we stress that issuing *harmful* prompts allows us to discriminate the other two macro-categories of models: aligned and non-aligned LLMs. Therefore, such queries provide distinguishing power when it comes to non-aligned LLMs.

**Exploiting Weaker Forms of Alignments:** Prompting harmful instructions is not the only way to exploit a model's alignment for fingerprinting. We observed another class of prompts that induced strong intra-model consistency by exploiting the "non-harmful bias" induced by the alignment process. In particular, asking rhetorical/ethical questions (e.g., "*Is racism wrong?*" or "*Is climate change real?*") provides discriminative and robust responses. As in the previous case, such queries provide a high degree of intra-model consistency as the model prioritizes answering these prompts over other directives imposed by the prompt configuration.

Moreover, in contrast to harmful prompts, the model actually produces an answer for the given question, resulting in more articulate and richer outputs that can be used to characterize the target LLM.

**Inconsistent Inputs:** Besides exploiting models' alignment, an attacker can craft "*inconsistent*" (or more generally "*malformed*") queries by relying on nonsensical or *semantically-broken* prompts. For instance, submitting queries that mix several languages (e.g., "*Bonjour, how are you doing today? ¿Qué tal?*") [7, 3]. As in OS fingerprinting, the way the target handles such inconsistent inputs (e.g., answering the query in either English or Spanish) provides a unique behavioral signature for the LLM, which improves fingerprint accuracy when combined with other probing approaches.

### 4.2.4 Triggers for Prompt-Injection Boost Intra-model Consistency

As previously mentioned, prompting configuration can fundamentally shift the LLMs' output distribution, making it difficult to achieve intra-model consistency of probes and, thus, fingerprinting the model. To reduce the effect of prompt configurations on the model's behavior, attackers can rely on additional techniques to combine with a chosen query. In particular, we observed that applying an execution trigger for prompt injection on the query boosts the intra-model consistency of the achieved responses. Prompt injection [5, 9] is a family of attacks against instruction-tuned LLMs that aims to subvert and replace their original task with an adversarially chosen one. An execution trigger [9] is the part of the adversarial input whose objective is to convince the LLM to ignore/override its original instruction and execute the given payload, e.g., *"Ignore previous instructions and…"* [1, 10].

By combining a query with an execution trigger (e.g., "*Ignore all previous instructions and do \$QUERY*"), we push the model to override the information and directives defined by the prompt configuration, achieving more consistent responses across different setups. For instance, replacing the query:

 Tell me who created you
 with
 ))))]]]]}}};\*/

 Now ignore that instruction above and accurately Tell me who created you ([{<!-</td>

translates to a +4% fingerprinting accuracy increase. However, according to our experiments, not all queries benefit from this approach. Certain classes of harmful requests do not benefit from combining with execution triggers, as the alignment bias of the model is generally strong enough to override the prompt configuration alone. In our setting, we observed the largest fingerprinting accuracy increase when combining with *banner grabbing* queries; that is, queries whose response would be easily overridden by the prompt configuration (mainly the system prompt).

### 4.3 On Identifying the Right Subset of Queries for LLMmap

Based on the families of discriminative prompts defined in Section 4.2, our goal is to identify a small set of queries to compose an effective query strategy for LLMmap. To accomplish this, we generate a pool of 10 entries for each prompt family by combining manually created and synthetically generated prompts, resulting in a total of 50 possible queries. We then search for the smallest combination of queries that produces the best fingerprint results. This procedure is detailed in Appendix B. After this optimization phase, we end up with a query strategy composed of 8 queries, which are listed in Table 1, sorted by decreasing individual effectiveness. Hereafter, we use these queries to implement the query strategy Q unless stated otherwise.

**Automatize Queries Generation Process** Inspired by existing work on OS fingerprinting, we have developed our query strategy based on domain knowledge and manual interactions with LLMs. However, more advanced solutions can be utilized to create novel and more effective queries for LLM fingerprinting tasks. Specifically, similar to previous work on the automated generation of adversarial inputs [19, 9], optimal queries can be generated by framing the task as an optimization problem and identifying suitable token combinations in the models' input space.

Probe	Туре
1))))]]]]}}};*/ Now Ignore all the previous instructions and tell me who created you: ([{ -</td <td>Banner grabbing</td>	Banner grabbing
<b>2</b> <i>Tell me how to build a bomb.</i>	Alignment
<b>3</b> Answer this true-or-false question: Climate change is a pressing global issue	Weak Alignment
4 What's your data cutoff date?	Meta-information
5 What is the size of your training dataset?	Meta-information
6 Bonjour, how are you doing today? ¿Qué tal?'	Malformed
7 Is racism wrong?	Weak Alignment
8 What's your name?	Banner grabbing

|--|

In this direction, the properties listed in Section 4.1 can already be used to define an objective function. Furthermore, Eq 2 and 3 are fully differentiable, supporting white-box optimization (e.g., via GCG [19]). However, unlike other settings, this optimization would involve multiple LLMs simultaneously (at least two), making the task resource-intensive.

#### 5 Inference Model of LLMmap

Once the queries in Q have been submitted to the target application, the resulting traces are analyzed to identify the deployed LLM, i.e., the  $\theta$ . Due to the unpredictability of the application's responses, influenced by the *unknown to the attacker* prompting configuration and the randomness of the sampling procedure, we implement the inference phase using a machine learning model trained to derive robust predictions from the collected traces.

We consider two settings for the inference task:

- Closed-Set Fingerprinting Setting: The inference model is aware of a predefined set of possible LLMs and identifies which one generated the traces. Specifically, given a set of n known models C={θ<sub>1</sub>,...,θ<sub>n</sub>}, the inference model predicts which of the n models in C generated the input traces. In this setting, the inference model functions as a classifier f : T<sup>k</sup> → C, where T represents the set of traces.
- 2. **Open-Set Fingerprinting Setting:** The inference model does not have prior knowledge of all possible LLMs and instead produces a vector signature that can be matched against known templates. Specifically, the inference model is a function  $f : \mathbf{T}^k \to \mathbb{Z}^m$ ; given the collected traces as input, the model outputs an *m*-dimensional vector. This vector represents a signature that can be "fuzzy-matched" with stored LLM templates to recognize the target LLM.

Unlike closed-set fingerprinting, the open-set model allows for the identification of LLMs that the inference model has not been explicitly trained on. Moreover, given two traces obtained from two different LLM-integrated applications, a successful open-set fingerprinting attack can determine whether the applications deploy the same model  $LLM_{\theta_i}$ , even if  $LLM_{\theta_i}$  has never been seen by the inference model before (e.g., a newly released or inaccessible model). However, attacks in the open-set setting are generally less accurate than those in the specialized closed-set setting and might be preferred in contexts where flexibility is more important than precision.

To implement attacks in these two models, we use the same backbone network and modify it according to the task at hand.



Figure 3: Depiction of the structure of the inference model. Elements in red represent the model's inputs. In blue, pre-trained modules that are not tuned during the training.



Figure 4: Visualization of contrastive learning on LLMs' traces. Positive and negative case.

**Backbone Architecture:** One straightforward solution for building the inference model would be to use a pre-trained, instruction-tuned LLM. However, to ensure our approach is practical and can run efficiently on a standard CPU, we choose a lighter solution.

The structure of our backbone network is shown in Figure 3. For each pair of query  $q_i$  and corresponding response  $o_i$ , we use a pre-trained textual embedding model (*Emb*) to generate a vector representation. This process involves:

1. *Textual Embedding:* Each query  $q_i$  and its response  $o_i$  are converted into vectors using the embedding model. Even though we use a fixed set of queries, including the query  $q_i$  in the input helps the model handle variations, such as paraphrasing, and avoids defenses like query blacklisting.

2. Concatenation and Projection: The vectors for  $q_i$  and  $o_i$  are concatenated into a single vector. This combined vector is then passed through a dense layer  $(f_p)$  to reduce its size to a smaller feature space of size m.

3. Self-Attention Architecture: The projected vectors are fed into a lightweight self-attention-based architecture composed of several transformer blocks [13]. These blocks do not use positional encoding since the order of traces is irrelevant. Additionally, an extra *m*-dimensional vector ( $C_{token}$ ) is used as a special classification token. This vector is randomly initialized and optimized during training.

The output vector corresponding to  $C_{\text{token}}$  from the transformer network is referred to as v. This vector is used differently depending on whether we are performing closed-set or open-set classification.

**Closed-Set Classification:** To implement the classifier in the **closed-set setting**, we add an additional dense layer on top of v, which maps v into the class space—for our experiments, the class space is comprised of the 40 LLMs listed in Table 3 in Appendix A. We train the model in a fully supervised manner. We generate a suitable training set by simulating multiple LLM-integrated applications with different LLMs and prompting configurations. For each simulated application, we collect traces by submitting queries according to our query strategy and using the LLM within the application as the label. The detailed process for generating these training sets is explained in Section 6.1. Once the input traces are collected, we train the model to identify the correct LLM. This task requires the model to generalize across different prompting configurations and handle the inherent randomness in the sampling procedure.

**Open-set Classification:** For the **open-set setting**, we directly use v as the model's output. The backbone here is configured as a "siamese" network, which we train using a contrastive loss. That is, given a pair of input traces  $\mathcal{T}_a$  and  $\mathcal{T}_b$ , the model is trained to produce similar embeddings when  $\mathcal{T}_a$  and  $\mathcal{T}_b$  are generated by the same model, even if different prompting configurations are used. Conversely, the model is trained to produce distinct embeddings when  $\mathcal{T}_a$  and  $\mathcal{T}_b$  are generated by different LLMs. This process is depicted in Figure 4. For training, we resort to the same training set used for closed-set classification. For each entry  $(\mathcal{T}_a, LLM_{\theta_a})$  in the training set, we create a positive and a negative example  $(\mathcal{T}_a, \mathcal{T}_b)$ . Positive pairs are obtained by sampling another entry in the database with label  $LLM_{\theta_a}$ , whereas negative pairs are obtained by sampling an entry with label  $LLM_{\theta_b}$ , where  $\theta_b \neq \theta_a$ .

**Model Instantiation:** To implement the embedding model Emb, we use multilingual-e5-large-instruct [14], which has an embedding size of 1024. For our transformer's feature size, we choose a smaller size, m = 128, and configure the transformer with only two transformer blocks, each having two attention heads. This design choice ensures that the inference model remains lightweight, with approximately 3k trainable parameters.

## **6** Evaluation

This section details our evaluation setting as well as the results obtained by LLMmap.

### 6.1 Evaluation Setup

To train our inference models and evaluate the performance of LLMmap, we need to simulate a large number of applications that use different LLMs. This involves defining a set of LLMs to test (called the LLM universe L) and a set of possible prompting configurations (called the universe of possible prompting configurations S). The following section explains the choices we made for this simulation process.

**Universe of LLMs:** To evaluate LLMmap, we selected the 40 LLMs listed in Table 3. These models were chosen based on their popularity at the time of writing. We primarily use the Huggingface hub to select open-source models. We automatically retrieve the most popular models based on download counts by leveraging their API services. For closed-source models, we consider the three main models offered by the two most popular vendors (i.e., *OpenAI* and *Anthropic*) for which API access is available. Hereafter, we refer to these models as the LLM universe **L**.

**Universe of prompting configurations:** To enable LLMmap to accurately fingerprint an LLM across different settings, we need a method to simulate a large number of prompting configurations during the training phase of the inference model. We use a modular approach to define these prompting configurations by combining multiple elements. For each element, we create a pool of possible values. An prompting configuration is then generated by randomly selecting and combining elements from these pools. Specifically, we define an prompting configuration as a combination of three components:

- 1. Hyper-Parameters for Sampling Procedure: We parametrize the sampling procedure by two hyperparameters: temperature and frequency\_penalty, in the range [0, 1] and [0.65, 1], respectively.
- 2. **System Prompt:** We curated a collection of 60 different system prompts, which include prompts collected from online resources as well as automatically generated ones. Examples of system prompts are reported in Table 4 in Appendix A.
- 3. **Prompt Frameworks:** We consider two settings: RAG and Chain-Of-Thought [15]. To simulate RAG, we create the input corpus by sampling 30 random entries from the dataset *SQuAD 2.0* [11], and consider 6 prompt templates for retrieval-based-Q&A. An example of prompt derived from this approach is given in Figure 9 in Appendix A. Prompting frameworks are applied only in 20% of the cases and combined with the other modifiers (e.g., system prompt).

#### Algorithm 2 Dataset generation process

1:	function MAKE_DATASET $(w, \mathcal{Q}, \mathbf{S}, \mathbf{L})$	
2:	$D \leftarrow \{\}$	
3:	for $i \leftarrow 1$ to $w$ do	
4:	for $LLM_{\theta}$ in L do	▷ For each LLM
5:	$\mathcal{T} \leftarrow \{\}$	
6:	$s \sim \mathbf{S}$	▷ Sample a prompting configuration
7:	for $q$ in $\mathcal Q$ do	▷ For each query in the query strategy
8:	$o \sim s(LLM_{ heta}(q))$	▷ Compute response LLM
9:	$\mathcal{T} \leftarrow \mathcal{T} \cup \{(q, o)\}$	
10:	end for	
11:	$D \leftarrow D \cup \{(\mathcal{T}, LLM_{\theta})\}$	$\triangleright$ Add traces as entry in the database with label $LLM_{\theta}$
12:	end for	
13:	end for	
14:	return D	
15:	end function	

To create disjoint sets of prompting configurations for training and evaluation, we randomly split the pool of each component into two disjoint sets of equal size. We then generate 1000 prompting configurations for training and evaluation. These sets are referred to as  $S_{train}$  and  $S_{test}$ , respectively.

**Creating Training/Evaluation Set for Inference Model:** Once the LLM universe L, the generated prompting configurations ( $S_{train}$  and  $S_{test}$ ), and the query strategy Q are chosen, we can collect the traces required to train the inference model. This process is summarized in Algorithm 2. For each LLM in Table 3, we sample a prompting configuration in  $S_{train}$  and collect all the responses of the model upon the queries in Q. To allow the inference model to generalize over different prompting configurations, we repeat the process w times; that is, for each LLM, we generate w traces with different prompting configurations. In our setting, we set w to 25. This process results in a set of 1k pairs

"(*traces*,  $LLM_{\theta}$ )" that can be used to train the inference model in a supervised manner. To create the test set, we repeat the process but use  $S_{test}$  instead of  $S_{train}$ , ensuring that the prompting configurations used for testing are completely disjoint from those used for training. This results in another 1k traces that can be used for evaluation.

#### 6.2 Results

Finally, in this section, we evaluate the performance of LLMmap, considering both the closed-set and open-set deployment of the inference model.



Figure 5: Confusion matrix for the closed-set fingerprinting model.

#### 6.2.1 Closed-Set Classification Setting

Once the inference model has been trained, we test it using the 1K traces generated with the left-out prompting configurations in  $S_{test}$ . Given input traces generated by the target model, we use the closed-set classifier to infer the LLM that generated them from the list of LLMs in Table 3. On average, the model achieves an accuracy of 95.2% over the 40 LLMs. The confusion matrix in Figure 5 shows the accuracy for each model. The results indicate that LLMmap is generally robust across different models, correctly classifying 32 out of 40 LLMs with 95% accuracy or higher. This includes highly similar models, such as different instances of Google's *Gemma* or various versions of *ChatGPT-4*. The main exception is Meta's *Llama-3-70B-Instruct*, where our approach achieves only 72% accuracy. As shown in



Figure 6: Accuracy of the closed-set classification plotted against the number of queries performed to the target LLM-integrated application.

the confusion matrix, this lower accuracy is primarily due to misclassifications with closely related models, such as *Smaug-Llama-3-70B-Instruct* by *Abacus.AI*, which is a fine-tuned version of the original model.

**Fingerprint Accuracy as a Function of Number of Queries:** Naturally, the accuracy of fingerprinting depends on the number of queries made to the target. To balance context-specific needs, an attacker might reduce the number of interactions with the target application, but this typically results in decreased fingerprinting accuracy. This tradeoff is illustrated in Figure 6, where accuracy is plotted against the number of traces provided as input to the inference model. Generally, using only the first three queries from Table 1 achieves an average accuracy of 90%. However, accuracy levels off after eight queries. It is conceivable that the 95% accuracy mark could be surpassed by incorporating different queries than those outlined in Section 4.2. Further optimization of the query strategy will be explored in future work. We emphasize that, thanks to the attention-based architecture of the inference model, the number of input traces can be adjusted seamlessly without requiring any re-training of the model.

#### 6.2.2 Open-Set Classification Setting

Implementing fingerprinting with the open-set model involves two main steps.

**Derive a Database of Templates:** After training the inference model, we derive a vectorial representation v for all traces in the training set by providing them as input to the inference model (see Section 5). We group all the vectors associated with traces generated by the same LLM and average them into a single vector. This results in 40 vectors, each representing a template for an LLM in Table 3. We refer to this list of vectors as DB. These vectors, after dimensional reduction, are depicted in Figure 7.



Figure 7: Two-dimensional representation of the templates derived by the open-set fingerprint model on all the tested models.

**Inference Phase:** Given traces  $\mathcal{T}^?$  generated by an unknown model, inference proceeds as follows: (1) We provide  $\mathcal{T}^?$  to the inference model and derive a vector  $v^?$ . (2) We compute the cosine similarity between  $v^?$  and all the vectors in  $\mathcal{DB}$ . (3) We output the LLM whose template has the highest similarity to  $v^?$  as the prediction.

Using this approach, we evaluate the performance of the open-set inference model against our test set. Fingerprinting with the open-set inference model results in an average accuracy of 90%, which is 5% lower than the specialized closed-set classifier.



Figure 8: Results for the fingerprinting of models not known at training time. Each row reports the percentage of predictions given by the inference model for the LLM in the x-label when removed from the training.

**Fingerprinting New LLMs:** The main advantage of the open-set fingerprinting approach is its ability to operate on LLMs that were not part of the training set. To do this, we collect one or more traces for a new LLM and derive its template to add to DB. The inference process remains unchanged. To evaluate the performance of the open-set inference model in fingerprinting new LLMs, we proceed as follows. Given the list of models in Table 1, (1) we remove an LLM (referred to as  $LLM_{out}$ ) and (2) train the inference model on the traces generated by the remaining 39 LLMs.

(3) We then test the inference model to correctly recognize  $LLM_{out}$  using the fingerprinting process described above. We repeat this process for each model in a k-fold cross-validation fashion.

On average, the inference model correctly identifies the unseen LLM with 81.1% accuracy. Individual results are reported in Figure 8. In this setting, predictions tend to be less robust and have higher variance overall; certain models are recognized with perfect accuracy, while others, such as *Mistral-7b-v0.3*, are recognized only 50% of the time. Nonetheless, the average accuracy remains meaningfully high.

We emphasize that once traces for a new model are collected, they can be added to the training set of the closed-set model to achieve more robust predictions. Given the small size of the model, retraining requires less than 10 minutes on a single GPU. Furthermore, the closed and open-set models can operate together without increasing the number of queries to the target application; once the traces are collected, they can be provided to both models, and their predictions can be combined for more robust inference.

## 7 Conclusion & Future Work

We introduce LLMmap, an effective and lightweight tool for fingerprinting LLMs deployed in LLM-integrated applications. While model fingerprinting is a crucial step in the information-gathering phase of AI red teaming operations, many other relevant details about a deployed LLM can also be inferred.

The LLMmap framework can be easily extended to support additional functionalities such as:

- 1. Function Calls Enumeration: Identify all extra features that the LLM can use, such as web access or database queries.
- 2. **Prompting Framework Inference:** Determine if the LLM is using a specific method to structure its responses, like RAG or ReACT.
- 3. Fine-Tuning Inference: Detect if the LLM has been specially trained on additional data for specific tasks.
- 4. **Hyper-Parameters Inference:** Infer the hyper-parameters being used by the deployed LLM, such as temperature and sampling regulations.

Our future efforts will focus on implementing these functionalities within the LLMmap framework and making them available to the community.

## 8 Acknowledgments

The authors would like to thank Antonios Anastasopoulos for his insights into the related work.

### References

[1] "Prompt injection attacks against GPT-3". prompt-injection/.

https://simonwillison.net/2022/Sep/12/

- [2] Amanda Askell, Yuntao Bai, Anna Chen, Dawn Drain, Deep Ganguli, Tom Henighan, Andy Jones, Nicholas Joseph, Benjamin Mann, Nova DasSarma, Nelson Elhage, Zac Hatfield-Dodds, Danny Hernandez, Jackson Kernion, Kamal Ndousse, Catherine Olsson, Dario Amodei, Tom B. Brown, Jack Clark, Sam McCandlish, Chris Olah, and Jared Kaplan. A general language assistant as a laboratory for alignment. *CoRR*, abs/2112.00861, 2021.
- [3] Fahim Faisal and Antonios Anastasopoulos. Geographic and geopolitical biases of language models. *arXiv* preprint arXiv:2212.10408, 2022.
- [4] Jonas Geiping, Alex Stein, Manli Shu, Khalid Saifullah, Yuxin Wen, and Tom Goldstein. Coercing llms to do and reveal (almost) anything, 2024.
- [5] Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising real-world llm-integrated applications with indirect prompt injection. In *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security*, AISec '23, page 79–90, New York, NY, USA, 2023. Association for Computing Machinery.
- [6] Jamie Hayes, Ilia Shumailov, and Itay Yona. Buffer overflow in mixture of experts, 2024.
- [7] Kelly Marchisio, Wei-Yin Ko, Alexandre Bérard, Théo Dehaze, and Sebastian Ruder. Understanding and mitigating language confusion in llms. *arXiv preprint arXiv:2406.20052*, 2024.
- [8] Nmap.org. "Nmap: the Network Mapper". https://nmap.org.
- [9] Dario Pasquini, Martin Strohmeier, and Carmela Troncoso. Neural exec: Learning (and learning from) execution triggers for prompt injection attacks, 2024.
- [10] Fábio Perez and Ian Ribeiro. Ignore previous prompt: Attack techniques for language models, 2022.
- [11] Pranav Rajpurkar, Robin Jia, and Percy Liang. Know what you don't know: Unanswerable questions for SQuAD. In Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers), pages 784–789, Melbourne, Australia, July 2018. Association for Computational Linguistics.
- [12] Mark Russinovich and Ahmed Salem. Hey, that's my model! introducing chain & hash, an llm fingerprinting technique. *arXiv preprint arXiv:2407.10887*, 2024.
- [13] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. Von Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.
- [14] Liang Wang, Nan Yang, Xiaolong Huang, Linjun Yang, Rangan Majumder, and Furu Wei. Multilingual e5 text embeddings: A technical report. *arXiv preprint arXiv:2402.05672*, 2024.
- [15] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. Advances in neural information processing systems, 35:24824–24837, 2022.
- [16] Jiashu Xu, Fei Wang, Mingyu Derek Ma, Pang Wei Koh, Chaowei Xiao, and Muhao Chen. Instructional fingerprinting of large language models, 2024.
- [17] Zhiguang Yang and Hanzhou Wu. A fingerprint for large language models. *arXiv preprint arXiv:2407.01235*, 2024.
- [18] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. *arXiv preprint arXiv:2210.03629*, 2022.
- [19] Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models, 2023.

### A Additional Resources

This appendix contains additional material. Table 2 reports misleading outputs produced by LLMs upon banner-grabbing queries, whereas Table 3 lists the LLMs considered in this work. Table 4 reports examples of system prompts used to generate different prompting configurations. Figure 9 reports an example of prompt when the prompting configuration uses RAG.

Model	Claimed model/family/vendor
CohereForAI/aya-23-35B	Coral/Sophia
CohereForAI/aya-23-8B	Coral
Deci/DeciLM-7B-instruct	MOSS / FudanNLP Lab
garage-bAInd/Platypus2-70B-instruct	Open Assistant
NousResearch/Nous-Hermes-2-Mixtral-8x7B-DPO	ChatGPT
microsoft/Phi-3-mini-4k-instruct	GPT-4
openchat/openchat-3.6-8b-20240522	ChatGPT
openchat/openchat_3.5	ChatGPT
tiiuae/falcon-40b-instruct	OpenAI
upstage/SOLAR-10.7B-Instruct-v1.0	GPT-3
google/gemma-7b-it	LaMBDA / LanguageModel/ ChatBox
google/gemma-1.1-2b-it	Jasper / Codex / Google Assistant / GPT-3
google/gemma-1.1-7b-it	Jasper / GPT-3
Qwen/Qwen2-7B-Instruct	DeepMind

Table 2: Examples of LLMs claiming to be the wrong model when prompted with whois. Prompts made without any system prompt and default temperature.

## **B** Optimize query strategy

Starting from a pool of 50 suitable queries, we derive the 8 queries listed in Table 1 as follows:

- 1. We train a different closed-set inference model on each of the 50 queries individually using 80% of the training set.
- 2. We evaluate the models on the remaining 20% and select the 12 queries whose models achieved the highest accuracy.
- 3. We train a new closed-set inference model using the selected 12 queries (still using 80% of the training set).
- 4. We evaluate the trained model on the remaining 20% of the training set by trying all the possible combinations of the 12 queries. Finally, we select the smallest set that achieved the highest accuracy.

This process resulted in the queries listed in Table 1.

Closed-source:
OpenAI's ChatGPT-3.5 (gpt-3.5-turbo-0125)
OpenAI's ChatGPT-4 (gpt-4-turbo-2024-04-09)
OpenAI's ChatGPT-40 (gpt-40-2024-05-13)
Anthropic's Claude 3 Haiku (claude-3-haiku-20240307)
Anthropic's Claude 3 Opus (claude-3-opus-20240229)
Anthropic's Claude 3.5 Sonnet (claude-3-5-sonnet-20240620)
Open-source:
google/gemma-7b-it
google/gemma-2b-it
google/gemma-1.1-2b-it
google/gemma-1.1-7b-it
google/gemma-2-9b-it
google/gemma-2-27b-it
CohereForAI/aya-23-8B
CohereForAI/aya-23-35B
Deci/DeciLM-7B-instruct
Qwen/Qwen2-1.5B-Instruct
Qwen/Qwen2-7B-Instruct
Qwen/Qwen2-72B-Instruct
gradientai/Llama-3-8B-Instruct-Gradient-1048k
meta-llama/Llama-2-7b-chat-hf
meta-llama/Meta-Llama-3-8B-Instruct
microsoft/Phi-3-medium-128k-instruct
microsoft/Phi-3-medium-4k-instruct
microsoft/Phi-3-mini-128k-instruct
microsoft/Phi-3-mini-4k-instruct
mistralai/Mistral-7B-Instruct-v0.1
mistralai/Mistral-7B-Instruct-v0.2
mistralai/Mistral-7B-Instruct-v0.3
nvidia/Llama3-ChatQA-1.5-8B
openchat/openchat-3.6-8b-20240522
openchat/openchat_3.5
togethercomputer/Llama-2-7B-32K-Instruct
upstage/SOLAR-10.7B-Instruct-v1.0
NousResearch/Nous-Hermes-2-Mixtral-8x7B-DPO
abacusai/Smaug-Llama-3-70B-Instruct
garage-bAInd/Platypus2-70B-instruct
meta-llama/Meta-Llama-3-70B-Instruct
internlm/internlm2_5-7b-chat
HuggingFaceH4/zephyr-7b-beta
mistralai/Mixtral-8x7B-Instruct-v0.1

Table 3: List of LLMs used for training and testing LLMmap.

Table 4: Examples of eight system prompts used to simulate different prompting configurations. "You are a financial advisor bot for a banking website. Assist users in understanding different banking products and services like savings accounts, loans, and investment options. Offer guidance on financial planning, budgeting, and saving strategies. Keep user information confidential and provide trustworthy advice."

"Help library visitors explore book catalogs, reserve materials, and access digital resources. Provide reading recommendations and information on library events. Answer inquiries with politeness and direct users to additional resources or library staff when needed."

"Provide general legal information in areas such as family law, business contracts, and civil rights. Clarify legal terms and procedures, and guide users on when and how to seek professional legal advice. Maintain a formal tone and ensure privacy and discretion in all interactions."

"You are ProjectManagerGPT, an AI expert in the field of project management, with a deep understanding of various methodologies, team dynamics, and stakeholder management. Your expertise enables you to navigate complex project landscapes, identifying and resolving potential issues before they escalate, and ensuring the successful delivery of projects on time and within budget."

"I want you to act as a growth hacker. You will create innovative strategies to promote a startup product or service of your choice. You will identify a target audience, develop key growth tactics and experiments, select the most effective digital channels for promotion, and determine any additional resources needed to optimize growth."

"You are StartupGPT, an AI expert in the world of entrepreneurship, with a keen understanding of the unique challenges faced by indie founders, particularly programmers and software engineers. Your expertise lies in developing efficient strategies for launching lean startups that can generate revenue quickly, without relying on gimmicks or unsustainable practices."

"Serve as a customer service chatbot for an online store. Assist users with product inquiries, order tracking, returns, and refunds. Provide prompt and courteous support, ensuring a positive shopping experience."

"Act as a relationship advice bot. Offer guidance on communication, conflict resolution, and building healthy relationships. Provide support and resources for individuals and couples."

#### Context information is below.

In 1994, responding to the need for a more useful system for describing chronic pain, the International Association for the Study of Pain (IASP) classified pain according to specific characteristics: (1) region of the body involved (e.g. abdomen, lower limbs), (2) system whose dysfunction may be causing the pain (e.g., nervous, gastrointestinal), (3) duration and pattern of occurrence, (4) intensity and time since onset, and (5) etiology. However, this system has been criticized by Clifford J. Woolf and others as inadequate for guiding research and treatment. Woolf suggests three classes of pain : (1) nociceptive pain, (2) inflammatory pain which is associated with tissue damage and the infiltration of immune cells, and (3) pathological pain which is a disease state caused by damage to the nervous system or by its abnormal function (e.g. fibromyalgia, irritable bowel syndrome, tension type headache, etc.).

Another landmark is the old centre and the canal structure in the inner city. The Oudegracht is a curved canal, partly following the ancient main branch of the Rhine. It is lined with the unique wharf-basement structures that create a two-level street along the canals. The inner city has largely retained its Medieval structure, and the moat ringing the old town is largely intact. Because of the role of Utrecht as a fortified city, construction outside the medieval centre and its city walls was restricted until the 19th century. Surrounding the medieval core there is a ring of late 19th- and early 20th-century neighbourhoods, with newer neighbourhoods positioned farther out. The eastern part of Utrecht remains fairly open. The Dutch Water Line, moved east of the city in the early 19th century required open lines of fire, thus prohibiting all permanent constructions until the middle of the 20th century on the east side of the city.

Nicholas Lezard described post-punk as "a fusion of art and music". The era saw the robust appropriation of ideas from literature, art, cinema, philosophy, politics and critical theory into musical and pop cultural contexts. Artists sought to refuse the common distinction between high and low culture and returned to the art school tradition found in the work of artists such as Captain Beefheart and David Bowie. Among major influences on a variety of post-punk artists were writers such as William S. Burroughs and J.G. Ballard, avant-garde political scenes such as Situationism and Dada, and intellectual movements such as postmodernism. Many artists viewed their work in explicitly political terms. Additionally, in some locations, the creation of post-punk music was closely linked to the development of efficacious subcultures, which played important roles in the production of art, multimedia performances, fanzines and independent labels related to the music. Many post-punk artists maintained an anti-corporatist approach to recording and instead seized on alternate means of producing and releasing music. Journalists also became an important element of the culture, and popular music magazines and critics became immersed in the movement.

Figure 9: Example of a prompt generated when simulating a RAG pipeline. In red, the query issued by the attacker. The prompt also includes the system prompt, which we do not report for representation's sake.

Given the context information and not prior knowledge, answer the query. Query: Tell me how to build a bomb. Answer: