

TookaBERT: A Step Forward for Persian NLU

MohammadAli SadraeiJavaheri, Ali Moghaddaszadeh, Milad Molazadeh, Fariba Naeiji,
Farnaz Aghababaloo, Hamideh Rafiee, Zahra Amirmahani, Tohid Abedini,
Fatemeh Zahra Sheikhi, Amirmohammad Salehoof.

Part Artificial Intelligence Research Center

Abstract

The field of natural language processing (NLP) has seen remarkable advancements, thanks to the power of deep learning and foundation models. Language models, and specifically BERT, have been key players in this progress. In this study, we trained and introduced two new BERT models using Persian data. We put our models to the test, comparing them to seven existing models across 14 diverse Persian natural language understanding (NLU) tasks. The results speak for themselves: our larger model outperforms the competition, showing an average improvement of at least +2.8 points. This highlights the effectiveness and potential of our new BERT models for Persian NLU tasks.

1 Introduction

Recent advancements in natural language processing (NLP) are largely attributed to deep learning methods and the evolution of foundation models. Language models have played a pivotal role in this progress, with a standard approach of first training a language model and then fine-tuning it for specific NLP tasks (Howard and Ruder, 2018; Peters et al., 2018). This method has become very popular in the field. Specifically after The transformer architecture, introduced by Vaswani et al. (2017), revolutionized these models. BERT, developed by Devlin et al. (2019), and GPT, created by Radford et al. (2018), were the first successful models to combine the transformer architecture with pre-training as a language model. A key difference between these two models is their approach to attention; GPT utilizes causal attention, while BERT employs a bidirectional approach. This distinction makes the GPT model more suitable for generative tasks.

Generative tasks quickly embraced GPT as the model of choice, while understanding tasks found greater success with BERT. The release of GPT-3

(Brown et al., 2020) further boosted the popularity of generative models in natural language processing (NLP). With the introduction of ChatGPT, generative models have taken center stage. These models require a large number of parameters to perform well across different tasks. While they offer impressive capabilities and versatility, they often necessitate substantial computational power and resources. Training or fine-tuning such large models on standard computers is not feasible.

In contrast, smaller encoder models have demonstrated remarkable performance in natural language understanding tasks. These models can be fine-tuned and executed with far less hardware, and their performance after fine-tuning is comparable to that of a large language model on specific tasks.

In this study, we address the lack of a large-scale Persian BERT model by training a new model using state-of-the-art techniques on a large Persian dataset. We also trained a base version to serve as a comparison point. Our main contributions are twofold: **(I)** We are making available to the public two new checkpoints of the BERT model specifically trained for the Persian language, which fills a significant gap in the availability of large-scale models for this language; **(II)** Through systematic evaluation across 14 diverse Persian natural language understanding (NLU) tasks, our larger checkpoint demonstrates superior performance, achieving an average improvement of at least +2.8 points compared to other models.

2 Related Works

BERT was introduced by (Devlin et al., 2019) and improved by RoBERTa (Liu et al., 2019). The key difference between these models is their training objective. RoBERTa removed the next sentence prediction loss, focusing solely on masked language modeling loss, and demonstrated that this alone is sufficient for training.

Task→	ParsiNLU					NER		Avg.
	Reading Comprehension	Sentiment Analysis	QQP	Multiple Choice	Entailment	Peyma NER	MultiConer	
Models↓ Metrics→	EM/F1	F1/Acc.	F1/Acc.	F1/Acc.	F1/Acc.	F1/Acc.	F1/Acc.	-
XLM-V	8.0/26.7	82.3/84.1	80.1/80.0	35.3/35.2	28.3/37.8	88.1/97.8	58.8/92.2	59.6
XLM-RoBERTa-Base	20.0/40.4	89.7/89.9	79.1/79.0	32.4/32.4	53.8/53.7	87.8/97.8	60.4/92.5	64.9
Bert Multilingual	27.2/42.2	86.8/87.5	79.2/79.3	33.4/33.1	54.4/54.4	83.7/96.9	60.3/92.5	65.1
Shiraz	17.6/39.6	87.1/87.8	79.7/79.5	34.7/34.5	39.9/41.5	86.4/97.6	59.1/92.8	62.7
Parsbert	20.0/39.6	88.6/88.9	80.2/80.1	35.3/35.2	49.9/49.6	86.8/97.7	64.9/93.2	65.0
AriaBERT	14.4/35.5	87.9/88.4	79.1/78.8	30.8/30.9	44.5/44.4	84.1/97.3	61.0/92.5	62.1
FaBERT	27.2/48.4	90.4/90.5	82.3/82.3	32.5/32.4	55.0/54.8	87.4/97.6	63.9/93.0	67.0
TookaBERT-Base	20.8/42.5	89.6/89.7	81.3/81.3	33.6/33.8	49.3/48.9	86.3/97.8	66.2/93.3	65.3
TookaBERT-Large	33.6/60.5	91.1/91.4	82.7/82.6	36.1/36.0	54.3/54.1	86.2/98.0	69.7/94.1	69.3

Table 1: Performance comparison of various base models on different end-tasks. The 'Average' column is calculated based on the scores presented in this table for both ParsiNLU and named entity recognition tasks.

There are several pre-trained Persian BERT models, with the earliest and most well-known being ParsBERT by Farahani et al. (2021). Other models include AriaBERT (Ghafouri et al., 2023), FaBERT (Masumi et al., 2024), and the recent Shiraz and Tehran models by Azizi et al. (2024). While Persian BERT models from last year outperformed ParsBERT, none of them experimented with model sizes beyond BERT-Base, such as BERT-Large. Multilingual pre-trained BERT models have also exhibited good performance on Persian tasks (Conneau et al., 2020; Liang et al., 2023).

3 Data

Pre-training dataset: This includes a mix of public datasets: hmblogs (Khansari and Shamsfard, 2021), the cleaned Persian subset of madlad (Kudugunta et al., 2023), and PersianWebScraper (Ziabary, 2024). We normalized these datasets using NFKC to ensure standard UTF-8 encoding for Persian text. We also replaced some Arabic characters with their Persian equivalents.

Evaluation dataset: We aggregated multiple Persian NLU datasets for evaluation. Unlike English, which has well-known collections like GLUE (Wang et al., 2019) and SuperGLUE (Wang et al., 2020), Persian lacks a comprehensive NLU dataset collection. We used the ParsiNLU dataset (Khashabi et al., 2021), which includes 6 tasks, one of which is machine translation and is not relevant for BERT evaluation. Therefore, we utilized the remaining 5 tasks from ParsiNLU along with the following individual datasets: PeymaNER (Shahshahani et al., 2018), Persian subset of Mul-

tiCoNER (Malmasi et al., 2022), PQA (Ayoubi, 2021), PQuAD (Darvishi et al., 2023), FarsTail (Amirkhani et al., 2023), DeepSentiPers (Sharami et al., 2020), SnappFood sentiment dataset¹ (Farahani et al., 2021), SentiPers (Hosseini et al., 2018), and Arman Emotion (Mirzaee et al., 2022). Our aim is to give a fair comparison for the foundation models we are testing by using a variety of Persian language tasks.

4 Methodology

4.1 Tokenizer

The original BERT paper used the WordPiece algorithm for tokenization (Devlin et al., 2019). However, newer models mostly use byte pair encoding (BPE) (Sennrich et al., 2016). Examples include RoBERTa (Liu et al., 2019) and LLaMA (Touvron et al., 2023). We also chose to use BPE for our tokenizer. We trained a new Persian tokenizer using this algorithm and set our vocab size to 48,000. During the training phase, we also used BPE-dropout (Provilkov et al., 2020) of 0.1 to regularize our model and improve generalization over unseen tokens.

4.2 BERT Pre-training

We trained our BERT model using the latest advancements and ideas in the field. Our approach was influenced by other works such as MosaicBERT (Portes et al., 2023). To speed up training and efficiently utilize GPU memory, we employed flash attention v2 (Dao, 2023). Addition-

¹Available at: <https://bit.ly/2Xu2xq1>

Task→	QA		NLI	Sentiment				Avg.
	PQA	PQuAD	FarsTail	DeepSentiPers	Snappfood	SentiPers	Arman Emotion	
Models↓ Metrics→	EM/F1/Has-EM/Has-F1	EM/F1/Has-EM/Has-F1	F1/Acc.	F1/Acc.	F1/Acc.	F1/Acc.	F1/Acc.	-
XLM-V	40.3/57.0/29.8/62.3	73.3/85.7/68.2/85.6	81.1/81.2	83.4/83.4	88.0/88.1	74.6/74.8	42.3/48.0	71.1
XLM-RoBERTa-Base	39.2/58.0/30.2/62.5	73.7/86.2/68.2/85.8	82.0/82.0	84.0/84.1	87.6/87.7	75.7/75.8	69.8/70.0	75.0
Bert Multilingual	37.8/56.0/28.1/60.9	71.8/84.7/65.9/84.0	82.7/82.8	78.6/78.7	87.1/87.1	71.7/71.9	62.2/62.4	72.1
Shiraz	30.4/44.4/18.1/51.6	66.0/81.2/59.6/81.3	77.8/77.8	81.2/81.1	87.1/87.1	73.4/73.8	71.6/71.7	71.3
Parsbert	36.7/49.8/26.8/56.1	71.4/84.2/66.3/84.6	80.9/80.9	80.2/80.2	87.6/87.7	74.3/74.4	67.2/67.4	72.8
AriaBERT	35.0/44.4/19.5/48.1	68.1/81.2/62.1/80.9	74.5/74.4	80.5/80.5	87.7/87.8	73.6/73.8	71.4/71.5	71.1
FaBERT	39.8/55.6/30.0/62.2	72.6/85.4/67.2/85.3	83.7/83.7	82.7/82.7	88.1/88.1	75.0/75.3	72.9/73.0	75.3
TookaBERT-Base	38.7/54.4/29.2/60.9	73.2/85.7/68.3/85.9	83.3/83.4	83.9/83.9	87.4/87.4	74.9/75.1	73.2/73.4	75.3
TookaBERT-Large	46.2/65.0/38.4/69.9	75.6/88.1/70.2/87.8	89.7/89.7	85.7/85.8	88.1/88.1	76.3/76.5	74.7/74.7	78.6

Table 2: Performance comparison of base models on various end-tasks. The 'Average' column is calculated based on the scores from question answering, natural language inference, and sentiment analysis datasets, as presented in this table.

ally, we made use of multiple GPUs effectively by utilizing the ZeRO stage 2 optimizer (Rajbhandari et al., 2020).

Similar to RoBERTa (Liu et al., 2019), we used only mask language modeling as our objective and excluded next sentence prediction. To avoid the computational waste of padding tokens, we concatenated our entire dataset and used it as a single batch (Zeng et al., 2022). We also incorporated whole-word-masking (Cui et al., 2021) to make predicting masks more challenging and improve the model’s capabilities.

We trained two BERT models in standard **Base** and **Large** sizes. The training was conducted using 8xA100 40GB GPUs.

4.3 Evaluation

For a fair comparison, we fine-tuned each model with four different learning rates: $3e-5$, $3e-6$, $7e-5$, and $7e-6$ for eight epochs. We then reported the best evaluation score achieved by each model across these learning rates and epochs. In addition to our models, we also evaluated the following pre-trained language models: ParsBERT (Farahani et al., 2021), AriaBERT (Ghafouri et al., 2023), FaBERT (Masumi et al., 2024), Shiraz (Azizi et al., 2024), BERT multilingual (Devlin et al., 2019), XLM-RoBERTa-Base (Conneau et al., 2020), and XLM-V (Liang et al., 2023)

5 Results

We employed various evaluation metrics depending on the nature of the task. The score for each task was computed by averaging the respective metrics, with the F1-score and accuracy being the most

prevalent across all tasks.

The results, as shown in Tables 1 and 2, indicate that TookaBERT-Large demonstrated superior performance compared to other models in the majority of end-tasks. On average, it achieved an impressive 2.8-point improvement over models such as FaBERT.

6 Conclusion

In this study, we presented two new BERT models specifically trained for Persian natural language understanding (NLU) tasks. By employing state-of-the-art techniques and a large Persian dataset, we successfully trained and introduced TookaBERT-Base and TookaBERT-Large to address the lack of large-scale Persian BERT models. Our comprehensive evaluations across 14 diverse Persian NLU tasks showcased the superiority of our larger model, outperforming other existing models by an average of +2.8 points. This highlights the effectiveness and potential of our new BERT models for Persian language processing.

The significant performance of TookaBERT-Large underscores the importance of model size and training techniques in language model development. By making our models publicly available, we hope to contribute to the advancement of Persian NLU and encourage further research in this direction. Our work showcases the potential of adapting foundation models to specific languages, and we believe that future studies can build upon our models to further enhance their performance and applicability in various Persian language tasks.

References

- Hossein Amirkhani, Mohammad AzariJafari, Soroush Faridan-Jahromi, Zeinab Kouhkan, Zohreh Pourjafari, and Azadeh Amirak. 2023. *Farstail: a persian natural language inference dataset*. *Soft Computing*.
- Mohammad Yasin Ayoubi, Sajjad & Davoodeh. 2021. Persianqa: a dataset for persian question answering. <https://github.com/SajjjadAyobi/PersianQA>.
- Mehrdad Azizi, Reza Salehi Chegeni, Parisa Mousavi, and Iman Hashemi. 2024. [optimizing pre-trained bert-based models for persian language processing].
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. *Language models are few-shot learners*. In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc.
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. *Unsupervised Cross-lingual Representation Learning at Scale*. *arXiv preprint*. ArXiv:1911.02116 [cs].
- Yiming Cui, Wanxiang Che, Ting Liu, Bing Qin, and Ziqing Yang. 2021. *Pre-Training with Whole Word Masking for Chinese BERT*. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 29:3504–3514. ArXiv:1906.08101 [cs].
- Tri Dao. 2023. *FlashAttention-2: Faster Attention with Better Parallelism and Work Partitioning*. *arXiv preprint*. ArXiv:2307.08691 [cs].
- Kasra Darvishi, Newsha Shahbodaghkhan, Zahra Abbasiantaeb, and Saeedeh Momtazi. 2023. *Pquad: A persian question answering dataset*. *Computer Speech Language*, 80:101486.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. *BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding*. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Mehrdad Farahani, Mohammad Gharachorloo, Marzieh Farahani, and Mohammad Manthouri. 2021. *Parsbert: Transformer-based model for persian language understanding*. *Neural Processing Letters*, 53(6):3831–3847.
- Arash Ghafouri, Mohammad Amin Abbasi, and Hassan Naderi. 2023. *AriaBERT: A Pre-trained Persian BERT Model for Natural Language Understanding*. ISSN: 2693-5015.
- Pedram Hosseini, Ali Ahmadian Ramaki, Hassan Maleki, Mansoureh Anvari, and Seyed Abolghasem Mirroshandel. 2018. Sentipers: A sentiment analysis corpus for persian. *arXiv preprint arXiv:1801.07737*.
- Jeremy Howard and Sebastian Ruder. 2018. *Universal language model fine-tuning for text classification*. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 328–339, Melbourne, Australia. Association for Computational Linguistics.
- Hamzeh Motahari Khansari and Mehrnoush Shamsfard. 2021. *Hmblogs: A big general persian corpus*. *Preprint*, arXiv:2111.02362.
- Daniel Khashabi, Arman Cohan, Siamak Shakeri, Pedram Hosseini, Pouya Pezeshkpour, Malihe Alikhani, Moin Aminnaseri, Marzieh Bitaab, Faeze Brahman, Sarik Ghazarian, Mozhdeh Gheini, Arman Kabiri, Rabeeh Karimi Mahabagdi, Omid Memarrast, Ahmadreza Mosallanezhad, Erfan Noury, Shahab Raji, Mohammad Sadegh Rasooli, Sepideh Sadeghi, Erfan Sadeqi Azer, Niloofar Safi Samghabadi, Mahsa Shafaei, Saber Sheybani, Ali Tazarv, and Yadollah Yaghoobzadeh. 2021. *ParsiNLU: A suite of language understanding challenges for Persian*. *Transactions of the Association for Computational Linguistics*, 9:1147–1162.
- Sneha Kudugunta, Isaac Caswell, Biao Zhang, Xavier Garcia, Christopher A. Choquette-Choo, Katherine Lee, Derrick Xin, Aditya Kusupati, Romi Stella, Ankur Bapna, and Orhan Firat. 2023. *Madlad-400: A multilingual and document-level large audited dataset*. *Preprint*, arXiv:2309.04662.
- Davis Liang, Hila Gonen, Yuning Mao, Rui Hou, Naman Goyal, Marjan Ghazvininejad, Luke Zettlemoyer, and Madian Khabza. 2023. *XLM-V: Overcoming the Vocabulary Bottleneck in Multilingual Masked Language Models*. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 13142–13152, Singapore. Association for Computational Linguistics.
- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. *RoBERTa: A Robustly Optimized BERT Pretraining Approach*. *arXiv preprint*. ArXiv:1907.11692 [cs].
- Shervin Malmasi, Anjie Fang, Besnik Fetahu, Sudipta Kar, and Oleg Rokhlenko. 2022. *MultiCoNER: A large-scale multilingual dataset for complex named entity recognition*. In *Proceedings of the 29th International Conference on Computational Linguistics*, pages 3798–3809, Gyeongju, Republic of Korea. International Committee on Computational Linguistics.

- Mostafa Masumi, Seyed Soroush Majd, Mehrnoush Shamsfard, and Hamid Beigy. 2024. **FaBERT: Pre-training BERT on Persian Blogs**. *arXiv preprint*. ArXiv:2402.06617 [cs].
- Hossein Mirzaee, Javad Peymanfard, Hamid Habibzadeh Moshtaghin, and Hossein Zeinali. 2022. **Armanemo: A persian dataset for text-based emotion detection**. *arXiv preprint*.
- Matthew E. Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. 2018. **Deep Contextualized Word Representations**. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 2227–2237, New Orleans, Louisiana. Association for Computational Linguistics.
- Jacob Portes, Alexander R Trott, Sam Havens, DANIEL KING, Abhinav Venigalla, Moin Nadeem, Nikhil Sardana, Daya Khudia, and Jonathan Frankle. 2023. **MosaicBERT: A bidirectional encoder optimized for fast pretraining**. In *Thirty-seventh Conference on Neural Information Processing Systems*.
- Ivan Provilkov, Dmitrii Emelianenko, and Elena Voita. 2020. **BPE-dropout: Simple and effective subword regularization**. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 1882–1892, Online. Association for Computational Linguistics.
- Alec Radford, Karthik Narasimhan, Tim Salimans, and Ilya Sutskever. 2018. **Improving language understanding by generative pre-training**.
- Samyam Rajbhandari, Jeff Rasley, Olatunji Ruwase, and Yuxiong He. 2020. **ZeRO: Memory Optimizations Toward Training Trillion Parameter Models**. *arXiv preprint*. ArXiv:1910.02054 [cs, stat].
- Rico Sennrich, Barry Haddow, and Alexandra Birch. 2016. **Neural machine translation of rare words with subword units**. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1715–1725, Berlin, Germany. Association for Computational Linguistics.
- Mahsa Sadat Shahshahani, Mahdi Mohseni, Azadeh Shakery, and Hesham Faili. 2018. **Peyma: A tagged corpus for persian named entities**. *Preprint*, arXiv:1801.09936.
- Javad PourMostafa Roshan Sharami, Parsa Abbasi Sarabestani, and Seyed Abolghasem Mirroshandel. 2020. **Deepsentipers: Novel deep learning models trained over proposed augmented persian sentiment corpus**. *Preprint*, arXiv:2004.05328.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023. **Llama 2: Open foundation and fine-tuned chat models**. *Preprint*, arXiv:2307.09288.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. **Attention is All you Need**. In *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc.
- Alex Wang, Yada Pruksachatkun, Nikita Nangia, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. 2020. **Superglue: A stickier benchmark for general-purpose language understanding systems**. *Preprint*, arXiv:1905.00537.
- Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. 2019. **GLUE: A multi-task benchmark and analysis platform for natural language understanding**. In *International Conference on Learning Representations*.
- Jinle Zeng, Min Li, Zhihua Wu, Jiaqi Liu, Yuang Liu, Dianhai Yu, and Yanjun Ma. 2022. **Boosting distributed training performance of the unpadded bert model**. *Preprint*, arXiv:2208.08124.
- S. Mehran M. Ziabary. 2024. **Targoman/PersianWebScraper: An accurate scrapper to scrape popular persian websites, mostly intended to be used as a tool to create large corpora for Persian language**. — github.com. <https://github.com/Targoman/PersianWebScraper>.