

Simpler Optimal Sorting from a Directed Acyclic Graph

Ivor van der Hoog, Eva Rotenberg, Daniel Rutschmann.
 Technical University of Denmark, DTU

Abstract

Fredman proposed in 1976 the following algorithmic problem: Given are a ground set X , some partial order P over X , and some comparison oracle O_L that specifies a linear order L over X that extends P . A *query* to O_L has as input distinct $x, x' \in X$ and outputs whether $x <_L x'$ or vice versa. If we denote by $e(P)$ the number of linear orders that extend P , then it follows from basic information theory that $\log e(P)$ is a worst-case lower bound on the number of queries needed to output the sorted order of X .

Fredman did not specify in what form the partial order is given. Haeupler, Hladík, Iacono, Rozhon, Tarjan, and Tětek ('24) propose to assume as input a directed acyclic graph, G , with m edges and $n = |X|$ vertices. Denote by P_G the partial order induced by G . Their algorithmic performance is measured in running time and the number of queries used, where they use $\Theta(m + n + \log e(P_G))$ time and $\Theta(\log e(P_G))$ queries to output X in its sorted order. Their algorithm is worst-case optimal in terms of running time and queries, both. Their algorithm combines topological sorting with heapsort. Their analysis relies upon sophisticated counting arguments using entropy, recursively defined sets defined over the run of their algorithm, and vertices in the graph that they identify as bottlenecks for sorting.

In this paper, we do away with sophistication. We show that when the input is a directed acyclic graph then the problem admits a simple solution using $\Theta(m + n + \log e(P_G))$ time and $\Theta(\log e(P_G))$ queries. Especially our proofs are much simpler as we avoid the usage of advanced charging arguments and data structures, and instead rely upon two brief observations.

Funding. Ivor van der Hoog received funding from the European Union’s Horizon 2020 research and innovation programme under the Marie Skłodowska-Curie grant agreement No 899987. Daniel Rutschmann and Eva Rotenberg received funding from Carlsberg Foundation Young Researcher Fellowship CF21-0302 “Graph Algorithms with Geometric Applications”. Eva Rotenberg additionally receives funding from DFF Grant 2020-2023 (9131-00044B) “Dynamic Network Analysis”, and VILLUM Foundation grant VIL37507 “Efficient Recomputations for Changeful Problems”.

1 Introduction

Sorting is a fundamental problem in computer science. In 1976, Fredman introduced a natural generalisation of sorting, namely sorting under partial information [4]:

Given a ground set X of size n , and some partial order P on X , and an oracle O_L with access to a ground-truth linear order L of X , the task is to minimise the number of oracle queries to recover the linear order of X . A query takes two input elements from X , and outputs their relation in the linear order. Algorithmic efficiency is measured in time, and the number of queries used. Let $e(P)$ denote the number of linear orders that extend the partial order P . Then, for any binary (e.g. yes/no) query, $\lceil \log_2(e(P)) \rceil$ is a worst-case lower bound for the number of queries needed, simply because the sequence of answers should be able to lead to any possible extension of the order.

Previous work. Fredman [4, TCS'76] shows an exponential-time algorithm for sorting under partial information that uses $\log e(P) + O(n)$ queries. This fails to match the $\Omega(\log e(P))$ lower bound when $\log e(P)$ is sublinear. Kahn and Saks [9, Order'84] prove that there always exists a query which reduces the number of remaining linear extensions by a constant fraction; showing that an $O(\log e(P))$ -query algorithm exists. Kahn and Kim [8, STOC'92] are the first to also consider algorithmic running time. They note that Kahn and Saks [9] can preprocess a partial order using exponential time and space, so that given O_L it can output the sorted order of X in linear time plus $O(\log e(P))$ queries. Kahn and Kim [8, STOC'92] propose the first polynomial time algorithm that performs $O(\log e(P))$ queries. They do not separate preprocessing the partial order and oracle queries, and use an unspecified polynomial time using the ellipsoid method. Cardinal, Fiorini, Joret, Jungers and Munro [2, STOC'10] (in their full version in *Combinatorica*) preprocess P in $O(n^{2.5})$ time, to output the sorted X in $O(\log e(P) + n)$ time using $O(\log e(P))$ queries. Their runtime poses the question whether query-optimal (sub)quadratic-time algorithms are possible.

For subquadratic algorithms, it becomes relevant how one obtains the partial order. Van der Hoog, Kostityna, Löffler and Speckmann [12, SOCG'19] study the problem in a restricted setting where P is induced by a set of intervals. Here, distinct $x_i, x_j \in X$ are incomparable whenever their intervals $([a_i, b_i], [a_j, b_j])$ intersect (otherwise, $x_i \prec_P x_j$ whenever $b_i < a_j$). They preprocess the intervals in $O(n \log n)$ time such that, given O_L , they can produce a pointer to a linked list storing X in its sorted order using $O(\log e(P))$ queries and time. For their queries, they use *finger search* [1] (i.e., *exponential search* from a pointer). Finger search has as input a value x_i , a sorted list π , and a finger $p \in \pi$ with $p < x_i$. It finds the farthest q along π for which $q < x_i$ in $O(1 + \log d_i)$ time and comparisons. Here, d_i denotes the length of the sublist from p to q [1].

Van der Hoog and Rutschmann [7, FOCS'24] assume that P is given as another oracle O_P where queries receive distinct $x, x' \in X$ and output whether $x \prec_P x'$. For fixed $c \geq 1$, they preprocess O_P using $O(n^{1+\frac{1}{c}})$ time and queries to O_P . Given O_L , they produce a pointer to a linked list storing X in its sorted order using $O(c \cdot \log e(P))$ queries and time. Their query algorithm also makes use of finger search. They show matching lower bounds in their setting.

Haeupler, Hladík, Iacono, Rozhon, Tarjan, and Tětek [5, '24] assume that the partial order P_G is induced by a graph G with m edges. Their algorithm can be seen as a combination of topological sort and heapsort. Their algorithm first isolates a collection $B \subset X$ which they call *bottlenecks*. They then iteratively consider all sources S in $G - B$, remove the source $s \in S$ that is *minimum* in the linear order L , and append s to the output a directed path π . Before appending s to π , they find the maximum prefix $B_s = \{b \in B \mid b <_L s\}$ using finger search where the finger is the head of B . They remove B_s from B , append B_s to π , and then append s . To obtain the minimum $s \in S$, they store all current sources of the graph in a *heap* where comparisons in the heap use the linear oracle O_L . Their algorithm does not separate preprocessing the graph G , and oracle queries. It uses $\Theta(n + m + \log e(P_G))$ overall time and $\Theta(\log e(P))$ linear oracle queries. Since reading the input takes at least $O(n + m)$ time, their overall algorithmic runtime is thereby worst-case optimal. The bulk of their analysis is dedicated to charging the algorithmic runtime and query time to the workings of their heap, and to handling the special bottleneck vertices. We note that for any input k , their solution can also report the first k elements of the sorted order in optimal time.

Contribution. We consider the setting from [5], where the input is a directed acyclic graph G over X with m edges and where, unlike [2, 7, 12], one does not separate the algorithmic performance between a pre-processing phase using G and a phase that uses queries to O_L . We show that this problem formulation allows for a surprisingly simple solution: G denotes the input and H_i the graph at iteration i . Remove a maximum-length directed path π from G to get H_1 . Iteratively

remove an *arbitrary* source x_i from H_i to get H_{i+1} . Insert x_i into π using *finger search* where the finger p_i is the farthest in-neighbour of x_i in G along π (we find p_i by simply iterating over all in-neighbours of x_i). We use $\Theta(n + m + \log e(P_G))$ time and $\Theta(\log e(P_G))$ queries. We consider this algorithm to be simpler. Our proof of correctness is considerably simpler, as it relies upon only one counting argument and one geometric observation.

2 Algorithm

The input is a directed acyclic graph G with vertex set $X = (x_1, \dots, x_n)$. This graph induces a partial order P_G where $x_i \prec x_j$ if and only if there exists a directed path from x_i to x_j in G . The input also contains an oracle O_L that specifies a linear order L over X . For any distinct x_i, x_j , an (oracle) query answers whether $x_i <_L x_j$. The goal is to output X in its sorted order L .

We describe our algorithm. Our key observation is that the problem becomes significantly easier when we first extract a maximum-length directed path π from G . We iteratively remove an *arbitrary* source x_i from $H = G - \pi$ and insert it into π . Once H is empty, we return π .

In our analysis, our logarithms are base 2 and $d^*(x_i)$ denotes the sum of the out-degree and the in-degree of a vertex x_i in G .

Data structures. We maintain a path π where for all vertices $p, q \in \pi$: $p <_L q$ if and only if p precedes q in π . We store π in two leaf-linked binary trees T_π and T'_π . Both trees are subject to finger insertions. T_π is used for (finger) search, and T'_π is used for a comparison operation:

FINGERINSERT(q_i, x_i, T). Given vertices $x_i \notin \pi$ and $q_i \in \pi$, and a tree T storing π , insert x_i into π succeeding q_i by replacing the leaf in T storing q_i with a node that has (q_i, x_i) as its children.

SEARCH(x_i, p_i, O_L). Given a vertex $x_i \notin \pi$ and a vertex $p_i \in \pi$ with $p_i <_L x_i$. Return the farthest vertex q_i along π where $q_i <_L x_i$. Let d_i denote the number of vertices on the subpath from p_i to q_i along π . We want to use $O(1 + \log d_i)$ time and queries to O_L . To achieve this, we store π in a balanced finger search tree T_π . Many implementations exist [1]. We choose the level-linked (2-4)-tree by Huddleston and Mehlhorn [6], which supports FINGERINSERT in amortised $O(1)$ -time.

COMPARE(p, q). Given $p, q \in \pi$, return q whenever q precedes p in $O(1)$ time (and p otherwise). We store π in a tree T'_π which itself is stored in the dynamic Lowest Common Ancestor (LCA) data structure by Cole, and Hariharan [3]. They maintain T'_π subject to FINGERINSERT in $O(1)$ time. LCA queries can for any pair of leaves (u, v) give their lowest common ancestor (and whether u is in the left subtree) in $O(1)$ time. This data structure does not support rotating T'_π . However, it also does not require T'_π to be balanced. Observe that COMPARE does not use the oracle O_L .

Algorithm and runtime analysis. Our algorithm is straightforward. The pseudo code is given by Algorithm 1 where each algorithmic step also indicates the running time. We require linear space. We first extract a longest directed path π from G , which we store in our two data structures. This takes $O(n + m)$ total time. If π has $n - k$ vertices, this leaves us with a graph H with k vertices.

We then iteratively remove an arbitrary source x_i from H . Since x_i is a source in H , all vertices $p \in X$ that have a directed path to x_i in G must be present in π . We iterate over all in-neighbours of x_i in G , and use our COMPARE operation to find the in-neighbour p_i that is furthest along π . If x_i has no in-neighbors, p_i is a dummy vertex that precedes the head of π instead. Finally, we proceed in a way that is very similar to the algorithm for topological sorting by Knuth [10]: We remove x_i from H , iterate over all out-neighbors of x_i in H and decrement their in-degree, and update the linked list of sources to include the newly found ones. Since we inspect each in- and out-edge of x_i only once, this takes $O(m)$ total time.

Algorithm 1 Sort(directed acyclic graph G over a ground set X , Oracle O_L)	time
1: $\pi \leftarrow$ a longest directed path in G	$\triangleright O(n + m)$
2: $T_\pi \leftarrow$ a level-linked (2-4)-tree over π [6]	$\triangleright O(n)$
3: $T'_\pi \leftarrow$ a LCA tree over π [3]	$\triangleright O(n)$
4: $H \leftarrow G - \pi$	$\triangleright O(n + m)$
5: Compute for each vertex in H its in-degree in H	$\triangleright O(n + m)$
6: $S \leftarrow$ sources in H	$\triangleright O(n)$
7: while $S \neq \emptyset$ do	
8: Remove an arbitrary vertex x_i from S	$\triangleright O(1)$
9: $p_i \leftarrow$ a dummy vertex, which is prepended before the head of π	$\triangleright O(1)$
10: for all in-neighbors u of x_i in G do	$\triangleright O(d^*(x_i))$
11: $p_i \leftarrow$ COMPARE(p_i, u)	
12: Remove x_i from H and add any new sources in H to S	$\triangleright O(d^*(x_i))$
13: $q_i \leftarrow$ SEARCH(x_i, p_i, O_L)	$\triangleright O(1 + \log d_i)$
14: FINGERINSERT(q_i, x_i, T_π)	$\triangleright O(1)$ amortised
15: FINGERINSERT(q_i, x_i, T'_π)	$\triangleright O(1)$
16: return the leaves of T_π in order	$\triangleright O(n)$

We then want to find the farthest q_i along π that precedes x_i in L . In the special case where p_i is the dummy vertex preceding the head h of π , we use a query to O_L to check whether $x_i <_L h$. If so, we return $q_i = p_i$. Otherwise, we set $p_i = h$ and invoke SEARCH. This returns q_i in $O(1 + \log d_i)$ time and queries, where d_i is the length of the subpath from p_i to q_i in π ($d_i = 1$ if $p_i = q_i$).

Finally, we insert x_i into T_π and T'_π succeeding q_i in constant time. We rebalance the tree T_π , which takes amortised $O(1)$ time. Thus, these operations take $O(n)$ total time over all insertions. Therefore, our algorithm uses $O\left(n + m + \sum_{x_i \in H} (1 + \log d_i)\right)$ time and $O\left(\sum_{x_i \in H} (1 + \log d_i)\right)$ queries.

2.1 Proof of optimality

Recall that $e(P_G)$ denotes the number of linear extensions of P_G and let H start out with k vertices. For ease of analysis, we re-index the vertices X so that the path π are vertices (x_{k+1}, \dots, x_n) , in order, and x_i for $i \in [k]$ is the i 'th vertex our algorithm inserts into T_π . We prove that our algorithm is tight by showing that $\sum_{i=1}^k (1 + \log d_i) = k + \sum_{i=1}^k \log d_i \in O(\log e(P_G))$.

Lemma 1. *Let G be a directed acyclic graph, P_G be its induced partial order and π be a longest directed path in G . If π has $n - k$ vertices then $\log e(P_G) \geq k$.*

Proof. Denote $\ell(x)$ the length of the longest directed path in G from a vertex x . Denote for $i \in [n]$ by $L_i := |\{x \in X \mid \ell(x) = i\}|$. For each $i \in [n - k]$, there is one $u \in \pi$ with $\ell(u) = i$ so: $k = \sum_{i=1}^{n-k} (L_i - 1)$. Consider a linear order L' that is obtained by first sorting all $x \in X$ by $\ell(x)$ from high to low, and ordering (u, v) with $\ell(u) = \ell(v)$ arbitrarily. The order L' must extend P_G , since any vertex w that has a directed path towards a vertex u must have that $\ell(w) > \ell(u)$. We count the number of distinct L' that we obtain in this way to lower bound $e(P_G)$:

$$e(P_G) \geq \prod_{i=1}^{n-k} L_i! \quad \Rightarrow \quad e(P_G) \geq \prod_{i=1}^{n-k} 2^{L_i-1} = 2^{\left(\sum_{i=1}^{n-k} (L_i-1)\right)} \quad \Rightarrow \quad e(P_G) \geq 2^k$$

Here, the first implication uses that $x! \geq 2^{x-1}$ and the second implication uses that $k = \sum_{i=1}^{n-k} (L_i - 1)$. \square

What remains is to show that $\sum_{i=1}^k \log d_i \in O(\log e(P_G))$. To this end, we create a set of intervals:

Definition 1. Let π^* be the directed path that Algorithm 1 outputs. For any $i \in [n]$ denote by $\pi^*(x_i)$ the index of x_i in π^* . We create an embedding E of X by placing x_i at position $\pi^*(x_i)$.

Recall that for $i \in [k]$, p_i is the finger from where Algorithm 1 invokes SEARCH with x_i as the argument. We create as set \mathcal{R} of n intervals $R_i = [a_i, b_i] \subseteq [1, n]$ as follows:

- If $i > k$ then $[a_i, b_i] := [\pi^*(x_i), \pi^*(x_i)]$.
- Else, $[a_i, b_i] := [\pi^*(p_i) + 1, \pi^*(x_i)]$.

Lemma 2. Given distinct $x_i, x_j \in X$. If there exists a directed path from x_i to x_j in G then the intervals $R_i = [a_i, b_i]$ and $R_j = [a_j, b_j]$ are disjoint with $b_i < a_j$.

Proof. We consider three cases.

If $j > k$ and $i > k$ then x_i and x_j are part of the original longest directed path in G . If x_i has a directed path to x_j in G then x_i precedes x_j on the original longest directed path. Thus, $\pi^*(x_i)$ precedes $\pi^*(x_j)$ and R_i and R_j are distinct singletons where R_i precedes R_j .

If $i \leq k$ and $j > k$ then x_i was inserted into the path π with x_j already in π . Since π^* is a linear extension of P_G , it follows that x_i was inserted preceding x_j in π . It follows that x_i precedes x_j in π^* and thus $R_i = [\pi^*(p_i) + 1, \pi^*(x_i)]$ lies strictly before $R_j = \{\pi^*(x_j)\}$.

If $j \leq k$ then the vertex p_j must equal or succeed x_i in π^* and thus $b_i = \pi^*(x_i) < a_j = \pi^*(p_j)$. \square

The set \mathcal{R} induces an interval order $P_{\mathcal{R}}$ over X , which is the partial order $\prec_{\mathcal{R}}$ where x_i and x_j are incomparable whenever R_i and R_j intersect, and where otherwise $x_i \prec_{\mathcal{R}} x_j$ whenever $b_i < a_j$. By Lemma 2, any linear order L that extends $P_{\mathcal{R}}$ must also extend P_G and so $e(P_{\mathcal{R}}) \leq e(P_G)$. The number of linear extensions of an interval order is much easier to count. In fact, Cardinal, Fiorini, Joret, Jungers and Munro [2] and Van der Hoog, Kostityna, Löffler and Speckmann [12] already upper bound the number of linear extensions of an interval order. We paraphrase their upper bound (for completeness, we show in Appendix A that this is correct paraphrasing). Let for an interval R with integer endpoints, $\#R$ denote the number of integers contained in R . Then:

Lemma 3 (Lemma 1 in [12] and Lemma 3.2 in [2]). Let $\mathcal{R} = (R_1, \dots, R_n)$ be a set of n intervals in $[1, n]$ with integer endpoints and $P_{\mathcal{R}}$ be its induced partial order. Then $\sum_{i=1}^n \log(\#R_i) \in O(\log e(P_{\mathcal{R}}))$.

We are now ready to prove our main theorem:

Theorem 1. Given a directed acyclic graph G over X , inducing a partial order P_G , and an oracle O_L whose queries specify a linear order L that extends P_G , there exists an algorithm that uses linear space, $O(n + m + \log e(P_G))$ time and $O(\log e(P_G))$ oracle queries to output the sorted order of X .

Proof. Our algorithm runs in $O(n + m + k + \sum_{i=1}^k \log d_i)$ time and uses $O(k + \sum_{i=1}^k \log d_i)$ comparisons.

By Lemma 1, $k \in O(\log e(P_G))$. The set \mathcal{R} of Definition 1 is a set where each interval R_i has integer coordinates. By Lemma 2, $e(P_{\mathcal{R}}) \leq e(P_G)$. For $i \leq k$, the size $\#R_i$ must be at least d_i since there are per construction at least d_i vertices on the subpath from $\pi^*(p_i)$ to $\pi^*(q_j)$ in the embedding E .

It follows by Lemma 3 that $\sum_{i=1}^k \log d_i \in O(\log e(P_{\mathcal{R}})) \subseteq O(\log e(P_G))$. \square

A Deriving Lemma 3

Lemma 3 is a weaker statement than Lemma 1 from [12] (which itself paraphrased Lemma 3.2 from [2]). We use Lemma 1 from [12] since its formulation is arithmetically a bit easier to use.

Lemma 3 (Lemma 1 in [12] and Lemma 3.2 in [2]). *Let $\mathcal{R} = (R_1, \dots, R_n)$ be a set of n intervals in $[1, n]$ with integer endpoints and $P_{\mathcal{R}}$ be its induced partial order. Then $\sum_{i=1}^n \log(\#R_i) \in O(\log e(P_{\mathcal{R}}))$.*

Proof. Let \mathcal{R} be set of intervals with integer endpoints. An (open or closed) interval R_1 precedes an interval R_2 whenever they are disjoint and each point in R_1 is to the left of each point in R_2 .

In [12], they define an *embedding* \mathcal{I} of \mathcal{R} into $[0, 1]$ as any set of *open* intervals (I_1, \dots, I_n) where I_i intersects I_j if and only if R_i intersects R_j , and I_i precedes I_j if and only if R_i precedes R_j . They denote by $E(\mathcal{R})$ the set of all embeddings of \mathcal{R} into $[0, 1]$ and by $|I_i|$ the size of the open interval.

We note that in [12] $H(\mathcal{R})$ denotes the *entropy* of \mathcal{R} and that $n \cdot H(\mathcal{R}) \leq 2 \log e(P_{\mathcal{R}})$. Lemma 1 from [12] then states that:¹

$$n \cdot H(\mathcal{R}) = \sup_{\mathcal{I} \in E(\mathcal{R})} \left(\sum_{I_i \in \mathcal{I}} \log(n|I_i|) \right).$$

Effectively, the inside of the log scales each open interval in $[0, 1]$ to an interval in $[0, n]$ instead. If we denote by $E^*(\mathcal{R})$ the set of all embeddings \mathcal{I}^* of \mathcal{R} into $[0, n]$, this implies that:

$$n \cdot H(\mathcal{R}) = \sup_{\mathcal{I}^* \in E^*(\mathcal{R})} \left(\sum_{I_i \in \mathcal{I}^*} \log(|I_i|) \right).$$

The set \mathcal{R} is a set of intervals with integer endpoints in $[1, n]$. We create a set \mathcal{R}' of open intervals by adding for each $[a_i, b_i] \in \mathcal{R}$ the interval $(a_i, b_i + 1)$. We observe that \mathcal{R}' is an embedding \mathcal{R}' of \mathcal{R} in $[0, n]$ where each open interval (a'_i, b'_i) has length $\#[a_i, b_i]$. Since $\mathcal{R}' \in E^*(\mathcal{R})$ it follows that:

$$\sum_{R_i \in \mathcal{R}} \log(\#R_i) = \sum_{R_i \in \mathcal{R}} |(a'_i, b'_i)| \leq n \cdot H(\mathcal{R}) \leq 2 \log e(P_{\mathcal{R}}) \quad \square$$

B Deriving Lemma 3 using graph entropy

To avoid the use of a length-2 chain of citations, we also provide a proof for Lemma 3 that only relies on the definition of graph entropy by Körner [11] (and Theorem 3.1 in [2] that relates graph entropy to $\log e(P)$). Let $\mathcal{R} = (R_1, \dots, R_n)$ be a collection of intervals in $[1, n]$ with integer endpoints. Let $\#R_i$ be the number of integer points in R_i .

Recalling the definition of graph entropy. We use the definition of graph entropy by Körner [11]. Let G be a graph with vertex set V of order n . We denote for any $S \subseteq V$ by x^S its characteristic vector and define the stable set polytope as an n -dimensional polytope:

$$\text{Stab}(G) := \text{conv}\{x^S \in \mathbb{R}^{|V|} \mid S \subseteq V, \quad S \text{ independent set in } G\}$$

Then the graph entropy $H(G)$ is then defined as:

$$H(G) := \min_{x \in \text{Stab}(G)} \frac{1}{n} \sum_{i=1}^n -\log x_i$$

¹We note that in [12], Lemma 1 uses a maximum which should be a supremum as $E(\mathcal{R})$ has infinite size.

Using graph entropy as an algorithmic lower bound. For a directed graph P , let \overline{P} denote its undirected complement (which includes an edge $\{u, v\}$ whenever there exists no directed path between u and v in either direction). Cardinal, Fiorini, Joret, Jungers and Munro [2] prove that:

Theorem 2 (Theorem 3.1 in [2]). *Let P be a poset of order n then $n \cdot H(\overline{P}) \leq 2 \log e(P)$.*

We derive Lemma 3 from Theorem 2.

B.1 Deriving Lemma 3 from Theorem 2

Claim 1. *Every $x \in S$ satisfies*

$$\sum_{i=1}^n x_i \cdot \#R_i \leq n$$

Proof. If C is a chain in P_R , then the intervals in C are disjoint, hence

$$\sum_{i \in C} \#R_i \leq n.$$

Equivalently, if B is an independent set in $\overline{P_R}$, then

$$\sum_{i \in B} \#R_i \leq n.$$

As this is a linear inequality, the claim follows from the definition of S as the convex hull of indicator vectors of independent sets. \square

Claim 2. *Every $x \in S$ satisfies*

$$\frac{1}{n} \sum_{i=1}^n -\log x_i \geq \frac{1}{n} \sum_{i=1}^n \log \#R_i$$

Proof. By convexity of $-\log(\dots)$

$$\frac{1}{n} \sum_{i=1}^n -\log x_i = \frac{1}{n} \sum_{i=1}^n \left(-\log(x_i \cdot \#R_i) - \log(1/\#R_i) \right) \geq -\log \left(\frac{1}{n} \sum_{i=1}^n x_i \cdot \#R_i \right) + \frac{1}{n} \sum_{i=1}^n -\log(1/\#R_i).$$

By the previous claim,

$$-\log \left(\frac{1}{n} \sum_{i=1}^n x_i \cdot \#R_i \right) \geq 0.$$

\square

Claim 3.

$$n \cdot H(\overline{P_R}) \geq \sum_{i=1}^n \log \#R_i$$

Proof. Using the definition of entropy and the previous claim

$$H(\overline{P_R}) = \min_{x \in S} \frac{1}{n} \sum_{i=1}^n -\log x_i \geq \frac{1}{n} \sum_{i=1}^n \log \#R_i$$

\square

Now Lemma 3 follows from $n \cdot H(\overline{P_R}) \leq 2 \cdot \log e(P_R)$ (Theorem 2).

C Deriving Lemma 3 from first principles

The previous proof still relies on a previous theorem (Theorem 2). For the reader, we also present an additional proof that is entirely from first principles.

Lemma 4. *Let $\mathcal{R} = R_1, \dots, R_n$ be a set of n non-empty open intervals in $(0, n)$, with integers endpoints. Let P_R be the partial order on these intervals defined by the rule “ $(a, b) \prec (c, d)$ iff $b \leq c$ ”. Then $\sum_{i=1}^n \log |R_i| \in O(\log e(P_R))$.*

Proof. Let R_1, R_2, \dots, R_m form a maximum chain in P_R . Define an $(n - m)$ -dimensional polytope associated with \mathcal{R} .

$$A = \left\{ x \in \mathbb{R}^n \mid x_i = \text{middle}(R_i) \text{ for } i \leq m \text{ and } x_i \in R_i \text{ for } i > m \right\}$$

It is straight-forward to see that $\text{Vol}(A) = \prod_{i=m+1}^n |R_i|$. Any $x \in A$ with distinct coordinates defines a linear extension L of P_R via the rule “ $i \prec j$ iff $x_i < x_j$ ”. We call x a *realization* of L . Due to how we picked x_1, \dots, x_m , not all linear extensions might be realizable this way.

Claim 4. *Let L be a linear extension of P_R . Let $A_L = \{x \in A \mid x \text{ realizes } L\}$, then*

$$\text{Vol}(A_L) \leq e^{n-m}.$$

Proof. If L cannot be realized, then $\text{Vol}(A_L) = 0$. Otherwise, let $x \in A$ be any realization of L . Consider the $m + 1$ buckets $(-0.5, x_1), (x_1, x_2), \dots, (x_m, n + 0.5)$. Each bucket has length ≥ 1 . A bucket is *non-empty* if it contains x_i for some $i \in \{m + 1, \dots, n\}$. Let G be the union of the non-empty buckets. Then $|G| \leq |(-0.5, n + 0.5)| - (m + 1) = n - m$, as there are $\geq m + 1$ empty buckets, each of length ≥ 1 . Let

$$B_L = \left\{ y \in \mathbb{R}^m \times G^{n-m} \mid y_i = \text{middle}(R_i) \text{ for } i \leq m \text{ and } (x_j < x_k \Leftrightarrow y_j < y_k) \text{ for } j, k > m \right\}.$$

Then $A_L \subseteq B_L$, hence

$$\text{Vol}(A_L) \leq \text{Vol}(B_L) = \frac{|G|^{n-m}}{(n-m)!} = \frac{(n-m)^{n-m}}{(n-m)!} \leq e^{n-m}.$$

□

Claim 5. $\sum_{i=m+1}^n \ln |R_i| \leq \ln e(P_R) + (n - m)$

Proof.

$$\sum_{i=m+1}^n \ln |R_i| = \ln \text{Vol}(A) \leq \ln \sum_{L \supseteq P_R} \text{Vol}(A_L) \leq \ln \left(e(P_R) \cdot e^{n-m} \right).$$

□

Claim 6.

$$\sum_{i=1}^m \ln |R_i| \leq (n - m)$$

Proof. As R_1, \dots, R_m is a chain, $\sum_{i=1}^m |R_i| \leq n$. By analysis, $\ln x \leq x - 1$, hence

$$\sum_{i=1}^m \ln |R_i| \leq \sum_{i=1}^m (|R_i| - 1) = (n - m).$$

□

Combining these two claims yields

$$\sum_{i=1}^n \log |R_i| = \frac{1}{\ln(2)} \cdot \sum_{i=1}^n \ln |R_i| \leq \log e(P_R) + \frac{2}{\ln(2)} \cdot (n - m).$$

By Lemma 1, $n - m \leq \log e(P_R)$.

□

References

- [1] Gerth Stølting Brodal. Finger search trees. In *Handbook of Data Structures and Applications*, pages 171–178. Chapman and Hall/CRC, 2018.
- [2] Jean Cardinal, Samuel Fiorini, Gwenaël Joret, Raphaël M. Jungers, and J. Ian Munro. Sorting under partial information (without the ellipsoid algorithm). *Combinatorica*, 33(6):655–697, Dec 2013.
- [3] Richard Cole and Ramesh Hariharan. Dynamic lca queries on trees. *SIAM Journal on Computing*, 34(4):894–923, 2005.
- [4] Michael L. Fredman. How good is the information theory bound in sorting? *Theoretical Computer Science*, 1(4):355–361, April 1976.
- [5] Bernhard Haeupler, Richard Hladík, John Iacono, Vaclav Rozhon, Robert Tarjan, and Jakub Tětek. Fast and simple sorting using partial information. *arXiv preprint arXiv:2404.04552*, 2024.
- [6] Scott Huddleston and Kurt Mehlhorn. A new data structure for representing sorted lists. *Acta informatica*, 17:157–184, 1982.
- [7] Daniel Rutschmann Ivor van der Hoog. Tight bounds for sorting under partial information. In *65th IEEE Annual Symposium on Foundations of Computer Science, FOCS*. IEEE, 2024.
- [8] Jeff Kahn and Jeong Han Kim. Entropy and sorting. In *Proceedings of the twenty-fourth annual ACM symposium on Theory of Computing, STOC '92*, pages 178–187, New York, NY, USA, July 1992. Association for Computing Machinery.
- [9] Jeff Kahn and Michael Saks. Balancing poset extensions. *Order*, 1(2):113–126, June 1984.
- [10] Donald E Knuth. *The Art of Computer Programming: Fundamental Algorithms, Volume 1*. Addison-Wesley Professional, 1997.
- [11] Janos Körner. Coding of an information source having ambiguous alphabet and the entropy of graphs. In *6th Prague conference on Information Theory, etc.*, pages 411–425. Academia, Prague, 1971.
- [12] Ivor van der Hoog, Irina Kostitsyna, Maarten Löffler, and Bettina Speckmann. Preprocessing Ambiguous Imprecise Points. In *35th International Symposium on Computational Geometry (SoCG 2019)*, volume 129, pages 42:1–42:16, 2019.