# SPEAKER ADAPTATION FOR QUANTISED END-TO-END ASR MODELS

Qiuming Zhao<sup>1</sup>, Guangzhi Sun<sup>2</sup>, Chao Zhang<sup>1</sup>, Mingxing Xu<sup>1</sup>, Thomas Fang Zheng<sup>1</sup>\*

<sup>1</sup>Tsinghua University, Beijing, China; <sup>2</sup>University of Cambridge, Cambridge, UK

zqm23@mails.tsinghua.edu.cn; gs534@cam.ac.uk; {cz277,xumx,fzheng}@tsinghua.edu.cn

## ABSTRACT

End-to-end models have shown superior performance for automatic speech recognition (ASR) [1–4]. However, such models are often very large in size and thus challenging to deploy on resource-constrained edge devices. While quantisation can reduce model sizes [5–7], it can lead to increased word error rates (WERs). Although improved quantisation methods were proposed to address the issue of performance degradation [8–13], the fact that quantised models deployed on edge devices often target only on a small group of users is under-explored. To this end, we propose personalisation for quantised models (P4Q), a novel strategy that uses speaker adaptation (SA) to improve quantised end-to-end ASR models by fitting them to the characteristics of the target speakers.

In this paper, we study the P4Q strategy based on Whisper and Conformer attention-based encoder-decoder (AED) end-to-end ASR models, which leverages a 4-bit block-wise NormalFloat4 (NF4) approach [14] for quantisation and the low-rank adaptation (LoRA) approach [15] for SA. Experimental results on the LibriSpeech and the TED-LIUM 3 corpora show that, with a 7-time reduction in model size and 1% extra speaker-specific parameters, 15.1% and 23.3% relative WER reductions were achieved on quantised Whisper and Conformer AED models respectively, comparing to the full precision models.

## 1. METHODOLOGY

The P4Q strategy consists of 3 stages: First, block-wise NF4 quantisation is applied to the model's primary weights; then LoRA starting from a random initialisation is pretrained using data from a large set of speakers; at last, SA is applied to the test-time speaker.

#### 1.1. k-bit NormalFloat Quantisation

NF4 quantisation equalises the number of values in each bin by determining the quantile of the input matrices through the empirical cumulative normal distribution. Parameters in a weight matrix are normalised to fit the range of the bins by dividing the maximum absolute value of the matrix. The NF4 quantisation is grounded in the fact that the parameters of a weight matrix generally conform to a normal distribution [14]. To mitigate the effect of outliers in weight matrices on maximum absolute value normalisation, block-wise quantisation divides these matrices into blocks. Each block is quantised with its own normalisation factor, confining outliers to their respective blocks. This method enables more fine-grained quantisation by using individual normalisation factors for each block, and results in a smaller quantisation error hence leading to a better performance.

## 1.2. LoRA for Speaker Adaptation

In situations with limited speaker data, full fine-tuning can lead to over-fitting, whereas LoRA can alleviate this issue. For the pretrained ASR model with weight matrix  $\mathbf{W}_0 \in \mathbb{R}^{d \times k}$ , its update is expressed through the following equation, where  $\mathbf{B} \in \mathbb{R}^{d \times r}$  and  $\mathbf{A} \in \mathbb{R}^{r \times k}$ , with the rank  $r \ll \min(d, k)$ .

$$\mathbf{W}_0 + \Delta \mathbf{W} = \mathbf{W}_0 + \mathbf{B}\mathbf{A} \tag{1}$$

Here we propose a LoRA pretraining approach that uses the data of some existing target domain speakers to estimate common initialisation values for the LoRA weights of all test-time speakers.

#### 2. EXPERIMENTS

With full NF4 quantisation, the sizes of Whisper and Conformer models were reduced by **7.25 times** (from 277.8M to 38.3M) and **6.85 times** (130.9M to 19.1M), and their %WERs increased from 10.02 to 11.22 and 12.43 to 12.77 respectively. Table 1 shows that compared to the baseline, Whisper-LoRA-pretrain-NF4 achieved a relative WER reduction of 24.2% on LibriSpeech-SA and 12.8% on TL3-SA (TED-LIUM 3) sets, showing large improvements over Whisper-FFT-NF4. The same experiments were also performed for Conformer as in Table 2. The Conformer-LoRA-pretrain-NF4 model achieved a WER reduction of 25.3% compared to the baseline.

**Table 1**. %WERs using quantised Whisper: -baseline means w/NF4 w/o SA; -FFT is full fine-tuning; -scratch is initialising LoRA weight randomly; -pretrain is full P4Q with LoRA pretraining.

System	LibriSpeech-SA	TL3-SA
Whisper-baseline	11.22	7.71
Whisper-FFT-FP32	9.59	6.85
Whisper-FFT-NF4	10.51	7.19
Whisper-LoRA-scratch-NF4	9.67	6.95
Whisper-LoRA-pretrain-NF4	8.51	6.72

**Table 2**. %WERs of Conformer AED: -baseline means w/ NF4 w/o SA. FFT, LoRA; scratch and pretrain are the same as in Table 1.

System	Librispeech-SA
Conformer-baseline	12.77
Conformer-FFT-FP32	10.43
Conformer-FFT-NF4	11.99
Conformer-LoRA-scratch-NF4	10.25
Conformer-LoRA-pretrain-NF4	9.54

### 3. REFERENCES

- A. Radford, J. W. Kim, T. Xu, G. Brockman, C. McLeavey, and I. Sutskever, "Robust speech recognition via large-scale weak supervision," in *Proc. ICML*, 2023.
- [2] A. Gulati, J. Qin, C. Chiu, N. Parmar, Y. Zhang, J. Yu, W. Han, S. Wang, Z. Zhang, Y. Wu, et al., "Conformer: Convolutionaugmented transformer for speech recognition," in *Proc. Interspeech*, 2020.
- [3] Q. Zhang, H. Lu, H. Sak, A. Tripathi, E. McDermott, S. Koo, and S. Kumar, "Transformer transducer: A streamable speech recognition model with transformer encoders and RNN-T loss," in *Proc. ICASSP*, 2020.
- [4] S. Kriman, S. Beliaev, B. Ginsburg, J. Huang, O. Kuchaiev, V. Lavrukhin, R. Leary, J. Li, and Y. Zhang, "Quartznet: Deep automatic speech recognition with 1d time-channel separable convolutions," in *Proc. ICASSP*, 2020.
- [5] S. Han, H. Mao, and W. J. Dally, "Deep compression: Compressing deep neural networks with pruning, trained quantization and Huffman coding," *arXiv preprint arXiv:1510.00149*, 2015.
- [6] Y. Qian and X. Xiang, "Binary neural networks for speech recognition," *Frontiers of Information Technology & Electronic Engineering*, vol. 20, no. 5, pp. 701–715, 2019.
- [7] C. Leng, Z. Dou, H. Li, S. Zhu, and R. Jin, "Extremely low bit neural network: Squeeze the last bit out with ADMM," in *Proc. AAAI*, 2018.
- [8] H. D. Nguyen, A. Alexandridis, and A. Mouchtaris, "Quantization aware training with absolute-cosine regularization for automatic speech recognition," 2020.
- [9] S. Ding, P. Meadowlark, Y. He, L. Lew, S. Agrawal, and O. Rybakov, "4-bit conformer with native quantization aware training for speech recognition," *arXiv preprint arXiv:2203.15952*, 2022.
- [10] K. Zhen, H. D. Nguyen, R. Chinta, N. Susanj, A. Mouchtaris, T. Afzal, and A. Rastrow, "Sub-8-bit quantization aware training for 8-bit neural network accelerator with on-device speech recognition," arXiv preprint arXiv:2206.15408, 2022.
- [11] J. Xu, S. Hu, X. Liu, and H. Meng, "Towards green ASR: Lossless 4-bit quantization of a hybrid TDNN system on the 300-hr Switchboard corpus," arXiv preprint arXiv:2206.11643, 2022.
- [12] S. Hernandez, D. Zhao, S. Ding, A. Bruguier, R. Prabhavalkar, T. N. Sainath, Y. He, and I. McGraw, "Sharing low rank conformer weights for tiny always-on ambient speech recognition models," in *Proc. ICASSP*, 2023.
- [13] Y. Yao, Y. Li, C. Wang, T. Yu, H. Chen, X. Jiang, J. Yang, J. Huang, W. Lin, H. Shu, et al., "Int8 Winograd acceleration for conv1d equipped asr models deployed on mobile devices," *arXiv preprint arXiv:2010.14841*, 2020.
- [14] T. Dettmers, A. Pagnoni, A. Holtzman, and L. Zettlemoyer, "QLoRA: Efficient finetuning of quantized LLMs," arXiv preprint arXiv:2305.14314, 2023.
- [15] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen, "LoRA: Low-rank adaptation of large language models," arXiv preprint arXiv:2106.09685, 2021.