TaSL: Task Skill Localization and Consolidation for Language Model Continual Learning

Yujie Feng, Xu Chu, Yongxin Xu, Zexin Lu, Bo Liu, Philip S. Yu, Fellow, IEEE, Xiao-Ming Wu

Abstract-Language model continual learning (CL) has recently garnered significant interest due to its potential to adapt large language models (LLMs) to dynamic real-world environments without re-training. A key challenge in this field is catastrophic forgetting, where models lose previously acquired knowledge when learning new tasks. Existing methods commonly employ multiple parameter-efficient fine-tuning (PEFT) blocks to acquire task-specific knowledge for each task, but these approaches lack efficiency and overlook the potential for knowledge transfer through task interaction. In this paper, we present a novel CL framework for language models called Task Skill Localization and Consolidation (TaSL), which enhances knowledge transfer without relying on memory replay. TaSL first divides the model into 'skill units' based on parameter dependencies, enabling more granular control. It then employs a novel group-wise skill localization technique to identify the importance distribution of skill units for a new task. By comparing this importance distribution with those from previous tasks, we implement a fine-grained skill consolidation strategy that retains task-specific knowledge, thereby preventing forgetting, and updates task-shared knowledge, which facilitates bi-directional knowledge transfer. As a result, TaSL achieves a superior balance between retaining previous knowledge and excelling in new tasks. TaSL also shows strong generalizability, suitable for general models and customizable for PEFT methods like LoRA. Additionally, it demonstrates notable extensibility, allowing integration with memory replay to further enhance performance. Extensive experiments on two CL benchmarks, with varying model sizes (from 220M to 7B), demonstrate the effectiveness of TaSL and its variants across different settings.

Index Terms—Language model continual learning, catastrophic forgetting, skill localization.

I. INTRODUCTION

E QUIPPING large language models (LLMs) with continual learning (CL) capabilities to sequentially learn different tasks is essential for their deployment in real-world scenarios [1], [2]. This capability enables LLMs to dynamically adapt to new tasks and acquire additional knowledge [3], [4]. An effective CL system must address two critical challenges: (1) Catastrophic Forgetting (CF) [5], the phenomenon where a model's proficiency in previous tasks deteriorates as it learns new ones, and (2) Knowledge Transfer (KT) [6], enhancing task performance through the transfer of knowledge. KT can



Fig. 1. Conceptual illustration of TaSL. By identifying task-relevant areas across both previously accumulated and current tasks, we can consolidate the task-specific and task-shared parameters to facilitate efficient knowledge transfer (KT) and mitigate catastrophic forgetting (CF).

be categorized into forward transfer, which improves new task performance using knowledge from previous tasks, and backward transfer, which enhances performance on previous tasks after learning a new relevant task. Achieving a balance between retaining previous knowledge and excelling in new tasks is vital for success.

Given the considerable computational demands, recent efforts have explored CL for LLMs using parameter-efficient fine-tuning (PEFT) methods [7], [8], such as Low-Rank Adaptation (LoRA) [7]. Traditional rehearsal-based approaches, which require storing data examples from past tasks for replay, face significant privacy and memory issues [3], [9], [10].

Another prominent line of work in recent studies is the parameter isolation CL methods [11]–[14]. These methods assign a dedicated PEFT block for each new task to acquire task-specific knowledge, preserving the block for selective activation during testing. However, they exhibit significant limitations in effectively addressing the KT and CF challenges.

On one hand, the prevalent design of these frameworks, which utilizes multiple PEFT blocks, introduces redundancy and inefficiency [15]. The number of required PEFT blocks increases with each new task, leading to substantial memory storage costs and making it difficult to handle long task sequences [16], [17]. Moreover, such approaches essentially create separate expert models for each task, which limits their ability to generalize to unseen tasks [18] (*Limitation 1*).

On the other hand, these parameter-isolation CL methods do not consider interactions between tasks, which hinders KT. For instance, the method in [12] involves learning each PEFT block separately within individual tasks. Similarly, Orthogonal Low-Rank Adaptation (O-LoRA) [19] updates parameters via gradient projection in orthogonal subspaces. Although these

Yujie Feng, Zexin Lu, Bo Liu, and Xiao-Ming Wu are with the Department of Computing, The Hong Kong Polytechnic University, Hong Kong S.A.R., China. E-mail: {yujie.feng, zexin.lu, bo.liu}@connect.polyu.hk, xiaoming.wu@polyu.edu.hk

Xu Chu and Yongxin Xu are with the School of Computer Science, Peking University, Beijing, China. E-mail: chu_xu@pku.edu.cn, xuyx@stu.pku.edu.cn

Philip S. Yu is with the Department of Computer Science, University of Illinois at Chicago, USA. E-mail: psyu@uic.edu

approaches may mitigate CF to some extent, they cut off the potential transfer of knowledge stored across different PEFT blocks, thus impeding bi-directional KT among various tasks and leading to suboptimal performance (*Limitation 2*).

To address these limitations, we introduce <u>Task Skill</u> <u>L</u>ocalization and Consolidation (TaSL) [20], a novel CL framework designed to improve KT between tasks without relying on memory replay. Our approach is motivated by recent findings that model parameters contribute unevenly to performance [21]. For instance, the authors in [22] uncovered a core region on LLMs crucial for all languages, while distinct monolingual regions exist for different languages. Preserving these important regions can help avoid forgetting. The research in [15] also found that during fine-tuning with LoRA, many redundant parameter modifications are often retained, suggesting that PEFT blocks contain significant redundancies.

Based on these insights, TaSL facilitates KT by identifying and consolidating the importance distribution of model parameters across tasks. TaSL initially employs a group-wise importance-aware *skill localization* technique that utilizes gradient trajectories to identify tiny regions within the parameter space that store crucial knowledge for the current task. By comparing the importance distribution with those of previous tasks, we can then differentiate between task-specific and taskshared regions, as illustrated in Figure 1. Our innovative *skill consolidation* phase then categorically integrates weights from previous tasks with the current one, enabling effective KT while minimizing forgetting.

In detail, TaSL first reconstructs the model or PEFT block into fine-grained "*skill units*". A skill unit refers to a distinct subset of model parameters that encapsulates specific functional capabilities or knowledge relevant to a particular task, such as the Query matrix within the self-attention layer. By operating at this finer granularity, we can localize and consolidate task-specific and shared knowledge within a single PEFT block, rather than adapting a separate PEFT block for each task as in previous works (**addressing Limitation 1**).

The importance-aware skill localization method employs a new group-wise metric to compute importance scores, effectively quantifying the significance of each skill unit for the current task. Our approach, focusing on parameter space rather than dataset-driven categorization of task-specific and task-shared knowledge, offers a more effective solution to managing KT in LLMs, overcoming inaccuracies caused by dataset noise. Our skill consolidation stage, then based on a fine-grained model averaging strategy, effectively manages different types of knowledge. During this phase, we promote forward KT by initializing new tasks with previously finetuned weights. For backward KT, we merge knowledge from both current and past tasks into localized task-shared skill units, enhancing their capability. To prevent CF, we preserve the integrity of skill units containing previous task-specific knowledge, ensuring they remain unaffected by new task learning (addressing Limitation 2).

Given the widespread adoption and success of LoRA in finetuning LLMs, there is a compelling opportunity to optimize the TaSL framework specifically for LoRA. While the original TaSL framework has shown promising results, it has only been validated on a specific sub-task, and its effectiveness on general CL benchmarks has yet to be explored. Additionally, on the technical side, the skill localization process in TaSL relies on first-order gradients, which may not always provide precise importance localization. Furthermore, the skill consolidation phase in TaSL involves many hyperparameters, potentially complicating the averaging process.

To address these issues, we propose TasLoRA, a LoRAtailored version of TaSL. TasLoRA reconstructs the LoRA adapter into new skill units based on parameter dependencies, ensuring more efficient management of knowledge through sequential task learning. During the fine-tuning process, an additional orthogonal loss is added to ensure that skill units within the same LoRA adapter capture distinct latent semantic features. For skill localization, TasLoRA employs a novel second-order gradient approximate group-wise metric to compute importance scores more precisely. For skill consolidation, we transition from the previous hard-mask model averaging approach to a soft-masking strategy, using an adaptive averaging technique. This allows for a more flexible integration of task-specific and shared parameters, dynamically adjusting the contribution of each skill unit based on its importance.

Furthermore, to adapt to a broader range of application scenarios, we combine TaSL with memory replay, introducing the TaSL-M model. Through extensive experiments on two CL benchmarks with different parameter-level backbones (from 220M to 7B), our TaSL framework, along with its variants, excels in mitigating CF and showcases remarkable capabilities for KT, outperforming state-of-the-art (SOTA) methods.

The main contributions are summarized as follows:

- We propose a novel Task Skill Localization and Consolidation (TaSL) framework for language model continual learning. By identifying and consolidating task-specific and task-shared knowledge at a granular skill unit level, TaSL achieves effective knowledge transfer and mitigates catastrophic forgetting, overcoming the limitations of previous approaches.
- We develop various group-wise skill localization and finegrained skill consolidation techniques. For instance, the parameter importance metric in skill localization can be based on first-order gradients or a new second-order gradient approximation method. In skill consolidation, our model averaging strategies include a categorical hardmask approach and an adaptive soft-mask method.
- The TaSL framework demonstrates strong generalizability and extensibility. The flexible design of skill units enables TaSL to be easily tailored to PEFT methods, such as LoRA, optimizing performance for specific model architectures. Additionally, TaSL can be integrated with memory replay technique to further enhance performance and adapt to a broader range of application scenarios.
- Extensive evaluation on two CL benchmarks underscores the superiority of our TaSL framework and its variants in facilitating knowledge transfer and mitigating catastrophic forgetting, especially in memory-free scenarios. Furthermore, TaSL consistently excels across diverse model sizes (ranging from 220M to 7B), different model architectures (T5 and LLaMA-2), and unseen tasks.

II. RELATED WORK

A. Continual Learning

Continual learning [3] aims to develop learning algorithms capable of accumulating knowledge from non-stationary data.

Conventional Continual Learning methods can be divided into three categories: (i) Regularization-based methods add explicit regularization terms to preserve the knowledge of previous tasks [13], [23]. (ii) Rehearsal-based methods address catastrophic forgetting by storing old training samples [24], [25] or by training generative models to provide pseudo samples of previous tasks [26], [27]. Due to the memory and data privacy issues associated with these methods, we focus on rehearsal-free CL methods. (iii) Parameter isolation-based methods dynamically expand model capacity or assign isolated parameters dedicated to each task throughout the CL process to prevent interference between tasks [28]–[30].

Language Model Continual Learning with PEFT. Based on PEFT methods, current approaches for the continual learning of LLMs adopt the concept of parameter isolation, using a pipeline fashion to learn and select PEFT blocks for each task [12], [31], [32]. However, these approaches are limited in effectively addressing the challenges of catastrophic forgetting (CF) and knowledge transfer (KT) [33]. For instance, the authors in [19] and [34] constrain the learning of PEFT blocks to maintain orthogonality, restricting KT among different tasks. Although the recent SAPT method [16] and DAP method [35] achieves KT, it relies on pseudo sample replay or unlabeled domain corpora.

Our method achieves KT without memory replay, offering unique advantages in data privacy and parameter efficiency. By using layering low-rank adapters on the key and value projection matrices of transformer blocks, we balance retaining previous knowledge and excelling in new tasks.

B. Skill Localization

Research shows that model parameters do not all contribute equally to performance [36]. The authors in [21] introduced the concept of "skill localization" to identify critical parameters in pre-trained language models, suggesting that fine-tuning only these critical parameters can achieve results comparable to full model fine-tuning. However, their method involves additional steps to identify and retrain these key parameters during the post-fine-tuning phase, which reduces efficiency.

Inspired by techniques from the pruning community, previous studies have utilized gradient-based metrics to pinpoint important parameters during fine-tuning. Sensitivitybased scoring [37], [38] evaluates the impact on training loss, and sensitivity smoothing, as employed by [39], helps remove unnecessary parameters for more efficient fine-tuning. Nonetheless, these methods often result in element-wise pruning, where individual parameters are removed based on their importance scores. This approach can be computationally and storage-intensive, as it requires detailed management of numerous parameters throughout the model.

Building on these advancements, we propose a novel importance-aware skill localization method. This approach uniquely differentiates between task-specific and shared parameters to mitigate forgetting and achieve KT in CL.

III. PRELIMINARIES

A. Continual Learning

Continual learning [40] aims to create learning algorithms that can continuously accumulate knowledge from ongoing sequences. In supervised continual learning, a sequence of tasks $\{\mathcal{T}_1, \ldots, \mathcal{T}_K\}$ is presented in a streaming manner. Each task \mathcal{T}_k includes a distinct target dataset $\mathcal{D}_k = \{(x_i^k, y_i^k)\}_{i=1}^{N_k}$ of size N_k , where $x_i^k \in \mathcal{X}_k$ and $y_i^k \in \mathcal{Y}_k$. The model must adapt to these tasks sequentially, having access only to \mathcal{D}_k during the k-th task. Generally, with a prediction model fparameterized by Θ , continual learning aims to optimize the following objective across all tasks:

$$\max_{\Theta} \sum_{k=1}^{K} \sum_{x, y \in \mathcal{D}_k} \log p_{\Theta}(y \mid x) \tag{1}$$

The notation f_k refers to the model after training on task \mathcal{T}_k , while \hat{f}_k denotes the model after averaging for \hat{f}_{k-1} and f_k . Our TaSL framework aims to address a more challenging scenario where the model cannot access any historical data during training [19]. Nevertheless, to adapt to a wider range of application scenarios, we have also combined TaSL with memory replay. In this setting, we randomly save $|\mathcal{M}|$ samples from the training set of each previous task \mathcal{T}_i in memory \mathcal{M}_i and jointly train the model on new task data \mathcal{D}_k and memory replay to enhance performance.

B. Low-Rank Adaption

Low-Rank Adaption (LoRA) [7] is a parameter-efficient fine-tuning method to adapt LLMs to novel tasks. It assumes that the changes of parameters lie in a low-rank space when the model is fully fine-tuned on a downstream task. This approach eliminates the necessity of fine-tuning the entire model, thereby improving computational efficiency and resource utilization.

Inspired by the low-rank internal dimensionality [41], LoRA hypothesizes the updates to the weights also has a low "intrinsic rank" during adaptation. For a pre-trained weight matrix $W^{(0)} \in \mathbb{R}^{out \times in}$ that takes x as input, LoRA modifies the output h of $W^{(0)}$ with a low-rank decomposition:

$$h = W^{(0)}x + \Delta Wx = W^{(0)}x + BAx,$$
 (2)

while $B \in \mathbb{R}^{out \times r}$, $A \in \mathbb{R}^{r \times in}$, and the rank $r \ll \min(in, out)$. A is initialized from a random Gaussian distribution and B is initialized with all zeros. During the training stage, $W^{(0)}$ is fixed, and only BA is updated. Due to its superior performance, LoRA has become one of the most popular PEFT methods in NLP community.



Fig. 2. Left: Illustration of reconstructing LoRA as fine-grained skill units. Right: Overview of TaSL. Step 1: We compute the importance scores of skill units for the current task k using our importance-aware skill localization method during fine-tuning. Step 2: Based on a categorical model averaging strategy, the skill consolidation mechanism merges the model \hat{f}_{k-1} , which accumulates knowledge of all previous tasks, with the current task's model f_k . The integration is guided by the importance distributions of skill units across various tasks. This process can be repeated with the introduction of each subsequent task.

IV. PROPOSED METHOD: TASL

A. Overview

TaSL includes two key components: (i) *Skill Localization*, utilizing a group-wise importance metric to accurately identify the importance distribution of parameters across tasks, and (ii) *Skill Consolidation*, which employs a novel fine-grained model averaging strategy to integrate model weights from both current and past tasks for effective knowledge transfer.

Figure 2 provides a comprehensive overview of our proposed TaSL framework, with the following subsections detailing each component and the corresponding extensions.

B. Fine-Grained Skill Unit

Before we localize the importance of parameters, we need to define a structure that helps us better organize the knowledge stored in the model. This structure will provide a clearer understanding of how to mitigate CF and achieve KT. Therefore, we refer to the basic unit of stored skills or knowledge in the model as a "skill unit." Based on different usage scenarios, we offer the following two structures for skill units:

1) Matrix-Level Skill Unit: In this division strategy, we define skill units as individual matrices in the model, such as the query or key matrices in the self-attention layer or the A matrix in LoRA. This approach aligns with the original TaSL framework. The advantage of this division is that it is model-agnostic, making it applicable to both traditional full-parameter fine-tuning and the latest parameter-efficient fine-tuning methods, such as LoRA. This provides a higher degree of generalizability.

2) LoRA-Tailored Skill Unit: While the matrix-level division is simple and intuitive, it did not sufficiently consider the intra-matrix redundancy and inter-matrix dependencies. To address these limitations and the inefficiencies noted in recent work [19], which treats each LoRA adapter as a container for task-specific knowledge, we decompose the model matrices into new, finer-grained "skill units" based on parameter dependencies tailored for LoRA. The construction process for these LoRA-tailored skill units is as follows.

As shown in Eq (2), A and B can be viewed as a combination of a set of vectors: $A = [a_1, a_2, \dots, a_r]$, $B = [b_1, b_2, \dots, b_r]$, where $a_i \in \mathbb{R}^{in}$, $b_i \in \mathbb{R}^{out}$. Thus BA can be further disassembled as:

$$W = W^{(0)} + b_1 a_1 + b_2 a_2 + \dots + b_r a_r$$

= W⁽⁰⁾ + u_1 + u_2 + \dots + u_r, (3)

where skill unit u_i is a matrix obtained by the product of the vectors b_i, a_i . Therefore, LoRA can be viewed as a fusion of knowledge learned from multiple skill units:

$$W = W^{(0)} + \sum_{i=1}^{r} b_i a_i = W^{(0)} + \sum_{i=1}^{r} u_i$$
(4)

This division strategy effectively decomposes the parameters of a single LoRA adapter, reducing the redundancy in the traditional approach of employing separate LoRA adapters for each task [19]. To ensure that different skill units within the same layer learn distinct latent semantic features, we apply a regularization term as introduced by [39]:

$$R(A,B) = \|A^T A - I\|_F^2 + \|B^T B - I\|_F^2,$$
(5)

where I is an identity matrix, this forces A and B to be orthogonal after training.

C. Importance-aware Skill Localization

To calculate the importance of each skill unit u, we introduce a group-wise metric that also addresses the significant computational and storage burdens associated with previous parameter-level importance calculation methods [42]:

$$\mathcal{I}(u) = \frac{1}{in \times out} \sum_{i=1}^{in} \sum_{j=1}^{out} s(w_{ij})$$
(6)

where w_{ii} denotes the trainable parameters, and $in \times out$ represents the total parameter count in a skill unit u. $\mathcal{I}(u)$ measures the collective importance of all parameters within each skill unit, where higher values signify increased importance. The importance function $s(\cdot)$ for individual parameters, inspired by the pruning community [43], is quantified by measuring the impact of its removal on the loss. Specifically, to estimate the importance of W_i , we calculate the change in loss when the parameter is zeroed out using:

$$I_{W_i} = |\Delta \mathcal{L}(\mathcal{D})| = |\mathcal{L}_{W_i}(\mathcal{D}) - \mathcal{L}_{W_i=0}(\mathcal{D})|$$

= $\left|\frac{\partial \mathcal{L}(\mathcal{D})}{\partial W_i} W_i - \frac{1}{2} W_i H_{ii} W_i + \mathcal{O}(||W_i||^3)\right|$ (7)

where H is the hessian matrix, W_i represents the *i*-th parameter in W, and \mathcal{L} represents the next-token prediction loss. If removing a parameter has a significant influence, then the model is sensitive to it, and we should retain it [44]. Based on Eq. (7), we can derive the following two metrics for calculating parameter importance:

1) First-Order Gradient-Based Metric: In original TaSL framework, we followed the standard approach, defining $s(\cdot)$ as the magnitude of the gradient-weight product:

$$I_{W_i} = |W_i \nabla_{W_i} \mathcal{L}| \tag{8}$$

This metric only considers the first-order gradient term in the importance calculation. However, the importance of a parameter is also reflected in the second-order gradients (Hessian matrix). Ignoring second-order gradient information may lead to biases in localization, thus affecting model performance. Therefore, we propose the following new metric.

2) Second-Order Gradient Approximation Metric: Direct computation of the Hessian matrix for LLMs is impractical due to its $\mathcal{O}(N^2)$ complexity. To address this, we propose a second-order gradient approximation for the importance metric, which balances the efficiency of first-order methods with the precision of second-order gradients. To reduce the computational complexity, the diagonal of the Hessian H_{ii} can be approximated by the Fisher information matrix [45], and the importance can be defined as:

$$I_{W_i} \approx \left| \frac{\partial \mathcal{L}(\mathcal{D})}{\partial W_i} W_i - \frac{1}{2} \sum_{j=1}^N \left(\frac{\partial \mathcal{L}(\mathcal{D}_j)}{\partial W_i} W_i \right)^2 \right|$$
(9)

However, calculating the importance as specified in Eq. (9) across the entire training set introduces significant challenges, as model training typically only has access to mini-batch data. **Input:** Training dataset \mathcal{D}_k for task \mathcal{T}_k ; total training iterations T; hyperparameters α_1, α_2 . for t = 1, ..., T do Sample a mini-batch from \mathcal{D}_k and compute the gradient $\nabla \mathcal{L}$: Compute the sensitivity $I(w_{ij})$ via Eq. (8) or Eq. (9); Update $\bar{I}^{(t)}$ via Eq. (10) and $\bar{U}^{(t)}$ via Eq. (11); end for

Compute the importance score $\mathcal{I}(u_i^k)$ for each skill unit u_i^k by Eq. (6), for i = 1, ..., n.

Output:
$$f_k$$
 and importance scores $\mathcal{I}(\mathcal{U}_k)$ for \mathcal{U}_k .

 $\overline{\mathbf{r}}_{\mathbf{r}}(t)$ ()

This means the metric is subject to variability due to stochastic sampling and training dynamics, introducing large uncertainty in estimating sensitivity. To mitigate this, we propose a more reliably importance metric based on sensitivity smoothing and uncertainty quantification [39]:

$$\bar{I}^{(t)}(w_{ij}) = \alpha_1 \bar{I}^{(t-1)}(w_{ij}) + (1 - \alpha_1) I^{(t)}(w_{ij})$$
(10)

$$\bar{U}^{(t)}(w_{ij}) = \alpha_2 \bar{U}^{(t-1)}(w_{ij}) + (1 - \alpha_2) \left| I^{(t)}(w_{ij}) - \bar{I}^{(t)}(w_{ij}) \right|$$
(11)

where α_1 and α_2 are smoothing factors, and t is the iteration number. $\bar{I}^{(t)}$ represents smoothed sensitivity and $\bar{U}^{(t)}$ is the uncertainty term quantified by the local variation between $I^{(t)}$ and $\overline{I}^{(t)}$. Using the exponential moving average of the importance metric, we can retain and explore the trajectory gradient for a longer time, providing a more robust and precise importance assessment. Importance is then determined by:

$$g^{(t)}(w_{ij}) = \bar{I}^{(t)}(w_{ij}) \cdot \bar{U}^{(t)}(w_{ij})$$
(12)

To compute the importance score of each skill unit for current task \mathcal{T}_k , we employ Eq. (6) during fine-tuning. The model f with n skill units is denoted as $\mathcal{U} = \{u_1, \ldots, u_n\}$, with their importance scores for task \mathcal{T}_k denoted by $\mathcal{I}(\mathcal{U}_k) \in \mathbb{R}^n$. The detailed computation process is provided in Algorithm 1.

After computing importance scores for each skill unit at the current task \mathcal{T}_k , it is essential to compare these with scores from all previously learned tasks to distinguish between taskspecific and task-shared skill units. To avoid the inefficiency of storing scores for each past task, we aggregate importance scores from all prior tasks into a cumulative score for tasks up to \mathcal{T}_{k-1} . This method allows for the iterative refinement of accumulated scores without separately saving past task scores. The skill units with these cumulative scores up to \mathcal{T}_{k-1} are denoted as $\hat{\mathcal{U}}_{k-1}$, calculated using:

$$\mathcal{I}(\hat{\mathcal{U}}_{k-1}) = \beta \operatorname{Norm}(\mathcal{I}(\hat{\mathcal{U}}_{k-2})) + (1-\beta)\operatorname{Norm}(\mathcal{I}(\mathcal{U}_{k-1}))$$
(13)

where $\beta \in [0, 1]$, and Norm(·) normalizes importance scores to the [0, 1] range, thus resolving discrepancies across models. The initial scores, $\mathcal{I}(\mathcal{U}_1)$, are set to be equal to $\mathcal{I}(\mathcal{U}_1)$. Following this, the importance distribution for skill units up to task \mathcal{T}_{k-1} is combined with that of the current task, \mathcal{T}_k , to facilitate the skill consolidation process.

D. Skill Consolidation

After skill localization, the subsequent vital phase involves consolidating the knowledge in the skill unit into a unified framework. This process demands a sophisticated model averaging approach considering various factors to optimize task performance. Traditional coarse-grained model averaging assumes that all model weights are equally important for the training task [46], [47], which can be written as the following iterative computation format:

$$\hat{f}_k = \lambda \hat{f}_{k-1} + (1-\lambda) f_k \tag{14}$$

However, coarse-grained methods may overemphasize weights that are irrelevant to the current task, contaminating previously acquired task-specific knowledge and leading to forgetting. To address this issue, we introduce two fine-grained averaging strategies that focus on skill units rather than the entire model. Our approach distinguishes between task-shared and task-specific skill units, applying weighted averaging to parameters within each unit. This tailored method provides a customized solution to meet the distinct needs of each task.

1) Static Weighted Consolidation: This strategy, used in the original TaSL framework, begins by setting importance thresholds δ using quantiles to select the top 20% of skill units based on importance scores. A skill unit u_i^k is deemed important (denoted as $(u_i^k)^+$) if its score $\mathcal{I}(u_i^k)$ is above δ_k , and unimportant $((u_i^k)^-)$ otherwise.

Our static weighted consolidation strategy customizes parameter combination for each skill unit, based on its importance under different tasks, as follows:

$$\hat{u}_{i}^{k} = \begin{cases} \gamma \hat{u}_{i}^{k-1} + (1-\gamma)u_{i}^{k}, & \text{if } (\hat{u}_{i}^{k-1})^{+}, (u_{i}^{k})^{+} \\ \hat{u}_{i}^{k-1}, & \text{if } (\hat{u}_{i}^{k-1})^{+}, (u_{i}^{k})^{-} \\ u_{i}^{k}, & \text{if } (\hat{u}_{i}^{k-1})^{-}, (u_{i}^{k})^{+} \\ \frac{1}{2}(\hat{u}_{i}^{k-1} + u_{i}^{k}), & \text{if } (\hat{u}_{i}^{k-1})^{-}, (u_{i}^{k})^{-} \end{cases}$$
(15)

This approach performs the element-wise adjustment of parameters within each skill unit based on its relevance to previous and current tasks, using hyperparameter γ to control their influences.

2) Adaptive Weighted Consolidation: Building upon the original TaSL framework, we propose an Adaptive Weighted Consolidation strategy as our latest extension. In contrast to the manual setting of multiple hyperparameters required in the original method, this adaptive strategy simplifies the process by automatically adjusting to various scenarios, making the averaging process more efficient and flexible. In detail, for a specific skill unit u_i , the weighting coefficients are:

$$\hat{\lambda}_i^{k-1} = \exp\left(\mathcal{I}(\hat{u}_i^{k-1})/\tau\right), \lambda_i^k = \exp\left(\mathcal{I}(u_i^k)/\tau\right)$$
(16)

where both exp and temperature coefficient τ are scaled to the raw importance score. Then the updated model parameters are:

$$\hat{u}_i^k = \left(\frac{\hat{\lambda}_i^{k-1}}{\hat{\lambda}_i^{k-1} + \lambda_i^k}\right) \cdot \hat{u}_i^{k-1} + \left(\frac{\lambda_i^k}{\hat{\lambda}_i^{k-1} + \lambda_i^k}\right) \cdot u_i^k \quad (17)$$

By using Eq. (15) or Eq. (17) in our skill consolidation phrase, it effectively addresses the challenges in CL:

Algorithm 2 TaSL

```
Input: Dataset \mathcal{D}_k for task k = 1, ..., K; initial pre-trained model f_0; hyperparameters \alpha_1, \alpha_2, \beta, \tau.
```

```
1: # sequential tasks.
```

- 2: for task k = 1, ..., K do
- 3: # skill localization.
- 4: Get f_k and calculate U_k by Algorithm (1);
- 5: **if** k = 1 **then**
- 6: *# initialization at beginning task.*

```
7: \hat{f}_1 \leftarrow f_1, \, \hat{\mathcal{U}}_1 \leftarrow \mathcal{U}_1;
```

```
8: else
```

- 9: *# skill consolidation*.
- 10: **for** skill unit $i = 1, \ldots, n$ **do**
- 11: Calculate \hat{u}_i^k by Eq. (17);
- 12: end for
- 13: Get the averaged model \hat{f}_k based on $\hat{\mathcal{U}}_k$;
- 14: Calculate accumulated importance score $\mathcal{I}(\mathcal{U}_k)$ according to Eq. (13);

15: **end if**

- 16: **end for**
- If \$\mathcal{I}(\hat{u}_i^{k-1})\$ is high while \$\mathcal{I}(u_i^k)\$ is low, it indicates that the skill unit \$u_i\$ is more important for the history task. According to Eq. (15) or (17), we maintain the previous task-specific knowledge stored in \$\hat{u}_i^{k-1}\$ untouched to prevent the contamination of historical knowledge with task-irrelevant information in \$u_i^k\$, thereby mitigating CF.
- If $\mathcal{I}(\hat{u}_i^{k-1})$ is low and $\mathcal{I}(u_i^k)$ is high, it suggests that the skill unit u_i is more important for the current task. Since the model's training initializes from the endpoint of the previous task, the historically learned knowledge is utilized to enhance performance on the current task. So we ensure the integrity of the parameters in u_i^k , which stores current task-specific knowledge, thereby facilitating forward KT.
- If both \$\mathcal{I}(\hat{u}_i^{k-1})\$ and \$\mathcal{I}(u_i^k)\$ are high, it indicates that the skill unit \$u_i\$ is important for both the previous and current tasks. Consequently, we integrate newly acquired knowledge into this task-shared skill unit to enable backward KT.
- If both \$\mathcal{I}(\hat{u}_i^{k-1})\$ and \$\mathcal{I}(u_i^k)\$ are low, it indicates the skill unit is not significantly relevant to any task. In this case, simply averaging the parameters within this unit is sufficient.

Skill consolidation is performed before starting a new task in CL, utilizing the averaged model for subsequent task initialization. Only the importance scores of $\hat{\mathcal{U}}_{k-1}$ and \mathcal{U}_k are retained for use between tasks, starting with $\hat{\mathcal{U}}_1 = \mathcal{U}_1$ estimated from f_1 on D_1 . Detailed implementation of entire TaSL algorithm is provided in Algorithm 2.

V. TASL WITH MEMORY REPLAY: TASL-M

To adapt TaSL to scenarios where historical data can be used, we propose a memory replay-enhanced version, TaSL-M, to further improve model performance. The implementation process is shown in Figure 3.

After training on task \mathcal{T}_k using the skill localization and skill consolidation, we obtain the model \hat{f}_k . Before the next task arrives, we introduce a replay stage, where the model \hat{f}_k



Fig. 3. Overview of TaSL-M.

is fine-tuned using historical data stored in the memory buffer $\mathcal{M}_{< k}$. This process results in a new model \hat{f}_k^m , which helps recover forgotten knowledge. Specifically, during the replay stage, we do not fine-tune the parameters of all skill units using historical data, as this could negatively impact the performance on the current task. Instead, we fix the current task-specific skill units and fine-tune only the remaining parameters. This approach achieves a better balance between retaining previous knowledge and excelling in new tasks.

VI. EXPERIMENTS AND ANALYSIS

A. Experimental Setup

1) Datasets: We utilize the SuperNI Benchmark [48], a comprehensive benchmark designed to evaluate diverse NLP tasks using expert-written instructions. This benchmark facilitates thorough evaluation in more practical settings for the CL of LLMs. It includes tasks in dialogue generation, information extraction, question answering, summarization, and sentiment analysis. Following the established CL setup [16], three tasks are chosen from each type, creating a sequence of 15 tasks in total for evaluation. For each task, 1,000 instances from the dataset are randomly selected for training, and 100 instances are used for validation and testing.

Additionally, we employ the Long Sequence Benchmark [18], a continual learning benchmark consisting of 15 classification datasets. In line with [19], we randomly select 1,000 samples for training each task and reserve 500 samples per class for validation and testing. We explore two different task orders for each benchmark. Please refer to the Appendix for more details about the tasks and orders.

2) Evaluation Metrics: We denote $a_{j,i}$ as the testing performance (Accuracy for classification task and Rouge-L [51] for others) on the *i*-th test set of task right after training on *j*-th task. The performance of CL is assessed using three metrics:

$$\mathbf{AP} = \frac{1}{K} \sum_{i=1}^{K} a_{K,i} \tag{18}$$

$$\mathbf{FWT} = \frac{1}{K-1} \sum_{i=2}^{K} a_{i-1,i}$$
(19)

$$\mathbf{BWT} = \frac{1}{K-1} \sum_{i=1}^{K-1} a_{K,i} - a_{i,i}$$
(20)

Average Performance (AP) [52] calculates the average performance across all tasks after training on the final task. Forward Transfer (FWT) [53] evaluates a model's generalization ability by measuring the averaged zero-shot performance. Backward Transfer (BWT) [54] assesses the impact of new learning on previous tasks. Negative BWT indicates the model lost some previously acquired knowledge.

3) Baselines: We evaluate TaSL against the following PEFT-based continual learning baseline methods: SeqLoRA: sequentially trains the LoRA on the task orders. IncLoRA: incremental learning of new LoRA parameters on a sequential series of tasks. Replay: replays real samples from old tasks when learning new tasks to avoid forgetting. EWC [46]: finetune the model with a regularization loss that prevents updating parameters that could interfere with previously learned tasks. L2P [49]: uses the input to dynamically select and update prompts from a fixed prompt pool. LFPT5 [50]: continuously trains a soft prompt for each task with generative replay and an auxiliary loss. **Prog-Prompt** [18]: sequentially concatenates previous learned prompts to the current one during the training and testing time. **O-LoRA** [19]: learns tasks in different LoRA subspaces that are kept orthogonal to each other and sums all LoRA weights up at testing time. SAPT [16]: leverages pseudo samples and a shared attention framework to align PEFT block learning and selection.

Table II compares our TaSL with these baselines, highlighting three distinct advantages: data privacy-friendliness, model parameter-friendliness, and generalization-friendliness. To clarify the specific localization and consolidation techniques used in TaSL and its variants: *TaSL*: our base framework utilizes original components, including matrix-level skill units, first-order gradient-based metric for skill localization (Eq. 8), and static weighted consolidation (Eq. 15). *TasLoRA*: as the latest extension of TaSL, it employs LoRA-tailored skill units, the second-order gradient approximation metric for skill localization (Eq. 9), and adaptive weighted consolidation (Eq. 17). *TasL-M and TasLoRA-M*: these variants combine TaSL or TasLoRA with memory replay techniques to further enhance performance.

4) Implementation Details: We utilize two language models adopted by the previous lines of works in CL for NLP: encoder-decoder T5 model [57] and decoder-only LLaMA model [58]. In TaSL, the hyperparameters α_1 and α_2 in Eq. (10) and Eq. (11) are set to 0.85. We set β in Eq. (13) to 0.7 and τ in Eq. (16) to 0.15. Following [59], the volume of replay samples is set to 2% of the original training set for all replay-based baseline methods. For different backbones, we utilized the following hyperparameters:

• T5-base (220M), T5-large (780M), and T5-XL (3B): Training was conducted with a learning rate of 3e-4, batch size of 8, maximum input length of 512, maximum target length of 128, rank = 8, targeting modules [q, v] and 10 epochs.

TABLE I

The overall results on two continual learning benchmarks with T5-large model. All results are averaged over two different orders of each benchmark. Our rehearsal-free TaSL outperforms the previous best method, O-LoRA, by achieving an average 2.3% absolute improvement on AP, an average 2.8% absolute improvement on FWT, and an 4.8% absolute increase in BWT.

Method	Memory-Replay	Supe AP↑	erNI Benc FWT↑	hmark BWT↑	Long S AP↑	Sequence B FWT↑	enchmark BWT↑
SeqLoRA		6.43	1.58	-30.94	9.72	6.81	-73.37
IncLoRA		19.12	2.03	- 31.24	62.50	2.62	-15.34
ProgPrompt [18]		3.34	5.29	-33.18	7.98	6.63	-66.71
EWC [46]	x	17.46	4.20	-28.61	45.45	3.73	-25.93
L2P [49]		12.73	1.14	-7.95	57.98	8.36	-16.63
LFPT5 [50]		24.76	7.46	-24.41	67.01	9.48	-12.80
O-LoRA [19]		25.89	8.14	-24.59	69.24	10.15	-4.05
TaSL (ours)		26.41	11.78	-18.55	70.71	11.80	-3.27
TasLoRA (ours)		27.43	11.02	-16.91	72.29	12.89	-2.04
Replay		35.37	2.35	-15.79	75.28	3.28	-1.88
SAPT [16]	1	51.54	8.88	-0.57	82.02	9.86	-1.25
TaSL-M (ours)		52.12	11.13	-1.31	84.26	12.32	-1.08
TasLoRA-M (ours)		53.01	11.21	-0.81	84.33	11.71	-0.98

TABLE II THE COMPARISON BETWEEN TASL AND OTHER CL METHODS. SPECIFICALLY, **RF** INDICATES WHETHER THE METHOD IS REHEARSAL-FREE. **PE** INDICATES WHETHER THE METHOD IS PARAMETER EFFICIENT. **UT** INDICATES WHETHER THE METHOD CAN BE APPLIED TO SOLVE UNSEEN TASKS. **KT** INDICATES WHETHER THE METHOD ENABLES KNOWLEDGE TRANSFER.

Method	RF	PE	UT	KT
EWC [46]	\checkmark			\checkmark
OGD [55]	\checkmark		\checkmark	
LFPT5 [50]		\checkmark		\checkmark
L2P [49]	\checkmark	\checkmark		
EIP [12]	\checkmark	\checkmark		
O-LoRA [19]	\checkmark	\checkmark	\checkmark	
MoCL [56]	\checkmark		\checkmark	\checkmark
SAPT [16]		\checkmark	\checkmark	\checkmark
TaSL	\checkmark	\checkmark	\checkmark	\checkmark

• LLaMA (7B): With a learning rate of 3e-4, batch size of 128, a cutoff length of 512, and 10 epochs. Lora settings were rank = 8, alpha = 16, dropout = 0.05, targeting modules [q_proj, v_proj]. For testing, settings included temperature = 0.02, top_p = 0, top_k = 1, max new tokens = 128. Experiments are carried out using 4 NVIDIA A100.

B. Main Results

Overall CL results of different methods at the same T5-large backbone are summarized in Table I.

Firstly, TaSL and its variants demonstrate superior CL performance through effective knowledge transfer. Compared to previous rehearsal-free methods such as IncLoRA and O-LoRA, TaSL excels in addressing the two critical challenges of CF and KT, achieving the highest AP, FWT, and BWT when learning tasks sequentially.

Moreover, our enhanced version, TasLoRA, shows significant improvements over TaSL. Specifically, TasLoRA achieves average gains of 1.3% on AP and 1.4% on BWT, indicating that our extensions to each component are effective. Notably, even without relying on memory replay, our method nearly matches the performance of SAPT with memory replay on Long Sequence Benchmark, particularly in BWT, with only a slight difference of 0.8% (-2.04% vs. -1.25%).

For memory-based methods, both TaSL-M and TasLoRA outperform the best SAPT methods, further demonstrating the versatility and robustness of our framework. For the convenience of subsequent experimental analysis and comparison, we focus on the performance of TasLoRA, the best-performing memory-free version, for further evaluations.

Secondly, TasLoRA consistently demonstrates superior performance across various backbones. To further validate the effectiveness of our framework, we conducted experiments using a range of parameter-level backbones, as shown in Figure 4, which highlight performance improvements with increasing model size. Across different backbones, our method consistently outperforms traditional approaches. For example, in T5-xl, TasLoRA significantly increases the AP metric from 28.6% to 33.3%, and achieves substantial improvements in both FWT and BWT metrics, rising from 11.1% to 16.1% and improving from -20.6% to -14.0%, respectively. These results further validate the robust generalization ability of our proposed framework.

Thirdly, adaptive skill consolidation effectively mitigates catastrophic forgetting. To rigorously assess our model's effectiveness in countering forgetting, we analyzed its performance on the initial task after training on subsequent tasks using the Long Sequence Benchmark. Figure 5 shows that our TasLoRA method significantly slows the forgetting rate, with an average performance decrease of only 11% after training on the final task. In stark contrast, vanilla backbones exhibit a substantial



Fig. 4. Performance of TaSL w/ different backbones.



Fig. 5. Performance trajectory of Task 1 on Long Sequence Benchmark during the CL process.

TABLE III Results on unseen tasks based on the T5-Large backbone model. We report the average Rouge-L of the 3 tasks under each category.

Unseen Tasks					Awa	
	Dialog	IE	QA	Sum	SA	Avg.
T5-ZS	7.49	6.70	4.28	12.14	4.54	7.03
O-LoRA	4.39	9.89	25.38	8.26	50.41	19.67
LFPT5	6.96	35.32	35.00	13.26	21.51	22.41
TasLoRA	10.32	31.34	37.13	14.20	47.17	28.03

average performance drop of 20%, underscoring our method's superior ability to mitigate forgetting.

C. Performance on Unseen Tasks

Following previous work [16], we further select three tasks from each one of the above task categories to assess the TaSL's cross-task generalization ability. This is also a crucial dimension for evaluating CL algorithms. Table III shows the results. T5-ZS represents the zero-shot approaches for task adaptation, respectively. TasLoRA achieved the best performance, which can be attributed to its ability to identify task-specific and shared parameters effectively.

D. Visualization of Skill Units

We visualized the distribution of importance scores for the skill units across tasks on T5-large, as shown in Figure 6 and



(b) Results on the Long Sequence benchmark

Figure 7, leading to several critical insights:

- There is a noticeable variation in the importance of skill units for the same task, with important skill units making up only a small fraction of all trainable LoRA parameters.
- The distribution of important skill units is task-dependent, indicating both task-shared and specific parameters, confirming TaSL's validity.
- For classification tasks, such as those in the Long Sequence Benchmark (Figure 6), the skill units in the encoder, particularly the lower layers closer to the model input, play a more significant role. In contrast, for generative tasks, such as dialogue generation and summarization in the SuperNI benchmark (Figure 7), both the encoder and decoder skill units are important, with both the lower and upper layers of the network being crucial.
- Within each layer, the importance of the Query (Q) matrices in the attention mechanism consistently surpasses that of the Value (V) matrices.

E. Ablation Study

In this section, we evaluate the impact of importanceaware skill localization, fine-grained skill consolidation, and hyperparameter sensitivity, with the results discussed below.

1) Effect of the proposed importance metric in skill localization: Our method calculates importance scores using Eq. (6). As shown in Table IV, we explore alternative importance scoring approaches: (i) to test the effectiveness of using moving averages on trajectory gradients, we modify $s(\cdot)$ in Eq. (6) to include only sensitivity, as described in Eq. (9); and (ii) to assess the validity of our proposed approximate second-order gradient importance metric in Eq. (6), we use a first-order Taylor expansion to approximate the importance I by using Eq. (8). The results indicate that using moving averages for importance scoring outperforms the alternatives, with the other two variants leading to performance decreases of up to 3.3%, 2.5%, and 4.2% across the three metrics. This underscores the value of accurate skill localization in enhancing model performance.

2) Effect of Adaptive Skill Consolidation: We compared our fine-grained skill unit-level adaptive LoRA averaging mechanism against two coarse-grained strategies: (i) Weight-Ensemble, which uses a global weight to uniformly average the



Fig. 6. Visualization of importance scores for skill units across different tasks on T5-large for the Long Sequence Benchmark.



Fig. 7. Visualization of importance scores for skill units across different tasks on T5-large for the SuperNI Benchmark.

 TABLE IV

 Ablation study. Evaluating the impact of importance scoring variations on skill localization.

Method	AP	FWT	BWT
vanilla T5-large	54.10	3.32	-29.63
$s\left(\cdot\right) = I\left(\cdot\right)$	70.48	10.39	-3.81
$s\left(\cdot\right) = \left \nabla_{w_{ij}}\mathcal{L}\right $	68.82	10.80	-6.22
TasLoRA (ours)	72.29	12.89	-2.04

TABLE V Ablation study. Comparing coarse- and fine-grained model averaging methods on skill consolidation.

Method	AP	FWT	BWT
vanilla T5-large	54.10	3.32	-29.63
Weight-Ens.	63.28	7.71	-11.82
EMA	62.76	8.23	-9.80
TasLoRA (ours)	72.29	12.89	-2.04

LoRA parameters, i.e., Eq. (14), and (ii) Exponential Moving Average (EMA) [60], which applies a running average of parameters at each fine-tuning iteration.

For Table V, Weight-Ensemble significantly improves upon the vanilla model, highlighting the benefits of coarse-grained averaging for continual learning. EMA generally outperforms Weight-Ensemble but falls short of our fine-grained approach due to its overuse of averaging, with frequent parameter adjustments within the same task potentially leading to suboptimal outcomes. Our method, which averages weights only after each task, enhances computational efficiency. 3) Sensitivity Analysis for Hyperparameters: The proposed framework incorporates three key hyperparameters, including the α for computing importance scores in Eq. (10) and Eq. (11), the β for calculating cumulative importance scores in Eq. (13), and the τ for performing weighted averaging within skill units as outlined in Eq. (16). Our analysis aims to assess the impact of varying these hyperparameters on our method's performance, testing on the T5-large backbone model.

As evidenced in Table VI, we determine that the optimal setting for α is 0.55. An α value too low results in a performance decline, indicating that the calculated importance scores are not sufficiently accurate. Furthermore, as depicted

TABLE VIPERFORMANCE COMPARISONS OF TASL EQUIPPED WITH DIFFERENT α ON
LONG SEQUENCE BENCHMARK AT TASK ORDER 1.

α_1, α_2	AP	FWT	BWT
Vanilla T5-large	51.6	5.6	-29.7
0.15	71.8	13.7	-3.7
0.35	71.2	14.1	-4.3
0.55	72.8	12.6	-2.5
0.85	70.7	12.9	-3.3
0.95	71.7	14.0	-3.6

 TABLE VII

 Performance comparisons of TaSL equipped with different β on Long Sequence Benchmark at task order 1.

β	AP	FWT	BWT
Vanilla T5-large	51.6	5.6	-29.7
0.1	73.8	13.6	-3.7
0.3	73.5	12.4	-3.4
0.5	74.3	13.5	-2.2
0.7	72.7	12.9	-2.3
0.9	60.2	14.2	-5.0

in Table VII, we also find that β values within a normal range do not significantly affect performance. However, excessively high or low values for β may skew the model towards favoring either past or current task knowledge, thereby disrupting the desired balance. Nonetheless, the model's performance remains relatively stable across most conditions, indicating a low sensitivity to hyperparameter variations.

The VIII below shows the model's performance under different temperature coefficients, τ . It can be seen that setting a higher τ (higher than 0.5) smooths the weights, thereby increasing the weight of unimportant skill units, which reduces the model's effectiveness and may contaminate historical knowledge, leading to forgetting. On the other hand, setting a lower τ (less than 0.1) may cause larger differences in weight coefficients, thereby limiting KT between different tasks.

VII. CONCLUSION

In this paper, we introduce a novel Task Skill Localization and Consolidation (TaSL) framework for language model continual learning, facilitating effective knowledge transfer across tasks. Our framework leverages an importance-aware skill localization and a fine-grained skill consolidation technique to differentiate between task-specific and shared knowledge within each skill unit, thereby mitigating forgetting. TaSL also demonstrates strong generalizability and extensibility, with optimizations to various components and the ability to integrate with memory replay methods for further performance enhancement. Comprehensive experiments showcase our framework's exceptional ability to balance preserving past knowledge and excelling in new tasks, surpassing previous state-of-the-art methods.

While our method significantly improves efficiency and performance in large language model continual learning, some

TABLE VIII Performance comparisons of TaSL (using T5-large as the backbone) equipped with different τ on Long Sequence Benchmark at task order 1.

temperature coefficient τ	AP	FWT	BWT
0.05	69.0	14.3	-3.4
0.15	73.4	12.8	-2.1
0.25	72.2	13.2	-2.5
0.35	72.1	13.6	-2.1
0.45	72.7	12.5	-3.0
0.55	70.9	11.6	-4.2

limitations remain. For instance, the choice of importance thresholds after determining the importance distribution can affect the effectiveness of subsequent consolidation. Dynamically selecting thresholds based on data distribution could lead to more accurate classification of task-shared and task-specific parameters, thereby enhancing performance. Additionally, we could explore merging the skill localization and consolidation stages, allowing for parameter consolidation based on importance during model training. This would enable more flexible adaptation and address scenarios in online continual learning.

APPENDIX DATASET DETAILS

Table IX & X show details of the datasets we used for our experiments, along with their evaluation metrics. Overall, in SuperNI, we choose 3 tasks from dialogue generation (Dialog), information extraction (IE), question answering (QA), summarization (Sum) and sentiment analysis (SA), respectively.

For the Long Sequence benchmark, this includes five tasks from the standard CL benchmark (AG News, Amazon reviews, Yelp reviews, DBpedia and Yahoo Answers), four from GLUE benchmark (MNLI, QQP, RTE, SST2), five from SuperGLUE benchmark (WiC, CB, COPA, MultiRC, BoolQ), and the IMDB movie reviews dataset. We report 4 different task orders used for our experiments in Table XI.

REFERENCES

- [1] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell *et al.*, "Language models are few-shot learners," *Advances in neural information processing systems*, vol. 33, pp. 1877–1901, 2020.
- [2] T. Wu, L. Luo, Y.-F. Li, S. Pan, T.-T. Vu, and G. Haffari, "Continual learning for large language models: A survey," arXiv preprint arXiv:2402.01364, 2024.
- [3] L. Wang, X. Zhang, H. Su, and J. Zhu, "A comprehensive survey of continual learning: Theory, method and application," *IEEE Transactions* on Pattern Analysis and Machine Intelligence, 2024.
- [4] D.-W. Zhou, H.-L. Sun, J. Ning, H.-J. Ye, and D.-C. Zhan, "Continual learning with pre-trained models: A survey," arXiv preprint arXiv:2401.16386, 2024.
- [5] M. McCloskey and N. J. Cohen, "Catastrophic interference in connectionist networks: The sequential learning problem," in *Psychology of learning and motivation*. Elsevier, 1989, vol. 24, pp. 109–165.
- [6] Z. Ke, B. Liu, N. Ma, H. Xu, and L. Shu, "Achieving forgetting prevention and knowledge transfer in continual learning," *Advances in Neural Information Processing Systems*, vol. 34, pp. 22443–22456, 2021.
- [7] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen, "Lora: Low-rank adaptation of large language models," *arXiv preprint arXiv:2106.09685*, 2021.

 TABLE IX

 The details of 15 datasets in the SuperNI Benchmark [48].

Dataset name	Task	Metric
1. task639_multi_woz_user_utterance_generation	dialogue generation	Rouge-L
2. task1590_diplomacy_text_generation	dialogue generation	Rouge-L
task1729_personachat_generate_next	dialogue generation	Rouge-L
4. task181_outcome_extraction	information extraction	Rouge-L
5. task748_glucose_reverse_cause_event_detection	information extraction	Rouge-L
6. task1510_evalution_relation_extraction	information extraction	Rouge-L
7. task002_quoref_answer_generation	question answering	Rouge-L
8. task073_commonsenseqa_answer_generation	question answering	Rouge-L
9. task591_sciq_answer_generation	question answering	Rouge-L
task511_reddit_tifu_long_text_summarization	summarization	Rouge-L
11. task1290_xsum_summarization	summarization	Rouge-L
12. task1572_samsum_summary	summarization	Rouge-L
task363_sst2_polarity_classification	sentiment analysis	accuracy
14. task875_emotion_classification	sentiment analysis	accuracy
15. task1687_sentiment140_classification	sentiment analysis	accuracy

 TABLE X

 The details of 15 classification datasets in the Long Sequence Benchmark [18]. First five tasks correspond to the standard CL benchmark [61].

Dataset name	Category	Task	Domain	Metric
1. Yelp	CL Benchmark	sentiment analysis	Yelp reviews	accuracy
2. Amazon	CL Benchmark	sentiment analysis	Amazon reviews	accuracy
3. DBpedia	CL Benchmark	topic classification	Wikipedia	accuracy
4. Yahoo	CL Benchmark	topic classification	Yahoo Q&A	accuracy
5. AG News	CL Benchmark	topic classification	news	accuracy
6. MNLI	GLUE	natural language inference	various	accuracy
7. QQP	GLUE	paragraph detection	Quora	accuracy
8. RTE	GLUE	natural language inference	news, Wikipedia	accuracy
9. SST-2	GLUE	sentiment analysis	movie reviews	accuracy
10. WiC	SuperGLUE	word sense disambiguation	lexical databases	accuracy
11. CB	SuperGLUE	natural language inference	various	accuracy
12. COPA	SuperGLUE	question and answering	blogs, encyclopedia	accuracy
13. BoolQA	SuperGLUE	boolean question and answering	Wikipedia	accuracy
14. MultiRC	SuperGLUE	question and answering	various	accuracy
15. IMDB	SuperGLUE	sentiment analysis	movie reviews	accuracy

 TABLE XI

 Four different orders of task sequences used for our experiments. Orders 1-2 correspond to the SuperNI benchmark. Orders 3-4

 Are long-sequence orders following [18].

Order	Model	Task Sequence
1	T5, LLaMA-2	$\begin{array}{l} task1572 \rightarrow task363 \rightarrow task1290 \rightarrow task181 \rightarrow task002 \rightarrow \\ task1510 \rightarrow task639 \rightarrow task1729 \rightarrow task073 \rightarrow task1590 \rightarrow \\ task748 \rightarrow task511 \rightarrow task591 \rightarrow task1687 \rightarrow task875 \\ task748 \rightarrow task073 \rightarrow task1590 \rightarrow task639 \rightarrow task1572 \rightarrow \end{array}$
2	T5, LLaMA-2	$task1687 \rightarrow task591 \rightarrow task363 \rightarrow task1510 \rightarrow task1729 \rightarrow task181 \rightarrow task511 \rightarrow task002 \rightarrow task1290 \rightarrow task875$
3	T5, LLaMA-2	$\begin{array}{l} mnli \rightarrow cb \rightarrow wic \rightarrow copa \rightarrow qqp \rightarrow boolqa \rightarrow rte \rightarrow imdb \rightarrow \\ yelp \rightarrow amazon \rightarrow sst-2 \rightarrow dbpedia \rightarrow ag \rightarrow multirc \rightarrow yahoo \end{array}$
4	T5, LLaMA-2	$\begin{array}{l} yelp \rightarrow amazon \rightarrow mnli \rightarrow cb \rightarrow copa \rightarrow qqp \rightarrow rte \rightarrow imdb \rightarrow \\ sst-2 \rightarrow dbpedia \rightarrow ag \rightarrow yahoo \rightarrow multirc \rightarrow boolqa \rightarrow wic \end{array}$

- [8] N. Ding, Y. Qin, G. Yang, F. Wei, Z. Yang, Y. Su, S. Hu, Y. Chen, C.-M. Chan, W. Chen *et al.*, "Delta tuning: A comprehensive study of parameter efficient methods for pre-trained language models," *arXiv* preprint arXiv:2203.06904, 2022.
- [9] S.-A. Rebuffi, A. Kolesnikov, G. Sperl, and C. H. Lampert, "icarl: Incremental classifier and representation learning," in *Proceedings of the IEEE conference on Computer Vision and Pattern Recognition*, 2017, pp. 2001–2010.
- [10] M. Boschini, L. Bonicelli, P. Buzzega, A. Porrello, and S. Calderara, "Class-incremental continual learning into the extended der-verse," *IEEE transactions on pattern analysis and machine intelligence*, vol. 45, no. 5, pp. 5497–5512, 2022.
- [11] A. A. Rusu, N. C. Rabinowitz, G. Desjardins, H. Soyer, J. Kirkpatrick, K. Kavukcuoglu, R. Pascanu, and R. Hadsell, "Progressive neural networks," *arXiv preprint arXiv:1606.04671*, 2016.
- [12] Z. Wang, Y. Liu, T. Ji, X. Wang, Y. Wu, C. Jiang, Y. Chao, Z. Han, L. Wang, X. Shao *et al.*, "Rehearsal-free continual language learning via efficient parameter isolation," in *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2023, pp. 10933–10946.
- [13] K. Książek and P. Spurek, "Hypermask: Adaptive hypernetwork-based masks for continual learning," arXiv preprint arXiv:2310.00113, 2023.
- [14] Z. Wang, Y. Li, L. Shen, and H. Huang, "A unified and general framework for continual learning," arXiv preprint arXiv:2403.13249, 2024.
- [15] D. Zhu, Z. Sun, Z. Li, T. Shen, K. Yan, S. Ding, K. Kuang, and C. Wu, "Model tailor: Mitigating catastrophic forgetting in multi-modal large language models," *arXiv preprint arXiv:2402.12048*, 2024.
- [16] W. Zhao, S. Wang, Y. Hu, Y. Zhao *et al.*, "Sapt: A shared attention framework for parameter-efficient continual learning of large language models," *arXiv preprint arXiv:2401.08295*, 2024.
- [17] Y.-S. Liang and W.-J. Li, "Inflora: Interference-free low-rank adaptation for continual learning," arXiv preprint arXiv:2404.00228, 2024.
- [18] A. Razdai, Y. Mao, R. Hou, M. Khabsa, M. Lewis, and A. Almahairi, "Progressive prompts: Continual learning for language models," in *The Eleventh International Conference on Learning Representations*, 2022.
- [19] X. Wang, T. Chen, Q. Ge, H. Xia, R. Bao, R. Zheng, Q. Zhang, T. Gui, and X. Huang, "Orthogonal subspace learning for language model continual learning," *arXiv preprint arXiv:2310.14152*, 2023.
- [20] Y. Feng, X. Chu, Y. Xu, G. Shi, B. Liu, and X.-M. Wu, "Tasl: Continual dialog state tracking via task skill localization and consolidation," in *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2024.
- [21] A. Panigrahi, N. Saunshi, H. Zhao, and S. Arora, "Task-specific skill localization in fine-tuned language models," in *International Conference* on Machine Learning. PMLR, 2023, pp. 27011–27033.
- [22] Z. Zhang, J. Zhao, Q. Zhang, T. Gui, and X. Huang, "Unveiling linguistic regions in large language models," *arXiv preprint arXiv:2402.14700*, 2024.
- [23] D. Li and Z. Zeng, "Crnet: A fast continual learning framework with random theory," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 45, no. 9, pp. 10731–10744, 2023.
- [24] Y. Wang, Y. Liu, C. Shi, H. Li, C. Chen, H. Lu, and Y. Yang, "Inscl: A data-efficient continual learning paradigm for fine-tuning large language models with instructions," *arXiv preprint arXiv:2403.11435*, 2024.
- [25] Q. Pham, C. Liu, and S. C. Hoi, "Continual learning, fast and slow," IEEE Transactions on Pattern Analysis and Machine Intelligence, 2023.
- [26] J. Huang, L. Cui, A. Wang, C. Yang, X. Liao, L. Song, J. Yao, and J. Su, "Mitigating catastrophic forgetting in large language models with self-synthesized rehearsal," *arXiv preprint arXiv:2403.01244*, 2024.
- [27] X. Li, S. Wang, J. Sun, and Z. Xu, "Variational data-free knowledge distillation for continual learning," *IEEE Transactions on Pattern Analysis* and Machine Intelligence, vol. 45, no. 10, pp. 12618–12634, 2023.
- [28] Y. Zhang, X. Wang, and D. Yang, "Continual sequence generation with adaptive compositional modules," arXiv preprint arXiv:2203.10652, 2022.
- [29] G. Rypeść, S. Cygert, V. Khan, T. Trzciński, B. Zieliński, and B. Twardowski, "Divide and not forget: Ensemble of selectively trained experts in continual learning," *arXiv preprint arXiv:2401.10191*, 2024.
- [30] J. Xu, J. Ma, X. Gao, and Z. Zhu, "Adaptive progressive continual learning," *IEEE transactions on pattern analysis and machine intelligence*, vol. 44, no. 10, pp. 6715–6728, 2021.
- [31] C. Qin, S. Joty, and C. Chen, "Lifelong sequence generation with dynamic module expansion and adaptation," arXiv preprint arXiv:2310.09886, 2023.

- [32] C. Chen, J. Song, L. Gao, and H. T. Shen, "Towards redundancy-free sub-networks in continual learning," arXiv preprint arXiv:2312.00840, 2023.
- [33] Y. Zuo, H. Yao, L. Yu, L. Zhuang, and C. Xu, "Hierarchical prompts for rehearsal-free continual learning," *arXiv preprint arXiv:2401.11544*, 2024.
- [34] J. S. Smith, L. Karlinsky, V. Gutta, P. Cascante-Bonilla, D. Kim, A. Arbelle, R. Panda, R. Feris, and Z. Kira, "Coda-prompt: Continual decomposed attention-based prompting for rehearsal-free continual learning," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023, pp. 11909–11919.
- [35] Z. Ke, Y. Shao, H. Lin, T. Konishi, G. Kim, and B. Liu, "Continual pretraining of language models," arXiv preprint arXiv:2302.03241, 2023.
- [36] P. Michel, O. Levy, and G. Neubig, "Are sixteen heads really better than one?" Advances in neural information processing systems, vol. 32, 2019.
- [37] V. Sanh, T. Wolf, and A. M. Rush, "Movement pruning: adaptive sparsity by fine-tuning," in *Proceedings of the 34th International Conference on Neural Information Processing Systems*, 2020, pp. 20378–20389.
- [38] Q. Zhang, S. Zuo, C. Liang, A. Bukharin, P. He, W. Chen, and T. Zhao, "Platon: Pruning large transformer models with upper confidence bound of weight importance," in *International Conference on Machine Learning.* PMLR, 2022, pp. 26 809–26 823.
- [39] Q. Zhang, M. Chen, A. Bukharin, P. He, Y. Cheng, W. Chen, and T. Zhao, "Adaptive budget allocation for parameter-efficient fine-tuning," in *International Conference on Learning Representations*. Openreview, 2023.
- [40] M. De Lange, R. Aljundi, M. Masana, S. Parisot, X. Jia, A. Leonardis, G. Slabaugh, and T. Tuytelaars, "A continual learning survey: Defying forgetting in classification tasks," *IEEE transactions on pattern analysis* and machine intelligence, vol. 44, no. 7, pp. 3366–3385, 2021.
- [41] A. Aghajanyan, L. Zettlemoyer, and S. Gupta, "Intrinsic dimensionality explains the effectiveness of language model fine-tuning," arXiv preprint arXiv:2012.13255, 2020.
- [42] T. Konishi, M. Kurokawa, C. Ono, Z. Ke, G. Kim, and B. Liu, "Parameter-Level Soft-Masking for Continual Learning," in *Proc. of ICML*, 2023.
- [43] Y. LeCun, J. Denker, and S. Solla, "Optimal brain damage," Advances in neural information processing systems, vol. 2, 1989.
- [44] C. Liang, S. Zuo, M. Chen, H. Jiang, X. Liu, P. He, T. Zhao, and W. Chen, "Super tickets in pre-trained language models: From model compression to improving generalization," in *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing* (Volume 1: Long Papers), 2021, pp. 6524–6538.
- [45] J. J. Rissanen, "Fisher information and stochastic complexity," *IEEE transactions on information theory*, vol. 42, no. 1, pp. 40–47, 1996.
- [46] J. Kirkpatrick, R. Pascanu, N. Rabinowitz, J. Veness, G. Desjardins, A. A. Rusu, K. Milan, J. Quan, T. Ramalho, A. Grabska-Barwinska et al., "Overcoming catastrophic forgetting in neural networks," *Proceedings of the national academy of sciences*, vol. 114, no. 13, pp. 3521–3526, 2017.
- [47] I. Eddine Marouf, S. Roy, E. Tartaglione, and S. Lathuilière, "Weighted ensemble models are strong continual learners," *arXiv e-prints*, pp. arXiv–2312, 2023.
- [48] Y. Wang, S. Mishra, P. Alipoormolabashi, Y. Kordi, A. Mirzaei, A. Arunkumar, A. Ashok, A. S. Dhanasekaran, A. Naik, D. Stap *et al.*, "Super-naturalinstructions: Generalization via declarative instructions on 1600+ nlp tasks," *arXiv preprint arXiv:2204.07705*, 2022.
- [49] Z. Wang, Z. Zhang, C.-Y. Lee, H. Zhang, R. Sun, X. Ren, G. Su, V. Perot, J. Dy, and T. Pfister, "Learning to prompt for continual learning," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022, pp. 139–149.
- [50] C. Qin and S. Joty, "Lfpt5: A unified framework for lifelong fewshot language learning based on prompt tuning of t5," arXiv preprint arXiv:2110.07298, 2021.
- [51] C.-Y. Lin, "Rouge: A package for automatic evaluation of summaries," in *Text summarization branches out*, 2004, pp. 74–81.
- [52] A. Chaudhry, P. K. Dokania, T. Ajanthan, and P. H. Torr, "Riemannian walk for incremental learning: Understanding forgetting and intransigence," in *Proceedings of the European conference on computer vision* (ECCV), 2018, pp. 532–547.
- [53] D. Lopez-Paz and M. Ranzato, "Gradient episodic memory for continual learning," Advances in neural information processing systems, vol. 30, 2017.
- [54] Z. Ke and B. Liu, "Continual learning of natural language processing tasks: A survey," arXiv preprint arXiv:2211.12701, 2022.

- [55] M. Farajtabar, N. Azizan, A. Mott, and A. Li, "Orthogonal gradient descent for continual learning," in *International Conference on Artificial Intelligence and Statistics*. PMLR, 2020, pp. 3762–3773.
- [56] M. Wang, H. Adel, L. Lange, J. Strötgen, and H. Schütze, "Rehearsalfree modular and compositional continual learning for language models," *arXiv preprint arXiv:2404.00790*, 2024.
- [57] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu, "Exploring the limits of transfer learning with a unified text-to-text transformer," *The Journal of Machine Learning Research*, vol. 21, no. 1, pp. 5485–5551, 2020.
- [58] H. Touvron, T. Lavril, G. Izacard, X. Martinet, M.-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar *et al.*, "Llama: Open and efficient foundation language models," *arXiv preprint arXiv:2302.13971*, 2023.
- [59] F.-K. Sun, C.-H. Ho, and H.-Y. Lee, "Lamol: Language modeling for lifelong language learning," arXiv preprint arXiv:1909.03329, 2019.
- [60] C. Szegedy, V. Vanhoucke, S. Ioffe, J. Shlens, and Z. Wojna, "Rethinking the inception architecture for computer vision," in *Proceedings of the IEEE conference on computer vision and pattern recognition*, 2016, pp. 2818–2826.
- [61] X. Zhang, J. Zhao, and Y. LeCun, "Character-level convolutional networks for text classification," Advances in neural information processing systems, vol. 28, 2015.