# Exploring Bias and Prediction Metrics to Characterise the Fairness of Machine Learning for Equity-Centered Public Health Decision-Making: A Narrative Review

Shaina Raza\*, Arash Shaban-Nejad<sup>†</sup>, Elham Dolatabadi<sup>‡</sup>, Hiroshi Mamiya<sup>§</sup>

Abstract—Background: The rapid advancement of Machine Learning (ML) represents novel opportunities to enhance public health research, surveillance, and decision-making. However, there is a lack of comprehensive understanding of algorithmic bias — systematic errors in predicted population health outcomes — resulting from the public health application of ML. The objective of this narrative review is to explore the types of bias generated by ML and quantitative metrics to assess these biases.

Methods : We performed search on PubMed, MEDLINE, IEEE (Institute of Electrical and Electronics Engineers), ACM (Association for Computing Machinery) Digital Library, Science Direct, and Springer Nature. We used keywords to identify studies describing types of bias and metrics to measure these in the domain of ML and public and population health published in English between 2008 and 2023, inclusive.

Results: A total of 72 articles met the inclusion criteria. Our review identified the commonly described types of bias and quantitative metrics to assess these biases from an equity perspective.

Conclusion : The review will help formalize the evaluation framework for ML on public health from an equity perspective.

Index Terms—Equity, Evaluation, Machine Learning, Fairness

#### I. INTRODUCTION

#### A. Public Health Utilities of Machine Learning

The aim of public health is to promote health and prevent disease, illness, and injury. The essential public health functions include health promotion, health surveillance, health protection, population health assessment, disease and injury prevention, and emergency preparedness and response [82]. Artificial Intelligence (AI) has demonstrated the potential to advance these key activities [82]. Its key discipline, Machine Learning (ML) led to the emergence of algorithms that incorporate ubiquitous social, environmental and population health data and generate accurate predictions for community health status, such as disease outcomes and risk factors [77], [64], [69].

1

By integrating multiple data streams, ML algorithms can provide a comprehensive understanding of public health dynamics in real time [90]. Public health applications of ML include computer vision techniques that identify urban environmental drivers of health, such as residential greenspace from a large number of street images [54]. ML has also been shown to be effective in identifying early warning signs of disease outbreaks such as COVID-19 [94], [85], forecasting disease prevalence by incorporating local environmental data [70] or social media data [26], and detecting outbreaks [7], [33], [19]. Moreover, ML enables the large-scale and automatic assessment of behavioural risk factors, such as physical activities and dietary patterns by processing the stream of data generated by wearable devices [98]. It also facilitates the population-scale understanding of public sentiment on various health topics from online social media data [105]. Finally, ML can support the development of targeted interventions tailored to the needs of specific populations [64] and help optimize the allocation of finite public health resources to those who can benefit most from interventions[64], [75].

#### B. Ethical Implications of Utilizing Machine Learning

However, the integration of ML algorithms into public health research and practice imposes ethical challenges, as it can generate disproportionately inaccurate predictions of diseases and risk factors among disadvantaged and marginalized population subgroups [64]. Such biased or "unfair" prediction can lead to inappropriate public health interventions not adapted to the needs of disadvantaged populations.

Health disparity represents disproportionately higher disease occurrences and risk factors, and lower resources to achieve health among disadvantaged populations [16]. These vulnerable and equity-deserving populations are characterized by the social determinants of health, which include race, ethnicity, income, education, disability, access to healthcare, sex, and gender [16], [88]. These key population characteristics are often called "sensitive attributes" in the field of AI fairness. Equitable public health strategies are policies and programs that reduce these gaps by targeting equity-deserving groups, including racialized minorities, low-income and low-education individuals, and females and women. Thus, equity represents

<sup>\*</sup>Shaina Raza is with the Vector Institute for Artificial Intelligence, Toronto, ON, Canada (Corresponding author, email: shaina.raza@torontomu.ca).

<sup>&</sup>lt;sup>†</sup>Arash Shaban-Nejad is with the Department of Pediatrics, University of Tennessee, Tennessee, United States (e-mail: ashabann@uthsc.edu).

<sup>&</sup>lt;sup>1</sup>Elham Dolatabadi is with the School of Health Policy & Management, York University and Vector Institute, Toronto, ON, Canada (email: edolatab@yorku.ca).

<sup>&</sup>lt;sup>§</sup>Hiroshi Mamiya is with the Department of Epidemiology, Biostatistics, and Occupational Health, McGill University, Montréal, Québec, Canada (email: hiroshi.mamiya@mail.mcgill.ca).

fair opportunities for all individuals to achieve optimum health by reducing existing health disparities.

Bias poses a significant challenge to applying ML equitably in public health, given the ML algorithm's tendency to generate inaccurate prediction for health outcomes among certain population groups [77], [89]. We note that the term "bias" has a slightly different definition in epidemiology, defined as a systematic deviation of etiologic associations from the (unobserved) true association [50]. Such bias in epidemiological investigation arises from erroneous practice in data collection and participant recruitment/retention (i.e., selection bias), measurement error (i.e., information bias) and inappropriate data analysis (e.g., collider stratification bias) [6], [36], [39], [45]. Throughout this study, we will use the former definition of bias related ML algorithms rather than epidemiological investigation, thereby focusing on the bias in prediction of population health (as opposed to bias in etiologic association).

To illustrate unfair predictions across different population subgroups due to bias, we present a scenario depicted in Figure 1. This figure shows a binary classifier (a type of ML method to predict a binary health outcome e.g., disease diagnosis) designed to assess a specific health condition at the population level, utilizing patient data that includes social determinants of health, race in this example. The algorithm's accuracy is noticeably higher for the category of white male compared to others. This discrepancy underscores the classifier's inability to equitably predict health outcomes, resulting in biases that favor certain groups at the expense of others. Such biases can often lead to serious public health issues, including delayed diagnoses and inappropriate treatments, which ultimately result in the widening of the existing disparities [79].



Fig. 1. Schematic Representation of Outcome Distribution by Race and Gender. This diagram illustrates the distribution of positive (blue and bordered) and negative (red) outcomes from an ML model for two groups, R1 and R2, representing white and black males, respectively. Notably, the classifier exhibits higher diagnostic accuracy for the condition in patients from the blue group R1 (White males) compared to the red group R2 (Black males). The dashed line represents the class boundary separating the outcomes for the two groups, visually emphasizing the disparity in accuracy between the groups.

#### C. Fairness and Equity in Machine Learning Applications

To mitigate bias, the data collection, development, evaluation, and implementation of ML should be conducted with fairness in consideration. This implies that assessing the potential impact of ML algorithms across populations at all stages of the ML lifecycle. Algorithmic fairness in AI is defined as the principle that decisions made by AI systems should not create unjust or prejudicial outcomes for certain groups based on their race, gender, or other social determinants of health (i.e., sensitive characteristics) [103].

Research has demonstrated that a lack of fairness in AI decision-making processes can exacerbate inequities in public health outcomes. Extant studies [64], [10], [99] highlight how biases in AI systems contribute to unequal healthcare experiences and results among different population groups. In public health, the term "fairness" implies a condition that ensures impartial treatment of communities and individuals and is related to equity [32], [12]. While the definition of fairness is interrelated between AI and public health, our study largely focuses on the former definition (algorithmic fairness in AI), which centers on measuring the equitable impact of ML, with the goal of preventing lower accuracies of ML algorithms among equity-deserving population subgroups [66].

*a)* Research Aim and Objective: This study aims to review and summarize the existing types of algorithmic bias that characterize unfair prediction of ML from the literature. We also explore and introduce the existing metrics to measure the bias created by of ML. The review adopts a narrative approach, which is suitable for broad topics.

Our study is unique to the existing reviews in AI fairness and medical and population science. The reviews are grouped into two broad categories. The first category of articles [21], [35], [84], [95], [2], [109], [63] mainly discusses the potential benefits and risks of using ML and AI in healthcare, with largely theoretical (mathematical) discussion to derive algorithmic fairness. The second group of literature [9], [52], [56], [58], [104], [110], [57] describes biases in healthcare data and ML algorithms, with general recommendations for incorporating an equity lens into big data research, data science, and performing fairness audits, rather than focusing on specific types of bias and fairness metrics. Some other works [27], [5], [61] discuss the challenges and opportunities in public health decision-making for policy objectives. Different from previous work, our review focuses on exploring the existing performance metrics of ML and biases that are directly relevant to measuring equity in population health.

#### II. METHODS

In this work, we aim to address the question: "Which types of biases are prevalent in public health-related ML algorithms, and what quantitative fairness metrics can be used to identify and quantify these biases?" Our search consists of literature published from 2008 to 2023 to account for the limited volume of work at the intersection of these three fields: Public health, ML and equity. The flow diagram showing the process of study selection is shown in Figure 2.

#### A. Databases Used

We conducted a search across various electronic databases and digital libraries, including PubMed, MEDLINE, IEEE (Institute of Electrical and Electronics Engineers), ACM (Association for Computing Machinery) Digital Library, Science Direct, Springer Nature and Nature Portfolio, to identify



Fig. 2. Flow diagram showing the process of study selection.

studies focused on the intersection of public health equity and ML fairness, published in English and relevant to our research. Our approach spanned multiple disciplines to ensure a thorough review of quantitative fairness metrics in healthrelated ML algorithms.

#### B. Search Terms

We employed Medical Subject Headings (MeSH) and specific keywords such as:

'machine learning,' 'public health,' and 'equity,' using Boolean operators for precise refinement of search outcomes. The search syntax was structured as follows: ("Machine Learning" [MeSH] OR "machine learning" OR "deep learning" OR "neural networks" OR "artificial intelligence") AND ("Public Health"[MeSH] OR "public health" OR "health equity" OR "health disparities" OR "community health" OR "population health" ) AND ("Bias"[MeSH] OR "algorithmic bias" OR "fairness" OR "equity" OR "social determinants of health" OR "healthcare inequality" OR "predictive fairness" OR "ethical algorithms") AND ("English"[Language]).

The inclusion criteria prioritized peer-reviewed articles that assessed or discussed quantitative fairness metrics in ML algorithms within the context of public health. Exclusion criteria were applied to non-peer-reviewed literature, non-English articles, and studies not focused on fairness metrics or their applications in public health.

#### C. Article Selection Strategy

The selection involved a preliminary review of titles and abstracts, followed by a full-text assessment for eligibility. Three independent reviewers conducted this process, resolving discrepancies by consensus or a fourth reviewer's input. A standardized form ensured consistent data collection, piloted on a subset of studies for reliability. We appraised study quality



Fig. 3. Various sources and categories of biases within the public health context mapped to concepts (rounded rectangles)

using a checklist adapted from the Joanna Briggs Institute (JBI) [44] standards, assessing bias risk and methodological rigour to ascertain each study's contribution to our research question. This critical appraisal was independently executed by two reviewers, with a third resolving any differences.

#### **III. RESULTS**

#### A. Biases impacting fairness of ML algorithms

We identified types of bias that are known to lead to unfair predictions by ML algorithms and grouped them into potential sources of these biases, as listed in Figure 3 and are detailed below.

1) Data Quality and Diversity: Data quality refers to minimizing errors in measurement, such as inaccuracies in labelling and data entry. This process is highly important to ensure that the data used in ML models accurately represent health trends and outcomes [18]. Data diversity refers to include the samples from all population groups. Relevant research, such as [23], [41], [97], [51], highlight this challenge of data quality and diversity.

Insufficient data representation refers to the bias resulting from training datasets that do not adequately capture the diversity of the population. This lack of diversity in data can cause ML models to generate inaccurate predictions or decisions for underrepresented groups, exacerbating existing inequalities and compromising the ability to generalize across the entire population [23]. For example, a ML model developed for medical diagnosis might be trained mostly on data from one ethnic group. This could result in less accurate diagnoses for patients from other ethnic backgrounds.

*Historical Bias* arises when ML models are trained on historical data embedded with systematic inequalities and societal biases. Such biases can lead to unequal treatment of specific groups (based on race, gender, age and so on) [97], [51]. An example of historical bias can be found in health insurance systems. If the data used to train these systems includes biases against certain racial or ethnic groups, likely due to unequal access to healthcare or different treatment based on socio-economic status; the resulting ML models might continue to perpetuate these biases. As a result, people from these groups could be unfairly labeled as higher risk, leading to them facing higher insurance premiums or even being denied coverage, regardless of their actual health or needs.

Selection Bias arises when the dataset used to train ML models does not accurately represent the broader population or specific scenario it aims to model. This form of bias often emerges from non-random sampling methods that inadvertently leave out significant portions of the population, resulting in ML systems that may not function equitably or effectively across various groups or conditions [29], [101], [22]. An example of selection bias can be observed in facial recognition technology, where a ML model trained predominantly with images of individuals from certain racial or ethnic groups will likely exhibit enhanced performance in recognizing individuals from those groups [78].

2) Algorithmic Processing: Bias in ML predictions can occur during algorithmic processing or training. This includes biases like model specification bias, feature selection bias, and algorithmic weighting bias. These types of bias introduce systematic errors into AI systems. They affect the importance or weight assigned to different features and impact the fairness of decisions [51], [74], [65], [83], [4], [59], [73]. These biases may initially appear during data collection and preparation due to sampling bias, where data might not fully represent the target population [22]. To address this, techniques like using diverse datasets, balanced feature selection, and unbiased data labeling are encouraged (details in Additional File 1).

*Model Specification Bias* Incorrect assumptions in models refer to biases introduced due to erroneous assumptions or oversimplifications made during the design phase of ML models. These biases can result in systematic errors in data processing and decision-making, which affects the model fairness and effectiveness across various scenarios and populations [51], [74], [65]. For example, a medical imaging ML model trained mainly on data from Caucasian patients may struggle to diagnose diseases in Asian, African, or other descent patients accurately. This happens because the model incorrectly assumes that the characteristics of its training data apply to everyone. As a result, it can lead to higher misdiagnosis rates for underrepresented groups.

*Feature Selection Bias* occurs when the data features (variables) chosen to train the model do not adequately represent the problem space or when irrelevant features are included that do not contribute to the model training to make accurate predictions. This bias can skew the outcomes of AI applications, and could lead to models that are less effective or fair [83], [4]. For example, a health AI application predicting patient disease risks may face feature selection bias if it relies on broad features like age and gender while ignoring important factors like lifestyle, diet, or genetics. This can lead the model to inaccurately assess disease risks, and can results in underestimations or overestimations for certain patient groups.

Algorithmic Weighting Bias occurs when an ML model assigns disproportionate importance or "weight" to certain features or variables over others in its decision-making process. This uneven weighting can significantly impact the outcomes of algorithmic decisions, potentially leading to unfair or biased results [83], [59], [73]. For example, a ML model in patient triage systems might overly prioritize certain symptoms or demographic factors like age or gender, while not fully considering a patient's complete medical history or current symptoms. This can result in misclassifying the urgency of care, causing younger patients to be prioritized over older ones or some symptoms being undervalued, irrespective of the true medical urgency.

3) Cultural and Social Context: Biases such as cultural misconceptions and socio-economic biases highlight the challenges in designing AI systems that are culturally sensitive and equitable across different socio-economic groups [28], [80], [88], [3]. Language and communication biases further demonstrate the difficulty in creating ML models that accurately understand and process language nuances and dialects [31], [42].

*Cultural Misconceptions* in health contexts, occur when AI systems fail to understand or incorporate the cultural nuances, values, beliefs, and practices of diverse populations. This lack of cultural sensitivity can lead to inappropriate, ineffective, or even harmful health recommendations and diagnoses [28], [87]. For example, an AI telehealth platform trained primarily on white population data may struggle to accurately interpret symptoms from diverse cultural backgrounds. This could result in incorrect treatment recommendations, as the AI might miss key information when patients describe their conditions using culturally specific terms or expressions.

*Socio-economic factors* also influence health outcomes, access to care, and the effectiveness of medical treatments. AI technologies that fail to account for these variables might exacerbate existing disparities [80], [88], [3]. For example, an AI system designed to optimize patient flow in a hospital might prioritize patients based on factors like promptness of insurance approval or the ability to schedule follow-up visits.

4) Human-AI Interaction : Biases in human-AI interactions, such as automation bias, confirmation bias, and complacency errors, highlight the complex relationship between humans and AI systems. These biases highlights the need for continuous human oversight and critical assessment to ensure that decisions made with AI assistance are both accurate and fair [97], [48], [67], [76], [37].

Automation Bias highlights the risk of over-reliance on AI systems, potentially leading to the undervaluation of human expertise and oversight. This bias can emerge in any field where AI is employed, including healthcare, where it may influence decision-making processes or the interpretation of data [97], [48]. For example, if a ML model is highly accurate but still has a small margin of error, healthcare professionals might neglect to perform a thorough review or consider other diagnostic possibilities, relying only on the AI conclusion.

*Confirmation Bias* is the tendency of humans to search for, interpret, favour, and recall information in a way that confirms or supports one's prior belief system or values [67], [76]. For example, users might frame queries to AI in a way that is likely to produce confirming evidence for their beliefs or may interpret AI outputs in a way that aligns with their preconceptions, as seen in interactions with large language models such as ChatGPT or Bard.

Complacency errors refer to the phenomenon where users become overly reliant on AI systems, leading to decreased

vigilance and critical assessment [37], [48]. This issue arises when individuals trust AI outputs without sufficient skepticism, potentially overlooking errors, biases, or inappropriate conclusions generated by the AI.

5) *Feedback Loops:* Feedback loops, such as reinforcing existing biases and algorithmic amplification, highlight the risk of perpetuating and exacerbating biases through AI systems [24], [17], [40], [110].

*Reinforcement of Existing Biases* In a standard AI setup, the outcomes may be shaped by pre-existing biases, which then get integrated into the system during subsequent training phases, and are amplified in model predictions [24], [17]. For instance, if a ML model is trained on healthcare records that inadequately represent specific demographic groups, it could yield less precise or biased assessments for those populations. When such biased results are reintroduced into the training process, they amplify the original bias, initiating a loop that sustains and intensifies these biases over time.

Algorithmic Amplification refers to the phenomenon where small initial biases in AI systems are magnified over time through iterative learning processes. This occurs because the AI system learning algorithms tend to give more weight to data patterns they encounter more frequently [40], [110]. For example, a skin cancer ML model trained mostly on images of lighter-skinned patients might initially underperform on darker-skinned individuals. Over time, this bias can become more severe as the system keeps learning mainly from the data where it performs best (i.e., on the images of lighter-skinned patients).

6) Equity and Access: Issues such as the digital divide and accessibility bias highlight disparities in health outcomes and access to AI technologies. These disparities emphasize the need for equitable distribution and accessibility of AI resources across different populations to ensure fair health outcomes [93], [15], [106], [77].

*Digital Divide* refers to the gap between individuals with access to modern information and communication technology (ICT) and those without. This divide can be due to various factors, including but not limited to socio-economic status, geographical location, age, and education level [93], [15]. For example, urban hospitals use AI for early diabetes detection and personalized care, while rural areas lag, highlighting how the digital divide worsens health disparities.

Accessibility Bias in AI implies that these technologies might not be designed with the needs of individuals with disabilities in mind, which might lead to unequal access [106], [77]. For example, a voice-activated health app that does not offer text-based commands could exclude users with speech impairments and deny them the benefits of AI in monitoring health or accessing medical information.

7) Regulatory and Ethical Oversight: Regulatory and ethical oversight challenges involve ensuring that AI systems maintain transparency, accountability, and adherence to ethical standards throughout their deployment [107], [14], [34], [63].

*Transparency and Accountability* refer to making the actions in AI decision-making open and understandable. The goal is to ensure that individuals and organizations can be trusted and held responsible for their results [107], [14]. This challenge is highlighted by the difficulties patients and healthcare professionals face in understanding AI-generated diagnoses or treatment recommendations. Such challanges obstruct the broad acceptance and effective use of AI within the public health sector.

*Ethical Non-Alignment* occurs when AI decisions in healthcare diverge from ethical norms or standards, potentially leading to scenarios where an AI recommends treatment options that, while clinically valid, may disregard patient values or ethical considerations [34], [63]. For example, an AI system might suggest a less expensive treatment option with a slightly lower success rate over a more costly, but potentially more effective treatment, not considering the patient's preference for the best possible outcome despite the cost.

8) Temporal Dynamics: Temporal dynamics refer to the changes and trends over time that influence the behavior and outcomes of a system or process [86]. Temporal dynamics, like model drift and non-stationary environment effects, highlight the need for AI models to adapt continuously to evolving health profiles and emerging threats [102], [49].

*Model Drift* refers to the phenomenon where AI models become outdated due to changes in population health profiles over time. These drifts are often seen in the evolving disease patterns or emerging health trends that requires ongoing updates to maintain accuracy and relevance in healthcare predictions and treatments [102]. For example, a ML model that was initially trained to predict flu outbreaks based on historical health data. If a sudden change in flu virus strains or a new pandemic emerges, like COVID-19, the model's predictions may become less accurate over time because it's not adapted to these new conditions.

*Non-stationary Environment Effects* occur when AI systems struggle to adjust to dynamic health environments and emerging health threats that are not represented in the existing data [49]. These effects can lead to decreased effectiveness in predicting and managing health conditions, as the models fail to incorporate the latest trends, outbreaks, or changes in population health behavior.

### B. Fairness Metrics to Assess the Performance of Machine Learning

Fairness metrics are quantitative measures designed to capture and evaluate the fairness or equity of a system or decision-making process [72]. We identified accuracy metrics that facilitate the evaluation of the equitable performance of ML models. Sensitivity, analogous to recall, measures the proportion of actual positives correctly identified by the model, which is crucial for ensuring that no cases are missed in disease surveillance [68]. Specificity, akin to the true negative rate, highlights the model's ability to accurately identify those population groups without the disease [68]. The Positive Predictive Value (PPV) mirrors precision, indicating the proportion of positive test results that are truly positive, essential for assessing the model's accuracy in predicting disease presence [68]. The F1 Score, which balances the PPV (precision) and sensitivity (recall) by penalizing imbalances, is crucial for models that need to correctly identify cases while avoiding

false alarms. Finally, the overall accuracy metric reflects the model's effectiveness in both disease detection and minimizing false alarms [108]

Common Fairness Metrics for Assessing Machine Learning Model Fairness in Public Health Contexts: The key fairness metrics used to evaluate ML models in public health contexts are as follows:

• *Disparate Impact Ratio*: Disparate Impact Ratio is a quantitative measure used to identify and assess the level of disparity [30], [111]. It is calculated as the ratio of the rate at which a particular outcome occurs for a protected group to the rate at which that outcome occurs for the dominant or comparison group. A ratio of 1 indicates perfect equality; values less than 1 indicate that the outcome is less favourable for the protected group, and values greater than 1 indicate more favourable outcomes for the protected group.

*Example:* If an ML model is used to recommend mental health services and it is found that the urban population is twice as likely to be recommended for these services compared to the rural population, this could indicate a bias in how services are offered or accessed. Suppose 20% of the urban population and only 10% of the rural population receive enhanced mental health services recommendations. The Disparate Impact Ratio in this case would be  $\frac{10\%}{20\%} = 0.5$ . This ratio, being significantly less than 1, suggests a disparate impact against the rural population, highlighting a potential bias in the algorithm's decision-making process.

- *Predicted Positive Rate (PPR)*: Measures the proportion of individuals within a specific group predicted by an ML model to have a positive outcome. This metric is crucial in evaluating the performance of predictive models across different demographic groups [100]. *Example:* When deploying a predictive model to identify patients at risk for heart disease, observing a PPR disparity; such as a PPR of 40% for one ethnicity compared to a PPR of 20% for another; can indicate potential biases or a lack of model sensitivity to diverse genetic backgrounds. Such disparities in PPR might suggest that the model disproportionately predicts positive outcomes (e.g., risk of heart disease) for one ethnic group over another, potentially due to factors like training data imbalances or overlooked genetic variations.
- *False Discovery Rate (FDR)*: Evaluates the proportion of false positives among all positive predictions made by an ML model, offering insight into the model precision in identifying true positive outcomes [96]. *Example:* If the ML model designed to screen for stroke risk in patients, predicts that 100 individuals are at high risk of experiencing a stroke, but later assessments reveal that 40 of these predictions are incorrect (i.e., these individuals are not actually at high risk), the FDR for the model would be 40%. This high FDR suggests a significant level of inaccuracy in the model's positive predictions, indicating a need for improvement in its predictive capabilities or a reconsideration of the features and data used for training to better distinguish between

true and false positives [38].

- False Positive Rate (FPR): This metric quantifies the frequency with which some individuals are incorrectly classified as having an outcome predictive model [96]. Example: If a cancer screening program using an ML model is designed to detect early signs of skin cancer and the program screens 1,000 individuals and mistakenly identifies 100 as at high risk of skin cancer, when in reality only 20 of these individuals exhibit early signs of the disease, the FPR would be calculated based on the number of false positives (those incorrectly identified as at risk) out of the total number of actual negatives (those who are healthy). In this case, if among the 1,000 screened, 980 are healthy, and 100 of these are falsely identified as at risk, the FPR would be  $\frac{100}{980}\approx 0.102,$  or 10.2%. A high FPR, such as this, indicates that many individuals are wrongly subjected to the anxiety and unnecessary follow-up tests associated with a potential cancer diagnosis. This scenario expects a ML model to reduce false alarms and ensure that the screening program accurately distinguishes between healthy individuals and those with genuine disease.
- *False Omission Rate (FOR)*: This metric assesses the proportion of false negatives within all negative predictions made by a diagnostic test or predictive model [71]. *Example:* In the context of screening for tuberculosis (TB), if a health screening program tests 1,000 individuals and 900 are predicted not to have TB (negative predictions). However, among these 900 individuals, 30 actually do have TB but were incorrectly classified as not having it (false negatives). The FOR in this case is calculated as the number of false negatives divided by the total number of negative predictions, which would be  $\frac{30}{900} = 0.0333$  or 3.33%. A high FOR in such a scenario suggests that a substantial number of TB cases might go undiagnosed due to the test or model's inability to identify all positive cases among those tested accurately.
- False Negative Rate (FNR): This metric captures the proportion of positive cases that a diagnostic test or predictive model fails to identify [71]. Example: In the context of COVID-19 testing, where a testing center conducts 1,000 tests, and there are 100 true positive cases among these. If the test fails to identify 20 of these true positives, reporting them as negative, the FNR would be calculated as the number of false negatives divided by the total number of positive cases, which would be  $\frac{20}{100}$  = 0.20 or 20%. A high FNR in such a critical situation indicates that many individuals infected with COVID-19 are mistakenly informed they do not have the virus. This misdiagnosis can have severe public health implications, as these individuals, believing they are virus-free, might not take necessary precautions to isolate themselves, thereby risking the continued spread of COVID-19 to others.
- *Group Size Ratio (GSR)*: This metric ensures the proportionate representation of different demographic or characteristic groups within a dataset or study population [62]. *Example:* In a clinical trial investigating the effects

of new diabetes medication, if there are 1,000 participants are enrolled, but only 200 of these are women. The GSR for women compared to men in this study can be calculated by dividing the number of female participants by the number of male participants. If there are 800 male participants, the GSR would be  $\frac{200}{800} = 0.25$ . This low GSR indicates a significant underrepresentation of female participants, which could lead to outcomes that might not be fully representative or equally applicable across genders.

- Equality of Opportunity: This metric ensures that individuals from different demographic or socio-economic groups have equal chances of receiving favorable outcomes, irrespective of their background [91]. Example: When evaluating the allocation of elective surgeries in a hospital, Equality of Opportunity can be applied to assess whether patients with varying insurance statuses are considered equally for surgery schedules. A review of hospital data reveals that patients with private insurance are twice as likely to be approved for elective surgeries compared to those with government-provided health coverage, even when controlling for medical needs. This discrepancy violates Equality of Opportunity, as the decisions seem to be influenced by the patient's ability to pay rather than their medical necessities.
- *Equalized Odds*: This fairness metric targets the achievement of comparable error rates (both false positives and false negatives) across different demographic or characteristic groups [8]. *Example*: In diagnosing lung diseases, the diagnostic model sensitivity (true positive rate) and specificity (true negative rate) must be consistent across different patient groups, such as smokers and nonsmokers. If a lung disease diagnostic model is tested on a diverse patient group, analysis shows that the model has a higher sensitivity in detecting lung disease in smokers. This discrepancy indicates that the model does not satisfy the Equalized Odds criterion, as the error rates (specifically, the rates of false positives and false negatives) vary significantly between these two groups.
- Balanced Accuracy: This metric is designed to equalize the importance of sensitivity (the ability to correctly identify true positives) and specificity (the ability to correctly identify true negatives) in models, especially when dealing with imbalanced datasets or when the cost of different types of errors is similar [13]. Example: If a ML model demonstrates high sensitivity in detecting mental health needs in younger individuals but lacks specificity in older populations-resulting in many false positives among the older adults —the overall accuracy might appear acceptable. However, this overlooks the model's disproportionate error rates across age groups. Employing the balanced accuracy would highlight this disparity by giving equal weight to the model performance in correctly identifying both those who do and do not require interventions across all demographic groups.
- *Predictive Parity*: This metric ensures that the positive predictive value (PPV)—the probability that subjects

with a positive screening test truly have the condition—remains consistent across different demographic or characteristic groups [25]. *Example:* If a healthcare model designed to predict the likelihood of hospital readmission within 30 days of discharge, disproportionately flags elderly patients as being at a high risk of readmission compared to younger patients, despite similar health statuses and hospitalization histories, it may indicate a lack of Predictive Parity. Such a bias could lead to unnecessary stress for elderly patients and their families, increased healthcare costs, and inappropriate allocation of resources. To avoid these biased healthcare decisions, it is important to adjust the model to ensure that the likelihood of correctly predicting readmission is equally accurate across age groups.

- *Calibration*: This metric assesses how well the predicted probabilities from a model correspond to the actual outcomes, ensuring accuracy and reliability across different groups [81]. *Example:* If a surveillance system is designed to predict the risk of disease outbreaks, proper calibration means that if the model estimates a 30% risk of an influenza outbreak in several regions, then, over time, approximately 30% of those regions should indeed experience outbreaks. An analysis of the system reveals that while the predicted and observed outbreak patterns closely align in urban areas, the predictions are consistently overestimated for rural regions. This discrepancy indicates a lack of calibration, as the model's predictions do not accurately reflect the actual outcomes across different geographical areas.
- Balanced Error Rate (BER): This metric aims to achieve an equilibrium between the rates of false positives (incorrectly predicting a positive outcome when it is negative) and false negatives (failing to predict a positive outcome when it exists), thereby reducing bias in predictive modeling [92]. Example: In using predictive models for screening genetic disorders, the BER must be kept low and consistent across different ethnic groups. For instance, if a model is used to screen for a specific genetic disorder, it is found that the false positive rate is significantly higher in one ethnic group compared to others. In comparison, the false negative rate is higher in another group. Such discrepancies indicate a lack of balance in error rates, leading to potential bias against certain groups.
- Background Negative Subgroup Positive (BNSP) AUC: This metric is designed to evaluate a model's accuracy in identifying positive cases within a predominantly negative background [11]. Example: In diagnosing a rare genetic disorder that affects only a small fraction of the population, the BNSP AUC metric would measure how effectively the model can pinpoint these few positive cases amidst a vast majority of negative (non-affected) cases. Achieving a high BNSP AUC is crucial because it signifies the model's capability to accurately identify the rare positive cases without generating an excessive number of false positives.

We present a case study on diabetes readmission based on

these metrics in Additional File 1.

#### IV. DISCUSSION

This review article outlined the existing biases to describe the types of unfairness in the prediction of population health outcomes using ML algorithms. We also explored the existing quantitative metrics to identify and measure the extent of unfairness across population subgroups. Our findings will facilitate the use of these metrics to develop and evaluate of ML, thus promoting the equitable application of ML in public health. Our study also highlights biases occur at all stages of the ML lifecycle, including data processing and collection, model development, evaluation, implementation, and post-implementation.

There is a guideline for the standardized development and reporting of medical prediction algorithms called Transparent Reporting of a multivariable prediction model for Individual Prognosis or Diagnosis' (TRIPOD) [20], with a framework to evaluate and build statistical learning algorithms adapted to a clinical setting. However, it has a limited applicability to the assessment of fairness concerning ML algorithms and do not describe the specific types and sources of biases we provided. While the TRIPOD guideline adapted to ML algorithms is under development currently, our work will supplement such guideline by providing various fairness metrics adapted to the aim of each study concerning the equitable development and evaluation of ML.

*a) Limitations:* Although we performed an extensive literature search, we might not have fully captured all recent studies, given the rapid advancement in the field of AI fairness and ML. Also, we note that the metrics for prediction performance, including the fairness metrics covered in our review, assume the accurate measurement of "ground truth", to which the predicted population health status is compared. However, systematic inaccuracy in ground truth measures routinely occurs due to bias in assessors and devices, for instance, assessment of medical charts or varying quality of devices that capture medical images [115] across institutions or populations. Therefore, research efforts to increase the validity of ground truth measures is critical.

b) Future Directions: Future research directions necessitate a multifaceted approach. First, there is a pressing need to cover studies that consider both the qualitative, besides the quantitative fairness methods. This should include a broader spectrum of ethical considerations relevant to AI applications in public health. Moreover, exploring innovative methodologies to enhance the effectiveness and applicability of fairness metrics across diverse public health contexts is crucial for effectively addressing and mitigating biases. Additionally, conducting a detailed case study is essential. These studies should delve into the practical challenges and opportunities of leveraging AI to promote public health equity, particularly capturing the diversity of public health scenarios and addressing the complexities of biases in real-world data.

While we provide a comprehensive list of fairness metrics, the use of particular metrics should depend on the specific public health applications of ML algorithms. These applications include public health surveillance, outbreak control, health promotion, and resource prioritization and optimization. Ideally, recommendations and frameworks to guide the appropriate fairness metrics suited for specific public health activities should be developed. Finally, the application of the fairness metrics in real-world practice may be limited by the unavailability of the key variables characterizing equitydeserving variables, i.e., income, race, and gender, in the population data. The use of proxy measures for such critical attributes (e.g., aggregated census neighbourhood-level income) are often used but are likely to reduce the fairness of algorithms [74]; thus, increasing access to these attributes at disaggregated, i.e., person-level, is critical, which can be achieved by the participation of public health and healthcare authorities for data sharing and linkage.

#### V. CONCLUSION

This review examined fairness metrics and biases associated with the application of ML, highlighting the importance of using quantitative measures to identify and address biases effectively. The review points out the challenges of data biases and methodological limitations, stressing the need for interdisciplinary collaboration and strong ethical guidelines in ML an public health applications. The review results show ML's potential to positively transform public health while warning of the risks of adopting methods without careful ethical and societal consideration.

#### REFERENCES

- Alekh Agarwal, Miroslav Dudík, and Zhiwei Steven Wu. Fair regression: Quantitative definitions and reduction-based algorithms. In *International Conference on Machine Learning*, pages 120–129. PMLR, 2019.
- [2] Muhammad Aurangzeb Ahmad, Arpit Patel, Carly Eckert, Vikas Kumar, and Ankur Teredesai. Fairness in machine learning for healthcare. In Proceedings of the 26th ACM SIGKDD international conference on knowledge discovery & data mining, pages 3529–3530, 2020.
- [3] Johanna Ahnquist, Sarah P Wamala, and Martin Lindstrom. Social determinants of health–a question of social or economic capital? interaction effects of socioeconomic factors on health outcomes. *Social science & medicine*, 74(6):930–939, 2012.
- [4] Mehmet Fatih Akay. Support vector machines combined with feature selection for breast cancer diagnosis. *Expert systems with applications*, 36(2):3240–3247, 2009.
- [5] Sara Allin, Elias Mossialos, Walter Holland, and Martin McKee. The wanless report and decision-making in public health. *Journal of Public Health*, 27(2):133–134, 2005.
- [6] Benjamin F Arnold, Ayse Ercumen, Jade Benjamin-Chung, and John M Colford Jr. Brief report: negative controls to detect selection bias and measurement bias in epidemiologic studies. *Epidemiology (Cambridge, Mass.)*, 27(5):637, 2016.
- [7] Muhammad Asif, Muhammad Ajmal, Ghazala Ashraf, Nadeem Muhammad, Ayesha Aziz, Tayyaba Iftikhar, Junlei Wang, and Hongfang Liu. The role of biosensors in coronavirus disease-2019 outbreak. *Current Opinion in Electrochemistry*, 23:174–184, 2020.
- [8] Pranjal Awasthi, Matthäus Kleindessner, and Jamie Morgenstern. Equalized odds postprocessing under imperfect group information. In *International conference on artificial intelligence and statistics*, pages 1770–1780. PMLR, 2020.
- [9] Vahid Azimi and Mark A Zaydman. Optimizing equity: Working towards fair machine learning algorithms in laboratory medicine. *The journal of applied laboratory medicine*, 8(1):113–128, 2023.
- [10] Marion J Ball, Charlotte Weaver, and Joan Kiel. *Healthcare information management systems: Cases, strategies, and solutions.* Springer Science & Business Media, 2013.
- [11] Daniel Borkan, Lucas Dixon, Jeffrey Sorensen, Nithum Thain, and Lucy Vasserman. Nuanced metrics for measuring unintended bias with real data for text classification. In *Companion proceedings of the 2019* world wide web conference, pages 491–500, 2019.

- [12] Paula Braveman. Health disparities and health equity: concepts and measurement. Annu. Rev. Public Health, 27:167–194, 2006.
- [13] Kay Henning Brodersen, Cheng Soon Ong, Klaas Enno Stephan, and Joachim M Buhmann. The balanced accuracy and its posterior distribution. In 2010 20th international conference on pattern recognition, pages 3121–3124. IEEE, 2010.
- [14] Joy Buolamwini and Timnit Gebru. Gender shades: Intersectional accuracy disparities in commercial gender classification. In *Conference* on fairness, accountability and transparency, pages 77–91. PMLR, 2018.
- [15] Claudia M Campbell and Robert R Edwards. Ethnic differences in pain and pain management. *Pain management*, 2(3):219–230, 2012.
- [16] Olivia Carter-Pokras and Claudia Baquet. What is a "health disparity"? Public health reports, 2002.
- [17] Elizabeth N Chapman, Anna Kaatz, and Molly Carnes. Physicians and implicit bias: how doctors may unwittingly perpetuate health care disparities. *Journal of general internal medicine*, 28:1504–1510, 2013.
- [18] Hong Chen, David Hailey, Ning Wang, and Ping Yu. A review of data quality assessment methods for public health information systems. *International journal of environmental research and public health*, 11(5):5170–5207, 2014.
- [19] Giphil Cho and Hyojung Lee. Detection of covid-19 epidemic outbreak using machine learning. *Frontiers in Public Health*, 11:1252357, 2023.
- [20] Gary S Collins, Johannes B Reitsma, Douglas G Altman, and Karel GM Moons. Transparent reporting of a multivariable prediction model for individual prognosis or diagnosis (tripod): the tripod statement. *Annals* of internal medicine, 162(1):55–63, 2015.
- [21] João V Cordeiro. Digital technologies and data science as health enablers: an outline of appealing promises and compelling ethical, legal, and social challenges. *Frontiers in Medicine*, 8:647897, 2021.
- [22] Corinna Cortes, Mehryar Mohri, Michael Riley, and Afshin Rostamizadeh. Sample selection bias correction theory. In *International conference on algorithmic learning theory*, pages 38–53. Springer, 2008.
- [23] Valentijn MT de Jong, Karel GM Moons, Marinus JC Eijkemans, Richard D Riley, and Thomas PA Debray. Developing more generalizable prediction models from pooled studies and large clustered data sets. *Statistics in medicine*, 40(15):3533–3559, 2021.
- [24] Laurence Devillers, Françoise Fogelman-Soulié, and Ricardo Baeza-Yates. Ai & human values: Inequalities, biases, fairness, nudge, and feedback loops. *Reflections on Artificial Intelligence for Humanity*, pages 76–89, 2021.
- [25] William Dieterich, Christina Mendoza, and Tim Brennan. Compas risk scales: Demonstrating accuracy equity and predictive parity. *Northpointe Inc*, 7(4):1–36, 2016.
- [26] Elham Dolatabadi, Diana Moyano, Michael Bales, Sofija Spasojevic, Rohan Bhambhoria, Junaid Bhatti, Shyamolima Debnath, Nicholas Hoell, Xin Li, Celine Leng, et al. Using social media to help understand patient-reported health outcomes of post–covid-19 condition: Natural language processing approach. *Journal of Medical Internet Research*, 25:e45767, 2023.
- [27] Vadim Dukhanin, Alexandra Searle, Alice Zwerling, David W Dowdy, Holly A Taylor, and Maria W Merritt. Integrating social justice concerns into economic evaluation for healthcare and public health: A systematic review. *Social Science & Medicine*, 198:27–35, 2018.
- [28] Yogesh K Dwivedi, Laurie Hughes, Elvira Ismagilova, Gert Aarts, Crispin Coombs, Tom Crick, Yanqing Duan, Rohita Dwivedi, John Edwards, Aled Eirug, et al. Artificial intelligence (ai): Multidisciplinary perspectives on emerging challenges, opportunities, and agenda for research, practice and policy. *International Journal of Information Management*, 57:101994, 2021.
- [29] Jean Faugier and Mary Sargeant. Sampling hard to reach populations. Journal of advanced nursing, 26(4):790–797, 1997.
- [30] Michael Feldman, Sorelle A Friedler, John Moeller, Carlos Scheidegger, and Suresh Venkatasubramanian. Certifying and removing disparate impact. In proceedings of the 21th ACM SIGKDD international conference on knowledge discovery and data mining, pages 259–268, 2015.
- [31] Dhir Gala and Amgad N Makaryus. The utility of language models in cardiology: a narrative review of the benefits and concerns of chatgpt-4. *International Journal of Environmental Research and Public Health*, 20(15):6438, 2023.
- [32] Sandro Galea. Within Reason: A Liberal Public Health for an Illiberal Time. University of Chicago Press, 2023.
- [33] Yue Gao, Guang-Yao Cai, Wei Fang, Hua-Yi Li, Si-Yuan Wang, Lingxi Chen, Yang Yu, Dan Liu, Sen Xu, Peng-Fei Cui, et al. Machine learning

based early warning system enables accurate mortality risk prediction for covid-19. *Nature communications*, 11(1):5033, 2020.

- [34] Sara Gerke, Timo Minssen, and Glenn Cohen. Ethical and legal challenges of artificial intelligence-driven healthcare. In *Artificial intelligence in healthcare*, pages 295–336. Elsevier, 2020.
- [35] Stephanie S Gervasi, Irene Y Chen, Aaron Smith-McLallen, David Sontag, Ziad Obermeyer, Michael Vennera, and Ravi Chawla. The potential for bias in machine learning and opportunities for health insurers to address it: Article examines the potential for bias in machine learning and opportunities for health insurers to address it. *Health Affairs*, 41(2):212–218, 2022.
- [36] Sander Greenland and Hal Morgenstern. Ecological bias, confounding, and effect modification. *International journal of epidemiology*, 18(1):269–274, 1989.
- [37] Matthew Grissinger. Understanding human over-reliance on technology. *Pharmacy and Therapeutics*, 44(6):320, 2019.
- [38] Thomas Grote and Philipp Berens. On the ethics of algorithmic decision-making in healthcare. *Journal of medical ethics*, 46(3):205– 211, 2020.
- [39] Scott D Halpern, Robert D Truog, and Franklin G Miller. Cognitive bias and public health policy during the covid-19 pandemic. *Jama*, 324(4):337–338, 2020.
- [40] Karen Hao. This is how ai bias really happens—and why it's so hard to fix. *MIT Technology Review*, 4, 2019.
- [41] Moritz Hardt, Eric Price, and Nati Srebro. Equality of opportunity in supervised learning. Advances in neural information processing systems, 29, 2016.
- [42] Maurice Jakesch, Jeffrey T Hancock, and Mor Naaman. Human heuristics for ai-generated language are flawed. *Proceedings of the National Academy of Sciences*, 120(11):e2208839120, 2023.
- [43] Taeuk Jang, Pengyi Shi, and Xiaoqian Wang. Group-aware threshold adaptation for fair classification. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 6988–6995, 2022.
- [44] Joanna Briggs Institute. Critical appraisal checklist for systematic reviews, 2017. Accessed: 2023-03-25.
- [45] Neil F Johnson, Michael Spagat, Sean Gourley, Jukka-Pekka Onnela, and Gesine Reinert. Bias in epidemiological studies of conflict mortality. *Journal of Peace Research*, 45(5):653–663, 2008.
- [46] Faisal Kamiran and Toon Calders. Data preprocessing techniques for classification without discrimination. *Knowledge and information* systems, 33(1):1–33, 2012.
- [47] Michael Kearns, Seth Neel, Aaron Roth, and Zhiwei Steven Wu. Preventing fairness gerrymandering: Auditing and learning for subgroup fairness. In *International conference on machine learning*, pages 2564– 2572. PMLR, 2018.
- [48] Charalampia Xaroula Kerasidou, Angeliki Kerasidou, Monika Buscher, and Stephen Wilkinson. Before and beyond trust: reliance in medical ai. *Journal of medical ethics*, 48(11):852–856, 2022.
- [49] Bangul Khan, Hajira Fatima, Ayatullah Qureshi, Sanjay Kumar, Abdul Hanan, Jawad Hussain, and Saad Abdullah. Drawbacks of artificial intelligence and their potential solutions in the healthcare sector. *Biomedical Materials & Devices*, pages 1–8, 2023.
- [50] David G Kleinbaum, HAL Morgenstern, and Lawrence L Kupper. Selection bias in epidemiologic studies. *American journal of epidemiology*, 113(4):452–463, 1981.
- [51] Nima Kordzadeh and Maryam Ghasemaghaei. Algorithmic bias: review, synthesis, and future research directions. *European Journal* of Information Systems, 31(3):388–409, 2022.
- [52] Casimir A Kulikowski. Ethics in the history of medical informatics for decision-making: Early challenges to digital health goals. *Yearbook of Medical Informatics*, 31(01):317–322, 2022.
- [53] Preethi Lahoti, Alex Beutel, Jilin Chen, Kang Lee, Flavien Prost, Nithum Thain, Xuezhi Wang, and Ed Chi. Fairness without demographics through adversarially reweighted learning. Advances in neural information processing systems, 33:728–740, 2020.
- [54] Andrew Larkin, Xiang Gu, Lizhong Chen, and Perry Hystad. Predicting perceptions of the built environment using gis, satellite and street view image approaches. *Landscape and urban planning*, 216:104257, 2021.
- [55] Susan Leavy. Gender bias in artificial intelligence: The need for diversity and gender theory in machine learning. In *Proceedings of the 1st international workshop on gender equality in software engineering*, pages 14–16, 2018.
- [56] Yun C Lin, Daniel Mallia, Andrea O Clark-Sevilla, Adam Catto, Alisa Leshchenko, David M Haas, Ronald Wapner, Itsik Pe'er, Anita Raja, and Ansaf Salleb-Aouissi. Preeclampsia predictor with machine learning: A comprehensive and bias-free machine learning pipeline. *medRxiv*, pages 2022–06, 2022.

- [57] Jessica Liu, Huaming Chen, Jun Shen, and Kim-Kwang Raymond Choo. Faircompass: Operationalising fairness in machine learning. *IEEE Transactions on Artificial Intelligence*, 2024.
- [58] Jonathan Lu, Amelia Sattler, Samantha Wang, Ali Raza Khaki, Alison Callahan, Scott Fleming, Rebecca Fong, Benjamin Ehlert, Ron C Li, Lisa Shieh, et al. Considerations in the reliability and fairness audits of predictive models for advance care planning. *Frontiers in Digital Health*, 4:943768, 2022.
- [59] Valerie A Luyckx and Barry M Brenner. Birth weight, malnutrition and kidney-associated outcomes—a global concern. *Nature Reviews Nephrology*, 11(3):135–149, 2015.
- [60] Debmalya Mandal, Samuel Deng, Suman Jana, Jeannette Wing, and Daniel J Hsu. Ensuring fairness beyond the training data. Advances in neural information processing systems, 33:18445–18456, 2020.
- [61] Michael Marmot. Fair society, healthy lives : the marmot review : strategic review of health inequalities in england post-2010. 2010.
- [62] MathWorks. Explore fairness metrics for credit scoring model. https://www.mathworks.com/help/risk/ explore-fairness-metrics-for-credit-scoring-model.html, 2023. (Accessed on 03/19/2024).
- [63] Melissa D McCradden, Shalmali Joshi, Mjaye Mazwi, and James A Anderson. Ethical limitations of algorithmic fairness solutions in health care machine learning. *The Lancet Digital Health*, 2(5):e221–e223, 2020.
- [64] Vishwali Mhasawade, Yuan Zhao, and Rumi Chunara. Machine learning and algorithmic fairness in public and population health. *Nature Machine Intelligence*, 3(8):659–666, 2021.
- [65] Steffen Mickenautsch. Systematic reviews, systematic error and the acquisition of clinical knowledge. BMC medical research methodology, 10:1–7, 2010.
- [66] Shira Mitchell, Eric Potash, Solon Barocas, Alexander D'Amour, and Kristian Lum. Algorithmic fairness: Choices, assumptions, and definitions. *Annual review of statistics and its application*, 8:141–163, 2021.
- [67] Sachin Modgil, Rohit Kumar Singh, Shivam Gupta, and Denis Dennehy. A confirmation bias view on social media induced polarisation during covid-19. *Information Systems Frontiers*, pages 1–25, 2021.
- [68] Thomas F Monaghan, Syed N Rahman, Christina W Agudelo, Alan J Wein, Jason M Lazar, Karel Everaert, and Roger R Dmochowski. Foundational statistical principles in medical research: sensitivity, specificity, positive predictive value, and negative predictive value. *Medicina*, 57(5):503, 2021.
- [69] Stephen J Mooney and Vikas Pejaver. Big data in public health: terminology, machine learning, and privacy. *Annual review of public health*, 39:95–112, 2018.
- [70] Monica F Myers, DJ Rogers, J Cox, Antoine Flahault, and Simon I Hay. Forecasting disease risk for increased epidemic preparedness in public health. Advances in parasitology, 47:309–330, 2000.
- [71] Hansjörg Neth, Felix Gaisbauer, Nico Gradwohl, and Wolfgang Gaissmaier. *riskyr: Rendering Risk Literacy more Transparent*. Social Psychology and Decision Sciences, University of Konstanz, Konstanz, Germany, 2022. R package (version 0.4.0, Aug. 15, 2022).
- [72] Aileen Nielsen. Practical fairness. O'Reilly Media, 2020.
- [73] Eirini Ntoutsi, Pavlos Fafalios, Ujwal Gadiraju, Vasileios Iosifidis, Wolfgang Nejdl, Maria-Esther Vidal, Salvatore Ruggieri, Franco Turini, Symeon Papadopoulos, Emmanouil Krasanakis, et al. Bias in datadriven artificial intelligence systems—an introductory survey. Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery, 10(3):e1356, 2020.
- [74] Ziad Obermeyer, Brian Powers, Christine Vogeli, and Sendhil Mullainathan. Dissecting racial bias in an algorithm used to manage the health of populations. *Science*, 366(6464):447–453, 2019.
- [75] Muhammed Ordu, Eren Demir, Chris Tofallis, and Murat M Gunal. A novel healthcare resource allocation decision support tool: A forecasting-simulation-optimization approach. *Journal of the operational research society*, 72(3):485–500, 2021.
- [76] Margit E Oswald and Stefan Grosjean. Confirmation bias. *Cognitive illusions: A handbook on fallacies and biases in thinking, judgement and memory*, 79, 2004.
- [77] Trishan Panch, Jonathan Pearson-Stuttard, Felix Greaves, and Rifat Atun. Artificial intelligence: opportunities and risks for public health. *The Lancet Digital Health*, 1(1):e13–e14, 2019.
- [78] Ravi B Parikh, Stephanie Teeple, and Amol S Navathe. Addressing bias in artificial intelligence in health care. *Jama*, 322(24):2377–2378, 2019.
- [79] Amy Peterson, Vignetta Charles, David Yeung, and Karin Coyle. The health equity framework: a science-and justice-based model for

public health researchers and practitioners. *Health promotion practice*, 22(6):741–746, 2021.

- [80] Kate E Pickett and Richard G Wilkinson. Income inequality and health: a causal review. *Social science & medicine*, 128:316–326, 2015.
- [81] G Pleiss, M Raghavan, F Wu, J Kleinberg, and KQ Weinberger. On fairness and calibration. arxiv prepr. arXiv preprint arXiv:1709.02012, 2017.
- [82] Public Health Agency of Canada. Summary of the chief public health officer's report on the state of public health in canada 2021. https://www.canada.ca/en/public-health/corporate/publications/ chief-public-health-officer-reports-state-public-health-canada/ state-public-health-canada-2021/summary.html, 2021. Accessed on April 30, 2024.
- [83] Nicholas Pudjihartono, Tayaza Fadason, Andreas W Kempa-Liehr, and Justin M O'Sullivan. A review of feature selection methods for machine learning-based disease risk prediction. *Frontiers in Bioinformatics*, 2:927312, 2022.
- [84] Alvin Rajkomar, Michaela Hardt, Michael D Howell, Greg Corrado, and Marshall H Chin. Ensuring fairness in machine learning to advance health equity. *Annals of internal medicine*, 169(12):866–872, 2018.
- [85] Shaina Raza. Connecting fairness in machine learning with public health equity. In 2023 IEEE 11th International Conference on Healthcare Informatics (ICHI), pages 704–708. IEEE, 2023.
- [86] Shaina Raza and Chen Ding. News recommender system considering temporal dynamics and news taxonomy. In 2019 IEEE international conference on big data (big data), pages 920–929. IEEE, 2019.
- [87] Shaina Raza and Chen Ding. Improving clinical decision making with a two-stage recommender system. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 2023.
- [88] Shaina Raza, Elham Dolatabadi, Nancy Ondrusek, Laura Rosella, and Brian Schwartz. Discovering social determinants of health from case reports using natural language processing: algorithmic development and validation. *BMC Digital Health*, 1(1):35, 2023.
- [89] Shaina Raza, Parisa Osivand Pour, and Syed Raza Bashir. Fairness in machine learning meets with equity in healthcare. In *Proceedings of* the AAAI Symposium Series, volume 1, pages 149–153, 2023.
- [90] Shaina Raza, Brian Schwartz, and Laura C Rosella. Coquad: a covid-19 question answering dataset system, facilitating research, benchmarking, and practice. *BMC bioinformatics*, 23(1):1–28, 2022.
- [91] John E Roemer and Alain Trannoy. Equality of opportunity. In Handbook of income distribution, volume 2, pages 217–300. Elsevier, 2015.
- [92] Joseph P. Romano and Michael Wolf. Balanced control of generalized error rates. *The Annals of Statistics*, 38(1):598 – 633, 2010.
- [93] Sy Atezaz Saeed and Ross MacRae Masters. Disparities in health care and the digital divide. *Current psychiatry reports*, 23:1–6, 2021.
- [94] Saloni Shah, Aos Mulahuwaish, Kayhan Zrar Ghafoor, and Halgurd S Maghdid. Prediction of global spread of covid-19 pandemic: a review and research challenges. *Artificial Intelligence Review*, pages 1–22, 2022.
- [95] Laura Sikstrom, Marta M Maslej, Katrina Hui, Zoe Findlay, Daniel Z Buchman, and Sean L Hill. Conceptualising fairness: three pillars for medical algorithms and health equity. *BMJ health & care informatics*, 29(1), 2022.
- [96] John D Storey. False discovery rate. International encyclopedia of statistical science, 1:504–508, 2011.
- [97] Isabel Straw. The automation of bias in medical artificial intelligence (ai): Decoding the past to create a better future. *Artificial intelligence in medicine*, 110:101965, 2020.
- [98] Eduardo Teixeira, Hélder Fonseca, Florêncio Diniz-Sousa, Lucas Veras, Giorjines Boppre, José Oliveira, Diogo Pinto, Alberto Jorge Alves, Ana Barbosa, Romeu Mendes, et al. Wearable devices for physical activity and healthcare monitoring in elderly people: A critical review. *Geriatrics*, 6(2):38, 2021.
- [99] Nicole M Thomasian, Carsten Eickhoff, and Eli Y Adashi. Advancing health equity with artificial intelligence. *Journal of public health policy*, 42:602–611, 2021.
- [100] Robert Trevethan. Sensitivity, specificity, and predictive values: foundations, pliabilities, and pitfalls in research and practice. *Frontiers in public health*, 5:308890, 2017.
- [101] Giovanni Tripepi, Kitty J Jager, Friedo W Dekker, and Carmine Zoccali. Selection bias and information bias in clinical research. *Nephron Clinical Practice*, 115(2):c94–c99, 2010.
- [102] Daniel Vela, Andrew Sharp, Richard Zhang, Trang Nguyen, An Hoang, and Oleg S Pianykh. Temporal quality degradation in ai models. *Scientific reports*, 12(1):11654, 2022.

- [103] Sahil Verma and Julia Rubin. Fairness definitions explained. In Proceedings of the international workshop on software fairness, pages 1–7, 2018.
- [104] Paul Wesson, Yulin Hswen, Gilmer Valdes, Kristefer Stojanovski, and Margaret A Handley. Risks and opportunities to ensure equity in the application of big data research in public health. *Annual Review of Public Health*, 43:59–78, 2022.
- [105] Brianna M White, Chad Melton, Parya Zareie, Robert L Davis, Robert A Bednarczyk, and Arash Shaban-Nejad. Exploring celebrity influence on public attitude towards the covid-19 pandemic: social media shared sentiment analysis. *BMJ Health & Care Informatics*, 30(1), 2023.
- [106] Meredith Whittaker, Meryl Alper, Cynthia L Bennett, Sara Hendren, Liz Kaziunas, Mara Mills, Meredith Ringel Morris, Joy Rankin, Emily Rogers, Marcel Salas, et al. Disability, bias, and ai. AI Now Institute, 8, 2019.
- [107] Rebecca Williams, Richard Cloete, Jennifer Cobbe, Caitlin Cottrill, Peter Edwards, Milan Markovic, Iman Naja, Frances Ryan, Jatinder Singh, and Wei Pang. From transparency to accountability of intelligent systems: Moving beyond aspirations. *Data & Policy*, 4:e7, 2022.
- [108] B Woodruff, O Bornemisza, F Checchi, and E Sondorp. The use of epidemiological tools in conflict-affected populations: open-access educational resources for policy-makers. *London School of Hygiene* and Tropical Medicine, 2009.
- [109] Jie Xu, Yunyu Xiao, Wendy Hui Wang, Yue Ning, Elizabeth A Shenkman, Jiang Bian, and Fei Wang. Algorithmic fairness in computational medicine. *EBioMedicine*, 84, 2022.
- [110] Jenny Yang, Andrew AS Soltan, and David A Clifton. Algorithmic fairness and bias mitigation for clinical machine learning: A new utility for deep reinforcement learning. *medRxiv*, pages 2022–06, 2022.
- [111] Muhammad Bilal Zafar, Isabel Valera, Manuel Gomez Rodriguez, and Krishna P Gummadi. Fairness beyond disparate treatment & disparate impact: Learning classification without disparate mistreatment. In *Proceedings of the 26th international conference on world wide web*, pages 1171–1180, 2017.
- [112] Carlos Vladimiro González Zelaya. Towards explaining the effects of data preprocessing on machine learning. In 2019 IEEE 35th international conference on data engineering (ICDE), pages 2086– 2090. IEEE, 2019.
- [113] Tao Zhang, Tianqing Zhu, Jing Li, Mengde Han, Wanlei Zhou, and S Yu Philip. Fairness in semi-supervised learning: Unlabeled data help to reduce discrimination. *IEEE Transactions on Knowledge and Data Engineering*, 34(4):1763–1774, 2020.
- [114] Jieyu Zhao, Tianlu Wang, Mark Yatskar, Vicente Ordonez, and Kai-Wei Chang. Gender bias in coreference resolution: Evaluation and debiasing methods. arXiv preprint arXiv:1804.06876, 2018.
- [115] Yongshuo Zong, Yongxin Yang, and Timothy Hospedales. Medfair: benchmarking fairness for medical imaging. arXiv preprint arXiv:2210.01725, 2022.

#### APPENDIX

## A. Glossary of Terms in Public Health, Equity, Fairness, Bias, and Machine Learning

**Health**: A state of complete physical, mental, and social well-being and not merely the absence of disease or infirmity. It covers the overall condition of an individual or population, including the presence or absence of illnesses, the level of physical and mental function, and the ability to respond to various factors that affect health.

**Public Health**: Refers to the science and art of preventing disease, prolonging life, and promoting health through organized efforts and informed choices of society, organizations, public and private, communities, and individuals.

**Equity:** The absence of avoidable or remediable differences among groups of people, whether those groups are defined socially, economically, demographically, or geographically. In health care, equity refers to providing care that does not vary in quality because of personal characteristics such as gender, ethnicity, geographic location, and socio-economic status.

Machine Learning (ML): A subset of artificial intelligence that involves the development of algorithms and statistical models that enable computers or programs to perform a task without using explicit instructions, relying instead on patterns and inference derived from data.

**Fairness:** In the context of ML and decision-making systems, fairness refers to the attribute that an algorithmic decision or model does not create biased outcomes, ensuring that all individuals or groups are treated equally and justly based on the relevant criteria.

**Bias:** Refers to a systematic error or non-random distortion in results or inferences from processes. In data science and machine learning, bias can emerge due to prejudiced assumptions during the model development phase, from the data collection process, or in the algorithmic processing, leading to unfair outcomes.

Algorithmic Bias: Occurs when a computer program or algorithm reflects the implicit values of the humans who are involved in coding, collecting, selecting, or using data to train the algorithm. This can lead to skewed outputs and discriminatory practices.

**Social Determinants of Health (SDOH)**: The conditions in the environments where people are born, live, learn, work, play, worship, and age that affect a wide range of health, functioning, and quality-of-life outcomes and risks.

**Health Disparities**: A type of difference in health that is closely linked with social, economic, and/or environmental disadvantage. Health disparities adversely affect groups of people who have systematically experienced greater obstacles to health based on their racial or ethnic group; religion; socio-economic status; gender; age; mental health; cognitive, sensory, or physical disability; sexual orientation or gender identity; geographic location; or other characteristics historically linked to discrimination or exclusion.

**Predictive Analytics:** The use of data, statistical algorithms, and machine learning techniques to identify the likelihood of future outcomes based on historical data. In public health, it's used for predicting disease outbreaks, health trends, and patient outcomes.

**Informed Consent**: A process for getting permission before conducting a healthcare intervention on a person. In research, it involves informing participants about the risks, benefits, and potential outcomes of studies or data collection.

**Privacy:** In the context of data and digital tools, privacy concerns the right of individuals to control or influence what information related to them may be collected and stored and by whom and to whom that information may be disclosed.

**Data Governance:** The overall management of the availability, usability, integrity, and security of the data employed in an organization, with the objective to ensure that data is accurate, available, and accessible.

**Disparate Impact:** Refers to practices or policies that may appear neutral but result in a disproportionate impact on a protected group. It's often used to identify unintentional biases in systems or models.

**Predicted Positive Rate (PPR)**: Measures the proportion of individuals in a group predicted to have a positive outcome. It's useful for identifying bias in predictive models across different demographic groups.

**False Discovery Rate (FDR):** The proportion of false positives within all positive predictions. A high FDR indicates many incorrect positive predictions, suggesting a need for model recalibration.

False Positive Rate (FPR): Indicates how frequently healthy individuals are mistakenly identified as diseased. A high FPR can lead to unnecessary stress and testing, highlighting the need for accurate diagnostic criteria.

False Omission Rate (FOR): Assesses the rate of false negatives among negative predictions. A high FOR, especially in diagnosing infectious diseases, could lead to untreated spread within communities.

False Negative Rate (FNR): Reflects the proportion of actual positives missed by the model. A high FNR, such as in COVID-19 testing, means many infected individuals are wrongly reassured they are virus-free, posing a public health risk.

Group Size Ratio (GSR): Examines the representation ratio of different groups within the data. It's important for ensuring research outcomes are representative and equally applicable across all groups.

**Equality of Opportunity:** Ensures individuals from different groups have equal chances of receiving a favorable outcome. It's crucial in healthcare to ensure decisions are based on medical need rather than the ability to pay.

**Equalized Odds:** Aims for similar error rates across groups to ensure fairness in treatment recommendations and other decisions made by predictive models.

**Balanced Accuracy:** Balances sensitivity and specificity across groups to ensure that a model accurately identifies needs regardless of demographic factors.

**Predictive Parity:** Measures consistency in predictive outcomes across different groups, ensuring that no group is disproportionately flagged by predictive models.

**Calibration:** Evaluates the alignment of predicted probabilities with actual outcomes across groups. It's essential for maintaining the reliability of predictive models in public health and other areas.

**Balanced Error Rate (BER):** Seeks to balance false positives and negatives to prevent bias in predictive modeling, ensuring equitable outcomes across all groups.

**Background Negative Subgroup Positive (BNSP) AUC:** Focuses on model accuracy when identifying positive cases against a largely negative backdrop. It's critical in rare disease identification to avoid overwhelming false alerts.

#### B. Algorithmic Processing

Techniques such as data augmentation and synthetic data generation can improve data diversity [55], [114], [110]. Additionally, methods like re-weighting and re-sampling are critical for achieving fair representation [112], [46], [113].

The model training phase is also susceptible to bias through the selection of model architecture, hyperparameters, and loss functions.

Mitigation strategies include designing models less sensitive to biased features, using fair loss functions, and adjusting training processes to improve fairness [72], [53], [60], [47], [1]. During model calibration, ensuring accurate and fair probabilistic estimates is crucial to avoid biases impacting prediction quality and decision fairness. Approaches for addressing calibration biases involve adjusting output probabilities, equalizing decision thresholds across diverse groups, and properly calibrating model outputs [41], [43], [81].

### C. Equitable Predictions in Machine Learning: A Case Study on Diabetes Readmission

1) Task Setting and Evaluation for Fairness: This case study investigates the fairness of machine learning (ML) model predictions across various demographics—age, gender, and race—using a comprehensive diabetes dataset. Our primary focus is on evaluating the equity of these predictions in determining the risk of 30-day hospital readmissions for diabetic patients. We examine whether ML models offer equitable predictions across different demographic groups, particularly in forecasting 30-day readmissions among diabetes patients. Our objective encompasses not only assessing the accuracy of these models but also scrutinizing their fairness and potential biases to ensure that healthcare predictive analytics equitably benefit all patient groups.

Leveraging data from 130 US hospitals between 1999 and 2008, this study narrows down on 45,715 patient records from an initial pool of 101,766, after filtering out identifiers, features with substantial missing values, and records lacking race or diagnosis information. The final dataset includes 50 attributes, highlighting a class imbalance in the 30-day readmission indicator. Our analysis deploys four ML models—Multi-Layer Perceptron (MLP), Generalized Linear Model (GLM), and Naive Bayes—optimized for accuracy and fairness across demographic lines through specific hyperparameter settings.

The evaluation framework combines accuracy metrics (precision, recall, F1 score, and overall accuracy) with a thorough fairness analysis. By adopting metrics like the disparate impact ratio and predicted positive rates, among others, we aim to provide equitable predictions across all demographics. The study follows a structured evaluation flow: generating model predictions, assessing accuracy, conducting a fairness analysis for sub-groups, examining accuracy within these groups, and iteratively refining models to balance accuracy with fairness.

In a city, over the past year there is a hospital where 10,000 White patients and 5,000 Black patients sought diagnosis for a disease that requires hospitalization. The White population is assumed to be in the majority. We want to examine the privileged and underprivileged groups who get the favourable outcome (hospitalization here), regardless of their population size. The following confusion matrices represent the actual number of patients from each racial subgroup who were diagnosed with the disease and required hospitalization (positive label for 'hospitalized' and negative for 'not hospitalized').

2) *Results:* Table C2 compares three models (MLP, GLM, Naive Bayes) on metrics like Precision, Recall, F1 Score, and Accuracy. We observe that MLP performs best across all metrics. It indicates that MLP is most effective in balancing correct predictions and minimizing false positives and negatives. GLM follows closely, while Naive Bayes lags behind, possibly

#### TABLE III

COMPARATIVE ANALYSIS OF FAIRNESS METRICS BY RACE FOR MLP, GLM, AND NB MODELS. THE TABLE HIGHLIGHTS DISPARITIES IN MODEL PERFORMANCE ACROSS RACIAL GROUPS, FOCUSING ON FAIRNESS THROUGH PPGR, FPR, FNR AND FOR METRICS. BOLD FIGURES INDICATE THE MOST FAVORABLE OUTCOMES, WITH LOWER ERROR RATES (FPR, FOR, FNR) PREFERRED AND HIGHER PPGR VALUES SUGGESTING MORE EQUITABLE POSITIVE PREDICTIONS

Race	Model	PPGR	FPR	FOR	FNR
African American	MLP	0.38	0.08	0.24	0.29
	GLM	0.39	0.08	0.24	0.29
	NB	0.36	0.14	0.31	0.40
Asian	MLP	0.56	0.01	0.23	0.17
	GLM	0.41	0.05	0.27	0.29
	NB	0.36	0.04	0.48	0.46
Caucasian	MLP	0.37	0.06	0.24	0.31
	GLM	0.39	0.07	0.24	0.29
	NB	0.36	0.13	0.31	0.41
Hispanic	MLP	0.38	0.11	0.35	0.39
	GLM	0.39	0.08	0.31	0.35
	NB	0.34	0.11	0.39	0.47
Other	MLP	0.5	0.11	0.34	0.27
	GLM	0.41	0.13	0.30	0.34
	NB	0.45	0.11	0.40	0.35

TABLE I Comparison of Different Models: Multilayer Perceptron (MLP), Generalized Linear Model (GLM), Naive Bayes (NB) Performance Across Precision, Recall, F1 Score, and Accuracy Metrics.

Model	Precision	Recall	F1 Score	Accuracy 0.819
MLP	<b>0.7978</b>	<b>0.987</b>	<b>0.882</b>	
GLM	0.7929	0.928	0.855	0.8097
Naive Bayes	0.7786	0.823	0.801	0.7404

due to its assumption of feature independence. The choice of model should also consider factors like computational cost and interpretability beyond these metrics.

While the performance metrics of these models are key to measure their effectiveness, assessing their impact across various demographic groups is vital for ensuring fairness. Fairness entails that these models' predictions do not systematically advantage or disadvantage any group based on sensitive attributes like age, gender, race, or socio-economic status. Evaluating model performance with a lens on demographic equity is essential to uncovering biases that could result in unfair outcomes, thus ensuring the models operate equitably without reinforcing or worsening existing disparities. EVALUATION OF FAIRNESS METRICS (PREDICTED POSITIVE GROUP RATE (PPGR), FALSE POSITIVE RATE (FPR), FALSE OMISSION RATE (FOR), FALSE NEGATIVE RATE (FNR)) ACROSS GENDER (FEMALE AND MALE) GROUPS FOR MLP, GLM, AND NB MODELS. BOLD INDICATES THE BEST SCORE WITHIN EACH GENDER GROUP, WITH LOWER ERROR RATES (FPR, FOR, FNR) PREFERRED AND HIGHER PPGR VALUES SUGGESTING MORE EQUITABLE POSITIVE PREDICTIONS.

Gender	Model	PPGR	FPR	FOR	FNR
Female	MLP	0.37	0.16	0.25	0.31
	GLM	0.38	0.17	0.27	0.32
	NB	0.35	0.13	0.35	0.45
Male	MLP	0.38	0.07	0.23	0.27
	GLM	0.42	0.08	0.24	0.29
	NB	0.4	0.12	0.31	0.42

Table C2 presents a nuanced view of fairness metrics across gender groups for different models, revealing disparities in model biases. For females, the MLP model demonstrates a balance in predicted PPGR and maintains lower error rates compared to GLM and NB, indicating a slightly less biased performance towards female subjects. However, for males, the MLP model shows superior fairness metrics, with the highest PPGR and the lowest rates of FPR, FOR, and FNR, suggesting it is the least biased model across both genders. Conversely, the NB model exhibits higher error rates for both genders, particularly in the FOR and FNR for females, and overall for males, pointing to a greater bias. This analysis indicates that while no model is entirely free of bias, MLP appears to be the most equitable, whereas NB could be considered the most biased, with GLM occupying a middle ground.

Table III disparities in model performance across racial groups, focusing on fairness metrics. Asians benefit most notably from the MLP model's precision, experiencing the most fir treatment with the lowest FPR and highest PPGR, highlighting its superior predictive equity. In contrast, the Hispanic and Asian groups face the greatest challenges with the NB model, which shows a tendency to underpredict positive outcomes for these demographics, indicating significant biases.

Overall, in these results, we observe that the MLP model emerges as the most equitable, especially for Asians, by achieving an optimal balance between fairness and accuracy across racial groups. The GLM model displays consistent fairness metrics, offering a stable, albeit less exceptional, performance that does not heavily favor or disadvantage any particular group. On the other hand, the NB model requires refinement to address its bias, particularly in improving fairness for Hispanic and Asian populations, where it currently lags in predictive accuracy and equity.