Towards Fully Autonomous Research Powered by LLMs: Case Study on Simulations

Zhihan Liu¹, Yubo Chai¹, and Jianfeng Li^{1,†}

¹The State Key Laboratory of Molecular Engineering of Polymers, The Research Center of AI for Polymer Science, Department of Macromolecular Science, Fudan University, Shanghai 200433, China [†]e-mail: lijf@fudan.edu.cn

ABSTRACT

The advent of Large Language Models (LLMs) has created new opportunities for the automation of scientific research, spanning both experimental processes and computational simulations. This study explores the feasibility of constructing an autonomous simulation agent (ASA) powered by LLM, through sophisticated API integration, to automate the entire research process, from experimental design, remote upload and simulation execution, data analysis, to report compilation. Using a simulation problem of polymer chain conformations as a case study, we assessed the performance of ASAs powered by different LLMs including GPT-4-Turbo. Our findings revealed that ASA-GPT-40 achieved near-flawless execution on designated research missions, underscoring the potential of LLMs to manage complete scientific investigations autonomously. The outlined automation can be iteratively performed up to twenty cycles without human intervention, illustrating the potential of LLMs for large-scale autonomous research endeavors. Additionally, we discussed the intrinsic traits of ASAs in managing extensive tasks, focusing on self-validation mechanisms and the balance between local attention and global oversight.

Introduction

In recent years, the rapid development of artificial intelligence technology, particularly the emergence of large language models (LLMs), has brought revolutionary changes to scientific research[1, 2, 3, 4, 5]. Since the launch of ChatGPT by OpenAI, LLMs such as GPT-4 and Anthropic's Claude have demonstrated outstanding performance in natural language processing, text generation, and translation [6, 7]. These AI models not only excel in traditional text processing tasks but also show significant potential in scientific research, gradually transforming conventional research methods and providing scientists with unprecedented tools and methodologies[8, 9, 10, 11].

The application of artificial intelligence (AI) in the fields of chemistry and materials engineering is continually expanding. By integrating machine learning and automated experimental technologies, faster experimental design and data analysis can be achieved, leading to the discovery of new materials and the optimization of existing material properties in a shorter timeframe [12, 13, 14]. In the domain of physical chemistry knowledge parsing, Meta's Galactica assists researchers with tasks such as information organization, knowledge inference, and writing, showcasing the immense potential of large language models in scientific and professional domains [13]. Meanwhile, DeepMind's AlphaFold series of algorithms enable the prediction of structures for biological molecules, from proteins and nucleic acids to larger and more complex complexes [15, 16]. In the fields of chemical synthesis and drug design, AI aids in complex chemical synthesis planning, chemical property prediction, and the generation of new materials. Integrating LLMs with specialized chemical tools and databases can extend their capabilities beyond general language tasks [17, 18, 19, 20, 21]. Additionally, some studies have highlighted the crucial role of prompt engineering in guiding models to produce accurate and useful outputs. Techniques such as Chain of Thought, ReAct, and Tree of Thoughts help structure the model's reasoning process, reduce errors, and improve the quality of generated results [20, 22, 23, 24].

Recent research shows that continuous human-AI interaction can accelerate various stages of scientific research. However, this human-led, AI-assisted model still limits the speed and depth of scientific research. Some work has explored an AI-dominated research model, such as smart laboratories (SDLs) that integrate AI, laboratory automation, and robotics to conduct autonomous experiments. These systems can automatically adjust and optimize based on intelligent analysis and decision-making support from experimental results [25, 26, 27]. The ultimate goal for future AI scientists is to achieve full automation of scientific research processes, from experimental design to data analysis and conclusion generation. This end-to-end automation is set to become a major development in chemical research and a primary objective in chemical engineering, including both experimental and simulation aspects.

This paper explores the AI automation paradigm in polymer theory simulation research. In traditional simulation research, a supervisor typically discusses and plans the research project with students. The students then write and modify the simulation program based on physical models, run simulations under different parameter conditions on remote servers, collect data, analyze results, and write reports. This paper envisions a new research paradigm where, after the research has been planned, the subsequent tasks are solely carried out by AI. Using an autonomous simulation agent (ASA) powered by LLM, after human researchers input a research plan (RP), the ASA will then take on the role of the student to complete the entire research process. Humans only need to review the AI's results at the end, thus achieving a research mode without human intervention.

To test this research paradigm, we systematically attempted ASAs powered by different LLMs on a moderately complex simulation problem in polymer physics. This involved an AI fully autonomously coding the simulation program, remote uploading and executing simulations, data organization, plotting, and scientific report writing.

Random walk and self-avoiding walk models are of significant physical importance in describing the spatial configuration of polymer chains. The random walk model assumes that each 'step' of the chain is independent and random, while the self-avoiding walk model considers the volume exclusion effects between chain segments. Therefore, they exhibit different dynamic behaviors and scaling properties, with different scaling relationships between the mean square end-to-end distance and the number of chain segmentss N. This scaling relationship has been theoretically derived by Flory, De Gennes, and others [28, 29] and validated through simulations and experiment [30, 31]. This problem is fundamental in polymer physics and has been extensively studied. However, for AI, it still presents a novel challenge. The difficulty of predicting the scaling exponent makes it neither too easy nor prohibitively difficult, thus serving as an excellent model problem for testing AI capabilities. We prompted the AI to write simulation programs for both random walk and selfavoiding walk models, compute the mean square end-to-end distance for different chain segment numbers N, fit the results to $\langle R^2 \rangle \propto N^{\nu}$, determine the scaling exponent ν , plot the data, and write a complete scientific report.

The ASA leverages an API automation program (AutoProg) to enable multi-round text interactions with LLMs via API (Figure 1). Initially, the AutoProg provides an RP witten by human researchers to an LLM, and the LLM will break the plan down into multiple sub-tasks and write Python code to complete the first sub-task in its response. The AutoProg then extracts the Python code, executes it, and returns the execution results and any errors along with the conversation history back to the LLM. The LLM then decide whether to modify the Python code or to proceed to the following sub-tasks. This process repeats until the LLM determines that the mission is complete, at which point the AutoProg stops. Upon mission completion, humans evaluate its success based on criteria such as correct simulation, plotting, etc. The ASA we developed is a general system (minor adjustments may be required in the AutoProg for different LLM APIs) that requires only a change in the original RP to be applicable to any simulation problem involving Python programming. In addition to the RPs designed for polymer conformation simulations, we have also crafted RPs for solar system planetary orbit simulations and asteroid trajectory simulations (Figure 1C and SI).

We compared the performance of ASAs powered by various LLMs, including GPT-40, and explored common characteris-



Figure 1. A. Schematic diagram of the AI automation process for theoretical simulation research conducted in this study. The human researcher writes the research plan (RP) for the theoretical simulation and provides it to the autonomous simulation agent (ASA), which is developed by sophisticated API programming (see Method section). The ASA first generates the simulation program, then uploads it to a remote server, performs simulation calculations with different parameter conditions, collects data, and finally writes a report based on the simulation results. B. Diagram of the LLM dialogue. The human researcher only inputs the RP at the beginning, and then the ASA makes decisions based on the dialogue history, achieving a fully autonomous research mode. C. Two typical simulation problems studied in this paper: the chain conformation simulation of a random walk and the gravitational model simulation of asteroid orbit prediction (See SI).

tics and issues when LLMs tackle long tasks. These findings provide insights for researchers to better improve and utilize LLMs for AI-driven scientific research.

Overall, this paper presents the first fully autonomous AIconducted simulation research process powered by LLMs. By adopting this new research paradigm, we aim to explore the potential of AI in highly complex and data-intensive scientific research, breaking traditional human limitations and advancing the automation and intelligence of scientific research.

Results

Automating Basic Simulations in Research

We designed three simulation missions related to polymer chain conformation modeling to demonstrate and test the ability of ASAs powered by different LLMs to autonomously complete the entire research process. Each mission includes multiple sub-tasks, covering the full spectrum from conducting experiments to analyzing data and writing reports. The research plans (RPs) for these missions are shown in **Figure 2**. Among these RPs, RP 1 is the simplest involving only basic research steps for simulations given below.

• **RP 1** requires generating a Python program to simulate a random walk, sampling different numbers of chain segments *N*, deriving the scaling relation $\langle R^2 \rangle \propto N^{\nu}$, saving chain conformation graphs and scaling relation fit plots, and writing a research report.

We established several evaluation criteria based on the requirements of the RP, such as whether graphs and plots were generated and whether the derived scaling relationships were correct, to assess task completion. We tested nine ASAs powered by different LLMs, including GPT-40, conducting 20 trials for each RP and recording the achievement of the evaluation criteria across these trials, as shown in **Figure 3**.

ASA-GPT-40 and ASA-GPT-4-Turbo excelled on RP 1, achieving near-perfect completion in both simulation and report writing tasks (**Figure 3B**). ASA-Claude-3.5 and ASA-Qwen-2 followed, performing well in simulation tasks but sometimes generating reports in response or as text files, failing to meet RP 1's requirements. Other models performed well in plotting graphs but lacked accuracy in establishing correct physical models and deriving correct scaling values through simulations.

Although chain conformation simulations are convenient for comparing different LLMs, they are less convincing due to being previously well-studied topics. To make a stronger case, we need more challenging problems. Additionally, to demonstrate that ASA can solve problems across different scientific domains, we designed RPs for gravitational simulation problems corresponding to RP S1 and RP S2 (**Figure S1** and **Figure 1C**). The mission of RP S2 is to evaluate the risk posed by a meteorite (or asteroid) to earth, given its initial position and velocity and write a report. This mission is challenging even for graduates from physics departments. By simply inputting RP S2 into the same ASA used for chain conformation problems, the ASA will automatically acquire the necessary parameters of the solar system, code the simulation program to calculate the asteroid's trajectory, and ultimately write the report. This result underscores the effectiveness of our API programming strategy (see Method section) and strongly demonstrates that ASA can address problems in entirely different fields.

Automating Simulations with Remote Server Operations and Volume Exclusion

RP 2 increases complexity with server interactions and RP 3 doubles the mission length and simulation difficulty. Brief introductions of these two RPs are shown below (**Figure 2**).

- **RP 2** directly provides a random walk simulation program, asking the ASA to modify it, run simulations in a designated folder on a remote server, download the experimental data, and generate graphs and plots and a research report.
- **RP 3** is similar to **RP 1** but includes both random walk and self-avoiding walk simulations.

For RP 2, which involves remote upload and remote simulations, completion rates across ASAs significantly declined, with some agents consistently failing across multiple trials. ASA-Claude-3.5 achieved the highest completion rate, successfully completing the entire mission, including generating all required graphs in over two-thirds of trials, though it occasionally missed displaying some generated graphs in the report. ASA-GPT-40, ASA-GPT-4-Turbo, and ASA-Qwen-2 also demonstrated some success in solving complex missions over 20 trials (**Figure 3**).

RP 3 required simulating a self-avoiding walk based on the random walk simulation in RP 1. Although the process was longer, it was less complex than RP 2, resulting in improved performance across agents. ASA-GPT-40, ASA-GPT-4-Turbo, ASA-Claude-3.5, and ASA-Gemini-1.5-Pro performed relatively well. Notably, none of the agents provided a correct self-avoiding scaling due to incorrect sampling methods during simulation, which will be discussed in detail in the Discussion section.

Moreover, ASA-GPT-40 and ASA-Claude-3.5 demonstrated unique advantages in generating rich content. They frequently produced detailed reports exceeding 1,000 words, delving into the distinctions between RW and SA scaling, and occasionally included precise literature citations. ASA-Claude-3.5 referenced accurate self-avoiding walk scaling relationships validated through theoretical derivations and experimental verifications, accompanied by brief analyses of simulation result deviations. Additionally, ASA-GPT-40 presented experimental data in enriched formats, such as frequency distribution plots of end-to-end distances and interactive web-based charts.

Research	Plans
----------	-------

RP 1:	RP 2:				
First, develop a Python script to generate 2000 polymer chains, each consisting of N segments of length 1. Randomly assign each segment's orientation in 3D space, ensuring uniform distribution (use caution when generating 3D unit vectors; randuniform for angles may not suffice). Compute the end-to-end distance vector from the first to Nth segment, and denote the mean squared end-to-end distance for N-segmented polymers as $h2(N)$. For N = 10, 50, 100, 200, 400, select 5D random chain conformations, plot them together in one graph (save as 6 J2006). DO NOT show the	 Modify the program to calculate the mean square end-to-end distance for a single N value, which should be externally input using argparse. For example, the program should be trunnable with a command like 'python py1.py -n 100'. Remove the calculation of v and the plot of h2(N)-N. Save a single image with 50 conformations, and save the end-to-end distances and N in a text file. Ensure that the saved filename is related to the input value of N. Only modify the program; do not execute it. (2) After the modification, save it as py1.py. Then, write a Python program to assist in uploading py1.py to a remote node (details provided at the end of this prompt) and running py1.py in the background for N=100, 200, 300, 400, 600, 800. Check if the conformation images and test files for these N values exist. If they all exist, use SFTP to transfer the images and text files to the local directory. Check if they are the N and P2 from each text file, save a M2(N)-N plot, and calculate the scaling law of h2(N)-N'. Print the value of v. (3) Utilize Python to generate a Word document and compose a detailed simulated experiment report (1000 words) based on the generated graphs and the provided instructions. Choose a suitable title and divide the report into four sections: begin with an abstract, followed by an 'Introduction' to briefly 				
images. Determine the scaling relationship h2(N) \propto N^v, print v.					
Next, create a Word document containing a detailed simulation experiment report based on the generated graphs and instructions. Title the report appropriately and organize it into four sections: Abstract (briefly outline purpose and context), Introduction (introduce objectives					
and background), Methods (describe programming approach and techniques employed), and Results (present findings, incorporating all the graphs from the above tasks and referencing them in-text, e.g., "Fig. 1"). Ensure each section contains approximately 300-500 words.					
RP 3:	introduce the purpose and background, 'Methods' to discuss the programming approach and methods used, and 'Results' to present the findings, incorporating the graphs from the second and third tasks				
(1) Develop a Python script to generate 2000 polymer chains, each consisting of N segments of length 1. Randomly assign each segment's orientation in 3D space, ensuring uniform distribution (use caution when generating 3D unit vectors; randuniform for angles may not suffice). Compute the end-to-end distance vector from the first to Nth segment and denote	and referencing them in the text (e.g., 'as shown in Fig. 1). Each section should contain approximate 300 to 500 words.				
	[python program]				
the mean squared end-to-end distance for N-segmented polymers as $h2(N)$. For N = 10, 50,	import numpy as np				
100, 200, select 50 random chain conformations, plot them together in one graph (save as Chain3D+str(N).png), and plot h2(N) vs. N (save as h2vsN.png). DO NOT display the PNG					
images; merely save them directly. Determine the scaling relationship h2(N) \propto N^v,	[END of python program]				
	[Information of Remote Node]:				
process. Ensure that every chain segment maintains a minimum distance of at least 1 unit	use paramiko to connect the remote node				
from all other segments within the same chain. Produce 2000 such chains for every given	hostname = '*****'				
length (N). Using faster algorithms can speed up this process.	username = '******'				
(3) Finally, use Python to create a Word document containing a detailed simulation experiment report based on the generated graphs and instructions. Title the report	password = '******'				
appropriately and organize it into four sections: Abstract (briefly outline purpose and	remote_path = '*****'				
context), Introduction (introduce objectives and background), Methods (describe programming approach and techniques employed) and Results (present findings	python_path = '*****'				
incorporating all the graphs from the above tasks and referencing them in-text, e.g., "Fig. 1").	use command = f"bash -l -c 'cd {remote_path} && {python_path}{remote_python_file} {pars_args}'" to execute remote python file				

Figure 2. Overview of **RP 1-3.** We designed three RPs, each containing multiple steps such as simulation, plotting, and report writing, and provided them to the ASA. RP 1 and RP 3 required the ASA to generate a complete Python program to simulate polymer chains, run the simulation locally, and produce a final report. RP 2 required the ASA to modify the provided simulation program, run the simulation on a remote server, and then generate a report. The provided simulation program (omitted in the figure) and remote server information were included in RP 2.

Automating Agent Coordination through RP Generation

In the preceding section, RPs were provided by humans. In this section, we task a Main AI with automatically breaking down a human-provided RP into sub-tasks and distributing them as AI RPs to several Subordinate AIs.

We provided RP 1 and 2 directly to the Master AI, adjusting the ASA to ensure each sub-task was handled by a distinct Subordinate AI without access to the Main AI's or other Subordinate AIs' conversation histories. The Main AI solely presents the AI RPs (**Figure 4A**) and received reports upon task completion.

We also employed GPT-4-turbo for this experiment. The results (**SI-data-2**) revealed that for RP 1, the Main AI effectively decomposes the mission into sub-tasks and successfully distributed them to Subordinate AIs, thereby completing RP 1. However, for RP 2, the Main AI encounters repeated failures. The primary issue lies in precise information transmission. RP 2 provides a random walk simulation program and details of a remote server, including hostname and username. Despite multiple attempts, the Main AI struggles to convey both the simulation program and server details accurately to the Subordinate AIs (**Figure 4B**). We attempted to instruct the Main AI to include all relevant information in the AI RPs, but this did

not notably enhance the accuracy of information transmission. Additionally, we observed instances where AI RPs contained irrelevant information, potentially confusing the Subordinate AIs about the mission's focus.

Automating the Automation: Crafting Multi-tier RPs for Large-Scale Research

Back in the Automating Basic Simulations section, for each ASA and each RP, we undertake 20 rounds of 'automation' by executing RP 1 and collecting the results including codes and files generated by the ASA. Can we automate the entire process of this study on reaserch automation or can we even automate the automation itself?

RP 4 is designed for this purpose. It is nested within RP 1, instructing the Primary AI to execute the command "python AutoProg.py -s p1.txt -n i" 20 times. Each execution generates an Agent AI to fulfill RP 1 contained in p1.txt, while the Primary AI collects all generated files and conducts result analysis. The detailed content of RP 4 is depicted in **Figure 4C**.

Using ASA-GPT-4-Turbo, we conducted tests on RP 4. The results (**SI**) strikingly demonstrate that the Primary AI successfully executed the 20 instances of RP 1, meticulously organizing all files into their respective folders and providing a brief summary after all experiments. During this process, the AI independently and without interruption wrote 66 programs (including 26 error versions), conducted more than 20 simulations, generated 120 images, and wrote 20 research reports totaling over 5,000 words. Marvelously, all these missions were accomplished without any human intervention. This illustrates the remarkable capability of multi-tier RP structures in handling large-scale missions.

Discussion

The experiments demonstrate that LLMs, with their robust coding ability [24, 32, 33, 34], can be directly employed in developing agents to autonomously complete complex research missions when aided by proper API programming. ASA-GPT-40 and ASA-GPT-4-turbo, notably, exhibits near-perfect completion rates for simpler missions, highlighting their potential. Multi-tier RP designs effectively handle more complex missions, though accurate information transmission remains challenging for such RPs. Enhancements in RP design and AI coordination are essential for fully harnessing AI's potential in automating scientific research. Below, we discuss several problems existing in the current reaserch.

Common Issues in Sequential Task

Despite varying completion rates among tested ASAs, their errors and failure points share common characteristics, reflecting the inherent logical features of LLMs.

First, some ASAs tend to overlook parts of the RP's requirements or "take shortcuts", not fully following the RP's instructions. For instance, they might skip plotting, fail to write a report, or ask humans to execute part of the task. These issues affect mission completeness and can disrupt the entire workflow. To improve autonomy in AI for science, we need to address these issues by continuously generating outputs describing the current mission status, periodically reviewing generated data, and confirming strict adherence to mission requirements. These improvements can be integrated through AutoProg modifications or by incorporating them into the "system" prompt input to LLMs or fine-tuning the LLMs.

Second, ASAs often underperform on technical aspects of tasks due to a lack of specialized domain knowledge. For example, when simulating a random walk, the algorithm needs to generate unit vectors uniformly distributed on a sphere to ensure isotropy. Although ASAs can often generate spatially random unit vectors, they fail to ensure uniform distribution on the sphere. In another example, for simulating self-avoiding walks, ASAs often incorrectly extend the random walk strategy by merely checking distances between points, resulting in high-energy state samples with large statistical errors. Correct sampling should use importance sampling to generate statistically significant conformations[35]. To avoid these issues in research, reliable solutions should be provided in the RPs, or relevant domain knowledge should be used for fine-tuning the LLMs to enhance their understanding.

Error Loops in Debugging

Each AutoProg involves a Python code debugging process. When bugs are detected, the LLM receives error messages and attempts to revise the code, iterating until it executes correctly. However, we've noted instances where the LLM struggles to generate functional code, resulting in mission failures. This typically occurs when the LLM becomes "stuck" after repeated unsuccessful debugging attempts, cycling through the same erroneous code without progress.

This phenomenon may be associated with the LLM's propensity to depend heavily on past dialogue content. Research has documented instances where LLMs utilize context to deliver responses preferred by users, indicating an excessive reliance on previous information [36, 37, 38]. While this capability allows LLMs to adapt responses based on short dialogue histories, it can also lead to persistent errors.

In our experiments, to prevent such deadlocks, we implemented a maximum debug attempt limit. Once this limit is reached, the AutoProg returns a "mission failed" message. To ensure the smooth execution of concrete research missions, it is crucial to avoid these debugging loops. One solution involves clearing parts of the memory after a certain number of debug attempts or encouraging the LLM to generate varied content in each iteration (Some LLMs include parameters to avoid generating duplicate content and to adjust the creativity of the models.).

Balancing Global Oversight and Local Attention

In our experiments, ASAs exhibited a significant level of global oversight, which allows them to track mission progress based on the dialogue history. They can retain details from earlier stages of missions even after focusing on lengthy subtasks. However, as discussed above, ASAs occasionally skip steps in prolonged missions or fail to deliver comprehensive solutions for sub-tasks, indicating a lack of sufficient local attention.

Achieving successful and precise mission completion requires a delicate balance between global oversight and local attention, two perspectives that are normally conflicting.

In Automating Agent Coordination section, we designed a collaboration plan where a Main AI and some Subordinate AIs handled different aspects of the mission: the Main AI defined sub-task requirements and received reports, while Subordinate AIs focused on specific sub-tasks. This approach minimized redundant information in their dialogue history, enhancing the Main AI's global awareness and the Subordinate AIs' local attention. While the Main AI effectively completed the mission in RP 1, the Main-Sub AI model encountered challenges in RP 2 due to the failure of precise information transmission. One potential optimization is to involve human-designed RPs distributed among various Subordinate AIs for execution.

Limitations and Next Steps

This study demonstrates the capability of LLM powered research agent ASA to independently undertake sophisticated

۸.								
Α -	LLM	Version	Developer	Ľ	ASA	P1	P2	P3
	GPT-4o	gpt-4o	OpenAl		ASA-GPT-4o	100.0	61.2	93.8
	GPT-4-Turbo	gpt-4-turbo	OpenAl		ASA-GPT-4-Turbo	97.8	49.3	79.5
	GPT-3.5-Turbo	gpt-3.5-turbo-0125	OpenAl		ASA-GPT-3.5-Turbo	24.0	24.4	21.2
	SparkDesk-3.5	generalv3.5	SparkDesk		ASA-SparkDesk-3.5	19.8	1	1
	Llama-3-Sonar	llama-3-sonar-large-32k-online	Perplexity		ASA-Llama-3-Sonar	28.8	/	8.8
	Gemini-1.5-Pro	gemini-1.5-pro	Google		ASA-Gemini-1.5-Pro	36.2	1	68.2
	Claude-3.5	claude-3-5-sonnet-20240620	Anthropic		ASA-Claude-3.5	60.7	69.1	72.3
	Moonshot	moonshot-v1-128k	Moonshot Al		ASA-Moonshot	31.9	1	35.9
	Qwen-2	qwen2-72b-instruct	Alibaba Cloud		ASA-Qwen-2	53.4	43.8	35.5

 B
 Prompt1 Criteria © Conformation Diagram Created © h²(N) vs. N Plot Created © Scaling Relation Derived © Accurate Plots and Correct Scaling Provided

 © Report Written © Report exceeds 200 words © All Generated Figures Included in Report

 ASA-GPT-40
 ASA-GPT-4-Turbo
 ASA-GPT-3.5-Turbo
 ASA-SparkDesk-3.5
 ASA-Lauae-3-Sonar
 ASA-Genini-1.5-Pro
 ASA-Claude-3.5
 ASA-Moonshot



Figure 3. Completion Rates of Various ASAs for RP 1-3. A. Table of LLM models used in this study. B. Statistics of the number of criteria met by each ASA over 20 experiments. We established seven criteria for RP 1-3 to measure mission completion rates and counted the number of times each ASA met these criteria across 20 experiments. Some zero results are not displayed. C. ASA Scoring. Relative scores for each ASA in RP 1-3 were calculated using the EWM and TOPSIS methods. D. ASA Generated Research Report Example. Demonstrates a Word report generated by ASA-GPT-4 for RP 1, including four sections, chain conformation diagrams and a scaling relation fit plot (also see SI).



Figure 4. A. Example of Main AI's Response. The Main AI first breaks down the overall mission into sub-tasks, then generates AI RPs beginning with '<<< prompt' and ending with 'end>>>'. The AI-generated RPs are then passed to subordinate AIs for execution. B. Example of Faulty and Incomplete AI RP. The black box highlights where the AI RP fails to provide necessary information such as username and password for connecting to the remote server, and the red box highlights where the AI RP includes irrelevant information. C. Overview of RP 4. The command 'python AI4SCI_VE13.py -s p1.txt -n i' generates an Agent AI to complete the mission of RP 1, where AI4SCI_VE13.py is the API automation execution program, p1.txt is the text file containing the RP, and i denotes the *i*th execution of the command.

simulation research missions, using a well-recognized polymer physics simulation problem and a more challenging celestial-simulation problem as representative examples. However, there remains ample opportunity to explore ASA's potential in tackling novel scientific challenges. Additionally, this study focuses on presenting an automated workflow, leaving room for further optimization of prompts and automation programs.

Several inherent limitations of ASAs were identified: (1) ASAs may overlook mission requirements, necessitating methods to prioritize critical information; (2) general LLMs lack specialized domain knowledge, requiring supplementary information in RPs; (3) LLMs may persist in errors by relying too heavily on previous content, requiring memory management strategies in ASAs' development; (4) balancing global awareness and local attention poses a challenge; (5) accurately transmitting specific information remains problematic. Addressing these issues is crucial for enhancing the role of AI in scientific research. This requires a thorough analysis of these limitations and adjustments to research methodologies and LLM capabilities, leveraging their strengths while mitigating their weaknesses.

Conclusion

This study demonstrates the potential of LLM powered research agent ASA to autonomously conduct scientific research missions, using a polymer theory simulation problem and a more challenging asteroid-trajectory prediction problem as model problems. This process, encompassing simulation coding, remote execution, data analysis, and report generation, represents the first fully autonomous AI-directed simulation research. The notable success herein can be largely attributed to the sophisticated API programming. Agents such as ASA- GPT-40 demonstrate high completion rates for missions, a strong grasp of task requirements, and consistent alignment with overall objectives across extensive tasks. Notably, the performance exhibited in completing RP 4, entailing a hierarchy of nested tasks, surpassed expectations in a significant manner. These capabilities underscore the readiness of ASAs to independently manage long-term scientific research missions, offering a new perspective on AI applications in science as well as in chemical engineering.

Method

API automation Program (AutoProg)

Based on the official documentation of various LLMs, we implemented the API automation programs (AutoProg) by configuring Python API calling methods and setting up the local environment. This setup included installing necessary Python packages like numpy, matplotlib, paramiko, and python-docx tailored for our simulation tasks. An AutoProg serves dual functions: 1) it engages in dialogue with the LLM via the API and preserves all historical dialogues, and 2) it extracts and executes Python programs generated by the LLM in response to prompts.

For instance, in the case of RP 1, an AutoProg initiates the automated research process by reading mission requirements saved in a txt file. It then calls the API to transmit the RP to the LLM, instructing it to generate a comprehensive Python program. The AutoProg extracts this program from the LLM's response, sends it back to the LLM via the API along with entire dialogue history, and requests error checking and compliance verification against mission requirements. Subsequently, the AutoProg executes the validated Python program, capturing and storing output or errors. In case of errors, the AutoProg sends the prior dialogues and program errors back to the LLM, asking for modifications. This process repeats until the program runs correctly. If errors persist beyond a predefined threshold, the AutoProg halts with a "mission failed" output. Conversely, upon successful execution, it returns the program output to the LLM, prompting it to check the dialogues and files in the working directory to determine the task progress. If the task remains incomplete, the next Python program will be generated by the LLM to continue the mission, iterating through checking and debugging processes until completion. When the mission achieves full execution, the AutoProg concludes with a "mission complete" output.

AutoProg.py and RP.txt, containing predefined instructions, are stored in the local working directory. To initiate the automated research process for each experiment, users navigate to the directory via the command line (CMD) and execute commands such as "python AutoProg.py -s RP.txt". Alternatively, AutoProg can be elevated to a command by creating a batch file (Windows) or shell script (Linux), allowing users to simply enter "AutoProg RP.txt" from any directory to execute it. A detailed video recording of the execution process is available for reference (**SI-video**), in which a batch file is used to facilitate the execution by running the command "do

AI4S_prj1.txt".

To evaluate LLM performance across RP 1-3, each ASA underwent 20 tests per RP, with all generated files and Auto-Prog outputs saved. Sample results are provided in the data (**SI-data-1**).

ASA Scoring via EWM and TOPSIS

To evaluate the performance of ASAs on designated RPs, we devised specific criteria for RP 1-3, including diagram generation, report composition, etc. Through systematic observation across multiple trials, we recorded each agent's fulfillment against these criteria. For quantitative analysis and scoring, we deployed the Entropy Weight Method (EWM) and TOP-SIS (Technique for Order of Preference by Similarity to Ideal Solution).

The EWM, a well-established approach for determining the relative significance of criteria in decision-making [39], was utilized to assign weights based on data variability. This ensures criteria with higher variability, and thus more informational value, receive higher weights in the final evaluation.

TOPSIS, originally formulated by Hwang and Yoon [40], was subsequently applied. This method computes the geometric distance between each agent's performance and both ideal and anti-ideal solutions, facilitating a comparative assessment of ASA efficacy.

The evaluation procedure is delineated as follows.

Initially, fulfillment data for all ASAs across various criteria were gathered over 20 trials, encapsulated in matrix X, wherein x_{ij} signifies the frequency of criterion *j*'s attainment by agent *i*. Normalization was then performed on x_{ij} :

$$r_{ij} = \frac{x_{ij} - \min(x_{ij})}{\max(x_{ij}) - \min(x_{ij})},\tag{1}$$

yielding the normalized matrix $\mathbf{R} = [r_{ij}]$. Subsequently, criterion weights were established utilizing EWM. The relative proportion p_{ij} of the criterion *j*:

$$p_{ij} = \frac{r_{ij}}{\sum_{i=1}^{m} r_{ij}}.$$
(2)

The entropy e_j of the criterion *j*:

$$e_j = -k \sum_{i=1}^m p_{ij} \ln(p_{ij}),$$
 (3)

with $k = 1/\ln(m)$, and *m* denoting the total number of agents. The weight ω_i of the criterion *j*:

$$\omega_j = \frac{d_j}{\sum_{i=1}^n d_j},\tag{4}$$

with $d_j = 1 - e_j$ the disparity of the criterion and *n* the total number of criteria. Conclusively, agent scores were derived via TOPSIS. Multiplication of r_{ij} by its respective weight ω_j yields the weighted normalized matrix $\mathbf{V} = [v_{ij}]$

with $v_{ij} = \omega_j \cdot r_{ij}$. The positive ideal solution v_j^+ and negative ideal solution v_j^- were determined as $v_j^+ = max(v_{ij})$ and $v_j^- = min(v_{ij})$, respectively.

Then the geometric distances S_j^+ and S_j^- from v_{ij} to the positive and negative ideal solutions can be computed, respectively, as

$$S_{j}^{+} = \sqrt{\sum_{j=1}^{n} \left(v_{ij} - v_{j}^{+} \right)^{2}}$$
(5)

and

$$S_{j}^{-} = \sqrt{\sum_{j=1}^{n} \left(v_{ij} - v_{j}^{-} \right)^{2}}.$$
 (6)

The relative closeness C_i^* for each agent was calculated as:

$$C_i^* = \frac{S_j^-}{S_j^+ + S_j^-}$$
(7)

A higher C_i^* signifies superior agent performance relative to peers on the assigned RP.

References

- Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. Bert: Pre-training of deep bidirectional transformers for language understanding. In Burstein, J., Doran, C. & Solorio, T. (eds.) Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), 4171–4186 (Association for Computational Linguistics, Minneapolis, Minnesota, 2019). URL https://aclanthology. org/N19–1423.
- Raffel, C. *et al.* Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research* 21, 1–67 (2020).
- **3.** Floridi, L. & Chiriatti, M. Gpt-3: Its nature, scope, limits, and consequences. *Minds and Machines* **30**, 681–694 (2020).
- Chowdhery, A. *et al.* Palm: Scaling language modeling with pathways. *Journal of Machine Learning Research* 24, 240:1–240:113 (2022).
- 5. Thoppilan, R. *et al.* Lamda: Language models for dialog applications. *arXiv* (2022). 2201.08239.
- 6. OpenAI. Gpt-4 technical report. https://cdn. openai.com/papers/gpt-4.pdf (2023). Retrieved June 24, 2024.
- 7. Anthropic. Model card and evaluations for claude models. https://www-cdn. 2 anthropic.com/files/4zrzovbb/website/ bd2a28d2535bfb0494cc8e2a3bf135d2e7523226. pdf (2023). Retrieved June 24, 2024.

- Ramesh, A. *et al.* Zero-shot text-to-image generation. In *International conference on machine learning*, 8821– 8831 (Pmlr, 2021).
- **9.** Bommasani, R. *et al.* On the opportunities and risks of foundation models (2022). 2108.07258.
- Chang, Y. et al. A survey on evaluation of large language models. ACM Transactions on Intelligent Systems and Technology 15 (2024).
- Kasneci, E. *et al.* Chatgpt for good? on opportunities and challenges of large language models for education. *Learning and Individual Differences* 103, 102274 (2023).
- Himanen, L., Geurts, A., Foster, A. S. & Rinke, P. Datadriven materials science: Status, challenges, and perspectives. *Advanced Science* 6, 1900808 (2019).
- **13.** Taylor, R., Kardas, M., Cucurull, G. & et al. Galactica: A large language model for science. *arXiv* (2022). 2211.09085.
- **14.** Wang, H., Fu, T., Du, Y. & et al. Scientific discovery in the age of artificial intelligence. *Nature* **620**, 47–60 (2023).
- **15.** Evans, R., O'Neill, M., Pritzel, A. & et al. Protein complex prediction with alphafold-multimer. *bioRxiv* (2021). 2021.10.04.463034.
- **16.** Abramson, J., Adler, J., Dunger, J. & et al. Accurate structure prediction of biomolecular interactions with alphafold 3. *Nature* **630**, 493–500 (2024).
- Brown, N., Fiscato, M., Segler, M. & et al. Guacamol: Benchmarking models for de novo molecular design. *Journal of Chemical Information and Modeling* 59, 1096– 1108 (2019).
- Stokes, J. M., Yang, K., Swanson, K. & et al. A deep learning approach to antibiotic discovery. *Cell* 180, 688– 702 (2020).
- **19.** Boiko, D. A., MacKnight, R., Kline, B. & et al. Autonomous chemical research with large language models. *Nature* **624**, 570–578 (2023).
- Bran, M., Cox, A., Schilter, S. & et al. Augmenting large language models with chemistry tools. *Nature Machine Intelligence* 6, 525–535 (2024).
- Kang, Y. & Kim, J. Chatmof: an artificial intelligence system for predicting and generating metal-organic frameworks using large language models. *Nature Communications* 15, 4705 (2024).
- 22. Jablonka, K. M., Schwaller, P., Ortega-Guerrero, A. & et al. Leveraging large language models for predictive chemistry. *Nature Machine Intelligence* 6, 161–169 (2024).

- **23.** Schulhoff, S., Ilie, M., Balepur, N. & et al. The prompt report: A systematic survey of prompting techniques. *arXiv* (2024). 2406.06608.
- **24.** Zhou, Z., Ning, X., Hong, K. & et al. A survey on efficient inference for large language models. *arXiv* (2024). 2404. 14294.
- 25. Abolhasani, M. & Kumacheva, E. The rise of self-driving labs in chemical and materials sciences. *Nature Synthesis* 2, 483–492 (2023).
- 26. Szymanski, N. J., Rendy, B., Fei, Y. & et al. An autonomous laboratory for the accelerated synthesis of novel materials. *Nature* 624, 86–91 (2023).
- 27. Volk, A. A., Epps, R. W., Yonemoto, D. T. & et al. Alphaflow: autonomous discovery and optimization of multi-step chemistry using a self-driven fluidic lab guided by reinforcement learning. *Nature Communications* 14, 1403 (2023).
- **28.** Flory, P. J. *Statistical Mechanics of Chain Molecules* (Interscience Publishers, 1969).
- **29.** De Gennes, P. G. *Scaling concepts in polymer physics* (Cornell University Press, 1979).
- **30.** Madras, N. & Slade, G. *The self-avoiding walk* (Birkhäuser Boston, 2013).
- **31.** Burchard, W. Static and dynamic light scattering from branched polymers and biopolymers. *Advances in Polymer Science* **48**, 1–124 (1983).
- **32.** Fang, C., Miao, N., Srivastav, S. & et al. Large language models for code analysis: Do llms really do their job? *arXiv* (2023). 2310.12357.
- **33.** Zhong, L. & Wang, Z. Can chatgpt replace stackoverflow? a study on robustness and reliability of large language model code generation. *arXiv* (2023). 2308.10335.
- **34.** Murr, L., Grainger, M. & Gao, D. Testing llms on code generation with varying levels of prompt specificity. *arXiv* (2023). 2311.07599.
- **35.** Madras, N. & Sokal, A. D. The pivot algorithm: A highly efficient monte carlo method for the self-avoiding walk. *Journal of Statistical Physics* **50**, 109–186 (1988).
- **36.** Brown, T. B., Mann, B. & Ryder, N. Language models are few-shot learners. *arXiv* (2020). 2005.14165.
- 37. Gao, T., Fisch, A. & Chen, D. Making pre-trained language models better few-shot learners. arXiv (2020). 2012.15723.
- 38. Wei, J. et al. Finetuned language models are zero-shot learners. In The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022 (OpenReview.net, 2022).

- **39.** Ravindran, A., Phillips, D. T. & Solberg, J. J. *Operations Research Principles & Practice* (John Wiley, New York, 1987), 2nd edn.
- **40.** Hwang, C. L. & Yoon, K. Methods for multiple attribute decision making. In *Multiple Attribute Decision Making*, vol. 186 of *Lecture Notes in Economics and Mathematical Systems* (Springer, Berlin, Heidelberg, 1981).

Acknowledgements

J.F.L. acknowledge supports from National Natural Science Foundation of China (Nos. 52394272, 22373022) and National Key Research and Development Program of China (No. 2023YFA0915300).

Supplementary information

We provide partial results for gravitational simulation mission along with examples of reports written by ASAs. (**SI.pdf**). We also provide partial AutoProgs and experimental result files for RP 1-3, main AI generating RP, and Multi-tier human RP. Some information has been obscured; readers can replace it with their own information and follow the instructions to run the AutoProgs (**SI-data-1.zip and SI-data-2.zip**). Additionally, we have created a demo video demonstrating the operation process of the automatic research system (**SIvideo.mp4**).