TempoFormer: A Transformer for Temporally-aware Representations in Change Detection

Talia Tseriotou¹, Adam Tsakalidis^{1,2,3} Maria Liakata^{1,2}

¹Queen Mary University of London, ²The Alan Turing Institute, ³European Centre for the Development of Vocational Training t.tseriotou@gmul.ac.uk

Abstract

Dynamic representation learning plays a pivotal role in understanding the evolution of linguistic content over time. On this front both context and time dynamics as well as their interplay are of prime importance. Current approaches model context via pre-trained representations, which are typically temporally agnostic. Previous work on modeling context and temporal dynamics has used recurrent methods, which are slow and prone to overfitting. Here we introduce TempoFormer, the fist task-agnostic transformer-based and temporally-aware model for dynamic representation learning. Our approach is jointly trained on inter and intra context dynamics and introduces a novel temporal variation of rotary positional embeddings. The architecture is flexible and can be used as the temporal representation foundation of other models or applied to different transformer-based architectures. We show new SOTA performance on three different realtime change detection tasks.

1 Introduction

Linguistic data sequences are generated continuously over time in the form of social media posts, written conversations or documents that keep evolving (e.g. through regular updates). While a large body of work has been devoted to assessing textual units or sub-sequences in isolation - i.e. in emotion classification (Alhuzali and Ananiadou, 2021), ICD coding (Yuan et al., 2022), task-specific dialogue generation (Brown et al., 2024), irony and sarcasm detection (Potamias et al., 2020) - such approaches leave significant historical (often timestamped) context unused. Fig. 1 provides an example from the task of identifying mood changes through users' online content, where the last post in isolation cannot denote if there has been a 'Switch' in the user's mood - the historical content provides important context for the user's originally positive mood, enhancing the signal for a negative switch in their behaviour.




Figure 1: The historical content provides important context towards identifying the Switch in the user's mood from positive to negative in the last post.

Dynamic representation learning approaches aim to tackle this challenge. Dynamic word embedding methods have been studied in the context of semantic change detection (Bamler and Mandt, 2017; Rosenfeld and Erk, 2018). While changes in this context occur over long time periods, dynamic representation learning has been explored in other more temporally fine-grained tasks such as event detection (Yan et al., 2019; Yang et al., 2019; Lai et al., 2020), fake news detection (Vaibhav et al., 2019; Raza and Ding, 2022; Kaliyar et al., 2021) and mental health condition detection (Sawhney et al., 2021b; Tsakalidis et al., 2022a; Tseriotou et al., 2023). Nevertheless, dynamic representation learning research remains largely task or even dataset specific.

Transformer-based injection. The above mentioned approaches have relied on either pre-trained contextualised representations or transformerbased model layers (Devlin et al., 2018; Liu et al., 2019) to fine-tune representations before feeding them into RNN and CNN-like architectures as they had been shown to outperform transformer-based models (Ji et al., 2021; Gao et al., 2021; Tsakalidis et al., 2022b). However, since LSTM-based systems tend to overfit small datasets, transformerbased methods that overcome this issue would be a preferable method (Yu et al., 2020). Yet so far adapting layers on top of a transformer fails to strike the right balance between representation learning and task dynamics (Li et al., 2022; Ng et al., 2023).

Temporal modelling. Although integration of time in language models has been explored for temporal adaption (Röttger and Pierrehumbert, 2021) in semantic change detection, (Rosin and Radinsky, 2022; Wang et al., 2023) there is not yet work that explores the abilities of transformers to model temporally distant textual sequences (streams). Recently LLMs have been shown to fall short in terms of temporal reasoning (Jain et al., 2023; Wallat et al., 2024), especially in event-event temporal reasoning (Chu et al., 2023). Here we make the following contributions:

- We present a novel, temporally-aware BERTbased model (**'TempoFormer'**)¹ that models streams of chronologically ordered textual information accounting for their temporal distance. TempoFomer is the first such model to directly modify the transformer architecture, doing so in a flexible and task-agnostic manner.
- We transform rotary position embeddings into rotary temporal embeddings that measure the temporal distance of sequential data points.
- Contrary to prior work reliant on pre-trained contextual embeddings, we allow for adaptation of transformers towards the domain and the temporal aspects of a dataset. We show that TempoFormer can be used as the foundation in more complex architectures (e.g. involving recurrence), striking the right balance between modeling a post/utterance (contextaware) and the timeline-level dynamics. Moreover the TempoFormer upper layers are flexible and can be applied in different Transformer-based architectures.
- We show SOTA performance on 3 change detection NLP tasks (longitudinal stance switch, identifying mood changes and identifying conversation derailment).

2 Related Work

Context-aware Sequential Models: Numerous social media related tasks such as rumour detection rely on chronologically ordered conversation threads (Ma et al., 2020; Lin et al., 2021; Ma and

Gao, 2020). Moreover Ng et al. (2023) have shown lift in performance when using the full context of medical notes, rather than the discharge summary alone, for ICD coding. However context-aware sequential models have so far relied on recurrent networks or hierarchical attention (Li et al., 2020; Ma et al., 2020; Tsakalidis et al., 2022a) without exploring the dynamics between sentence level and stream level representations.

Longitudinal Modeling and Change Detection: In addition to the importance of the linguistic stream, longitudinal tasks rely on temporal dynamics to asses the progression and identify changes over time. In the case of (a) *identifying changes* in user mood (Tsakalidis et al., 2022b; Hills et al., 2023; Tseriotou et al., 2023) and suicidal ideation through social media (Sawhney et al., 2021a) change is relative to the temporal evolution of users' mood over time and approaches have relied mostly on recurrence and on utterance-level pretrained language model (PLM) representations. Tseriotou et al. (2024) introduced a longitudinal variation of (b) stance detection (Yang et al., 2022; Kumar and Carley, 2019) for detecting shifts (changes) in the public's opinion towards an online rumour. They used Sentence-BERT (Reimers and Gurevych, 2019) representations with integration of path signatures (Lyons, 1998) in recurrence. For (c) conversation topic derailment, previous work has relied on fine-tuning transformer-based models (Konigari et al., 2021), providing extended context in their input (Kementchedihieva and Søgaard, 2021) or applying recurrence over the utterance (Zhang et al., 2019a) and context stream (Chang and Danescu-Niculescu-Mizil, 2019). In this work we integrate stream dynamics directly into the transformer and show the flexibility of our approach as the foundation of different longitudinal tasks.

Temporal Language Modeling: Many of the above tasks involve timestamps, which can enhance change detection through temporal dynamics. However, little research in NLP leverages time intervals and those who do assume equidistant time intervals between events (Ma and Gao, 2020; Tsakalidis and Liakata, 2020). Other work on temporal modelling has relied on hand crafted periodic task-specific time features (Kwon et al., 2013), concatenation of timestamp with linguistic representations (Tseriotou et al., 2023, 2024) or Hawkes temporal point process applied on top of recurrence (Guo et al., 2019; Hills et al., 2023). These approaches applied on top of LM representations miss the opportu-

¹https://github.com/ttseriotou/tempoformer

nity of training representations informed by temporal dynamics. Additionally, transformer-based models lack temporal sensitivity (Lazaridou et al., 2021; Loureiro et al., 2022). Rosin and Radinsky (2022) has conditioned attention weights on time, while Rosin et al. (2022); Wang et al. (2023) concatenated time tokens to text sequences. Although these methods create time-specific contextualised embeddings, they utilise absolute points in time rather than leveraging the temporal distance between units of textual information, important for context-aware and longitudinal tasks. Here we adapt the transformer attention mechanism to cater for the relative temporal aspect (§3.5).

Hierarchical Models: Long content modeling approaches have leveraged transformer or attentionbased blocks hierarchically on long documents, on input chunks/sentences and then on the sequence of such chunks (Zhang et al., 2019c; Pappagari et al., 2019; Wu et al., 2021; Li et al., 2023). This produces chunk-level summary embeddings, which preserve both the local and global aspects of contextualised representations. Here we leverage such local and global context dynamics to more efficiently model linguistic streams.

3 Methodology

Here we introduce the TempoFormer architecture. We first provide the problem formulation (\$3.1), followed by model overview (\$3.2) and then discuss the various model components (\$3.3-3.7).

3.1 Problem Formulation

A fundamental concept underpinning longitudinal tasks is that of timelines, P, defined as chronologically ordered units of information between two dates (Tsakalidis et al., 2022b), here either in the form of a sequence of users' posts, a conversation or an online thread. Specifically the cth timeline, P^c , consists of a series of posts², u_i , each with a corresponding timestamp, t_i . $P^c =$ $[\{u_0, t_0\}, \{u_1, t_1\}, ..., \{u_{N-1}, t_{N-1}\}]$. The length of the timeline, N, can vary. We formulate the problem of assessing textual units in a timeline as early-stage, real-time classification, following Tseriotou et al. (2023). We map each *timeline* into Ntraining samples, that we call streams. Each stream contains a predefined window, w, of the most recent posts and a label for the most recent post:

$$([\{u_{i-w+1}, t_{i-w+1}\}, ..., \{u_{i-1}, t_{i-1}\}, \{u_i, t_i\}], l_i).$$

3.2 TempoFormer Overview




Figure 2: TempoFormer Architecture on 5-post window.

Fig. 2 provides an overview of **TempoFormer**. Its hierarchical architecture consists of three main modules, temporally-aware enhancement in multihead attention to model the temporal distance between posts and a classification head. The modules are: **post-level (local) encoding** (§3.3) – obtaining word-level representation of each post using BERT's first 10 layers; **stream (global) encoding** (§3.4) – modeling the sequential and temporal interactions between posts; and **context-enhanced encoding** (§3.6) – fusing stream-awareness in post-level representations to make them context-aware.

3.3 Post-level Encoding (Local)

Each training instance is a stream consisting of the current post and its recent history, alongside corresponding timestamps: $[{\mathbf{u}_{i-w+1}, t_{i-w+1}}, ..., {\mathbf{u}_{i-1}, t_{i-1}}, {\mathbf{u}_i, t_i}],$ with a total of w posts in a stream. Timestamps are ignored at this stage. This stream of posts is converted into a stream, e, of word-level embeddings of word sequence length K via the word and position embedding layer of BERT: $\{\{\mathbf{e}_{1,i-w+1},\mathbf{e}_{2,i-w+1}...,\mathbf{e}_{K,i-w+1}\},...\}$ $\{\mathbf{e}_{1,i}, \mathbf{e}_{2,i}, \dots, \mathbf{e}_{K,i}\}$]. Specifically, in this module, the posts of each stream pass without post-post interactions via the first 10 BERT layers, resulting in hidden word-level representations for each post. Note that since a post is part of multiple streams through their window, it will pass through the BERT layers as part of each corresponding stream. For each post j (belonging to a stream q), the word-level representations from the z-th

 $^{^{2}}$ We use terms *posts* and *utterances* interchangeably as the exact nature of the textual unit depends on the specific task.

Transformer layer are denoted as: $\mathbf{H}_{j_q}^z$ Therefore at the 10-th layer we reconstruct the stream and form local stream representation: $[\mathbf{H}_{i-w+1}^{10},...,\mathbf{H}_{i}^{10}]$.

3.4 Stream-level Encoding (Global)

Inspired by Wu et al. (2021), who model long documents hierarchically by stacking transformer-based layers of sentence, document and document-aware embeddings, we build stream and context-enhanced layers on top of post-level representations. At the stream encoding layer, we capture inter-stream dynamics. Stream-level position embeddings (PE), s¹⁰, added after the 10-th layer, encode post order within the stream. By then passing the word-level stream PE representations to another BERT layer, we obtain word-level sequence-aware updated hidden representations [$\mathbf{H}_{1,i-w+1}^{11}, ..., \mathbf{H}_{1,i}^{11}$].

Next, we obtain the order-aware [CLS] token from the stream and apply **Temporal Rotary Multi-head Attention** (MHA), a proposed variation of RoFormer (Su et al., 2024), which accounts for the *temporal* rather than the *sequential* distance between posts (see §3.5). These context-aware, temporally-enhanced tokens are fed back to replace the respective [CLS] tokens in the hidden representations from the previous BERT layer, resulting in $[\mathbf{H}_{1,i-w+1}^{'11},...,\mathbf{H}_{1,i}^{'11}]$. This enables the propagation of the learnt stream embeddings to the post-level.

3.5 Temporal Rotary Multi-Head Attention

BERT relies on positional embeddings to meaningfully encode the sequential order of words which are then fused via self-attention. Such embeddings are absolute (position-specific) and lack a relative sense. Su et al. (2024) proposed the Rotary Position Embeddings (RoPE) that incorporate the *relative* position between tokens within self-attention. Besides flexibility (in terms of sequence length generalisability), this introduces in the formulation intuitive inter-token dependency, which decays with increasing token distance. Given the attention formulation Attn($\mathbf{Q}, \mathbf{K}, \mathbf{V}$)_m = $\frac{\sum_{n=1}^{N} (\exp(\mathbf{q}_m^T \mathbf{k}_n / \sqrt{d})) \mathbf{v}_n}{\sum_{n=1}^{N} (\exp(\mathbf{q}_m^T \mathbf{k}_n / \sqrt{d}))}$, where m/n denote the query/key positions, after applying RoPE self-attention, the $\mathbf{q}_m^T \mathbf{k}_n$ becomes:

$$\mathbf{q}_m^T \mathbf{k}_n = (R_{\theta,m}^d \mathbf{q}_m)^T (R_{\theta,n}^d \mathbf{k}_n) = \mathbf{q}_m^T R_{\theta,n-m}^d \mathbf{k}_n, \quad (1)$$

where $R_{\theta,m}^d$ is the rotary matrix with *d* embedding dimensions and the following formulation:

	$\begin{pmatrix} \cos(m\theta_1)\\ \sin(m\theta_1) \end{pmatrix}$	$\frac{-\sin(m\theta_1)}{\cos(m\theta_1)}$	0 0	$\begin{pmatrix} 0 \\ 0 \end{pmatrix}$
$R^d_{\theta,m} =$:	·	·	:
	0	0	$\cos(m\theta_{d/2})$	$-\sin(m\theta_{d/2})$ $\cos(m\theta_{d/2})$
	0	0	$\sin(m\theta_{d/2})$	$\cos(m\theta_{d/2})$

where $\theta_i = 10000^{-2(i-1)/d}i \in [1, 2, ..., d/2]$. The rotary matrix incorporates the relative position information through rotation of q and k based on their position in the sequence. The dot product decreases as the tokens move further apart. In Eq. 1, the formulation results in the relative position (m - n), so the rotation between the 6-th and the 3-rd tokens is the same as between the 7-th and the 4-th ones.

Here, in order to model the temporal dynamics, we propose a novel variation of Eq. 1, named Temporal Rotary Multi-head Attention, making use of the relative position property. Instead of $R^d_{\theta,n-m}$, we reformulate the rotary matrix to model the temporal, rather than the positional differences, $R^d_{\theta, \mathbf{t_n}-\mathbf{t_m}}$. We employ it on the stream-level using the [CLS] tokens to capture the stream global context through both the temporal and linguistic dynamics. The developed layer includes solely selfattention without the need for feed-forward and normalisation layers. In practice, since we measure time in seconds, we log-transform time in order to remove task dependancies on the scale of temporal propagation, to account for stream non-linearities and to alleviate exclusion of temporal outliers.

3.6 Context-enhanced Encoding

Literature has shown the effectiveness of enhancing word-level representations hierarchically through context-level learnt dynamics (Zheng et al., 2020; Wu et al., 2021; Ng et al., 2023). To this effect we introduce a second-layer of stream-level position embeddings, s^{11} , to re-instate the absolute sequence position of each post for context-enhanced modeling. These are fed into a global contextaware layer, essentially a word-level transformer layer. Since the [CLS] tokens of each post are stream-aware, they contextualise the token-level representations based on the temporal and global learnt dynamics, obtaining: $[\mathbf{H}_{1,i-w+1}^{12},...,\mathbf{H}_{1,i}^{12}]$. To fully model the stream dynamics given the now context-enhanced [CLS] tokens, we employ a last layer of Temporal Rotary MHA resulting in $[\mathbf{H}_{1,i-w+1}^{'12},...,\mathbf{H}_{1,i}^{'12}]$. Lastly, we adapt the Gated Context Fusion (Gate&Norm) mechanism

by Zheng et al. (2020) to fuse both the utterance word-level informed (\mathbf{H}_{CLS}^{12}) and the stream utterance-level informed ($\mathbf{H}_{CLS}^{'12}$) [CLS] tokens through element-wise multiplication \odot :

$$\begin{split} \mathbf{g} &= \sigma\big(W_g[\mathbf{H}_{CLS}^{12};\mathbf{H}_{CLS}^{12}]\big)\\ \mathbf{C}_{CLS}^G &= \mathrm{LayerNorm}[(1-\mathbf{g})\odot H_{CLS}^{12} + \mathbf{g}\odot H_{CLS}^{\prime 12}] \end{split}$$

3.7 Network Fine-Tuning

Although the proposed architecture can in principle be applied to any Transformer-based model, we select BERT (Devlin et al., 2018) as the foundation model and initialise all word-level weights. Literature on longitudinal context-aware classification has shown the importance of efficiently combining the current utterance with historical information (Sawhney et al., 2020, 2021a; Tseriotou et al., 2023). We thus concatenate the local streamagnostic [CLS] token of the current utterance from the 10-th layer, \mathbf{C}_{CLS}^{L} , (obtained through typical BERT Pooling) with the obtained global streamenhanced [CLS], \mathbf{C}_{CLS}^{G} (Fig. 2). This final representation is fed through two fully connected layers with ReLU activation and dropout (Srivastava et al., 2014). The architecture is fine-tuned for each classification task (§4) using alpha-weighted focal loss (Lin et al., 2017), to assign more importance to minority classes and alleviate class imbalance.

4 **Experiments**

4.1 Tasks and Datasets

We test our model on three different longitudinal tasks of different temporal granularity: 1) **Stance Switch Detection** – identification of switches in overall user stance around a social media claim, 2) **Moments of Change (MoC)** – identification of mood changes through users' online posts and 3) **Conversation Topic Shift** – conversation diversion identification. We adopt a real-time prediction formulation (see §3.1) to assess system ability to perform early change detection in real-world scenarios. Table 1 provides the detailed statistics of each dataset showing the different degree of temporal granularity and dataset specifics. More details are provided in Appendix A.

Stance Switch Detection: Introduced by Tseriotou et al. (2024) this binary classification task tracks the support of posts towards a rumourous claim to identify switches in the overall stance. We use the **LRS** dataset based on RumourEval-2017 (Gorrell et al., 2019) and use *N-Sw*: to denote absence of

switch and *Sw*: (switch) to denote a shift in the number of opposing vs supporting posts.

Moments of Change (MoC): Introduced by Tsakalidis et al. (2022b) this 3-class classification task assesses the mood changes of users given their online posting timelines. We use the **TalkLife** dataset with: *IS*: (switches) sudden mood shift from positive to negative (or v.v.); *IE*: (escalations) gradual mood progression from neutral or positive/negative to more positive/negative; and *O*: no mood change. In both datasets each post is accompanied by its timestamp.

Conversation Topic Shift: Given a corpus of conversations between humans, this binary classification task identifies utterance relevance to the main conversation topic versus another (derailment). We use the **Topic Shift-MI** (Mixed-Initiative) dataset (Konigari et al., 2021) annotated on a subset of Switch-board (Godfrey et al., 1992; Calhoun et al., 2010). This has a single but different major topic for each conversation, with *M*: (major) utterances belonging to the main topic and *R*: (rest) utterances that pertain to a different topic. Here conversations are not timestamped.

Dataset	LRS	TalkLife	Topic Shift MI
# Data Points	5,568	18,604	12,536
# Timelines	325	500	74
Mean (median)	17.1	37.2	169.4
Timeline Length in Posts	(13)	(30)	(153.5)
Mean (median)	1h 26m 40s	6h 51m 11s	-
Time inbetween Posts	1m 39s	59m 38s	(-)
Mean (median)	6.5	IS:1.8, IE:4.0	60.5
# Minority Events/Timeline	(0)	(IS:1, IE:1)	(51.5)

Table 1: Statistics of Datasets.

4.2 Baselines and Experimental Setup

We select baselines that are both *post-level* and *stream-level* (current post and recent history window, see §3.1).

<u>Post-level</u>: **Random**: post classification based on class distribution. **BERT/RoBERTa**: BERT (Devlin et al., 2018) or RoBERTa (Liu et al., 2019) fine-tuned using focal loss (Lin et al., 2017).

Llama2-7B-U (5/10-shot): Llama2-7B-chat-hf LLM (Touvron et al., 2023) with a crafted prompt for each dataset and few-shot (5/10) examples based on the distribution of input text, randomly sampled from each label distribution of each dataset, following Min et al. (2022). MistralInst2-7B-U(5/10-shot): MistralInst2-7B-U (Jiang et al., 2023): LLM with few shot examples. Same setting as for Llama2-7B-chat.

Stream-level: FFN History: Feed-forward on the concatenation of SBERT (Reimers and Gurevych, 2019) embeddings of the current post and the average of the window stream. SWNU (Tseriotou et al., 2023): feeds convolution-informed expanding path signature streams of SBERT representations and time into a BiLSTM modeling information progression. Seq-Sig-Net (Tseriotou et al., 2023): Sequential Network of SWNU modeled through a BiL-STM for long-term dependencies. BiLSTM: with a single layer on window stream SBERT embeddings. Llama2-7B-S (5-shot): Few-shot Llama2-7B-chathf prompted with the recent history of window 5 provided with each shot for context. MistralInst2-7B-S (5/10-shot): Same context-based setting as for Llama2-7B-S using Mistral-7B-Instruct-v0.2.

Evaluation: In line with published literature we report F1 scores for model performance, per class and macro-averaged. For each dataset we perform 5-fold cross validation with train/dev/test sets consisting of different timelines. We run and report the performance of each model on the exact same four random seeds (0,1,12,123) and report the average result on the test set. Appendix D provides information about implementation details and hyperparameter search.

5 Results and Discussion

5.1 Comparison against baselines

We present results for TempoFormer and baselines in Table 2. TempoFormer is the most performant in all three tasks based on macro-averaged F1. We note that recurrent models based on pre-trained BERT representations (BiLSTM for LRS and Topic Shift MI and Seq-Sig-Net for TalkLife), ranked second best. These models have been the SOTA for these datasets (Tseriotou et al., 2023, 2024). While the datasets are of different sizes, temporal characteristics, timeline length and change event distribution (see Table 1), TempoFormer retains its high performance, showcasing its generalisability for real-time change detection. Importantly, our model has the highest F1 for all minority classes, with the exception of Topic Shift MI, where other baselines have higher class-specific F1 scores for M but much lower F1 for R. Since TempoFormer operates on a contextual window of recent posts we select the appropriate window for each stream based on a window analysis, reported in §5.2.

We distinguish baselines into post and streamlevel ones, noticing that smaller fine-tuned Lan-




Figure 3: TempoFormer Results for Different Contextual Window Sizes.

guage Models, even as simple as an FFN, allowing for stream-level context, score consistently better than post-level ones - with the exception of RoBERTa for TalkLife. This consistent finding underscores the importance of developing contextually informed representations for change detection. Few-shot prompted LLMs have consistently lower performance than smaller fine-tuned LMs, in line with reported poor temporal abilities of LLMs (Jain et al., 2023; Bian et al., 2023). For post-level, while Mistral's performance improved from 5 to 10-shot, it is still barely above the random baseline and significantly behind BERT and RoBERTa. For LRS and Topic Shift MI the stream-level 5 and 10-shot Mistral performance increases, but falls way short of BERT/RoBERTa and all the streamlevel models, indicating that although sequential context is important it is not modelled appropriately using LLMs. In line with (Wenzel and Jatowt, 2024), Llama2 suffers from generating responses outside the predefined classes, resulting in very low performance. TempoFormer demonstrates a generalisable architecture that enhances word-level post representations given the context, while modelling effectively the interplay between linguistic and temporal dynamics.

5.2 Window Length

Since stream-based models operate on recent context, selecting appropriate contextual windows to include in the stream is important. Following Tseriotou et al. (2024) we determine window selection based both on model performance and dataset characteristics. Fig. 3 demonstrates TempoFormer's

			LR	s		Т	alkLif	e	Topic Shift MI		
	Model	N-Sw	Sw	macro-avg	IE	IS	0	macro-avg	M	R	macro-avg
	Random	61.4	37.5	49.5	11.2	4.5	84.4	33.4	35.9	63.9	49.9
	Llama2-7B-U (5-shot)	22.4	50.6	36.5	10.1	7.5	31.9	16.5	46.6	45.4	46.0
vel	MistralInst2-7B-U (5-shot)	71.4	28.0	49.7	23.3	4.1	67.8	31.7	46.4	44.6	45.5
t-le	Llama2-7B-U (10-shot)	8.8	52.5	30.7	12.8	6.2	31.3	16.7	48.5	39.5	44.0
Post-level	MistralInst2-7B-U (10-shot)	71.2	30.5	50.8	27.6	3.5	72.1	34.4	42.6	55.7	49.1
-	BERT	69.0	45.3	57.1	43.9	28.1	86.8	52.9	36.0	70.0	53.0
	RoBERTa	68.2	46.4	57.3	46.3	30.4	86.6	54.4	34.5	70.2	52.4
	FFN History	71.6	52.8	62.2	45.4	27.1	88.0	53.5	39.4	70.1	54.8
	SWNU	75.5	55.5	65.5	48.0	29.3	89.5	55.6	38.7	66.0	52.3
vel	Seq-Sig-Net	74.7	58.9	66.8	48.4	30.2	89.5	56.0	37.4	66.7	52.1
Stream-level	BiLSTM	75.0	60.7	67.8	46.1	27.0	89.2	54.1	37.8	73.8	55.8
an	Llama2-7B-S (5-shot)	2.2	50.2	26.2	15.5	7.6	24.2	15.7	52.6	1.3	27.0
Stre	MistralInst2-7B-S (5-shot)	58.3	50.2	54.3	22.0	4.6	70.0	32.2	42.3	57.3	49.8
	MistralInst2-7B-S (10-shot)	54.4	51.8	53.1	23.4	3.5	74.9	33.9	37.8	63.7	50.8
	TempoFormer (ours)	75.9	62.0	68.9	50.0	32.4	88.8	57.1	41.6	70.7	56.1

Table 2: (Best) F1-scores across all tasks. Stream-level models are applied on the optimal window, per dataset.

F1 performance on windows of 5, 10 and 20 recent posts (see Table 11 for full results). While LRS and Topic Shift MI both benefit from the large window of 20 posts (blue) with clear performance gains overall and for the minority classes, TalkLife demonstrates better performance over a window of 10 (green). The optimal window findings for LRS and TalkLife are consistent with (Tseriotou et al., 2024). These differences are attributed to dataset characteristics (Table 1) and the mean number of change events in timelines, which need to be captured within the contextual windows. This analysis informs our stream-level experiments and at the same time demonstrates the flexibility of Tempo-Former with respect to contextual window length. We recommend exploratory analysis according to dataset characteristics for appropriate window selection for new datasets.

5.3 Ablations Study

In Table 3 we present an ablation study to assess each of TempoFormer's components.

Temporal Rotary Multi-head Attention (MHA): By using the vanilla sequential distance version of RoPE in Multi-head attention instead of the temporal one, for the timestamped datasets, we see a drop in performance. This showcases the advantage of modeling linguistic streams while accounting for their temporal dynamics and the success of temporally distant RoPE. The relatively small drop in performance is due to the secondary role of temporal dynamics compared to the linguistic evolution in change detection.

RoPE MHA: By further replacing the RoPE MHA with the vanilla version of MHA we see a significant drop in performance (in macro-avg): -2.9% for LRS, -1.2% for TalkLife and -0.6% for Topic Shift MI, demonstrating the success of RoPE on its

LRS				1	alkLife	2	Topic Shift MI		
I-Sw	Sw	macro-avg	IE	IS	0	macro-avg	Μ	R	macro-avg
75.9	62.0	68.9	50.0	32.4	88.8	57.1	41.6	70.7	56.1
75.5	62.0	68.7	49.3	31.7	88.7	56.6	-	-	-
74.1	57.9	66.0	48.0	31.5	88.2	55.9	39.6	71.4	55.5
75.4	59.0	67.2	49.4	31.7	89.2	56.8	38.9	70.5	54.7
74.5	61.3	67.9	49.8	31.1	88.7	56.6	40.7	69.6	55.2
7777	5.5 4.1 5.4	-Sw Sw 5.9 62.0 5.5 62.0 4.1 57.9 5.4 59.0	Sw Sw macro-avg 5.9 62.0 68.9 5.5 62.0 68.7 4.1 57.9 66.0 5.4 59.0 67.2	Sw Sw macro-avg IE 5.9 62.0 68.9 50.0 5.5 62.0 68.7 49.3 4.1 57.9 66.0 48.0 5.4 59.0 67.2 49.4	Sw Sw macro-avg IE IS 5.9 62.0 68.9 50.0 32.4 5.5 62.0 68.7 49.3 31.7 4.1 57.9 66.0 48.0 31.5 5.4 59.0 67.2 49.4 31.7	Sw macro-avg IE IS O 5.9 62.0 68.9 50.0 32.4 88.8 5.5 62.0 68.7 49.3 31.7 88.7 4.1 57.9 66.0 48.0 31.5 88.2 5.4 59.0 67.2 49.4 31.7 89.2	-Sw Sw macro-avg IE IS O macro-avg 5.9 62.0 68.9 50.0 32.4 88.8 57.1 5.5 62.0 68.7 49.3 31.7 88.7 56.6 4.1 57.9 66.0 48.0 31.5 88.2 55.9 5.4 59.0 67.2 49.4 31.7 89.2 56.8	Sw macro-avg IE IS O macro-avg M 5.9 62.0 68.9 50.0 32.4 88.8 57.1 41.6 5.5 62.0 68.7 49.3 31.7 88.7 55.6 - 4.1 57.9 66.0 48.0 31.5 88.2 55.9 39.6 5.4 59.0 67.2 49.4 31.7 89.2 56.8 38.9	Sw macro-avg IE IS O macro-avg M R 5.9 62.0 68.7 50.0 32.4 88.8 57.1 41.6 70.7 5.5 62.0 68.7 49.3 31.7 88.7 56.6 - 4.1 57.9 66.0 48.0 31.5 88.2 55.9 39.6 71.4 5.4 59.0 67.2 49.4 31.7 89.2 56.8 38.9 70.5

Table 3: Ablation Studies for TempoFormer based on F1 with one component ablated at a time for all datasets.

own. We postulate that this signifies the ability of RoPE to enable MHA integration in architectures without the need for normalisation and FFN in a full transformer layer.

Stream embeddings: Removing these embeddings from TempoFormer layers brings noticeable performance drops in all datasets, showcasing the importance of propagating position information in building stream-aware and context-enhanced post embeddings. Topic Shift MI shows the largest drop of -1.4% among all its ablated models. Since this dataset does not obtain sequential signal from temporal dynamics, it relies on stream embeddings to model the distance between consecutive posts.

Gate&Norm operation updates the stream postlevel [CLS] tokens with post word-level information, which is better informed by the word-level dynamics. This fuses together the word and stream dynamics in a gated learnable way. Large performance drops for all tasks when we ablate this component shows the importance of multi-level fusion.

5.4 The curious case of recurrence

Since longitudinal and change detection models have so far heavily relied on recurrence-based architectures, we evaluate the effect of recurrence on models jointly trained for stream and post-level representations. To do so we adapt RoBERT (Pappagari et al., 2019), originally developed for long document classification, which applies recurrence over BERT's pooled [CLS] for each post. Here, we pro-

		LR	s	TalkLife				Topic Shift MI		
model	N-Sw	Sw	macro-avg	IE	IS	0	macro-avg	М	R	macro-avg
TempoFormer	75.9	62.0	68.9	50.0	32.4	88.8	57.1	41.6	70.7	56.1
RoBERT	75.8	62.3	69.0	36.7	3.3	88.4	42.8	33.3	75.7	54.5
RoTempoFormer	76.2	63.6	69.9	47.1	27.5	88.3	54.3	36.6	73.2	54.9

Table 4: Results (macro-avg F1) on Recurrentbased Language Models, including TempoFormer (nonrecurrent) for comparison. **Best** scores are marked.

Dataset	BERTScore ↓	Cosine Sim. \downarrow	Outlier ↑		
LRS	.457	.245	.867		
TalkLife	.358	.123	.934		
Topic Shift MI	.385	.188	.896		

Table 5: Diversity Scores per Dataset.

pose RoTempoFormer, a modification of RoBERT, that uses recurrence over TempoFormer's pooled [CLS] for each post. Both RoBERT and RoTempo-Former are stream-level, recurrence-based models. We report results in Table 4.

RoTempoFormer consistently outperforms RoBERT for all datasets. RoTempoFormer strikes the right balance between jointly modeling context-aware post representations and recurrence in stream dynamics. Only for LRS do recurrencebased models have a better performance than TempoFormer. To examine this phenomenon we measure the diversity of each dataset with respect to its content and report it in Table 5. We report the BERTScore (Zhang et al., 2019b) and Cosine similarity between SBERT pairs of representations as well as the Outlier metric (Larson et al., 2019; Stasaski et al., 2020) on SBERT which measures the Euclidean distance between the (unseen) posts in the test set and the mean training corpus across folds and seeds for all datasets. Thus we assess both the semantic diversity and test set diversity. Across all metrics we consistently see that TalkLife is the most and LRS the least diverse. We postulate that for more diverse datasets like TalkLife, RoBERT has a really low performance, while it performs much better on less diverse ones. This could be due to: 1) overfitting due to recurrence and 2) inability of RoBERT to jointly model diverse context-aware representations, while capturing their evolution. RoTempoFormer, maintains its high performance, striking a good balance between modeling the context-aware post-level and the timeline-level dynamics. Importantly, we show that TempoFormer can be used as the foundation for temporal representation learning in other architectures.

model	IE	IS	0	macro-avg
BERT	43.9	28.1	86.8	52.9
RoBERTa	46.3	30.4	86.6	54.4
TempoFormer (BERT)	50.0	32.4	88.8	57.1
TempoFormer (RoBERTa)	52.4	36.9	87.3	58.8

Table 6: Results (macro-avg F1) on TalkLife using BERT *vs* RoBERTa as the base model for TempoFormer.

5.5 Model Adaptability

To examine the flexibility of the TempoFormer stream-level and context-enhanced layers beyond the BERT architecture, we use TempoFormer with RoBERTa (roberta-base). Specifically, we allow the first 10 RoBERTa layers to model post-level (local) dynamics and modify its top two layers to capture stream dynamics. Since in Table 2, TalkLife benefits from the use of RoBERTa over BERT at the post-level, we examine if this gain also transfers to the TempoFormer. Summarising results in Table 6, we show that the RoBERTa-based TempoFormer achieves a new SOTA of 58.8% macro-avg F1, +1.7% over the BERT-based TempoFormer. This increase is in line with the +1.5% performance increase between vanilla BERT and RoBERTa macroavg F1. Importantly, the increase in overall F1 is driven by clear performance gains in the IE and IS minority classes, further demonstrating the success and adaptable nature of TempoFormer in identifying changes over time.

6 Conclusion

We introduce TempoFormer, a transformer-based model for change detection operating on textual (timestamped) streams. Importantly we do so by avoiding recurrence, and only modifying the last two layers of the transformer. Furthermore, TempoFormer has the ability to model the temporal distance between textual units through a modification of rotary positional embeddings. The model achieves new SOTA, outperforming recurrent and LLM-based models on three different change detection tasks with datasets of varying temporal granularity and linguistic diversity, without loss in generalisability. We demonstrate its usability as a foundation model in other architectures, striking the right balance between word-level, post-level and stream-level linguistic and temporal dynamics. Lastly, we showcase its flexibility in terms of base model integration, further boosting stream-level performance on par with post-level gains.

Limitations

While TempoFormer shows SOTA performance on three different tasks and datasets of diverse temporal granularity involving change detection, namely: social media overall stance shift, user mood change detection and open conversation major topic shift detection, we are yet to evaluate its performance on a wider range of tasks and datasets. Additionally, although we demonstrate strong performance in datasets as small as 5,500 data points, we believe that our model, as most machine learning models, benefits from larger corpora in training where we can more meaningfully fine-tune the inter and intrapost relationships to model the dataset's linguistic style and change intricacies. TempoFormer models post dynamics through a predefined stream window, identified through understanding the characteristics of a dataset via preliminary experiments. The need for initial exploration can be limiting compared to a dynamic window setting. Furthermore, despite the fact that our implementation is flexible and can be applied to different encoder architectures, the codebase is built in PyTorch, therefore imposing the constraint of PyTorch-only frameworks. On the classification front, we operate on a supervised setting therefore assuming the availability of annotated data which can be expensive to obtain especially from experts. Regarding evaluation, we focus on post-level metrics, and have not yet considered metrics more appropriate for longitudinal tasks and streams (Tsakalidis et al., 2022b). Lastly, since our model operates by finetuning a pre-trained transformer-based model, like BERT, it automatically assumes the availability of such model in the language of the dataset/interest (English in our case), which might not be the case for low-resource languages.

Ethics Statement

The performance of our model, TempoFormer, is demonstrated on three datasets: LRS, TalkLife and Topic Shift MI. The LRS dataset is based on the publicly available RumourEval 2017 dataset (Gorrell et al., 2019) for stance detection, while the Topic Shift MI dataset is also a publicly available dataset based on human to human open domain conversations. Since the TalkLife dataset contains sensitive and personal user data, the appropriate Ethics approval was received from the Institutional Review Board (IRB), followed by data anonymisation and appropriate sensitive data sharing procedures. Access to this dataset was granted and approved by TalkLife ³ through licensing for research purposes associated with the corresponding submitted proposal. All examples in the paper are paraphrased. Models were built on a secure server with authorised user-only access, while the labeled TalkLife dataset and the developed models are not indented to be made publicly available in order avoid any potential risks of unintended use.

References

- Hassan Alhuzali and Sophia Ananiadou. 2021. Spanemo: Casting multi-label emotion classification as span-prediction. *arXiv preprint arXiv:2101.10038*.
- Robert Bamler and Stephan Mandt. 2017. Dynamic word embeddings. In *International conference on Machine learning*, pages 380–389. PMLR.
- Ning Bian, Xianpei Han, Le Sun, Hongyu Lin, Yaojie Lu, Ben He, Shanshan Jiang, and Bin Dong. 2023. Chatgpt is a knowledgeable but inexperienced solver: An investigation of commonsense problem in large language models. *arXiv preprint arXiv:2303.16421*.
- Andrew Brown, Jiading Zhu, Mohamed Abdelwahab, Alec Dong, Cindy Wang, and Jonathan Rose. 2024. Generation, distillation and evaluation of motivational interviewing-style reflections with a foundational language model. arXiv preprint arXiv:2402.01051.
- Sasha Calhoun, Jean Carletta, Jason M Brenier, Neil Mayo, Dan Jurafsky, Mark Steedman, and David Beaver. 2010. The nxt-format switchboard corpus: a rich resource for investigating the syntax, semantics, pragmatics and prosody of dialogue. *Language resources and evaluation*, 44:387–419.
- Jonathan P Chang and Cristian Danescu-Niculescu-Mizil. 2019. Trouble on the horizon: Forecasting the derailment of online conversations as they develop. *arXiv preprint arXiv:1909.01362*.
- Zheng Chu, Jingchang Chen, Qianglong Chen, Weijiang Yu, Haotian Wang, Ming Liu, and Bing Qin. 2023. Timebench: A comprehensive evaluation of temporal reasoning abilities in large language models. *arXiv preprint arXiv:2311.17667*.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. arXiv preprint arXiv:1810.04805.
- Shang Gao, Mohammed Alawad, M Todd Young, John Gounley, Noah Schaefferkoetter, Hong Jun Yoon, Xiao-Cheng Wu, Eric B Durbin, Jennifer Doherty,

³https://www.talklife.com/

Antoinette Stroup, et al. 2021. Limitations of transformers on clinical text classification. *IEEE journal of biomedical and health informatics*, 25(9):3596– 3607.

- John J Godfrey, Edward C Holliman, and Jane Mc-Daniel. 1992. Switchboard: Telephone speech corpus for research and development. In Acoustics, speech, and signal processing, ieee international conference on, volume 1, pages 517–520. IEEE Computer Society.
- Genevieve Gorrell, Elena Kochkina, Maria Liakata, Ahmet Aker, Arkaitz Zubiaga, Kalina Bontcheva, and Leon Derczynski. 2019. Semeval-2019 task 7: Rumoureval 2019: Determining rumour veracity and support for rumours. In *Proceedings of the 13th International Workshop on Semantic Evaluation: NAACL HLT 2019*, pages 845–854. Association for Computational Linguistics.
- Siwen Guo, Sviatlana Höhn, and Christoph Schommer. 2019. A personalized sentiment model with textual and contextual information. In *Proceedings of the* 23rd conference on computational natural language learning (CoNLL), pages 992–1001.
- Anthony Hills, Adam Tsakalidis, and Maria Liakata. 2023. Time-aware predictions of moments of change in longitudinal user posts on social media. In *International Workshop on Advanced Analytics and Learning on Temporal Data*, pages 293–305. Springer.
- Raghav Jain, Daivik Sojitra, Arkadeep Acharya, Sriparna Saha, Adam Jatowt, and Sandipan Dandapat. 2023. Do language models have a common sense regarding time? revisiting temporal commonsense reasoning in the era of large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 6750–6774.
- Shaoxiong Ji, Matti Hölttä, and Pekka Marttinen. 2021. Does the magic of bert apply to medical code assignment? a quantitative study. *Computers in biology and medicine*, 139:104998.
- Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. 2023. Mistral 7b. *arXiv preprint arXiv:2310.06825*.
- Rohit Kumar Kaliyar, Anurag Goswami, and Pratik Narang. 2021. Fakebert: Fake news detection in social media with a bert-based deep learning approach. *Multimedia tools and applications*, 80(8):11765– 11788.
- Yova Kementchedjhieva and Anders Søgaard. 2021. Dynamic forecasting of conversation derailment. *arXiv preprint arXiv:2110.05111*.
- Diederik P Kingma and Jimmy Ba. 2014. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*.

- Rachna Konigari, Saurabh Ramola, Vijay Vardhan Alluri, and Manish Shrivastava. 2021. Topic shift detection for mixed initiative response. In *Proceedings* of the 22nd Annual Meeting of the Special Interest Group on Discourse and Dialogue, pages 161–166.
- Sumeet Kumar and Kathleen M Carley. 2019. Tree lstms with convolution units to predict stance and rumor veracity in social media conversations. In *Proceedings of the 57th annual meeting of the association for computational linguistics*, pages 5047–5058.
- Sejeong Kwon, Meeyoung Cha, Kyomin Jung, Wei Chen, and Yajun Wang. 2013. Prominent features of rumor propagation in online social media. In 2013 IEEE 13th international conference on data mining, pages 1103–1108. IEEE.
- Viet Dac Lai, Tuan Ngo Nguyen, and Thien Huu Nguyen. 2020. Event detection: Gate diversity and syntactic importance scoresfor graph convolution neural networks. *arXiv preprint arXiv:2010.14123*.
- Stefan Larson, Anish Mahendran, Andrew Lee, Jonathan K Kummerfeld, Parker Hill, Michael A Laurenzano, Johann Hauswald, Lingjia Tang, and Jason Mars. 2019. Outlier detection for improved data quality and diversity in dialog systems. arXiv preprint arXiv:1904.03122.
- Angeliki Lazaridou, Adhi Kuncoro, Elena Gribovskaya, Devang Agrawal, Adam Liska, Tayfun Terzi, Mai Gimenez, Cyprien de Masson d'Autume, Tomas Kocisky, Sebastian Ruder, et al. 2021. Mind the gap: Assessing temporal generalization in neural language models. *Advances in Neural Information Processing Systems*, 34:29348–29363.
- Jingye Li, Meishan Zhang, Donghong Ji, and Yijiang Liu. 2020. Multi-task learning with auxiliary speaker identification for conversational emotion recognition. *arXiv preprint arXiv:2003.01478*.
- Xianming Li, Zongxi Li, Xiaotian Luo, Haoran Xie, Xing Lee, Yingbin Zhao, Fu Lee Wang, and Qing Li. 2023. Recurrent attention networks for long-text modeling. *arXiv preprint arXiv:2306.06843*.
- Zhenhao Li, Marek Rei, and Lucia Specia. 2022. Multimodal conversation modelling for topic derailment detection. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 5115– 5127.
- Hongzhan Lin, Jing Ma, Mingfei Cheng, Zhiwei Yang, Liangliang Chen, and Guang Chen. 2021. Rumor detection on twitter with claim-guided hierarchical graph attention networks. *arXiv preprint arXiv:2110.04522*.
- Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. 2017. Focal loss for dense object detection. In *Proceedings of the IEEE international conference on computer vision*, pages 2980–2988.

- Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. arXiv preprint arXiv:1907.11692.
- Ilya Loshchilov and Frank Hutter. 2017. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101.*
- Daniel Loureiro, Francesco Barbieri, Leonardo Neves, Luis Espinosa Anke, and Jose Camacho-Collados. 2022. Timelms: Diachronic language models from twitter. arXiv preprint arXiv:2202.03829.
- Terry J Lyons. 1998. Differential equations driven by rough signals. *Revista Matemática Iberoamericana*, 14(2):215–310.
- Jing Ma and Wei Gao. 2020. Debunking rumors on twitter with tree transformer. ACL.
- Jing Ma, Wei Gao, Shafiq Joty, and Kam-Fai Wong. 2020. An attention-based rumor detection model with tree-structured recursive neural networks. *ACM Transactions on Intelligent Systems and Technology* (*TIST*), 11(4):1–28.
- Sewon Min, Xinxi Lyu, Ari Holtzman, Mikel Artetxe, Mike Lewis, Hannaneh Hajishirzi, and Luke Zettlemoyer. 2022. Rethinking the role of demonstrations: What makes in-context learning work? *arXiv preprint arXiv:2202.12837*.
- Boon Liang Clarence Ng, Diogo Santos, and Marek Rei. 2023. Modelling temporal document sequences for clinical icd coding. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 1640–1649.
- Raghavendra Pappagari, Piotr Zelasko, Jesús Villalba, Yishay Carmiel, and Najim Dehak. 2019. Hierarchical transformers for long document classification. In 2019 IEEE automatic speech recognition and understanding workshop (ASRU), pages 838–844. IEEE.
- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. 2019. PyTorch: An imperative style, high-performance deep learning library. *Advances in Neural Information Processing Systems*, 32.
- Rolandos Alexandros Potamias, Georgios Siolas, and Andreas-Georgios Stafylopatis. 2020. A transformerbased approach to irony and sarcasm detection. *Neural Computing and Applications*, 32(23):17309– 17320.
- Shaina Raza and Chen Ding. 2022. Fake news detection based on news content and social contexts: a transformer-based approach. *International Journal of Data Science and Analytics*, 13(4):335–362.
- Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. *arXiv preprint arXiv:1908.10084*.

- Alex Rosenfeld and Katrin Erk. 2018. Deep neural models of semantic shift. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 474–484.
- Guy D Rosin, Ido Guy, and Kira Radinsky. 2022. Time masking for temporal language models. In *Proceedings of the fifteenth ACM international conference on Web search and data mining*, pages 833–841.
- Guy D Rosin and Kira Radinsky. 2022. Temporal attention for language models. In *Findings of the Association for Computational Linguistics: NAACL 2022*, pages 1498–1508.
- Paul Röttger and Janet Pierrehumbert. 2021. Temporal adaptation of bert and performance on downstream document classification: Insights from social media. In *Findings of the Association for Computational Linguistics: EMNLP 2021*, pages 2400–2412.
- Ramit Sawhney, Harshit Joshi, Lucie Flek, and Rajiv Shah. 2021a. Phase: Learning emotional phaseaware representations for suicide ideation detection on social media. In *Proceedings of the 16th conference of the European Chapter of the Association for Computational Linguistics: main volume*, pages 2415–2428.
- Ramit Sawhney, Harshit Joshi, Saumya Gandhi, and Rajiv Shah. 2020. A time-aware transformer based model for suicide ideation detection on social media. In Proceedings of the 2020 conference on empirical methods in natural language processing (EMNLP), pages 7685–7697.
- Ramit Sawhney, Harshit Joshi, Rajiv Shah, and Lucie Flek. 2021b. Suicide ideation detection via social and temporal user representations using hyperbolic learning. In Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 2176–2190.
- Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. 2014. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958.
- Katherine Stasaski, Grace Hui Yang, and Marti A Hearst. 2020. More diverse dialogue datasets via diversityinformed data collection. In *Proceedings of the 58th annual meeting of the association for computational linguistics*, pages 4958–4968.
- Jianlin Su, Murtadha Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. 2024. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro,

Faisal Azhar, et al. 2023. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.

- Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, et al. 2022a. Overview of the clpsych 2022 shared task: Capturing moments of change in longitudinal user posts.
- Adam Tsakalidis and Maria Liakata. 2020. Sequential modelling of the evolution of word representations for semantic change detection. In *Proceedings of the* 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), pages 8485–8497.
- Adam Tsakalidis, Federico Nanni, Anthony Hills, Jenny Chim, Jiayu Song, and Maria Liakata. 2022b. Identifying moments of change from longitudinal user text. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4647–4660.
- Talia Tseriotou, Ryan Chan, Adam Tsakalidis, Iman Munire Bilal, Elena Kochkina, Terry Lyons, and Maria Liakata. 2024. Sig-networks toolkit: Signature networks for longitudinal language modelling. In Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics: System Demonstrations, pages 223–237.
- Talia Tseriotou, Adam Tsakalidis, Peter Foster, Terence Lyons, and Maria Liakata. 2023. Sequential path signature networks for personalised longitudinal language modeling. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 5016– 5031.
- Vaibhav Vaibhav, Raghuram Mandyam Annasamy, and Eduard Hovy. 2019. Do sentence interactions matter? leveraging sentence level representations for fake news classification. *arXiv preprint arXiv:1910.12203*.
- Jonas Wallat, Adam Jatowt, and Avishek Anand. 2024. Temporal blind spots in large language models. *arXiv preprint arXiv:2401.12078*.
- Jiexin Wang, Adam Jatowt, Masatoshi Yoshikawa, and Yi Cai. 2023. Bitimebert: Extending pre-trained language representations with bi-temporal information. In Proceedings of the 46th International ACM SI-GIR Conference on Research and Development in Information Retrieval, pages 812–821.
- Georg Wenzel and Adam Jatowt. 2024. Temporal validity change prediction. *arXiv preprint arXiv:2401.00779*.
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. 2019. Huggingface's transformers: State-ofthe-art natural language processing. *arXiv preprint arXiv:1910.03771*.

- Chuhan Wu, Fangzhao Wu, Tao Qi, and Yongfeng Huang. 2021. Hi-transformer: Hierarchical interactive transformer for efficient and effective long document modeling. *arXiv preprint arXiv:2106.01040*.
- Haoran Yan, Xiaolong Jin, Xiangbin Meng, Jiafeng Guo, and Xueqi Cheng. 2019. Event detection with multiorder graph convolution and aggregated attention. In Proceedings of the 2019 conference on empirical methods in natural language processing and the 9th international joint conference on natural language processing (EMNLP-IJCNLP), pages 5766–5770.
- Ruichao Yang, Jing Ma, Hongzhan Lin, and Wei Gao. 2022. A weakly supervised propagation model for rumor verification and stance detection with multiple instance learning. In *Proceedings of the 45th international ACM SIGIR conference on research and development in information retrieval*, pages 1761–1772.
- Sen Yang, Dawei Feng, Linbo Qiao, Zhigang Kan, and Dongsheng Li. 2019. Exploring pre-trained language models for event extraction and generation. In *Proceedings of the 57th annual meeting of the association for computational linguistics*, pages 5284–5294.
- Jianfei Yu, Jing Jiang, Ling Min Serena Khoo, Hai Leong Chieu, and Rui Xia. 2020. Coupled hierarchical transformer for stance-aware rumor verification in social media conversations. Association for Computational Linguistics.
- Zheng Yuan, Chuanqi Tan, and Songfang Huang. 2022. Code synonyms do matter: Multiple synonyms matching network for automatic icd coding. *arXiv preprint arXiv:2203.01515*.
- Hongfei Zhang, Xia Song, Chenyan Xiong, Corby Rosset, Paul N Bennett, Nick Craswell, and Saurabh Tiwary. 2019a. Generic intent representation in web search. In Proceedings of the 42nd International ACM SIGIR Conference on Research and Development in Information Retrieval, pages 65–74.
- Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q Weinberger, and Yoav Artzi. 2019b. Bertscore: Evaluating text generation with bert. *arXiv preprint arXiv:1904.09675*.
- Xingxing Zhang, Furu Wei, and Ming Zhou. 2019c. Hibert: Document level pre-training of hierarchical bidirectional transformers for document summarization. arXiv preprint arXiv:1905.06566.
- Zaixiang Zheng, Xiang Yue, Shujian Huang, Jiajun Chen, and Alexandra Birch. 2020. Towards making the most of context in neural machine translation. *arXiv preprint arXiv:2002.07982.*

A Dataset Specifics

Since we are following 5-fold cross validation the test set consists of 20% of the datapoints. For LRS and Topic Shift MI the remaining data are split

25%/75% between dev/train sets and for TalkLife they are split 33.3%/66.7% between dev/train sets. The difference between these percentages is in order to ensure that we have substantial training data for LRS and Topic Shift MI in each fold as these are relatively small datasets in size. Splitting between train/dev/test is stratified so that all timeline examples belong only to one of the sets, therefore the above percentages are approximate (not exact).

B Libraries

All experiments were ran under the same Python 3.10.12 environment including these libraries: pandas=1.5.2, matplotlib=3.7.1, pip=23.2.1, scikitlearn=1.2.0, pytorch=2.0.1, pytorch-cuda=11.8, transformers=4.35.0, tokenizers=0.14.1, huggingface-hub==0.20.3

For Seq-Sig-Net and SWNU baselines we used the Sig-Networks package and its environment as reported in Tseriotou et al. (2024).

C Computational Infrastructure

The experiments for the LRS and TalkLife datasets were ran on a machine with 2 NVIDIA A40 GPUs of 48GB GPU RAM each, 96 cores and 256 GB of RAM.

The experiments for the Topic Shift dataset were ran on machine with 3 NVIDIA A30 GPUs of 24GB GPU RAM each, 40 cores and 384 GB of RAM.

D Experimental Details

Implementation Details In our experiments for all models we train on 4 epochs with early stopping and patience 3, gradient accumulation and focal loss with $\gamma = 2$ and alpha of $\sqrt{1/p_t}$ where p_t is the probability of class t in the training data (Tseriotou et al., 2023). For Transformer-based models we use the AdamW optimiser (Loshchilov and Hutter, 2017) and a linear scheduler and for the rest we use the Adam optimiser (Kingma and Ba, 2014). The models are implemented using Pytorch (Paszke et al., 2019).

For TempoFormer we use bert-base-uncased. We build our custom model with Huggingface's (Wolf et al., 2019) BERT classes and RoPE Llama classes (Touvron et al., 2023) as a starting point. All applicable BERT defaults are kept unchanged, using max length of 512 and 12 attention heads. For the classification feedforward-network we use two 64-dimensional layers and a dropout of 0.1 with ReLU. Following an initial space search, learning rate is selected using grid-search on: $[1e^{-5}, 5e^{-6}]$.

BERT/RoBERTa: Fine-tuned versions of bert-base-uncased/roberta-base using a grid search over learning rates of $\in [1e^{-6}, 5e^{-6}, 1e^{-5}]$. **FFN History**: Following Tseriotou et al. (2024), we perform hyperparameter search over learning rates $\in [1e^{-3}, 5e^{-4}, 1e^{-4}]$ and hidden dimensions $\in [[64, 64], [128, 128], [256, 256], [512, 512]]$, over 100 epochs with a batch size of 64 and a dropout rate of 0.1.

SWNU and Seq-Sig-Net: We perform a hyperparameter search over: learning rates \in [0.0005, 0.0003], feed-forward hidden dimensions of the two layers \in [[32, 32], [128, 128]], LSTM hidden dimensions of SWNU units \in [10, 12], convolution-1d reduced dimensions \in [6, 10] and BiLSTM hidden dimensions for Seq-Sig-Net of \in [300, 400]. Models were developed using the log-signature, time encoding in the path as well as concatenated at its output for LRS and TalkLife and sequence index in the path for Topic Shift MI. We use 100 epochs with a batch size of 64 and a dropout rate of 0.1.

BiLSTM: Following Tseriotou et al. (2024), we perform hyperparameter search over learning rates $\in [1e^{-3}, 5e^{-4}, 1e^{-4}]$ and hidden dimensions [200, 300, 400], over 100 epochs with a batch size of 64 and a dropout rate of 0.1.

SBERT: SentenceBERT (SBERT) representations were used for different baselines (Reimers and Gurevych, 2019) in order to obtain semantically meaningful post-level embeddings. We use 384-dimensional embeddings through all-MiniLM-L6-v2 from the sentence_transformers library.

RoBERT: Following Pappagari et al. (2019) we develop RoBERT with the exact same parameters as in the original paper and a grid search through learning rates $\in [1e^{-6}, 5e^{-6}, 1e^{-5}]$. We follow the same grid search for RoTempoFormer.

E LLM Prompts

To construct Mistral classification prompts we follow the recommended classification prompts as per provided guidelines ⁴. For constructing the Llama prompts we experimented with multiple prompts

⁴https://docs.mistral.ai/guides/prompting_ capabilities/#classification

per dataset and identified the ones with the most stable performance. For fairer performance assessment we apply post-processing in LLM predictions to bucket them in the corresponding classification class (e.g. if the LLM generates *esc* we mark it as an *escalation*). In Tables 7, 8, 9, 10 we provide our LLM prompts for the LRS dataset.

F Window Results

Full results for the window analysis are presented in Table 11.

Table 7: MistralInst2-7B-U for n-shot Post/Utterancelevel prompting

MistralInst2-7B-U Template

You are a helpful, respectful and honest assistant for labeling online Twitter conversations between users. Given the online post of a user in a conversation stream around a rumourous claim on a newsworthy event which it is discussed by tweets in the stream, determine if in the current post there is a switch with respect to the overall stance. Answer with "none" for either the absence of a switch or cases where the numbers of supporting and opposing posts are equal and with "switch" for switch between the total number of oppositions (querying or denying) and supports or vice versa. Your task is to assess and categorize post input after <<<>>> into one of the following predefined outputs:

none switch

You will only respond with the output. Do not include the word "Output". Do not provide explanations or notes.

Here are some examples:

Input: post example 1 Output: post label 1 Input: post example n Output: post label n #####
 Table 8: MistralInst2-7B-S for n-shot Stream-level

 prompting

MistralInst2-7B-S Template

You are a helpful, respectful and honest assistant for labeling online Twitter conversations between users. Given the most recent online conversation history between users around a rumourous claim on a newsworthy event, determine if the most recent input user post is a switch with respect to the overall conversation stance. Answer with "none" for either the absence of a switch or cases where the numbers of supporting and opposing posts are equal and with "switch" for switch between the total number of oppositions (querying or denying) and supports or vice versa. Your task is to assess and categorize post input after <<<>>> into one of the following predefined outputs:

none switch

You will only respond with the output. Do not include the word "Output". Do not provide explanations or notes.

####

Here are some examples:

Conversation History:

 u_{a-4} u_{a-3} u_{a-2} u_{a-1} Input: post example 1, u_a Output: post label 1 ... Conversation History: u_{b-4} u_{b-3} u_{b-2} u_{b-1} Input: post example n, u_b Output: post label n ##### Table 9: Llama2-7B-U for n-shot Post/Utterance-levelprompting

Llama2-7B-U Template

 $\langle s \rangle [INST] \langle \langle SYS \rangle \rangle$

You are a helpful, respectful and honest assistant for labeling online Twitter conversations between users.

<</SYS>>

Given the online post of a user in a conversation stream around a rumourous claim on a newsworthy event which it is discussed by tweets in the stream, determine if in the current post there is a switch with respect to the overall stance.

Answer with "none" for either the absence of a switch or cases where the numbers of supporting and opposing posts are equal and with "switch" for switch between the total number of oppositions (querying or denying) and supports or vice versa.

Example 1: Input: *post example 1* Output: *post label 1*

Example n: Input: *post example n* Output: *post label n*

Only return "none" or "switch". Limit the answer to 1 word. [/INST]</s> Table 10: Llama2-7B-S for n-shot Stream-level prompting

Llama2-7B-S Template

 $\langle s \rangle [INST] \langle \langle SYS \rangle \rangle$

You are a helpful, respectful and honest assistant for labeling online Twitter conversations between users.

 $\langle \langle SYS \rangle \rangle$

Given the most recent online conversation history between users around a rumourous claim on a newsworthy event, determine if the most recent input user post is a switch with respect to the overall conversation stance.

Answer with "none" for either the absence of a switch or cases where the numbers of supporting and opposing posts are equal and with "switch" for switch between the total number of oppositions (querying or denying) and supports or vice versa.

Example 1: Conversation History: u_{a-4} u_{a-3} u_{a-2} u_{a-1} Input: post example 1, u_a Output: post label 1 . . . Example n: **Conversation History:** u_{b-4} u_{b-3} u_{b-2} u_{b-1} Input: *post example n*, u_b Output: post label n

Only return "none" or "switch". Limit the answer to 1 word. [/INST] < /s >

		LRS			Talk	Life	Topic Shift			
window	N-Sw	Sw	avg	IE	IS	0	avg	М	R	avg
5	69.9	55.0	62.5	50.1	27.9	88.7	55.6	38.3	71.1	54.7
10	73.0	56.4	64.7	50.0	32.4	88.8	57.1	40.3	71.1	55.7
20	75.9	62.0	68.9	49.5	32.0	88.8	56.8	41.6	70.7	56.1

Table 11: F1 scores for TempoFormer on all datasets for different window sizes. Best scores are marked.