Evaluating near-surface wind speeds simulated by the CRCM6-GEM5 model using AmeriFlux data over North America

Tim Whittaker¹, Alejandro Di Luca¹, Francois Roberge¹, Katja Winger¹

¹Centre pour l'étude et la simulation du climat à l'échelle régionale (ESCER), Département des Sciences de la Terre et de l'Atmosphère, Université du Québec à Montréal, Montréal, Québec, Canada

Key Points:

- Introducing a hierarchy of error metrics significantly alters the conclusions regarding the performance and ranking of the simulations.
- The inclusion of a turbulent orographic form drag scheme notably improves the simulation of near-surface variables.
- Accurately modeling surface winds under very stable atmospheric conditions remains a primary challenge for most simulations.

 $Corresponding \ author: \ Tim \ Whittaker, \ \texttt{whittaker.tim@courrier.uqam.ca}$

Abstract

We evaluate the performance of various configurations of the Canadian Regional Climate Model (CRCM6-GEM5) in simulating 10-meter wind speeds using data from 27 AmeriFlux stations across North America. The assessment employs a hierarchy of error metrics, ranging from simple mean bias to advanced metrics that account for the dependence of wind speeds on variables such as friction velocity and stability. The results reveal that (i) the value of roughness length (z0) has a large effect on the simulation of wind speeds, (ii) using a lower limit for the Obhukov length instead of a lower limit for the lowest level wind speed seems to deteriorate the simulation of wind speeds under very stable conditions, (iii) the choice of stability function has a small but noticeable impact on the wind speeds, (iv) the turbulent orographic form drag scheme shows improvement over effective roughness length approach.

Plain Language Summary

Accurate wind speed forecasting is essential for various applications, from predicting health impacts and wildfire risks to assessing wind energy and storm damage. This study examines how well the Canadian Regional Climate Model (CRCM6-GEM5) predicts wind speeds at 10 meters above the ground, using measurements from 27 AmeriFlux stations. The research examines how different model settings, such as surface roughness and atmospheric stability, affect wind speed predictions. By using a variety of error metrics, the study identifies areas where the model performs well and where improvements are needed, particularly in how it handles stable atmospheric conditions and surface roughness.

1 Introduction

The wind speed near the surface is a key variable in a number of applications, including the calculation of heat and windchill indices to quantify impacts in human and animal health (Osczevski & Bluestein, 2005; Anderson et al., 2013), wildfire risk and fire spread (Stocks et al., 1989; Hung et al., 2024), assessing of the potential for wind-generated electricity (Pryor & Barthelmie, 2021; Hsu & Yeh, 2021) and assessing damages associated with storm hazards (Chen et al., 2022; Schwierz et al., 2010; Hewson & Neu, 2015). Winds are also important because they transport heat and water from distant locations, thereby influencing local temperature and specific humidity including heat waves, cold

-2-

waves and precipitation processes. In addition, near-surface winds affect the intensity of turbulence which in turn affects fluxes of energy, water, and momentum between the surface and the atmosphere (Garratt, 1994).

Therefore, accurate simulation of winds, especially near the surface, is essential for reliable weather forecasts and climate projections. However, this task is challenging because surface wind speeds are influenced by multiple processes that operate at different spatiotemporal scales while interacting with each other. First, surface winds are influenced by upper-level winds through the vertical transfer of horizontal momentum. This means that upper-level processes, such as Rossby waves, extratropical cyclones, and even mesoscale convective systems, must be accurately simulated (Chen et al., 2022; Trzeciak et al., 2016; Hewson & Neu, 2015; Schumacher & Rasmussen, 2020). Second, the vertical transfer of momentum between low levels and the free atmosphere depends on the representation of processes in the planetary boundary layer (Chen et al., 2022; O'Neill, 2012), including buoyancy and turbulence, and are fully parameterized in current numerical weather prediction (NWP) and climate models (Mahrt, 1998; Sušelj & Sood, 2010; Mctaggart-Cowan & Zadra, 2015; Beljaars, 1992). Third, low level winds also depend on the representation of exchanges between the surface and the atmosphere within the surface layer which is usually done employing Monin-Obukhov Similarity Theory (MOST) (Monin & Obukhov, 1954; Lee & Buban, 2020; Jiménez et al., 2012).

Most studies looking at the sensitivity of surface wind speeds to models' configuration have focused on their representation of surface layer processes (Jiménez et al., 2012; Jiménez & Dudhia, 2013, 2012; Sušelj & Sood, 2010). Most NWP and climate models, such as the National Center for Atmospheric Weather Research and Forecasting model (Jiménez et al., 2012; Skamarock et al., 2019), the European Centre for Medium-Range Forecasts Integrated Forecasting System (ECMWF, 2016, 2023) and the Global Environmental Multiscale (GEM) model (McTaggart-Cowan, Vaillancourt, Zadra, Chamberland, et al., 2019), to mention just a few, all utilize MOST theory to represent processes in the surface layer (Shin et al., 2019). The implementation of MOST in numerical models, however, is far from straightforward, as it requires empirically determining several parameters and depends on the numerical formulation of the model, such as the height of the lowest model level (Shin et al., 2019; McTaggart-Cowan, Vaillancourt, Zadra, Chamberland, et al., 2019).

For instance, a key parameter that must be specified empirically is the roughness length (z_0) . This parameter can vary significantly, often by several orders of magnitude over short distances, making it challenging to derive a single value over the grid boxes used in current NWP and climate models. Over land, z_0 has been parameterized following two main approaches (Jiménez & Dudhia, 2012; Fiedler & Panofsky, 1972; Beljaars et al., 2004): an effective roughness length that combines information of both the local surface characteristics and the subgrid-scale orography (Fiedler & Panofsky, 1972; Jiménez & Dudhia, 2012) and a roughness length that depends only on the local surface characteristics while the influence of the orography is included separately as an extra drag term in the resolved equations (Beljaars et al., 2004; Jiménez & Dudhia, 2012). Wind speeds have been shown to be highly sensitive to the value of z_0 . For instance, Nelli et al. (2020) used station data from a tower in the Arabian Peninsula and found that the z_0 value used in the WRF model (with a horizontal grid spacing of 1.33 km) was nearly 10 times larger than the observed z_0 . This discrepancy resulted in wind speed differences averaging about 0.5 m/s between the default and corrected z_0 values. They also demonstrated that the change in z_0 caused a nearly constant decrease in wind speeds, mostly independent of the wind speed's magnitude. Lee and Buban (2020) used station data from towers installed over different land surface types, including early growth soybean, native grassland, and mature soybean. They evaluated MOST under varying conditions, considering the diverse roughness lengths associated with each land surface type. They found that, despite the sites being only 1.7 km apart, the MOST relationships (i.e., variations in the von Kármán constant) differed significantly. This finding suggests that MOST may not hold uniformly even within a single grid cell.

Another parameter that needs to be empirically specified is the functional form of the stability function that is used to correct wind speeds based on the surface layer stability. Several functional forms are proposed in the literature (Delage, 1997; Beljaars & Holtslag, 1991), most of them derived from observed data available from a handful of field experiments (e.g., the Kansas experiment, Kaimal and Wyngaard (1990)). For instance, Jiménez et al. (2012) modified the WRF model's surface layer scheme by refining the empirical stability functions for very stable and unstable situations. Their new scheme resulted in sharper afternoon transitions from stable to unstable conditions, aligning well with observations. Additionally, they reported overall improvements in near-surface variables, particularly in terms of diurnal amplitudes.

-4-

In addition to certain parameters, MOST requires specific assumptions, such as spatial homogeneity and stationarity, to be met. However, these assumptions can be violated during events like thunderstorms. In Markowski et al. (2019), near-surface vertical wind profiles and vertical momentum fluxes observations are used to evaluate the performance of MOST on thunderstorm days, when these assumptions do not hold. The study finds that MOST underestimates the nondimensional vertical wind shear near the surface under such conditions, highlighting the inadequacy of MOST, especially during convective events.

The specific implementation of MOST might also incorporate some ad hoc assumptions to address special conditions. For example, Jiménez et al. (2012) reported that earlier implementations of MOST in the WRF model included several limits that were imposed on certain variables in order to avoid undesired effects (e.g., a lower limit of 1 m s^{-1} for the friction velocity). Similarly, the current version of the GEM model uses a minimum Obukhov length of 20 m (McTaggart-Cowan, Vaillancourt, Zadra, Chamberland, et al., 2019) while an earlier version used a minimum lowest level wind speed, both limits imposed to maintain land-atmosphere coupling under very stable conditions.

In this work we evaluate the ability of several configurations of the latest version of the Canadian Regional Climate Model (CRCM6-GEM5) to simulate 10-m wind speeds (u_{10}) measurements from 27 stations from the AmeriFlux network. We focus on physical processes within the surface layer and test the sensitivity of simulated u_{10} to variations in the representation of very stable regimes, surface roughness, land-surface schemes, and stability function choices. The wind speed model evaluation involves using a hierarchy of error metrics, ranging from simple metrics such as mean bias, to errors in the diurnal and annual cycles, to more advanced error metrics that evaluate errors in u_{10} based on its dependence on other near-surface variables (e.g., friction velocity and the Obukhov length).

This paper is organized as follows. In Sect. 2.1, we provide a detailed description of the model and the set of simulations used in the analysis and in Sect. 2.2 we describe the AmeriFlux station data, including a height correction that was applied to wind data to facilitate the comparison with model output. Sect. 3 introduces the hierarchy of error metrics that are used to evaluate the simulations. In Sect. 4 we present the evaluation of the simulations with respect to the hierarchy of metrics. Some implications of our results are discussed in Sect. 5. Finally, the main conclusions are presented in Sect. 6.

2 Data

2.1 The CRCM6-GEM5 model and sensitivity experiments

All simulations were performed using the latest version of the CRCM6-GEM5 (Roberge et al., 2024) which is based on the fifth generation of the GEM model (Côté et al., 1998; Girard et al., 2014; McTaggart-Cowan, Vaillancourt, Zadra, Chamberland, et al., 2019). GEM5 is developed by the Recherche en Prévision Numérique (RPN) group at Environment and Climate Change Canada and is used for numerical weather prediction by the Canadian Meteorological Centre.

Simulations were performed using a horizontal grid spacing of 0.11° over the CORDEX North American (CORDEX-NA) domain (Giorgi & Gutowski, 2015; Roberge et al., 2024). In the vertical, the model uses 71 hybrid levels with the highest prognostic level at 10 hPa and the lowest level at ~10 m for temperature and moisture and at ~20 m for winds. Simulations were initialized and driven at the boundaries and the interior of the domain using data from the ERA5 reanalysis (Hersbach et al., 2020) for the 2015-2020 period. Large-scale nudging using a spectral method was applied within the domain to drive zonal and meridional winds and temperatures (Separovic et al., 2012). This nudging was applied for vertical levels higher than the 0.85 hybrid level which corresponds approximately to 850 hPa and for waves with a wavelength greater than 200 km using a relaxation time scale of 24 hours. The use of spectral nudging ensures a substantial level of agreement between the large-scale patterns from ERA5 and the simulations (Separovic et al., 2012).

All configurations of the CRCM6-GEM5 model use the Bechtold scheme to represent shallow convection (Bechtold et al., 2001), the Kain-Fritsch scheme to represent deep convection (Kain & Fritsch, 1990; McTaggart-Cowan, Vaillancourt, Zadra, Separovic, et al., 2019), an elevated-convection scheme (McTaggart-Cowan et al., 2020), a planetary boundary layer scheme based on a 1.5-order closure with a prognostic equation for the turbulent kinetic energy (Bélair et al., 1999; Mctaggart-Cowan & Zadra, 2015; McTaggart-Cowan, Vaillancourt, Zadra, Chamberland, et al., 2019) and the Predicted Particle Properties (P3) scheme (Morrison & Milbrandt, 2015; Milbrandt & Morrison, 2016) to represent cloud and precipitation microphysical processes. In addition, a Subgrid Cloud and

-6-

Precipitation Fraction scheme has been used to adapt P3 to the model resolution (Jouan et al., 2020; Chosson et al., 2014). All simulations also use the Fresh-water Lake model (FLake, (Martynov et al., 2012)) to account for changes in surface water temperature and roughness length over lakes.

The surface layer wind speeds in CRCM6-GEM5 are estimated using MOST, resulting in a log wind profile of the form:

$$u_z = \frac{u_*}{k} \left[\log\left(\frac{z+z_0}{z_0}\right) - \Psi_m \right],\tag{1}$$

where k = 0.4 is the von Kármán constant, u_* the friction velocity, z_0 the roughness length, and Ψ_m an empirical stability function (Beljaars & Holtslag, 1991; Delage & Girard, 1992; McTaggart-Cowan, Vaillancourt, Zadra, Chamberland, et al., 2019; Delage, 1997) correction with the following general form,

$$\Psi_m = \begin{cases} \Psi_m^{stable} \text{ for } \zeta > 0\\ 0 \text{ for } \zeta = 0\\ \Psi_m^{unstable} \text{ for } \zeta < 0. \end{cases}$$

The stability parameter $\zeta = z/L$ is a dimensionless variable that is inversely proportional to the Obukhov length scale L defined as,

$$L = -\frac{\bar{\theta}_v u_*^3}{kg(\overline{w'\theta_v})} = \frac{u_*^2 \bar{\theta}_v}{kg\theta_*},\tag{2}$$

where $\overline{w'\theta'_v}$ is the vertical component of the kinematic buoyancy flux (note that, $\overline{w'\theta'_v} = \overline{w'\theta'} + 0.608\overline{\theta} \ \overline{w'q'}$; Garratt (1994)), θ_* is the potential temperature scale and $\overline{\theta}_v$ is the virtual potential temperature. The Obukhov length scale L is positive when the buoyancy flux is negative (i.e., for stable conditions) which leads to $\Psi_m > 0$ and a negative stability correction. On the other hand, when the buoyancy flux is positive (i.e., for unstable conditions), L > 0 and the stability correction is positive. In practice, L is calculated in GEM5 using the bulk Richardson number (McTaggart-Cowan, Vaillancourt, Zadra, Chamberland, et al., 2019).

The friction velocity (u_*) is computed as,

$$u_* = \left(\frac{|\tau_z|}{\rho}\right)^{1/2} = \frac{k \cdot u(z)}{\log\left(\frac{z}{z_0}\right) - \Psi_m}.$$
(3)

Figure 1 shows the flow of computation and the variables involved in the calculation of wind speeds in the surface layer. Note that errors in wind speeds can be influenced directly by errors in u_* , ζ and z_0 . Also note that due to the nonlinear nature of



Figure 1. CRCM6-GEM5 surface wind speeds dependence map. Nodes represent variables, and arrows indicate the direction of information flow, labeled by the equations that relate the variables. Red arrows represent variable connections which are positively correlated, blue arrows those which are negatively correlated and black arrows those that can be positively or negatively correlated.

interactions, tracking the source of errors in wind speeds is challenging. For example, while we might know that u_* and ζ are wrongly simulated, we cannot pinpoint which variable is at the origin of errors since they depend on each other.

We performed multiple simulations with the CRCM6-GEM5 model using different configurations. The main characteristics of simulations are included in Table 1. Two GEM5 model versions are used, GEM5.0.2 (hereafter GEM50) and GEM5.1.1 (denoted as GEM51). These two versions differ in several respects, but the main difference affecting wind speeds lies in the strategy used to handle very stable regimes. In GEM50 (simulation **GEM50-C-DEL**), the lowest-level wind speeds are constrained to never fall below a certain wind-speed threshold value to maintain a minimum level of mechanical turbulence. This wind-speed threshold value depends on the surface type (land, open ocean, lake, etc) and was chosen to be 2.5 m s⁻¹ for land surfaces. In GEM51 (simulation **GEM51-C-DEL**), the strategy to avoid issues when representing very stable regimes relies in limiting the Obukhov length scale L so it can never be lower than a threshold value (see Table 1 for details). Again, this prevents the model from going into very stable regimes and prevents vanishing wind speeds.

Two distinct groups of empirical stability functions are tested for both stable/unstable regimes: those from Delage (1997), here denoted as *DEL*, and those from Beljaars and Holtslag (1991), denoted as *BEL*. The comparison between **GEM51-C-DEL** and **GEM51-C-BEL** allows to isolate the effect of changing the stability functions. The analytical form of both empirical functions is given in Sect. 1 of the Supporting Information (SI).

Two different land-surface models (LSMs) are used to represent surface processes: the Interaction Soil Biosphere Atmosphere (Noilhan & Mahfouf, 1996; Bélair et al., 2003) and the version 3.6 of the Canadian Land Surface Scheme (Verseghy, 1991, 2000). The choice of the LSM can affect wind speeds in multiple ways. A direct impact of the LSM is through the calculation of the roughness length (z_0) that is used in Eq. 1. An indirect impact is related with the calculation and partition of sensible and latent heat fluxes which affect the value of the Obukhov length (L) and the stability correction. The effect of the LSM is evaluated by comparing results from the **GEM51-C-BEL** and the **GEM51-I-BEL** simulations.

The roughness length z_0 is calculated using three different methods. Two methods, one from ISBA and another from CLASS, use the concept of "effective roughness length" by combining an orographic roughness length, $z_{(0,oro)}$, dependent on the subgridscale orography, and a vegetation roughness length, $z_{(0,veg)}$, dependent on the surface type (e.g., forest or grass). A third method, only used with the CLASS LSM, uses the turbulent orographic form drag (TOFD) scheme from Beljaars et al. (2004) to account for the effect of subgrid-scale orography, combined with a pure vegetation roughness length $(z_0 = z_{(0,veg)})$.

The determination of $z_{(0,oro)}$ and $z_{(0,veg)}$ is based on high-resolution (~ 900 m) elevation and land cover fields produced by the US Geological Survey (Earth Resources Observation And Science (EROS) Center, 2017a, 2017b). While both ISBA and CLASS use the same input data, they employ different methods to determine the vegetation roughness length, as well as the way $z_{(0,veg)}$ is combined with $z_{(0,orog)}$ to obtain the effective roughness length z_0 . Some calculation details and the resulting effective z_0 for CLASS, CLASS-TOFD, ISBA and AMF (estimated using the approach described in Section 2.2)

manuscript submitted to Journal of Advances in Modeling Earth Systems (JAMES)



Figure 2. Flowchart of simulations where each node represents a distinct simulation configuration. Connections between nodes indicate a single degree of change in the configuration from one simulation to the next.

are provided in the SI (see Fig. S8 and Table S1). We highlight some similarities and differences in the roughness length across different datasets. First, for all four datasets, the z_0 varies strongly across stations with differences attaining about two orders of magnitude between the lowest and largest z_0 . Second, the average z_0 from CLASS and CLASS-TOFD is closer to AMF than ISBA, with the later showing excessively large z_0 values. Third, there is no spatial correlation between the AMF z_0 and the CLASS, CLASS-TOFD or ISBA z_0 .

To separate the direct and indirect effects introduced by changing the LSM, a simulation was performed using the CLASS LSM with the ISBA roughness length z_0 (simulation **GEM51-C-BEL-Iz0**). The comparison between **GEM51-C-BEL** and **GEM51-C-BEL-Iz0** allows to isolate the effect of the roughness length.

In addition, to assess the effects of using an orographic drag in the resolved equations, a simulation was performed using the TOFD scheme. The comparison between **GEM51-C-DEL** and **GEM51-C-DEL-TOFD** allows to isolate the effect of changing the formulation of the roughness length.

Figure 2 illustrates the degree of similarity between the configuration of all 6 simulations. Note that each simulation has a corresponding twin simulation that differs by only one configuration change, allowing for a controlled comparison of the effects of individual changes.

2.2 AmeriFlux data and height adjustment

AmeriFlux (denoted as AMF) is a network of sites measuring air-surface fluxes of CO_2 , water, and energy in North, Central and South America. AMF data contains high-

| | GEM | Land Surface | Stability | Very stable | Roughness |
|------------------|---------|--------------|-----------|--------------------------------|------------------------|
| Simulation Name | version | Model | function | regime | Length |
| GEM50-C-DEL | 5.0 | CLASS | DEL | $u \ge 2.5 \mathrm{~m~s^{-1}}$ | z_0^C |
| GEM51-C-DEL | 5.1.1 | CLASS | DEL | $L \ge \! 20 \ \mathrm{m}$ | z_0^C |
| GEM51-C-DEL-TOFD | 5.1.1 | CLASS | DEL | $L \ge \! 20 \ \mathrm{m}$ | $z^C_{(0,veg)}$, TOFD |
| GEM51-C-BEL | 5.1.1 | CLASS | BEL | $L \ge \! 20 \mbox{ m}$ | z_0^C |
| GEM51-C-BEL-Iz0 | 5.1.1 | CLASS | BEL | $L \ge \! 20 \ \mathrm{m}$ | z_0^I |
| GEM51-I-BEL | 5.1.1 | ISBA | BEL | $L \ge 20 {\rm ~m}$ | z_0^C |

Table 1. Simulations configuration details including the GEM model version, the land surface model, the stability functions, the strategy for very stable regimes and the formulation of the roughness length. For the stable regime strategy, the threshold values given for the wind speed (u) of the lowest level and the Obukhov length (L) correspond to those over land. The superscript in z_0 values indicates whether the ISBA (I) or the CLASS (C) LSM is being used. In the case that TOFD is used, only the the vegetation roughness length is retained.

temporal resolution measurements of a range of variables near and at the surface including soil, atmospheric, and biological measurements. In particular, AMF provides direct measurements of atmospheric vertical turbulent fluxes acquired using eddy-covariance flux towers (Baldocchi, 2003).

We use the AmeriFlux BASE under the CC-BY-4.0 data use policy that includes a total of 311 sites across South, Central, and North America. We select 27 stations within the CORDEX-NA domain (see Fig. 3 for a map of the stations) which include wind speed (u), friction velocity (u_*) , and the Monin-Obukhov stability parameter (ζ) in the period 2015-2020. While most stations provide measurements every 30 minutes, hourly values were calculated to match the hourly resolution of the simulated data. Hourly values are calculated using the average of the two 30-minute values when both are available or by simply considering a single 30-minute value when only one value is available. Only stations that contain at least one year of hourly measurements over the entire 6-year period are considered. In addition, we excluded stations for which we do not have instrument height information, as it is needed to perform the height adjustment. Considering all stations, a total of 756824 measurements are obtained, which is equivalent to about 86 years of hourly data. More information on the individual stations, including their latitude, longitude, measurement height, name, associated DOI, and total number of measurements, is available in Tab. S2 of SI.

Since the stations have varying measurement heights, we adjusted the wind speed and stability parameter measurements to the standard height of 10 m, which is commonly used to report near-surface wind speeds and is also the standard height used by the model. We only adjust the wind speeds and the stability parameter as we assume, as usually done within the MOST theory, that turbulent fluxes are constant within the surface layer (Garratt, 1994).

The adjustment of the stability parameter is given by,

$$\zeta_{10} = \frac{10}{h} \zeta_h,\tag{4}$$

where h is the height of the measurement. As for the wind speed, we first estimate the roughness length at each station by using the log-wind relationship in neutral conditions $(\zeta_{10} \sim 0)$. We assume that stability conditions are obtained when the modulus of the stability parameter $(|\zeta_{10}|)$ is lower than 0.02 (Draxl et al., 2014),



Figure 3. Map of the CORDEX-NA domain used for the simulations with red crosses showing the location of the 27 stations used in the study.

$$z_0 = \frac{z}{\exp(\frac{u\kappa}{u_*}) - 1},\tag{5}$$

$$u_{10} = u_h + \frac{u_*}{\kappa} \left[\log \frac{h}{10} + (\Psi_{10} - \Psi_h) \right].$$
(6)

We use BEL stability functions for both the stable and unstable branches. Furthermore, we adjust the stability parameter length (ζ) to a minimum value of -5 and a maximum value of 10 so the stability correction is within a reasonable range (Optis et al., 2016). The number of times that the stability parameter is outside the [-5,10] range varies between stations but it is at most 4% of the time.

An alternative correction is performed using the $(z + z_0)$ formulation instead of (z):

$$u_{10} = u_h + \frac{u_*}{\kappa} \left[\log \frac{h + z_0}{10} + (\Psi_{10} - \Psi_h) \right].$$
(7)

In Fig. 4 we show the distribution on the original AMF wind speeds and two adjusted versions at 10 m (with and without z_0). Adjusted 10-m wind speeds distributions are somewhat shifted towards larger wind speeds as the mean height of wind speeds measurements is ~ 3.5 m, lower than the reference height of 10 m. The shift is substantial and nearly doubled the mean wind speed of the original dataset, showing the key im-



Figure 4. Density histogram of wind speeds for the original AMF stations (in red) and for two adjusted versions (in black). Adjusted versions differ on the use of z_0 in the numerator of the logarithm (see Eqs. 6 and 7).

portance of performing the height correction before comparing observations and simulated data. Results for the two proposed methods, with or without z_0 , show little to no differences. In the rest of the analysis, the corrected data without z_0 has been used.

3 Methods

3.1 Comparing AMF and CRCM6-GEM5 output data

The CRCM6-GEM5 model outputs 10-m wind speed (u_{10}) , friction velocity (u_*) , and Obukhov length scale (L) every hour over the entire CORDEX-NA domain and during the whole 2015-2020 period. The comparison between each CRCM6-GEM5 simulation and the AMF adjusted measurements is performed by:

- 1. selecting the model grid point closest to each AMF station (see Fig. 3),
- 2. selecting only the modeled hourly time steps for which the station has measurements (see section 2.2).

This procedure guarantees that the number of values available from both simulations and observations is equal and that both datasets sample the same calendar days. As it will be discussed in detail in the next section, comparisons are not made directly between single model grid points and stations. Although comparing individual model grid points directly with stations is sometimes practiced in model evaluation studies (Nelli et al., 2020), it can be problematic due to differences in observed and simulated roughness lengths.

3.2 A hierarchy of wind speeds error metrics

A hierarchy of error metrics is employed to describe u_{10} errors, progressing from basic error metrics to more advanced and sophisticated measures. All error metrics are derived using different ways of grouping and averaging observed and simulated u_{10} .

For observations and simulations, the u_{10} data can be represented as $u = u_{x,t}$, with the index x representing individual stations and the index t representing hourly time steps at the station x. Note that the number of hours available at each station x is generally different. Individual time series can then be mapped into specific hours of the day (h) and months (m) as $u_{x,t} \rightarrow u_{h,m,n_{h,m}}$, with the index h ranging from 1 to 24, the index m from 1 to 12 and the index $n_{h,m}$ from 1 to $N_{h,m}$, depending on the number of occurrences for the hour h and the month m. The average u_{10} across all stations and times can then be calculated as (for simplicity, the subindex 10 has been removed):

$$\overline{u} = \frac{1}{T \cdot X} \sum_{x} \sum_{t} u_{x,t(x)} = \frac{1}{T \cdot X} \sum_{h} \sum_{m} \sum_{n_{h,m}} u_{h,m,n_{h,m}} = \frac{1}{T \cdot X} \sum_{h} \sum_{m} N_{h,m} \cdot \overline{u_{h,m}}, \quad (8)$$

where T is the average number of hourly measurements across all stations, X is the number of stations (i.e., X = 27) and $T \cdot X$ gives the total number of observations considering all stations ($T \cdot X = 756824$). We define:

$$\overline{u_{h,m}} = \frac{1}{N_{h,m}} \sum_{n_{h,m}} u_{h,m,n_{h,m}} \tag{9}$$

Calculating \overline{u} from observed and simulated data allows us to estimate multiple error metrics. The simplest error metric is given by the absolute error of the mean bias:

$$\epsilon^s_{bias} = |\overline{u^s} - \overline{u^o}| \tag{10}$$

where s denotes the sth simulation and o the AMF observations.

The mean wind speed can also be expressed using the mean diurnal $(\overline{u_h})$ and annual $(\overline{u_m})$ cycle of wind speeds:

$$\overline{u} = \frac{M}{T \cdot X} \sum_{h} \frac{1}{M} \sum_{m} N_{h,m} \cdot \overline{u_{h,m}} = \frac{M}{T \cdot X} \sum_{h} \overline{u_{h}}$$
(11)

$$\overline{u} = \frac{H}{T \cdot X} \sum_{m} \frac{1}{H} \sum_{h} N_{h,m} \cdot \overline{u_{h,m}} = \frac{H}{T \cdot X} \sum_{m} \overline{u_{m}}$$
(12)

The second and third error metrics are given by the sum of absolute errors from the diurnal and annual cycles respectively:

$$\epsilon_{diu}^{s} = \frac{M}{T \cdot X} \sum_{h} \left| \overline{u_{h}^{s}} - \overline{u_{h}^{o}} \right| \tag{13}$$

$$\epsilon_{ann}^{s} = \frac{H}{T \cdot X} \sum_{m} |\overline{u_{m}^{s}} - \overline{u_{m}^{o}}| \tag{14}$$

Defined this way, $\epsilon_{ann}^s \geq \epsilon_{bias}^s$ and $\epsilon_{diu}^s \geq \epsilon_{bias}^s$ and the two error metrics quantify errors associated with the forced variability resulting from the diurnal and the annual cycles respectively. Moreover, a metric quantifying simultaneously diurnal and annual cycle errors can be calculated as:

$$\epsilon_{ann,diu}^{s} = \frac{1}{T \cdot X} \sum_{h} \sum_{m} N_{h,m} \cdot \left| \overline{u_{h,m}^{s}} - \overline{u_{h,m}^{o}} \right|, \tag{15}$$

with $\epsilon^s_{ann,diu} \ge \epsilon^s_{ann} \ge \epsilon^s_{bias}$ and $\epsilon^s_{ann,diu} \ge \epsilon^s_{diu} \ge \epsilon^s_{bias}$.

To quantify errors associated with higher frequency variability (e.g., hourly variability), wind speeds are mapped according to a range of wind speed intensities: $u_{x,t(x)} \rightarrow u_{k,n_k}$ where the index k denotes the wind speeds within the bin $B_k = [u_k, u_{k+1}]$. The mean wind speed is given by:

$$\overline{u} = \frac{1}{T \cdot X} \sum_{k} \sum_{n_k} u_{k,n_k} = \frac{1}{T \cdot X} \sum_{k} N_k \overline{u_k}$$
(16)

with $\overline{u_k}$ the mean wind speed and N_k the number of occurrences at the intensity bin B_k . An error metric, identified as the frequency-intensity (fi) error metric, can be defined as:

$$\epsilon_{fi}^{s} = \frac{1}{T \cdot X} \sum_{k} \left| N_{k}^{s} \overline{u_{k}^{s}} - N_{k}^{o} \overline{u_{k}^{o}} \right| \sim \frac{1}{T \cdot X} \sum_{k} \left| N_{k}^{s} - N_{k}^{o} \right| \cdot \overline{u_{k}^{o}}$$
(17)

because $\overline{u_k^s}\sim\overline{u_k^o}.$ The error metric verifies that $\epsilon_{fi}^s\geq\epsilon_{bias}^s.$

All five error metrics defined above make use of a single variable: u_{10} . As discussed in Section 2.1, multiple variables affect u_{10} , and can be a source of u_{10} errors. Specifically, u_{10} explicitly depends on the friction velocity u^* and the stability parameter ζ , two variables that are measured and available in the AMF dataset. To account for the influence of u_* and ζ in wind speed errors, we first discretize (i.e., bin) u_* and ζ into different categories (denoted here as "regimes") with u_* between $[u_{*i}, u_{*,i+1}]$ and ζ between $[\zeta_j, \zeta_{j+1}]$. Based on hourly values of $u_{*,x,t(x)}$ and $\zeta_{x,t(x)}$, wind speeds $(u_{x,t(x)})$ are mapped into the (u_*, ζ) regimes phase space so that $u_{x,t(x)} \to u_{i,j,n_{i,j}}$. Each regime (i, j) thus contains a total number of occurrences $N_{i,j}$ and an average wind speed $\overline{u_{i,j}}$ so the mean wind speed can be estimated as,

$$\overline{u} = \frac{1}{T \cdot X} \sum_{i} \sum_{j} \sum_{n_{i,j}} u_{i,j,n_i} = \frac{1}{T \cdot X} \sum_{i} \sum_{j} N_{i,j} \overline{u_{i,j}}$$
(18)

A stability/friction velocity (ζ, u_*) regime error metric can be defined as the difference between simulated and observed values,

$$\epsilon_{reg}^{s,tot} = \frac{1}{T \cdot X} \sum_{i} \sum_{j} \left(\left(\Delta N_{i,j} \cdot \overline{u_{i,j}^{o}} \right) + \left(\Delta \overline{u_{i,j} \cdot N_{i,j}^{o}} \right) + \left(\Delta \overline{u_{i,j}} \cdot \Delta N_{i,j} \right) \right)$$
$$= \sum_{i} \sum_{j} \left(\left(\Delta p_{i,j} \cdot \overline{u_{i,j}^{o}} \right) + \left(\Delta \overline{u_{i,j}} \cdot p_{i,j}^{o} \right) + \left(\Delta \overline{u_{i,j}} \cdot \Delta p_{i,j} \right) \right)$$
$$= \epsilon_{reg}^{s,p} + \epsilon_{reg}^{s,u} + \epsilon_{reg}^{s,p\cdot u}$$
(19)

That is, the total regime error $(\epsilon_{reg}^{s,tot})$ is expressed as the sum of three terms:

- 1. Frequency error: the term ϵ_{reg}^{p} quantifies the degree to which the simulation produces the right frequency of regimes.
- 2. Mean wind speed error: the term ϵ_{reg}^{u} quantifies the degree to which the simulation produces the right mean wind speed at each regime.
- 3. Interaction error: the term $\epsilon_{reg}^{p \cdot u}$ quantifies the degree to which errors ΔN and $\Delta \overline{u}$ are correlated (e.g., the error in the frequency of regimes is associated with the error in mean wind speeds).

Using the decomposition above, we can also define an error that penalizes simulations showing important compensating errors as follows:

$$\epsilon_{reg}^s = |\epsilon_{reg}^{s,p}| + |\epsilon_{reg}^{s,u}| + |\epsilon_{reg}^{s,p\cdot u}| \tag{20}$$

Defined this way, ϵ_{reg}^s is equal to zero if and only if the simulation produces the right wind speed for different friction velocities and stability regimes, and ϵ_{reg}^s does not allow for the compensation of errors across regimes. For example, a simulation that would have the right mean wind speed while constantly being in the wrong (u_*, ζ) regime would be penalized.

To emphasize errors in the variability of wind speeds, error metrics are also calculated using a simple unbiased version of simulated wind speeds that removes the overall mean wind speed \overline{u} , thus replacing u by $u - \overline{u}$. Unbiased errors are denoted using a prime (i.e., ϵ') and are always lower than biased errors (i.e., they verify that $\epsilon' \leq \epsilon$).

Finally, to compare all errors in a single plot and assess the performance of simulations ranking, normalized errors are calculated by dividing each error by the maximum across all simulations:

$$\hat{\epsilon}^i = \frac{\epsilon^i}{max(\epsilon^i)} \tag{21}$$

4 Results

4.1 Hourly and monthly mean wind speed errors

Top panels in Fig. 5 show the annual and diurnal mean cycles of 10-m wind speed from the AMF data. The AMF mean wind speed \overline{u} across all stations and times is 3.7 m s⁻¹. The annual cycle is relatively weak with monthly variations within 15% of $\overline{u_m^o}$ (~0.6 m s⁻¹) and a maximum value in spring. The diurnal cycle is somewhat stronger than the annual cycle with variations attaining 20% of $\overline{u_h^o}$ (~1.0 m s⁻¹), with a minima of 3.3 m s⁻¹ at ~7 am local time and a maxima of 4.3 m s⁻¹ at ~5 pm local time.

Simulations mean errors (Fig. 5 c-f) for \overline{u} vary between -0.25 m s⁻¹ and 0.80 m s⁻¹ for the **GEM51-I-BEL** and **GEM51-C-DEL-TOFD** simulations respectively. Fig. 5 c-f shows that errors in the diurnal and annual cycles (errors in $\overline{u}_{h,m}^{o}$) are dominated by errors in the mean wind speed \overline{u} and there is a strong reduction in the error when considering the unbiased version of errors (bottom panels in Fig. 5). For the annual cycle, most simulations, with maybe the exception of **GEM51-C-DEL-TOFD**, show an overestimation of wind speeds during the summer/fall and an underestimation during winter/spring. For the diurnal cycle, error differences between simulations are substantial, and the simulations are highly sensitive to the choice of model version and of roughness length values. For instance, simulations using GEM51 usually show an underestimation in the early afternoon and an overestimation in the late afternoon while the simulations using the ISBA z_0 show the opposite behavior.

Figure 6 presents the combined monthly and hourly mean wind speeds of the AMF data (Figure 6a) and biased (Fig. 6b,d) and unbiased errors (Fig. 6c,e) for two selected simulations (**GEM50-C-DEL** and **GEM51-C-DEL**) that display some error patterns observed in other simulations (biased and unbiased errors for all simulations are shown



Figure 5. AMF annual (a) and diurnal (b) cycles averaged across all stations. Simulation errors are shown for the annual (left) and diurnal (right) cycles (left) and for the biased (middle panels) and unbiased (bottom panels) errors.

in Fig. S1, S2 of the SI). Similarly to Sect. 4.1, we observe both the diurnal and annual cycles in the AMF data, with the highest wind speeds of about 5 m s⁻¹ occurring in the afternoon during the months of April and May, and the lowest wind speeds of about 2 m s⁻¹ occurring in the early morning in August-September.

Figure 6b, d shows the biased hourly-monthly mean wind speed error for **GEM50-C-DEL** and **GEM51-C-DEL**, respectively. Both simulations show similar error patterns during the months of June to October with a large overestimation of the wind speeds. Between November and May, **GEM50-C-DEL** shows an overall underestimation of wind speeds which is in contrast with **GEM51-C-DEL** which shows a general overestimation except during the daytime when it shows a light underestimation. Once the biases are removed (Fig. 6c,e), the magnitude of errors changes little for **GEM50-C-DEL**, showing a similar error pattern. **GEM51-C-DEL**, on the other hand, has a significant reduction in error for the months of June through October, and an increase in underestimation for the other months.



Figure 6. Combined monthly and hourly wind speed cycles from AMF (a), along with the biased (b,d) and unbiased (c,e) errors for GEM50-C-DEL (b,c) and GEM51-C-DEL (d,e).

4.2 Hourly frequency-intensity wind speed errors

Figure 7a shows the frequency-intensity distribution of the AMF wind speeds over all stations. For wind speeds greater than approximately 4 m s⁻¹, the distribution shows an exponential decrease in the frequency of hourly wind speeds as intensity increases, with the highest observed values reaching about 22 m s⁻¹. Figure 7b,c shows the absolute error, which is the frequency error weighted by the mean observed intensity (i.e., $(N_k^s - N_k^o) \cdot \overline{u_k^o})$, for the biased (Fig. 7b) and the unbiased (Fig. 7c) simulations. For both biased and unbiased simulations, total errors are dominated by errors occurring at wind speeds between 0 and about 10 m s⁻¹, with a peak at about 5 m s⁻¹. Biased simulations with the z_0 from CLASS usually underestimate the frequency of wind speeds below 5 m s⁻¹ and overestimate the frequency of wind speeds above 5 m s⁻¹. Biased simulations with the z_0 from ISBA have lower errors and the opposite behavior: an overestimation of low wind speeds and an underestimation of high wind speeds. Removing the mean wind speed from simulations and AMF data (Figure 7c) leads to much lower errors for all simulations (nearly 3 times smaller), especially for the **GEM51-C-DEL-TOFD** that shows very low errors for all wind speed intensities.

Fig. 7d,e shows the relative errors, at each bin, of individual simulations with respect to AMF. For the biased simulations (Fig. 7d), errors are generally within 50% for wind speeds below 10 m s⁻¹. All simulations but **GEM51-C-DEL-TOFD** substantially underestimate the frequency of wind speeds larger than 10 m s⁻¹ and they do not produce any value larger than about 17 m s⁻¹. For the unbiased simulations (Fig. 7e), we note that relative errors are much smaller and within about 10 % for wind speeds below 5 m s⁻¹ but they increase as we consider higher wind speeds, except for the **GEM51-C-DEL-TOFD** simulation.

4.3 Wind speed errors conditioned on stability and friction velocity

Figure 8 shows the AMF mean wind speed ($\overline{u_{i,j}}$; Fig. 8a) and the probability of occurrences ($p = N_{i,j}/N$, Fig. 8b) for different stability and friction velocity regimes. Results show that the AMF mean wind speed increases as the friction velocity increases, with $\overline{u_{i,j}}$ values below 1 m s⁻¹ for $u_* < 0.13$ m s⁻¹ and $\overline{u_{i,j}}$ values attaining about 7 m s⁻¹ for $u_* > 2.6$ m s⁻¹. Fig. 8a) also shows that mean wind speed usually increases as the surface layer becomes more stable, although this is only observed for weak and moderate u_* values. The number of occurrences for different regimes (Fig. 8b) shows strong variability with very unstable or very stable regimes mostly associated with low to moderate friction velocities, and unstable, neutral, and stable conditions occurring with high friction velocities. Note that, according to AMF data, the surface layer is never in a very stable regime with very high friction velocities. The resulting wind speed per regime (Fig. 8c), obtained from the product between the mean wind speed and the occurrence ($\overline{u_{i,j}}$ · $p_{i,j}$), is dominated by the probability of occurrences, and shows the highest values for regimes



Figure 7. AMF wind speed frequency-intensity distribution (a), the absolute frequencyintensity errors (b,c) and the relative frequency-intensity errors (d,e) for the biased (b,d) and the unbiased (c,e) simulations. Absolute errors are calculated as $(N_k^s - N_k^o) \cdot \overline{u_k^o}$ while relative errors are defined as $(N_k^s - N_k^o)/(N_k^s + N_k^o)$.



Figure 8. (a) AMF mean wind speed for different regimes of friction velocity and stability and (b) the probability of occurrence of each regime. Panel c) shows the wind speed per regime, calculated as the product between the mean wind speed and the probability of occurrences. See Eq. 18 for more details.

with large friction velocities under unstable and neutral conditions. Note that the sum of the wind speed per regime across all regimes gives the AMF mean wind speed of 3.7 m s⁻¹.

Figure 9 shows the different terms of the regime-conditioned error decomposition (see Eq. 19) for the **GEM51-C-DEL-TOFD** simulation. The other five simulations are shown in Figs. S3-S7. Fig. 9a) shows the total error in each regime $(\epsilon_{reg}^{s,tot})$ that is obtained as the sum of the frequency error $(\epsilon_{reg}^{s,p}; \text{Fig. 9b})$, the intensity error $(\epsilon_{reg}^{s,u}; \text{Fig. 9c})$ and the interaction error $(\epsilon_{reg}^{s,p\cdot u}, \text{Fig. 9d})$ terms. We see that the unstable and neutral cases have an overall negative bias which is dominated by errors in the intensity term (Fig. 9c), indicating that **GEM51-C-DEL-TOFD** underestimates the wind speed intensity in these regimes. The very unstable and stable cases, on the other hand, are pri-



Figure 9. Decomposed regime errors for the GEM51-C-DEL-TOFD simulation (see Eq. 19). (a) shows the total wind speed error (ϵ_{reg}^s) that results from the sum of the decomposition terms: (b) the frequency error $(\epsilon_{reg}^{s,p})$, (c) the intensity error $(\epsilon_{reg}^{s,u})$, and (d) the interaction error $(\epsilon_{reg}^{s,p\cdot u})$. Colors indicate the relative errors (in %) while absolute errors are annotated for each regime. Errors were calculated using the biased simulation.

marily dominated by frequency error (Fig. 9c) and show a positive bias. Notably, the simulation shows the largest errors for high friction velocity regimes (total error of about 1.3 m s^{-1}) and for very stable regimes (total error of about 1.4 m s^{-1}). The interaction error (Fig. 9d) is generally small compared to the other terms.

The regime error (ϵ_{reg}^s) , as calculated using Eq. 20, is presented in Fig. 10 for all six simulations. With the exception of the **GEM50-C-DEL** simulation, all simulations show the largest errors for the very stable regime. Some simulations, including both simulations using the ISBA z_0 , also show relatively large errors for high friction velocity regimes. Overall, the simulation **GEM50-C-DEL** shows the lowest errors. All GEM51 simulations show a very large error in the large friction velocity, very stable regime and **GEM50-C-DEL** seems to perform best in that regime.



Figure 10. Absolute errors (ϵ_{reg}) within each friction velocity and stability regime for individual simulations. Errors were calculated using Eq. 19 and the biased simulations.

4.4 Synthesizing wind speed error metrics

We combine the results of all error metrics (see Section 3.2) in Fig. 11 for both biased and unbiased (left and right panels respectively) and absolute and normalized (top and bottom panels respectively) errors. As expected, the hierarchy of error metrics holds verifying that $\epsilon_{ann,diu} \geq \epsilon_{ann} \geq \epsilon_{bias}$, $\epsilon_{ann,diu} \geq \epsilon_{diu} \geq \epsilon_{bias}$, $\epsilon_{fi} \geq \epsilon_{bias}$ and $\epsilon_{reg} \geq \epsilon_{bias}$.

For biased errors (left panels in Fig. 11), the **GEM50-C-DEL** simulation shows the best overall performance across most metrics, with **GEM51-C-BEL-Iz0** closely following and showing the lowest mean absolute bias. Conversely, **GEM51-C-DEL-TOFD** performs the worst across all error metrics with only the exception of the stability/friction velocity regime-conditioned error. However, once the mean wind speed has been removed from AMF and observations, error metrics are substantially modified (right panels in Fig. 11). For instance, in Fig. 11b), **GEM51-C-DEL-TOFD** demonstrates a good performance compared to the other simulations, with the lowest errors for the diurnal and annualdiurnal cycle errors, and the second lowest error for the frequency-intensity and regime error metrics. The two simulations differing on the choice of stability function (**GEM51-C-DEL** and **GEM51-C-BEL**), show very similar errors although **GEM51-C-BEL** performs slightly but systematically better than **GEM51-C-DEL**.

Finally, we note the presence of distinct clusters, particularly in the unbiased stability/friction velocity regime-conditioned error. Three groups seem to emerge: the first group, showing the highest error, includes the two simulations using the ISBA roughness length; the second group comprises the remaining three GEM51 simulations; and the third group, exhibiting the best performance, consists of the GEM50 simulation.



Figure 11. Combined biased errors (a), combined unbiased errors (b), combined normalized biased errors (c), combined normalized unbiased errors (d).

5 Discussion

We have assessed the performance and sensitivity of 6 configurations of the CRCM6-GEM5 model using data from 27 stations from the AmeriFlux network that cover a variety of North American climates. We evaluate the performance of simulations at simulating specific aspects of near-surface wind speeds by using a variety of error metrics (presented in Sect. 3.2) and by establishing a hierarchy of errors based on the extent to which each metric allows for the compensation of errors. The approach we follow is inspired by and has been used to quantify errors in other variables (Di Luca et al., 2020, 2021; Picart et al., 2024).

At the bottom of this hierarchy, there is the error in mean wind speed which allows for all possible error compensations (e.g., a low ϵ_{bias} can be obtained by producing the wrong diurnal or annual cycle). Three additional error metrics are defined to avoid the compensation of wind speed errors in the diurnal cycle (ϵ_{diu}), the annual cycle (ϵ_{ann}), and the diurnal/annual cycles combined ($\epsilon_{diu,ann}$). A fifth error metric quantifies differences in the frequency-intensity distribution of hourly wind speeds (ϵ_{fi}). Finally, we define an error metric that quantifies the behavior of wind speed conditioned to the occurrence of multiple stability (ζ) and friction velocity (u_*) regimes (ϵ_{reg}). These two variables, u_* and ζ , are selected because they are directly measured in AmeriFlux sites and are two of the three key variables determining wind speeds according to MOST theory. In addition, we calculate biased and unbiased versions of all errors in order to highlight errors in the variability of wind speeds.

The analysis of multiple error metrics shows that:

- With the exception of the regime error metric, all error metrics are dominated by the error in the mean wind speed thus providing the same ranking of simulations. Errors calculated after removing mean wind speeds (i.e., unbiased simulations) provide a completely different view on the relative performance of simulations.
- The increasing complexity of error metrics reduces the likelihood of error compensation, which in turn highlights whether simulations reproduce observations for the right reasons (e.g., bias being the primary source of error in TOFD simulations).

Among all 6 simulations, **GEM50-C-DEL** performs best with respect to most metrics including the stability/friction velocity regime-conditioned error indicating the least compensation of errors. Similarly, for unbiased simulations, **GEM51-C-DEL-TOFD** is the second best performed across most metrics.

In terms of the effect of specific changes in the CRCM6-GEM6 model configuration, our results show that:

GEM version (GEM50-C-DEL → GEM51-C-DEL): the sensitivity of wind speeds to changes in the model version is very high. The simulation GEM50-C-DEL performs better than GEM51-C-DEL for all error metrics including the frequency-intensity distribution (ε_{fi}) and the physical coherence among variables (ε_{req}). The GEM51-C-DEL simulation produces very stable regimes too often,

particularly for very low and very high friction velocities. This behavior is likely due to the strategy used to deal with very stable regimes (L cutoff, see Table 1).

- Stability functions (GEM51-C-DEL → GEM51-C-BEL): the sensitivity of wind speeds to changes in stability functions is low and these two simulations show relatively minor differences. However, for most metrics, GEM51-C-BEL performs slightly but consistently better than GEM51-C-DEL. Both simulations show the largest errors for very stable regimes. This suggests that the majority of errors are unlikely due to the choice of stability function but are instead influenced by other factors that affect simulation accuracy in very stable regimes.
- Roughness length (z₀) formulation (GEM51-C-DEL → GEM51-C-DEL-TOFD): the sensitivity of wind speeds to changes in the roughness length formulation is high. The GEM51-C-DEL-TOFD simulation, while showing a much larger error in the mean wind speed, outperforms the simulation GEM51-C-DEL in all other aspects when the mean bias is removed. Specifically, GEM51-C-DEL-TOFD substantially improves the representation of the intensity distribution of hourly wind speeds compared to GEM51-C-DEL. The TOFD z₀ formulation, by avoiding the usage of roughness length in some cases (e.g., when the orographic roughness length is large), seems to outperform the other GEM51 configurations for all error metrics except for the mean bias.
- Roughness length values (GEM51-C-BEL → GEM51-C-BEL-Iz0): the sensitivity of wind speeds to changes in z₀ values is very high. When considering the biased version of errors, the simulation GEM51-C-BEL-Iz0 outperforms GEM51-C-BEL for all error metrics with the exception of the regimes error metric. The reason is that GEM51-C-BEL-Iz0 shows strong error compensations with some regimes showing an overestimation of the mean wind speed with an underestimation of the regimes' occurrence.
- Land surface model (GEM51-C-BEL → GEM51-I-BEL): the sensitivity of wind speeds to changes in the LSM seems low to moderate if we exclude the impact of changing the roughness length values. The simulation GEM51-I-BEL shows a similar performance to GEM51-C-BEL-IzO suggesting that most differences with GEM51-C-BEL are related with changes in z₀. The simulation using CLASS shows a slightly better performance than ISBA for all biased metrics and little differences for unbiased error metrics.

Representing the model's roughness length remains an elusive problem. We use two sets of z_0 values in our model, both based on two distinct land cover type fields. Additionally, we estimate the roughness length at each station and find little resemblance between the spatial distribution of z_0 used in simulations and the one estimated from AMF data (see Figure S1). This discrepancy is expected, as station measurements are often taken over a grass surface (or sometimes bare soil if the station is in a desert area), even if the station is surrounded by a forest. In the best-case scenario, the model will assume a z_0 consistent with the surrounding forest, leading to the observed differences. In addition, there is a problem with the spatial representativity of the data. The inability of knowing the roughness length makes it difficult to directly comparing station data with the simulated conditions in the closest grid point. Our approach was to merge together all 27 locations in the analysis and avoid the comparison of single grid points.

6 Conclusions

The evaluation of the ability of several configurations of the version 6 of the Canadian Regional Climate Model (CRCM6-GEM5) to simulate 10-m wind speeds (u_{10}) allows us to conclude that the ranking of simulations depends on the error metric used, and five of the six error metrics used in the study are dominated by errors in the mean wind speed. The only error metric that is only partially affected by errors in mean wind speeds is regime-conditioned error metric, that explores errors in u_{10} based on its dependence on other near-surface variables.

Our results show that:

- Using a TOFD scheme instead of the simpler effective roughness length approach is a step in the right direction, as it significantly improves the intensity distribution of hourly wind speeds.
- Using a lower limit for the Obhukov length instead of a lower limit for the lowestlevel wind speed seems to deteriorate the simulation of wind speeds under very stable conditions.
- The value of the roughness length (z_0) at different grid points has a massive effect on the simulation of wind speeds. However, determining the true roughness length remains problematic.

• Using the CLASS LSM instead of the ISBA LSM and the Beljaars and Holtslag (1991) instead of the Delage (1997) stability functions, results in small but consistent improvements in the simulation of wind speeds.

Further work is needed to assess the sensitivity of wind speeds to other changes such as the models' horizontal resolution, the imposition of other limits to deal with very stable regimes and modifications to key parameters in the planetary boundary layer scheme. Additionally, alternative approaches to surface layer processes should be considered, as current methods based on the Monin-Obukhov similarity theory (MOST) may have limitations.

Open Research Section

- Data availability: The processed data from the AmeriFlux stations and the CRCM6-GEM5 simulation data are available in the Borealis data repository (Whittaker et al., 2024).
- Code availability: The code to reproduce the study is available at https://github .com/timwhittaker/WindErrorHierarchy.

Acknowledgments

We acknowledge the following AmeriFlux sites for their data records: Tab. S2. In addition, funding for AmeriFlux data resources was provided by the U.S. Department of Energy's Office of Science. The authors would like to thank Frédérik Toupin for maintaining a user-friendly local computing facility and for downloading and preparing some of the precipitation datasets. The authors would like to thank Ayrton Zadra for discussion about MOST and its implementation in the CRCM6-GEM5 model, and Danahe Paquin for valuable feedback. This research has been conducted as part of the project "Simulation et analyse du climat à haute resolution" thanks to the financial participation of the Government of Québec. Alejandro Di Luca was funded by the Natural Sciences and Engineering Research Council of Canada (NSERC) (grant no. RGPIN-2020-05631). This research was enabled in part by support provided by Calcul Québec (calculquebec.ca) and the Digital Research Alliance of Canada (alliancecan.ca).

References

- Anderson, G. B., Bell, M. L., & Peng, R. D. (2013, Oct). Methods to calculate the heat index as an exposure metric in environmental health research. *Environmental health perspectives*, 121(10), 1111-1119. Retrieved from https://doi.org/10.1289/ehp.1206273 (23934704[pmid]) doi: 10.1289/ehp.1206273
- Baker, J., & Griffis, T. (2018). Ameriflux us-ro4 rosemount prairie. doi: 10.17190/ AMF/1419507
- Baker, J., & Griffis, T. (2021). Ameriflux fluxnet-1f us-ro5 rosemount i18_south. doi: 10.17190/AMF/1818371
- Baker, J., & Griffis, T. (2022). Ameriflux fluxnet-1f us-ro6 rosemount i18_north. doi: 10.17190/AMF/1881590
- Baldocchi, D. (2003). Assessing the eddy covariance technique for evaluating carbon dioxide exchange rates of ecosystems: past, present and future. *Global Change Biology*, 9(4), 479-492. Retrieved from https://onlinelibrary.wiley.com/doi/abs/10.1046/j.1365-2486.2003.00629.x doi: https://doi.org/10.1046/j.1365-2486.2003.00629.x
- Bechtold, P., Bazile, E., Guichard, F., Mascart, P., & Richard, E. (2001, apr). A mass-flux convection scheme for regional and global models. Quarterly Journal of the Royal Meteorological Society, 127(573), 869–886. Retrieved from https://onlinelibrary.wiley.com/doi/10.1002/qj.49712757309 doi: 10.1002/qj.49712757309
- Bélair, S., Mailhot, J., Strapp, J. W., & Macpherson, J. I. (1999). An examination of local versus nonlocal aspects of a TKE-based boundary layer scheme in clear convective conditions. *Journal of Applied Meteorology*, 38(10), 1499–1518. doi: 10.1175/1520-0450(1999)038(1499:AEOLVN)2.0.CO;2
- Beljaars, A. (1992). The parametrization of the planetary boundary layer. Meteorological Training Course Lecture Series(May 1992), 1-57. Retrieved from https://www.ecmwf.int/sites/default/files/elibrary/2002/ 16959-parametrization-planetary-boundary-layer.pdf
- Beljaars, A., Brown, A. R., & Wood, N. (2004). A new parametrization of turbulent orographic form drag. Quarterly Journal of the Royal Meteorological Society, 130(599), 1327-1347. Retrieved from https://rmets.onlinelibrary.wiley .com/doi/abs/10.1256/qj.03.73 doi: https://doi.org/10.1256/qj.03.73

- Beljaars, A., & Holtslag, A. A. M. (1991). Flux parameterization over land surfaces for atmospheric models. Journal of Applied Meteorology and Climatology, 30(3), 327 - 341. Retrieved from https://journals.ametsoc.org/view/ journals/apme/30/3/1520-0450_1991_030_0327_fpolsf_2_0_co_2.xml doi: 10.1175/1520-0450(1991)030(0327:FPOLSF)2.0.CO;2
- Bergamaschi, B., & Windham-Myers, L. (2018). Ameriflux us-srr suisun marsh rush ranch. doi: 10.17190/AMF/1418685
- Bélair, S., Crevier, L. P., Mailhot, J., Bilodeau, B., & Delage, Y. (2003). Operational implementation of the ISBA land surface scheme in the Canadian regional weather forecast model. Part I: Warm season results. Journal of Hydrometeorology, 4(2), 352–370. doi: 10.1175/1525-7541(2003)4(352: OIOTIL>2.0.CO;2
- Chen, T.-C., Di Luca, A., Winger, K., Laprise, R., & Thériault, J. M. (2022, August). Seasonality of Continental Extratropical-Cyclone Wind Speeds Over Northeastern North America. Geophysical Research Letters, 49(15). Retrieved from https://onlinelibrary.wiley.com/doi/10.1029/ 2022GL098776https://agupubs.onlinelibrary.wiley.com/doi/10.1029/ 2022GL098776 doi: 10.1029/2022GL098776
- Chosson, F., Vaillancourt, P. A., Milbrandt, J. A., Yau, M. K., & Zadra, A. (2014). Adapting two-moment microphysics schemes across model resolutions: Subgrid cloud and precipitation fraction and microphysical sub-time step. *Journal of the Atmospheric Sciences*, 71(7), 2635–2653. doi: 10.1175/JAS-D-13-0367.1
- Côté, J., Gravel, S., Méthot, A., Patoine, A., Roch, M., & Staniforth, A. (1998). The operational CMC-MRB global environmental multiscale (GEM) model. Part I: Design considerations and formulation. Monthly Weather Review, 126(6), 1373–1395. doi: 10.1175/1520-0493(1998)126(1373:TOCMGE)2.0.CO;
 2
- Delage, Y. (1997, Jan 01). Parameterising sub-grid scale vertical transport in atmospheric models under statically stable conditions. *Boundary-Layer Meteorology*, 82(1), 23-48. Retrieved from https://doi.org/10.1023/A:1000132524077 doi: 10.1023/A:1000132524077
- Delage, Y., & Girard, C. (1992, Jan 01). Stability functions correct at the free convection limit and consistent for for both the surface and ekman layers.

Boundary-Layer Meteorology, 58(1), 19-31. Retrieved from https://doi.org/ 10.1007/BF00120749 doi: 10.1007/BF00120749

- Di Luca, A., Argüeso, D., Sherwood, S., & Evans, J. P. (2021, July). Evaluating Precipitation Errors Using the Environmentally Conditioned IntensityFrequency Decomposition Method. Journal of Advances in Modeling Earth Systems, 13(7), 1-22. Retrieved from https://onlinelibrary.wiley.com/
 doi/10.1029/2020MS002447
 doi: 10.1029/2020MS002447
- Di Luca, A., Pitman, A. J., & de Elía, R. (2020). Decomposing Temperature Extremes Errors in CMIP5 and CMIP6 Models. Geophysical Research Letters, 47(14), 1–10. doi: 10.1029/2020GL088031
- Draxl, C., Hahmann, A. N., Peña, A., & Giebel, G. (2014). Evaluating winds and vertical wind shear from weather research and forecasting model forecasts using seven planetary boundary layer schemes. Wind Energy, 17(1), 39-55. Retrieved from https://onlinelibrary.wiley.com/doi/abs/10.1002/we.1555 doi: https://doi.org/10.1002/we.1555
- Earth Resources Observation And Science (EROS) Center. (2017a). Global 30 Arc-Second Elevation (GTOPO30). U.S. Geological Survey. Retrieved 2024-07-11, from https://www.usgs.gov/centers/eros/science/ usgs-eros-archive-digital-elevation-global-30-arc-second-elevation -gtopo30?qt-science_center_objects=0#qt-science_center_objects doi: 10.5066/F7DF6PQS
- Earth Resources Observation And Science (EROS) Center. (2017b). Global Land Cover Characterization (GLCC). U.S. Geological Survey. Retrieved 2024-07-11, from https://www.usgs.gov/centers/eros/science/usgs-eros -archive-land-cover-products-global-land-cover-characterization -glcc doi: 10.5066/F7GB230D
- ECMWF. (2016). IFS Documentation CY41R2: Part IV: Physical Processes. IFS Documentation CY41R2(March), 213.
- ECMWF. (2023). IFS Documentation CY48R1 Part III: Dynamics and Numerical Procedures (Tech. Rep.). Retrieved 2024-07-05, from https://www.ecmwf.int/ en/elibrary/81369-ifs-documentation-cy48r1-part-iii-dynamics-and -numerical-procedures (Publisher: ECMWF) doi: 10.21957/26F0AD3473

Eichelmann, E., Knox, S., Sanchez, C. R., Valach, A., Sturtevant, C., Szutu, D., ...

Baldocchi, D. (2020). Fluxnet-ch4 us-tw4 twitchell east end wetland. doi: 10.18140/FLX/1669698

- Fiedler, F., & Panofsky, H. A. (1972, January). The geostrophic drag coefficient and the 'effective' roughness length. Quarterly Journal of the Royal Meteorological Society, 98(415), 213-220. Retrieved 2024-07-04, from https://rmets .onlinelibrary.wiley.com/doi/10.1002/qj.49709841519 doi: 10.1002/qj .49709841519
- Flerchinger, G. (2017a). Ameriflux us-rms rcew mountain big sagebrush. doi: 10 .17190/AMF/1375202
- Flerchinger, G. (2017b). Ameriflux us-rws reynolds creek wyoming big sagebrush. doi: 10.17190/AMF/1375201
- Flerchinger, G. (2018). Ameriflux us-rls rcew low sagebrush. doi: 10.17190/AMF/ 1418682
- Flerchinger, G. (2020). Ameriflux US-Rwf rcew upper sheep prescibed fire. doi: 10 .17190/AMF/1617724
- Garratt, J. R. (1994). The atmospheric boundary layer (1st ed.). Cambridge, UK: Cambridge University Press.
- Giorgi, F., & Gutowski, W. J. (2015). Regional Dynamical Downscaling and the CORDEX Initiative. Annual Review of Environment and Resources, 40, 467– 490. doi: 10.1146/annurev-environ-102014-021217
- Girard, C., Plante, A., Desgagné, M., McTaggart-Cowan, R., Côté, J., Charron,
 M., ... Zadra, A. (2014). Staggered vertical discretization of the canadian environmental multiscale (gem) model using a coordinate of the loghydrostatic-pressure type. Monthly Weather Review, 142(3), 1183–1196. doi: 10.1175/MWR-D-13-00255.1
- Goslee, S. (2021). Ameriflux us-hwb usda ars pasture sytems and watershed management research unit- hawbecker site. Retrieved from https://www.osti.gov/ biblio/1811363 doi: 10.17190/AMF/1811363
- Hersbach, H., Bell, B., Berrisford, P., Hirahara, S., Horányi, A., Muñoz-Sabater, J.,
 ... Thépaut, J. N. (2020). The ERA5 global reanalysis. *Quarterly Journal of the Royal Meteorological Society*, 146 (730), 1999–2049. doi: 10.1002/qj.3803
- Hewson, T. D., & Neu, U. (2015). Cyclones, windstorms and the IMILAST project. Tellus, Series A: Dynamic Meteorology and Oceanography, 6(1). doi: 10.3402/

tellusa.v67.27128

- Hsu, W.-K., & Yeh, C.-K. (2021). Offshore wind potential of west central taiwan: A case study. *Energies*, 14(12). Retrieved from https://www.mdpi.com/1996 -1073/14/12/3702 doi: 10.3390/en14123702
- Huggins, D. (2021). Ameriflux fluxnet-1f us-cf1 caf-ltar cook east. doi: 10.17190/ AMF/1832158
- Huggins, D. (2022a). Ameriflux fluxnet-1f us-cf2 caf-ltar cook west. doi: 10.17190/ AMF/1881573
- Huggins, D. (2022b). Ameriflux fluxnet-1f us-cf3 caf-ltar boyd north. doi: 10.17190/ AMF/1881574
- Huggins, D. (2022c). Ameriflux fluxnet-1f us-cf4 caf-ltar boyd south. doi: 10.17190/ AMF/1881575
- Hung, W.-T., Campbell, P. C., Moon, Z., Saylor, R., Kochendorfer, J., Lee, T. R., & Massman, W. (2024). Evaluation of an in-canopy wind and wind adjustment factor model for wildfire spread applications across scales. *Journal* of Advances in Modeling Earth Systems, 16(7), e2024MS004300. Retrieved from https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/ 2024MS004300 (e2024MS004300 2024MS004300) doi: https://doi.org/10.1029/ 2024MS004300
- Jiménez, P. A., & Dudhia, J. (2012). Improving the representation of resolved and unresolved topographic effects on surface wind in the wrf model. Journal of Applied Meteorology and Climatology, 51(2), 300 - 316. Retrieved from https://journals.ametsoc.org/view/journals/apme/51/ 2/jamc-d-11-084.1.xml doi: 10.1175/JAMC-D-11-084.1
- Jiménez, P. A., & Dudhia, J. (2013). On the ability of the WRF model to reproduce the surface wind direction over complex terrain. Journal of Applied Meteorology and Climatology, 52(7), 1610 - 1617. Retrieved from https://journals .ametsoc.org/view/journals/apme/52/7/jamc-d-12-0266.1.xml doi: 10 .1175/JAMC-D-12-0266.1
- Jiménez, P. A., Dudhia, J., González-Rouco, J. F., Navarro, J., Montávez, J. P., & García-Bustamante, E. (2012). A revised scheme for the WRF surface layer formulation. Monthly Weather Review, 140(3), 898 - 918. Retrieved from https://journals.ametsoc.org/view/journals/mwre/140/3/

mwr-d-11-00056.1.xml doi: 10.1175/MWR-D-11-00056.1

- Jouan, C., Milbrandt, J. A., Vaillancourt, P. A., Chosson, F., & Morrison, H. (2020). Adaptation of the predicted particles properties (P3) microphysics scheme for large-scale numerical weather prediction. Weather and Forecasting, 35(6), 2541–2565. doi: 10.1175/WAF-D-20-0111.1
- Kaimal, J. C., & Wyngaard, J. C. (1990, March). The Kansas and Minnesota experiments. Boundary-Layer Meteorology, 50(1-4), 31-47. Retrieved 2024-07-05, from http://link.springer.com/10.1007/BF00120517 doi: 10.1007/BF00120517
- Kain, J. S., & Fritsch, J. M. (1990, dec). A One-Dimensional Entraining/Detraining Plume Model and Its Application in Convective Parameterization. Journal of the Atmospheric Sciences, 47(23), 2784-2802. Retrieved from http:// journals.ametsoc.org/doi/10.1175/1520-0469(1990)047%3C2784:AODEPM% 3E2.0.C0;2 doi: 10.1175/1520-0469(1990)047/2784:AODEPM>2.0.CO;2
- Knox, S., Matthes, J. H., Verfaillie, J., & Baldocchi, D. (2016). Ameriflux us-twt twitchell island. Retrieved from https://www.osti.gov/biblio/1246140 doi: 10.17190/AMF/1246140
- Kusak, K., Sanchez, C. R., Szutu, D., & Baldocchi, D. (2022). Ameriflux fluxnet-1f us-snf sherman barn. doi: 10.17190/AMF/1854371
- Lee, T. R., & Buban, M. (2020). Evaluation of Monin-Obukhov and bulk Richardson parameterizations for surface-atmosphere exchange. Journal of Applied Meteorology and Climatology, 59(6), 1091 - 1107. Retrieved from https:// journals.ametsoc.org/view/journals/apme/59/6/jamcD190057.xml doi: 10.1175/JAMC-D-19-0057.1
- Ma, S., Xu, L., Verfaillie, J., & Baldocchi, D. (2016). Ameriflux us-var vaira ranchione. doi: 10.17190/AMF/1245984
- Mahrt, L. (1998, Jun 01). Stratified atmospheric boundary layers and breakdown of models. Theoretical and Computational Fluid Dynamics, 11(3), 263-279. Retrieved from https://doi.org/10.1007/s001620050093 doi: 10.1007/s001620050093
- Markowski, P. M., Lis, N. T., Turner, D. D., Lee, T. R., & Buban, M. S. (2019).Observations of near-surface vertical wind profiles and vertical momentum fluxes from vortex-se 2017: Comparisons to monin–obukhov similarity theory.

Monthly Weather Review, 147(10), 3811 - 3824. Retrieved from https:// journals.ametsoc.org/view/journals/mwre/147/10/mwr-d-19-0091.1.xml doi: 10.1175/MWR-D-19-0091.1

- Martynov, A., Sushama, L., Laprise, R., Winger, K., & Dugas, B. (2012). Interactive lakes in the Canadian Regional Climate Model, version 5: The role of lakes in the regional climate of North America. *Tellus, Series A: Dynamic Meteorology* and Oceanography, 64(1), 0–22. doi: 10.3402/tellusa.v64i0.16226
- Matthes, J. H., Sturtevant, C., Oikawa, P., Chamberlain, S. D., Szutu, D., Ortiz, A. A., ... Baldocchi, D. (2020). Fluxnet-ch4 us-myb mayberry wetland. doi: 10.18140/FLX/1669685
- McTaggart-Cowan, R., Vaillancourt, P. A., Separovic, L., Corvec, S., & Zadra, A. (2020, December). A Convection Parameterization for Low-CAPE Environments. Monthly Weather Review, 148(12), 4917-4941. Retrieved 2024-07-11, from https://journals.ametsoc.org/view/journals/mwre/148/12/mwr-d-20-0020.1.xml doi: 10.1175/MWR-D-20-0020.1
- McTaggart-Cowan, R., Vaillancourt, P. A., Zadra, A., Chamberland, S., Charron, M., Corvec, S., ... Yang, J. (2019). Modernization of atmospheric physics parameterization in canadian nwp. Journal of Advances in Modeling Earth Systems, 11(11), 3593-3635. Retrieved from https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/2019MS001781 doi: https://doi.org/10.1029/2019MS001781
- McTaggart-Cowan, R., Vaillancourt, P. A., Zadra, A., Separovic, L., Corvec,
 S., & Kirshbaum, D. (2019). A lagrangian perspective on parameterizing deep convection. Monthly Weather Review, 147(11), 4127–4149. doi: 10.1175/MWR-D-19-0164.1
- Mctaggart-Cowan, R., & Zadra, A. (2015). Representing richardson number hysteresis in the NWP boundary layer. Monthly Weather Review, 143(4), 1232–1258. doi: 10.1175/MWR-D-14-00179.1
- Milbrandt, J. A., & Morrison, H. (2016). Parameterization of cloud microphysics based on the prediction of bulk ice particle properties. Part III: Introduction of multiple free categories. Journal of the Atmospheric Sciences, 73(3), 975–995. doi: 10.1175/JAS-D-15-0204.1
- Monin, A. S., & Obukhov, A. M. (1954). Osnovne zakonomernosti turbulentnogo

peremeshivaniya v prizemnom sloe atmosfery (basic laws of turbulent mixing in the ground layer of the atmosphere). Trudy Geofizicheskogo Instituta, Akademiya Nauk SSSR, 24(151), 163–187.

- Morrison, H., & Milbrandt, J. A. (2015). Parameterization of cloud microphysics based on the prediction of bulk ice particle properties. Part I: Scheme description and idealized tests. Journal of the Atmospheric Sciences, 72(1), 287–311. doi: 10.1175/JAS-D-14-0065.1
- Nelli, N. R., Temimi, M., Fonseca, R. M., Weston, M. J., Thota, M. S., Valappil, V. K., ... Al Naqbi, H. (2020). Impact of roughness length on wrf simulated land-atmosphere interactions over a hyper-arid region. Earth and Space Science, 7(6), e2020EA001165. Retrieved from https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/2020EA001165 (e2020EA001165 2020EA001165) doi: https://doi.org/10.1029/2020EA001165
- Noilhan, J., & Mahfouf, J.-F. (1996). The isba land surface parameterisation scheme. Global and Planetary Change, 13(1), 145-159. Retrieved from https://www.sciencedirect.com/science/article/pii/0921818195000437 (Soil Moisture Simulation) doi: https://doi.org/10.1016/0921-8181(95)00043 -7
- Oikawa, P. (2021). Ameriflux fluxnet-1f us-edn eden landing ecological reserve. doi: 10.17190/AMF/1832159
- Optis, M., Monahan, A., & Bosveld, F. C. (2016). Limitations and breakdown of monin-obukhov similarity theory for wind profile extrapolation under stable stratification. Wind Energy, 19(6), 1053-1072. Retrieved from https://onlinelibrary.wiley.com/doi/abs/10.1002/we.1883 doi: https://doi.org/10.1002/we.1883
- Osczevski, R., & Bluestein, M. (2005). The new wind chill equivalent temperature chart. Bulletin of the American Meteorological Society, 86(10), 1453 1458. Retrieved from https://journals.ametsoc.org/view/journals/bams/86/10/bams-86-10-1453.xml doi: 10.1175/BAMS-86-10-1453
- O'Neill, L. W. (2012). Wind speed and stability effects on coupling between surface wind stress and sst observed from buoys and satellite. Journal of Climate, 25(5), 1544 1569. Retrieved from https://journals.ametsoc.org/view/journals/clim/25/5/jcli-d-11-00121.1.xml doi: 10.1175/

JCLI-D-11-00121.1

- Picart, T., Di Luca, A., & Laprise, R. (2024, February). Uncertainty and outliers in high-resolution gridded precipitation products over eastern North America. International Journal of Climatology(June 2023), 1-22. Retrieved from https:// rmets.onlinelibrary.wiley.com/doi/10.1002/joc.8369 doi: 10.1002/joc. 8369
- Pryor, S. C., & Barthelmie, R. J. (2021, Mar 01). A global assessment of extreme wind speeds for wind energy applications. *Nature Energy*, 6(3), 268-276. Retrieved from https://doi.org/10.1038/s41560-020-00773-7 doi: 10.1038/ s41560-020-00773-7
- Rey-Sanchez, C., Wang, C. T., Szutu, D., Hemes, K., Verfaillie, J., & Baldocchi, D. (2022). Ameriflux fluxnet-1f us-bi2 bouldin island corn. doi: 10.17190/AMF/1871135
- Rey-Sanchez, C., Wang, C. T., Szutu, D., Shortt, R., Chamberlain, S. D., Verfaillie, J., & Baldocchi, D. (2022). Ameriflux fluxnet-1f us-bi1 bouldin island alfalfa. doi: 10.17190/AMF/1871134
- Roberge, F., Di Luca, A., Laprise, R., Lucas-Picher, P., & Thériault, J. (2024, February). Spatial spin-up of precipitation in limited-area convection-permitting simulations over North America using the CRCM6/GEM5.0 model. *Geoscientific Model Development*, 17(4), 1497–1510. Retrieved from https://gmd.copernicus.org/articles/17/1497/2024/ doi: 10.5194/gmd-17-1497-2024
- Schumacher, R. S., & Rasmussen, K. L. (2020, June). The formation, character and changing nature of mesoscale convective systems. Nature Reviews Earth & Environment, 1(6), 300-314. Retrieved 2024-07-05, from https://www.nature .com/articles/s43017-020-0057-7 doi: 10.1038/s43017-020-0057-7
- Schwierz, C., Köllner-Heck, P., Zenklusen Mutter, E., Bresch, D. N., Vidale, P.-L.,
 Wild, M., & Schär, C. (2010, August). Modelling European winter wind storm losses in current and future climate. *Climatic Change*, 101(3), 485– 514. Retrieved from https://doi.org/10.1007/s10584-009-9712-1 doi: 10.1007/s10584-009-9712-1
- Separovic, L., de Elía, R., & Laprise, R. (2012). Impact of spectral nudging and domain size in studies of RCM response to parameter modification. *Climate Dy-*

namics, 38(7-8), 1325-1343. doi: 10.1007/s00382-011-1072-7

- Shin, H. H., Ming, Y., Zhao, M., Chen, X., & Lin, S. (2019, April). Improved Surface Layer Simulation Using Refined Vertical Resolution in the GFDL Atmospheric General Circulation Model. Journal of Advances in Modeling Earth Systems, 11(4), 905–917. Retrieved 2024-07-04, from https://agupubs.onlinelibrary.wiley.com/doi/10.1029/2018MS001437 doi: 10.1029/2018MS001437
- Shortt, R., Hemes, K., Szutu, D., Verfaillie, J., & Baldocchi, D. (2022). Ameriflux fluxnet-1f us-sne sherman island restored wetland. doi: 10.17190/AMF/ 1871144
- Silveira, M. (2021). Ameriflux fluxnet-1f us-ona florida pine flatwoods. doi: 10 .17190/AMF/1832163
- Skamarock, W. C., Klemp, J. B., Dudhia, J., Gill, D. O., Liu, Z., Berner, J., ... Huang, X.-Y. (2019, March). A Description of the Advanced Research WRF Model Version 4 (Tech. Rep.). UCAR/NCAR. Retrieved 2024-07-05, from https://opensky.ucar.edu/islandora/object/opensky:2898 doi: 10.5065/1DFH-6P97
- Stocks, B. J., Lawson, B. D., Alexander, M. E., Wagner, C. E. V., McAlpine, R. S., Lynham, T. J., & Dubé, D. E. (1989). The canadian forest fire danger rating system: An overview. *The Forestry Chronicle*, 65(6), 450-457. Retrieved from https://doi.org/10.5558/tfc65450-6 doi: 10.5558/tfc65450-6
- Sušelj, K., & Sood, A. (2010). Improving the Mellor-Yamada-Janjić Parameterization for wind conditions in the marine planetary boundary layer. Boundary-Layer Meteorology, 136(2), 301–324. doi: 10.1007/s10546-010-9502-3
- Trzeciak, T. M., Knippertz, P., Pirret, J. S. R., & Williams, K. D. (2016, June). Can we trust climate models to realistically represent severe European windstorms? *Climate Dynamics*, 46(11), 3431–3451. Retrieved from https://doi.org/10.1007/s00382-015-2777-9 doi: 10.1007/s00382-015-2777-9
- Valach, A., Shortt, R., Szutu, D., Eichelmann, E., Knox, S., Hemes, K., ... Baldocchi, D. (2016). Ameriflux us-tw1 twitchell wetland west pond. doi: 10.17190/AMF/1246147
- Vazquez-Lule, A., & Vargas, R. (2020). Fluxnet-ch4 us-stj st jones reserve. doi: 10 .18140/FLX/1669695

- Verseghy, D. L. (1991). Class—a canadian land surface scheme for gcms. i. soil model. International Journal of Climatology, 11(2), 111-133. Retrieved from https://rmets.onlinelibrary.wiley.com/doi/abs/10.1002/ joc.3370110202 doi: https://doi.org/10.1002/joc.3370110202
- Verseghy, D. L. (2000). The Canadian land surface scheme (CLASS): Its history and future. Atmosphere - Ocean, 38(1), 1–13. Retrieved from https://doi.org/10 .1080/07055900.2000.9649637 doi: 10.1080/07055900.2000.9649637
- Vivoni, E. R. (2020). Ameriflux us-srs santa rita experimental range mesquite savanna. doi: 10.17190/AMF/1660351
- Wagner-Riddle, C. (2019). Ameriflux ca-er1 elora research station. Retrieved from https://www.osti.gov/biblio/1579541 doi: 10.17190/AMF/1579541
- Whittaker, T., Di Luca, A., & Roberge, F. (2024). Surface Atmospheric Variables for the Evaluation of Winds (SAVE-Winds) catalog. Borealis. Retrieved from https://doi.org/10.5683/SP3/VWMCY0 doi: 10.5683/SP3/VWMCY0

Supporting Information for "Evaluating near-surface wind speeds simulated by the CRCM6-GEM5 model using AmeriFlux data over North America"

Tim Whittaker¹, Alejandro Di Luca¹, Francois Roberge¹, Katja Winger¹

¹Centre pour l'étude et la simulation du climat à l'échelle régionale (ESCER), Département des Sciences de la Terre et de

l'Atmosphère, Université du Québec à Montréal, Montréal, Québec, Canada

1. Stability Functions in the CRCM6-GEM6 model

Under stable conditions, the stability functions used are the following,

$$\Psi_m^{stable} = \begin{cases} \frac{1}{2} \left[a - \frac{z}{h} - \ln\left(1 + \frac{b}{2}z + a\right) - \frac{b}{2\sqrt{c}} \operatorname{arcsin}\left(\frac{b - 2cz}{d}\right) \right] & \text{for DEL} \\ -(a\zeta + b(\zeta - c/d)e^{-d\zeta} + bc/d) & \text{for BEL} \end{cases}$$

,

,

:

with a = 1, b = 2/3, c = 5, d = 0.35 and the boundary layer height h for DEL given by $h = max(h_1, h_2, h_3, h_4)$ where

$$h_1 = \gamma \cdot (zu + 10 \cdot z_0)$$
$$\gamma = 1.2$$

zu = height of the model's lowest prognostic (momentum) level

$$h_{2} = b_{s} \sqrt{\frac{\kappa u_{*}L}{|f|}}$$

$$f = \text{Coriolis parameter}$$

$$b_{s} = 1$$

$$h_{3} = \frac{\gamma}{4a_{s}\beta}L$$

$$a_{s} = 12$$

$$\beta = 1$$

 $h_4 = h_{min} = 30$ m in the operational system

For unstable conditions, stability functions are given by,

$$\Psi_m^{unstable} = \begin{cases} 2\ln(w+1) + \frac{1}{2}\ln(w^2 - w + 1) + \frac{3}{2}\ln(w^2 + w + 1) - \sqrt{3}\arctan\frac{(w^2 - 1)}{\sqrt{3}w} \text{ for DEL}, \\ \log z - 2\log(r+1) - \log(r^2 + 1) + 2\arctan(r) \text{ for BEL} \end{cases}$$

with, $w(\zeta) = (1 - \beta c_i \zeta)^{1/6}$ and $r = (1 - 16\zeta)^{1/4}$ where β and c_i are parameters with default values $\beta = 1, c_i = 40.$

:

2. Roughness length calculation in the CRCM6-GEM6 model

Over land grid points, the effective roughness length z_0 is calculated differently in both landsurface schemes, ISBA and CLASS. In CLASS we have:

$$z_0 = \max(z_{(0,oro)}, z_{(0,veg)}), \tag{1}$$

And in ISBA we have:

$$\frac{1}{\left[\ln\frac{z_{ref}}{z_0}\right]^2} = \frac{1}{\left[\ln\frac{z_{ref}}{z_{0,veg}}\right]^2} + \frac{1}{\left[\ln\frac{z_{ref}}{z_{0,orog}}\right]^2},\tag{2}$$

:

3. Extra Figures and Tables



Figure S1. Combined monthly and hourly wind speed cycle errors for all simulations.

August 29, 2024, 12:52am



Figure S2. Combined monthly and hourly wind speed cycle errors for all simulations with bias removed.





Figure S3. Decomposed percent regime errors for GEM50-C-DEL. Panel a) shows the total binned error, Panel b) shows the binned frequency error, Panel c) shows the binned mean wind speed error, and Panel d) shows the binned residual error.



Figure S4. Decomposed percent regime errors for GEM50-C-DEL. Panel a) shows the total binned error, Panel b) shows the binned frequency error, Panel c) shows the binned mean wind speed error, and Panel d) shows the binned residual error.





Figure S5. Decomposed percent regime errors for GEM51-C-DEL. Panel a) shows the total binned error, Panel b) shows the binned frequency error, Panel c) shows the binned mean wind speed error, and Panel d) shows the binned residual error.





Figure S6. Decomposed percent regime errors for GEM51-C-BEL. Panel a) shows the total binned error, Panel b) shows the binned frequency error, Panel c) shows the binned mean wind speed error, and Panel d) shows the binned residual error.



Figure S7. Decomposed percent regime errors for GEM51-C-BEL-Iz0. Panel a) shows the total binned error, Panel b) shows the binned frequency error, Panel c) shows the binned mean wind speed error, and Panel d) shows the binned residual error.



Figure S8. Effective roughness lengths for ISBA (a), CLASS (b), and CLASS using TOFD (c).

| | z_0 mean (m) | z_0 median (m) | Corr(AMF,sim) |
|------------|----------------|------------------|---------------|
| AMF | 0.11 | 0.073 | 1 |
| ISBA | 0.6 | 0.158 | 0.01 |
| CLASS | 0.25 | 0.037 | -0.09 |
| CLASS-TOFD | 0.11 | 0.04 | 0.06 |

Table S1. Mean and median and z_0 for AMF, ISBA, CLASS and CLASS-TOFD. The third column shows the correlation between AMF and the simulations across all 27 stations.

References

- Baker, J., & Griffis, T. (2018). Ameriflux us-ro4 rosemount prairie. doi: 10.17190/AMF/ 1419507
- Baker, J., & Griffis, T. (2021). Ameriflux fluxnet-1f us-ro5 rosemount i18_south. doi: 10.17190/ AMF/1818371
- Baker, J., & Griffis, T. (2022). Ameriflux fluxnet-1f us-ro6 rosemount i18_north. doi: 10.17190/ AMF/1881590
- Bergamaschi, B., & Windham-Myers, L. (2018). Ameriflux us-srr suisun marsh rush ranch. doi: 10.17190/AMF/1418685

| ٠ |
|---|
| |
| • |

| Station Name | Longitude | Latitude | Altitude (m) | Measurement Height (m) | Reference |
|--------------|-----------|----------|--------------|------------------------|--|
| CA-ER1 | 43.64 | -80.41 | 370 | 1.93 | (Wagner-Riddle, 2019) |
| US-Bi1 | 38.10 | -121.50 | -2.7 | 3.9 | (Rey-Sanchez, Wang, Szutu, Shortt, et al., 2022) |
| US-Bi2 | 38.11 | -121.54 | -5 | 5.11 | (Rey-Sanchez, Wang, Szutu, Hemes, et al., 2022) |
| US-CF1 | 46.78 | -117.08 | 794 | 4.0 | (Huggins, 2021) |
| US-CF2 | 46.78 | -117.09 | 795 | 4.0 | (Huggins, 2022a) |
| US-CF3 | 46.76 | -117.13 | 795 | 2.1 | (Huggins, 2022b) |
| US-CF4 | 46.75 | -117.13 | 795 | 2.1 | (Huggins, 2022c) |
| US-EDN | 37.62 | -122.11 | - | 4.34 | (Oikawa, 2021) |
| US-HWB | 40.86 | -77.85 | 378 | 5 | (Goslee, 2021) |
| US-Myb | 38.04 | -121.76 | 338 | 5.44 | (Matthes et al., 2020) |
| US-ONA | 27.38 | -81.95 | 25 | 2.8 | (Silveira, 2021) |
| US-Rls | 43.14 | -116.73 | 1608 | 2.09 | (Flerchinger, 2018) |
| US-Rms | 43.06 | -116.74 | 2111 | 2.28 | (Flerchinger, 2017a) |
| US-Ro4 | 44.67 | -93.07 | 274 | 2.5 | (Baker & Griffis, 2018) |
| US-Ro5 | 44.69 | -93.06 | 283 | 2 | (Baker & Griffis, 2021) |
| US-Ro6 | 44.69 | -93.06 | 282 | 2.3 | (Baker & Griffis, 2022) |
| US-Rwf | 43.12 | -116.72 | 1878 | 3.5 | (Flerchinger, 2020) |
| US-Rws | 43.16 | -116.71 | 1425 | 2.05 | (Flerchinger, 2017b) |
| US-SRS | 31.81 | -110.85 | 1169 | 7 | (Vivoni, 2020) |
| US-Sne | 38.04 | -121.75 | -5 | 5.43 | (Shortt et al., 2022) |
| US-Snf | 38.04 | -121.73 | -4 | 3.49 | (Kusak et al., 2022) |
| US-Srr | 38.20 | -122.02 | 8 | 3.4 | (Bergamaschi & Windham-Myers, 2018) |
| US-StJ | 39.08 | -75.43 | 6.7 | 3.5 | (Vazquez-Lule & Vargas, 2020) |
| US-Tw1 | 38.10 | -121.64 | -5 | 4.64 | (Valach et al., 2016) |
| US-Tw4 | 38.10 | -121.64 | -5 | 5.36 | (Eichelmann et al., 2020) |
| US-Twt | 38.11 | -121.65 | -7 | 3.18 | (Knox et al., 2016) |
| US-Var | 38.41 | -120.95 | 129 | 2 | (Ma et al., 2016) |

 Table S2.
 AmeriFlux details for the station used in the study.

- Eichelmann, E., Knox, S., Sanchez, C. R., Valach, A., Sturtevant, C., Szutu, D., ... Baldocchi,
 D. (2020). Fluxnet-ch4 us-tw4 twitchell east end wetland. doi: 10.18140/FLX/1669698
- Flerchinger, G. (2017a). Ameriflux us-rms rcew mountain big sagebrush. doi: 10.17190/AMF/ 1375202
- Flerchinger, G. (2017b). Ameriflux us-rws reynolds creek wyoming big sagebrush. doi: 10.17190/ AMF/1375201
- Flerchinger, G. (2018). Ameriflux us-rls rcew low sagebrush. doi: 10.17190/AMF/1418682
- Flerchinger, G. (2020). Ameriflux US-Rwf rcew upper sheep prescribed fire. doi: 10.17190/AMF/ 1617724
- Goslee, S. (2021). Ameriflux us-hwb usda ars pasture sytems and watershed management research unit- hawbecker site. Retrieved from https://www.osti.gov/biblio/1811363 doi: 10 .17190/AMF/1811363
- Huggins, D. (2021). Ameriflux fluxnet-1f us-cf1 caf-ltar cook east. doi: 10.17190/AMF/1832158
- Huggins, D. (2022a). Ameriflux fluxnet-1f us-cf2 caf-ltar cook west. doi: 10.17190/AMF/ 1881573
- Huggins, D. (2022b). Ameriflux fluxnet-1f us-cf3 caf-ltar boyd north. doi: 10.17190/AMF/ 1881574
- Huggins, D. (2022c). Ameriflux fluxnet-1f us-cf4 caf-ltar boyd south. doi: 10.17190/AMF/ 1881575
- Knox, S., Matthes, J. H., Verfaillie, J., & Baldocchi, D. (2016). Ameriflux us-twt twitchell island. Retrieved from https://www.osti.gov/biblio/1246140 doi: 10.17190/AMF/1246140
- Kusak, K., Sanchez, C. R., Szutu, D., & Baldocchi, D. (2022). Ameriflux fluxnet-1f us-snf sherman barn. doi: 10.17190/AMF/1854371

- Ma, S., Xu, L., Verfaillie, J., & Baldocchi, D. (2016). Ameriflux us-var vaira ranch- ione. doi: 10.17190/AMF/1245984
- Matthes, J. H., Sturtevant, C., Oikawa, P., Chamberlain, S. D., Szutu, D., Ortiz, A. A., ... Baldocchi, D. (2020). *Fluxnet-ch4 us-myb mayberry wetland.* doi: 10.18140/FLX/1669685
- Oikawa, P. (2021). Ameriflux fluxnet-1f us-edn eden landing ecological reserve. doi: 10.17190/ AMF/1832159
- Rey-Sanchez, C., Wang, C. T., Szutu, D., Hemes, K., Verfaillie, J., & Baldocchi, D. (2022). Ameriflux fluxnet-1f us-bi2 bouldin island corn. doi: 10.17190/AMF/1871135
- Rey-Sanchez, C., Wang, C. T., Szutu, D., Shortt, R., Chamberlain, S. D., Verfaillie, J., & Baldocchi, D. (2022). Ameriflux fluxnet-1f us-bi1 bouldin island alfalfa. doi: 10.17190/ AMF/1871134
- Shortt, R., Hemes, K., Szutu, D., Verfaillie, J., & Baldocchi, D. (2022). Ameriflux fluxnet-1f us-sne sherman island restored wetland. doi: 10.17190/AMF/1871144
- Silveira, M. (2021). Ameriflux fluxnet-1f us-ona florida pine flatwoods. doi: 10.17190/AMF/ 1832163
- Valach, A., Shortt, R., Szutu, D., Eichelmann, E., Knox, S., Hemes, K., ... Baldocchi, D. (2016). Ameriflux us-tw1 twitchell wetland west pond. doi: 10.17190/AMF/1246147
- Vazquez-Lule, A., & Vargas, R. (2020). Fluxnet-ch4 us-stj st jones reserve. doi: 10.18140/FLX/ 1669695
- Vivoni, E. R. (2020). Ameriflux us-srs santa rita experimental range mesquite savanna. doi: 10.17190/AMF/1660351
- Wagner-Riddle, C. (2019). Ameriflux ca-er1 elora research station. Retrieved from https://www.osti.gov/biblio/1579541 doi: 10.17190/AMF/1579541