A Comparative Study of Pre-training and Self-training

Yiheng Wang^{*} Jiayu Lin^{*†} Zuoquan Lin[†] Information and Computation Science Department Peking University wangyiheng@stu.pku.edu.cn {linjiayu,linzuoquan}@pku.edu.cn

Abstract

Pre-training and self-training are two approaches to semi-supervised learning. The comparison between pre-training and self-training has been explored. However, the previous works led to confusing findings: self-training outperforms pre-training experienced on some tasks in computer vision, and contrarily, pre-training outperforms self-training experienced on some tasks in natural language processing, under certain conditions of incomparable settings. We propose, comparatively and exhaustively, an ensemble method to empirical study all feasible training paradigms combining pre-training, self-training, and fine-tuning within consistent foundational settings comparable to data augmentation. We conduct experiments on six datasets, four data augmentation, and imbalanced data for sentiment analysis and natural language inference tasks. Our findings confirm that the pre-training and fine-tuning paradigm yields the best overall performances. Moreover, self-training offers no additional benefits when combined with semi-supervised pre-training. ¹

1 Introduction

Semi-supervised learning (SSL) involves the utilization of both labeled and unlabeled data, typically relies on a constrained amount of labeled data, and improves learning performance through the incorporation of a larger set of unlabeled data (for surveys, see [28, 33]).

^{*}Equal contributions.[†] Correspondence authors.

¹Our codes are available at https://github.com/PKUAI-LINGroup/PAS.

Pre-training and *self-training* are two approaches in SSL (for surveys, see [37, 1]). While pre-training and self-training share similarities that leverage unlabeled data, their methodologies and applications also have distinct differences.

In pre-training, a model is initially trained on a large amount of unlabeled data in a self-supervised way. This pre-trained model is then fine-tuned on smaller labeled data in a supervised way for the specific tasks. *Fine-tuning* is the supervised component of semi-supervised pre-training. The pre-training and fine-tuning paradigm involves training with unlabeled data and then labeled data, which can continue multiple times. Unsupervised pre-training or self-supervised pre-training refers to the pre-training conducted without subsequent fine-tuning. The pre-training and fine-tuning paradigm yields superior results for specific tasks than unsupervised pre-training. Continual pre-training refers to the pre-training and fine-tuning paradigm conducted as an additional step to continue pre-training on task-specific unlabeled data before fully supervised fine-tuning [11].

In self-training, on the other hand, the teacher model is initially trained on a small set of labeled data. The model then makes predictions on the unlabeled data, and the data points with high-confidence predictions are pseudo-labeled and added to the labeled data, resulting in the student model. The model is trained on this expanded labeled and pseudo-labeled data, and the process is iterated. The teacher and student paradigm involves training first with labeled data and then acquiring high-confidence pseudo-labels from additional unlabeled data. Self-training incorporates a form of label propagation through pseudo-labeling from unlabeled data, effectively extending the labeled data. Pre-training does not involve label propagation, instead, it centers on representation learning through patterns and structures inherent in unlabeled data.

Due to the prominence of pre-trained large language models (LLMs), pre-training remains the best practice under scaling laws (for a survey, see [36]). While self-trained large models have yet to emerge, self-training and its interplay with pre-training have garnered increasing research interest.

The comparison between pre-training and self-training has been explored. In [38] experienced in computer vision (CV), the finding was that self-training is stronger than pre-training in the following sense: Self-training performed effectively in the same setup where pre-training failed. In [23, 21] experienced in natural language processing (NLP), the finding was that pre-training is stronger than self-training in the following sense: Continual pre-training performed better than various self-training methods. These findings led to confusion. The comparison between pre-training and self-training about these findings is somewhat unfair and lacks clarity, especially given the different settings and extra techniques involved (for detail see the section 2).

In this paper, we revisit the relationship between pre-training and self-training, while also rethinking the limitations that may prevent one from improving the performance of the other. To our knowledge, we are the first to propose an ensemble method to comparatively and exhaustively investigate all feasible training paradigms combining pre-training, self-training, and fine-tuning. In particular, we employ language models, or so-called foundation models (for a survey, see [4])), as consistent foundational settings across all paradigms of ensemble training for downstream tasks. We employ data augmentation techniques to enhance the effectiveness of self-training. We undertake an empirical study to assess the effectiveness of the ensemble paradigms, specifically targeting six datasets, four data augmentation, and imbalanced data for sentiment analysis and natural language inference tasks in NLP. Our contributions are the findings summarized as follows:

- (1) We find that semi-supervised pre-training consistently outperforms self-training and all the other training paradigms, exhibiting robust performance across varying intensities of data augmentation.
- (2) We find that the combination of pre-training, fine-tuning, and self-training yields no benefit over the pre-training and fine-tuning paradigm. In other words, self-training offers no additional benefits when combined with semi-supervised pre-training.
- (3) We find a modest decline in pre-training performance in scenarios characterized by data imbalance; conversely, other training paradigms experienced a significant reduction in efficacy.

2 Related works

The relationship between pre-training and self-training has been examined from two perspectives: first, to evaluate the relative strengths of pre-training versus self-training; and second, to investigate how combining these two methods can mutually enhance their overall effectiveness.

Pre-training vs. self-training. As the first comparative study to challenge the prevailing paradigm of pre-training with self-training [38], this research posited that self-training is stronger than pre-training experienced in CV. Specifically, the self-training demonstrated superior performance compared to the pre-training, particularly under conditions of enhanced data augmentation and increased availability of labeled data for image recognition tasks. Notably, these experiments employed unsupervised pre-training without subsequent fine-tuning. This result contrasts with the strong baseline established by pre-trained language models. It is widely acknowledged that smaller models utilized in these experiments lack the capacity for zero-shot or few-shot learning, a capability present in LLMs [6, 36]. The substantial data and strong augmentation leveraged in the self-training are not adequately mirrored in unsupervised pre-training; thus, this comparative discrepancy

renders the performance comparisons between pre-training and self-training somewhat inequitable.

In [23, 21], the authors argued that pre-training is stronger than self-training experienced in NLP. Specifically, continual pre-training with or without prompt templates showed superior performance to several self-training methods for natural language understanding tasks. Compared to continual pre-training in a task-specific way, the self-training methods employed back-translation as data augmentation [18]. However, a comparison still needs to be made between unsupervised pre-training used in a task-agnostic manner and self-training.

Pre-training & **self-training**. Two complementary can be identified in combining pretraining and self-training. One involves utilizing pre-training to enhance self-training [26, 10, 32, 15, 22]. The effectiveness of self-training is heavily dependent on the quality of the pseudo labels, underscoring the importance of a high-performing initial teacher model. In this context, the teacher model of self-training is typically initialized using pre-trained language models [26, 32], such as BERT or RoBERTa, as demonstrated in [15, 10, 22]. This paradigm enhances model calibration and has gained traction for effectively combining self-training with pre-training, showcasing a strongly additive relationship between the two methods.

The other entails employing self-training to improve pre-training [38, 8, 10, 17, 29, 12, 14]. Self-training improved upon pre-training, demonstrating a strong additive effect [38]. Self-training with strong data augmentation offered complementary advantages to unsupervised and continual pre-trained language models [10, 17]. Notably, most of these experiments did not conduct a comparison with the pre-training and fine-tuning paradigm. The complementary relationship between self-training and pre-training was further explored in [29, 12]. In [14], self-training was utilized in a task-specific manner as a form of unsupervised fine-tuning, aimed at improving the performance of zero-shot learning in pre-trained models. Almost all of these self-training methods rely on strong data augmentation. Therefore, it is necessary to consider the effect of data augmentation when comparing pre-training and self-training.

Historically, self-training was first applied in NLP [34] (originally back [19]). In this work, we contend that a meaningful comparison between pre-training and self-training is achievable only when utilizing consistent foundational settings, particularly language models. This is especially relevant as both NLP and CV serve as downstream tasks that can be analogized to data augmentation. It is important to exclude additional training and techniques specifically developed in prior studies to prevent incomparable settings and potentially conflicting conclusions. We aim to establish a fair comparison between pre-training and self-training within the context of language models. Embracing the pre-training and fine-tuning paradigm is crucial, as it closely mirrors the teacher-student paradigm em-

ployed in self-training. Unlike previous studies, we confirm that the pre-training and finetuning paradigm achieves the best overall performance, with no additional benefits from combining it with self-training.

3 Method

We revisit the comparison and complementarity between pre-training and self-training, while also rethinking the limitations that may prevent one from improving the performance of the other. To this end, comparatively and exhaustively, we propose an ensemble method to study all feasible training paradigms combining pre-training and self-training within consistent foundational settings.

Ensemble principles. When considering (unsupervised) pre-training and fine-tuning as separate processes, we identify three training components: pre-training, fine-tuning, and self-training. When combining pre-training and self-training, it is crucial to determine whether fine-tuning is included in the training protocol. It's important to recognize that not all combinations of these three components are feasible or effective for training. When designing the ensemble for these three training components, we consider the following principles:

- A training component cannot occur consecutively, as adjacent identical training components are considered the same.
- Pre-training can only serve as the initial component of an ensemble. If the pretrained model is initialized during training any prior training becomes irrelevant.
- Self-training requires the unlabeled data in iterations and can only be performed once unless additional unlabeled data becomes available.

Paradigms and notations. According to the ensemble principles, we list all feasible paradigms of ensemble training. For convenience, we use the abbreviation notations for various paradigms described in Table 1.

We leave F along, i.e. supervised training, and P, i.e. unsupervised pre-training, as baselines that are not SSL. Most of the previous works [26, 38, 8, 10, 32, 15, 10, 17, 29, 12] belong to PFS (see the section 2). In [10], the student model was also initialized with the pre-trained model, which can be viewed as a variant of PFS (an analysis see Figure 2 in the section 4). In [14], an unsupervised classifier included self-training is similar to PS.

SF, PSF, and PFSF have not been explored in prior research. We examine these paradigms for some considerations. One major challenge in self-training is semantic drift, where accumulating incorrect pseudo labels can misguide the training process over time.

Notations	Description
F (Fine-tuning)	Supervised training.
P (Pre-training)	Unsupervised pre-training.
S (Self-training)	Self-training.
PF (Pre-training \rightarrow Fine-tuning)	Pre-training first and then fine-tuning.
SF (Self-training→Fine-tuning)	Fine-tuning the student model in the last iteration of
	self-training.
PS (Pre-training→Self-training)	Self-training iterations commence based on pre-
	trained initial teacher model.
PSF (Pre-training→Self-training	
→Fine-tuning)	Fine-tuning the student model in the last iteration of
	PS.
PFS (Pre-training→Fine-tuning	
\rightarrow Self-training)	Fine-tune a pre-trained model as the initial teacher
	model of self-training.
PFSF (Pre-training→Fine-tuning	
\rightarrow Self-training \rightarrow Fine-tuning)	Fine-tuning the student model in the last iteration of
	PFS.

Table 1: Notations for the paradigms.

A potential solution to this problem is to fine-tune the final student model using labeled data. The complex PFSF is depicted in Figure 1 (for self-training strategy refer to the explanation below). To some extent, other paradigms can be regarded as special parts of PFSF. As we shall see later, the limitation of PFSF is that increasing training costs does not necessarily bring efficiency.

Self-training. We use a competitive version of pseudo-labeling by using a self-paced curriculum strategy in the context of self-training [7]. Pseudo-labeling is trained incrementally by iteratively propagating labels from labeled data to unlabeled data using the model, re-labeling high-confidence predictions, and retraining with labeled and pseudo-labeled data. Instead of adding all pseudo-labeled data in each iteration in original pseudo-labeling [13], self-pace pseudo-labeling carefully selects a subset of the most confident data to help guide the model towards harder samples in a controlled manner, improving performance. The algorithm is briefly described as follows:

- (1) Train: The teacher model is first trained on the labeled data.
- (2) *Predict*: Pseudo-labels are assigned to the unlabeled data using the current model.



Figure 1: The training process of PFSF: Fine-tuning the student model in the last iteration of the self-training that fine-tunes a pre-trained model as its initial teacher model.

- (3) *Select*: A subset of pseudo-labeled data is selected based on their prediction scores and percentile thresholds.
- (4) *Re-train*: The student model is trained from scratch using both labeled and selected pseudo-labeled data.
- (5) *Repeat*: Steps (2-4) are repeated until all data in the dataset have been used during training.

To alleviate concept drift and confirmation bias, the model parameters are reinitialized before each iteration. This ensures that previous erroneous predictions do not accumulate over time (for detail, refer to [7]).

Language models. We employ language models as consistent foundational settings across all paradigms of ensemble training for various downstream tasks. Specifically, we utilize the transformer-based BERT model as our initial backbone [9].

We value BERT's encoding representation capability, as we do not primarily consider the generation capability of language models. Moreover, we choose the basic BERT model by two key considerations: first, we aim to avoid using stronger pre-trained language models to maintain a level playing field for self-training; second, we know that utilizing pretrained language models as the initial teacher model enhances the self-training process. The effectiveness of self-training is heavily dependent on the calibration of the teacher model, as inaccurate pseudo-labels generated by the initial teacher can misguide the training of the student model.

Data augmentation. Data augmentation (DA) artificially increases the size of a training dataset by generating modified versions of existing data points, addressing the challenge of limited labeled data like SSL. Previous research has shown that experiments favoring self-training over pre-training often employed data augmentation to enhance the effectiveness of self-training. Consequently, we investigate the impact of four data augmentation strategies of varying intensities on different paradigms of ensemble training, including natural noise, conditional BERT, and back-translation.

Datasets	Labeled	Unlabeled	Valiadation	Test
IMDB	15,000	50,000	25,000	25,000
SST	7,349	60,000	1,800	1,800
AG News	10,000	50,000	7k600	7,600
Elec	25,000	200,000	25,000	25,000
SNLI	10,000	50,000	10,000	10,000
MultiNLI	10,000	50,000	10,000	10,000

Table 2: Statistics of the datasets.

Natural noise is a data augmentation technique in NLP that simulates common human errors, introducing character-level and word-level mistakes to enhance comprehension [2]. Conditional BERT addresses data-label mismatch via masked language modeling, allowing it to generate sentences aligned with specific labels during fine-tuning [31]. Additionally, back-translation involves translating text to a target language and back to the source to create augmented data that retains the original meaning while varying its form [20], facilitated by tools like Fairseq [18].

4 Experiments

4.1 Datasets

We conduct experiments on two tasks in NLP: sentiment analysis (SA) and natural language inference (NLI). NA identifies the emotions and feelings expressed in text and is a text classification problem with two or more classes. We use four datasets: IMDB [16], SST [25], AG News [35] and Elec [24]. NLI judges whether the premise and the hypothesis match, and the result can be *True*, *False*, and *Undetermined*. We use two datasets: SNLI [5] and MultiNLI [30]. The statistics of the datasets are shown in Table 2.

4.2 Implementations

We employ BERT to map input text into a feature space. We attach a linear layer as a classifier atop the BERT model for classification tasks. We utilize BERT in two configurations: BERT-medium, which comprises 8 layers with a hidden size of 512, 8 attention heads, and an intermediate size of 2048 [3, 27], and BERT-base, which comprises 12 layers with a hidden size of 768, 12 attention heads, and an intermediate size of 3072 [9].

For the select step in self-training (refer to the section 3), we retrieve the top R%

Daradiams			NA			NLI
r ai auigilis	IMDB	SST	Elec	AG News	SNLI	MultiNLI
F	.8391	.7580	.8775	.8453	.5274	.4343
Р	.5000	.5000	.5000	.2500	.3333	.3333
S	.8556	.7695	.8776	.8800	.5427	.4424
PF	.8878	.8658	.9246	.8882	.7696	.6578
SF	.8404	.7661	.8747	.8739	.5407	.4448
PS	.8540	.7833	.8766	.8803	.4703	.4245
PSF	.8451	.7775	.8769	.8672	.5306	.4290
PFS	.8551	.7672	.8778	.8797	.5344	.4502
PFSF	.8482	.7649	.8762	.8786	.5408	.4426

Table 3: Accuracy of the paradigms.

(the multiples of 10 or 20) confident data with R improving as the number of iterations increases from all unlabeled data. As usual, we set the learning rate as 1e-5 and batch size as 64 and trained the model within 20 epochs and 40 epochs for BERT-medium and BERT-base respectively.

4.3 Results

We conduct experiments for each paradigm of ensemble training on all the datasets to observe the performance. The results are shown in Table 3, from which we can find the following facts:

- Self-training (S) is effective, surpassing the baselines (F and P).
- The pre-training and fine-tuning paradigm (PF) demonstrates the best performance across all the datasets. This verifies the superiority of PF.
- The accuracy of S, PS, and PFS are close, which reveals the invalidity of the pretrained teacher model with or without fine-tuning (see more discussions in the section 5).
- Fine-tuning has either resulted in negligible improvement or a slight decline in the performance of S, PS, and PFS, which indicates that the information in labeled data has already been exploited sufficiently.

Strategy	Description
DA0	No data augmentation.
DA1	Natural noise.
DA2	Conditional BERT and natural noise.
DA3	Back-translation, conditional BERT, and natural noise.
DA4	The same as DA3 with larger magnitude.

Table 4: Data augmentation strategies.

Paradigms	DA0	DA1	DA2	DA3	DA4
F	.5641	.7680(+20.39%)	.7697(+20.56%)	.7748(+21.07%)	.7741(+21.00%)
S	.7595	.8199(+6.04%)	.8197(+6.02%)	.8218(+6.23%)	.8178(+5.83%)
SF	.7888	.8132(+2.44%)	.8013(+1.25%)	.7958(+0.7%)	.8168(+2.80%)
PT	.8393	.8413 (+0.02%)	.8411 (+0.18%)	.8446 (+0.53%)	.8377 (-0.16%)
PS	.7370	.8134(+7.64%)	.8104(+7.34%)	.8170(+8%)	.8120(+7.5%)
PSF	.7798	.8021(+2.23%)	.8017(+2.19%)	.8095(+2.97%)	.8136(+3.38%)
PFS	.7752	.8201(+4.49%)	.8176(+4.24%)	.8191(+4.39%)	.8192(+4.40%)
PFSF	.7908	.8141(+2.33%)	.8090(+1.82%)	.8066(+1.58%)	.8202(+2.94%)

Table 5: Accuracy of the paradigms on IMDB using BERT-medium.

4.4 Data augmentation

We perform experiments to assess the effectiveness of varying intensities of data augmentation within ensemble paradigms. We create four data augmentation strategies by integrating natural noise, conditional BERT, and back-translation to ensure increased data augmentation. These strategies are designated as DA1, DA2, DA3, and DA4, as detailed in Table 4, where we write DA0 for no data augmentation for the sake of comparison.

We perform experiments using two datasets: IMDB and SST. We begin by sampling 1,000 instances evenly from each class as labeled data while leaving the unlabeled data unchanged. We then augment the labeled data to a total of 10,000 instances. The objective is to investigate the effects of pre-training intensity and the degree of data augmentation. The findings are detailed in Table 5, Table 6, Table 7, and Table 8.

We've omitted the accuracy of P in these tables due to its trivial nature. The number in the bracket indicates the change magnitude relative to DA0. We find two trends regarding accuracy as the magnitude of data augmentation increases:

• Accuracy initially rises and then declines as the extent of the data augmentation strategy grows.

Paradigms	DA0	DA1	DA2	DA3	DA4
F	.5001	.7713(+27.12%)	.7742(+27.41%)	.7685(+26.84%)	.7662(+26.61%)
S	.7927	.8202(+2.75%)	.8162(+2.35%)	.8209(+2.82%)	.7794(-1.33%)
SF	.8023	.8195(+1.72%)	.8164(+1.41%)	.8180(+1.57%)	.7867(-1.56%)
PT	.8470	.8709 (+2.39%)	.8742 (+2.72%)	.8807 (+3.37%)	.8736 (+2.66%)
PS	.7741	.8222(+4.81%)	.8179(+4.38%)	.8252(+5.11%)	.7967(+2.26%)
PSF	.7747	.8232(+4.85%)	.8172(+4.25%)	.8195(+4.48%)	.8012(+2.65%)
PFS	.7827	.8182(+3.55%)	.8127(+3.00%)	.8182(+3.25%)	.8074(+2.47%)
PFSF	.7830	.8195(+3.65%)	.8157(+3.27%)	.8180(+3.50%)	.8117(+2.87%)

Table 6: Accuracy of the paradigms on IMDB using BERT-base.

Paradigms	DA0	DA1	DA2	DA3	DA4
F	.5722	.7007(+12.85%)	.6984(+12.62%)	.6972(+12.5%)	.6961(+12.39%)
S	.6927	.7259(3.32%)	.7133(+2.06%)	.7087(+1.6%)	.7087(+1.6%)
SF	.6869	.7236(+3.67%)	.7167(+2.98%)	.6915(+0.46%)	.7156(+2.87%)
PT	.8096	.8257 (+1.61%)	.8119 (+0.23%)	.7982 (-1.14%)	.8073 (-0.23%)
PS	.5401	.6720(+13.19%)	.6307(+9.06%)	.6984(+15.83%)	.6800(+13.99%)
PSF	.5849	.6755(+9.06%)	.6755(+9.06%)	.6892(+10.43%)	.6915(+10.66%)
PFS	.6697	.7213(+5.16%)	.7236(+5.39%)	.7133(+4.36%)	.7259(+5.62%)
PFSF	.6846	.7053(+2.07%)	.7179(+3.33%)	.6915(+0.69%)	.7144(+2.98%)

Table 7: Accuracy of the paradigm on SST using BERT-medium.

Paradigms	DA0	DA1	DA2	DA3	DA4
F	.5092	.6881(+17.89%)	.6846(+17.54%)	.6991(+18.99%)	.6778(+16.86%)
S	.6250	.7385(+11.35%)	.7179(+9.29%)	.7213(+9.63%)	.7397(+11.47%)
SF	.6904	.7351(+4.47%)	.7122(+2.18%)	.7156(+2.52%)	.7339(+4.35%)
PT	.8773	.8865 (+0.92%)	.8716 (-0.57%)	.8784 (+0.11%)	.8693 (-0.8%)
PS	.5952	.7076(+11.24%)	.6709(+7.57%)	.7167(+12.15%)	.6479(+5.27%)
PSF	.5688	.7099(+14.11%)	.6686(+9.98%)	.7053(+13.65%)	.6823(+11.35%)
PFS	.6892	.7420(+5.58%)	.7305(+4.43%)	.7225(+3.63%)	.7351(+4.89%)
PFSF	.6823	.7443(+6.2%)	.7259(+4.36%)	.7202(+3.79%)	.7305(+4.82%)

Table 8: Accuracy of the paradigms on SST using BERT-medium.

• Accuracy increases initially and then stabilizes, indicating that moderate data augmentation enhances performance, whereas excessive augmentation is ineffective and

Danadiama]	[MDB	AG News	
rarauigins	balanced	imbalanced	balanced	imbalanced
F	.8391	.7894(-4.97%)	.8453	.7418(-9.73%)
S	.8556	.8531(-0.25%)	.8800	.4487(-43.14%)
SF	.8404	.8163(-2.41%)	.8739	.4654(-40.85%)
PF	.8878	.8471(-4.07%)	.8882	.8391 (-4.91%)
PS	.8540	.8532(-0.08%)	.8803	.6566(-22.37%)
PSF	.8451	.8231(-2.2%)	.8672	.6513(-21.59%)
PFS	.8551	.8547 (-0.4%)	.8797	.5633(-31.64%)
PFSF	.8482	.8042(-4.4%)	.8786	.5691(-30.95%)

Table 9: Accuracy of the paradigms on imbalanced data.

may even hinder results.

Additionally, the pre-training and fine-tuning paradigm demonstrates greater stability than other paradigms. It shows resistance to variations in data augmentation magnitude and does not depend on sufficient labeled data.

Our observations reveal that when using pre-trained weights, stronger pre-training knowledge (BERT-base) outperforms weaker pre-training knowledge (BERT-medium) in scenarios with no data augmentation and moderate data augmentation. While most paradigms that utilize pre-training knowledge, apart from PF, struggle with strong pre-training under excessive data augmentation, PF shows improvement. Specifically, PS, PFS, PSF, and PFSF exhibit poorer performance or only marginal increases compared to PF. Employing a stronger pre-training model results in a wider performance gap between PF and the other paradigms.

4.5 Imbalanced data

Data imbalance is a prevalent issue that hinders model performance, prompting us to examine the effectiveness of the paradigms in this context. To create imbalanced training data, we sample from the original datasets and conduct experiments on two datasets: IMDB for binary classification and AG News for four-category classification. The data ratio for IMDB is set at 1:5, while for AG News, the ratio is 1:1:1:7. The results of these experiments are demonstrated in Table 9. The number in the bracket indicates the change magnitude relative to balanced data.

In binary classification, the performance of the paradigms does not experience a significant decline. However, the four-category classification shows a marked drop in performance across the paradigms. Notably, PS and PSF demonstrate greater resilience to the adverse effects of data imbalance compared to PFS and PFSF, while PFS and PFSF maintain more stability than S and SF. Although most other paradigms face substantial decreases, PF maintains consistent performance with a few value changes.

5 Discussions

We discuss the reasons behind the failure of PFS in the experiments. Unlike previous studies, we find that self-training and pre-training do not function as complementarity. Notably, there are instances where PFS performs worse than S. To delve deeper into this issue, we analyze the evaluation accuracy for each iteration in PFS.

As illustrated in Figure 2 (a)(b) for PFS with random initialization (written as PFS Random-init), i.e. regular self-training described in the section 3, there is a significant drop in performance during the first iteration, followed by gradual improvements in subsequent iterations, but converges to poor performance. This pattern indicates that the student model in the initial iteration struggles to retain the collective knowledge gained during pre-training. We hypothesize that this may result from inefficient knowledge transfer from the pre-trained teacher model to the student model through pseudo-labels in the process of PFS.

We consider the PFS with a student model with sufficient pre-training knowledge to test our hypothesis. To inject pre-trained knowledge into a student model, the student model is initialized with pre-trained parameters and then fine-tuned by labeled and pseudo-labeled data in each iteration (written as PFS Pre-init). We find that the PFS outperforms both PF and S, as depicted in Figure 2 (c)(d). This observation illustrates that the PFS with sufficient pre-training knowledge succeeds in improving upon PF and provides evidence to support our hypothesis.

6 Conclusions

We proposed an ensemble method to empirically explore all feasible training paradigms that combine pre-training, self-training, and fine-tuning with language models. Our study revisited the relationship between pre-training and self-training, while critically examining the limitations that may hinder improvements in either approach.

Our findings indicated that the pre-training and fine-tuning paradigm is the most effective among the various training paradigms. While this is not a discovery, it clarifies existing research on self-training and its interaction with pre-training. This analysis provides valuable insights for future design considerations and assists in selecting the most



Figure 2: Accuracy of each iteration for PFS with different initialization.

appropriate learning strategies.

References

- Massih-Reza Amini, Vasilii Feofanov, Loic Pauletto, Lies Hadjadj, Emilie Devijver, and Yury Maximov. Self-training: A survey. *arXiv preprint arXiv:2202.12040*, 2022.
 2
- [2] Yonatan Belinkov and Yonatan Bisk. Synthetic and natural noise both break neural machine translation. In 6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings. OpenReview.net, 2018. 8

- [3] Prajjwal Bhargava, Aleksandr Drozd, and Anna Rogers. Generalization in NLI: Ways (not) to go beyond simple heuristics. In *Proceedings of the Second Workshop on Insights from Negative Results in NLP*, pages 125–135, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. 8
- [4] Rishi Bommasani, Drew A. Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S. Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, Erik Brynjolfsson, S. Buch, Dallas Card, Rodrigo Castellon, Niladri S. Chatterji, Annie S. Chen, Kathleen A. Creel, Jared Davis, Dora Demszky, Chris Donahue, Moussa Doumbouya, Esin Durmus, Stefano Ermon, John Etchemendy, Kawin Ethayarajh, Li Fei-Fei, Chelsea Finn, Trevor Gale, Lauren E. Gillespie, Karan Goel, Noah D. Goodman, Shelby Grossman, Neel Guha, Tatsunori Hashimoto, Peter Henderson, John Hewitt, Daniel E. Ho, Jenny Hong, Kyle Hsu, Jing Huang, Thomas F. Icard, Saahil Jain, Dan Jurafsky, Pratyusha Kalluri, Siddharth Karamcheti, Geoff Keeling, Fereshte Khani, O. Khattab, Pang Wei Koh, Mark S. Krass, Ranjay Krishna, Rohith Kuditipudi, Ananya Kumar, Faisal Ladhak, Mina Lee, Tony Lee, Jure Leskovec, Isabelle Levent, Xiang Lisa Li, Xuechen Li, Tengyu Ma, Ali Malik, Christopher D. Manning, Suvir P. Mirchandani, Eric Mitchell, Zanele Munyikwa, Suraj Nair, Avanika Narayan, Deepak Narayanan, Benjamin Newman, Allen Nie, Juan Carlos Niebles, Hamed Nilforoshan, J. F. Nyarko, Giray Ogut, Laurel Orr, Isabel Papadimitriou, Joon Sung Park, Chris Piech, Eva Portelance, Christopher Potts, Aditi Raghunathan, Robert Reich, Hongyu Ren, Frieda Rong, Yusuf H. Roohani, Camilo Ruiz, Jack Ryan, Christopher R'e, Dorsa Sadigh, Shiori Sagawa, Keshav Santhanam, Andy Shih, Krishna Parasuram Srinivasan, Alex Tamkin, Rohan Taori, Armin W. Thomas, Florian Tramèr, Rose E. Wang, William Wang, Bohan Wu, Jiajun Wu, Yuhuai Wu, Sang Michael Xie, Michihiro Yasunaga, Jiaxuan You, Matei A. Zaharia, Michael Zhang, Tianyi Zhang, Xikun Zhang, Yuhui Zhang, Lucia Zheng, Kaitlyn Zhou, and Percy Liang. On the opportunities and risks of foundation models. arXiv preprint arXiv:2108.07258, 2021. 3
- [5] Samuel R. Bowman, Gabor Angeli, Christopher Potts, and Christopher D. Manning. A large annotated corpus for learning natural language inference. In Lluís Màrquez, Chris Callison-Burch, and Jian Su, editors, *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 632–642, Lisbon, Portugal, September 2015. Association for Computational Linguistics. 8
- [6] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon

Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners, 2020. 3

- [7] Paola Cascante-Bonilla, Fuwen Tan, Yanjun Qi, and Vincente Ordonez. Curriculum labeling: Revisiting pseudo-labeling for semi-supervised learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 6912–6920, Online, February 2021. Association for the Advancement of Artificial Intelligence. 6, 7
- [8] Ting Chen, Simon Kornblith, Kevin Swersky, Mohammad Norouzi, and Geoffrey Hinton. Big self-supervised models are strong semi-supervised learners. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, NIPS'20, Red Hook, NY, USA, 2020. Curran Associates Inc. 4, 5
- [9] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pretraining of deep bidirectional transformers for language understanding. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. 7, 8
- [10] Jingfei Du, Edouard Grave, Beliz Gunel, Vishrav Chaudhary, Onur Celebi, Michael Auli, Veselin Stoyanov, and Alexis Conneau. Self-training improves pre-training for natural language understanding. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 5408–5418, Online, June 2021. Association for Computational Linguistics. 4, 5
- [11] Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A. Smith. Don't stop pretraining: Adapt language models to domains and tasks, 2020. 2
- [12] Gi-Cheon Kang, Sungdong Kim, Jin-Hwa Kim, Donghyun Kwak, and Byoung-Tak Zhang. Generative self-training improves pre-training for visual dialog. In *First Workshop on Pre-training: Perspectives, Pitfalls, and Paths Forward at ICML 2022*, 2022. 4, 5
- [13] Dong-Hyun Lee. Pseudo-label: The simple and efficient semi-supervised learning method for deep neural networks. In *Workshop on challenges in representation learning, ICML*, volume 3, 2013. 6

- [14] Junnan Li, Silvio Savarese, and Steven Hoi. Masked unsupervised self-training for label-free image classification. In *The Eleventh International Conference on Learning Representations*, 2023. 4, 5
- [15] Shiyang Li, Semih Yavuz, Wenhu Chen, and Xifeng Yan. Task-adaptive pre-training and self-training are complementary for natural language understanding. In *Findings* of the Association for Computational Linguistics: EMNLP 2021, pages 1006–1015, Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. 4, 5
- [16] Andrew L. Maas, Raymond E. Daly, Peter T. Pham, Dan Huang, Andrew Y. Ng, and Christopher Potts. Learning word vectors for sentiment analysis. In *Proceedings* of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies, pages 142–150, Portland, Oregon, USA, June 2011. Association for Computational Linguistics. 8
- [17] Fei Mi, Wanhao Zhou, Lingjing Kong, Fengyu Cai, Minlie Huang, and Boi Faltings. Self-training improves pre-training for few-shot learning in task-oriented dialog systems. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 1887–1898, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. 4, 5
- [18] Myle Ott, Sergey Edunov, Alexei Baevski, Angela Fan, Sam Gross, Nathan Ng, David Grangier, and Michael Auli. fairseq: A fast, extensible toolkit for sequence modeling. In *Proceedings of the 2019 Conference of the North American Chapter* of the Association for Computational Linguistics (Demonstrations), pages 48–53, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. 4, 8
- [19] Henry Scudder. Probability of error of some adaptive pattern-recognition machines. *IEEE Transactions on Information Theory*, 11(3):363–371, 1965. 4
- [20] Rico Sennrich, Barry Haddow, and Alexandra Birch. Improving neural machine translation models with monolingual data. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 86–96, Berlin, Germany, August 2016. Association for Computational Linguistics. 8
- [21] Zhengxiang Shi and Aldo Lipani. Don't stop pretraining? make prompt-based fine-tuning powerful learner. Advances in Neural Information Processing Systems, 36:5827–5849, 2023. 2, 4

- [22] Zhengxiang Shi and Aldo Lipani. Don't stop pretraining? make prompt-based finetuning powerful learner. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine, editors, *Advances in Neural Information Processing Systems*, volume 36, pages 5827–5849. Curran Associates, Inc., 2023. 4
- [23] Zhengxiang Shi, Francesco Tonolini, Nikolaos Aletras, Emine Yilmaz, Gabriella Kazai, and Yunlong Jiao. Rethinking semi-supervised learning with language models. arXiv preprint arXiv:2305.13002, 2023. 2, 4
- [24] Devendra Singh. ssl-text-classification. https://github.com/DevSinghSachan/ ssl_text_classification, 2019. 8
- [25] Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D. Manning, Andrew Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the 2013 Conference on Empirical Methods in Natural Language Processing*, pages 1631–1642, Seattle, Washington, USA, October 2013. Association for Computational Linguistics. 8
- [26] Zijun Sun, Chun Fan, Xiaofei Sun, Yuxian Meng, Fei Wu, and Jiwei Li. Neural semi-supervised learning for text classification under large-scale pretraining, 2020.
 4, 5
- [27] Iulia Turc, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Well-read students learn better: The impact of student initialization on knowledge distillation. *CoRR*, abs/1908.08962, 2019. 8
- [28] Jesper E Van Engelen and Holger H Hoos. A survey on semi-supervised learning. Machine Learning, 109(2):373–440, 2020. 1
- [29] Changhan Wang, Anne Wu, Juan Pino, Alexei Baevski, Michael Auli, and Alexis Conneau. Large-Scale Self- and Semi-Supervised Learning for Speech Translation. In *Proc. Interspeech 2021*, pages 2242–2246, 2021. 4, 5
- [30] Adina Williams, Nikita Nangia, and Samuel Bowman. A broad-coverage challenge corpus for sentence understanding through inference. In Marilyn Walker, Heng Ji, and Amanda Stent, editors, Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers), pages 1112–1122, New Orleans, Louisiana, June 2018. Association for Computational Linguistics. 8

- [31] Xing Wu, Shangwen Lv, Liangjun Zang, Jizhong Han, and Songlin Hu. Conditional bert contextual augmentation. In *Computational Science - ICCS 2019: 19th International Conference, Faro, Portugal, June 12 - 14, 2019, Proceedings, Part IV*, pages 84–95, Berlin, Heidelberg, 2019. Springer-Verlag. 8
- [32] Qiantong Xu, Alexei Baevski, Tatiana Likhomanenko, Paden Tomasello, Alexis Conneau, Ronan Collobert, Gabriel Synnaeve, and Michael Auli. Self-training and pretraining are complementary for speech recognition. In ICASSP 2021 - 2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pages 3030–3034, 2021. 4, 5
- [33] Xiangli Yang, Zixing Song, Irwin King, and Zenglin Xu. A survey on deep semisupervised learning. *IEEE Transactions on Knowledge and Data Engineering*, 35(9):8934–8954, 2023. 1
- [34] David Yarowsky. Unsupervised word sense disambiguation rivaling supervised methods. In 33rd annual meeting of the association for computational linguistics, pages 189–196, 1995. 4
- [35] Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In *Proceedings of the 28th International Conference on Neural Information Processing Systems - Volume 1*, NIPS'15, pages 649–657, Cambridge, MA, USA, 2015. MIT Press. 8
- [36] Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, Yifan Du, Chen Yang, Yushuo Chen, Zhipeng Chen, Jinhao Jiang, Ruiyang Ren, Yifan Li, Xinyu Tang, Zikang Liu, Peiyu Liu, Jian-Yun Nie, and Ji-Rong Wen. A survey of large language models, 2023. 2, 3
- [37] Ce Zhou, Qian Li, Chen Li, Jun Yu, Yixin Liu, Guangjing Wang, Kai Zhang, Cheng Ji, Qiben Yan, Lifang He, et al. A comprehensive survey on pretrained foundation models: A history from bert to chatgpt. *arXiv preprint arXiv:2302.09419*, 2023. 2
- [38] Barret Zoph, Golnaz Ghiasi, Tsung-Yi Lin, Yin Cui, Hanxiao Liu, Ekin D Cubuk, and Quoc V Le. Rethinking pre-training and self-training. *arXiv preprint arXiv:2006.06882*, 2020. 2, 3, 4, 5