Federated Prototype-based Contrastive Learning for Privacy-Preserving Cross-domain Recommendation

Li Wang, Quangui Zhang, Lei Sang, Qiang Wu, Senior Member, IEEE, and Min Xu*, IEEE, Member

Abstract-Cross-domain recommendation (CDR) aims to improve recommendation accuracy in sparse domains by transferring knowledge from data-rich domains. However, existing CDR methods often assume the availability of user-item interaction data across domains, overlooking user privacy concerns. Furthermore, these methods suffer from performance degradation in scenarios with sparse overlapping users, as they typically depend on a large number of fully shared users for effective knowledge transfer. To address these challenges, we propose a Federated Prototype-based Contrastive Learning (CL) method for Privacy-Preserving CDR, named FedPCL-CDR. This approach utilizes non-overlapping user information and prototypes to improve multi-domain performance while protecting user privacy. FedPCL-CDR comprises two modules: local domain (client) learning and global server aggregation. In the local domain, FedPCL-CDR clusters all user data to learn representative prototypes, effectively utilizing non-overlapping user information and addressing the sparse overlapping user issue. It then facilitates knowledge transfer by employing both local and global prototypes returned from the server in a CL manner. Simultaneously, the global server aggregates representative prototypes from local domains to learn both local and global prototypes. The combination of prototypes and federated learning (FL) ensures that sensitive user data remains decentralized, with only prototypes being shared across domains, thereby protecting user privacy. Extensive experiments on four CDR tasks using two real-world datasets demonstrate that FedPCL-CDR outperforms the state-of-the-art baselines.

Index Terms—Contrastive Learning, Federated Learning, Prototype, and Cross-Domain Recommendation

I. INTRODUCTION

Cross-domain recommendation (CDR) has emerged as a critical strategy to address the challenge of data sparsity in recommendation systems by transferring knowledge, such as user-item interaction histories and review texts, across domains [1], [2]. Based on different recommendation scenarios, existing CDR can be divided into two categories: single-target CDR and multi-target CDR. The first genre [3], [4] aims to improve recommendation performance in the target domain by utilizing rich information from the source domain. However, it cannot enhance model performance across multiple domains simultaneously. To address this issue, multi-target CDR [5], [6] has emerged. Literature focusing on feature aggregation [3], [7] and feature disentanglement [8], [9] has been proposed to



Fig. 1. The illustrations of knowledge transfer via overlapping and non-overlapping users.

further improve recommendation performance. Feature aggregation methods typically learn representations in each domain separately and then design an aggregation function to combine these representations. On the other hand, feature disentanglement approaches concentrate on separating domain-common and domain-specific embeddings and transferring domaincommon embeddings across domains. Although these works have achieved good performance, they still face two major challenges.

CH1. How to effectively protect user privacy when transferring knowledge across domains? Most existing literature [7], [10], [11] cannot solve this problem well. They usually assume that the user-item ratings or representations are directly transferred across domains. However, in the setting of privacy-preserving, these methods are unsuitable [12]. To resolve this problem, some privacy-preserving CDR methods [13]–[15] have gained lots of attention. For example, PriCDR [13] first introduces Differential Privacy (DP) technology to publish the source rating matrix and subsequently conduct CDR modeling. P2FCDR [14] independently learns embeddings in each domain using orthogonal functions and applies the local differential privacy (LDP) technique to protect these embeddings. However, these approaches introduce a trade-off between privacy preservation and recommendation accuracy, as the added noise can distort the underlying data patterns.

CH2. How to improve recommendation performance with few overlapping users across domains? Many existing CDR methods depend on fully overlapping users as a bridge to transfer knowledge across domains [7], [8]. For example, as shown in Figure 1, John is an overlapping user with interactions in both the Movie and Book domains. If knowledge transfer is solely based on fully overlapping users, John may be interested in the comedic book "Bossypants" because he watches movies in the same genre, like "Anchor-

Li Wang, Qiang Wu, and Min Xu are with the School of Electrical and Data Engineering, University of Technology Sydney, Sydney 2000, Australia. Shoujin Wang is with the institute of data science, University of Technology Sydney, Sydney 2000, Australia. Quangui Zhang is with the School of Artificial Intelligence, Chongqing University of Arts and Sciences, Chongqing 402160, China.

^{*}Corresponding author: Min Xu (e-mail: Min.Xu@uts.edu.au)

man." However, in real-world datasets, there are very few overlapping users. For instance, the Amazon dataset has only a 5% overlapping user ratio [11]. As a result, the model performance will be degraded with such sparse overlapping users. To address this problem, we can utilize non-overlapping user information to improve recommendation performance. For instance, Lily shares similar interests with John based on their common interaction with the movie "Anchorman". By effectively utilizing Lily's interests, we can infer that John may like the thriller book "Gone Girl" based on Lily's preference for the thriller movie "Get Out", which couldn't be realized by relying solely on fully overlapping users.

To address these challenges, we propose FedPCL-CDR, a federated prototype-based contrastive learning (CL) approach for privacy-preserving CDR (PPCDR). Our method consists of two key modules, i.e., local domain learning and global server aggregation, where user-item interaction histories and review texts are stored in local domains and knowledge is transferred via prototypes within the federated learning (FL) framework, ensuring user privacy. Specifically, in the local domain, we first learn comprehensive user and item embeddings from user-item interactions and review texts. Subsequently, we utilize k-means clustering [16] to generate prototypes (cluster centroids). On one hand, these prototypes convey overlapping and nonoverlapping user preferences as they are derived from the interest alignments of all entities in the domain. On the other hand, these prototypes serve as generalized representations of group-level preferences, making it more difficult for attackers to infer sensitive information about individual users. We then select representative prototypes based on overlapping users and upload them to the global server. The global server, in turn, models both local and global prototypes by aggregating these representative prototypes and transmits them back to the respective local domains. To effectively transfer knowledge, the local domain refines user embeddings by using both local and global prototypes in a CL manner. This dual-prototype approach allows for transferring knowledge at varying granularities, enabling more nuanced learning of user embeddings from different perspectives.

In summary, our proposed model makes the following contributions:

- We introduce a novel federated prototype-based CL approach for PPCDR that aims to solve the sparse overlapping user and privacy protection concerns.
- Our method effectively leverages non-overlapping users for knowledge transfer by clustering all users, thereby enhancing model performance in scenarios with sparse overlapping users across domains.
- We utilize local and global prototypes to transfer knowledge within the FL framework, protecting user privacy.
- Extensive experiments on four CDR tasks from two large-scale real-world datasets, Amazon and Douban, demonstrate the effectiveness of FedPCL-CDR compared to state-of-the-art baselines.

II. RELATED WORK

A. Cross Domain Recommendation

Cross-domain recommendation (CDR) aims to address the challenge of data sparsity by transferring cross-domain knowledge [17]. The core step in CDR involves designing an effective transfer method to improve recommendation accuracy in sparse domains. With the advancements in deep learning, various transfer methods have emerged in CDR, including learning mapping functions across domains [18], feature combination [7], feature alignment [19], and transfer methods based on Graph Neural Networks (GNNs) [20], [21]. However, these approaches depend on fully overlapping users for knowledge transfer and overlook concerns about user privacy leakage. In this paper, we propose FedPCL-CDR to address these challenges.

B. Privacy-Preserving CDR

With the increasing attention on user privacy, many scholars have begun studying PPCDR methods [12]–[14], [22]–[26]. PriCDR [13] and PPGenCDR [22] both use DP to protect user-item ratings during knowledge transfer. P2FCDR [14] is a privacy-preserving federated framework that learns an orthogonal mapping matrix to transform embeddings across domains and applies LDP to the transformed embeddings for user privacy protection. Meanwhile, PPCDR [12] introduces a federated graph framework that utilizes FL and LDP technologies to protect user privacy. Despite their effectiveness, these PPCDR methods must strike a balance between utility and privacy. We propose a prototype-based FL framework to address these limitations.

C. Contrastive Learning

Contrastive Learning (CL) has been widely used in computer vision [27], [28] and natural language processing [29], [30]. It is a self-supervised learning technique that aims to maximize the mutual information between two representations. To achieve this, InfoNCE [31] is proposed to learn representations by contrasting positive pairs (similar samples) against negative pairs (dissimilar samples), which discovers the semantic information shared by different views. Nowadays, CL has been applied to the CDR to improve representation learning [11], [19], [32], [33]. For instance, DCCDR [19] leverages CL to learn domain-specific and domain-invariant representations. Meanwhile, CL-DTCDR [11] utilizes CL to learn more representative user and item embeddings with useritem interaction data and side information. However, these methods directly utilize user-item ratings or representations to construct positive and negative pairs across domains, which is not feasible under privacy-preserving constraints. In this work, we construct prototype-based CL tasks to transfer crossdomain user interests, thereby protecting user privacy.

III. METHODOLOGY

A. Definitions and Notations

We assume there are M domains (clients) denoted as $\{D^1, D^2, ..., D^M\}$ and a global server, where D^i denotes the



Fig. 2. The framework of FedPCL-CDR. (1) Local Domain Learning: It focuses on mining non-overlapping user information by clustering all user data and transferring user interests across domains using local and global prototypes in a CL manner; It can be further divided into three components: (a) Graph Representation Learning: Introducing LightGCN to learn comprehensive user and item embeddings. (b) Clustering and Prototype Selection: Clustering all user embeddings to obtain prototypes and then select representative prototypes based on overlapping users. (c) Prototype-based Contrastive Learning: Facilitating knowledge transfer across domains in a contrastive manner using both local and global prototypes. (2) Global Server Aggregation: It aggregates representative prototypes uploaded from multiple domains to generate local and global prototypes.

i-th domain. Within each domain, there exists a user set U^i and an item set V^i . There are partial overlapping users and nonoverlapping items across domains. The overlapping user set is denoted as U^o . Let $\mathbf{R}^i \in \{0,1\}^{|U^i| \times |V^i|}$ represent the binary user-item interaction matrix, which is private and cannot be shared across domains. Figure 2 depicts the overall framework of FedPCL-CDR. We illustrate the paradigm for domain D^i , and the corresponding paradigm for other domains can be easily inferred accordingly.

B. Local domain Learning Module

1) Graph Representation Learning: Inspired by the effectiveness of GNNs in capturing high-dimensional and complex relationships between users and items, we adopt LightGCN [34] to learn embeddings for user and item IDs as well as their review texts. We construct a graph G^i , where nodes represent users and items, and edges indicate interactions between them. By utilizing the graph convolution and propagation layers of LightGCN, we encode user and item embeddings based on G^i . Specifically, we denote ID embeddings and review text embeddings at the *l*-th layer as $\mathbf{E}_l^{i(id)}$ and $\mathbf{E}_l^{i(rev)}$, respectively. Initially, ID embeddings $\mathbf{E}_l^{i(rev)}$ are randomly initialized, while review text embeddings $\mathbf{E}_l^{i(rev)}$ are learned using the document embedding model Doc2Vec [35]. Given the graph G^i , $\mathbf{E}_l^{i(id)}$ and $\mathbf{E}_l^{i(rev)}$ are calculated as follows:

$$\mathbf{E}_{l}^{i(id)} = (\mathbf{D}^{-1/2} \mathbf{A} \mathbf{D}^{-1/2}) \mathbf{E}_{l-1}^{i(id)};
\mathbf{E}_{l}^{i(rev)} = (\mathbf{D}^{-1/2} \mathbf{A} \mathbf{D}^{-1/2}) \mathbf{E}_{l-1}^{i(rev)},$$
(1)

where **D** is a diagonal matrix and **A** is a adjacency matrix. After *l* times of propagation, we can generate the final user and item ID embedding matrices $\mathbf{E}_{u}^{i(id)}$ and $\mathbf{E}_{v}^{i(id)}$ by concatenating multiple embedding matrices from $\mathbf{E}_{0}^{i(id)}$ to $\mathbf{E}_{l}^{i(id)}$. Similarly, we obtain the user and item review text embedding matrix $\mathbf{E}_{u}^{i(rev)}$ and $\mathbf{E}_{v}^{i(rev)}$. Finally, we concatenate the ID embeddings and review text embeddings to learn comprehensive user and item embeddings:

$$\mathbf{E}_{u}^{i} = f(\mathbf{E}_{u}^{i(id)}; \mathbf{E}_{u}^{i(rev)}); \mathbf{E}_{v}^{i} = f(\mathbf{E}_{v}^{i(id)}; \mathbf{E}_{v}^{i(rev)}), \quad (2)$$

where f represents the concatenation function. Here, we use the element-wise sum aggregation method.

2) Clustering and Prototype Selection: In this subsection, our objective is to generate representative prototypes by clustering the user embeddings \mathbf{E}_{u}^{i} . The clustering process incorporates data from all users within a domain, not limited to overlapping users. This not only leverages the shared knowledge among overlapping users but also explores the effective utilization of knowledge from non-overlapping users.

We begin by introducing the k-means algorithm [16], which aims to cluster user embeddings into K groups. We obtain the cluster centroid set with K clusters:

$$T^{i} = \{\mathbf{t}_{j}^{i}\}_{j=1}^{K} = Kmeans(\mathbf{E}_{u}^{i}),$$
(3)

Each cluster is defined by its centroid, acting as the central representation for that particular group. These centroids are regarded as prototypes, providing a comprehensive integration of information from similar users. As a result, we derive the prototype set $T^i = {\mathbf{t}_1^i, \mathbf{t}_2^i, ..., \mathbf{t}_K^i}$.

We then select representative prototypes by considering overlapping users across domains. This involves choosing prototypes whose clusters include overlapping users. The rationale behind this choice lies in the intention that overlapping users have similar interests in different domains. The representative prototype set is calculated as follows:

$$C^{i} = \{\mathbf{t}_{j}^{i}\}_{j=1}^{K} \xrightarrow{\text{overlapping users}} \{\mathbf{c}_{j}^{i}\}_{j=1}^{K'}, \ K' \leq K.$$
(4)

In addition, we select overlapping users in each cluster to form the overlapping user set O^i :

$$O^{i} = \{o_{j}^{i}\}_{j=1}^{K'}, \ o_{j}^{i} \subset U^{o}.$$
 (5)

Finally, we upload each domain's representative prototype set C^i and overlapping user set O^i to the global server.

3) Prototype-based Contrastive Learning: In the previous subsection, we uploaded representative prototypes to the global server. The server then aggregates these prototypes to derive both local and global prototypes (as further discussed in the next section) and subsequently returns them to local domains. Due to data privacy constraints, direct transfer of original data is not feasible. To address this problem, we employ prototypes and introduce prototype-based CL losses, which comprise a global part and a local part. These prototypes represent the collective preferences of multiple users rather than any single individual, making it more difficult for an attacker to associate a prototype with a specific user.

To transfer knowledge from other domains to domain D^i , we enforce the alignment of user embeddings with corresponding global prototypes while distancing them from distinct global prototypes. The global prototype-based CL loss is defined as follows:

$$L^{i}_{global} = -log \frac{exp(f(\mathbf{e}^{i}_{u}, \mathbf{g}^{i}_{k}))}{exp(f(\mathbf{e}^{i}_{u}, \mathbf{g}^{i}_{k})) + \sum_{\mathbf{g}^{i}_{j} \in A(\mathbf{g}^{i}_{k}), j \neq k} exp(f(\mathbf{e}^{i}_{u}, \mathbf{g}^{i}_{j}))},$$
(6)

where \mathbf{g}_k^i denotes the global prototype corresponding to cluster k, to which the user embedding \mathbf{e}_{u}^{i} belongs. We regard $(\mathbf{e}_{u}^{i}, \mathbf{g}_{k}^{i})$ that belongs to the same cluster as a positive pair. Conversely, \mathbf{g}_{i}^{i} denotes the global prototype corresponding to cluster j, to which user embedding \mathbf{e}_{u}^{i} doesn't belong, and $(\mathbf{e}_{u}^{i}, \mathbf{g}_{i}^{i})$ forms a negative pair. $A(\mathbf{g}_k^i)$ is the set of global prototypes excluding \mathbf{g}_k^i . f indicates a similar function. We define it as:

$$f(\mathbf{e}_{u}^{i}, \mathbf{g}_{k}^{i}) = \frac{\mathbf{e}_{u}^{i} \cdot \mathbf{g}_{k}^{i}}{||\mathbf{e}_{u}^{i}|| \times ||\mathbf{g}_{k}^{i}||} / \tau,$$
(7)

where τ represents the temperature coefficient, which controls the concentration strength of representation [36].

In addition to the global prototype-based CL loss, we introduce the local prototype-based CL loss to align \mathbf{e}_{u}^{i} with local prototypes of each domain through domain-wise CL in the latent space, enhancing inter-domain knowledge sharing. The local prototype-based CL loss is defined as follows:

$$L_{local}^{i} = -\frac{1}{M} \sum_{m=1}^{M} \log \frac{exp(f(\mathbf{e}_{u}^{i}, \mathbf{l}_{k}^{m}))}{exp(f(\mathbf{e}_{u}^{i}, \mathbf{l}_{k}^{m})) + \sum_{\mathbf{l}_{j}^{i} \in A(\mathbf{l}_{k}^{i}), j \neq k} exp(f(\mathbf{e}_{u}^{i}, \mathbf{l}_{j}^{i}))}, \text{ The local prototype set can be}$$

$$(8) \quad \{L_{1}^{i}, L_{2}^{i}, ..., L_{K'}^{i}\}.$$

where \mathbf{I}_k^m denotes the local prototype of cluster k from domains that have overlapping users with the cluster to which the user embedding \mathbf{e}_{u}^{i} belongs. \mathbf{l}_{k}^{i} indicates the local prototype of cluster k that includes \mathbf{e}_{u}^{i} , and $A(\mathbf{l}_{k}^{i})$ is the set of local prototypes excluding \mathbf{l}_{k}^{i} .

The global and local prototypes capture cluster-relevant information at different granularity, guiding the transfer of user interests from various perspectives.

4) Local Training: After refining the user embedding \mathbf{e}_{u}^{i} , we concatenate it with the item embedding \mathbf{e}_v^i and feed them into MLP layers to predict the user's preferences. We aim to minimize the following loss function:

$$L^i_{prd} = l(\hat{r}^i, r^i), \tag{9}$$

where l denotes the cross-entropy loss function, \hat{r}^i is the predictive label, and r^i is the ground-truth label.

The total loss function is defined as follows:

$$L^{i} = L^{i}_{prd} + \alpha (L^{i}_{global} + L^{i}_{local}), \tag{10}$$

where α is the trade-off parameter that balances the prediction loss and prototype-based CL losses. The detailed training process is in Algorithm 1 of Appendix A.

C. Global Server Aggregation

After receiving representative prototype set C and overlapping user set O from all domains, the global server calculates global prototypes for each domain. First, for overlapping user set $o_k^i \in O^i$, we construct the prototype set C_k^i that includes all representative prototypes containing overlapping users with o_k^i across domains:

$$\hat{C}_k^i = \bigcup_{i' \in D, k' \le K'} \{ \mathbf{c}_{k'}^{i'} | o_{k'}^{i'} \cap o_k^i \neq \emptyset \}.$$

$$(11)$$

Then, we calculate the global prototype \mathbf{g}_k^i for cluster k:

$$\mathbf{g}_{k}^{i} = \frac{1}{\hat{K}} \sum_{k=1}^{K} \hat{\mathbf{c}}_{k}^{i}, \qquad (12)$$

where \hat{K} is the length of prototype set \hat{C}_k^i .

Finally, we form the global prototype set G^i = $\{\mathbf{g}_{1}^{i}, \mathbf{g}_{2}^{i}, ..., \mathbf{g}_{K'}^{i}\}$. The global prototype incorporates user preferences across domains from a high-level perspective.

Different from the global prototypes, for the local prototypes, we select some representative prototypes in all domains rather than a single one via similarity calculation. Specifically, for each representative prototype \mathbf{c}_k^i , we first calculate the cosine similarity between \mathbf{c}_k^i and representative prototypes from other domains that include overlapping users with o_{i}^{i} . Then, we select the representative prototype with maximum similarity to \mathbf{c}_{k}^{i} in each domain to form the local prototype set L_k^i for cluster k:

$$L_k^i = \{ \hat{\mathbf{c}}_k^i \}_{k=1}^{\hat{K}} \xrightarrow{\text{similarity}} \{ \mathbf{l}_k^i \}_{k=1}^M, M \le \hat{K}.$$
(13)

represented as L^i =

After aggregation, the global server sends the global and local prototype sets G^i and L^i into the local domain D^i .

D. Privacy Preserving Analysis

The proposed FedPCL-CDR effectively ensures user privacy. Firstly, within the FL framework, the data in each domain remains private and localized, significantly reducing the risk of user privacy leakage [37], [38]. Secondly, knowledge transfer across domains is facilitated through prototypes, which naturally protect data privacy [39]. These prototypes are 1-D vectors derived from averaging low-dimensional representations of samples within the same cluster, which is an irreversible process. We provide a detailed example in Appendix B.

IV. EXPERIMENTS

A. Experimental Settings

1) Datasets.: Motivated by CDR methods [8], [14], [19], we conduct experiments on four real-world benchmark subsets from the Amazon dataset¹: Phone, Electronics (Elec), Clothing, Shoes nad Jewelry (Cloth), and Sport, and three subsets from the Douban dataset²: Book, Movie, and Music. We combine them into four CDR tasks. Table 1 of Appendix C presents basic statistics for these datasets. For each dataset, we transform the explicit ratings into implicit feedback. To improve data quality, we employ filtering criteria, removing records with fewer than 10 interactions for all users and items, in accordance with existing research [40], [41].

2) Parameter Settings and Evaluation.: We obtain optimal hyperparameters by optimizing the loss function (10) using the Adam optimizer with a learning rate of 0.001. The weight α for the prototype-based CL losses is set to 0.01. Additionally, the embedding size is fixed at 64, and the batch size is set to 128. The temperature coefficient in CL is established at 0.2, and the cluster number is set to 10. Furthermore, we apply batch normalization, dropout, and early stopping techniques to prevent overfitting. We use Hit Ratio (HR) and Normalized Discounted Cumulative Gain (NDCG) as evaluation metrics, which are frequently used in CDR methods [3], [5], [42].

3) Baseline Methods.: We compare the performance of FedPCL-CDR with SOTA baselines including NeuMF [43], LightGCN [34], FedNCF [44], GA-DTCDR [7], NMCDR [10], CL-DTCDR [11], GA-MTCDR-P [5], PriCDR [13], and P2FCDR [14], which are widely used in CDR approaches [9], [11], [24]. In Appendix D, we provide detailed descriptions of these baselines.

B. Experimental Results and Analysis

1) Performance Evaluation.: We evaluate the performance of FedPCL-CDR and the baselines using commonly used evaluation metrics w.r.t. HR@10 and NDCG@10. From the experimental results in Table I, We can observe that:

 Our model, FedPCL-CDR, surpasses other baselines, showcasing its capability to achieve satisfactory performance while also safeguarding user privacy. Specifically, FedPCL-CDR outperforms the top-performing CDR baseline by an average of 7.38% in HR@10 and 4.86% in NDCG@10 across all tasks. This improvement can be attributed to the following reasons: (1) FedPCL-CDR efficiently utilizes non-overlapping user data to transfer cross-domain knowledge, which is particularly beneficial in scenarios with sparse overlapping users, such as Phone&Sport. (2) By constructing prototype-based CL tasks, FedPCL-CDR achieves more effective knowledge transfer.

- FedPCL-CDR outperforms single-domain federated methods such as FedNCF. This demonstrates the significant role of cross-domain knowledge in enhancing recommendation performance within the FL framework. In addition, FedPCL-CDR performs better than PriCDR and P2FCDR, indicating that methods leveraging prototypes and FL for user privacy protection surpass those utilizing differential privacy technology. Moreover, FedPCL-CDR exceeds the performance of GA-DTCDR, which depends on fully overlapping users for knowledge transfer. This indicates that effectively utilizing non-overlapping user information can improve model performance. Finally, although our method and CL-DTCDR both use CL to transfer knowledge, FedPCL-CDR still performs better than CL-DTCDR, showing that our method not only protects user privacy but also improves model performance.
- GNN-based methods outperform non-graph methods, such as LightGCN vs NeuMF. This demonstrates that incorporating high-order neighbor information can improve model accuracy.
- CDR methods consistently outperform single-domain approaches, as evidenced by the comparison between GA-DTCDR and NeuMF. This shows that cross-domain knowledge can alleviate the data-sparsity issue.

2) Ablation Studies.: To validate the effectiveness of each component in FedPCL-CDR, we conducted ablation experiments. We created two variants: (1) w/o loc-proto: we eliminate the local prototype-based CL loss. (2) w/o glob-proto: we remove the global prototype-based CL loss. The results of the ablation studies are shown in Table II. We can observe that: (1) The inferior performance of models w/o loc-proto and w/o glob-proto demonstrates the significant contributions of local and global prototype-based CL to the outcome. (2) In general, w/o loc-proto contributes more, which shows that local prototype-based CL plays an important role in improving model performance. In conclusion, each component in FedPCL-CDR plays a crucial role, demonstrating the rationality and effectiveness of our design.

3) Performance for different proportions of overlapping users.: To assess FedPCL-CDR's capability in addressing sparse overlapping users within CDR, we manipulate the overlapping ratio specifically for Task 1 across different settings. These varying ratios signify different levels of commonality, where a higher ratio indicates a greater number of overlapping users across domains. For instance, in Task 1 with the "Phone-Sport" dataset and an overlapping ratio of 30%, the number of overlapping users is computed as 655 * 30% = 196. Due to space limitations, we report results about several representative CDR methods. The corresponding results with different overlapping ratio are shown in Table III. As the overlapping ratio

¹https://cseweb.ucsd.edu/ jmcauley/datasets/amazon/links.html

²https://www.dropbox.com/s/u2ejjezjk08lz1o/Douban.tar.gz?e=2&dl=0

 TABLE I

 EXPERIMENTAL RESULTS ON FOUR CDR TASKS. THE BEST PERFORMANCE IS IN BOLD, AND THE SECOND BEST IS UNDERLINED.

Task	Domain	Metric	NeuMF	LightGCN	FedNCF	GA-DTCDR	GA-MTCDR-P	NMCDR	CL-DTCDR	PriCDR	P2FCDR	FedPCL-CDR	Imp
Task 1	Phone	HR	0.3490	0.3552	0.3477	0.3809	0.3827	0.3841	0.5277	0.3553	0.3756	0.5933	6.56%
		NDCG	0.2141	0.2267	0.2034	0.2285	0.2304	0.2349	0.3193	0.2259	0.2267	0.3949	7.56%
	Sport	HR	0.3134	0.3257	0.3018	0.3749	0.3799	0.3914	0.5660	0.3687	0.4235	0.6766	11.06%
		NDCG	0.1886	0.1939	0.1593	0.2056	0.2148	0.2166	0.3344	0.2389	0.2578	0.4534	11.90%
Task 2	Elec	HR	0.4065	0.4124	0.3921	0.4568	0.4585	0.5234	0.5404	0.4234	0.4873	0.6078	6.74%
		NDCG	0.3300	0.3315	0.3223	0.3402	0.3417	0.3316	0.3592	0.3534	0.3552	0.4018	4.26%
	Cloth	HR	0.2207	0.2367	0.2133	0.3044	0.2969	0.3030	0.4435	0.2816	0.3021	0.5018	5.83%
		NDCG	0.1215	0.1402	0.1045	0.2156	0.2024	0.1965	0.2511	0.1856	0.2035	0.3166	6.55%
	Phone	HR	0.3490	0.3552	0.3477	0.4021	0.4093	0.4823	0.5159	0.3915	0.4329	0.5970	8.11%
		NDCG	0.2141	0.2267	0.2034	0.2614	0.2705	0.3142	0.3059	0.2621	0.2804	0.3844	7.02%
	Movie	HR	0.3294	0.3325	0.3145	0.3629	0.3691	0.3787	0.3525	0.3459	0.3703	0.4379	8.54%
T 1 2		NDCG	0.1768	0.1867	0.1505	0.1955	0.2014	0.2156	0.2016	0.2286	0.2037	0.2356	3.40%
Task 3	Music	HR	0.2686	0.2639	0.2987	0.3142	0.3187	0.3225	0.3351	0.3044	0.3223	0.4518	11.67%
		NDCG	0.1468	0.1503	0.1789	0.1980	0.2004	0.2288	0.2310	0.2072	0.2159	0.2487	1.77%
Task 4	Book	HR	0.2907	0.3045	0.2847	0.3869	0.3891	0.3796	0.4431	0.3525	0.3684	0.4724	2.93%
		NDCG	0.1830	0.1904	0.1809	0.2260	0.2318	0.2316	0.2772	0.1902	0.2132	0.2865	0.93%
	Movie	HR	0.3294	0.3325	0.3145	0.374	0.3687	0.3703	0.4328	0.3336	0.3856	0.4601	2.73%
		NDCG	0.1768	0.1867	0.1505	0.1894	0.1769	0.1968	0.2221	0.1530	0.2046	0.2444	2.23%
	Music	HR	0.2686	0.2639	0.2987	0.3142	0.3178	0.3525	0.3521	0.3050	0.3169	0.4745	12.20%
		NDCG	0.1468	0.1503	0.1689	0.1780	0.1795	0.1888	0.1877	0.1685	0.1736	0.2059	1.71%

TABLE II Ablation studies on FedPCL-CDR.

Teals	Damain	Matria	w/o	w/o	FedPCL-CDR	
Task	Domain	Metric	loc-proto	glob-proto		
	Dhama	HR@10	0.5796	0.5870	0.5933	
Tasla 1	Phone	NDCG@10	0.3853	0.3862	0.3949	
Task I	Canant	HR@10	0.6610	0.6721	0.6766	
	Sport	NDCG@10	0.4468	0.4495	0.4534	
	Flag	HR@10	0.5980	0.6011	0.6087	
	Elec	NDCG@10	0.3908	0.3931	0.4018	
Tasla 0	Clash	HR@10	0.4954	0.5006	0.5018	
Task 2	Ciota	NDCG@10	0.3123	0.3137	0.3166	
	Dhama	HR@10	0.5863	0.5811	0.5970	
	Phone	NDCG@10	0.3733	0.3743	0.3844	
	Dool	HR@10	0.4915	0.4967	0.5009	
Tesla 2	DOOK	NDCG@10	0.2896	0.2876	0.2980	
Task 3	Mouio	HR@10	0.4608	0.4595	0.4621	
	wiovie	NDCG@10	0.2352	0.2444	0.2450	
	Dool	HR@10	0.4688	0.4677	0.4724	
	DOOK	NDCG@10	0.2727	0.2769	0.2865	
Tasl: 4	Mouio	HR@10	0.4506	0.4514	0.4601	
Task 4	wiovie	NDCG@10	0.2291	0.2285	0.2444	
	Maria	HR@10	0.4532	0.4388	0.4745	
	wiusic	NDCG@10	0.2619	0.2514	0.2691	

increases, the performance of all models demonstrates improvement. This is intuitively sensible, as a higher overlapping ratio implies a greater number of shared users, facilitating a more straightforward transfer of cross-domain knowledge. The performance of GA-DTCDR and PriCDR shows significant fluctuations, primarily because they heavily rely on fully overlapping users. In contrast, both NMCDR, CL-DTCDR and our method, FedPCL-CDR, demonstrate relatively minor changes, indicating that effectively transferring knowledge across nonoverlapping users can enhance performance and ensure model stability.

4) Empirical Study of Privacy.: In this subsection, we demonstrate the privacy-preserving capabilities of our FedPCL-CDR model by simulating an attack in which an attacker attempts to reconstruct the original user embeddings from intercepted prototypes. We analyze the difficulty of this reconstruction and evaluate the effectiveness of our privacy-preserving mechanisms. We assume that an attacker intercepts

TABLE III Experimental results on Task 1 with different overlapping user ratios.

Domain	overlapping	Matria	CA DTCDP	NMCDP	DriCDD	CL	PedPCL
Domain	user ratio	Meure	UA-DICDK	NNCDK	FIICDK	-DTCDR	-CDR
-	200	HR	0.2042	0.3649	0.2041	0.4954	0.5831
	50%	NDCG	0.1022	0.1994	0.1053	0.2685	0.3852
	500	HR	0.2691	0.3762	0.2110	0.5047	0.5861
Dhama	50%	NDCG	0.1426	0.2078	0.1185	0.2736	0.3886
Phone	70%	HR	0.2838	0.3733	0.2449	0.5124	0.5909
		NDCG	0.1596	0.2037	0.1464	0.2731	0.3825
	100%	HR	0.3809	0.3841	0.3753	0.5277	0.5933
		NDCG	0.2285	0.2349	0.2259	0.3193	0.3949
	2007	HR	0.2520	0.3746	0.1429	0.5292	0.6664
	30%	NDCG	0.1413	0.1951	0.0743	0.3173	0.4453
	500	HR	0.2910	0.3863	0.1865	0.5381	0.6696
Concert	50%	NDCG	0.1713	0.2026	0.1002	0.3203	0.4475
spon	700	HR	0.3144	0.3908	0.2271	0.5493	0.6706
	/0%	NDCG	0.1983	0.2128	0.1286	0.3302	0.4508
	1000	HR	0.3749	0.3914	0.4087	0.5660	0.6766
	100%	NDCG	0.2056	0.2166	0.2389	0.3344	0.4534

the local prototypes during the client-server communication. The attacker employs a deep neural network model to infer the original user embeddings from these intercepted prototypes, training the model to minimize the difference between the reconstructed and actual embeddings. We use Mean Squared Error (MSE) as an evaluation metric to measure the accuracy of the reconstructed embeddings compared to the original ones. We conducted experiments on Tasks 1 and 2 and reported the results in Table IV. These high MSE values indicate that the attacker faces significant difficulty in accurately inferring the original user embeddings from the intercepted prototypes, demonstrating the strong privacy-preserving capabilities of our model.

TABLE IV MSE on Tasks 1 and 2.

Task	Tas	k 1	Task 2				
Domain	Phone	Sport	Elec	Cloth	Phone		
MSE	6.79	10.22	6.80	7.74	5.20		

5) Impact of Hyper-parameters.: In this section, we assess the model's performance across different configurations of two pivotal parameters: the weight parameter α associated with prototype-based CL losses, and the cluster number c. Due to space limitations, we only report HR@10 and NDCG@10 on Tasks 1 (Phone&Sport) and 3 (Movie&Music).

• Impact of α . We employ the parameter α to control the degree of knowledge transfer across domains. To evaluate its impact, we conduct experiments with different α values, namely [0.001, 0.01, 0.1, 0.2]. Figure 3 illustrates the outcomes for HR@10 and NDCG@10. We find that as the weight parameter α increases, the performance first rises and then decreases. FedPCL-CDR achieves optimal results when α is set to 0.01.



Fig. 3. Performance of different α .

• Impact of cluster number c. The number of clusters significantly influences the generalization of prototypes, thereby affecting the learning of user preferences. As shown in Figure 4, our model reaches its peak performance when the number of clusters is set to 10. With the increase in the number of clusters, the HR@10 and NDCG@10 metrics initially rise, reaching a maximum at c = 10, and subsequently decline. This trend can be attributed to the fact that an excessive number of clusters results in overly specific prototypes, which lack generalization capabilities and lead to suboptimal knowledge transfer.



Fig. 4. Performance of different cluster number c.

V. CONCLUSION AND FUTURE WORK

In this paper, we propose a Federated User Preference Modeling framework (FUPM) for PPCDR to address the data sparsity issue while protecting user privacy. Within FUPM, we first design a comprehensive preference exploration module to learn comprehensive user preferences from review texts and potentially positive items. We then devise a private preference transfer module to privately transfer user preferences within the FL framework. Importantly, in order to protect user privacy during cross-domain knowledge transfer, we learn local prototypes and apply LDP techniques to them before transfer. Extensive experimental results on four CDR tasks based on real-world Amazon and Douban datasets demonstrate the effectiveness of our proposed FUPM.

Our study assumes overlapping users and non-overlapping items across domains. While our method can be extended to scenarios with partially overlapping users, it is not applicable to scenarios with no user overlap or only partial item overlap. Future work includes exploring effective methods to address these challenges.

REFERENCES

- F. Zhu, Y. Wang, C. Chen, J. Zhou, L. Li, and G. Liu, "Cross-domain recommendation: Challenges, progress, and prospects," in *Proceedings* of the Thirtieth International Joint Conference on Artificial Intelligence, IJCAI-21, 8 2021, pp. 4721–4728.
- [2] G. Hu, Y. Zhang, and Q. Yang, "Conet: Collaborative cross networks for cross-domain recommendation," in *Proceedings of the 27th ACM international conference on information and knowledge management*, 2018, pp. 667–676.
- [3] F. Zhu, C. Chen, Y. Wang, G. Liu, and X. Zheng, "Dtcdr: A framework for dual-target cross-domain recommendation," in *Proceedings of the* 28th ACM International Conference on Information and Knowledge Management, 2019, pp. 1533–1542.
- [4] Y. Zhu, Z. Tang, Y. Liu, F. Zhuang, R. Xie, X. Zhang, L. Lin, and Q. He, "Personalized transfer of user preferences for cross-domain recommendation," in *Proceedings of the Fifteenth ACM International Conference on Web Search and Data Mining*, 2022, pp. 1507–1515.
- [5] F. Zhu, Y. Wang, J. Zhou, C. Chen, L. Li, and G. Liu, "A unified framework for cross-domain and cross-system recommendations," *IEEE Transactions on Knowledge and Data Engineering*, 2021.
- [6] J. Zhu, Y. Wang, F. Zhu, and Z. Sun, "Domain disentanglement with interpolative data augmentation for dual-target cross-domain recommendation," in *Proceedings of the 17th ACM Conference on Recommender Systems*, 2023, pp. 515–527.
- [7] F. Zhu, Y. Wang, C. Chen, G. Liu, and X. Zheng, "A graphical and attentional framework for dual-target cross-domain recommendation." in *IJCAI*, 2020, pp. 3001–3008.
- [8] J. Cao, X. Lin, X. Cong, J. Ya, T. Liu, and B. Wang, "Disencdr: Learning disentangled representations for cross-domain recommendation," in *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, 2022, pp. 267–277.
- [9] X. Guo, S. Li, N. Guo, J. Cao, X. Liu, Q. Ma, R. Gan, and Y. Zhao, "Disentangled representations learning for multi-target cross-domain recommendation," *ACM Transactions on Information Systems*, vol. 41, no. 4, pp. 1–27, 2023.
- [10] W. Xu, S. Li, M. Ha, X. Guo, Q. Ma, X. Liu, L. Chen, and Z. Zhu, "Neural node matching for multi-target cross domain recommendation," in 2023 IEEE 39th International Conference on Data Engineering (ICDE). IEEE, 2023, pp. 2154–2166.
- [11] J. Lu, G. Sun, X. Fang, J. Yang, and W. He, "A contrastive learning framework for dual-target cross-domain recommendation," in *Proceedings of the 31st ACM International Conference on Multimedia*, 2023, pp. 6332–6339.
- [12] C. Tian, Y. Xie, X. Chen, Y. Li, and X. Zhao, "Privacy-preserving Cross-domain Recommendation with Federated Graph Learning," ACM *Transactions on Information Systems*, vol. 42, no. 5, pp. 1–29, Sep. 2024.
- [13] C. Chen, H. Wu, J. Su, L. Lyu, X. Zheng, and L. Wang, "Differential private knowledge transfer for privacy-preserving cross-domain recommendation," in *Proceedings of the ACM Web Conference 2022*, 2022, pp. 1455–1465.

- [14] G. Chen, X. Zhang, Y. Su, Y. Lai, J. Xiang, J. Zhang, and Y. Zheng, "Win-win: a privacy-preserving federated framework for dual-target cross-domain recommendation," in *Proceedings of the AAAI Conference* on Artificial Intelligence, vol. 37, no. 4, 2023, pp. 4149–4156.
- [15] W. Liu, X. Zheng, C. Chen, J. Xu, X. Liao, F. Wang, Y. Tan, and Y.-S. Ong, "Reducing Item Discrepancy via Differentially Private Robust Embedding Alignment for Privacy-Preserving Cross Domain Recommendation," in *Forty-First International Conference on Machine Learning*, Jun. 2024.
- [16] J. MacQueen, "Classification and analysis of multivariate observations," in 5th Berkeley Symp. Math. Statist. Probability, pp. 281–297.
- [17] T. Zang, Y. Zhu, H. Liu, R. Zhang, and J. Yu, "A Survey on Crossdomain Recommendation: Taxonomies, Methods, and Future Directions," ACM Transactions on Information Systems, vol. 41, no. 2, pp. 1–39, Apr. 2023.
- [18] T. Man, H. Shen, X. Jin, and X. Cheng, "Cross-domain recommendation: An embedding and mapping approach." in *IJCAI*, vol. 17, 2017, pp. 2464–2470.
- [19] R. Zhang, T. Zang, Y. Zhu, C. Wang, K. Wang, and J. Yu, "Disentangled contrastive learning for cross-domain recommendation," in *International Conference on Database Systems for Advanced Applications*. Springer, 2023, pp. 163–178.
- [20] Q. Cui, T. Wei, Y. Zhang, and Q. Zhang, "Herograph: A heterogeneous graph framework for multi-target cross-domain recommendation." in ORSUM@ RecSys, 2020.
- [21] C. Zhao, C. Li, and C. Fu, "Cross-domain recommendation via preference propagation graphnet," in *Proceedings of the 28th ACM international conference on information and knowledge management*, 2019, pp. 2165–2168.
- [22] X. Liao, W. Liu, X. Zheng, B. Yao, and C. Chen, "Ppgencdr: A stable and robust framework for privacy-preserving cross-domain recommendation," arXiv preprint arXiv:2305.16163, 2023.
- [23] C. Gao, C. Huang, Y. Yu, H. Wang, Y. Li, and D. Jin, "Privacy-preserving Cross-domain Location Recommendation," *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies*, vol. 3, no. 1, pp. 1–21, Mar. 2019.
- [24] W. Liu, C. Chen, X. Liao, M. Hu, J. Yin, Y. Tan, and L. Zheng, "Federated probabilistic preference distribution modelling with compactness co-clustering for privacy-preserving multi-domain recommendation," in *Proceedings of the 32rd International Joint Conference on Artificial Intelligence (IJCAI)*, 2023, pp. 2206–2214.
- [25] D. Yan, Y. Zhao, Z. Yang, Y. Jin, and Y. Zhang, "Fedcdr: Privacypreserving federated cross-domain recommendation," *Digital Communications and Networks*, vol. 8, no. 4, pp. 552–560, 2022.
- [26] S. Liu, S. Xu, W. Yu, Z. Fu, Y. Zhang, and A. Marian, "FedCT: Federated Collaborative Transfer for Recommendation," in *Proceedings* of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval, ser. SIGIR '21. New York, NY, USA: Association for Computing Machinery, Jul. 2021, pp. 716–725.
- [27] T. Chen, S. Kornblith, M. Norouzi, and G. Hinton, "A simple framework for contrastive learning of visual representations," in *International conference on machine learning*. PMLR, 2020, pp. 1597–1607.
- [28] K. He, H. Fan, Y. Wu, S. Xie, and R. Girshick, "Momentum contrast for unsupervised visual representation learning," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2020, pp. 9729–9738.
- [29] T. Gao, X. Yao, and D. Chen, "Simcse: Simple contrastive learning of sentence embeddings," arXiv preprint arXiv:2104.08821, 2021.
- [30] Y.-S. Chuang, R. Dangovski, H. Luo, Y. Zhang, S. Chang, M. Soljačić, S.-W. Li, W.-t. Yih, Y. Kim, and J. Glass, "Diffcse: Differencebased contrastive learning for sentence embeddings," *arXiv preprint arXiv:2204.10298*, 2022.
- [31] A. v. d. Oord, Y. Li, and O. Vinyals, "Representation learning with contrastive predictive coding," arXiv preprint arXiv:1807.03748, 2018.
- [32] J. Wu, X. Wang, F. Feng, X. He, L. Chen, J. Lian, and X. Xie, "Selfsupervised graph learning for recommendation," in *Proceedings of the* 44th international ACM SIGIR conference on research and development in information retrieval, 2021, pp. 726–735.
- [33] M. Chen, C. Huang, L. Xia, W. Wei, Y. Xu, and R. Luo, "Heterogeneous graph contrastive learning for recommendation," in *Proceedings of the sixteenth ACM international conference on web search and data mining*, 2023, pp. 544–552.
- [34] X. He, K. Deng, X. Wang, Y. Li, Y. Zhang, and M. Wang, "Lightgen: Simplifying and powering graph convolution network for recommendation," in *Proceedings of the 43rd International ACM SIGIR conference* on research and development in Information Retrieval, 2020, pp. 639– 648.

- [35] Q. Le and T. Mikolov, "Distributed representations of sentences and documents," in *International conference on machine learning*. PMLR, 2014, pp. 1188–1196.
- [36] F. Wang and H. Liu, "Understanding the behaviour of contrastive loss," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2021, pp. 2495–2504.
- [37] C. Wu, F. Wu, Y. Cao, Y. Huang, and X. Xie, "FedGNN: Federated Graph Neural Network for Privacy-Preserving Recommendation," *Nature Communications*, vol. 13, no. 1, p. 3091, Jun. 2022.
- [38] W. Meihan, L. Li, C. Tao, E. Rigall, W. Xiaodong, and X. Cheng-Zhong, "FedCDR: Federated Cross-Domain Recommendation for Privacy-Preserving Rating Prediction," in *Proceedings of the 31st ACM International Conference on Information & Knowledge Management*. Atlanta GA USA: ACM, Oct. 2022, pp. 2179–2188.
- [39] Y. Tan, G. Long, L. Liu, T. Zhou, Q. Lu, J. Jiang, and C. Zhang, "Fedproto: Federated prototype learning across heterogeneous clients," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 36, no. 8, 2022, pp. 8432–8440.
- [40] S. Kang, J. Hwang, D. Lee, and H. Yu, "Semi-supervised learning for cross-domain recommendation to cold-start users," in *Proceedings of the 28th ACM international conference on information and knowledge management*, 2019, pp. 1563–1572.
- [41] C. Zhao, C. Li, R. Xiao, H. Deng, and A. Sun, "Catn: Cross-domain recommendation for cold-start users via aspect transfer network," in *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*, 2020, pp. 229– 238.
- [42] P. Li and A. Tuzhilin, "Ddtcdr: Deep dual transfer cross domain recommendation," in *Proceedings of the 13th International Conference* on Web Search and Data Mining, 2020, pp. 331–339.
- [43] X. He, L. Liao, H. Zhang, L. Nie, X. Hu, and T.-S. Chua, "Neural collaborative filtering," in *Proceedings of the 26th international conference* on world wide web, 2017, pp. 173–182.
- [44] V. Perifanis and P. S. Efraimidis, "Federated neural collaborative filtering," *Knowledge-Based Systems*, vol. 242, p. 108441, 2022.