Galled Perfect Transfer Networks

Alitzel López Sánchez¹ and Manuel Lafond¹

Department of Computer Science. Université de Sherbrooke, 2500 boul de l'Université, J1K2R1 Quebec, Canada {alitzel.lopez.sanchez, manuel.lafond}@usherbrooke.ca

Abstract. Predicting horizontal gene transfers often requires comparative sequence data, but recent work has shown that character-based approaches could also be useful for this task. Notably, perfect transfer networks (PTN) explain the character diversity of a set of taxa for traits that are gained once, rarely lost, but that can be transferred laterally. Characterizing the structure of such characters is an important step towards understanding more complex characters. Although efficient algorithms can infer such networks from character data, they can sometimes predict overly complicated transfer histories.

With the goal of recovering the simplest possible scenarios in this model, we introduce galled perfect transfer networks, which are PTNs that are galled trees. Such networks are useful for characters that are incompatible in terms of tree-like evolution, but that do fit in an almost-tree scenario. We provide polynomial-time algorithms for two problems: deciding whether one can add transfer edges to a tree to transform it into a galled PTN, and deciding whether a set of characters are galled-compatible, that is, they can be explained by some galled PTN. We also analyze a real dataset comprising of a bacterial species trees and KEGG functions as characters, and derive several conclusions on the difficulty of explaining characters in a galled tree, which provide several directions for future research.

Keywords: Galled trees · Horizontal Gene Transfer · Algorithms

1 Introduction

Trees have served as a conventional representation of evolution for centuries in biology. However, contemporary evidence has found frequent exchanges of genetic material between co-existing species, indicating that evolution should rather be expressed as a "web of life". Horizontal Gene Transfer (HGT) is an important force of innovation between and within in all the domains of life [43]. They are known to occur routinely between procaryotes [27,44] but also happen between different domains. For example, the thermotogale bacteria, which thrive in extreme environments, are believed to have acquired several genes from archea [15,35]. HGTs also affect eukaryotes [25], with examples including the acquisition of fructophily from bacteria by yeasts [16] and transfers from parasitic plants to their hosts [46].

Owing to their central role in evolution, several algorithmic approaches have been developed to identify HGTs [39]. *Parametric methods* seek DNA regions

that exhibit a signature that differs from the rest of the genome [29], whereas *phylogenetic methods* rely on the comparison of reconstructed species and gene trees, often using reconciliation [32,4]. Some approaches also use sequence divergence patterns to infer timing discrepancies that correspond to transfers [41,14,28,23].

The vast majority of these methods rely on sequence comparisons. However, sequence-based methods are known to struggle when highly divergent sequences are involved, especially in the presence of ancient transfer events [6]. An alternative is to predict HGTs with *characters*, which are morphological or molecular traits that a taxa may possess or not. Character-based methods have been successfully applied to recover recombination or hybridation events [18]. A fundamental example of character-based data is gene expression, where the trait is whether or not a gene is expressed in a condition of interest [9,38,40], which can sometimes exhibit better phylogenetic signals than similarity measures [1].

These approaches aim to explain the diversity of a set of taxa \mathcal{S} that each possess a subset of characters from a set \mathcal{C} . Ideally, there should be a phylogeny in which, for each character $C \in \mathcal{C}$, the taxa that possess C form a clade. If such a tree exists, it is called a perfect phylogeny [5,12,3,22]. In this setting, perfect phylogenies assume that each character has a unique origin (no-homoplasy), and is always inherited vertically once acquired (no-losses). Of course, these are strong assumptions that rarely apply to real biological datasets. However, understanding this theoretical model has led to multiple extensions with practical applications. Examples include the reconstruction of evolution from Short Interspersed Nuclear Elements (SINE) using partial characters [36]; haplotyping [3]; or the inference of cancer phylogenies, which were modeled as an extension of perfect phylogenies in [11], and broadened to Dollo parsimonies in [10]. Therefore, gaining a deeper understanding of such restricted models can often serve as a stepping stone to reconstruct more complex evolutionary scenarios.

When a perfect phylogeny does not exist for a set of characters, one may instead consider network-like structures to explain this diversity. To this end, Nakhleh et al. introduced $Perfect\ Phylogenetic\ Networks$ (PPNs) in [34,33]. These networks allow multi-state characters and require that, for each character C, the network contains a tree in which nodes in the same state are connected. This is a powerful model that is, unfortunately, difficult to work with, since even deciding whether a known network explains a set of characters is NP-hard. We note that in parallel to our work, this question was studied in the context of binary characters on galled trees [45], which we discuss in more detail below.

Importantly, PPNs were introduced as trees with additional transfer edges. This implies knowledge of the vertical versus horizontal transmissions, and that these networks belong to the class of tree-based networks [37,13] (in fact, they are LGT networks, see next section). In [31], we introduced perfect transfer networks (PTNs), a specialization of PPNs where characters satisfy the same assumptions as perfect phylogenies: they are binary, have a unique origin, and are assumed to always be inherited vertically once acquired. An important difference of PTNs is that one cannot choose which subtree of the network can be used to explain a character, as the tree of vertical inheritance is fixed. Because of this, as we

showed in [31], even PPNs on binary characters are different from PTNs. In the latter, a character may or may not be transferred horizontally to other species. This can be useful for transferrable characters that are difficult to revert, such as material acquired horizontally from mitochondria or chloroplasts resulting from endosymbiotic events [47,2], or in the case of metabolites when HGT plays a role in the generation of new metabolic pathways in bacteria [17]. From an algorithmic standpoint, an advantage of the more restricted PTN model is that the problems of deciding whether a network explains a set of characters, or whether a tree can be augmented with transfers to do so, become polynomial-time solvable.

Thus, PTNs are a promising model for HGT inference from characters. However, PTNs have demonstrated a tendency to introduce an excessive number of transfer events. In [31], we provide an algorithm that shows that *any tree* can be made to explain *any set of characters* by adding transfers, although the resulting networks may be overly complicated and bloated with HGT edges. This raises the question of explaining a set of characters with the *simplest* possible network. One way would be to build a network or augment a tree with a minimum number of transfers, which is an unsolved complexity problem. Another direction is to impose structural conditions on the desired network.

Our contribution. In this work, we focus on the second direction. We explore the evolutionary structure that many consider as the simplest beyond trees, namely galled trees. These consist of networks in which all underlying cycles are independent, and were first used in the context of hybridization and recombination [19]. When they fit the data, galled trees are desirable because of their parsimonious nature and ease of interpretation. They are also a popular graph-theoretical structure that serves as a first-step towards the development of more structurally complex networks [20,8]. In our case, characters that can be explained by a galled tree can be thought of "not quite tree-like, but almost".

We present galled perfect transfer networks (galled PTNs) which are galled tree-based networks with unidirectional edges that explain a set of characters. We then provide polynomial-time algorithms for two problems. In the galled-completion problem, we ask whether it is possible to complete a given tree with transfers to obtain a galled PTN. We also study the galled-compatibility problem in which, given a set of characters, we must decide whether a galled PTN can explain them. During the process, we provide several structural characterizations of characters that can be displayed on a given tree or a network. Althought most of our theoretical results are intuitive, the detailed proofs are sometimes involved. To improve the reading experience, we provide a sketch for most proofs, and refer to the appendix for the full details.

We also propose a case study of perfect transfer networks on a real dataset consisting of bacterial species and functional characters obtained from the Kyoto Encyclopedia of Genes and Genomes (KEGG) database [24]. We show that the conditions required to explain a set of characters with a galled tree are difficult to achieve, as most characters prevent such an explanation, even when taken individually. On the other hand, the case study lets us see that character losses

and unresolved species trees can be responsible for this phenomenon. This leads to future questions such as how to model losses and transfers together, and how character-based transfer prediction can be used to resolve trees.

Related work. Aside from PPNs, other models have been proposed to explain characters via networks. In recombination networks [18], characters are explained by an ancestral recombination graph (ARG) in which hybridation nodes represent recombination events through crossovers. A fundamental difference is that such hybrids do not consider a donor/recipient relationship whereas in HGTs, it can be important to distinguish between the parental and lateral acquisition. As we showed in [31, Figure 3], PTNs and recombination graphs explain different sets of characters, even on galled trees with a single transfer/hybridation event, the main reason being that crossover events are different from transfer events. Nonetheless, it is worth mentioning that in [19], the author shows how to reconstruct a galled ancestral recombination graph from a set of m characters and n taxa, if possible, in time $O(nm+n^3)$. Using this approach, the aforementioned work of Warnow et al. [45] shows how a galled tree can be reconstructed (or not) from a set of characters in the PPN model, where characters are interpreted as bipartitions of the trees contained in the network, achieving the same time complexity. In Section 2, we show how this formulation differs from ours. In a similar vein, in [21,26] the authors study the question of reconstructing a network that displays a set of characters in the *softwired* sense, meaning that for each character, some tree contained in the network contains it as a clade (characters are called *clusters* therein). In particular, one can reconstruct in polynomial time a level-1 network that explains a set of characters, if one exists. As level-1 networks are closely related to galled trees, it is likely that the latter can be used in our setting. But, as also argued in [31, Figure 2], softwired characters can explain different sets of characters than PTNs. The main reason is that distinguishing between horizontal and vertical edges does not allow choosing which tree of the network should be used to explain a character.

2 Preliminaries

A phylogenetic network, or simply a network for short, is a directed acyclic graph N=(V,E) with one node $\rho(N)$ of in-degree zero, called the root. A node of indegree one and outdegree zero is a leaf, and L(N) denotes the set of leaves of N. A node of in-degree and out-degree 1 is a subdivision node, which we allow. For $W\subseteq V,\,N-W$ is the directed graph obtained after removing W and incident edges. An underlying cycle of N is a set of nodes and edges that form a cycle when ignoring the edge directions. A network N is a galled tree if no two distinct underlying cycles of N contain a common node (see Figure 1.(c)).

A tree T is a network with no underlying cycle. We write $u \leq_T v$ if v is on the path from $\rho(T)$ to u, in which case v is an ancestor of u and u a descendant of v (we may drop the T subscript if unambiguous). Note that v is an ancestor and descendant of itself. Two nodes u,v are incomparable in T if none descends from the other, i.e., if neither $u \leq v$ nor $v \leq u$. The parent of a node v in T is

 $p_T(v)$. For $v \in V(T)$, we use T(v) for the subtree of T rooted at v, that is, T(v) contains v and all of its descendants. We may write $L_T(v)$ as a shorthand for L(T(v)), or just L(v) if T is understood. The set L(v) is called a *clade* of T.

An LGT network (where LGT comes from Lateral Gene Transfers) [7] is a network $N = (V, E_S \cup E_T)$, where $\{E_S, E_T\}$ is a specified partition of the edgeset of N, such that the subgraph $\mathcal{T}_N := (V, E_S)$ is a tree with the same set of nodes as N. The tree \mathcal{T}_N is called the support tree of N. The edges in E_S are called support edges and the edges in E_T are called transfer edges. A node that is the endpoint of a transfer edge is called a transfer node. We assume that for each transfer edge $(u, v) \in E_T$, the nodes u and v are incomparable in \mathcal{T}_N . We also assume that transfer nodes have exactly one out-neighbor in \mathcal{T}_N . The tree obtained from \mathcal{T}_N by suppressing its subdivision nodes is called the base tree of N^1 . For $v \in V(N) \setminus \{\rho(N)\}$, we use $p_N(v)$ to denote the unique in-neighbor of v in the support tree of N. For simplicity, an LGT network that is also a galled tree will be called a galled LGT network.

2.1 Perfect transfer networks

Let S be a set of taxa. A character C is a subset of S, which represents the set of taxa that possess the common trait. We usually denote a set of characters by C. To formalize PTNs, given an LGT network N, a C-labeling of N is a function $l:V(N) \to 2^C$ that maps each node to the subset of characters it possesses.

Definition 1. Let S be a set of taxa, let $C \subseteq 2^S$ be a set of characters, and let $N = (V, E_S \cup E_T)$ be an LGT network with leafset S. We say that a C-labeling l of N explains C if the following conditions hold:

- 1. for each leaf x, $l(x) = \{C \in \mathcal{C} : x \in C\}$ (leaves are labeled by their characters);
- 2. for each support edge $(u, v) \in E_S$, $C \in l(u)$ implies that $C \in l(v)$ (never lost once acquired);
- 3. for each $C \in \mathcal{C}$, there exists a unique node $v \in V$ that, in N, reaches every node w satisfying $C \in l(w)$ (single origin).

Furthermore, we call N a perfect transfer network (PTN) for C if there exists a C-labeling of N that explains C.

In short, each character $C \in \mathcal{C}$ must emerge at some node v, then be transmitted to every vertical descendant, and possibly horizontally to other species (and if so, such other species must in turn also transmit to their vertical descendants, and possibly transfer horizontally as well). Figure 1 shows two PTNs for the same set of characters. It does not exhibit the full \mathcal{C} -labeling, but a possible origin of each character is annotated on the internal nodes. In [31], it is shown that any set of characters can be explained by some PTN. In fact, any tree can become a PTN by adding enough transfer edges. Our goal is to constrain the PTNs to avoid overcomplicated solutions.

¹ Suppressing a subdivision node u with parent p and child v consists of removing u and adding an edge from p to v




Fig. 1. (a) A tree and characters C_1, C_2, C_3 . (b) A PTN with T as base tree that is not a galled tree (two underlying cycles contain the left child of the root). Notice for example the circle character C_2 , which does not use any transfer and only needs to be transmitted vertically to its descendants after emergence. On the other hand, the square character C_1 needs to be transferred to two other ancestral species (left and right) after emergence. The triangle character C_3 needs one transfer, and uses the same arc going to the left as C_1 . (c) A different PTN with T as a base tree, which is a galled-completion of T.

Let T be a tree on leafset \mathcal{S} , and let \mathcal{C} be a set of characters. We say that T is galled-completable for \mathcal{C} if there exists a galled LGT network N that explains \mathcal{S} and whose base tree is T. We call such a galled PTN a galled-completion of T. An example of this problem is shown on Figure 1. For a set of characters \mathcal{C} on taxa \mathcal{S} , we say that \mathcal{C} is galled-compatible if there exists a galled tree on leafset \mathcal{S} that explains \mathcal{C} . Our problems of interest are the following:

- The Galled Completion problem: given a tree T on leafset S and a character set C, is T galled-completable for C?
- The Galled Compatibility problem. Given a set of taxa S and a character set C, is C galled-compatible?

2.2 Properties of galled PTNs

We begin by stating properties of galled PTNs that will be useful throughout. Let N be a network that explains a set of characters C. Observe that if a leaf l does not possess a character $C \in C$, then by the "never lost once acquired" condition, the parent of l in \mathcal{T}_N cannot possess C either (otherwise, the parent would be required to transfer C to v). In fact, no ancestor of l in \mathcal{T}_N can possess C. This lets us deduce a subset F_C of nodes that forbid C, as follows:

$$F_C(N) = \{ v \in V(N) : \exists l \in L_{\mathcal{T}_N}(v) \text{ such that } l \notin C \}.$$

It follows that the origin of C must be a node of $N - F_C$. By the "single origin" condition, it is also necessary that this origin reaches every leaf in C. As shown in [31], the existence of such a node is also sufficient to explain C. Since it is easier to deal with, we will heavily use the following characterization².

² Note that we adapted this characterization, since in the original definition of PTNs, the taxa were treated as sets of characters instead of the other way around.

Lemma 1 ([31]). Let N be an LGT network and let C be a set of characters. Then N is a perfect transfer network for C if and only if for every character $C \in C$, the network $N - F_C(N)$ contains a node v that reaches every leaf in C.

Proof (sketch). If N is a PTN for C, then for a character $C \in C$, as mentioned the nodes in $F_C(N)$ cannot possess C. This means that the origin of C, that is, a node that satisfies the third condition of PTNs, must be in $N - F_C(N)$. Conversely, if some node of $N - F_C(N)$ reaches every leaf, then it can serve as the origin of the character.

We also describe two useful generic properties of galled LGT networks. The first one says that a node v cannot have two descending transfer nodes that each go outside of the v subtree (otherwise, v would be part of two distinct cycles).

Lemma 2. Let $N = (V, E_S \cup E_T)$ be a galled LGT network and let $v \in V(N)$ be a node with two distinct descendants x and y in \mathcal{T}_N that are transfer nodes (with $v \in \{x,y\}$ being possible). Then one of the transfer edges incident to x or y has both endpoints in the subtree $\mathcal{T}_N(v)$.

Proof (sketch). If v has two descendants x, y with transfer neighbors that are external to the v subtree of \mathcal{T}_N , then the two outgoing transfers inevitably create two distinct cycles that both contain v, contradicting the galled property. \square

The next property states that if some x is able to reach a node y that does not descend from it, then x must of course achieve this through a transfer edge.

Lemma 3. Let $N = (V, E_S \cup E_T)$ be a galled LGT network. Let $x, y \in V$ be two nodes that are not comparable in \mathcal{T}_N and such that x reaches y in N. Then there exists an edge $(x', y') \in E_T$ such that $x' \preceq_{\mathcal{T}_N} x$ and $y \preceq_{\mathcal{T}_N} y'$.

Proof (sketch). Consider the first transfer edge (x', y') on a path from x to y in N. Note that x' must descend from x in \mathcal{T}_N . If y is not a descendant of y', then from y' the path needs to borrow another transfer edge that goes out of the y' subtree of \mathcal{T}_N . Thus, the y' subtree has two transfers with external endpoints, contradicting Lemma 2.

2.3 Differences with reconstructions from bipartitions

As we pointed out in the introduction, Warnow et al. [45] also independently developed galled tree reconstructions algorithms from character data (which are assumed to be SNPs in the paper). Therein, for each character, the species can be in one of two states, and the states are assumed to correspond to a bipartition of a galled tree N. A bipartition is a partition of the leaves that can be obtained by taking a tree displayed by N, removing an edge, and taking the two sets of leaves of the resulting connected components (here, "displayed" means a tree that can be obtained by removing one parent edge from each node of in-degree two). They discuss algorithms to reconstruct a galled tree that contains a set of given characters, that is, that contains all the corresponding bipartitions. More

specifically, they show that if all the bipartitions of a galled tree N are known (but N is unknown), then N can be reconstructed in polynomial time. They also show that this approach is statistically consistent if characters evolve on a galled tree and may or may not be transmitted on edges labeled as transfer.

We refer to this as the Perfect Phylogenetic Network (PPN) model, as the notion of explaining a character is the same as in [33]. If we interpret one state as "presence" and the other as "absence", this is very similar to our formulation, with two notable exceptions. First, in our work on PTNs we impose an ordering in states from "absence" to "presence", whereas no such ordering is assumed in the PPN model. More importantly, the notion of displaying a tree does not distinguish between transfer and vertical descent edges. Figure 2 illustrates this difference. Suppose that a given set of characters (i.e., bipartitions) results in the network shown on the left, and consider the character C denoted by the colored square. In the model of [45], this character is considered as explained, since the displayed tree on the right shows that the character indeed corresponds to a bipartition. On the other hand, this network does not explain the character under the PTN model. Roughly speaking, displaying a tree allows removing a vertical edge, whereas we would require transmitting characters along that removed vertical edge. See the figure caption for details. We do note that [45] consider an evolutionary model in which characters evolve down a tree in which transfer edges are explicitly labeled. However, this is only to describe the statistically consistent model, as unlike us the algorithms do not consider this labeling. Let us also mention that [45] do not consider the tree completion problem.




Fig. 2. (a) An example that shows that galled PPNs are not necessarily galled PTNs. The colored square represents a character present at the two rightmost leaves (or in the PPN formulation, there are two states: with or without a square). (b) A tree displayed by the network, obtained by deleting one edge (we left the resulting subdivision node, although they could be suppressed). The illustrated character labeling shows that this network explains the character under the PPN model. As for PTNs, one can see from the definition of $F_C(N)$ that under the PTN formulation, no internal node of the initial network can contain the character, that there is no possible origin, and thus that the network cannot explain it.

3 The Galled Completion Problem

In this section, let T be a tree on taxa S and let C be a set of characters. We assume that T has no subdivision node. We will first describe the necessary conditions for T to be galled-completable. The key factor lies in the ancestor relationship that exists between any set of first-appearance (FA) nodes for distinct characters.

Definition 2. Let T be a tree on leafset S and let $C \subseteq S$ be a character. A node $v \in V(T)$ is a first-appearance (FA) node for C if $L_T(v) \subseteq C$ and v is either the root, or its parent u satisfies $L_T(u) \not\subseteq C$. The set of FA nodes for C in T is denoted as $\alpha_T(C)$.

In other words, v is a FA for C if it roots a maximal subtree of taxa that contain C. An example of this definition is shown in Figure 3.




Fig. 3. A tree T on species $S = \{s_1, s_2, s_3, s_4, s_5, s_6, s_7\}$ with character set $C = \{C_1, C_2, C_3, C_4\}$. Every colored shape indicates to which character a specific taxa belongs to. The corresponding sets of FAs for every character are as follows: $\alpha_T(C_1) = \{x, y\}, \alpha_T(C_2) = \{y, s_2\}, \alpha_T(C_3) = \{v\}, \alpha_T(C_4) = \{u\}.$

For a character $C \in \mathcal{C}$ and a network N, we will say that a node v is an origin for C if v reaches every leaf in C in $N - F_C(N)$. By Lemma 1, our goal is to add arcs to T to ensure that every character has an origin. We first show that in any galled-completion of a tree T, an origin of a character C must descend from a FA node (or it could be a transfer node added just above it), and it must "give" its character to all other FAs by transferring just above them.

Lemma 4. Let N be a galled-completion of a tree T that explains C. Let $C \in C$ be a character and let w be an origin for C in N. Then there is $\alpha_i \in \alpha_T(C)$ such that both of the following hold:

- either $w \preceq_{\mathcal{T}_N} \alpha_i$ or w is a transfer node whose child in \mathcal{T}_N is α_i .
- for every $\alpha_j \in \alpha_T(C) \setminus \{\alpha_i\}$ there is a transfer edge (u, v) such that $u \leq w$ and $v = p_N(\alpha_j)$.

Proof (sketch). By definition, in T the ancestors of FAs are in $F_C(N)$ since they have descendants not in C. Thus, an origin w in N must be in a FA subtree, or it could be a transfer node inserted above such an FA during the process of adding transfer edges from T to N. If there are multiple FAs, w must be able to reach the other ones, and Lemma 3 lets us establish that transfer edges as described are needed to achieve this.

We next argue that the galled requirement places an important limitation on FAs, as there can be at most two per character. This means that a character C must either be a clade of T, or it could be split in two clades, but not more. This is both useful in theory, but also in our experiments since it allows checking quickly whether an individual character can be explained by a galled-tree.

Lemma 5. Let T be a galled-completable tree for a character set C. Then for any character $C \in \mathcal{C}$, $\alpha_T(C) \leq 2$.

Proof (sketch). By Lemma 4, an origin for C must be in one of the FA subtrees (or just above). If there are three FAs, that origin must also reach the other two FAs, but this requires two descending transfers that contradict Lemma 2.

We next show that FAs of distinct characters have limited ancestry relationships. The proof relies on a case analysis and the previous properties.

Lemma 6. Let T be a galled-completable tree for C. Suppose that there exists two distinct characters A and B with $\alpha_T(A) = \{a_1, a_2\}$ and $\alpha_T(B) = \{b_1, b_2\}$. Then the two following statements hold:

```
1. If b_1 \prec a_1 and b_2 is not comparable to a_1, then a_2 = b_2.
```

2. If $a_1 = b_1$, then either $b_2 \prec a_2$ or $a_2 \prec b_2$.

Proof (sketch). For the first statement, if $b_1 \prec a_1$ and b_2 is outside of the a_1 subtree, then b_1 needs to use the same transfer edge as a_1 to exchange material (because of the galled property). This is only possible if they send the character to the same clade, that is, if $a_2 = b_2$.

For the second statement, if $a_1 = b_1$, then again the two characters must use the same transfer edge to exchange material. In fact, one can argue that $a_1 = b_1$ must be the receiving end of the transfer, and that a_2, b_2 must be comparable to be able to use the same node to send the character.

Note that in the detailed proof of the first statement of Lemma 6, we use the fact that transfer edges are unidirectional — the statement in the sketch that b_1 needs to use the "same" transfer as a_1 remains true, but they do not need to send the character to the same clade in a bidirectional setting, as the sending could go both ways. If we allowed bidirectional transfer edges, we can devise examples in which the lemma does not hold. This shows that even apparently minor changes to the model can lead to more complex structures.

We can begin describing our algorithmic strategy. The first step is to locate and count the FAs for each character to verify the condition established by

Lemma 5. A subtree which is rooted at a FA for a specific character C is in fact a maximal clade for C. An intuitive way of joining these clades is to add transfer edges between the different subtrees to fulfill the connectivity requirement in Lemma 1. However, this may add superfluous transfer edges, as only the *minimal* ones are required.

To make this precise, let $v \in V(T)$. We say that another node $w \in V(T)$ is an FA neighbor of v if there exists a character $C \in \mathcal{C}$ such that $\alpha_T(C) = \{v, w\}$. We also say that w is a minimal FA neighbor of v if $w \preceq_T w'$ for every FA neighbor of v. A pair of FA nodes $\{v, w\}$ is called simple if w is the unique FA neighbor of v and v is the unique FA neighbor of w.

Definition 3. Let T be a tree on leafset S with character set C. Let T' be the tree obtained by subdividing every edge of T once. Then the redundancy-free network for T is the LGT-network $N = (V, E_S \cup E_T)$ with T' as support tree obtained as follows:

- for each $v \in V(T)$ with at least two FA neighbors, and for every minimal FA neighbor w of v, add the transfer edge $(p_{T'}(w), p_{T'}(v))$;
- for each pair $\{v, w\}$ of simple FA nodes, add one of the transfer edges $(p_{T'}(v), p_{T'}(w))$ or $(p_{T'}(w), p_{T'}(v))$ arbitrarily (but not both).




Fig. 4. (a) A given tree T on four characters. (b) The FA neighbors between every FAs for each character are indicated by the dashed lines. (c) The redundancy free network of T. Note that C_3 has simple FAs, so the direction for the transfer edge is arbitrary. On the other hand, for C_1 and C_2 note that z is the minimal FA neighbor of y so the direction of the transfer edge is not arbitrary.

The idea of this network is that if a node y has multiple FA neighbors, as in Figure 4, then there are many characters with y as a FA. By adding a transfer edge whose sender is the parent of the minimal FA neighbor z of y, again as in the figure, all those characters can have their origin on the z side and transfer to y. In the figure, we add a transfer from the parent of z to that of y for character C_2 . At the same time, C_1 can use that same transfer edge because it also wants y and its descendants to inherit the character. For characters whose FAs correspond to a simple pair, no such transfer re-use is needed and the direction is arbitrary.

Before proving our main characterization in terms of redundancy-free networks, we need an intermediary result.

Lemma 7. Let T be a tree on leafset S and character set C. If T is galled-completable, then in the redundancy-free network $N = (V_T, E_T)$ of T, every node is incident to at most one transfer edge.

Proof (sketch). Suppose that some node u' of N is incident to two distinct transfer edges, with v' and w' as the other endpoints (where u', v', w' are subdivision nodes added when transforming T to N). Since N only adds transfers between minimal FA neighbors, this means that v' and w' are incomparable nodes of \mathcal{T}_N (a special case arises when v' = w', see the full proof for details). Roughly speaking, this means that two characters need to exchange material between the clades of u' and v', and also between the clades of u' and w'. This is only possible in a galled-completion if the u' subtree contains at least two transfers, one exchanging with v' and the other with w'. This creates two transfers below u' with external endpoints, contradicting the galled property by Lemma 2.

We finally arrive to our characterization of galled-completable trees.

Lemma 8. A tree T on leafset S with character set C is galled-completable if and only if its redundancy-free network $N = (V, E_S \cup E_T)$ is a galled tree.

Proof (sketch). In the forward direction, if T can be completed into a galled tree N' that explains \mathcal{C} , we can argue that for every transfer edge (u,v) the is present in the redundancy-free network N, there is a corresponding transfer edge in N' whose endpoints are either u and v, or in their support tree descendants. Roughly speaking, this means that the cycles of N have corresponding cycles in N', and since N' is a galled tree, so is N. Conversely, if N is galled, it explains \mathcal{C} by construction. That is, for every character split into two clades in T, we either added an edge above the subtrees to connect them, or there is an edge that was added in the descendants due to some minimal FA neighbor, which allow meeting the connectivity requirements of Lemma 1.

The previous lemma implies a polynomial time verification algorithm, detailed in Algorithm 1. We build the redundancy-free network and verify that it is a galled tree. We can calculate the set of FAs for each character and use this information to assign the FA neighbors to each node in T. Then, in a postorder traversal pick every node v that has FA neighbors. Note that if those neighbors are not all comparable, then there exists no completion, since two outgoing transfers are necessary to explain them. When v has multiple FA neighbors, we find the minimal one (c_{min} in the algorithm) and add the corresponding transfer edge. If c_{min} is the only FA neighbor of v, we "mark" v. If c_{min} is also marked, then $\{v, c_{min}\}$ is a simple pair, and if not, then either c_{min} will be marked later, or it has multiple FA neighbors and will create its own transfer.

Theorem 1. Algorithm 1 correctly solves the Galled Tree Completion problem in time $O(|V(T)||\mathcal{C}|)$.

Let us remark that the complexity of the algorithm is dominated by the computation of the set of FA nodes. Assuming a traversal of T for each $C \in \mathcal{C}$,

```
1 function FindGalledCompletion(T, S, C)
        //T is a tree on taxa set \mathcal{S}, \mathcal{C} is the character set.
 2
       Let T' be the tree that results from subdividing every edge in T, let
 3
       // FA(v) is a set that will keep track of FA neighbors present in v. for
         C \in \mathcal{C} do
           Compute \alpha_T(C), the set of FAs of C in T
 5
           if |\alpha_T(C)| > 2 then return "not galled-completable"
 6
           if \alpha_T(C) = \{u, v\} then add u to FA(v) and add v to FA(u)
 7
       for v in postorder(T) do
 8
           Let c_{min} be an arbitrary element of FA(v)
 9
           for u in FA(v) do
10
               if u is not comparable to c_{min} then
11
                   return "not galled-completable"
12
13
               if u \prec c_{min} then set c_{min} = u
           if |FA(v)| \geq 2 then
14
              Add (p_N(c_{min}), p_N(v)) to N
15
           else
16
               if c_{min} is marked as "possibly simple" then
17
                   Add (p_N(v), p_N(c_{min})) to N.
18
               else
19
20
                   Mark v as "possibly simple"
       if N is a galled tree then return N
21
       else return "not galled-completable"
22
```

Algorithm 1: Check if a given tree T is galled-completable.

this takes time $O(|V(T)||\mathcal{C}|)$. The rest of the algorithm only adds a time of $O(|V(T)| + |\mathcal{C}|)$. We leave the problem of computing FAs in linear time, if at all possible, for a future discussion.

4 The Galled Compatibility Problem

Let us recall the galled compatibility problem: we are given a set of characters \mathcal{C} on a set of taxa \mathcal{S} and must decide whether a galled tree N explains \mathcal{C} . Note that if such an N exists, then its base tree is galled-completable. Therefore, \mathcal{C} is galled-compatible if and only if there exists a tree T that is galled-completable for \mathcal{C} . Instead of aiming to construct N directly, our strategy is to build such a T using the characterizations from the previous section.

Let T be a tree and $v \in V(T)$. Let $C \in \mathcal{C}$ be a character and suppose that C has two FAs x_1, x_2 in T. In this case, we say that C is *split into* $L_T(x_1)$ and $L_T(x_2)$ (noting that the union of these two leafsets must be C since there are only two FAs). A character $C \in \mathcal{C}$ is maximal if there is no $C' \in \mathcal{C}$ such that $C \subset C'$. Two characters $A, B \in \mathcal{C}$ are compatible if there exists a tree T in which A and B are clades, and incompatible otherwise. It is well-known that A, B are compatible if and only if either $A \cap B = \emptyset$ or one of A or B is a subset of the




Fig. 5. An example instance with characters $\mathcal{C} = \{A, B, C, X, Y, P, Q, R\}$ on taxa $\mathcal{S} = \{a, b, c, d, e, f, g, h, i, j, k, l, m\}$ used to illustrate the main steps 1-4 of the algorithm. Step (1) splits A into $A \setminus B$, $A \cap B$. Step (2) integrates the clades forced by X, Y, which intersect the two clades of A. Step (3) integrates B and C as clades. Step (4) solves for P recursively, and then for Q, R recursively, then the transfer required by A, X, and Y is added.

other. This means that if A, B are incompatible, then the sets $A \cap B$, $A \setminus B$, are all non-empty. Recall that for any set C of pairwise-compatible characters, there is a tree T whose set of clades is exactly C, plus the clade of the root and the leaves (see e.g. [18]).

The detailed algorithm is somewhat involved, but the main idea can be described in a few steps that are illustrated in Figure 5:

- (0) if there is a maximal character C that is compatible with all the others, we may assume that T splits the root with child clades C and $S \setminus C$ (not shown in figure, see Lemma 9), and that each remaining character is contained in one of these clades. We can solve each subset of characters recursively;
- (1) otherwise, every maximal character A has some incompatibility with some B, as in Figure 5. We can show that T must either split A into clades $\{A \setminus B, A \cap B\}$, or split B into clades $\{B \setminus A, B \cap A\}$. We try the first option, and if it leads to a dead-end we try the other option. That is, for each of these two possibilities, we initiate a tree with only the two clades and proceed to the next steps. For the rest of the description, we assume that we start a tree with $A \setminus B, A \cap B$ as in Figure 5.1. This means that in any completion, there will be a transfer edge between the two clades to provide an origin for A;
- (2) each character that intersects both clades must use that same transfer edge in a completion. Such characters enforce new clades that refine the previous ones. For example in Figure 5.2, X enforces the clade $\{d,e\}$, which is the intersection $X \cap \{a,b,c,d,e\}$, and similarly Y enforces $\{c,d,e\}$. These enforced new clades must be ordered by inclusion;
- (3) other characters can enforce further clades, namely those that contain the minimal clades enforced so far. For example, the character C from Figure 5 contains $\{d,e\}$, and so the clade C is enforced. Likewise, B is forced since it contains $\{f,g,h\}$. These are added in Figure 5.3;

(4) it turns out that if C is galled-compatible, then any unforced character so far represents a set of leaves that have the same parent v in T. See P, Q, R in Figure 5.3. We can recurse into the leaf children of each v and replace the leaves by the resulting network. In Figure 5.4, the leaf set $\{i, j, k\}$ is replaced by a network that explains Q, R, and $\{f, g, h\}$ by a network that explains P.

An important subtlety arises in Step (1). If we need to recurse on both possible splits $\{A \setminus B, A \cap B\}$ and $\{B \setminus A, B \cap A\}$, the complexity could become exponential. Our algorithm is designed so that we never have to recurse on both. That is, we actually make a series of checks before trying $\{A \setminus B, A \cap B\}$, and we only recurse after all the checks pass. These checks are designed so that if the recursion fails to find a solution, then $\{B \setminus A, B \cap A\}$ would fail too anyways. This will become apparent in the details below, to which we now proceed.

As explained in step 0 above, we can first show that maximal compatible characters are easy to deal with, see Figure 6.

Lemma 9. Suppose that C contains a maximal character C that is compatible with every other character. Let $C_1 = \{A \in C : A \subset C\}$ and $C_2 = \{A \in C : A \cap C \neq \emptyset\}$. Then C is galled-compatible if and only if C_1 and C_2 are both galled-compatible.

Moreover, given galled PTNs N_1 , N_2 that explain C_1 , C_2 , respectively, one can obtain in time O(|C|) a galled PTN N that explains C.




Fig. 6. Illustration of Lemma 9. If C is maximal and compatible, we split the problem into two subproblems on C_1 , which contains only subsets of C, and C_2 , which do not intersect with C, and put the resulting networks under a common root.

Proof (sketch). If C as stated exists, we can start constructing a tree whose root has two children, one with C as a clade, and the other with everything not in C. This automatically explains C. We can then recursively solve for C_1 on the C side, and for C_2 on the non-C side, and replace the child clades with the corresponding networks. Because C is compatible, every character will be on one side, this solves for every character.

The next step is to handle maximal incompatible characters. We first show a fundamental property on pairs of incompatible characters: one of them must be a clade and the other must be split.

Lemma 10. Let T be a tree that is galled-completable for C, and let $A, B \in C$ be a pair of incompatible characters. Then one of the following holds:

```
-A is split into A \setminus B, A \cap B in T, and B is a clade of T; -B is split into B \setminus A, A \cap B in T, and A is a clade of T.
```

Proof (sketch). By incompatibility, A and B cannot both be clades of T. If only one of them is a clade, say A, then we are done since the only way to have two FAs for B is to put $B \cap A$ inside of A, and $B \setminus A$ elsewhere. So assume that both A and B are split, having two FAs a_1, a_2 and b_1, b_2 each. Because A and B intersect, with some effort it can be shown that these FAs must be related by ancestry (i.e., $a_1 \prec b_1$ or $b_1 \prec a_1$, and also $a_2 \prec b_2$ or $b_2 \prec a_2$). The proof shows that each possible case leads to requiring two distinct transfers to explain A and B, which create intersecting cycles.

Note that if we allow bidirectional transfers, there are examples in which the above lemma is not always true.

Our algorithm will find maximal incompatible A and B and try splitting A, or B. When trying the split $A_1 = A \cap B$, $A_2 = B \setminus A$, the characters that intersect with both A_1 and A_2 must also be split. Furthermore, one of the FAs of those must be all equal to either that of A_1 or A_2 , and the other FAs must form a chain under that of A_1 or A_2 . This can be formalized as follows.

Let A be a character and let $\{A_1, A_2\}$ be a partition of A. Let $\mathcal{X} \subseteq \mathcal{C}$ be the set of characters that intersect both A_1 and A_2 (note that $A \in \mathcal{X}$). We say that \mathcal{X} forms an (A_1, A_2) -chain if the elements of \mathcal{X} can be ordered as $\mathcal{X} = \{X_1, \ldots, X_l\}$ such that $X_l = A$, and both of the following holds:

```
-(X_1 \cap A_1) \subset (X_2 \cap A_1) \subset \ldots \subset (X_l \cap A_1) = A_1; and - for every X_i \in \mathcal{X}, X_i \setminus A_1 = A_2.
```

We call $X_1 \cap A_1$ the bottom of the chain, and we call A_2 the stable side of the chain. In Figure 5.3, $A_1 = \{a, b, c, d, e\}, A_2 = \{f, g, h\}$ and $\mathcal{X} = \{X, Y, A\}$. One can see that \mathcal{X} forms an (A_1, A_2) -chain with bottom $\{d, e\}$ and stable side $\{f, g, h\}$. The concept of a chain is illustrated in Figure 7.

Lemma 11. Let A be a maximal character of C. Suppose that T is a galled-completable tree for C in which A is split into the clades A_1 and A_2 . Let $X \subseteq C$ be the subset of characters that intersect with both A_1 and A_2 .

Then, after possibly exchanging the subscripts of A_1 and A_2 , \mathcal{X} is an (A_1, A_2) -chain. Moreover, for every $X \in \mathcal{X}$, the clades $X \cap A_1$ and $X \cap A_2$ are in T.

Proof (sketch). Assuming that A is split into A_1, A_2 , the maximality of A implies that any $X \in \mathcal{X}$ that intersects with both must also be split. In fact, to avoid creating intersecting cycles, every such X must be explained using the same transfer edge that explains A_1 and A_2 . This can only be achieved if, in T, the FAs of the X's are ordered by ancestry on one side, and all lead to the same clade on the other side. Moreover, because A is maximal, every such X must be a subset of A. This results in an (A_1, A_2) -chain.




Fig. 7. An (A_1, A_2) -chain, where $X_1, X_2, X_3 \in \mathcal{X}$ all intersect with both A_1 and A_2 . On the A_1 side, the FAs are ordered by ancestry, and the only way to explain all these characters is to have them use the same transfer to reach the A_2 side.

Lemma 11 shows that if we choose to split A into A_1 and A_2 , then we know how to split the characters that intersect with both A_1 and A_2 . We can make a similar deduction for the other characters that contain the bottom or stable side of the (A_1, A_2) -chain.

Lemma 12. Let A be a maximal character of C. Suppose that T is a galled-completable tree for C in which A is split into the clades A_1 and A_2 . Let $\mathcal{X} \subseteq C$ be the subset of characters that intersect with both A_1 and A_2 and suppose that \mathcal{X} is an (A_1, A_2) -chain. Let $X_1 \cap A_1$ be the bottom of the chain and let A_2 be the stable side of the chain.

If $C \in \mathcal{C} \setminus \mathcal{X}$ contains $X_1 \cap A_1$ or contains A_2 , then C is a clade of T.

Proof (sketch). Any C as described intersects with exactly one of $X_1 \cap A_1$ or A_2 , but not both (otherwise, it would be in \mathcal{X}). In this case, one can show that C and X_1 must be incompatible. Since X_1 is assumed to be split, we know by Lemma 10 that C cannot also be split, and thus it must be a clade.

For an example, see the characters B and C in Figure 5. So far, we have handled characters "forced" by a split of A into A_1 and A_2 . As it turns out, the other characters can be handled in a recursive manner.

To put this precisely, let us gather all the information on the tree that has been shown to be forced so far. Let A be a maximal character of \mathcal{C} and let $\{A_1, A_2\}$ be a partition of A into two non-empty sets. Let \mathcal{X} be the characters that intersect with A_1 and A_2 and suppose that \mathcal{X} forms and (A_1, A_2) -chain. We say that a character $C \in \mathcal{C}$ is forced by $\{A_1, A_2\}$ if either: $C \in \mathcal{X}$; C contains the bottom of the \mathcal{X} chain; or C contains the stable side of the \mathcal{X} chain.

Furthermore, a clade $Y \subseteq \mathcal{S}$ is forced by $\{A_1, A_2\}$ if either: $Y = X \cap A_1$ or $Y = X \cap A_2$ for some $X \in \mathcal{X}$; or Y = C for some character $C \in \mathcal{C}$ that contains the bottom or the stable side of the \mathcal{X} chain. The first type of clades are enforced due to Lemma 11, and the second type due to Lemma 12.

The next lemma is crucial: it shows that non-forced characters can be grouped and dealt with recursively according to the tree that contains the forced clades.

Lemma 13. Let A be a maximal character of C and suppose that there is a galled-completable tree T^* for C in which A is split into A_1 and A_2 . Let T be the tree whose set of clades is precisely the clades forced by $\{A_1, A_2\}$ (plus the root clade and the leaves).

If $C \in \mathcal{C}$ is a character not forced by $\{A_1, A_2\}$, then all the taxa in C have the same parent in T.




Fig. 8. An illustration of Lemma 13. Left: the tree T that contains the forced clades, with $X_1 \cap A_1$ the bottom of the chain and A_2 the stable side. We assume that some characters B, D, E enforced other clades. If we assume that some character C has elements with distinct parents, the situation on the right is unavoidable. A transfer will be needed to link the bottom and stable side, and another transfer to explain C. These two transfers create intersecting underlying cycles.

Proof (sketch). Suppose that T^* is galled-completable for \mathcal{C} . By the previous lemmata, all forced clades must be in T^* , and thus T^* is a "refinement" of T (that is, T^* contains the same clades, plus possibly more). We know that a transfer edge is required between the bottom of the chain and the stable side. If there is a non-forced character C with taxa having distinct parents, then no matter how T is refined into T^* , we will need an additional transfer edge to explain C, which will create a cycle that intersects with the one we created near the bottom of the chain. See Figure 8 and the caption for an illustration.

By combining the elements gathered so far, we finally arrive at an algorithmically useful characterization of galled-compatible characters.

Lemma 14. Let A be a maximal character of C and let $\{A_1, A_2\}$ be a partition of A. Then there is a tree that is completable for C and that contains the clades A_1 and A_2 if and only if all the following conditions hold:

- 1. Let \mathcal{X} be the characters that intersect with A_1 and A_2 . Then \mathcal{X} forms an (A_1, A_2) -chain;
- 2. There exists a tree T on leafset S whose set of clades is precisely the set of clades forced by $\{A_1, A_2\}$ (plus the root clade and leaves).

- 3. Let C_F be the set of characters forced by $\{A_1, A_2\}$. Then for any $C \in \mathcal{C} \setminus \mathcal{C}_F$, all the taxa of C have the same parent in T.
- 4. For any subset $C' \subseteq C \setminus C_F$ such that all taxa that belong to some character of C' have the same parent in T, C' is galled-compatible.

Proof (sketch). In the (\Rightarrow) direction, we know by all the previous lemmata that all the stated conditions must be satisfied by a galled-completable tree for \mathcal{C} . In the (\Leftarrow) direction, suppose that all the conditions hold. Let T be a tree that contains all the clades forced by $\{A_1, A_2\}$. Then we can explain all the forced characters by adding a transfer edge just above the bottom of the \mathcal{X} chain, going just above the stable side. As for the other characters, for a node v of T, let $\mathcal{C}_v \subseteq \mathcal{C}$ be the non-forced characters having taxa whose parent is v. We can find a galled network N_v that explains \mathcal{C}_v and "attach" N_v as a child of v. Doing this for every v does not create intersecting cycles and explains all the remaining characters.

Our strategy is then to find a maximal character A and some B it is incompatible with. We try to split A into $A \setminus B$ and $A \cap B$ and if all the conditions of Lemma 14 pass, we have succeeded. Otherwise, it is B that we split into $B \setminus A$ and $B \cap A$. We want to check the conditions on this split, but since Lemma 14 only apply to maximal characters, then B must be maximal as well. We thus need the following.

Lemma 15. Suppose that C has no maximal character that is compatible with all the others. Then there exists a pair of incompatible characters $\{A, B\}$ of C such that A and B are both maximal.

Proof (sketch). Let A be maximal. Then A has some incompatibility. Letting B be the character of maximum cardinality such that A, B are incompatible, one can argue that B is also maximal.

Algorithm 2 is the full pseudocode of the galled-compatibility algorithm. For simplicity, it only solves the decision version of the problem (i.e., whether the characters are galled-compatible or not), but it can easily be adapted to reconstruct a network.

The idea of the algorithm is as follows.

- 1. If C has a maximal character C compatible with every character, then we know that we can simply recurse into C_1 and C_2 as in Lemma 9.
- 2. Otherwise, we must deal with maximal characters that are all incompatible. We choose incompatible A, B that are both maximal (shown to exist in Lemma 15).
- 3. We know that a galled-completable tree, if one exists, must contain the clades $A \setminus B$, $A \cap B$, or $B \setminus A$, $B \cap B$. We do not know which one it is, so we try the former first. That is, first consider the partition $\{A_1, A_2\} = \{A \setminus B, A \cap B\}$.
- 4. The function tryPartition checks whether it is possible to satisfy Conditions 1,2,3 from Lemma 14 with $\{A_1, A_2\}$ enforced. If one of those conditions fails, we know that A_1, A_2 cannot lead to a solution, and tryPartition

```
1 fonction getGalledTree(C)
        if C = \emptyset then return true
 2
        if C has a maximal character C compatible with every C' \in \mathcal{C} then
 3
             Let C_1 = \{A \in \mathcal{C} : A \subset C\}, C_2 = \{A \in \mathcal{C} : A \cap C = \emptyset\}
 4
             return getGalledTree(C_1) \land getGalledTree(C_2)
 5
 6
        Let \{A, B\} be a pair of maximal incompatible characters from \mathcal{C}
 7
        Let \{A_1, A_2\} = \{A \setminus B, A \cap B\}
 8
        result = tryPartition(C, \{A_1, A_2\})
        if result = "yes" then return true
10
        if result = "no" then return false
11
12
        //otherwise, result = "invalid partition", try the other partition
13
        Let \{B_1, B_2\} = \{B \setminus A, B \cap A\}
14
        result = tryPartition(C, \{B_1, B_2\})
15
        if result = "yes" then return true, otherwise return false
16
17
18 fonction tryPartition(C, \{A_1, A_2\})
        Let \mathcal{X} be the characters that intersect A_1 and A_2
        if \mathcal{X} is not an (A_1, A_2)-chain nor an (A_2, A_1)-chain then return
          "invalid partition"
21
        Let \mathcal{C}_F and F be the characters and clades, respectively, forced by
          {A_1, A_2}
        Let T be the tree whose set of non-trivial clades is F
22
        if T does not exist then return "invalid partition"
23
        if there is C \in \mathcal{C} \setminus \mathcal{C}_F and u, v \in C with distinct parents in T then return
24
          "invalid partition"
        foreach v \in V(T) do
25
26
             Let C_v \subset C \setminus C_F be the characters only containing taxa whose parent is
             if C_v \neq \emptyset \land getGalledTree(C_v) = false then return "no"
27
        return "yes"
28
```

Algorithm 2: Main galled-tree reconstruction algorithm.

returns "invalid partition". When getCalledTree receives this answer, it attempts to check whether using $\{B_1, B_2\} = \{B \setminus A, B \cap A\}$ works instead, which is the only other possibility.

Do note that Lemma 14 only applies to maximal characters. Since we potentially check them on A and B, it is crucial to have both A and B as maximal characters.

5. If $\{A_1, A_2\}$ passes the three tests in tryPartition, then we check recursively that all the C_v 's are galled-compatible. If they all are, we return "yes" and we are done. If some C_v is not galled-compatible, then we know that A_1, A_2 cannot lead to a solution.

An important subtlety arises in this case. We do not return "invalid partition", because this would lead to trying with $\{B_1, B_2\}$ instead. This could

lead to an exponential time algorithm, because we would recurse into too many cases on both $\{A_1, A_2\}$ and $\{B_1, B_2\}$. Instead, we return "no", and the main algorithm returns false without even trying $\{B_1, B_2\}$. This is correct, because if we find a C_v that is not galled-compatible, we know that C itself is not galled-compatible and there is no point in trying $\{B_1, B_2\}$.

The correctness and complexity details of the algorithm now follow.

Theorem 2. The GALLED COMPATIBILITY problem can be solved in time $O(n|\mathcal{C}|^3)$.

5 Galled PTNs on functional characters: a case study

We now turn to a real-data case analysis of galled-completion in order to gain better insight on its potential for the prediction horizontal gene transfers, as there is a general lack of benchmarks for the interactions between transfers and characters. However, a few studies have now started exploring this territory, and here we take inspiration from [48], which implemented machine learning approaches to infer HGTs from functional characters using the Kyoto Encyclopedia of Genes and Genomes (KEGG) Orthology database [24] (see below). The authors of [48] used curated HGTs between bacteria, with the list of functions of each taxa as features, allowing them to predict the presence or absence of HGT between any two bacterial species. They therefore solve a binary classification task, making one prediction per species pair. They inferred 147,889 transfers between 6566 bacterial genomes, although some of these transfers could all be manifestations of one ancestral transfer in the phylogeny (but because these predictions are made in a pairwise manner, the time of these transfers cannot be inferred by the approach).

In our case study, we also used functional characters from the KEGG database, which associates molecular functions of genes and proteins to orthologous groups. Table 1 lists the functions that we used, along with their hierarchical classification. The main type of entries in the database are KEGG Orthologs (KO), which are groups of genes sharing common functions (members of the same group are viewed as functional orthologs). Most groups are formed based on experimental evidence, with some generalizations to other organisms based on sequence similarity.

We took a subset of 45 species from the bacterial species used in [48], which consists of species that were predicted to be involved in interphylum transfers. We obtained the corresponding species tree from NCBI Taxonomy Browser [42], noting that it is not completely resolved and is therefore non-binary. Observe that this is not a problem for our tree-completion procedure, as only the inserted transfer nodes are assumed to be binary in our model — not the nodes of the input tree. The whole annotated genomes of these species are contained in KEGG, and so as characters, we chose 23 KOs based on the features that were shown as most important for the Graph Convolutional Network model presented in [48]. These features include metabolism-related, information processing and antibiotic resistance KOs among other functions. The whole

datasets and scripts used for this part are contained in the following repository: https://github.com/AliLopSan/ptns.

Character	Brite Hierarchy Classification	Function Description
K18220	01504 Antimicrobial resistance genes	ribosomal protection tetracycline resistance protein
K02257	09100 Metabolism	heme o synthase
K01610	09101 Carbohydrate metabolism	phosphoenolpyruvate carboxykinase (ATP)
K04068	09191 Unclassified: metabolism	anaerobic ribonucleoside -triphosphate reductase activating protein
K00627	09101 Carbohydrate metabolism	pyruvate dehydrogenase E2 component
K00241	09101 Carbohydrate metabolism	succinate dehydrogenase cytochrome b subunit
K01679	09101 Carbohydrate metabolism	fumarate hydratase, class II
K13628	03016 Transfer RNA biogenesis	iron-sulfur cluster assembly protein
K01669	03400 DNA repair and recombination proteins	deoxyribodipyrimidine photo-lyase
K03980	09183 Protein families: signaling and cellular processes	putative peptidoglycan lipidII flippase
K06886	99996 General function prediction only	hemoglobin
K07305	99980 Enzymes with EC numbers	peptide-methionine (R)-S-oxide reductase
K01589	00230 Purine metabolism	5-(carboxyamino) imidazole ribonucleotide synthase
K00561	03009 Ribosome biogenesis	23S rRNA (adenine-N6)-dimethyltransferase
K07483	99976 Replication and Repair	transposase
K17836	01501 beta-Lactam resistance	beta-Lactam resistance
K02227	00860 Porphyrin metabolism	adenosylcobinamide-phosphate synthase
K18214	01504 Antimicrobial resistance genes	MFS transporter, DHA3 family, tetracycline resistance protein
K19310	09131 Membrane transport	bacitracin transport system permease protein
K19115	02048 Prokaryotic defense system	CRISPR-associated protein Csh2
K02274	00190 Oxidative phosphorylation	cytochrome c oxidase subunit I
K03737	00720 Carbon fixation pathways in prokaryotes	pyruvate-ferredoxin/flavodoxin oxidoreductase
K00850	00010 Glycolysis / Gluconeogenesis	6-phosphofructokinase 1

Table 1. List of the complete set of characters used for our experiments which includes their function classification according to the KEGG BRITE database and a brief description of their function.

Losses can obstruct galled-completability. Using the Fitch labeling algorithm described in [31], we first calculated the number of first-appearance nodes of each character as well as their position in the species tree. As established in Lemma 5, this serves as a first test for galled-completability, as finding three or more such nodes for a character is sufficient to discard the instance. Figure 9 shows the distribution of the number of first-appearance nodes for each character. It is immediately clear that the "at most two first-appearances" condition is far from being satisfied, although it is insightful to understand why. For several characters, the majority of first-appearance nodes are leaves. An example of this phenomenon is shown in Figure 10. Notably, there is a clade in the top-right part of the tree in which every leaf has the character except one, resulting in three first-appearances in that clade. This prevents the common ancestor of the clade from being labeled with that character. It is plausible that the character was transferred to the common ancestor of the clade, and then simply lost in one species, as shown on the right. This strongly indicates that the "transfer-only" model is too rigid, and in future work we plan to work on approaches to identify situations in which losses are more likely than transfers.

Unresolved species trees can obstruct galled-completability. Going back to Figure 9, we note that there do exist characters that possess at most two first-appearances. We checked whether this subset of four characters could at least be




Fig. 9. Distribution of the number of first-appearances per character. We distinguish those first-appearance nodes that are leaves and those that are inner nodes. Most characters have more than two first-appearances, thus if there exists a PTN that can explain them, it will not be galled. We note however that there exists a set of characters that have at most two first appearances: $\{K13628, K19115, K00561, K19310\}$ which are those that fall below the green dashed line.




Fig. 10. An example that shows how allowing losses can lead to a completion that requires less transfers. We show the first appearances of character K016699. Note that in order to fulfill the connectivity requirements of Lemma 1 transfer edges should connect every colored block. Notice that with the no loss condition, there exist three clades at the right-hand side of (a) that need at least two transfers to remain connected since the species T03770 does not contain the character. In (b) we show that this could be explained by a loss event at species T03770, thus reducing by two the number of transfers that are needed to connect the updated first-appearance nodes.




Fig. 11. (a) The species tree with 45 species with annotated leaves showing colored annotations by clade according to the presence of one of the characters: $\{K13628, K19115, K00561, K19310\}$. Note that between annotations of the same color there should exist a transfer edge that could join the parts of the tree where the characters are present. Leaf names correspond to the species id present in the KEGG orthology database. Notice that the redundancy-free network is not galled since the cycles resulting from joining the first appearances of characters K13628 and K00561 contain the root of the tree as a common node. However as shown in (b), by resolving one of the children of the root node, as the black dot, this network becomes galled. Tree annotations where visualized using iTOL tool [30].

galled-completable, but it turns out that this is not even the case. This is shown in Figure 11 on the left. As explained in the caption, if we built the redundancy-free network for these characters and applied Lemma 8, we would add a transfer edge linking the branches above the roots of the blue character, and above the roots of the green character. These are non-redundant edges that create two cycles that intersect at the root. But one could hypothesize that the unresolved root is responsible for this: Figure 11 on the right partially resolves the tree by expanding the root, creating a branch in a way that the cycle of the blue characters now avoids the root. One can now check that the resulting redundancy-free network is galled, and that this set of characters is galled-completable.

To sum up, our ad hoc study leads to several insights and future directions. It shows that the possibility of gene losses cannot be ignored, and that these should either be predicted in a pre-processing step, or included as part of the model altogether. The analysis also shows that unresolved species trees may be an obstacle to galled completions. On the other hand, our approach may be useful in resolved such species trees.

6 Conclusion

In this work, we expanded the foundations on perfect phylogenies to galled trees. While compatible character in trees enjoy an elegant mathematical structure, it

appears that the difficulty of characterizing compatibility ramps up very quickly as we move beyond trees. Nonetheless, this work can serve as a stepping-stone towards the understanding of character evolution on more complex structures. A small step in this direction would be to allow bidirectional transfers in galled trees. This change is not as trivial as it seems, since several of our key results do not hold when such edges are present. It will also be interesting to integrate broader classes of networks, for example level-k networks, and to solve the open problem of finding a PTN with a minimum number of transfer edges.

Perhaps a more important direction, as exemplified by our case study, is to remove the "no-loss" assumption on characters. In the case of trees, one of the closest extension of perfect phylogenies is the Dollo parsimony model, where a character can be lost multiple times across the phylogeny, but can never be regained after it has been lost. Extending the perfect transfer networks to a form of Dollo parsimony may be interesting to reduce the "non-transfer noise" seen in our experimental study. It is worth noting though that any character can be explained with a single emergence at the root and losses under Dollo parsimony. That is, transfers are never needed to explain a character, and therefore some weighing scheme between transfers and losses will need to be developed before the model can become applicable on real data at a large scale. Examples of other directions include extensions to multi-state characters (as initiated by [33]), finding maximal sets of characters that fit in a galled tree, or devising non-binary species tree resolution algorithms.

References

- Alexander, P.A., He, Y., Chen, Y., Orban, J., Bryan, P.N.: The design and characterization of two proteins with 88% sequence identity but different structure and function. Proceedings of the National Academy of Sciences 104(29), 11963–11968 (2007)
- 2. Anselmetti, Y., El-Mabrouk, N., Lafond, M., Ouangraoua, A.: Gene tree and species tree reconciliation with endosymbiotic gene transfer. Bioinformatics 37(Supplement_1), i120-i132 (2021)
- 3. Bafna, V., Gusfield, D., Lancia, G., Yooseph, S.: Haplotyping as perfect phylogeny: A direct approach. Journal of Computational Biology **10**(3-4), 323–340 (2003)
- Bansal, M.S., Alm, E.J., Kellis, M.: Efficient algorithms for the reconciliation problem with gene duplication, horizontal transfer and loss. Bioinformatics 28(12), i283-i291 (Jun 2012). https://doi.org/10.1093/bioinformatics/bts225, http://dx. doi.org/10.1093/bioinformatics/bts225
- 5. Bodlaender, H.L., Fellows, M.R., Warnow, T.J.: Two strikes against perfect phylogeny. In: International Colloquium on Automata, Languages, and Programming. pp. 273–283. Springer (1992)
- 6. Boto, L.: Horizontal gene transfer in evolution: facts and challenges. Proceedings of the Royal Society B: Biological Sciences **277**(1683), 819–827 (2010)
- Cardona, G., Pons, J.C., Rosselló, F.: A reconstruction problem for a class of phylogenetic networks with lateral gene transfers. Algorithms for Molecular Biology 10(1) (Dec 2015). https://doi.org/10.1186/s13015-015-0059-z, http://dx. doi.org/10.1186/s13015-015-0059-z

- Cardona, G., Zhang, L.: Counting and enumerating tree-child networks and their subclasses. Journal of Computer and System Sciences 114, 84–104 (Dec 2020). https://doi.org/10.1016/j.jcss.2020.06.001, http://dx.doi.org/10.1016/j.jcss. 2020.06.001
- 9. De Jong, G.: Phenotypic plasticity as a product of selection in a variable environment. The American Naturalist **145**(4), 493–512 (1995)
- 10. El-Kebir, M.: Sphyr: tumor phylogeny estimation from single-cell sequencing data under loss and error. Bioinformatics **34**(17), i671–i679 (2018)
- 11. El-Kebir, M., Satas, G., Oesper, L., Raphael, B.J.: Inferring the mutational history of a tumor using multi-state perfect phylogeny mixtures. Cell systems **3**(1), 43–53 (2016)
- Fernández-Baca, D.: The perfect phylogeny problem. In: Steiner Trees in Industry, pp. 203–234. Springer (2001)
- 13. Fischer, M., Galla, M., Herbst, L., Long, Y., Wicke, K.: Classes of tree-based networks. Visual Computing for Industry, Biomedicine, and Art 3(1) (May 2020). https://doi.org/10.1186/s42492-020-00043-z, http://dx.doi.org/10.1186/s42492-020-00043-z
- 14. Geiß, M., Anders, J., Stadler, P.F., Wieseke, N., Hellmuth, M.: Reconstructing gene trees from fitch's xenology relation. Journal of Mathematical Biology 77(5), 1459–1491 (Jun 2018). https://doi.org/10.1007/s00285-018-1260-8, http://dx.doi.org/10.1007/s00285-018-1260-8
- Gogarten, J.P., Townsend, J.P.: Horizontal gene transfer, genome innovation and evolution. Nature Reviews Microbiology 3(9), 679-687 (Aug 2005). https://doi.org/10.1038/nrmicro1204, http://dx.doi.org/10.1038/nrmicro1204
- Gonçalves, C., Wisecaver, J.H., Kominek, J., Oom, M.S., Leandro, M.J., Shen, X.X., Opulente, D.A., Zhou, X., Peris, D., Kurtzman, C.P., Hittinger, C.T., Rokas, A., Gonçalves, P.: Evidence for loss and reacquisition of alcoholic fermentation in a fructophilic yeast lineage. eLife 7 (Apr 2018). https://doi.org/10.7554/elife.33034, http://dx.doi.org/10.7554/eLife.33034
- Goyal, A.: Horizontal gene transfer drives the evolution of dependencies in bacteria. iScience 25(5), 104312 (May 2022). https://doi.org/10.1016/j.isci.2022.104312, https://doi.org/10.1016/j.isci.2022.104312
- 18. Gusfield, D.: ReCombinatorics: the algorithmics of ancestral recombination graphs and explicit phylogenetic networks. MIT press (2014)
- 19. Gusfield, D., Eddhu, S., Langley, C.: Optimal, efficient reconstruction of phylogenetic networks with constrained recombination. Journal of Bioinformatics and Computational Biology 2(01), 173–213 (2004)
- 20. Huson, D.H., Rupp, R., Berry, V., Gambette, P., Paul, C.: Computing galled networks from real data. Bioinformatics **25**(12), i85-i93 (May 2009). https://doi.org/10.1093/bioinformatics/btp217, http://dx.doi.org/10.1093/bioinformatics/btp217
- 21. van Iersel, L., Kelk, S., Rupp, R., Huson, D.: Phylogenetic networks do not need to be complex: using fewer reticulations to represent conflicting clusters. Bioinformatics **26**(12), i124–i131 (Jun 2010). https://doi.org/10.1093/bioinformatics/btq202, http://dx.doi.org/10.1093/bioinformatics/btq202
- 22. Iersel, L.V., Jones, M., Kelk, S.: A third strike against perfect phylogeny. Systematic Biology **68**(5), 814–827 (2019)
- Jones, M., Lafond, M., Scornavacca, C.: Consistency of orthology and paralogy constraints in the presence of gene transfers (2017). https://doi.org/10.48550/ARXIV.1705.01240, https://arxiv.org/abs/1705.01240

- Kanehisa, M., Sato, Y., Kawashima, M., Furumichi, M., Tanabe, M.: KEGG as a reference resource for gene and protein annotation. Nucleic Acids Research 44(D1), D457–D462 (Oct 2015). https://doi.org/10.1093/nar/gkv1070, https://doi.org/ 10.1093/nar/gkv1070
- Keeling, P.J., Palmer, J.D.: Horizontal gene transfer in eukaryotic evolution. Nature Reviews Genetics 9(8), 605–618 (Aug 2008). https://doi.org/10.1038/nrg2386, http://dx.doi.org/10.1038/nrg2386
- Kelk, S., Scornavacca, C., van Iersel, L.: On the elusiveness of clusters. IEEE/ACM Transactions on Computational Biology and Bioinformatics 9(2), 517–534 (2012). https://doi.org/10.1109/TCBB.2011.128
- Koonin, E.V., Makarova, K.S., Aravind, L.: Horizontal gene transfer in prokaryotes: quantification and classification. Annual Reviews in Microbiology 55(1), 709–742 (2001)
- 28. Lafond, M., Hellmuth, M.: Reconstruction of time-consistent species trees. Algorithms for Molecular Biology 15(1) (Aug 2020). https://doi.org/10.1186/s13015-020-00175-0, http://dx.doi.org/10.1186/s13015-020-00175-0
- 29. Lawrence, J.G., Ochman, H.: Reconciling the many faces of lateral gene transfer. Trends in Microbiology 10(1), 1-4 (2002). https://doi.org/https://doi.org/10.1016/S0966-842X(01)02282-X, https://www.sciencedirect.com/science/article/pii/S0966842X0102282X
- Letunic, I., Bork, P.: Interactive Tree of Life (iTOL) v6: recent updates to the phylogenetic tree display and annotation tool. Nucleic Acids Research 52(W1), W78-W82 (04 2024). https://doi.org/10.1093/nar/gkae268, https://doi.org/10. 1093/nar/gkae268
- 31. López Sánchez, A., Lafond, M.: Predicting horizontal gene transfers with perfect transfer networks. Algorithms for Molecular Biology **19**(1), 6 (2024)
- 32. Menet, H., Daubin, V., Tannier, E.: Phylogenetic reconciliation. PLoS Comput. Biol. 18(11), e1010621 (Nov 2022)
- 33. Nakhleh, L.: Phylogenetic networks. Ph.D. thesis, The University of Texas at Austin (2004)
- 34. Nakhleh, L., Ringe, D., Warnow, T.: Perfect phylogenetic networks: A new methodology for reconstructing the evolutionary history of natural languages. Language 81(2), 382-420 (2005), http://www.jstor.org/stable/4489897
- 35. Nesbo, C.L., l'Haridon, S., Stetter, K.O., Doolittle, W.F.: Phylogenetic analyses of two "archaeal" genes in thermotoga maritima reveal multiple transfers between archaea and bacteria. Molecular Biology and Evolution 18(3), 362–375 (2001)
- 36. Pe'er, I., Pupko, T., Shamir, R., Sharan, R.: Incomplete directed perfect phylogeny. SIAM Journal on Computing **33**(3), 590–607 (2004)
- 37. Pons, J.C., Semple, C., Steel, M.: Tree-based networks: characterisations, metrics, and support trees. Journal of Mathematical Biology **78**(4), 899–918 (oct 2018). https://doi.org/10.1007/s00285-018-1296-9
- 38. Pontes, B., Giráldez, R., Aguilar-Ruiz, J.S.: Configurable pattern-based evolutionary biclustering of gene expression data. Algorithms for Molecular Biology 8(1), 1–22 (2013)
- 39. Ravenhall, M., Škunca, N., Lassalle, F., Dessimoz, C.: Inferring horizontal gene transfer. PLOS Computational Biology 11(5), e1004095 (May 2015). https://doi.org/10.1371/journal.pcbi.1004095, http://dx.doi.org/10.1371/journal.pcbi.1004095
- 40. Rawat, A., Seifert, G.J., Deng, Y.: Novel implementation of conditional coregulation by graph theory to derive co-expressed genes from microarray data. In: BMC Bioinformatics. vol. 9, pp. 1–9. Springer (2008)

- 41. Schaller, D., Lafond, M., Stadler, P.F., Wieseke, N., Hellmuth, M.: Indirect identification of horizontal gene transfer. Journal of Mathematical Biology 83(1) (Jul 2021). https://doi.org/10.1007/s00285-021-01631-0, http://dx.doi.org/10.1007/s00285-021-01631-0
- 42. Schoch, C.L., Ciufo, S., Domrachev, M., Hotton, C.L., Kannan, S., Khovanskaya, R., Leipe, D., Mcveigh, R., O'Neill, K., Robbertse, B., et al.: Ncbi taxonomy: a comprehensive update on curation, resources and tools. Database **2020**, baaa062 (2020)
- 43. Soucy, S.M., Huang, J., Gogarten, J.P.: Horizontal gene transfer: building the web of life. Nature Reviews Genetics 16(8), 472–482 (Jul 2015). https://doi.org/10.1038/nrg3962, http://dx.doi.org/10.1038/nrg3962
- 44. Thomas, C.M., Nielsen, K.M.: Mechanisms of, and barriers to, horizontal gene transfer between bacteria. Nature Reviews Microbiology 3(9), 711–721 (2005)
- 45. Warnow, T., Tabatabaee, Y., Evans, S.N.: Statistically consistent estimation of rooted and unrooted level-1 phylogenetic networks from snp data. In: RECOMB International Workshop on Comparative Genomics. pp. 3–23. Springer (2024)
- 46. Wickell, D.A., Li, F.: On the evolutionary significance of horizontal gene transfers in plants. New Phytologist **225**(1), 113–117 (Jul 2019). https://doi.org/10.1111/nph.16022, http://dx.doi.org/10.1111/nph.16022
- 47. Zachar, I., Boza, G.: Endosymbiosis before eukaryotes: mitochondrial establishment in protoeukaryotes. Cellular and Molecular Life Sciences 77(18), 3503—3523 (Feb 2020). https://doi.org/10.1007/s00018-020-03462-6, https://doi.org/10.1007/s00018-020-03462-6
- 48. Zhou, H., Beltrán, J.F., Brito, I.L.: Functions predict horizontal gene transfer and the emergence of antibiotic resistance. Science Advances **7**(43), eabj5056 (2021). https://doi.org/10.1126/sciadv.abj5056, https://www.science.org/doi/abs/10.1126/sciadv.abj5056

A Proofs for Section 2 (Preliminaries)

Lemma 2. Let $N = (V, E_S \cup E_T)$ be a galled LGT network and let $v \in V(N)$ be a node with two distinct descendants x and y in \mathcal{T}_N that are transfer nodes (with $v \in \{x,y\}$ being possible). Then one of the transfer edges incident to x or y has both endpoints in the subtree $\mathcal{T}_N(v)$.

Proof. We prove this by contraposition. Let x' and y' be nodes that share a transfer edge with x and y, respectively. Suppose that neither x' nor y' are contained in $\mathcal{T}_N(v)$. Write lca(a,b) for the lowest common ancestor of a,b in \mathcal{T}_N . By our supposition, in \mathcal{T}_N we have that v is on the path from lca(x,x') to x, and from lca(y,y') to y. This implies the existence of two underlying cycles in N: there is a cycle formed by lca(x,x')-x'-x-lca(x,x') and the cycle formed by lca(y,y')-y'-y-lca(y,y') (where the edges between and x',x, and between y',y are used, and the rest use edges of \mathcal{T}_N). These cycles are distinct since they use a different (unique) transfer edge. However, they intersect at v, and thus N is not galled.

Lemma 3. Let $N = (V, E_S \cup E_T)$ be a galled LGT network. Let $x, y \in V$ be two nodes that are not comparable in \mathcal{T}_N and such that x reaches y in N. Then there exists an edge $(x', y') \in E_T$ such that $x' \preceq_{\mathcal{T}_N} x$ and $y \preceq_{\mathcal{T}_N} y'$.

Proof. Suppose for a contradiction that such (x', y') does not exist in N. Since x reaches y in N, we know that there must exist at least another node $w \in V(N)$ incomparable to both x and y that serves as an intermediary node from x to y. More specifically, there exists a transfer edge with an endpoint in $\mathcal{T}_N(x)$ and whose receiving end is w. Nevertheless, y is not a descendant of w (otherwise, w = y' would end the proof), which implies the existence of a transfer edge from some descendant of w to a node incomparable with w. However this creates a situation where $\mathcal{T}_N(w)$ is a subtree with two transfer edges that have their endpoints outside of the subtree, which is forbidden by Lemma 2

B Proofs for Section 3 (The Galled Completion Problem)

Lemma 4. Let N be a galled-completion of a tree T that explains C. Let $C \in C$ be a character and let w be an origin for C in N. Then there is $\alpha_i \in \alpha_T(C)$ such that both of the following hold:

- either $w \preceq_{\mathcal{T}_N} \alpha_i$ or w is a transfer node whose child in \mathcal{T}_N is α_i .
- for every $\alpha_j \in \alpha_T(C) \setminus \{\alpha_i\}$ there is a transfer edge (u, v) such that $u \leq w$ and $v = p_N(\alpha_i)$.

Proof. We focus on the first condition. First observe that if $v \in V(T)$, then $v \in V(N)$ as well. Moreover, the parent of v in \mathcal{T}_N is either also the parent p_v of v in T, or it could be a transfer node created to complete T into N. In the latter case, note that at most one transfer node could could be present on the path between p_v and v in \mathcal{T}_N , as otherwise, there would be two consecutive

transfer nodes which, as one can check, would violate Lemma 2 (p_v would have two descendants with outgoing transfers). This lets us establish that some edges of T are subdivided to obtain \mathcal{T}_N , but each edge can be subdivided at most once.

Let us next observe that if w is an origin for C, by definition it must be a node in $N-F_C(N)$, which is a graph that only contains FA nodes of T, their support tree descendants in N, and possibly transfer nodes that are the parents of FA nodes. Thus either w descends from some $\alpha_i \in \alpha_T(C)$, or results from a subdivision of $(p_T(\alpha_i), \alpha_i)$. In the latter case, w is the parent of α_i since an edge can only be subdivided once, as explained above. Therefore, the first condition of our statement holds.

For the second condition, as we now know the origin w descends from some α_i or is its parent. Let α_j be a FA other than α_i . Let l be a leaf descending from α_i in \mathcal{T}_N . Since w is an origin, it reaches l in $N - F_C(N)$ and thus also in N. Since first-appearance nodes are incomparable in T and \mathcal{T}_N , w is not an ancestor of l in \mathcal{T}_N . By Lemma 3 there is a transfer edge (u,v) in N such that $u \leq w$ and $l \leq v$ in \mathcal{T}_N . The endpoints of this transfer edge must also be in $N - F_C(N)$ for w to be able to use it. Next, note that $p_T(\alpha_i)$ has descendants not in C. Thus in N, $p_T(\alpha_i)$ and its support tree ancestors are in $F_C(N)$, and so it follows that v descends from α_i or is a transfer node on its parent edge, in which case $v = p_N(\alpha_i)$ (again since edges can only be subdivided once). If α_i is a leaf, the latter must hold and we are done. So assume that α_j is not a leaf and let l_1, l_2 be two leaves descending from α_j in \mathcal{T}_N . Then there are two transfer edges (u_1, v_1) and (u_2, v_2) that exist in $N - F_C(N)$, where u_1, u_2 descend from w and v_1, v_2 are ancestors of l_1 and l_2 , respectively. Since these two transfers go out of the $\mathcal{T}_N(w)$ subtree, they must in fact be equal by Lemma 2. In other words, w reaches every leaf below α_i through a single transfer (u, v) such that v is an ancestor of all those leaves. Since v is in $N - F_C(N)$, it follows that v must be the parent of α_i (and not α_i itself because it cannot be a transfer node as its has at least two children, by assumption on T).

Lemma 5. Let T be a galled-completable tree for a character set C. Then for any character $C \in \mathcal{C}$, $\alpha_T(C) \leq 2$.

Proof. Let N be a galled-completion of T that explains \mathcal{C} . Suppose for contradiction that $\alpha_T(C) \geq 3$ for some $C \in \mathcal{C}$. Let w be an origin for C in $N - F_C(N)$. By Lemma 4, w descends from or is the parent of one of the FAs, say $x \in \alpha_T(C)$. Let y, z be two other FAs of C. Note that, by definition of FAs, x, y, z are pairwise incomparable in T. By the second statement of Lemma 4, there are transfer edges $(u_1, p_N(y))$ and $(u_2, p_N(z))$ where u_1 and u_2 descend from w in T_N . This implies that the subtree $T_N(w)$ contains two outgoing transfers, which contradicts Lemma 2. Thus $|\alpha_T(C)| \leq 2$ for all $C \in \mathcal{C}$.

Lemma 6. Let T be a galled-completable tree for C. Suppose that there exists two distinct characters A and B with $\alpha_T(A) = \{a_1, a_2\}$ and $\alpha_T(B) = \{b_1, b_2\}$. Then the two following statements hold:

1. If $b_1 \prec a_1$ and b_2 is not comparable to a_1 , then $a_2 = b_2$.

2. If $a_1 = b_1$, then either $b_2 \prec a_2$ or $a_2 \prec b_2$.

Proof. We begin with the first statement. Suppose for a contradiction that the conditions of the lemma hold, but that $a_2 \neq b_2$. Let N be a galled-completion of T that explains C. This leads to the following two cases.

- Case 1: a_2 and b_2 are comparable. Suppose $b_2 \prec a_2$. Let w be an origin for A in $N F_A(N)$. By Lemma 4, w descends from a_1 or a_2 , or is a transfer node with one of those as a child. Suppose first that $w \preceq a_1$ or $w = p_N(a_1)$. We know by Lemma 4 that there exists a transfer edge from some descendant of w that has $p_N(a_2)$ as endpoint. Also by Lemma 4, $p_N(b_2)$ or a descendant of b_2 is a transfer node whose other endpoint is $p_N(b_1)$ or a descendant of b_1 . This implies that there are two transfer nodes in the subtree $\mathcal{T}_N(p_N(a_2))$ whose other endpoint is outside, which is forbidden by Lemma 2. The case where $w \preceq a_2$ or is the parent of a_2 is symmetric.
 - Next suppose that $a_2 \prec b_2$. By Lemma 4, one of $p_N(a_1)$ or $p_N(a_2)$ is the receiving end of a transfer, whose sending end is on the other side. If $p_N(a_1)$ is a transfer node, we also know that $p_N(b_1)$ or one of its descendants is a transfer node, with the other endpoint on the b_2 side. Either way, $\mathcal{T}_N(p_N(a_1))$ has two descending transfer nodes with external endpoints, contradicting Lemma 4. Thus $p_N(a_2)$ is the receiving end of a transfer. By a symmetric argument, $p_N(b_1)$ is the receiving end of a transfer. This implies that there are transfers between $\mathcal{T}_N(a_1)$ and $\mathcal{T}_N(b_2)$ (or their parents) going in opposite directions. Because transfer edges are unidirectional, these transfers are distinct, from which it can easily be seen that there are two underlying cycles intersecting. Therefore, this case is not possible.
- Case 2: a_2 and b_2 are incomparable. By Lemma 4, there is one transfer with one endpoint being $p_N(a_1)$ or a descendant of a_1 , and the other being $p_N(a_2)$ or a descendant of a_2 . Likewise, there is a similar transfer connecting b_1 and b_2 . Since a_2 and b_2 are incomparable, these two transfers must be distinct, they are both in $\mathcal{T}_N(a_1)$ or $\mathcal{T}_N(p_N(a_1))$, and they both have external endpoints since b_2 is not comparable with a_1 , contradicting Lemma 2.

Since neither case is possible, we must have $a_2 = b_2$.

Next, consider the second statement. Let N be a galled-completion of T that explains C. Suppose for a contradiction that $a_1 = b_1$, but neither $a_2 \prec b_2$ nor $b_2 \prec a_2$ holds i.e. a_2 and b_2 are incomparable in \mathcal{T}_N . By Lemma 4, there is a transfer edge between descendants of a_1 and a_2 (or their parents), and a transfer edge between descendants of b_1 and b_2 (or their parents). Since a_2 and b_2 are incomparable, these transfers must be distinct. However, they imply the existence of two transfer nodes descending from $a_1 = b_1$ (or its parent) that have an external endpoint, contradicting Lemma 2.

Lemma 7. Let T be a tree on leafset S and character set C. If T is galled-completable, then in the redundancy-free network $N = (V_T, E_T)$ of T, every node is incident to at most one transfer edge.

Proof. Suppose for contradiction that some node u' of N is incident to two distinct transfer edges, with v', w' the other endpoints of those edges (note that v' = w' is possible). By construction, u', v', w' are subdivision vertices of \mathcal{T}_N , and are respective parents of FA nodes u, v, w in T. Moreover, v and w must be FA neighbors of u, and so there are characters C_{uv} (resp. C_{uw}) with FAs $\{u, v\}$ (resp. $\{u, w\}$) in T.

Suppose first that $v \neq w$. In that case, C_{uv} and C_{vw} are distinct as their FAs differ. By the second part of Lemma 6, the two characters C_{uv} and C_{uw} have a common FA u, and thus v and w are comparable. Suppose without loss of generality that $w \prec_T v$. We can further assume that w is a minimal FA neighbor of u (otherwise, we choose w to be such a neighbor, which does not affect the presence of the edge between u' and v'), which guarantees that $(w', u') \in E_T$. By the construction of N, the edge (v', u') cannot be in E_T , as u' only receives transfers from its minimal neighbors. Therefore, the transfer between u' and v' is in the (u', v') direction. As v is not in a simple pair, this edge is present because v has multiple FA neighbors and u is minimal. This means that there is another character C_{vz} with FAs $\{v, z\}$, where $z \neq u$. Using Lemma 6 in the same way as before, we get $u \prec_T z$. We now have two pairs of FAs $\{z, v\}$ and $\{u, w\}$, where $u \prec_T z$, w is not comparable to z (because v is not), and $w \neq v$. By putting $\{z, v\} = \{a_1, a_2\}$ and $\{u, w\} = \{b_1, b_2\}$, we obtain a contradiction of the first part of Lemma 6.

So suppose that v=w, and hence $C_{uv}=C_{uw}$. This means that both edges (u',v') and (v',u') are present. This is not possible if $\{u,v\}$ is simple, so u,v both have at least two FA neighbors, v must be a minimal FA neighbor of u and u a minimal FA neighbor of v. Let $x \neq v$ be another FA neighbor of u. Then some character C_{ux} has $\{u,x\}$ as FAs. Since C_{uv} has FAs $\{u,v\}$, by the second part of Lemma 6, x and v must be comparable. Since v is minimal, $v \prec_T x$. As v also has other FA neighbors, by a symmetric argument, some character C_{vy} has FAs $\{v,y\}$ with $u \prec_T y$. But the pair of FAs $\{y,v\}$, $\{u,x\}$ has $u \prec_T y$, x incomparable to y ($x \prec_T y$ is not possible since v would descend from y, and $y \prec_T x$ is not possible as u would descend from x), and $v \neq x$, a contradiction of the first part of Lemma 6.

Lemma 8. A tree T on leafset S with character set C is galled-completable if and only if its redundancy-free network $N = (V, E_S \cup E_T)$ is a galled tree.

Proof. (\Rightarrow) Suppose that T is galled-completable and let $N' = (V', E'_S \cup E'_T)$ be a galled-completion for T that explains \mathcal{C} . We need to show that N is a galled tree. We assume that N' is obtained from T by subdividing every edge once, then adding a set of transfer edges between subdivision nodes (note that if N' exists, such a galled-completion also exists). Since N also subdivides every edge once, this allows us to assume that N' and N have the same set of nodes, putting the nodes in correspondence without ambiguity.

We first build an injective map, that associates each transfer edge (u', v') of N with a distinct transfer edge (x, y) of N', such that $y \in \{u', v'\}$. Let $(u', v') \in E_T$. Note that by the construction of N, u', v' are subdivision nodes of \mathcal{T}_N and are

parents of FAs u, v. Moreover, u, v are FA neighbors, and thus there is some character C with $\alpha_T(C) = \{u, v\}$. By Lemma 4, in N' there is a transfer edge (x, y), where either $x \leq_{\mathcal{T}_N} u'$ and y = v', or $x \leq_{\mathcal{T}_N} v'$ and y = u'. Either way, we map (u', v') to (x, y). We claim that no other transfer edge of N can be mapped to (x, y) in this manner. Suppose that some other transfer edge (u'', v'') of N maps to (x, y). According to our map, y = u'' or y = v'', but either way, y is incident to two transfer arcs in N, contradicting Lemma 7. Therefore, only (u', v') can be mapped to (x, y).

Next, consider $(u',v') \in E_T$ and its associated edge (x,y) in N'. Suppose that $(x,y) = (\tilde{u},v')$ for some descendant \tilde{u} of u' in $\mathcal{T}_{N'}$. Consider the network \tilde{N} obtained from N' by removing (\tilde{u},v') and inserting (u',v') (which does nothing if $\tilde{u}=u'$). Note that in N', the transfer edge (\tilde{u},v') belongs to a unique underlying cycle H formed by the transfer edge, plus the paths from \tilde{u} and from v' to the lowest common ancestor of \tilde{u} and v' in $\mathcal{T}_{N'}$. Since u' is on the path between that ancestor and \tilde{u} , in \tilde{N} the incorporation of (u',v') only creates an underlying cycle whose set of vertices is a subset of H. Since H did not intersect with other underlying cycles in N', this new underlying cycle does not either, and it follows that \tilde{N} is a galled tree as well. The same idea applies if y=u' instead.

Since all underlying cycles of N' are independent, we can apply the transformation from the previous paragraph to replace every mapped transfer edge of N' by a transfer edge of N, one after another, while maintaining the property that no cycles intersect. Notice that because each $(u',v') \in E_T$ maps to a distinct transfer edge of N', every edge of N is incorporated, and no edge of N' is "moved" twice by this process. Therefore, we obtain a galled tree whose set of transfer edges contains E_T . It then follows that N is a galled tree as well.

(\Leftarrow) Suppose that the redundancy-free network N is a galled tree. We show that for every character in $C \in \mathcal{C}$ there exists a node in $N - F_C(N)$ that reaches every leaf in C as required by Lemma 1. Note that if $|\alpha_N(C)| = 1$, then C forms a clade in T and thus in \mathcal{T}_N . If u is the FA node of C in T, then u is able to reach every element of C in $N - F_C(N)$ since every support tree descendant of u is also in $N - F_C(N)$, which is sufficient to explain C.

Suppose that $|\alpha_T(C)| = 2$. Let u and v be the FAs of C in T, which are the roots of clades C_1 and C_2 such that $C = C_1 \cup C_2$. Denote $p_u = p_{\mathcal{T}_N}(u)$ and $p_v = p_{\mathcal{T}_N}(v)$, where p_u and p_v are transfer nodes since every edge of T was subdivided to produce N. Note that by definition, in \mathcal{T}_N all the descendants of p_u and of p_v are in C, and thus both of them appear in $N - F_C(N)$. Suppose that one of the edges (p_u, p_v) or (p_v, p_u) is present. In the first case, p_u is an origin for C and in the second case, p_v is an origin.

So suppose that neither transfer edge is present. Then by construction, either u or v has at least two FA neighbors (otherwise, we would have added one of the two edges between their parent in an arbitrary direction and be in the previous case). Suppose without loss of generality that u has at least two FA neighbors. Then v is not one of its minimal FA neighbors, which means that there is some minimal FA neighbor w of u such that $w \prec_T v$. Let $p_w = p_{\mathcal{T}_N}(w)$ and note that v contains the transfer edge v, v, v is an origin for v, since it is in

 $N - F_C(N)$, it can reach all the elements of C that descend from itself in \mathcal{T}_N , and all those that descend from u through the transfer edge (p_w, p_u) .

We have therefore shown that all characters have an origin, which by Lemma 1 implies that N is a PTN for C, as desired.

Theorem 1. Algorithm 1 correctly solves the Galled Tree Completion problem in time O(|V(T)||C|).

Proof. We begin by arguing that the algorithm is correct. The first for loop in Line 4 ensures that each character has at most two FAs as stated in Lemma 5. We claim that the second for loop will find all the required minimal transfers. For a fixed node v, we traverse its set of FA neighbors, noting that those are not necessarily comparable. However, if v has two incomparable FA neighbors, then v must also have at least two minimal incomparable FA neighbors. This then implies that the redundancy-free network N will have two transfer edges incident to $p_N(v)$, a contradiction of Lemma 7. Thus, Line 12 allows us to rule out these cases. After we ensure that all the FA neighbors of v are comparable we will find the minimum among them, which will allow us to add the desired transfer edge. For simple characters on the other hand, the verification in Line 20 allows us to add an arbitrary direction only when its unique neighbor is a marked node. The reason for this is that whenever the node is marked we know that there do not exist other FA neighbors to compare c_{min} to.

Let us now argue the complexity. Let T=(V,E) be the given tree. The complexity will be dominated by the first for loop. For a given character $C \in \mathcal{C}$, computing the FAs can be done in time O(|V|). Thus the first for can be done in time $O(|\mathcal{C}||V|)$. On the other hand, the postorder traversal of T that adds the transfer edges can be done in time $O(|V|+|\mathcal{C}|)$. This is because we traverse O(|V|) nodes, and each $\{u,v\}$ relationship of FA neighborhood requires work at most twice throughout the algorithm, once for u and once for v. Moreover, each character implies at most one FA relationship, the total work over the FA neighbor hood relationships is $O(|\mathcal{C}|)$. We note that checking for the incomparability or descendance of nodes can be achieved in constant time with standard pre-processing of the tree. Finally, the last verification on Line 21 can be done in time O(|V|) (see e.g. [18]).

C Proofs for Section 4 (The Galled Compatibility Problem)

Lemma 9. Suppose that C contains a maximal character C that is compatible with every other character. Let $C_1 = \{A \in C : A \subset C\}$ and $C_2 = \{A \in C : A \cap C \neq \emptyset\}$. Then C is galled-compatible if and only if C_1 and C_2 are both galled-compatible.

Moreover, given galled PTNs N_1 , N_2 that explain C_1 , C_2 , respectively, one can obtain in time O(|C|) a galled PTN N that explains C.

Proof. The first direction of the if and only if statement is trivial: if C is galled-compatible, then any of its subset is galled-compatible, including C_1 and C_2 , since

a network that explains C also explains C_1, C_2 . In the other direction, suppose that C_1 and C_2 are galled-compatible. Since C is compatible with every character, for any $A \in \mathcal{C} \setminus \{C\}$, one of $A \subseteq C, C \subseteq A$, or $A \cap C \neq \emptyset$ holds. Also, because C is maximal, $C \subseteq A$ does not hold. It follows that A is in one of \mathcal{C}_1 or \mathcal{C}_2 and thus $\{C_1, C_2\}$ is a partition of $C \setminus \{C\}$. Moreover, by defining $S_1 := \bigcup_{A \in C_1} A$ and $S_2 := \bigcup_{B \in C_2} B$, we get that $S_1 \subseteq C$ and $S_2 \cap C = \emptyset$. In particular, S_1 and S_2 are disjoint. Let N_1 and N_2 be galled trees that explain \mathcal{C}_1 and \mathcal{C}_2 , respectively. Then $L(N_1)$ and $L(N_2)$ are also disjoint. Consider the network N obtained by (1) creating a root node r; (2) adding $r(N_1)$ and $r(N_2)$ as children of r; (3) for each $s \in C \setminus S_1$, adding s as a leaf child of $r(N_2)$. Observe that, since N_1 and N_2 are galled trees, by adding r and its two child edges cannot create intersecting cycles, nor can adding leaves under $r(N_2)$. Moreover, it is not hard to see that every character of \mathcal{C}_1 and \mathcal{C}_2 is still explained by N, and C is also explained since it is a clade of N. Thus \mathcal{C} is galled-compatible. This construction also shows how to obtain N from N_1 and N_2 in time O(|C|), since it only requires adding a new root and adding up to |C| leaves under $r(N_2)$.

Lemma 10. Let T be a tree that is galled-completable for C, and let $A, B \in C$ be a pair of incompatible characters. Then one of the following holds:

```
- A is split into A \setminus B, A \cap B in T, and B is a clade of T;
```

Proof. Since A and B are incompatible, by definition T cannot contain both as a clade and so at most one can be. So assume for now that neither A nor B is a clade of T. Then both characters have two FAs in T (and not more, by Lemma 5). Let a_1, a_2 and b_1, b_2 be the FA nodes of A and B, respectively, and let A_1, A_2, B_1, B_2 be the respective clades of a_1, a_2, b_1, b_2 .

We claim that some a_i is a strict ancestor of some b_j or vice-versa. Note that $A \cap B \neq \emptyset$, so we may assume without loss of generality that $A_1 \cap B_1 \neq \emptyset$. Thus, a_1 has a descending leaf in common with b_1 , which implies that a_1 is an ancestor of b_1 or vice-versa. If $a_1 \neq b_1$, our claim holds. If $a_1 = b_1$, then $a_2 \prec b_2$ or $b_2 \prec a_2$ by Lemma 6 (part 2), and again our claim holds.

We may therefore assume, without loss of generality, that a_1 is a strict ancestor of b_1 , which implies $B_1 \subseteq A_1$. Notice that b_2 cannot be a descendant of a_1 , since otherwise we would have $B_2 \subseteq A_1$ and $B_1 \cup B_2 \subseteq A_1$, contradicting the incompatibility of A and B. Since b_2 is incomparable with b_1 , it also cannot be an ancestor of a_1 , and thus b_1 is also incomparable with a_1 . Then by Lemma 6 (part 1), $a_2 = b_2$. Those imply $B_1 \subseteq A_1$ and $A_2 = B_2$, in turn implying $B \subseteq A$ and contradicting that A and B are incompatible.

This establishes that exactly one of A or B is a clade of T. Suppose that B is a clade and that A is split into A_1 and A_2 in T, with respective FAs a_1, a_2 . Let b be the (unique) FA of B. If $b \leq a_1$ or $b \leq a_2$, then $B \subseteq A$ and A, B would be compatible. Moreover, B intersects with at least one of A_1 and A_2 since it intersects with A, and thus b is an ancestor of a_1 or a_2 . If b is an ancestor of both, then $A \subseteq B$ and again A, B would be compatible. Hence b is an ancestor of exactly one of a_1 or a_2 . If b is an ancestor of a_1 , then $a_1 \in B \cap A$ and $a_2 \in A \setminus B$.

⁻ B is split into $B \setminus A, A \cap B$ in T, and A is a clade of T.

If b is an ancestor of a_2 , then $A_2 = B \cap A$ and $A_1 = A \setminus B$. This shows that the first case of the statement holds.

If A is a clade of T instead, then using the same arguments, we get the second case of the statement. \Box

Lemma 11. Let A be a maximal character of C. Suppose that T is a galled-completable tree for C in which A is split into the clades A_1 and A_2 . Let $X \subseteq C$ be the subset of characters that intersect with both A_1 and A_2 .

Then, after possibly exchanging the subscripts of A_1 and A_2 , \mathcal{X} is an (A_1, A_2) chain. Moreover, for every $X \in \mathcal{X}$, the clades $X \cap A_1$ and $X \cap A_2$ are in T.

Proof. Let a_1, a_2 be the FAs of A in T, which respectively correspond to the clades A_1 and A_2 . Let $X \in \mathcal{X} \setminus \{A\}$ and note that although X intersects with both A_1 and A_2 , it cannot contain both, as otherwise A would not be maximal. Thus one of $X \cap A_1 \subset A_1$ or $X \cap A_2 \subset A_2$ holds.

If $X \cap A_1 \subset A_1$, then a_1 has descending leaves not in X, implying that X has a FA x_1 that strictly descends from a_1 . Since X also intersects with A_2 , X has another FA x_2 that must be incomparable with a_1 and, by Lemma 6 (part 1), the other FA x_2 of X is equal to a_2 . This implies $X \setminus A_1 = A_2$. If $X \cap A_2 \subset A_2$, then instead this argument yields $x_1 = a_1, x_2 \prec a_2$ and $X \cap A_2 \subset A_2, X \setminus A_2 = A_1$. Suppose for the remainder that $x_1 \prec a_1$ and $x_2 = a_2$. This is without loss of generality, as otherwise we can swap the subscripts of A_1 and A_2 .

Next, consider another character $X' \in \mathcal{X} \setminus \{X,A\}$. As above, X' must have two FAs x_1', x_2' with either $x_1' \prec a_1$ and $x_2' = a_2$, or vice-versa. By the latter case, we mean $x_2' \prec a_2$ and $x_1' = a_1'$, which we claim cannot occur. If this were true, we get $x_1 \prec a_1 = x_1'$ while $x_2 = a_2 \neq x_2'$, contradicting Lemma 6 (part 1). It must then be that $x_1' \prec a_1$ and $x_2' = a_2$.

It follows that every $X' \in \mathcal{X}$ has a FA equal to a_2 . By Lemma 6 (part 2), the FAs other than a_2 of two characters of \mathcal{X} are comparable and, by the above, descend from a_1 . Therefore, the FAs on the a_1 side are pairwise-comparable in terms of strict ancestry. This implies that in T, there is a path from a_1 to one of its descendants that contains all the FAs of the elements of \mathcal{X} on the a_1 side. By listing these FAs from the deepest up until a_1 , we get an ordering $X_1, \ldots, X_l = A$ of \mathcal{X} such that $X_1 \cap A_1 \subset X_2 \cap A_1 \subset \ldots \subset X_l \cap A_1 = A_1$. Also, the FAs on the a_2 side are all equal to a_2 , which means that $X \setminus A_1 = A_2$ for each X of \mathcal{X} .

It follows that \mathcal{X} is an (A_1, A_2) -chain, and that each $X \cap A_1$ and each $X \cap A_2 = A_2$ forms a clade in T.

Lemma 12. Let A be a maximal character of C. Suppose that T is a galled-completable tree for C in which A is split into the clades A_1 and A_2 . Let $X \subseteq C$ be the subset of characters that intersect with both A_1 and A_2 and suppose that X is an (A_1, A_2) -chain. Let $X_1 \cap A_1$ be the bottom of the chain and let A_2 be the stable side of the chain.

If $C \in \mathcal{C} \setminus \mathcal{X}$ contains $X_1 \cap A_1$ or contains A_2 , then C is a clade of T.

Proof. Suppose that C contains $X_1 \cap A_1$. If $C = X_1 \cap A_1$, then T contains C by Lemma 11. Otherwise, C is a strict superset of $X_1 \cap A_1$. Note that since

 $C \notin \mathcal{X}$ and already intersects with A_1 , C does not intersect with A_2 . However, $X_1 \setminus A_1 = A_2$ by the definition of an (A_1, A_2) -chain. Therefore, $C \setminus X_1$ and $X_1 \setminus C$ are non-empty, which implies that C and X_1 are incompatible. By Lemma 10, one of C or X_1 must be a clade of T. We know that X_1 is already split into $X_1 \cap A_1$ and $X_1 \cap A_2$ in T, and thus C must be a clade of T.

Suppose that C contains A_2 . If $C = A_2$, then T contains C as a clade by assumption. Otherwise, C is a strict superset of $A_2 = X_1 \cap A_2$. As before, C does not intersect with A_1 , and thus does not intersect with $X_1 \cap A_1$ and is therefore incompatible with X_1 . Again, C is a clade of T by Lemma 10.

Lemma 13. Let A be a maximal character of C and suppose that there is a galled-completable tree T^* for C in which A is split into A_1 and A_2 . Let T be the tree whose set of clades is precisely the clades forced by $\{A_1, A_2\}$ (plus the root clade and the leaves).

If $C \in \mathcal{C}$ is a character not forced by $\{A_1, A_2\}$, then all the taxa in C have the same parent in T.

Proof. Let T and T^* be as defined in the lemma statement. Also, let \mathcal{X} be the set of characters that intersect both A_1 and A_2 . By Lemma 11, we may assume that \mathcal{X} forms an (A_1, A_2) -chain. Let $X_1 \in \mathcal{X}$ be such that $X_b := X_1 \cap A_1$ is the bottom of the chain, and $X_s := X_1 \setminus A_1 = A_2$ is the stable side (using the subscripts b for bottom and s for stable). Let x_b be root node of the X_b clade in T and let x_s be the root node of the X_s clade.

By Lemma 11 and Lemma 12, T^* contains all the clades forced by $\{A_1, A_2\}$. Thus T^* contains all the clades of T, plus possibly others. We assume that a clade present in both T and T^* is rooted at the same node in both trees — that is, if y is the root of some clade Y of T, then y is also present in T^* and is the root of clade Y in T^* as well. We will therefore assume that $V(T) \subseteq V(T^*)$. Notably, T^* also contains X_b and X_s , so we assume that the same nodes x_b and x_s are the roots of these clades in T^* as well.

Before proceeding, we establish a fact on the structure of T (as can be seen in Figure 12 below).

Fact 1. Every internal node of T is an ancestor of x_b or x_s , and the root of T is the only node that is an ancestor of both.

Proof We claim that every non-trivial clade of T is either a (not necessarily strict) superset of X_b or of X_s (a trivial clade is either a single element or all of L(T)). Recall that we can distinguish three types of forced clades in T: (1) forced clades of the form $X \cap A_1$ for $X \in \mathcal{X}$, which by the chain properties must be supersets of $X_1 \cap A_1 = X_b$; (2) forced clades of the form $X \cap A_2$, which are equal to $A_2 = X_s$; (3) forced clades from those those C' that contain X_b or X_s . In all cases, our claim holds.

Given this claim, notice that any non-root internal node v of T either roots the clade A_1 , A_2 , or it roots a forced clade. Since any such clade contains X_b or X_s , v must be an ancestor of x_b or x_s .

Now assume that a non-root node v has both x_b and x_s as descendants in T. Let a_1 be the root of the A_1 clade. Note that a_1 is an ancestor of x_b but

not x_s , so a_1 is on the path from x_b to x_s (when viewing T as an undirected graph). This implies that v is an ancestor of a_1 and thus the clade corresponding to v contains A_1 . As v is also an ancestor of x_s , which roots the A_2 clade, then the clade of v also contains A_2 . Thus, the clade of v contains $A_1 \cup A_2 = A$. By assumption, A is not a clade of T, so the clade of v is a strict superset of A. Moreover, since v is not a root, the clade of v must be in T because it was forced, implying the existence of a character in C that strictly contains A, contradicting its maximality, thereby establishing our fact.

Observe that Fact 1 implies that in T, all the children of x_b and x_s are leaves. In fact, aside from the root, all the nodes on the path between x_b and x_s have a single non-leaf child, which is the one that leads to x_b or x_s .

Now suppose that some $C \in \mathcal{C}$ is not forced by $\{A_1, A_2\}$, but that there are $y, z \in C$ such that the parent p_y of y in T is different from the parent p_z of z in T. Assume without loss of generality that the distance between p_y and the root of T is smaller than or equal to the distance between p_z and the root. Since p_y and p_z are internal nodes of T, they are ancestors of x_b or x_s in T by Fact 1. Figure 8 illustrates one possible scenario where p_y is the root of T and p_z is on the path between the root and x_b . Note that $\{p_y, p_z\} = \{x_b, x_s\}$ is not possible, since otherwise C would intersect with both $X_b \subseteq A_1$ and $X_s \subseteq A_2$, in which case C should be in \mathcal{X} and be a forced character. Thus at least one of p_y or p_z is a strict ancestor of x_b or x_s in T. Since p_y is closer to the root, we may assume that this holds for p_y .

Next, consider T^* , and let $r = lca_{T^*}(x_b, x_s)$, that is, the lowest common ancestor of x_b and x_s in T^* . Note that because T^* can have more clades than T, r is not necessarily the root of T^* . Let P be the set of nodes of T^* on the path between r and x_b , or on the path between r and x_s , excluding x_b and x_s themselves.

Fact 2. Let N be any galled-completion of T^* that explains \mathcal{C} . Then there is an underlying cycle in N that contains all the nodes in P, plus possibly nodes that descend from x_b or x_s , but no other nodes.

Proof Since X_1 is split into X_b and X_s in T^* , by Lemma 4 there must be a transfer edge between $p_N(x_b)$ or a descendant of x_b , and $p_N(x_s)$ and a descendant of x_s , which implies that existence of the claimed cycle.

Our next step is to argue that because of y and z, there is some other cycle that intersects with P. To this end, define p_y' as the first ancestor of y in T^* that has one of x_b or x_s as a descendant, and define p_z' as the first ancestor of z in T^* that has one of x_b or x_s as a descendant. Recall that p_y is the parent of y in T, but that p_y is also in T^* and represents the same clade, although p_y might not be the parent of y in T^* . But in T^* , p_y has y plus one of x_b or x_s as a descendant. Because of this, we have that p_y' is either equal to p_y , or it is a descendant of p_y (in T^*). Likewise, p_z' is a descendant of p_z in T^* . Figure 12 shows a case where p_y is a strict ancestor of p_y' and $p_z = p_z'$.




Fig. 12. An illustration of T versus T^* . The white circles represent clades that are common to T and T^* .

Fact 3. Let N be any galled-completion of T^* for \mathcal{C} . Then there is an underlying cycle in N that contains an ancestor of y not in P, plus all the nodes on the path between p'_y and p'_z .

Proof Let us first argue that p'_y is not a FA node for C in T^* : if this was the case, because p'_y has x_b or x_s as a descendant, having p'_y as a FA of C would imply that C contains X_b or X_s and it would be forced. Therefore, there is a FA node f_y of C that is a strict descendant of p'_y and an ancestor of y. Likewise, p'_z is not a FA of C either, and there is a FA f_z that is a strict descendant of p'_z and an ancestor of z.

Next, note that y is not a descendant of p_z in T, as otherwise p_y would descend from p_z and would be farther from the root. Since p_z still represents the same clade in T^* , the same holds in T^* . Then in T^* , since p_z' is a descendant of p_z , we deduce that $p_y' \neq p_z'$ (otherwise, we would have $y \prec_{T^*} p_y' = p_z' \preceq_{T^*} p_z$). Thus, f_y and f_z are distinct nodes. By Lemma 4, there is a transfer edge between these two FA subtrees. Because f_y and f_z strictly descend from a node in P, the endpoints of this transfer edge are not in P, implying the existence of a cycle that contains the created transfer nodes, along with the path from that node to p_y' , then the path from p_y' to p_z' , followed by the path from p_z' to the transfer node in that subtree.

We may conclude the proof with that last fact. Consider the cycle H obtained from Fact 2 that contains the nodes of P and possible descendants of x_s and x_b . Then consider the cycle H' obtained from Fact 3. The latter has an ancestor of y not in P, and because y does not descend from x_b or x_s , these two cycles are different. Moreover, H' contains p'_y . If p'_y is a node of P, then H and H' intersect, a contradiction. Otherwise, p'_y must be a strict ancestor of r. This can only occur if p_y was the root of T, and that p'_y ended up as an ancestor of $lca_{T^*}(x_b,x_s)$ when refining T to T^* . In this case however, p_z could not be the root of T as well, and p_z must be a descendant of r. Therefore, H' contains r and again, this implies that H and H' intersect, which concludes the proof. \square

Lemma 14. Let A be a maximal character of C and let $\{A_1, A_2\}$ be a partition of A. Then there is a tree that is completable for C and that contains the clades A_1 and A_2 if and only if all the following conditions hold:

- 1. Let \mathcal{X} be the characters that intersect with A_1 and A_2 . Then \mathcal{X} forms an (A_1, A_2) -chain;
- 2. There exists a tree T on leafset S whose set of clades is precisely the set of clades forced by $\{A_1, A_2\}$ (plus the root clade and leaves).
- 3. Let C_F be the set of characters forced by $\{A_1, A_2\}$. Then for any $C \in \mathcal{C} \setminus \mathcal{C}_F$, all the taxa of C have the same parent in T.
- 4. For any subset $C' \subseteq C \setminus C_F$ such that all taxa that belong to some character of C' have the same parent in T, C' is galled-compatible.

Proof. Suppose that there is a tree T^* that contains the clades A_1, A_2 , such that T^* is galled-completable for \mathcal{C} . Condition 1 holds because by Lemma 11, \mathcal{X} forms an (A_1, A_2) -chain. For Condition 2, by Lemma 11 and 12, T^* contains all the clades forced by $\{A_1, A_2\}$, and therefore T as described in the condition must exist. Condition 3 holds by Lemma 13. Finally, Condition 4 holds because by the existence of T^* , we have that \mathcal{C} is galled-compatible. By heredity, any subset $\mathcal{C}' \subseteq \mathcal{C}$ is galled-compatible, including those described in the condition.

In the converse direction, assume that all the conditions of our statement hold. We show how to obtain a tree T^* with clades A_1 and A_2 that is galled-completable for \mathcal{C} . Let T be the tree whose set of clades consists of the clades forced by $\{A_1, A_2\}$. Let \mathcal{X} be the characters that intersect A_1 and A_2 . Let $X_1 \in \mathcal{X}$ such that $X_1 \cap A_1$ is the bottom of the chain and $X_1 \setminus A_1 = A_2$. We know that T has the clades $X_1 \cap A_1$ and A_2 , since they are forced. For later reference, we let x_b and x_s be the roots of these clades in T, respectively.

Next, for each internal node $v \in V(T)$, let C_v be the characters whose taxa all have v as their parent in T. We know that C_v is galled-compatible, so there is a tree T_v that is galled-completable for C_v . We modify T as follows: remove every leaf that is a child of v, and add the root of T_v as a new child of v. After doing this for every v, we obtain the tree T^* .

We claim that T^* is galled-completable for \mathcal{C} . First, notice that T^* contains all the clades of T, since we have only removed leaves (trivial clades) and replaced them by subtrees, which does not remove clades that were already present in T. Thus every clade forced by $\{A_1, A_2\}$ is in T^* . In particular, $X_1 \cap A_1$ and A_2 are still clades of T^* , still rooted at x_b and x_s , respectively. Add a transfer edge from the parent branch of x_b to the parent branch of x_s . This yields a network that we call N.

Let C_F be the characters forced by $\{A_1, A_2\}$. We will add further edges to N, but for the moment we claim that N, with the single transfer edge $(p_N(x_b), p_N(x_s))$, explains the characters in C_F . Recall that there are three types of forced characters, which we deal with as follows:

- let $C \in \mathcal{C}_F$ such that C contains the bottom of the chain, namely $X_1 \cap A_1$. Then C is a forced clade, which is in T and therefore in T^* . Thus T^* explains C without requiring any transfer.

- let $C \in \mathcal{C}_F$ such that C contains the stable side of the chain, namely A_2 . Again, C is forced in T and thus T^* and is also explained.
- let $C \in \mathcal{C}_F$ such that $C \in \mathcal{X}$. Then C intersects both A_1 and A_2 . By the definition of an (A_1, A_2) -chain, $C \cap A_1$ is either equal to $X_1 \cap A_1$, or it is a strict superset of $X_1 \cap A_1$. Also by the definition of chains, $C \cap A_2 = A_2$. We know that $C \cap A_1$ and $C \cap A_2$ are forced by $\{A_1, A_2\}$ and are thus present in T and T^* . The network N can explain C by putting the origin at the root of the $C \cap A_1$ clade, and using the transfer edge $(p(x_b), p(x_s))$ to send the character to $C \cap A_2 = A_2$. Note that this is possible since $C \cap A_1$ is a superset of $X_1 \cap A_2$, and thus the root of the $C \cap A_1$ clade is an ancestor of $p(x_b)$, or is equal to x_b when $C = X_1$ (in which case the transfer can still be used).

It only remains to explain the characters not in C_F . For each subtree T_v , replace T_v by a galled completion N_v that explains C_v , which exists by assumption. This ensures that each character from each C_v is explained by the resulting network. Moreover, since the T_v 's are independent subtrees, all additional cycles created are entirely contained inside the N_v subnetworks and, in particular, do not contain v. This implies that we do not create intersecting cycles that involve nodes from two distinct N_v subnetworks, and that do not intersect with the cycle involving $(p(x_b), p(x_s))$. Therefore, the resulting network is a galled tree. This concludes the proof.

Lemma 15. Suppose that C has no maximal character that is compatible with all the others. Then there exists a pair of incompatible characters $\{A, B\}$ of C such that A and B are both maximal.

Proof. Let A be a maximal character of \mathcal{C} . By assumption, there is some $B \in \mathcal{C}$ such that A and B are incompatible. Choose such a B of maximum cardinality. Note that $A \cap B$, $B \setminus A$, $A \setminus B$ are all non-empty. Suppose that B is not maximal, i.e. there is $B' \in \mathcal{C}$ such that $B \subset B'$. We have $A \cap B' \neq \emptyset$ because B' contains B. Also, $B' \subset A$ is not possible since $B \setminus A$ is non-empty, and $A \subset B'$ is not possible since A is maximal. Thus A and B' are incompatible, contradicting the choice of B.

Theorem 2. The Galled Compatibility problem can be solved in time $O(n|\mathcal{C}|^3)$.

Proof. We first prove by induction on $|\mathcal{C}|$ that the algorithm always returns the correct answer. As a base case, when $|\mathcal{C}| = 0$, \mathcal{C} is trivially galled-compatible and the algorithm correctly returns true.

So suppose for the inductive step that $|\mathcal{C}| > 0$. If \mathcal{C} has a maximal compatible character C, then by Lemma 9, \mathcal{C} is galled-compatible if and only if \mathcal{C}_1 and \mathcal{C}_2 are galled-compatible. Since, by induction, the algorithm returns the correct answer on both \mathcal{C}_1 and \mathcal{C}_2 , returning $getGalledTree(\mathcal{C}_1) \wedge getGalledTree(\mathcal{C}_2)$ is correct.

So suppose that \mathcal{C} does not have a maximal compatible character. Note that by Lemma 15, the algorithm will find maximal incompatible A and B. First assume that \mathcal{C} is galled-compatible, in which case we need to argue that the

algorithm returns true. Let T^* be a tree that is galled-completable for \mathcal{C} . By Lemma 10, T^* contains either the clades $\{A_1, A_2\} = \{A \setminus B, A \cap B\}$ or $\{B_1, B_2\} = \{B \setminus A, B \cap A\}$. Assume first that T^* contains A_1, A_2 . Then all the conditions of Lemma 14 hold for A_1, A_2 . Thus, all the conditions verified by tryPartition on input $\{A_1, A_2\}$ will succeed (including the calls to $getGalledTree(\mathcal{C}_v)$, which are assumed to return true by induction). It follows that tryPartition will return "yes" and that getGalledTree will correctly return true.

Next, assume instead that T^* contains the clades $\{B_1, B_2\}$. If Algorithm 2 gets to call $tryPartition(\mathcal{C}, \{B_1, B_2\})$, then as in the previous case, we know that all the tests made by tryPartition will pass and that it will return "yes". However, we will not reach that point if the prior call $tryPartition(\mathcal{C}, \{A_1, A_2\})$ has returned "yes" or "no". If that previous call returned "yes", then getGalledTree will return true, which is actually the correct answer. A problem occurs if this previous call returned "no" on input $\{A_1, A_2\}$. By inspecting tryPartition, we see that this only occurs when there is a \mathcal{C}_v on which $getGalledTree(\mathcal{C}_v)$ returns false. By induction, this means that \mathcal{C}_v is not galled-compatible, implying in turn that \mathcal{C} is not galled-compatible, a contradiction. Thus, we may assume that tryPartition on input $\{A_1, A_2\}$ either returns "yes" (in which case we correctly return true), or "invalid partition", in which case we correctly return true by then $trying \{B_1, B_2\}$.

In the converse direction, suppose that C is not galled-compatible. Then one of the four conditions of Lemma 14 must fail on both $\{A_1, A_2\}$ and $\{B_1, B_2\}$. This means that on either inputs, tryPartition will either return "no" or "invalid partition", which leads getGalledTree to correctly returning false.

Now let us argue the complexity. Let us first analyze the recursive search tree R created by the algorithm, where each node of R corresponds to a call to getGalledTree. We show by induction on the height of R that R contains at most $3 \cdot \max(1, |\mathcal{C}|)$ nodes. As a base case, when R has height 0, it is a terminal case with $1 \leq 3$ node, in which case our claim holds (even if \mathcal{C} is empty). So assume that R has higher height. Thus \mathcal{C} is non-empty. If \mathcal{C} has a maximal compatible character C, then we make recursive calls on disjoint strict subsets $\mathcal{C}_1, \mathcal{C}_2$ of \mathcal{C} , none of which contains C. If $\mathcal{C}_1, \mathcal{C}_2$ are non-empty, by induction the number of nodes of the recursion tree is at most $3|\mathcal{C}_1| + 3|\mathcal{C}_2| + 1$ (counting the root), which is at most $3(|\mathcal{C}|-1)+1\leq 3|\mathcal{C}|$ since $|\mathcal{C}_1|+|\mathcal{C}_2|<|\mathcal{C}|$. If, say, \mathcal{C}_1 is empty but not \mathcal{C}_2 (or vice-versa), the number of nodes in the recursion tree is at most $1+3|\mathcal{C}_2|+1<1+3(|\mathcal{C}_1|-1)+1\leq 3|\mathcal{C}_1|$. If both $\mathcal{C}_1,\mathcal{C}_2$ are empty, the recursion tree has 3 nodes, which is at most $3|\mathcal{C}|$.

If no maximal compatible C exists, the algorithm makes recursive calls on C_v sets in tryPartition, either when it receives $\{A_1, A_2\}$ or $\{B_1, B_2\}$ (but not both). Suppose that recursive calls are made when $\{A_1, A_2\}$ is received. Again, we observe that we either return "yes" or "no", and then getGalledTree exits without attempting $\{B_1, B_2\}$. It thus suffices to count the recursive calls in one call of tryPartition, on disjoint subsets C_v of C (which are non-empty since this is checked by the algorithm). Note that these subsets do not contain A. Hence,

the number of nodes in R is at most

$$\sum_{v \in V(T)} 3|\mathcal{C}_v| + 1 \le 3(|\mathcal{C}| - 1) + 1 \le 3|\mathcal{C}|$$

since all the C_v 's are disjoint and none of them contains A from C. If instead some recursive calls are made when $\{B_1, B_2\}$ is the input to tryPartition, we can repeat the same analysis and reach the same conclusion. This proves our claim.

It thus only remains to analyze the time needed to handle one node of the recursion tree. Recall that n is the number of taxa. Testing compatibility of two characters requires computing set operations in time O(n). Finding a maximal compatible character, or a pair of incompatible maximal characters, can be achieved by testing compatibility between each pair of characters, taking a total time of $O(n|\mathcal{C}|^2)$. This also allows finding A_1, A_2, B_1, B_2 in the same complexity.

During one recursion, we run tryPartition at most once, say on A_1, A_2 . Computing \mathcal{X} can be done in time $O(n|\mathcal{C}|)$ by computing two intersections for each character against A_1, A_2 . Testing the chain property can be done in time $O(n|\mathcal{X}|) = O(n|\mathcal{C}|)$ by sorting the \mathcal{X} 's by size (using e.g. bucket sort) and verifying the inclusions. It is straightforward to construct a tree T in time $O(n|\mathcal{C}|^2)$ from the forced clades \mathcal{C}_F (or decide that it does not exist) by relating them by set inclusion and building the corresponding tree top-down from the maximal clades to the minimal ones. Checking the "same parent" condition and building the \mathcal{C}_v sets is easily seen to not take more than $O(n|\mathcal{C}|^2)$ time.

Overall, we spend time $O(n|\mathcal{C}|^2)$ in one call to getGalledTree and tryPartition. Since the recursion tree has $O(|\mathcal{C}|)$ nodes, the total time is $O(n|\mathcal{C}|^3)$.