

Position Fair Mechanisms Allocating Indivisible Goods

Ryoga Mahara¹, Ryuhei Mizutani¹, Taihei Oki², and Tomohiko Yokoyama¹

¹The University of Tokyo

{mahara, ryuhei_mizutani, tomohiko_yokoyama}@mist.i.u-tokyo.ac.jp

²Hokkaido University

oki@icredd.hokudai.ac.jp

Abstract

In the fair division problem for indivisible goods, mechanisms that output allocations satisfying fairness concepts, such as envy-freeness up to one good (EF1), have been extensively studied. These mechanisms usually require an arbitrary order of agents as input, which may cause some agents to feel unfair since the order affects the output allocations. In the context of the cake-cutting problem, Manabe and Okamoto [MO12] introduced *meta-envy-freeness* to capture such kind of fairness, which guarantees the absence of envy compared to different orders of agents.

In this paper, we introduce *position envy-freeness* and its relaxation, *position envy-freeness up to k goods* (PEF k), for mechanisms in the fair division problem for indivisible goods, analogous to the meta-envy-freeness. While the round-robin or the envy-cycle mechanism is not PEF1, we propose a PEF1 mechanism that always outputs an EF1 allocation. In addition, in the case of two agents, we prove that any mechanism that always returns a maximum Nash social welfare allocation is PEF1, and propose a modified adjusted winner mechanism satisfying PEF1. We further investigate the round-robin and the envy-cycle mechanisms to measure how far they are from position envy-freeness.

1 Introduction

Allocating resources fairly is an important task and has attracted increasing attention in social choice theory and economics. The classical fair division problem for divisible goods, also known as the cake-cutting problem, dates back to the 1940s [Ste48]. In recent years, its significance has started to be recognized in computer science [Wal20, ALMW22, AAB⁺23], and fair division methods are increasingly being implemented in real-world applications [GP15, IY23, HS24].

The fair division problem for indivisible goods is to allocate m indivisible goods M to n agents N . Every agent $a \in N$ has a utility function $u_a : 2^M \rightarrow \mathbb{R}_{\geq 0}$ that evaluates the utility of a given bundle (a subset of M) for a . In this paper, all utility functions are assumed to be additive. The most basic fairness concept in the fair division problem is the *envy-freeness* [Fol67]. An allocation is called *envy-free* if every agent has a utility for their own bundle at least as much as that for any other agent's bundle. Unfortunately, an envy-free allocation may not exist in the case of allocating indivisible goods. To avoid this limitation, a relaxation of envy-freeness, *envy-freeness up to one good* (EF1), has been extensively studied [Bud11]. An allocation is said to be *EF1* if, for any two agents, either one does not envy the other, or the envy can be eliminated by removing at most one good from the envied agent's bundle. For agents with monotone utility functions, an EF1 allocation always exists and can be found in polynomial time by the envy-cycle mechanism [LMMS04]. For agents with additive utility functions, an EF1 allocation can be computed in polynomial time by the round-robin mechanism [CKM⁺19]. Moreover, when $n = 2$, the discrete version of the

adjusted winner mechanism produces an EF1 allocation satisfying the *Pareto optimality* (PO), which is an efficiency criterion that guarantees that no allocation can improve an agent’s utility without diminishing the utility of at least one other agent [ACIW22]. See Section 2 for detailed problem settings and definitions.

This paper considers a fairness concept with regard to the *order* or *positions* of agents. To explain it, imagine that we are an organizer allocating indivisible goods to agents by using the round-robin mechanism. As explained above, this mechanism is fair in the sense that it produces an EF1 allocation (if the utility functions are additive as we have assumed). However, to apply the round-robin mechanism, we need to designate an order of the agents, which affects the output allocation (see Example 7). Therefore, although the algorithm always produces an EF1 allocation for any order of agents, some agents might compare their given bundles to those that would be allocated to them under a different order of agents, complaining that the order chosen by the organizer was “unfair”. Many other mechanisms, such as serial dictatorship and envy-cycle mechanisms, also depend on the order of agents.

In the cake-cutting problem, this kind of fairness was considered by Manabe and Okamoto [MO12] as *meta-envy-freeness*. A meta-envy-free mechanism outputs an allocation in which no agent desires to change their position in an arbitrary used order of the agents. In other words, meta-envy-freeness ensures that each agent’s utility does not decrease by any reordering of the agents.

In this paper, we introduce an analogous fairness concept, *meta-envy-freeness*, for the fair division problem for indivisible goods. We say that a mechanism is *position envy-free*¹ if for any input ordered set of agents, no agent prefers the bundle they would receive under a permutation of the agents to their allocated bundle under the current ordering.

Unfortunately, no mechanism can attain position envy-freeness (see Example 5) as in the case of envy-freeness. We thus propose a relaxed notion termed *position envy-freeness up to k goods* (PEF k). A mechanism is PEF k if for any ordered set of agents, no agent does not desire to change their position in the ordering when they lose the k best goods after changing their position. We further introduce the concept of the mechanism’s *degree of position envy* as the minimum k such that the mechanism satisfies PEF k .

As the round-robin and envy-cycle mechanisms produce EF1 allocations, one might expect that these mechanisms would satisfy PEF1. However, we will see that these mechanisms are indeed not PEF1. This result would pose the following natural question: *is it possible to design a mechanism that is PEF1 and always returns an EF1 allocation?*

1.1 Our Contributions

We answer the above question affirmatively. As a primary contribution, we present in Section 3 a PEF1 mechanism that always produces an EF1 allocation in polynomial time. Our approach employs a maximum-weight bipartite matching algorithm to determine a subset of goods allocated to agents in each round as well as careful consideration of tie-breaking rules. While the natural adaptation of a maximum-weight bipartite matching algorithm would lose the invariance under scaling each agent’s utility, which is a desired property to address so-called utility monsters [Noz74], we present an algorithm that is scale invariant.

We next prove that PEF1 is compatible with both EF1 and PO when $n = 2$ in Section 4. Specifically, we demonstrate that any mechanism that returns a maximum Nash social welfare allocation, which maximizes the Nash social welfare and is known to be EF1 and PO, also satisfies PEF1 when $n = 2$. Additionally, we propose a modified adjusted winner mechanism, which satisfies PEF1 and produces an EF1 and PO allocation in polynomial time when $n = 2$.

We then investigate the round-robin and envy-cycle mechanisms in Sections 5 and 6, respectively. We show that the round-robin mechanism does not satisfy PEF1 when n and m are both

¹We use the term “meta-envy-free” instead of “position envy-free” to clarify the meaning of “meta”.

sufficiently large. More strongly, we prove that the degree of position envy of the round-robin mechanism is at least $\lfloor \log_2 n \rfloor$ when the number of rounds satisfies $\lceil m/n \rceil \geq \lfloor \log_2 n \rfloor$. This implies that the round-robin mechanism is not PEF1 when $n \geq 4$ and $m \geq n + 1$. Conversely, we prove that the round-robin mechanism satisfies PEF1 when $n \in \{2, 3\}$. For the envy-cycle mechanism, we show that it is PEF1 if and only if $m - \lfloor \frac{m}{n} \rfloor \leq 1$ by considering the ordering in which unenvied agents are prioritized when ties occur.

1.2 Related Work

Mechanisms via weighted bipartite matchings. In the context of the fair division with subsidy, Brustle et al. [BDN⁺20] proposed a mechanism that returns an envy-freeable and EF1 allocation. Their mechanism is similar to ours in the sense that both rely on a maximum-weight bipartite matching algorithm. Our mechanism is distinguished by its scaling invariance and the method by which bundles selected in each round are determined independently of the order of agents.

Randomized mechanisms. Randomized mechanisms are allocation mechanisms that utilize randomness within their process and return a probabilistic allocation. When considering position fairness, randomized mechanisms offer one solution. For instance, mechanisms that treat all agents uniformly at random are considered fair in terms of probabilistic outcomes. Randomized mechanisms have been extensively studied in the literature. Notable examples include the random serial dictatorship [AS98], and the probabilistic serial mechanism [BM01]. Recent advancements have introduced the concept of best-of-both-worlds fairness in recourse allocation [FSV20, BEF22, AFSV23, FMNP23]. The best-of-both-worlds mechanism guarantees fairness in expectation (ex-ante) while simultaneously ensuring a certain level of fairness in the realized allocation (ex-post).

In this paper, we focus on evaluating potential unfairness in discrete deterministic mechanisms, particularly in scenarios such as tie-breaking.

Anonymity and equal-treatment-of-equals. The notion of anonymity can be traced back to the early works in social choice theory and mechanism design [Gib73, Sat75]. Anonymity is a fundamental principle that requires a mechanism to treat all agents equally, regardless of their identities. In other words, even if two agents have swapped each other's utilities, the outcome allocation of the mechanism should remain unchanged. In this paper, we distinguish between anonymity and position envy-freeness. Position envy-freeness guarantees that the utilities which agents get do not change while the allocation produced by the mechanism may vary.

The equal-treatment-of-equals is also a well-known fairness concept for mechanisms [Mou04]. This concept requires for a mechanism that agents with identical preferences should receive the same bundle of goods. The trade-offs between anonymity or equal-treatment-of-equals, and other desirable properties in resource allocation mechanisms have been extensively studied [SS74, Zho90, BM01, RSU05, BHS20].

2 Preliminaries

2.1 Basic Fair Division Model

We consider the fair division problem where m indivisible goods are allocated to n agents. Let N be the set of n agents and M be the set of m goods. We call a subset of M a *bundle*. Each agent $a \in N$ has a non-negative utility function $u_a : 2^M \rightarrow \mathbb{R}_{\geq 0}$. We assume that u_a is *additive*, that is, $u_a(S) = \sum_{g \in S} u_a(\{g\})$ holds for any bundle $S \subseteq M$. To simplicity, let $u_a(g) = u_a(\{g\})$ for each $g \in M$. A *profile* is a family $u = \{u_a\}_{a \in N}$ of the utility functions of all agents.

An *allocation* $A = \{A_a\}_{a \in N}$ is a partition of M into n bundles indexed by N , i.e., $M = \bigcup_{a \in N} A_a$ and $A_a \cap A_{a'} = \emptyset$ for any $a \neq a' \in N$. An allocation A *Pareto dominates* another allocation A' if $u_a(A_a) \geq u_a(A'_a)$ for all $a \in N$ and there exists an agent a' such that $u_{a'}(A_{a'}) > u_{a'}(A'_{a'})$. An allocation A is called *Pareto optimal (PO)* if there is no allocation that Pareto dominates A . Given an allocation A , we say that agent a *envies* agent a' if $u_a(A_a) < u_a(A_{a'})$. An allocation A is called *envy-free* if $u_a(A_a) \geq u_a(A_{a'})$ for all $a, a' \in N$, i.e., no agent envies any other agent. Budish [Bud11] introduced a more feasible variant of envy-freeness, termed as *envy-freeness up to one good (EF1)*, as follows.

Definition 1 (Envy-freeness up to one good (EF1)). An allocation A is called *envy-free up to one good (EF1)* if for every pair of agents $a, a' \in N$, $u_a(A_a) \geq u_a(A_{a'})$ holds, or there exists a good $g \in A_{a'}$ such that $u_a(A_a) \geq u_a(A_{a'} \setminus \{g\})$.

We define the notion of maximum Nash social welfare (MNW). Caragiannis et al. [CKM⁺19] show that MNW allocations achieve EF1 and PO.

Definition 2 (Maximum Nash social welfare (MNW) allocation). The *Nash social welfare (NW)* of an allocation A is defined as $NW(A) = \prod_{a \in N} u_a(A_a)$. We say that an allocation A is *maximum Nash social welfare (MNW)* if it maximizes the NW among all allocations.

2.2 Position Fairness

This paper considers allocation mechanisms that depend on an order of agents. For definition, we shall define an *agent ordering* π as a bijection from N to $[n] = \{1, 2, \dots, n\}$, where π arranges the agents in order $\pi^{-1}(1), \pi^{-1}(2), \dots, \pi^{-1}(n)$. We call $\pi(a)$ the *position* of $a \in N$ under π . Let Π denote the set of all agent orderings. For a profile $u = \{u_a\}_{a \in N}$ and an agent ordering $\pi \in \Pi$, an *ordered profile* u_π is defined as a list of the utilities in u arranged according to π , i.e., $u_\pi = (u_{\pi^{-1}(1)}, u_{\pi^{-1}(2)}, \dots, u_{\pi^{-1}(n)})$. A *mechanism* is a map \mathcal{M} from the set \mathcal{U} of all ordered profiles to the set \mathcal{A} of all *ordered allocations*. Here, an ordered allocation A means a partition of M into n bundles indexed from 1 to n , i.e., $A = (A_1, A_2, \dots, A_n)$. The output $A = \mathcal{M}(u_\pi)$ of a mechanism is interpreted as an allocation to the agents in such a way that each agent $a \in N$ receives a bundle $A_{\pi(a)}$.

Example 3 (Round-robin mechanism). Consider the round-robin mechanism. For an ordered profile u_π , this mechanism repeats the following steps while some items are remaining: each agent from $\pi^{-1}(1)$ to $\pi^{-1}(n)$, in this order, takes their most preferred good from the remaining goods. The round-robin mechanism computes possibly different allocations for different orders of agents even if the profile u is identical.

We now introduce a fairness concept of a mechanism concerning agent orderings, called *position envy-freeness*. Note that $\mathcal{M}(u_\pi)_{\pi(a)}$ denotes the bundle that agent a receives under a profile u , an agent ordering π , and a mechanism \mathcal{M} .

Definition 4 (Position envy-freeness). A mechanism \mathcal{M} satisfies *position envy-freeness* if for any profile u , agent orderings $\pi, \pi' \in \Pi$, and agent $a \in N$,

$$u_a(\mathcal{M}(u_\pi)_{\pi(a)}) \geq u_a(\mathcal{M}(u_{\pi'})_{\pi'(a)}). \quad (1)$$

Since the inequality (1) also holds even if π and π' are interchanged, (1) holds with equality for every $\pi, \pi' \in \Pi$ if \mathcal{M} satisfies position envy-freeness. Intuitively, position envy-freeness claims that each agent a prefers π to π' if agent a obtains a higher utility under π than that under π' . As mentioned in Introduction, this concept is already known as *meta-envy-freeness* [MO12] in the fair division for divisible goods.

Unfortunately, a position envy-free mechanism may not exist when goods are indivisible, as shown in the following.

Example 5. Consider an instance with two agents $N = \{a, b\}$, a single good $M = \{g\}$, and a profile $u = (u_a, u_b)$ with $u_a(g) = u_b(g) > 0$. We have $\Pi = \{\pi_1, \pi_2\}$ with $\pi_1(a) = 1, \pi_1(b) = 2$ and $\pi_2(a) = 2, \pi_2(b) = 1$. Let \mathcal{M} be a mechanism. Since u_a and u_b are the same utility function, the bundle allocated to an agent in position i is constant for $i = 1, 2$, meaning $\mathcal{M}(u_{\pi_1})_{\pi_1(a)} = \mathcal{M}(u_{\pi_2})_{\pi_1(b)}$ and $\mathcal{M}(u_{\pi_1})_{\pi_1(b)} = \mathcal{M}(u_{\pi_2})_{\pi_1(a)}$. We may assume without loss of generality that $\mathcal{M}(u_{\pi_1})_{\pi_1(a)} = \mathcal{M}(u_{\pi_2})_{\pi_1(b)} = \{g\}$. Then we have $u_a(\mathcal{M}(u_{\pi_1})_{\pi_1(a)}) = u_a(g) > u_a(\emptyset) = u_a(\mathcal{M}(u_{\pi_2})_a)$. This implies that no position envy-free mechanism exists.

Following the spirit of EF1, we introduce a relaxation of the position envy-freeness, called *position envy-freeness up to k goods* (PEF k), defined as follows.

Definition 6 (Position envy-freeness up to k goods). A mechanism \mathcal{M} satisfies *position envy-freeness up to k goods* (PEF k) if for any profile $u \in \mathcal{U}$, agent orderings $\pi, \pi' \in \Pi$, and agent $a \in N$, there exists $S \subseteq \mathcal{M}(u_{\pi'})_{\pi'(a)}$ with $|S| \leq k$ such that

$$u_a(\mathcal{M}(u_{\pi})_{\pi(a)}) \geq u_a(\mathcal{M}(u_{\pi'})_{\pi'(a)} \setminus S).$$

This framework allows a marginal decrease in an agent's utility, limited to some units, when they are shifted from their current position. Consequently, regardless of their position, each agent is guaranteed a utility that is not substantially inferior compared to the utility that she gets in the most favorable position.

Note that this definition is invariant under scaling or normalization of the utilities. We further define the *degree of position envy* of a mechanism as the minimum number of k such that the mechanism satisfies PEF k .

A natural question is then whether well-known mechanisms such as the round-robin and envy-cycle mechanisms satisfy PEF k with a small constant k . Unfortunately, the degrees of position envy of these mechanisms can increase as n and m increase (for details, see Theorems 14 and 19). Furthermore, even when $n = 4$, the round-robin mechanism is not PEF1, illustrated in the following example.

Example 7. Consider an instance with four agents, five goods, and the profile u given by the following table, where c_1, c_2 , and c_3 are positive constants with $c_1 > c_2 > c_3 > 0$.

	g_1	g_2	g_3	g_4	g_5
a_1	c_1	0	0	c_3	c_2
a_2	0	c_1	0	0	c_2
a_3	c_1	0	c_2	0	0
a_4	0	c_1	c_3	c_2	0

We compare two agent orderings $\pi_1, \pi_2 \in \Pi$ such that $\pi_1(a_i) = i$ and $\pi_2(a_i) = 5 - i$ for each $i = 1, 2, \dots, 4$. By the round-robin mechanism under π_1 , agent a_1 obtains the bundle $\mathcal{M}(u_{\pi_1})_{\pi_1(a_1)} = \{g_1, g_5\}$, while agent a_1 gets $\mathcal{M}(u_{\pi_2})_{\pi_2(a_1)} = \{g_4\}$ by that under π_2 . Since $c_1 > c_2 > c_3$, for any single good g in $\mathcal{M}(u_{\pi_1})_{\pi_1(a_1)}$, we have $u_1(\mathcal{M}(u_{\pi_1})_{\pi_1(a_1)} \setminus \{g\}) > u_1(\mathcal{M}(u_{\pi_2})_{\pi_2(a_1)})$.

Finally, we define the scale invariance of mechanisms. For a profile $u = (u_a)_{a \in N} \in \mathcal{U}$ and a tuple of positive reals $(\alpha_a)_{a \in N} \in \mathbb{R}_{>0}^n$ indexed by agents N , let αu denote the profile given by $(\alpha u)_a(S) = \alpha_a u_a(S)$ for $a \in N$ and $S \subseteq M$. It is clear that if u is additive, so is αu . We say that a mechanism \mathcal{M} is *scale invariant* if $\mathcal{M}(u, \pi) = \mathcal{M}(\alpha u, \pi)$ holds for any $\alpha \in \mathbb{R}_{>0}^n$, $u \in \mathcal{U}$, and $\pi \in \Pi$.

3 PEF1 + EF1

This section shows the existence of a PEF1 mechanism that produces an EF1 allocation by proving the following:

Theorem 8. *Mechanism 1 is scale-invariant, PEF1, and always produces an EF1 allocation in polynomial time.*

Mechanism 1 is described in Section 3.1, and the proof of Theorem 8 will be given in Section 3.2.

3.1 Mechanism Description

Mechanism 1 PEF1 mechanism that produces an EF1 allocation

Input: N, M , profile u , and agent ordering π

Output: Allocation $\{A_a\}_{a \in N}$

- 1: Add dummy goods until m is divisible by n
 - 2: Set bundles $A_a \leftarrow \emptyset$ for all $a \in N$ and $I \leftarrow M$
 - 3: **for** $r = 1, 2, \dots, \lceil \frac{m}{n} \rceil$ **do**
 - 4: Construct the complete bipartite graph $G = (N \cup I, E)$
 - 5: Compute a maximum-weight matching μ^r with respect to w in G
 - 6: **for** $a \in N$ **do**
 - 7: Set $A_a \leftarrow A_a \cup \{\mu^r(a)\}$
 - 8: Set $I \leftarrow I \setminus \{\mu^r(a)\}$
 - 9: **return** $\{A_a\}_{a \in N}$
-

We explain Mechanism 1. First, we fix indices of goods as $M = \{g_1, g_2, \dots, g_m\}$. Second, if the number of goods is not divisible by n , we add dummy goods that are valued at 0 by all agents until the total number of goods becomes divisible by n . We set an initial allocation as $A_a = \emptyset$ for all $a \in N$. We refer the **for** loop of lines 3-8 in Mechanism 1 as *round*. For each round r , let I denote the set of remaining goods and we construct the complete bipartite graph $G = (N \cup I, E)$ with two vertex sets N and I , where $E = \{\{a, g\} \mid a \in N, g \in I\}$. A subset $\mu \subseteq E$ is called a *matching* if each vertex appears in at most one edge of the subset. For a weight function $w : E \rightarrow \mathbb{R}_{\geq 0}$ and an edge $e = \{a, g\} \in E$, we use the notation $w(a, g) = w(e)$.

We define two types of weights, denoted as w_1 and w_2 . Let k_a denote the number of distinct utilities for agent a . For each $a \in N$ and each $g \in I$, define $w_1(a, g) = 2^{k_a - i}$ if a has the i -th highest utility to a good g for $i \in [k_a]$. If multiple goods have the same utility, they are assigned the same power of 2. Secondly, we define $w_2(a, g_j) = 2^{m-j}$ for each edge $\{a, g_j\} \in E$. For each edge $e \in E$, define a weight function w as $w(e) = nm2^m \cdot w_1(e) + w_2(e)$. We can find a maximum weight matching with respect to w in polynomial time (see Section 9 in [LP09]). Note that a maximum weight matching with respect to w is a matching that has the highest weight with respect to w_2 among maximum weight matchings with respect to w_1 .

In each round r , we compute a maximum-weight matching μ_π^r with respect to w in G . For an agent $a \in N$, let $\mu_\pi^r(a)$ denote the good matched to agent a under μ_π^r . We allocate goods to agents according to μ_π^r as each agent a obtains good $\mu_\pi^r(a)$ (lines 6-8).

3.2 Proof of Theorem 8

Proof of Theorem 8. Let $\mu_\pi^r(N)$ denote the set of goods adjacent to agents under μ_π^r . We claim that $\mu_\pi^r(N)$ is unique and does not depend on agent ordering π for $r = 1, 2, \dots, \lceil \frac{m}{n} \rceil$. When $r = 1$, if there are two maximum weight matchings μ and ν with respect to w , then we have $w_2(\mu) = w_2(\nu)$, where $w_2(\mu) = \sum_{e \in \mu} w(e)$ and $w_2(\nu) = \sum_{e \in \nu} w(e)$. Since w_2 represents the binary representation

with respect to indices of goods, $\mu_\pi^1(N) = \nu_\pi^1(N)$. Thus, $\mu_\pi^1(N)$ is uniquely determined and does not depend on π . By repeating this argument inductively on r , we complete the proof of the claim.

We proceed to prove that Mechanism 1 is PEF1. We compare any pair of two agent orderings $\pi_1, \pi_2 \in \Pi$. Since $\mu_\pi^r(N)$ does not depend on π , we have $\mu_{\pi_1}^r(N) = \mu_{\pi_2}^r(N)$ for all r . Let $g_a^r = \mu_{\pi_1}^r(a)$ and $h_a^r = \mu_{\pi_2}^r(a)$ for each agent $a \in N$ and each $r = 1, 2, \dots, \lceil \frac{m}{n} \rceil$. Choose $r \in \{1, 2, \dots, \lceil \frac{m}{n} \rceil - 1\}$. We claim that $u_a(g_a^{r+1}) \leq u_a(h_a^r)$. Since $g_a^{r+1} \notin \bigcup_{r'=1}^r \mu_{\pi_1}^{r'}(N)$, we obtain $g_a^{r+1} \notin \bigcup_{r'=1}^r \mu_{\pi_2}^{r'}(N)$. Then, we get $w_1(a, g_a^{r+1}) \leq w_1(a, h_a^r)$ since otherwise good g_a^{r+1} is included in the maximum weight matching $\mu_{\pi_2}^r$. By the definition of w_1 , this implies $u_a(g_a^{r+1}) \leq u_a(h_a^r)$. This leads that

$$u_a(\mathcal{M}(u_{\pi_2})_{\pi_2(a)}) = \sum_{r=1}^{\lceil \frac{m}{n} \rceil} u_a(h_a^r) \geq \sum_{r=1}^{\lceil \frac{m}{n} \rceil - 1} u_a(h_a^r) \geq \sum_{r=2}^{\lceil \frac{m}{n} \rceil} u_a(g_a^r) = u_a(\mathcal{M}(u_{\pi_1})_{\pi_1(a)} \setminus \{g_a^1\})$$

for any two agent orderings $\pi_1, \pi_2 \in \Pi$ and for all $a \in N$. This implies that the mechanism is PEF1.

Next, we show that Mechanism 1 always produces an EF1 allocation. Fix any agent ordering π . Let $g_a^r = \mu_\pi^r(a)$ for each $r = 1, 2, \dots, \lceil \frac{m}{n} \rceil$ and $a \in N$. Since we choose a maximum weight matching with respect to w_1 , we have $u_a(g_a^{r+1}) \leq u_a(g_a^r)$ for any two agents $a, a' \in N$ and $r = 1, 2, \dots, \lceil \frac{m}{n} \rceil - 1$. Then, for all $a, a' \in N$, we have

$$u_a(\mathcal{M}(u_\pi)_{\pi(a)}) = \sum_{r=1}^{\lceil \frac{m}{n} \rceil} u_a(g_a^r) \geq \sum_{r=2}^{\lceil \frac{m}{n} \rceil} u_a(g_a^r) \geq \sum_{r=2}^{\lceil \frac{m}{n} \rceil} u_a(g_{a'}^r) = u_a(\mathcal{M}(u_\pi)_{\pi(a')} \setminus \{g_{a'}^1\}).$$

We finally consider the time complexity and scaling invariance of Mechanism 1. In each round, we can find a maximum weight matching with respect to w in polynomial time, and the number of round is $\lceil \frac{m}{n} \rceil$. Hence, Mechanism 1 runs in polynomial time. Furthermore, the weight function w is unchanged if the profile is multiplied by a tuple of positive reals. Therefore, the mechanism is scaling invariant. \square

4 PEF1 + EF1 + PO for $n = 2$

In this section, we consider mechanisms for $n = 2$. We show that there exist PEF1 mechanisms which produce EF1 and PO allocations when $n = 2$.

4.1 Nash Social Welfare

Caragiannis et al. [CKM⁺19] showed that every MNW allocation satisfies EF1 and PO. We prove that any mechanism that always produces an MNW allocation is PEF1 when $n = 2$.

Theorem 9. *When $n = 2$, any mechanism that always returns an MNW allocation is PEF1.*

Proof. Let $N = \{a_1, a_2\}$ denote the set of two agents. Let $A = (A_{a_1}, A_{a_2})$ and $B = (B_{a_1}, B_{a_2})$ be two distinct MNW allocations where each agent $a \in \{a_1, a_2\}$ obtains the bundles A_a and B_a . Since two allocations are distinct, we have $A_{a_1} \neq B_{a_1}$. Without loss of generality, we can assume that $B_{a_1} \setminus A_{a_1} \neq \emptyset$. We will show that $u_{a_1}(A_{a_1}) \geq u_{a_1}(B_{a_1} \setminus g)$ holds for some $g \in B_{a_1}$. Suppose to the contrary that $u_{a_1}(A_{a_1}) < u_{a_1}(B_{a_1} \setminus \{g\})$ for every $g \in B_{a_1} \setminus A_{a_1}$. Take a good $h \in B_{a_1} \setminus A_{a_1}$. We have $h \in A_{a_2}$. Let $A' = (A'_{a_1}, A'_{a_2})$ and $B' = (B'_{a_1}, B'_{a_2})$ be allocations where $A'_{a_1} = A_{a_1} \cup \{h\}$, $A'_{a_2} = A_{a_2} \setminus \{h\}$, $B'_{a_1} = B_{a_1} \setminus \{h\}$ and $B'_{a_2} = B_{a_2} \cup \{h\}$. We will show that

$$\text{NW}(A') \cdot \text{NW}(B') > \text{NW}(A) \cdot \text{NW}(B),$$

which implies a contradiction. To show this, we observe that

$$\begin{aligned}
\frac{\text{NW}(A')}{\text{NW}(A)} \cdot \frac{\text{NW}(B')}{\text{NW}(B)} &= \frac{u_1(A'_1)}{u_1(A_1)} \cdot \frac{u_2(A'_2)}{u_2(A_2)} \cdot \frac{u_1(B'_1)}{u_1(B_1)} \cdot \frac{u_2(B'_2)}{u_2(B_2)} \\
&= \left(1 + \frac{u_1(h)}{u_1(A_1)}\right) \cdot \left(1 - \frac{u_2(h)}{u_2(A_2)}\right) \cdot \left(1 - \frac{u_1(h)}{u_1(B_1)}\right) \cdot \left(1 + \frac{u_2(h)}{u_2(B_2)}\right) \\
&= \left(1 + \frac{u_{a_1}(h)}{u_{a_1}(A_{a_1})} - \frac{u_{a_1}(h)}{u_{a_1}(B_1)} - \frac{u_{a_1}(h)^2}{u_{a_1}(A_{a_1})u_{a_1}(B_{a_1})}\right) \\
&\quad \cdot \left(1 - \frac{u_{a_2}(h)}{u_{a_2}(A_{a_2})} + \frac{u_{a_2}(h)}{u_{a_2}(B_{a_2})} - \frac{u_{a_2}(h)^2}{u_{a_2}(A_{a_2})u_{a_2}(B_{a_2})}\right).
\end{aligned}$$

Since $u_{a_1}(A_{a_1}) < u_{a_1}(B_{a_1} \setminus \{h\})$ by the assumption, we have

$$1 + \frac{u_{a_1}(h)}{u_{a_1}(A_{a_1})} - \frac{u_{a_1}(h)}{u_{a_1}(B_{a_1})} - \frac{u_{a_1}(h)^2}{u_{a_1}(A_{a_1})u_{a_1}(B_{a_1})} = 1 + \frac{u_{a_1}(h)(u_{a_1}(B_{a_1}) - u_{a_1}(A_{a_1}) - u_{a_1}(h))}{u_{a_1}(A_{a_1})u_{a_1}(B_{a_1})} > 1.$$

Since A is an MNW allocation, we have $\text{NW}(A) \geq \text{NW}(B')$, which implies

$$\text{NW}(A) = u_{a_1}(A_{a_1})u_{a_2}(A_{a_2}) \geq u_{a_1}(B'_{a_1})u_{a_2}(B'_{a_2}) = \text{NW}(B').$$

We also have $u_{a_1}(A_{a_1}) < u_{a_1}(B_{a_1} \setminus \{h\}) = u_{a_1}(B'_{a_1})$. Hence, $u_{a_2}(A_{a_2}) \geq u_{a_2}(B'_{a_2}) = u_{a_2}(B_{a_2}) + u_{a_2}(h)$. Therefore, we obtain

$$1 - \frac{u_{a_2}(h)}{u_{a_2}(A_{a_2})} + \frac{u_{a_2}(h)}{u_{a_2}(B_{a_2})} - \frac{u_{a_2}(h)^2}{u_{a_2}(A_{a_2})u_{a_2}(B_{a_2})} = 1 + \frac{u_{a_2}(h)(u_{a_2}(A_{a_2}) - u_{a_2}(B_{a_2}) - u_{a_2}(h))}{u_{a_2}(A_{a_2})u_{a_2}(B_{a_2})} \geq 1,$$

which completes the proof. \square

4.2 Adjusted Winner Mechanism

Next, we investigate the discrete version of the adjusted winner mechanism, which produces an EF1 and PO allocation in polynomial time when $n = 2$ [ACIW22]. We call it the discrete adjusted winner mechanism.

Let $N = \{a_1, a_2\}$ denote the set of two agents. We first categorize M into four disjoint subsets: $M_{a_1} = \{g \in M \mid u_{a_1}(g) > 0 \wedge u_{a_2}(g) = 0\}$, $M_{a_2} = \{g \in M \mid u_{a_1}(g) = 0 \wedge u_{a_2}(g) > 0\}$, $M_3 = \{g \in M \mid u_{a_1}(g) > 0 \wedge u_{a_2}(g) > 0\}$ and $M_4 = \{g \in M \mid u_{a_1}(g) = 0 \wedge u_{a_2}(g) = 0\}$. We discard goods in M_4 as they are irrelevant to envy-freeness, position envy-freeness and Pareto optimality. Thus, we can represent M as $M = M_{a_1} \cup M_{a_2} \cup M_3$.

We describe the discrete adjusted winner mechanism. In this mechanism, an agent ordering represents which agent is prioritized. We establish a fixed order of the goods before the mechanism begins. At the first step of the mechanism, we allocate all goods in $M_{\pi^{-1}(1)} \cup M_3$ to agent $\pi^{-1}(1)$, and all goods in $M_{\pi^{-1}(2)}$ to agent $\pi^{-1}(2)$. Then, we transfer goods in M_3 from agent $\pi^{-1}(1)$ to agent $\pi^{-1}(2)$ in non-increasing order of the ratio $\frac{u_{\pi^{-1}(2)}(g)}{u_{\pi^{-1}(1)}(g)}$. Note that if some goods have the same ratio value, we break ties by ordering such goods in the increasing order of indices. At the moment when agent $\pi^{-1}(2)$ envies agent $\pi^{-1}(1)$ by at most one good, that is, when there exists a good $g \in A_{\pi^{-1}(1)}$ such that $u_{\pi^{-1}(2)}(A_{\pi^{-1}(2)}) \geq u_{\pi^{-1}(2)}(A_{\pi^{-1}(1)} \setminus \{g\})$, we stop transferring goods. If $M_3 = \emptyset$, then the mechanism returns allocation (M_{a_1}, M_{a_2}) .

Unfortunately, the degree of position envy of the discrete adjusted winner mechanism is at least $\lceil \frac{m}{2} \rceil - 1$, and thus the mechanism is not PEF1 when $m \geq 3$.

Proposition 10. *The degree of position envy of the discrete adjusted winner mechanism is at least $\lceil \frac{m}{2} \rceil - 1$.*

Proof. Let ε be a small constant such that $0 < \varepsilon < 1/m$. Let $N = \{a_1, a_2\}$ denote the set of agents and $M = \{g_1, g_2, \dots, g_m\}$ denote the set of goods. We define the profile $(u_a(g))_{a \in N, g \in M}$ as follows:

$$u_a(g) = \begin{cases} 1 & \text{if } a = a_1 \text{ and } g \in M, \\ 1 & \text{if } a = a_2 \text{ and } g = g_m, \\ \varepsilon & \text{if } a = a_2 \text{ and } g \in M \setminus \{g_m\}. \end{cases}$$

We compare two agent orderings $\pi_1, \pi_2 \in \Pi$ where $\pi_1(a_i) = i$ and $\pi_2(a_i) = 3 - i$ for each $i = 1, 2$. By the mechanism under π_1 , agent a_1 initially obtains all goods. Then, since the allocation $(A_{a_1}, A_{a_2}) = (\{g_1, g_2, \dots, g_{m-1}\}, \{g_m\})$ satisfies EF1, we get $\mathcal{M}(u_{\pi_1})_{\pi_1(a_1)} = \{g_1, g_2, \dots, g_{m-1}\}$. By the mechanism under π_2 , agent a_2 initially receives all the goods. Then, after almost half of all the goods, i.e., $g_1, g_2, \dots, g_{\lfloor m/2 \rfloor}$, have been passed, the mechanism terminates. Hence, $\mathcal{M}(u_{\pi_2})_{\pi_2(a_1)} = \{g_1, g_2, \dots, g_{\lfloor m/2 \rfloor}\}$ and agent a_1 has envy at least $m - 1 - \lfloor m/2 \rfloor = \lceil m/2 \rceil - 1$ goods. \square

4.2.1 Modification.

We propose a modified discrete adjusted winner mechanism, described as Mechanism 2, and show that the mechanism is PEF1 and produces an EF1 and PO allocation.

Mechanism 2 Modified adjusted winner mechanism

Input: $N = \{a_1, a_2\}$, M , profile u , and agent ordering π

Output: Allocation (A_{a_1}, A_{a_2})

- 1: Find an envy-free and equitable minimally fractional allocation $(P_{a_1}, P_{a_2}, g, \lambda_{a_1}, \lambda_{a_2})$
 - 2: **if** $\lambda_{\pi^{-1}(1)} \geq \lambda_{\pi^{-1}(2)}$ **then**
 - 3: **return** $(A_{\pi^{-1}(1)}, A_{\pi^{-1}(2)})$ where $A_{\pi^{-1}(1)} = M_{\pi^{-1}(1)} \cup P_{\pi^{-1}(1)} \cup \{g\}$ and $A_{\pi^{-1}(2)} = M_{\pi^{-1}(2)} \cup P_{\pi^{-1}(2)}$
 - 4: **else**
 - 5: **return** $(A_{\pi^{-1}(1)}, A_{\pi^{-1}(2)})$ where $A_{\pi^{-1}(1)} = M_{\pi^{-1}(1)} \cup P_{\pi^{-1}(1)}$ and $A_{\pi^{-1}(2)} = M_{\pi^{-1}(2)} \cup P_{\pi^{-1}(2)} \cup \{g\}$
-

In Mechanism 2, we fix indices of goods and an agent ordering $\pi : \{a_1, a_2\} \rightarrow \{1, 2\}$. If $M_3 = \emptyset$, then the mechanism returns allocation (M_{a_1}, M_{a_2}) . We assume that $M_3 \neq \emptyset$. In line 1, we employ the method introduced by Aziz et al. [ABFR⁺15] to find an equitable and envy-free minimally fractional allocation on M_3 . To elucidate this, we will explain the concept of minimally fractional allocation on M_3 . We first arrange the goods in M_3 in non-increasing order based on their utility ratios, denoted as g_1, g_2, \dots, g_ℓ , where $\ell = |M_3|$. This arrangement satisfies that

$$\frac{u_{\pi^{-1}(1)}(g_1)}{u_{\pi^{-1}(2)}(g_1)} \geq \dots \geq \frac{u_{\pi^{-1}(1)}(g_{k-1})}{u_{\pi^{-1}(2)}(g_{k-1})} \geq \frac{u_{\pi^{-1}(1)}(g_k)}{u_{\pi^{-1}(2)}(g_k)} \geq \frac{u_{\pi^{-1}(1)}(g_{k+1})}{u_{\pi^{-1}(2)}(g_{k+1})} \geq \dots \geq \frac{u_{\pi^{-1}(1)}(g_\ell)}{u_{\pi^{-1}(2)}(g_\ell)}. \quad (2)$$

For the arrangement, a *minimally fractional allocation* on M_3 is defined as a tuple of $(P_{a_1}, P_{a_2}, g_k, \lambda_{a_1}, \lambda_{a_2})$, where $k \in [\ell]$, $P_{a_1} = \{g_1, g_2, \dots, g_{k-1}\}$ is allocated to agent a_1 , $P_{a_2} = \{g_{k+1}, g_{k+2}, \dots, g_\ell\}$ allocated to agent a_2 , and g_k is a single good that may be split between the two agents. Moreover, $\lambda_{a_1}, \lambda_{a_2} \in \mathbb{R}_{\geq 0}$ are parameters with $\lambda_{a_1} + \lambda_{a_2} = 1$, which represents the fractions of good g_k allocated to agents a_1 and a_2 . We have $P_{a_1} \cap P_{a_2} \cap \{g_k\} = \emptyset$ and $P_{a_1} \cup P_{a_2} \cup \{g_k\} = M$. For this allocation, agent a_1 obtains the utility of $u_{a_1}(P_{a_1}) + \lambda_{a_1} \cdot u_{a_1}(g_k)$, and agent a_2 gets that of $u_{a_2}(P_{a_2}) + \lambda_{a_2} \cdot u_{a_2}(g_k)$. A minimally fractional allocation $(P_{a_1}, P_{a_2}, g_k, \lambda_{a_1}, \lambda_{a_2})$ is *envy-free* if

we have $u_a(P_a) + \lambda_a \cdot u_a(g_k) \geq u_a(P_{a'}) + \lambda_{a'} \cdot u_a(g_k)$ for all $a, a' \in \{a_1, a_2\}$, and is equitable if $\frac{u_{a_1}(P_{a_1}) + \lambda_{a_1} \cdot u_{a_1}(g_k)}{u_{a_1}(M)} = \frac{u_{a_2}(P_{a_2}) + \lambda_{a_2} \cdot u_{a_2}(g_k)}{u_{a_2}(M)}$.

In line 1, we can find an envy-free and equitable minimally fractional allocation in polynomial time [ABFR⁺15]. Hence, Mechanism 2 runs in polynomial time.

Lemma 11. *Let $M_3 = \{g_1, g_2, \dots, g_\ell\}$ be sorted as in (2). Given a profile u , there exist unique $g_k \in M_3$, $w_{\pi^{-1}(1)} \in \mathbb{R}_{\geq 0}$, and $\lambda_{\pi^{-1}(2)} \in \mathbb{R}_{\geq 0}$, where $\lambda_{\pi^{-1}(1)} + \lambda_{\pi^{-1}(2)} = 1$, satisfying the following conditions, and we can find them in polynomial time:*

1. *the minimally fractional allocation $(P_{a_1}, P_{a_2}, g_k, \lambda_{a_1}, \lambda_{a_2})$ on M_3 is equitable where $P_{\pi^{-1}(1)} = \{g_1, g_2, \dots, g_{k-1}\}$ and $P_{\pi^{-1}(2)} = \{g_{k+1}, g_{k+2}, \dots, g_\ell\}$, and*
2. *the minimally fractional allocation $(M_{a_1} \cup P_{a_1}, M_{a_2} \cup P_{a_2}, g_k, \lambda_{a_1}, \lambda_{a_2})$ on M is envy-free, i.e., for every pair of agents $a, a' \in \{a_1, a_2\}$, we have*

$$u_a(M_a \cup P_a) + \lambda_a \cdot u_a(g_k) \geq u_a(M_{a'} \cup P_{a'}) + \lambda_{a'} \cdot u_a(g_k). \quad (3)$$

Proof. Aziz et al. [ABFR⁺15] show that we can find a boundary line which leads an equitable and envy-free minimally fractional allocation on M_3 by the following steps.

1. Give all goods in M_3 to agent $\pi^{-1}(1)$.
2. Order goods in non-increasing order of the valuation ratios such that $\frac{u_{\pi^{-1}(1)}(g_1)}{u_{\pi^{-1}(2)}(g_1)} \geq \frac{u_{\pi^{-1}(1)}(g_2)}{u_{\pi^{-1}(2)}(g_2)} \geq \dots \geq \frac{u_{\pi^{-1}(1)}(g_\ell)}{u_{\pi^{-1}(2)}(g_\ell)}$.
3. From right to left, continuously transfer goods fractionally until we get an equitable, envy-free, and minimally fractional allocation on M_3 .

Let g_k denote the split good and suppose that g_k is divided in the ratio λ_{a_1} to λ_{a_2} . Here, we achieve the equitable minimally fractional allocation with respect to M_3 . Moreover, envy-freeness of the minimally fractional allocation on M_3 implies

$$u_a(P_a) + \lambda_a \cdot u_a(g_k) \geq u_a(P_{a'}) + \lambda_{a'} \cdot u_a(g_k)$$

for all $a, a' \in N$. Since $u_a(M_a \cup P_a) \geq u_a(P_a)$ and $u_a(M_{a'} \cup P_{a'}) = u_a(P_{a'})$, we obtain

$$u_a(M_a \cup P_a) + \lambda_a \cdot u_a(g_k) \geq u_a(M_{a'} \cup P_{a'}) + \lambda_{a'} \cdot u_a(g_k).$$

From equitability, such the boundary line is uniquely determined. This implies the uniqueness of g_k , λ_{a_1} and λ_{a_2} . \square

A minimally fractional allocation is *Pareto optimal* if there does not exist an alternative minimally fractional allocation that makes one agent better off without making another agent worse off. Then, we have the following lemma.

Lemma 12. *Let $M_3 = \{g_1, g_2, \dots, g_\ell\}$ be sorted as in (2). Fix any $k \in [\ell]$. Let $P_{\pi^{-1}(1)} = \{g_1, g_2, \dots, g_{k-1}\}$ and $P_{\pi^{-1}(2)} = \{g_{k+1}, g_{k+2}, \dots, g_\ell\}$. The allocations $(M_{a_1} \cup P_{a_1} \cup \{g_k\}, M_{a_2} \cup P_{a_2})$ and $(M_{a_1} \cup P_{a_1}, M_{a_2} \cup P_{a_2} \cup \{g_k\})$ on M are both Pareto optimal.*

Proof. Aziz et al. [ABFR⁺15] show that the minimally fractional allocation on M_3 induced by a boundary line is not Pareto dominated by any other allocations on M_3 wherever the boundary line is. Thus, the allocation $(P_{a_1} \cup \{g_k\}, P_{a_2})$ and $(P_{a_1}, P_{a_2} \cup \{g_k\})$ on M_3 are not Pareto dominated by any other allocations on M_3 . We show that no allocation on M does not Pareto dominate the allocations $(M_{a_1} \cup P_{a_1} \cup \{g_k\}, M_{a_2} \cup P_{a_2})$ or $(M_{a_1} \cup P_{a_1}, M_{a_2} \cup P_{a_2} \cup \{g_k\})$. Indeed, if there exists

an allocation A' that Pareto dominates the allocation on M , then A' can only be constructed by transferring goods in M_3 from $(P_{a_1} \cup \{g_k\}, P_{a_2})$ or $(P_{a_1}, P_{a_2} \cup \{g_k\})$. This contradicts that $(P_{a_1} \cup \{g_k\}, P_{a_2})$ and $(P_{a_1}, P_{a_2} \cup \{g_k\})$ are Pareto optimal among all allocations on M_3 . \square

In lines 3 and 5 of the mechanism, we round the minimally fractional allocation according to λ_{a_1} and λ_{a_2} . In the case of $\lambda_{a_1} = \lambda_{a_2}$, we round it based on the agent ordering π . Now, we have the following theorem.

Theorem 13. *The modified adjusted winner mechanism (Mechanism 2) produces an EF1 and PO allocation in polynomial time. Moreover, the mechanism is PEF1.*

Proof. Firstly, from Lemma 12, the allocation produced by Mechanism 2 is Pareto optimal.

Secondly, we show that the outcome allocation is EF1. Let g_k be the divided good by the boundary line. Without loss of generality, we assume that $\pi^{-1}(1) = a_1$. When $\lambda_{a_1} \geq \lambda_{a_2}$, we have $A_{a_1} = M_{a_1} \cup P_{a_1} \cup \{g_k\}$ and $A_{a_2} = M_{a_2} \cup P_{a_2}$. Utilizing the inequality (3) in Lemma 11 and $\lambda_{a_1} \leq 1$, we prove that the allocation satisfies EF1 when $\lambda_{a_1} \geq \lambda_{a_2}$ as

$$\begin{aligned}
u_{a_1}(A_{a_1}) &= u_{a_1}(M_{a_1} \cup P_{a_1} \cup \{g_k\}) \\
&= u_{a_1}(M_{a_1} \cup P_{a_1}) + u_{a_1}(g_k) \\
&\geq u_{a_1}(M_{a_2} \cup P_{a_2}) + \lambda_{a_2} \cdot u_{a_1}(g_k) + (1 - \lambda_{a_1}) \cdot u_{a_1}(g_k) && \text{(Using the inequality (3))} \\
&\geq u_{a_1}(M_{a_2} \cup P_{a_2}) && \text{(Using } 1 \geq \lambda_{a_1}\text{)} \\
&= u_{a_1}(A_{a_2}),
\end{aligned}$$

and

$$\begin{aligned}
u_{a_2}(A_{a_2}) &= u_{a_2}(M_{a_2} \cup P_{a_2}) \\
&\geq u_{a_2}(M_{a_1} \cup P_{a_1}) + \lambda_{a_1} \cdot u_{a_2}(g_k) - \lambda_{a_2} \cdot u_{a_2}(g_k) && \text{(Using the inequality (3))} \\
&\geq u_{a_2}(M_{a_1} \cup P_{a_1}) \\
&= u_{a_2}(A_{a_1} \setminus \{g_k\}).
\end{aligned}$$

In the case where $\lambda_{a_1} < \lambda_{a_2}$, we have $A_{a_1} = M_{a_1} \cup P_{a_1}$ and $A_{a_2} = M_{a_2} \cup P_{a_2} \cup \{g_k\}$, and the allocation can be shown to be EF1 in a similar manner.

Finally, we prove that the mechanism is PEF1. Since the minimally fractional allocation satisfying equitability is uniquely determined regardless of agent orderings, each agent $a \in \{a_1, a_2\}$ obtains either $M_a \cup P_a$ or $M_a \cup P_a \cup \{g\}$, where g is a good that may be split in the minimally fractional allocation. Thus, Mechanism 2 is PEF1. \square

5 Round-robin Mechanism

In this section, we investigate the round-robin mechanism. The round-robin mechanism operates that, wherein each iteration, agents consecutively select their most preferred goods in accordance with a prescribed order. We refer each iteration as a *round*. We fix indices of goods, and during each round, each agent selects the good with the smallest index number among the goods with the highest utility.

As demonstrated in Example 7, there is an case where the round-robin mechanism does not satisfy PEF1. In this section, we clear the precise circumstances under which the round-robin mechanism satisfies PEF1.

5.1 Not PEF1 when $n \geq 4$

We first prove that, as n increases, the degree of position envy correspondingly escalates at a rate that is at least of the order of the logarithm of n .

Theorem 14. *The degree of position envy of the round-robin mechanism is at least $\lfloor \log_2 n \rfloor$ when $\lceil m/n \rceil \geq \lfloor \log_2 n \rfloor$.*

Proof. We note that, for two positive integers ℓ and n , $\lfloor \frac{\lfloor \frac{n}{2^\ell} \rfloor}{2} \rfloor = \lfloor \frac{n}{2^{\ell+1}} \rfloor$ holds. In the proof, we demonstrate an example to illustrate that the degree of position envy of the mechanism is at least $\lfloor \log_2 n \rfloor$. We compare two agent orderings $\pi_1, \pi_2 \in \Pi$ such that $\pi_1(a_i) = i$ and $\pi_2(a_i) = n+1-i$ for each $i = 1, 2, \dots, n$. Let g_a^r denote the good selected by agent a at the round r under π_1 . Let C be a positive constant such that $C > \lceil m/n \rceil - \lfloor \log_2 n \rfloor + 1 \geq 1$. We define the profile $(u_a(g))_{a \in N, g \in M}$ as follows:

- For $r = 1, 2, \dots, \lfloor \log_2 n \rfloor$, set $u_{a_1}(g_{a_1}^r) = C$.
- For $r = \lfloor \log_2 n \rfloor + 1, \lfloor \log_2 n \rfloor + 2, \dots, \lceil m/n \rceil$, set $u_{a_1}(g_{a_1}^r) = 1$.
- For $r = 2, 3, \dots, \lceil m/n \rceil$ and for $i = 2, 3, \dots, n$, set $u_{a_i}(g_{a_i}^r) = 1$.
- For each $r = 1, 2, \dots, \lfloor \log_2 n \rfloor$, let $j = \lfloor \frac{n}{2^{r-1}} \rfloor - i + 1$ for each $i = \lfloor \frac{n}{2^{r-1}} \rfloor, \lfloor \frac{n}{2^{r-1}} \rfloor - 1, \dots, \lfloor \frac{\lfloor \frac{n}{2^{r-1}} \rfloor}{2} \rfloor + 1 = \lfloor \frac{n}{2^r} \rfloor + 1$. Then set $u_{a_i}(g_{a_j}^r) = 1$.
- Otherwise, set $u_a(g) = 0$.

To aid the understanding, we present an example for the case where $n = 5$ and goods are abundantly available in Table 1.

	$g_{a_1}^1$	$g_{a_2}^1$	$g_{a_3}^1$	$g_{a_4}^1$	$g_{a_5}^1$	$g_{a_1}^2$	$g_{a_2}^2$	$g_{a_3}^2$	$g_{a_4}^2$	$g_{a_5}^2$	$g_{a_1}^3$	$g_{a_2}^3$	$g_{a_3}^3$	$g_{a_4}^3$	$g_{a_5}^3$
a_1	C					C					1				
a_2		1				1	1					1			
a_3			1					1					1		
a_4		1		1					1					1	
a_5	1				1					1					1

Table 1: An example which illustrates the profile when $n = 5$. Each blank space indicates the utility of 0. In this example, under agent ordering π_1 , agent a_1 obtains $\{g_{a_1}^1, g_{a_1}^2, g_{a_1}^3\}$. Under agent ordering π_2 , agent a_1 only gets good $g_{a_1}^3$.

Under agent ordering π_1 , agent a_1 obtains

$$\mathcal{M}(u_{\pi_1})_{\pi_1(a_1)} = \{g_{a_1}^1, g_{a_1}^2, \dots, g_{a_1}^{\lceil m/n \rceil}\}.$$

We will show that, for agent a_1 , the set of goods obtained by removing the top $\lfloor \log_2 n \rfloor - 1$ highest goods from $\mathcal{M}(u_{\pi_2})_{\pi_2(a_1)}$ still has a strictly greater utility than $\mathcal{M}(u_{\pi_1})_{\pi_1(a_1)}$.

We now consider the agent ordering π_2 . Under this agent ordering, for each $i = n, n-1, \dots, \lfloor \frac{n}{2} \rfloor + 1$, agent a_i selects good $g_{a_{n-i+1}}^1$ in the first round. Next, since good $g_{a_{\lfloor \frac{n}{2} \rfloor}}^1$ have already been selected, agent $a_{\lfloor \frac{n}{2} \rfloor}$ choose good $g_{a_1}^2$. Inductively, by the forth condition, for each $r = 1, 2, \dots, \lfloor \log_2 n \rfloor$, and for each $i = \lfloor \frac{n}{2^{r-1}} \rfloor, \lfloor \frac{n}{2^{r-1}} \rfloor - 1, \dots, \lfloor \frac{n}{2^r} \rfloor + 1$, agent a_i selects good g_j^r where $j = \lfloor \frac{n}{2^{r-1}} \rfloor - i + 1$. When $r = \lfloor \log_2 n \rfloor$, good $g_{a_1}^{\lfloor \log_2 n \rfloor}$ is selected by agent a_{j_1} where $j_1 = \lfloor \frac{n}{2^{\lfloor \log_2 n \rfloor - 1}} \rfloor - \lfloor \frac{n}{2^{\lfloor \log_2 n \rfloor}} \rfloor + 1 > 1$ since we have $\lfloor \frac{n}{2^{\lfloor \log_2 n \rfloor}} \rfloor = 1$. Therefore, agent a_1 chooses

good $g_{a_1}^{\lfloor \log_2 n \rfloor + 1}$ in the first round. From the above discussion, we obtain $g_{a_1}^{\lfloor \log_2 n \rfloor} \notin \mathcal{M}(u_{\pi_2})_{\pi_2(a_1)}$ and

$$\left\{ g_{a_1}^{\lfloor \log_2 n \rfloor + 1}, g_{a_1}^{\lfloor \log_2 n \rfloor + 2}, \dots, g_{a_1}^{\lceil m/n \rceil} \right\} \supseteq \mathcal{M}(u_{\pi_2})_{\pi_2(a_1)}.$$

From the first condition of the profile, we have

$$\begin{aligned} u_{a_1}(g_{a_1}^{\lfloor \log_2 n \rfloor}) &= C \\ &> \lceil m/n \rceil - \lfloor \log_2 n \rfloor + 1 \\ &> \lceil m/n \rceil - \lfloor \log_2 n \rfloor \\ &= \sum_{r=\lfloor \log_2 n \rfloor + 1}^{\lceil m/n \rceil} u_{a_1}(g_{a_1}^r) \\ &\geq u_{a_1}(\mathcal{M}(u_{\pi_2})_{\pi_2(a_1)}). \end{aligned}$$

Since $g_{a_1}^{\lfloor \log_2 n \rfloor} \in \mathcal{M}(u_{\pi_1})_{\pi_1(a_1)} \setminus \{g_{a_1}^1, g_{a_1}^2, \dots, g_{a_1}^{\lfloor \log_2 n \rfloor - 1}\}$, we get

$$u_1(\mathcal{M}(u_{\pi_1})_{\pi_1(a_1)} \setminus \{g_{a_1}^1, g_{a_1}^2, \dots, g_{a_1}^{\lfloor \log_2 n \rfloor - 1}\}) \geq u_{a_1}(g_{a_1}^{\lfloor \log_2 n \rfloor}),$$

and then

$$\begin{aligned} &\min_{S \subseteq \mathcal{M}(u_{\pi_1})_{\pi_1(a_1)} \text{ with } |S| = \lfloor \log_2 n \rfloor - 1} u_{a_1}(\mathcal{M}(u_{\pi_1})_{\pi_1(a_1)} \setminus S) \\ &= u_{a_1}(\mathcal{M}(u_{\pi_1})_{\pi_1(a_1)} \setminus \{g_{a_1}^1, g_{a_1}^2, \dots, g_{a_1}^{\lfloor \log_2 n \rfloor - 1}\}) \\ &\geq u_{a_1}(g_{a_1}^{\lfloor \log_2 n \rfloor}) \\ &> u_{a_1}(\mathcal{M}(u_{\pi_2})_{\pi_2(a_1)}). \end{aligned}$$

This implies that the round-robin mechanism does not satisfy $\text{PEF}(\lfloor \log_2 n \rfloor - 1)$, and the degree of position envy of the round-robin mechanism is at least $\lfloor \log_2 n \rfloor$. \square

The result in Theorem 14 implies the following corollary.

Corollary 15. *The round-robin mechanism is not PEF1 when $n \geq 4$ and $m \geq n + 1$.*

When $m < n + 1$, for any agent orderings, the round-robin mechanism outputs an allocation where each agent receives at most one good. Thus, the round-robin mechanism is PEF1 when $m < n + 1$.

5.2 PEF1 when $n \in \{2, 3\}$

Next, we present that the round-robin mechanism is PEF1 when the number of agents is two or three. To this end, we show that the set of goods chosen until a certain round is almost the same even if the order of agents is changed.

Theorem 16. *The round-robin mechanism is PEF1 when $n = 2$ or 3 .*

To prove Theorem 16, we compare the round-robin mechanism under two agent orderings π_1 and π_2 for $n = 2, 3$. Let $N = \{a_1, a_2, \dots, a_n\}$ be the set of n agents. Let g_a^k (resp. h_a^k) denote the good which agent a selects in the round r of the round-robin mechanism under π_1 (resp. π_2). Let $A_a = \{g_a^1, g_a^2, \dots, g_a^{\lceil m/n \rceil}\}$ and $B_a = \{h_a^1, h_a^2, \dots, h_a^{\lceil m/n \rceil}\}$. Moreover, for each agent $a \in N$ and for each round $r = 1, 2, \dots, \lceil m/n \rceil$, let $A_a^r = \{g_a^{r'} \mid r' = 1, 2, \dots, r\}$ and $B_a^r = \{h_a^{r'} \mid r' = 1, 2, \dots, r\}$. Let $A^r = \bigcup_{a \in N} A_a^r$ and $B^r = \bigcup_{a \in N} B_a^r$.

If we show that for every agent $a \in N$ and for every round $r = 1, 2, \dots, \lceil m/n \rceil - 1$,

$$u_a(h_a^r) \geq u_a(g_a^{r+1}) \quad \text{and} \quad u_a(g_a^r) \geq u_a(h_a^{r+1}), \quad (4)$$

then we have $u_a(B_a) = \sum_{r=1}^{\lceil m/n \rceil} u_a(h_a^r) \geq u_a(h_a^1) + \sum_{r=1}^{\lceil m/n \rceil - 1} u_a(g_a^{r+1}) \geq u_a(A_a \setminus \{g_a^1\})$ and $u_a(A_a) = \sum_{r=1}^{\lceil m/n \rceil} u_a(g_a^r) \geq u_a(g_a^1) + \sum_{r=1}^{\lceil m/n \rceil - 1} u_a(h_a^{r+1}) \geq u_a(B_a \setminus \{h_a^1\})$ for every $a \in N$. These complete the proof of Theorem 16. Thus, our goal is to show the two inequalities (4) for both $n = 2, 3$ and for all $\pi_1, \pi_2 \in \Pi$.

5.2.1 Proof for two agents.

We prove the two inequalities (4) for $n = 2$. To complete the proof, we first present Lemma 17, which guarantees that the set of goods chosen until a certain round in the mechanism under π_2 is almost included that under π_1 . We prove this lemma by induction on r .

Lemma 17. *Suppose that $n = 2$ and $N = \{a_1, a_2\}$. We assume that $\pi_1(a_i) = i$ for each $i = 1, 2$. For every $\pi_2 \in \Pi$ and for all $r = 1, 2, \dots, \lceil m/n \rceil - 1$, we have either $B^r = A^r$ or $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_1}^{r+1}\}$.*

Proof. If $\pi_1 = \pi_2$, then $A_a^r = B_a^r$ for all $a \in N = \{a_1, a_2\}$ and all $r = 1, 2, \dots, \lceil m/n \rceil - 1$, and the statement holds.

We consider the case where $\pi_1(a_i) = i$ and $\pi_2(a_i) = 3 - i$ for each $i = 1, 2$. We prove the statement by induction on r . The case where $r = 1$ can be checked easily. Indeed, if under π_2 , agent a_2 selects the good which is chosen by agent a_1 under π_1 , that is, we have $h_{a_2}^1 = g_{a_1}^1$, then $h_{a_1}^1 = g_{a_2}^1$ or $g_{a_1}^2$ holds. Otherwise, we have $h_{a_2}^1 = g_{a_2}^1$ and $h_{a_1}^1 = g_{a_1}^1$. Hence, $B^1 = \{h_{a_1}^1, h_{a_2}^1\} = \{g_{a_1}^1, g_{a_2}^1\} = A^1$ or $B^1 = \{h_{a_1}^1, h_{a_2}^1\} = \{g_{a_1}^1, g_{a_1}^2\} = A^1 \setminus \{g_{a_2}^1\} \cup \{g_{a_1}^2\}$, and the statement for $r = 1$ holds. By the induction hypothesis, we consider two cases represented in Figure 1.

(i) As the first case, suppose that it holds by induction that

$$B^{r-1} = A^{r-1}.$$

Then, in the round r of the mechanism under π_2 , agent a_2 selects $g_{a_1}^r$ or $g_{a_2}^r$ since they are the most desirable candidates for agent a_2 among the remaining goods. Thus, we get $h_{a_2}^r = g_{a_1}^r$ or $h_{a_2}^r = g_{a_2}^r$. (i) If $h_{a_2}^r = g_{a_1}^r$, then $g_{a_1}^r = g_{a_2}^r$ or $g_{a_1}^{r+1}$. The former case implies that $B^r = A^r$. The latter case leads that $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_1}^{r+1}\}$. (ii) If $h_{a_2}^r = g_{a_2}^r$, then $h_{a_1}^r = g_{a_1}^r$. This implies that $B^r = A^r$.

(ii) As the second case, suppose that

$$B^{r-1} = A^{r-1} \setminus \{g_{a_2}^{r-1}\} \cup \{g_{a_1}^r\}.$$

Then, in the round r of the mechanism under π_2 , the most desirable good remaining for agent a_2 is $g_{a_2}^{r-1}$. Thus, $h_{a_2}^r = g_{a_2}^{r-1}$ must hold. Then, we obtain $h_{a_1}^r = g_{a_2}^r$ or $g_{a_1}^{r+1}$. The former case implies that $B^r = A^r$. The latter case implies that $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_1}^{r+1}\}$.

These complete the proof of Lemma 17. \square

We now show the following lemma.

Lemma 18. *Suppose that $n = 2$. For every $a \in N$ and for every $r = 1, 2, \dots, \lceil m/n \rceil - 1$, we have*

$$u_a(h_a^r) \geq u_a(g_a^{r+1}) \quad \text{and} \quad u_a(g_a^r) \geq u_a(h_a^{r+1}).$$

Proof. We consider the case where $\pi_1(a_i) = i$ and $\pi_2(a_i) = 3 - i$ for each $i = 1, 2$. For a round r such that $B^r = A^r$ holds, we have $u_a(h_a^r) \geq u_a(g_a^{r+1})$ and $u_a(g_a^r) \geq u_a(h_a^{r+1})$ for all $a \in N$ since

	(b) Case (ii)																				
(a) Case (i)																					
<table border="1" style="border-collapse: collapse; width: 100%; text-align: center;"> <tr> <td style="padding: 5px;">a_1</td> <td style="padding: 5px; background-color: #e0e0e0;">A_1^{r-2}</td> <td style="padding: 5px;">$g_{a_1}^{r-1}$</td> <td style="padding: 5px;">$g_{a_1}^r$</td> <td style="padding: 5px;">$g_{a_1}^{r+1}$</td> </tr> <tr> <td style="padding: 5px;">a_2</td> <td style="padding: 5px; background-color: #e0e0e0;">A_2^{r-2}</td> <td style="padding: 5px;">$g_{a_2}^{r-1}$</td> <td style="padding: 5px;">$g_{a_2}^r$</td> <td style="padding: 5px;">$g_{a_2}^{r+1}$</td> </tr> </table>	a_1	A_1^{r-2}	$g_{a_1}^{r-1}$	$g_{a_1}^r$	$g_{a_1}^{r+1}$	a_2	A_2^{r-2}	$g_{a_2}^{r-1}$	$g_{a_2}^r$	$g_{a_2}^{r+1}$	<table border="1" style="border-collapse: collapse; width: 100%; text-align: center;"> <tr> <td style="padding: 5px;">a_1</td> <td style="padding: 5px; background-color: #e0e0e0;">A_1^{r-2}</td> <td style="padding: 5px;">$g_{a_1}^{r-1}$</td> <td style="padding: 5px;">$g_{a_1}^r$</td> <td style="padding: 5px;">$g_{a_1}^{r+1}$</td> </tr> <tr> <td style="padding: 5px;">a_2</td> <td style="padding: 5px; background-color: #e0e0e0;">A_2^{r-2}</td> <td style="padding: 5px;">$g_{a_2}^{r-1}$</td> <td style="padding: 5px;">$g_{a_2}^r$</td> <td style="padding: 5px;">$g_{a_2}^{r+1}$</td> </tr> </table>	a_1	A_1^{r-2}	$g_{a_1}^{r-1}$	$g_{a_1}^r$	$g_{a_1}^{r+1}$	a_2	A_2^{r-2}	$g_{a_2}^{r-1}$	$g_{a_2}^r$	$g_{a_2}^{r+1}$
a_1	A_1^{r-2}	$g_{a_1}^{r-1}$	$g_{a_1}^r$	$g_{a_1}^{r+1}$																	
a_2	A_2^{r-2}	$g_{a_2}^{r-1}$	$g_{a_2}^r$	$g_{a_2}^{r+1}$																	
a_1	A_1^{r-2}	$g_{a_1}^{r-1}$	$g_{a_1}^r$	$g_{a_1}^{r+1}$																	
a_2	A_2^{r-2}	$g_{a_2}^{r-1}$	$g_{a_2}^r$	$g_{a_2}^{r+1}$																	

Figure 1: The table which illustrate two cases. The gray shaded region represents the set B^{r-1} .

good h_a^{r+1} (resp. g_a^{r+1}) remains when agent a selects a new good in round r of the mechanism under π_1 (resp. π_2).

For a round r such that $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_1}^{r+1}\}$ holds, we have $u_{a_2}(h_{a_2}^r) = u_{a_2}(g_{a_2}^r) \geq u_{a_2}(g_{a_2}^{r+1})$ since good $g_{a_2}^r$ remains when agent a_2 chooses a new good in the round r under π_2 , and agent a_2 selects the good. Furthermore, agent a_1 picks $g_{a_1}^{r+1}$ in the round r under π_2 . Then, we obtain $h_{a_1}^r = g_{a_1}^{r+1}$ and $u_{a_1}(h_{a_1}^r) \geq u_{a_1}(g_{a_1}^{r+1})$. In the round $r+1$ under π_2 , agent a_2 can not choose any good better than $\{g_{a_2}^r\}$. Thus, $u_{a_2}(g_{a_2}^r) \geq u_{a_2}(h_{a_2}^{r+1})$. Similarly, in the round $r+1$ under π_2 , agent a_1 can not choose any good better than $\{g_{a_1}^r\}$, and then we get $u_{a_1}(g_{a_1}^r) \geq u_{a_1}(h_{a_1}^{r+1})$. \square

We defer the proof of Theorem 16 for three agents to Appendix A. We show it by a case analysis.

6 Envy-cycle Mechanism

In this section, we study the envy-cycle mechanism. To describe the mechanism, we first define the concept of *envy graph*. We say that $P = \{P_a\}_{a \in N}$ is a *partial allocation* if $\bigcup_{a \in N} P_a \subseteq M$ and $P_a \cap P_{a'} = \emptyset$ for all $a \neq a'$. For a partial allocation $P = \{P_a\}_{a \in N}$, *envy graph* is defined as a directed graph $G_P = (N, E)$, where the vertex set is the set N , and $(a, a') \in E$ if and only if $u_a(P_a) < u_a(P_{a'})$.

In the mechanism, we first order the goods arbitrarily. While there are unassigned goods, we give the next good to an unenvied agent. If there are several unenvied agents, then we break ties among them based on a given agent ordering. After allocating the good, if there is no unenvied agent, we can find a directed cycle in the envy graph and we remove it by cyclically exchanging of bundles.

We show that the presence of agents who lack interest in the goods can lead to an increase in position unfairness.

Theorem 19. *The degree of position envy of the envy-cycle mechanism is at least $m - \lfloor \frac{m}{n} \rfloor$ when $m \geq n$.*

Proof. Let $N = \{a_1, a_2, \dots, a_n\}$ be the set of n agents. We define the profile $(u_a(g))_{a \in N, g \in M}$ as follows:

$$u_{a_i}(g) = \begin{cases} 1 & \text{if } i = 1 \text{ and } g \in M, \\ 0 & \text{if } i \in [n] \setminus 1 \text{ and } g \in M. \end{cases}$$

By the mechanism under the agent ordering π_1 with $\pi_1(a_i) = i$ for each $i = 1, 2, \dots, n$, agent a_1 obtains all goods since at any point, no agent envies another. Under π_2 with $\pi_2(a_i) = n + 1 - i$ for $i = 1, 2, \dots, n$, agent a_1 can only receive a good once every n times. Thus, the number of goods agent a_1 receives is $\lfloor \frac{m}{n} \rfloor$. Hence, the degree of position envy is at least $m - \lfloor \frac{m}{n} \rfloor$ when $m \geq n$. \square

Theorem 19 implies that the envy-cycle mechanism does not satisfy PEF1 when $m - \lfloor \frac{m}{n} \rfloor \geq 2$, that is, when $n = 2$ and $m \geq 3$, or $n \geq 3$ and $m \geq 2$. Moreover, we have the following theorem.

Theorem 20. *The envy-cycle mechanism is PEF1 if and only if $m - \lfloor \frac{m}{n} \rfloor \leq 1$.*

Proof. From Theorem 19, if the envy-cycle mechanism is PEF1, then $m - \lfloor \frac{m}{n} \rfloor \leq 1$. We now demonstrate that the envy-cycle mechanism is PEF1 when $m - \lfloor \frac{m}{n} \rfloor = 0$ or 1. If $m \geq 3$, then $m - \lfloor \frac{m}{n} \rfloor$ is neither 0 nor 1. Thus, we only need to consider the cases where $m = 1$ or 2. When $m = 1$, the envy-cycle mechanism trivially satisfies PEF1 since all agents obtain at most one good.

When $n = 2$ and $m = 2$, we show that the envy-cycle mechanism is PEF1. Let $N = \{a_1, a_2\}$ be the set of two agents. Let $M = \{g_1, g_2\}$ be the set of two goods, and assume without loss of generality that g_1 is received before g_2 . First, consider the agent ordering $\pi_1(a_i) = i$ for $i = 1, 2$. In this case, good g_1 must be allocated to agent a_1 . If $u_{a_2}(g_1) \neq 0$, then good g_2 is allocated to agent a_2 . If $u_{a_1}(g_1) < u_{a_1}(g_2)$ and $u_{a_2}(g_1) > u_{a_2}(g_2)$, then the bundles of agents a_1 and a_2 are exchanged. If $u_{a_2}(g_1) = 0$, then agent a_1 obtains both g_1 and g_2 . Consequently, the allocation $\mathcal{M}(u_{\pi_1})$ is either $(\{g_1\}, \{g_2\})$ or $(\{g_2\}, \{g_1\})$ if $u_{a_2}(g_1) \neq 0$, and $(\{g_1, g_2\}, \emptyset)$ otherwise.

Next, consider the agent ordering $\pi_2(a_i) = 3 - i$ for $i = 1, 2$. Similarly, the allocation $\mathcal{M}(u_{\pi_2})$ is either $(\{g_1\}, \{g_2\})$ or $(\{g_2\}, \{g_1\})$ if $u_{a_1}(g_1) \neq 0$, and $(\emptyset, \{g_1, g_2\})$ otherwise. Therefore, if both $u_{a_1}(g_1) \neq 0$ and $u_{a_2}(g_1) \neq 0$, then each agent obtains at most one good. When $u_{a_1}(g_1) \neq 0$ and $u_{a_2}(g_1) = 0$, there exists a good g such that $u_{a_1}(\mathcal{M}(u_{\pi_1})_{\pi_1(a_1)} \setminus \{g\}) \leq u_{a_1}(\mathcal{M}(u_{\pi_2})_{\pi_2(a_1)})$, and there exists a good g' such that $u_{a_2}(\mathcal{M}(u_{\pi_2})_{\pi_2(a_2)} \setminus \{g'\}) \leq u_{a_2}(\mathcal{M}(u_{\pi_1})_{\pi_1(a_2)})$. When $u_{a_1}(g_1) = 0$ and $u_{a_2}(g_1) = 0$, we have $u_{a_1}(\mathcal{M}(u_{\pi_1})_{\pi_1(a_1)} \setminus \{g_2\}) = 0 \leq u_{a_1}(\mathcal{M}(u_{\pi_2})_{\pi_2(a_1)})$ and $u_{a_2}(\mathcal{M}(u_{\pi_2})_{\pi_2(a_2)} \setminus \{g_2\}) = 0 \leq u_{a_2}(\mathcal{M}(u_{\pi_1})_{\pi_1(a_2)})$. Hence, the envy-cycle mechanism is PEF1 when $n = 2$ and $m = 2$. \square

7 Discussions

This paper introduces the concepts of position envy-freeness and position envy-freeness up to k goods for mechanisms allocating indivisible goods. We demonstrate that PEF1 is compatible with EF1 for agents with additive utilities by presenting Mechanism 1. Moreover, for the case of $n = 2$, we prove that PEF1 is compatible with both EF1 and PO.

Our work opens up several directions for future research. Firstly, while we have shown that any mechanism producing an MNW allocation is PEF1 when $n = 2$, this result has not been generalized to cases where $n > 2$. We conjecture that for any number of agents, any mechanism returning an MNW allocation is PEF1. Furthermore, it remains unknown whether PEF1 is compatible with both EF1 and PO for any number of agents. These questions can present future researches. Secondly, exploring the strategic aspects of position fairness is also an important direction.

References

- [AAB⁺23] Georgios Amanatidis, Haris Aziz, Georgios Birmipas, Aris Filos-Ratsikas, Bo Li, Hervé Moulin, Alexandros A. Voudouris, and Xiaowei Wu. Fair division of indivisible goods: Recent progress and open questions. *Artificial Intelligence*, 322:103965, 2023.
- [ABFR⁺15] Haris Aziz, Simina Brânzei, Aris Filos-Ratsikas, Søren Kristoffer, and Stiiil Frederiksen. The adjusted winner procedure: characterizations and equilibria. In *Proceedings of the 24th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 454–460, 2015.
- [ACIW22] Haris Aziz, Ioannis Caragiannis, Ayumi Igarashi, and Toby Walsh. Fair allocation of indivisible goods and chores. *Autonomous Agents and Multi-Agent Systems*, 36(1):3:1–3:21, 2022.
- [AFSV23] Haris Aziz, Rupert Freeman, Nisarg Shah, and Rohit Vaish. Best of both worlds: Ex-ante and ex-post fairness in resource allocation. *Operations Research*, 72(4):1674–1688, 2023.

- [ALMW22] Haris Aziz, Bo Li, Hervé Moulin, and Xiaowei Wu. Algorithmic fair allocation of indivisible items: A survey and new questions. *ACM SIGecom Exchanges*, 20(1):24–40, 2022.
- [AS98] Atila Abdulkadiroğlu and Tayfun Sönmez. Random serial dictatorship and the core from random endowments in house allocation problems. *Econometrica*, 66(3):689–701, 1998.
- [BDN⁺20] Johannes Brustle, Jack Dippel, Vishnu V. Narayan, Mashbat Suzuki, and Adrian Vetta. One dollar each eliminates envy. In *Proceedings of the 21st ACM Conference on Economics and Computation (EC)*, page 23–39, 2020.
- [BEF22] Moshe Babaioff, Tomer Ezra, and Uriel Feige. Best-of-both-worlds fair-share allocations. In *Proceedings of the 18th International Workshop on Internet and Network Economics (WINE)*, pages 237–255, 2022.
- [BHS20] Xiaohui Bei, Guangda Huzhang, and Warut Suksompong. Truthful fair division without free disposal. *Social Choice and Welfare*, 55:523–545, 2020.
- [BM01] Anna Bogomolnaia and Hervé Moulin. A new solution to the random assignment problem. *Journal of Economic Theory*, 100(2):295–328, 2001.
- [Bud11] Eric Budish. The combinatorial assignment problem: approximate competitive equilibrium from equal incomes. *Journal of Political Economy*, 119(4):1061–1103, 2011.
- [CKM⁺19] Ioannis Caragiannis, David Kurokawa, Hervé Moulin, Ariel D. Procaccia, Nisarg Shah, and Junxing Wang. The unreasonable fairness of maximum Nash welfare. *ACM Transactions on Economics and Computation*, 7(3):1–12, 2019.
- [FMNP23] Michal Feldman, Simon Mauras, Vishnu V. Narayan, and Tomasz Ponitka. Breaking the envy cycle: Best-of-both-worlds guarantees for subadditive valuations. *arXiv preprint arXiv:2304.03706*, 2023.
- [Fol67] Duncan K. Foley. Resource allocation and the public sector. *Yale Economic Essays*, 7:45–98, 1967.
- [FSV20] Rupert Freeman, Nisarg Shah, and Rohit Vaish. Best of both worlds: Ex-ante and ex-post fairness in resource allocation. In *Proceedings of the 21st ACM Conference on Economics and Computation (EC)*, pages 21–22, 2020.
- [Gib73] Allan Gibbard. Manipulation of voting schemes: A general result. *Econometrica*, 41(4):587–601, 1973.
- [GP15] Jonathan Goldman and Ariel D. Procaccia. Spliddit: Unleashing fair division algorithms. *ACM SIGecom Exchanges*, 13(2):41–46, 2015.
- [HS24] Jiatong Han and Warut Suksompong. Fast & fair: A collaborative platform for fair division applications. In *Proceedings of the 38th AAAI Conference on Artificial Intelligence (AAAI)*, pages 23796–23798, 2024.
- [IY23] Ayumi Igarashi and Tomohiko Yokoyama. Kajibuntan: a house chore division app. In *Proceedings of the 37th AAAI Conference on Artificial Intelligence (AAAI)*, pages 16449–16451, 2023.
- [LMMS04] Richard J. Lipton, Evangelos Markakis, Elchanan Mossel, and Amin Saberi. On approximately fair allocations of indivisible goods. In *Proceedings of the 5th ACM Conference on Electronic Commerce (EC)*, pages 125–131, 2004.

- [LP09] László Lovász and Michael D. Plummer. *Matching Theory*. American Mathematical Society, 2009.
- [MO12] Yoshifumi Manabe and Tatsuaki Okamoto. Meta-envy-free cake-cutting and pie-cutting protocols. *Journal of Information Processing*, 20(3):686–693, 2012.
- [Mou04] Hervé Moulin. *Fair division and collective welfare*. MIT press, 2004.
- [Noz74] Robert Nozick. *Anarchy, State, and Utopia*. Basic Books, New York, 1974.
- [RSU05] Alvin E. Roth, Tayfun Sönmez, and M. Utku Ünver. Pairwise kidney exchange. *Journal of Economic Theory*, 125(2):151–188, 2005.
- [Sat75] Mark Allen Satterthwaite. Strategy-proofness and arrow’s conditions: Existence and correspondence theorems for voting procedures and social welfare functions. *Journal of Economic Theory*, 10(2):187–217, 1975.
- [SS74] Lloyd Shapley and Herbert Scarf. On cores and indivisibility. *Journal of Mathematical Economics*, 1(1):23–37, 1974.
- [Ste48] Hugo Steinhaus. The problem of fair division. *Econometrica*, 16:101–104, 1948.
- [Wal20] Toby Walsh. Fair division: The computer scientist’s perspective. In *Proceedings of the 29th International Joint Conference on Artificial Intelligence (IJCAI)*, pages 4966–4972, 2020.
- [Zho90] Lin Zhou. On a conjecture by Gale about one-sided matching problems. *Journal of Economic Theory*, 52(1):123–135, 1990.

A Omitted Proofs in Section 5.2

In this section, we prove Theorem 16 for $n = 3$. Similarly to the proof for $n = 2$, we will present that the set of goods chosen until a certain round under π_2 is almost included in that under π_1 . Specifically, we show that B^r is represented as one of six cases (a), (b), (c), (d), (e) and (f) in Figure 2. We fix π_1 as $\pi_1(a_i) = i$ for each $i = 1, 2, 3$, and assume that $\pi_2 \neq \pi_1$.

Lemma 21. *Suppose that $n = 3$. Let $\pi_2(N) = (\pi_2(a_1), \pi_2(a_2), \pi_2(a_3))$. We have the followings:*

1. *When $\pi_2(N) = (1, 3, 2), (3, 1, 2)$ or $(3, 2, 1)$, for all $r = 1, 2, \dots, \lceil m/n \rceil - 1$, we have $B^r = A^r$ (case (a)), $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (b)), or $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_2}^{r+1}\}$ (case (c)).*
2. *When $\pi_2(N) = (2, 3, 1)$, for all $r = 1, 2, \dots, \lceil m/n \rceil - 1$, we have $B^r = A^r$ (case (a)), $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (b)), or $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (d)).*
3. *When $\pi_2(N) = (2, 1, 3)$, for all $r = 1, 2, \dots, \lceil m/n \rceil - 1$, we have $B^r = A^r$ (case (a)), $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (b)), $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (d)), $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_2}^{r+1}\}$ (case (e)), or $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_3}^{r+1}\}$ (case (f)).*

Proof. Similarly to the proof of Lemma 17, we prove the each statement by induction on r . We check the statement when $r = 1$ through a case analysis.

1. In the case where $\pi_2(N) = (1, 3, 2)$, in the first round under π_2 , agent a_1 selects the good $g_{a_1}^1$. Then, we have $h_{a_1}^1 = g_{a_1}^1$. Consequently, agent a_3 chooses $g_{a_2}^1$ or $g_{a_3}^1$.
 - (i) When $h_{a_3}^1 = g_{a_2}^1$, agent a_2 chooses $g_{a_3}^1$ or $g_{a_1}^2$ or $g_{a_2}^2$. Therefore, the possible patterns for selecting B^1 are the cases (a), (b) or (c) illustrated in Figure 2 for $r = 2$.

(a)	(b)	(c)																																				
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 15%;">a_1</td><td style="width: 25%;">A_1^{r-1}</td><td style="width: 15%;">$g_{a_1}^r$</td><td style="width: 45%;">$g_{a_1}^{r+1}$</td></tr> <tr><td>a_2</td><td>A_2^{r-1}</td><td>$g_{a_2}^r$</td><td>$g_{a_2}^{r+1}$</td></tr> <tr><td>a_3</td><td>A_3^{r-1}</td><td>$g_{a_3}^r$</td><td>$g_{a_3}^{r+1}$</td></tr> </table>	a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$	a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$	a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 15%;">a_1</td><td style="width: 25%;">A_1^{r-1}</td><td style="width: 15%;">$g_{a_1}^r$</td><td style="width: 45%;">$g_{a_1}^{r+1}$</td></tr> <tr><td>a_2</td><td>A_2^{r-1}</td><td>$g_{a_2}^r$</td><td>$g_{a_2}^{r+1}$</td></tr> <tr><td>a_3</td><td>A_3^{r-1}</td><td>$g_{a_3}^r$</td><td>$g_{a_3}^{r+1}$</td></tr> </table>	a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$	a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$	a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 15%;">a_1</td><td style="width: 25%;">A_1^{r-1}</td><td style="width: 15%;">$g_{a_1}^r$</td><td style="width: 45%;">$g_{a_1}^{r+1}$</td></tr> <tr><td>a_2</td><td>A_2^{r-1}</td><td>$g_{a_2}^r$</td><td>$g_{a_2}^{r+1}$</td></tr> <tr><td>a_3</td><td>A_3^{r-1}</td><td>$g_{a_3}^r$</td><td>$g_{a_3}^{r+1}$</td></tr> </table>	a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$	a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$	a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$
a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$																																			
a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$																																			
a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$																																			
a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$																																			
a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$																																			
a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$																																			
a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$																																			
a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$																																			
a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$																																			
(d)	(e)	(f)																																				
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 15%;">a_1</td><td style="width: 25%;">A_1^{r-1}</td><td style="width: 15%;">$g_{a_1}^r$</td><td style="width: 45%;">$g_{a_1}^{r+1}$</td></tr> <tr><td>a_2</td><td>A_2^{r-1}</td><td>$g_{a_2}^r$</td><td>$g_{a_2}^{r+1}$</td></tr> <tr><td>a_3</td><td>A_3^{r-1}</td><td>$g_{a_3}^r$</td><td>$g_{a_3}^{r+1}$</td></tr> </table>	a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$	a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$	a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 15%;">a_1</td><td style="width: 25%;">A_1^{r-1}</td><td style="width: 15%;">$g_{a_1}^r$</td><td style="width: 45%;">$g_{a_1}^{r+1}$</td></tr> <tr><td>a_2</td><td>A_2^{r-1}</td><td>$g_{a_2}^r$</td><td>$g_{a_2}^{r+1}$</td></tr> <tr><td>a_3</td><td>A_3^{r-1}</td><td>$g_{a_3}^r$</td><td>$g_{a_3}^{r+1}$</td></tr> </table>	a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$	a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$	a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 15%;">a_1</td><td style="width: 25%;">A_1^{r-1}</td><td style="width: 15%;">$g_{a_1}^r$</td><td style="width: 45%;">$g_{a_1}^{r+1}$</td></tr> <tr><td>a_2</td><td>A_2^{r-1}</td><td>$g_{a_2}^r$</td><td>$g_{a_2}^{r+1}$</td></tr> <tr><td>a_3</td><td>A_3^{r-1}</td><td>$g_{a_3}^r$</td><td>$g_{a_3}^{r+1}$</td></tr> </table>	a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$	a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$	a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$
a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$																																			
a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$																																			
a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$																																			
a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$																																			
a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$																																			
a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$																																			
a_1	A_1^{r-1}	$g_{a_1}^r$	$g_{a_1}^{r+1}$																																			
a_2	A_2^{r-1}	$g_{a_2}^r$	$g_{a_2}^{r+1}$																																			
a_3	A_3^{r-1}	$g_{a_3}^r$	$g_{a_3}^{r+1}$																																			

Figure 2: The table which illustrate six cases. The gray shaded region represents the set B^r .

- (ii) When $h_{a_3}^1 = g_{a_3}^1$, agent a_2 selects good $g_{a_2}^1$, and $B^1 = A^1$ (case (a)).
2. In the case where $\pi_2(N) = (3, 1, 2)$, agent a_3 first selects $g_{a_1}^1$, $g_{a_2}^1$ or $g_{a_3}^1$.
 - (i) When $h_{a_3}^1 = g_{a_1}^1$, agent a_1 picks a good from $\{g_{a_2}^1, g_{a_3}^1, g_{a_1}^2\}$. If $h_{a_1}^1 = g_{a_2}^1$, then $h_{a_2}^1 = g_{a_3}^1$ (case (a)), $g_{a_1}^2$ (case (b)) or $g_{a_2}^2$ (case (c)). If $h_{a_1}^1 = g_{a_3}^1$, then $h_{a_2}^1 = g_{a_2}^1$ (case (a)). If $h_{a_1}^1 = g_{a_1}^2$, then $h_{a_2}^1 = g_{a_2}^1$ (case (b)).
 - (ii) When $h_{a_3}^1 = g_{a_2}^1$, agent a_1 obtains $g_{a_1}^1$, and agent a_2 picks $g_{a_3}^1$ (case (a)), $g_{a_1}^2$ (case (b)) or $g_{a_2}^2$ (case (c)).
 - (iii) When $h_{a_3}^1 = g_{a_3}^1$, agent a_1 obtains $g_{a_1}^1$, and agent a_2 obtains $g_{a_2}^1$ (case (a)).
 3. In the case where $\pi_2(N) = (3, 2, 1)$, agent a_3 selects $g_{a_1}^1$, $g_{a_2}^1$ or $g_{a_3}^1$.
 - (i) When $h_{a_3}^1 = g_{a_1}^1$, agent a_2 obtains $g_{a_2}^1$, and agent a_1 picks $g_{a_3}^1$ (case (a)) or $g_{a_1}^2$ (case (b)).
 - (ii) When $h_{a_3}^1 = g_{a_2}^1$, agent a_2 picks a good from $\{g_{a_1}^1, g_{a_3}^1, g_{a_1}^2, g_{a_2}^2\}$. If $h_{a_2}^1 = g_{a_1}^1$, then $h_{a_1}^1 = g_{a_3}^1$ (case (a)) or $g_{a_1}^2$ (case (b)). If $h_{a_2}^1 = g_{a_3}^1$, then $h_{a_1}^1 = g_{a_1}^1$ (case (a)). If $h_{a_2}^1 = g_{a_1}^2$, then $h_{a_1}^1 = g_{a_1}^1$ (case (b)). If $h_{a_2}^1 = g_{a_2}^2$, then $h_{a_1}^1 = g_{a_1}^1$ (case (c)).
 - (iii) When $h_{a_3}^1 = g_{a_3}^1$, agent a_2 obtains $g_{a_2}^1$, and agent a_1 obtains $g_{a_1}^1$ (case (a)).
 4. In the case where $\pi_2(N) = (2, 3, 1)$, agent a_2 selects $g_{a_1}^1$ or $g_{a_2}^1$.
 - (i) When $h_{a_2}^1 = g_{a_1}^1$, agent a_3 next chooses $g_{a_2}^1$ or $g_{a_3}^1$. If $h_{a_3}^1 = g_{a_2}^1$, then agent a_1 picks $g_{a_3}^1$ (case (a)) or $g_{a_1}^2$ (case (b)). If $h_{a_3}^1 = g_{a_3}^1$, then agent a_1 picks $g_{a_2}^1$ (case (a)) or $g_{a_1}^2$ (case (d)).
 - (ii) When $h_{a_2}^1 = g_{a_2}^1$, agent a_3 next chooses $g_{a_1}^1$ or $g_{a_3}^1$. If $h_{a_3}^1 = g_{a_1}^1$, then agent a_1 selects $g_{a_3}^1$ (case (a)) or $g_{a_1}^2$ (case (b)). If $h_{a_3}^1 = g_{a_3}^1$, then $h_{a_1}^1 = g_{a_1}^1$ (case (a)).
 5. In the case where $\pi_2(N) = (2, 1, 3)$, agent a_2 selects $g_{a_1}^1$ or $g_{a_2}^1$.
 - (i) When $h_{a_2}^1 = g_{a_1}^1$, agent a_1 next chooses $g_{a_2}^1$, $g_{a_3}^1$ or $g_{a_1}^2$. If agent a_1 picks $g_{a_2}^1$, then agent a_3 selects $g_{a_3}^1$ (cases (a)). If agent a_1 picks $g_{a_3}^1$, then agent a_3 selects $g_{a_2}^1$ (cases (b)) or $g_{a_1}^1$ (cases (d)). If agent a_1 selects $g_{a_1}^2$, then agent a_3 picks $g_{a_2}^1$, $g_{a_1}^2$, $g_{a_2}^2$ or $g_{a_3}^2$. Each case corresponds to each case (a), (d), (e) or (f).

(ii) When $h_{a_2}^1 = g_{a_2}^1$, agent a_1 picks $g_{a_1}^1$, and agent a_3 picks $g_{a_3}^1$ (case (a)).

From these discussion, the statement holds for $r = 1$.

Next, suppose the statement holds for $r - 1$ holds by induction. When $B^{r-1} = A^{r-1}$ (case (a)), the statement holds for r by the same argument as for the case of $r = 1$.

We consider the case where $B^{r-1} \neq A^{r-1}$ and show the statement for r by a case analysis.

1. The case of $\pi_2(N) = (1, 3, 2)$.

- (i) When $B^{r-1} = A^{r-1} \setminus \{g_{a_3}^{r-1}\} \cup \{g_{a_1}^r\}$ (case (b)), agent a_1 first selects $g_{a_3}^{r-1}$, $g_{a_2}^r$, $g_{a_3}^r$ or $g_{a_1}^{r+1}$. If $h_{a_1}^r = g_{a_3}^{r-1}$, then $(h_{a_3}^r, h_{a_2}^r) = (g_{a_2}^r, g_{a_3}^r)$, $(g_{a_2}^r, g_{a_1}^{r+1})$, $(g_{a_2}^r, g_{a_2}^{r+1})$, or $(g_{a_3}^r, g_{a_2}^r)$. If $h_{a_1}^r = g_{a_2}^r$, then $(h_{a_3}^r, h_{a_2}^r) = (g_{a_3}^{r-1}, g_{a_3}^r)$, $(g_{a_3}^{r-1}, g_{a_1}^{r+1})$, $(g_{a_3}^{r-1}, g_{a_2}^{r+1})$, $(g_{a_3}^r, g_{a_3}^{r-1})$, $(g_{a_3}^r, g_{a_1}^{r+1})$ or $(g_{a_3}^r, g_{a_2}^{r+1})$. If $h_{a_1}^r = g_{a_3}^r$, then $(h_{a_3}^r, h_{a_2}^r) = (g_{a_3}^{r-1}, g_{a_2}^r)$. If $h_{a_1}^r = g_{a_1}^{r+1}$, then $(h_{a_3}^r, h_{a_2}^r) = (g_{a_3}^{r-1}, g_{a_2}^r)$. Only cases (a), (b), (c) or (a) occur.
- (ii) When $B^{r-1} = A^{r-1} \setminus \{g_{a_3}^{r-1}\} \cup \{g_{a_2}^r\}$ (case (c)), agent a_1 first selects $g_{a_3}^{r-1}$ or $g_{a_1}^r$. If $h_{a_1}^r = g_{a_3}^{r-1}$, then $(h_{a_3}^r, h_{a_2}^r) = (g_{a_1}^r, g_{a_3}^r)$, $(g_{a_1}^r, g_{a_1}^{r+1})$, $(g_{a_1}^r, g_{a_2}^{r+1})$, $(g_{a_3}^r, g_{a_1}^r)$, $(g_{a_3}^r, g_{a_1}^{r+1})$, or $(g_{a_3}^r, g_{a_2}^{r+1})$. Thus, only cases (a), (b) or (c) happen. If $h_{a_1}^r = g_{a_1}^r$, $(h_{a_3}^r, h_{a_2}^r) = (g_{a_3}^{r-1}, g_{a_3}^r)$, $(g_{a_3}^{r-1}, g_{a_1}^{r+1})$, or $(g_{a_3}^{r-1}, g_{a_2}^{r+1})$. For both case, only cases (a), (b) or (c) happen.

2. The case of $\pi_2(N) = (3, 1, 2)$.

- (i) When $B^{r-1} = A^{r-1} \setminus \{g_{a_3}^{r-1}\} \cup \{g_{a_1}^r\}$ (case (b)), agent a_3 first selects $g_{a_3}^{r-1}$. Then, $(h_{a_1}^r, h_{a_2}^r) = (g_{a_2}^r, g_{a_3}^r)$, $(g_{a_2}^r, g_{a_1}^{r+1})$, $(g_{a_2}^r, g_{a_2}^{r+1})$, $(g_{a_3}^r, g_{a_2}^r)$, or $(g_{a_1}^{r+1}, g_{a_2}^r)$.
- (ii) When $B^{r-1} = A^{r-1} \setminus \{g_{a_3}^{r-1}\} \cup \{g_{a_2}^r\}$ (case (c)), agent a_3 first selects $g_{a_3}^{r-1}$. Then, $(h_{a_1}^r, h_{a_2}^r) = (g_{a_1}^r, g_{a_3}^r)$, $(g_{a_1}^r, g_{a_1}^{r+1})$, or $(g_{a_1}^r, g_{a_2}^{r+1})$. Only cases (a), (b), or (c) happen.

3. The case of $\pi_2(N) = (3, 2, 1)$.

- (i) When $B^{r-1} = A^{r-1} \setminus \{g_{a_3}^{r-1}\} \cup \{g_{a_1}^r\}$ (case (b)), agent a_3 first selects $g_{a_3}^{r-1}$. Then, $(h_{a_2}^r, h_{a_1}^r) = (g_{a_2}^r, g_{a_3}^r)$ or $(g_{a_2}^r, g_{a_1}^{r+1})$.
- (ii) When $B^{r-1} = A^{r-1} \setminus \{g_{a_3}^{r-1}\} \cup \{g_{a_2}^r\}$ (case (c)), agent a_3 first selects $g_{a_3}^{r-1}$. Then, $(h_{a_2}^r, h_{a_1}^r) = (g_{a_1}^r, g_{a_3}^r)$, $(g_{a_1}^r, g_{a_1}^{r+1})$, $(g_{a_3}^r, g_{a_1}^r)$, $(g_{a_1}^{r+1}, g_{a_1}^r)$, or $(g_{a_2}^{r+1}, g_{a_1}^r)$. Only cases (a), (b), or (c) happen.

4. The case of $\pi_2(N) = (2, 3, 1)$.

- (i) When $B^{r-1} = A^{r-1} \setminus \{g_{a_3}^{r-1}\} \cup \{g_{a_1}^r\}$ (case (b)), agent a_2 first selects $g_{a_3}^{r-1}$ or $g_{a_2}^r$. If $h_{a_2}^r = g_{a_3}^{r-1}$, then $(h_{a_3}^r, h_{a_1}^r) = (g_{a_2}^r, g_{a_3}^r)$ (case (a)), $(g_{a_2}^r, g_{a_1}^{r+1})$ (case (b)), $(g_{a_3}^r, g_{a_2}^r)$ (case (a)) or $(g_{a_3}^r, g_{a_1}^{r+1})$ (case (d)). If $h_{a_2}^r = g_{a_2}^r$, then $(h_{a_3}^r, h_{a_1}^r) = (g_{a_3}^{r-1}, g_{a_3}^r)$ or $(g_{a_3}^{r-1}, g_{a_1}^{r+1})$.
- (ii) When $B^{r-1} = A^{r-1} \setminus \{g_{a_3}^{r-1}\} \cup \{g_{a_2}^r\}$ (case (d)), agent a_2 first selects $g_{a_2}^{r-1}$. Then, $(h_{a_3}^r, h_{a_1}^r) = (g_{a_2}^r, g_{a_3}^r)$, $(g_{a_2}^r, g_{a_1}^{r+1})$, or $(g_{a_3}^r, g_{a_2}^r)$. Only cases (a), (b), or (d) happen.

5. The case of $\pi_2(N) = (2, 1, 3)$.

- (i) When $B^{r-1} = A^{r-1} \setminus \{g_{a_3}^{r-1}\} \cup \{g_{a_1}^r\}$ (case (b)), agent a_2 first selects $g_{a_3}^{r-1}$ or $g_{a_2}^r$. If $h_{a_2}^r = g_{a_3}^{r-1}$, then $(h_{a_3}^r, h_{a_1}^r) = (g_{a_2}^r, g_{a_3}^r)$, $(g_{a_2}^r, g_{a_1}^{r+1})$, $(g_{a_3}^r, g_{a_2}^r)$, or $(g_{a_3}^r, g_{a_1}^{r+1})$. If $h_{a_2}^r = g_{a_2}^r$, then $(h_{a_3}^r, h_{a_1}^r) = (g_{a_3}^{r-1}, g_{a_3}^r)$ or $(g_{a_3}^{r-1}, g_{a_1}^{r+1})$.
- (ii) When $B^{r-1} = A^{r-1} \setminus \{g_{a_3}^{r-1}\} \cup \{g_{a_2}^r\}$ (case (d)), agent a_2 first selects $g_{a_2}^{r-1}$. Then, $(h_{a_3}^r, h_{a_1}^r) = (g_{a_2}^r, g_{a_3}^r)$, $(g_{a_2}^r, g_{a_1}^{r+1})$, $(g_{a_3}^r, g_{a_2}^r)$, or $(g_{a_3}^r, g_{a_1}^{r+1})$.
- (iii) When $B^{r-1} = A^{r-1} \setminus \{g_{a_2}^{r-1}\} \cup \{g_{a_2}^r\}$ (case (e)), agent a_2 first selects $g_{a_2}^{r-1}$. Then, $(h_{a_3}^r, h_{a_1}^r) = (g_{a_1}^r, g_{a_3}^r)$, $(g_{a_1}^r, g_{a_1}^{r+1})$ or $(g_{a_3}^r, g_{a_1}^r)$.

- (iv) When $B^{r-1} = A^{r-1} \setminus \{g_{a_2}^{r-1}\} \cup \{g_{a_3}^r\}$ (case (f)), agent a_2 first selects $g_{a_2}^{r-1}$. Then, $(h_{a_3}^r, h_{a_1}^r) = (g_{a_1}^r, g_{a_2}^r), (g_{a_1}^r, g_{a_2}^{r+1}), (g_{a_2}^r, g_{a_1}^r), (g_{a_1}^{r+1}, g_{a_1}^r), (g_{a_2}^{r+1}, g_{a_1}^r)$ or $(g_{a_3}^{r+1}, g_{a_1}^r)$. Only cases (a), (d), (e) or (f) happen.

Therefore, the statement holds for r and we complete the proof. \square

We finally show the two inequalities (4) for $n = 3$.

Lemma 22. *Suppose that $n = 3$ and $N = \{a_1, a_2, a_3\}$. For every $a \in N$ and for every $r = 1, 2, \dots, \lceil m/n \rceil - 1$,*

$$u_a(h_a^r) \geq u_a(g_a^{r+1}) \quad \text{and} \quad u_a(g_a^r) \geq u_a(h_a^{r+1}).$$

Proof. For a round r such that $B^r = A^r$ (cases (a) in Figure 2) holds, the both inequalities hold for every $a \in N$. Thus, we only consider a round r such that there exist $i_1 \in \{2, 3\}$ and $i_2 \in \{1, 2, 3\}$ such that $B^r = A^r \setminus \{g_{a_{i_1}}^r\} \cup \{g_{a_{i_2}}^{r+1}\}$ (cases (b), (c), (d), (e) and (f) in Figure 2). For each $i \in \{1, 2, 3\} \setminus \{i_2\}$, we have $u_{a_i}(h_{a_i}^r) \geq u_{a_i}(g_{a_i}^{r+1})$ since good $g_{a_i}^{r+1}$ remains in round r under π_2 , i.e., $g_{a_i}^{r+1} \notin B^r$.

To complete the proof, we consider a case analysis.

1. The case of $\pi_2(N) = (1, 3, 2)$.

- (i) When $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (b)), from above discussion, we have $u_{a_2}(h_{a_2}^r) \geq u_{a_2}(g_{a_2}^{r+1})$ and $u_{a_3}(h_{a_3}^r) \geq u_{a_3}(g_{a_3}^{r+1})$. Since $\pi_2(a_1) < \pi_2(a_2)$, in round r under π_2 , agent a_1 must pick good $g_{a_1}^{r+1}$ or a good that is preferable to good $g_{a_1}^{r+1}$. Thus, we have $h_{a_2}^r = g_{a_2}^{r+1}$, $u_{a_2}(h_{a_2}^r) \geq u_{a_2}(g_{a_2}^{r+1})$ and the first inequality.

For each agent $a \in N$, there is no good within $M \setminus B^r$ that is preferable to good g_a^r . Thus, we obtain the second inequality.

- (ii) When $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_2}^{r+1}\}$ (case (c)), we have $u_{a_1}(h_{a_1}^r) \geq u_{a_1}(g_{a_1}^{r+1})$ and $u_{a_3}(h_{a_3}^r) \geq u_{a_3}(g_{a_3}^{r+1})$. In round r under π_2 , good $g_{a_2}^{r+1}$ must be selected agent a_2 . Otherwise, agents a_1 or a_3 choose good $g_{a_2}^{r+1}$, and this contradicts that goods $g_{a_1}^{r+1}$ and $g_{a_3}^r$ remain. Thus, we have $h_{a_2}^r = g_{a_2}^{r+1}$, $u_{a_2}(h_{a_2}^r) \geq u_{a_2}(g_{a_2}^{r+1})$ and the first inequality.

For each agent $a \in N$, there is no good within $M \setminus B^r$ that is preferable to good g_a^r . Thus, we obtain the second inequality.

2. The case of $\pi_2(N) = (3, 1, 2)$.

- (i) When $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (b)), we obtain the two inequalities by the same discussion as that in the case $\pi_2(N) = (1, 3, 2)$ and case (b).
- (ii) When $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_2}^{r+1}\}$ (case (c)), we obtain the two inequalities by the same discussion as that in the case $\pi_2(N) = (1, 3, 2)$ and case (c).

3. The case of $\pi_2(N) = (3, 2, 1)$.

- (i) When $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (b)), we have $u_{a_2}(h_{a_2}^r) \geq u_{a_2}(g_{a_2}^{r+1})$ and $u_{a_3}(h_{a_3}^r) \geq u_{a_3}(g_{a_3}^{r+1})$. In round r under π_2 , good $g_{a_1}^{r+1}$ must be selected by agent a_1 or a_2 , since good $g_{a_3}^r$ remains and agent a_3 never choose good $g_{a_1}^{r+1}$.
- (ii) When $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_2}^{r+1}\}$ (case (c)), we obtain the two inequalities by the same discussion as that in the case $\pi_2(N) = (1, 3, 2)$ and case (c).

4. The case of $\pi_2(N) = (2, 3, 1)$.

- (i) When $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (b)), we have $u_{a_2}(h_{a_2}^r) \geq u_{a_2}(g_{a_2}^{r+1})$ and $u_{a_3}(h_{a_3}^r) \geq u_{a_3}(g_{a_3}^{r+1})$. In round r under π_2 , good $g_{a_1}^{r+1}$ must be selected by agents a_1 or a_2 . When good $g_{a_1}^{r+1}$ is selected by agent a_1 , we have $h_{a_1}^r = g_{a_1}^{r+1}$. When good $g_{a_1}^{r+1}$ is selected by agent a_2 , good $g_{a_2}^r$ must have been chosen in round $r - 1$ under π_2 . However, when $\pi_2(N) = (2, 3, 1)$, we have $g_{a_2}^r \notin B^{r-1}$. Thus, good $g_{a_1}^{r+1}$ is selected agent a_1 . Hence, $u_{a_1}(h_{a_1}^r) \geq u_{a_1}(g_{a_1}^{r+1})$.

For each agent $a \in N$, there is no good within $M \setminus B^r$ that is preferable to good g_a^r . Thus, we obtain the second inequality.

- (ii) When $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (d)), we have $u_{a_2}(h_{a_2}^r) \geq u_{a_2}(g_{a_2}^{r+1})$ and $u_{a_3}(h_{a_3}^r) \geq u_{a_3}(g_{a_3}^{r+1})$. In round r under π_2 , good $g_{a_1}^{r+1}$ must be selected by agents a_1 or a_3 since good $g_{a_2}^r$ remains and agent a_2 never chooses good $g_{a_1}^{r+1}$. When good $g_{a_1}^{r+1}$ is selected by agent a_3 , we must have $g_{a_3}^r \in B^{r-1}$ or agent a_2 picks good $g_{a_3}^r$ in round r under π_2 . Now we have $g_{a_3}^r \notin B^{r-1}$ when $\pi_2(N) = (2, 3, 1)$, and agent a_2 chooses good $g_{a_3}^r$ in round r . In this case, agent a_1 selects good $g_{a_1}^r$ in round r under π_2 , and we get $u_{a_1}(h_{a_1}^r) \geq u_{a_1}(g_{a_1}^{r+1})$.

For agents a_1 and a_2 , there is no good within $M \setminus B^r$ that is preferable to good $g_{a_1}^r$ and good $g_{a_2}^r$ each. Then, we get $u_{a_1}(g_{a_1}^r) \geq u_{a_1}(h_{a_1}^{r+1})$ and $u_{a_1}(g_{a_1}^r) \geq u_{a_1}(h_{a_1}^{r+1})$. For agent a_3 , good $g_{a_2}^r \in M \setminus B^r$ may be preferable to good $g_{a_3}^r$. However, in round $r + 1$ under π_2 , agent a_2 picks good $g_{a_2}^r$. Then, agent a_3 can not choose good $g_{a_2}^r$ in round $r + 1$ under π_2 and we have $u_{a_3}(g_{a_3}^r) \geq u_{a_3}(h_{a_3}^{r+1})$. Therefore, we obtain the second inequality.

5. The case of $\pi_2(N) = (2, 1, 3)$.

- (i) When $B^r = A^r \setminus \{g_{a_3}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (b)), we have $u_{a_2}(h_{a_2}^r) \geq u_{a_2}(g_{a_2}^{r+1})$ and $u_{a_3}(h_{a_3}^r) \geq u_{a_3}(g_{a_3}^{r+1})$. In round r under π_2 , good $g_{a_1}^{r+1}$ must be selected by agents a_1 or a_2 . When good $g_{a_1}^{r+1}$ is selected by agent a_2 , good $g_{a_2}^r$ must have been chosen in round $r - 1$ under π_2 . Thus, in round $r - 1$, case (e) holds. However, in the case (e), $g_{a_2}^{r-1} \notin B^{r-1}$ and agent a_2 selects good $g_{a_2}^{r-1}$ in round r . Hence, good $g_{a_1}^{r+1}$ is not selected by agent a_2 , and good $g_{a_1}^{r+1}$ must be selected by agents a_1 . Therefore, we obtain $u_{a_1}(h_{a_1}^r) \geq u_{a_1}(g_{a_1}^{r+1})$, and the first inequality.

For each agent $a \in N$, there is no good within $M \setminus B^r$ that is preferable to good g_a^r . Thus, we obtain the second inequality.

- (ii) When $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_1}^{r+1}\}$ (case (d)), we have $u_{a_2}(h_{a_2}^r) \geq u_{a_2}(g_{a_2}^{r+1})$ and $u_{a_3}(h_{a_3}^r) \geq u_{a_3}(g_{a_3}^{r+1})$. In round r under π_2 , good $g_{a_1}^{r+1}$ must be selected by agents a_1 or a_3 . Since $\pi_2(a_1) < \pi_2(a_3)$, in round r under π_2 , agent a_1 must pick good $g_{a_1}^{r+1}$ or a good that is preferable to good $g_{a_1}^{r+1}$. Thus, we get the first inequality.

Moreover, we obtain the second inequalities by the same discussion as that in the case $\pi_2(N) = (2, 3, 1)$ and case (d).

- (iii) When $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_2}^{r+1}\}$ (case (e)), we have $u_{a_1}(h_{a_1}^r) \geq u_{a_1}(g_{a_1}^{r+1})$ and $u_{a_3}(h_{a_3}^r) \geq u_{a_3}(g_{a_3}^{r+1})$. Now, we have $g_{a_2}^r \notin B^r$. Thus, agent a_2 gets a good that is preferable to good $g_{a_1}^{r+1}$ in round r under π_2 . Then, we have $u_{a_2}(h_{a_2}^r) \geq u_{a_2}(g_{a_2}^{r+1})$.

For agents a_1 and a_2 , there is no good within $M \setminus B^r$ that is preferable to good $g_{a_1}^r$ and good $g_{a_2}^r$ each. For agent a_3 , good $g_{a_2}^r \in M \setminus B^r$ may be preferable to good $g_{a_3}^r$. However, in round $r + 1$ under π_2 , agent a_2 picks good $g_{a_2}^r$. Then, we have $u_{a_3}(g_{a_3}^r) \geq u_{a_3}(h_{a_3}^{r+1})$.

- (iv) When $B^r = A^r \setminus \{g_{a_2}^r\} \cup \{g_{a_3}^{r+1}\}$ (case (f)), we have $u_{a_1}(h_{a_1}^r) \geq u_{a_1}(g_{a_1}^{r+1})$ and $u_{a_2}(h_{a_2}^r) \geq u_{a_2}(g_{a_2}^{r+1})$. In round r under π_2 , good $g_{a_3}^{r+1}$ must be selected by agent a_3 since $g_{a_1}^{r+1}, g_{a_2}^{r+1} \notin B^r$. Thus, we have $h_{a_3}^r = g_{a_3}^{r+1}$ and $u_{a_3}(h_{a_3}^r) \geq u_{a_3}(g_{a_3}^{r+1})$.

Moreover, we obtain the second inequalities by the same discussion as that in the case $\pi_2(N) = (2, 1, 3)$ and case (e).

From these discussion, we complete the proof.

□