# Improving the Reliability of Quantum Circuits by Evolving Heterogeneous Ensembles

Owain Parry, John Clark, and Phil McMinn

University of Sheffield {o.b.parry,john.clark,p.mcminn}@sheffield.ac.uk

Abstract. Quantum computers can perform certain operations exponentially faster than classical computers, but designing quantum circuits is challenging. To that end, researchers used evolutionary algorithms to produce probabilistic quantum circuits that give the correct output more often than not for any input. They can be executed multiple times, with the outputs combined using a classical method (such as voting) to produce the final output, effectively creating a homogeneous ensemble of circuits (i.e., all identical). Inspired by *n*-version programming and ensemble learning, we developed a tool that uses an evolutionary algorithm to generate heterogeneous ensembles of circuits (i.e., all different), named QUEEN. We used it to evolve ensembles to solve the Iris classification problem. When using ideal simulation, we found the performance of heterogeneous ensembles to be greater than that of homogeneous ensembles to a statistically significant degree. When using noisy simulation, we still observed a statistically significant improvement in the majority of cases. Our results indicate that evolving heterogeneous ensembles is an effective strategy for improving the reliability of quantum circuits. This is particularly relevant in the current NISQ era of quantum computing where computers do not yet have good tolerance to quantum noise.

**Keywords:** Quantum Computing · Evolutionary Algorithms · Software Reliability

# 1 Introduction

Quantum computers can efficiently solve certain problems that would be intractable for classical computers [9,10]. However, designing quantum circuits is difficult [2,9,19], so researchers investigated the effectiveness of evolutionary algorithms [3] to generate them [2,9,10,19]. To read the output after executing a circuit, the qubits needs to be measured, resulting in the collapse of the quantum state into a classical state. Generally, this is a non-deterministic process. Massey et al. [9] evolved a *deterministic circuit* for adding integers that always gives the correct output for any input. However, they were unable to evolve deterministic circuits for more challenging problems, reasoning that evolutionary algorithms are better suited to finding good approximate solutions. Instead, they evolved *probabilistic circuits*, that give the correct output more often than an incorrect

#### 2 Owain Parry, John Clark, and Phil McMinn

output for any input. They may be executed repeatedly, and the outputs combined in some classical way to produce the final output (e.g., a vote), effectively equivalent to a *homogeneous ensemble* of circuits (i.e., all the same).

In software engineering, *n*-version programming is a method used to improve software safety [8]. It involves independently producing multiple functionally equivalent programs from a single specification and executing them in parallel for improved fault-tolerance through a voting mechanism. In machine learning, ensemble learning is a state-of-the art solution for classification and regression problems [14]. It improves upon the performance of a single predictive model by training a *heterogeneous ensemble* of models (i.e., all different) and combining their predictions. Despite the success of combining the outputs of diverse solutions in software engineering and machine learning, there has been no attempt to evolve heterogeneous ensembles of quantum circuits to our knowledge.

The Noisy Intermediate-Scale Quantum (NISQ) era refers to the current state of quantum computing where computers lack dependable tolerance to quantum noise [5]. A common manifestation is depolarizing error, where the state of a qubit undergoes random perturbations, making circuits less likely to produce the correct output [11,12]. As in *n*-version programming, heterogeneous ensembles may provide greater reliability in the presence of noise by way of redundancy. Because the circuits are all different, the impact of noise on each circuit may also be different, and so collectively they may be more likely to produce the correct final output through a voting mechanism than a homogeneous ensemble.

We developed a tool that uses an evolutionary algorithm to generate heterogeneous ensembles of probabilistic quantum circuits, named QUEEN (QUantum Evolved Ensembles). We used it to evolve ensembles of 3, 5, and 7 circuits to tackle the Iris classification problem [4]. In each case, we found the performance of heterogeneous ensembles to be greater than that of homogeneous ensembles of the same size to a statistically significant degree when using ideal simulation. When using noisy simulation, we still observed a statistically significant improvement for ensembles of size 5 and 7 in the vast majority cases. These results indicate that our approach produces more reliable ensembles, in the sense that they are more likely to produce the correct output even with noise.

In summary, the main contributions of this paper are:

**1.** QuEEn. We developed a new tool for evolving heterogeneous ensembles of quantum circuits (see Section 2).

**2.** Novel Evaluation. Ours is the first study to compare the performance of heterogeneous ensembles of circuits to homogeneous ensembles (see Section 3).

**3. Findings and Implications.** Our results indicate that evolving heterogeneous ensembles is an effective strategy, potentially paving the way for more advanced techniques in quantum circuit evolution (see Section 4).

# 2 QuEEn

Our tool QUEEN uses an evolutionary algorithm [3] to evolve a population of equally-sized heterogeneous ensembles of probabilistic quantum circuits that im-

plement a solution to a given problem. A circuit operates on a quantum register of qubits, following which, one or more are measured to populate a classical register of bits that encode the circuit's output value. The tool represents a circuit as a list of quantum gates and their parameters. It supports two gate types: U gates, a generic single-qubit rotation gate with three angles, and CX gates, a controlled-not gate. These two gates form a universal gate set sufficient to express any quantum circuit [1]. The tool considers an ensemble to be a set of circuits whose collective output value is the most frequent among its members. In the event of a tie, the ensemble would select uniformly at random among the tied circuit output values. As arguments, QUEEN takes the number of qubits in the quantum register, a file to write the population to, and a file to read test cases from. A test case represents a specific instance of the problem. It consists of an initialization circuit to set the quantum register to some input value, along with the expected output value to compare against the output value of an ensemble.

The tool uses the qiskit package [7] to simulate circuit execution and qubit measurement. By default, QUEEN uses ideal simulation that does not consider noise. Optionally, QUEEN takes the name of a *fake backend*. These are provided by qiskit and approximately reproduce the noise measured in specific quantum computers for simulations [12]. The state of the classical register after measurement is non-deterministic so QUEEN performs 1,000 repeats of the circuit simulation. This results in a discrete probability distribution over the possible output values. The tool computes the output distribution for an ensemble based on the output distributions of its circuits and the voting scheme described earlier in this section. The *fitness* of an ensemble, which measures how well it addresses the problem, is its mean probability of producing the expected output value over the set of test cases (higher is better). While more complex fitness functions exist [16], we selected this because it has an intuitive interpretation. Our fitness function does not penalize ensembles based on the number of gates in its circuits but QUEEN does enforce a fixed upper bound. In this initial study, QUEEN does not explicitly promote circuit diversity within ensembles. However, we plan to implement and evaluate the impact of this as part of future work.

# 3 Evaluation

In this section, we describe our methodology for answering our research questions regarding evolved ensembles of probabilistic quantum circuits:

**RQ1.** What is the difference in fitness between heterogeneous and homogeneous ensembles?

**RQ2.** How does noise impact the fitness difference between heterogeneous and homogeneous ensembles?

**Problem and Test Cases.** We used the Iris classification problem [4] in our evaluation because it is non-trivial, yet relatively straight-forward to address and has seen extensive use as a benchmark for statistical classification techniques. It consists of determining the species of an Iris flower from three possibilities

#### 4 Owain Parry, John Clark, and Phil McMinn

based on the length and width of its sepal and petal (four features). The corresponding dataset contains 150 examples, 50 for each of the three classes, which we converted into test cases for QUEEN. For each test case, we generated the appropriate initialization circuit based on an angle encoding scheme [17] that requires one qubit per feature. This requires a quantum register of four qubits because there are four features. The expected output for each test case encodes the correct class in two classical bits which are to be measured from the first two qubits. Because there are only three possible classes, one of the four possible output values represents an "invalid" class. We randomly split the 150 test cases into 100 for evolving ensembles (the *evolution tests*) and 50 for evaluating the fitness of each ensemble in the final population (the *evaluation tests*). This is to avoid any bias in our results caused by overfitting.

Answering our Research Questions. To answer RQ1, we invoked QUEEN four times to evolve ensembles of size 1, 3, 5, and 7 based on the evolution tests. Where the ensemble size was 1, we are evolving individual circuits. In each case, we set the population size to 600 ensembles and the number of generations to 5,000. We selected these values to explore the search space as much as possible within the constraints of the computational resources available to us. Once the evolution was complete, we used QUEEN to evaluate the fitness of each ensemble in each of the four final populations based on the evaluation tests. We did not specify any fake backend during evolution or evaluation, meaning QUEEN always used ideal simulation. For the final population of individual circuits (ensemble size of 1), we additionally used QUEEN to evaluate the fitness of each circuit as a homogeneous ensemble of size 3, 5, and 7. This represents executing the same circuit several times and applying the voting mechanism described in Section 2. For each of the three final populations of heterogeneous ensembles (ensemble size of 3, 5, and 7), we compared the fitnesses to those of the corresponding homogeneous ensembles using a two-tailed Mann-Whitney U hypothesis test. In each case, the null hypothesis is that the distribution underlying the fitnesses of the heterogeneous ensembles is same as that of the homogeneous ensembles. In other words, there is no general difference in fitness (mean probability of producing the expected output value) between combining the outputs of several different circuits and combining the outputs from repeating the same circuit several times. To answer **RQ2**, we repeated the methodology for answering **RQ1** ten times, aside from evolving the ensembles again, specifying a different fake backend each time. In each case, this means QUEEN used noisy simulation when evaluating ensemble fitnesses based on the evaluation tests. We selected the ten fake backends at random from those provided by **giskit** [7].

Threats to Validity. Evolutionary algorithms are highly randomized and nondeterministic. Therefore, our results may be unreproducible. Ideally, we would have mitigated this risk by performing many reruns of the ensemble evolution. However, given the computational complexity of quantum simulation, this was not possible within the constraints of the resources available to us. Instead, we mitigated this risk by performing hypothesis testing between populations of ensembles, rather than comparing the best individual ensembles directly. All

**Table 1.** For three values of ensemble size (n): the median fitness (Med Fit) of the heterogeneous (Het) and homogeneous (Hom) ensembles, and the p-value (p) and rankbiserial correlation effect size (r) from the two-tailed Mann-Whitney U test. The first row shows the results where QUEEN used ideal simulation when evaluating ensemble fitnesses. The subsequent rows shows the results where QUEEN used noisy simulation.

	n=3				n = 5				n=7			
	Med	l Fit			Med Fit				Med Fit			
Backend	Het	Hom	p	r	Het	Hom	p	r	Het	Hom	p	r
ideal	0.782	0.757	< 0.001	0.932	0.920	0.775	< 0.001	0.997	0.920	0.783	< 0.001	0.987
boeblingen	0.705	0.724	< 0.001	-0.895	0.864	0.758	< 0.001	0.990	0.841	0.773	< 0.001	0.957
cairo	0.754	0.746	< 0.001	0.803	0.895	0.770	< 0.001	0.997	0.891	0.780	< 0.001	0.981
casablanca	0.727	0.734	< 0.001	-0.784	0.872	0.764	< 0.001	0.990	0.859	0.777	< 0.001	0.964
essex	0.687	0.711	< 0.001	-0.899	0.812	0.751	< 0.001	0.966	0.796	0.769	$<\!0.001$	0.758
guadalupe	0.736	0.742	< 0.001	-0.734	0.880	0.768	< 0.001	0.990	0.867	0.779	$<\!0.001$	0.969
kyoto	0.250	0.251	< 0.001	-0.212	0.251	0.251	0.003	-0.099	0.250	0.251	$<\!0.001$	-0.161
manila	0.728	0.731	< 0.001	-0.511	0.890	0.762	< 0.001	0.995	0.877	0.776	< 0.001	0.977
quito	0.615	0.675	< 0.001	-0.931	0.730	0.725	< 0.001	0.491	0.705	0.751	< 0.001	-0.932
rome	0.719	0.732	< 0.001	-0.840	0.864	0.762	< 0.001	0.987	0.847	0.776	$<\!0.001$	0.957
washington	0.752	0.745	$<\!0.001$	0.772	0.894	0.770	$<\!0.001$	0.996	0.887	0.780	$<\!0.001$	0.980

types of hypothesis tests make assumptions about the distributions underlying the data. If these do not hold, the results are likely to be invalid. To mitigate this risk, we selected the Mann-Whitney U test because it makes relatively few assumptions compared to other tests, such as Student's *t*-test.

# 4 Results

What is the difference in fitness between heterogeneous and homogeneous ensembles? The first row of Table 1 shows the results for **RQ1**, where QUEEN used ideal simulation when evaluating ensemble fitnesses. For ensemble sizes 3, 5, and 7, it shows the median fitness of the heterogeneous and homogeneous ensembles, and the *p*-value and rank-biserial correlation effect size from the two-tailed Mann-Whitney U test. A p-value less than 0.001 indicates that we can reject the null hypothesis of no difference in fitness between heterogeneous and homogeneous ensembles at the 99.9% confidence interval. The rank-biserial correlation effect size ranges from -1 to 1. Positive values indicate that heterogeneous ensembles tend to be fitter than homogeneous ensembles, negative values indicate the opposite trend, and zero indicates no difference. In all three cases, the *p*-values are low enough to reject the null hypothesis and conclude that there is a difference in fitness. The effect sizes are all positive and close to 1, indicating that heterogeneous ensembles are almost always fitter than homogeneous ensembles. Comparing the median fitnesses when the ensemble size is 3, there is only a minor improvement in favor of heterogeneous ensembles (0.782) 6 Owain Parry, John Clark, and Phil McMinn

vs. 0.757). However, for sizes 5 and 7, the improvement appears more substantial (0.920 vs. 0.775 and 0.920 vs. 0.783 respectively).

How does noise impact the fitness difference between heterogeneous and homogeneous ensembles? The ten subsequent rows show the results for **RQ2**, where QUEEN used noisy simulation when evaluating ensemble fitnesses. The *p*-values are low enough to reject the null hypothesis for all three ensemble sizes and all ten fake backends except for when the size is 5 and the backend is "kyoto" (p = 0.003). When the ensemble size is 3, the effect sizes are now negative in most cases, indicating that homogeneous ensembles tend to be fitter than heterogeneous ensembles. However, in the case of 5 and 7 circuits, the effect sizes remain positive except for when the fake backend is "kyoto" or "quito".

# 5 Related Work

Schuld et al. [15] proposed quantum ensembles for binary classification tasks in the context of quantum machine learning [18]. Their aim was to implement classical ensemble learning [6] in a quantum setting. Our aim was to improve the reliability of probabilistic quantum circuits by evolving them as heterogeneous ensembles and combining their outputs classically. While the problem we used in our evaluation is typically used as a benchmark for machine learning classifiers [4], our approach is applicable to any problem with test cases. Their concept of a quantum ensemble is implemented within a single circuit, so the benefits of redundancy with respect to noise resistance from combining diverse circuits (inspired by *n*-version programming [8]) does not apply, unlike our work.

Rather than using evolutionary algorithms to generate quantum circuits, researchers have used them to transform existing circuits. For example, O'Brien et al. [13] introduced a genetic improvement approach to transform an arbitrary quantum circuit such that it can be correctly and efficiently executed on a specific quantum computer. Researchers have also applied evolutionary algorithms in a wider context, such as Muqueet et al. [11], who proposed a genetic programming technique to generate accurate expression-based quantum noise models.

# 6 Conclusion and Future Work

Our results demonstrate that heterogeneous ensembles of probabilistic quantum circuits generally perform better than homogeneous ensembles when using ideal simulation. They also show that heterogeneous ensembles still mostly outperform homogeneous ensembles when using noisy simulation, provided the ensembles are large enough. These findings imply that our approach of evolving heterogeneous ensembles is more reliable than evolving individual probabilistic circuits and executing them several times. As future work, we plan to evaluate the impact of explicitly promoting circuit diversity within ensembles during evolution. We also plan on evaluating several different problems and voting mechanisms.

### References

- Barenco, A., Bennett, C.H., Cleve, R., DiVincenzo, D.P., Margolus, N., Shor, P., Sleator, T., Smolin, J.A., Weinfurter, H.: Elementary gates for quantum computation. Physical Review A 52(5), 3457 (1995)
- Barnes, K.M., Gale, M.B.: Meta-genetic programming for static quantum circuits. In: Proceedings of the Genetic and Evolutionary Computation Conference Companion. pp. 2016–2019 (2019)
- Bartz-Beielstein, T., Branke, J., Mehnen, J., Mersmann, O.: Evolutionary algorithms. Data Mining and Knowledge Discovery 4(3), 178–195 (2014)
- Chen, S.M., Fang, Y.D.: A new approach for handling the iris data classification problem. Applied Science and Engineering 3(1), 37–49 (2005)
- Chen, S., Cotler, J., Huang, H.Y., Li, J.: The complexity of NISQ. Nature Communications 14(1), 6001 (2023)
- Dong, X., Yu, Z., Cao, W., Shi, Y., Ma, Q.: A survey on ensemble learning. Frontiers of Computer Science 14(2), 241–258 (2020)
- 7. IBM quantum, https://www.ibm.com/quantum/qiskit (2024)
- Khoury, R., Hamou-Lhadj, A., Couture, M., Charpentier, R.: Diversity through nversion programming: Current state, challenges and recommendations. Information Technology and Computer Science 4(2), 56 (2012)
- Massey, P., Clark, J.A., Stepney, S.: Evolving quantum circuits and programs through genetic programming. In: Proceedings of the Genetic and Evolutionary Computation Conference. pp. 569–580 (2004)
- Massey, P., Clark, J.A., Stepney, S.: Evolution of a human-competitive quantum fourier transform algorithm using genetic programming. In: Proceedings of the Genetic and Evolutionary Computation Conference. pp. 1657–1663 (2005)
- Muqeet, A., Ali, S., Arcaini, P.: Approximating stochastic quantum noise through genetic programming. In: Proceedings of the International Symposium on Search Based Software Engineering. pp. 56–62 (2024)
- Muqeet, A., Ali, S., Yue, T., Arcaini, P.: A machine learning-based error mitigation approach for reliable software development on IBM's quantum computers. In: Companion Proceedings of the International Conference on the Foundations of Software Engineering. pp. 80–91 (2024)
- O'Brien, G., Clark, J.A.: Using genetic improvement to retarget quantum software on differing hardware. In: Proceedings of the International Workshop on Genetic Improvement. pp. 31–38 (2021)
- Sagi, O., Rokach, L.: Ensemble learning: A survey. Data Mining and Knowledge Discovery 8(4), e1249 (2018)
- Schuld, M., Petruccione, F.: Quantum ensembles of quantum classifiers. Scientific Reports 8(1), 2772 (2018)
- Stepney, S., Clark, J.A.: Searching for quantum programs and quantum protocols. Computational and Theoretical Nanoscience 5(5), 942–969 (2008)
- Weigold, M., Barzen, J., Leymann, F., Salm, M.: Expanding data encoding patterns for quantum algorithms. In: Proceedings of the International Conference on Software Architecture Companion. pp. 95–101 (2021)
- Zhang, Y., Ni, Q.: Recent advances in quantum machine learning. Quantum Engineering 2(1), e34 (2020)
- Zhu, W., Pi, J., Peng, Q.: A brief survey of quantum architecture search. In: Proceedings of the International Conference on Algorithms, Computing and Systems. pp. 1–5 (2022)