Kernelization complexity of solution discovery problems

Mario Grobler University of Bremen, Germany

Amer E. Mouawad American University of Beirut, Lebanon

Vijayaragunathan Ramamoorthi† University of Bremen, Germany

Stephanie Maaz[∗] University of Waterloo, Canada

Naomi Nishimura[∗] University of Waterloo, Canada

Sebastian Siebertz University of Bremen, Germany

Abstract

In the solution discovery variant of a vertex (edge) subset problem Π on graphs, we are given an initial configuration of tokens on the vertices (edges) of an input graph *G* together with a budget *b*. The question is whether we can transform this configuration into a feasible solution of Π on *G* with at most *b* modification steps. We consider the token sliding variant of the solution discovery framework, where each modification step consists of sliding a token to an adjacent vertex (edge). The framework of solution discovery was recently introduced by Fellows et al. [Fellows et al., ECAI 2023] and for many solution discovery problems the classical as well as the parameterized complexity has been established. In this work, we study the kernelization complexity of the solution discovery variants of VERTEX COVER, INDEPENDENT SET, DOMINATING SET, SHORTEST PATH, MATCHING, and VERTEX CUT with respect to the parameters number of tokens *k*, discovery budget *b*, as well as structural parameters such as pathwidth.

1 Introduction

In the realm of optimization, traditional approaches revolve around computing optimal solutions to problem instances from scratch. However, many practical scenarios can be formulated as the construction of a feasible solution from an infeasible starting state. Examples of such scenarios include reactive systems involving human interactions. The inherent dynamics of such a system is likely to lead to an infeasible state. However, computing a solution from scratch may lead to a solution that may differ arbitrarily from the starting state. The modifications required to reach such a solution from the starting state may be costly, difficult to implement, or sometimes unacceptable.

Let us examine a specific example to illustrate. A set of workers is assigned tasks so that every task is handled by a qualified worker. This scenario corresponds to the classical matching problem in bipartite graphs. Suppose one of the workers is now no longer available (e.g. due to illness); hence, the schedule has to be changed. An optimal new matching could be efficiently recomputed from scratch, but it is desirable to find one that is as close to the original one as possible, so that most of the workers keep working on the task that they were initially assigned.

[∗]Funded by a grant from the Natural Sciences and Engineering Research Council of Canada.

[†]Funded by the "Mind, Media, Machines" high-profile area at the University of Bremen.

Such applications can be conveniently modeled using the *solution discovery* framework, which is the central focus of this work. In this framework, rather than simply finding a feasible solution to an instance $\mathcal I$ of a source problem Π , we investigate whether it is possible to transform a given infeasible configuration into a feasible one by applying a limited number of transformation steps. In this work we consider vertex (edge) subset problems Π on graphs, where the *configurations* of the problem are sets of vertices (edges). These configurations are represented by the placement of tokens on the vertices (edges) of the configuration. An atomic *modification step* consists of moving one of the tokens and the question is whether a feasible configuration is reachable after at most *b* modification steps. Inspired by the well-established framework of combinatorial reconfiguration [\[5,](#page-46-0) [20,](#page-47-0) [19\]](#page-47-1), commonly allowed modification steps are the addition/removal of a single token, the jumping of a token to an arbitrary vertex/edge, or the slide of a token to an adjacent vertex (edge).

Problems defined in the solution discovery framework are useful and have been appearing in recent literature. Fellows et al. [\[14\]](#page-47-2) introduced the term *solution discovery*, and along with Grobler et al. [\[16\]](#page-47-3) initiated the study of the (parameterized) complexity of solution discovery problems for various NP-complete source problems including VERTEX COVER (VC) , INDEPENDENT SET (IS) , DOMINATING SET (DS), and COLORING (COL) as well as various source problems in P such as SPANNING TREE (ST), SHORTEST PATH (SP), MATCHING (MAT), and VERTEX CUT (VCUT) / EDGE CUT (ECUT).

Fellows et al. [\[14\]](#page-47-2) and Grobler et al. [\[16\]](#page-47-3) provided a full classification of polynomial-time solvability vs. NP-completeness of the above problems in all token movement models (token addition/removal, token jumping, and token sliding). For the NP-complete solution discovery problems, they provided a classification of fixed-parameter tractability vs. W[1]-hardness. Recall that a *fixed-parameter tractable algorithm* for a problem Π with respect to a parameter *p* is one that solves Π in time $f(p) \cdot n^{\mathcal{O}(1)}$, where *n* is the size of the instance and *f* is a computable function dependent solely on *p*, while W[1]-hardness provides strong evidence that the problem is likely not fixed-parameter tractable (i. e., does not admit a fixed-parameter tractable algorithm) [\[11\]](#page-47-4).

A classical result in parameterized complexity theory is that every problem Π that admits a fixed-parameter tractable algorithm necessarily admits a kernelization algorithm as well [\[6\]](#page-46-1). A *kernelization algorithm* for a problem Π is a polynomial-time preprocessing algorithm that, given an instance *x* of the problem Π with parameter *p*, produces a *kernel* – an equivalent instance *x* ′ of the problem Π with a parameter p' , where both the size of x' and the parameter p' are bounded by a computable function depending only on *p* [\[11\]](#page-47-4). Typically, kernelization algorithms generated using the techniques of Cai et al. [\[6\]](#page-46-1) yield kernels of exponential (or even worse) size. In contrast, designing problem-specific kernelization algorithms frequently yields more efficiently-sized kernels, often quadratic or even linear with respect to the parameter. Note that once a decidable problem Π with parameter *p* admits a kernelization algorithm, it also admits a fixed-parameter tractable algorithm, as a kernelization algorithm always produces a kernel of size that is simply a function of *p*. The fixed-parameter tractable solution discovery algorithms of Fellows et al. [\[14\]](#page-47-2) and Grobler et al. [\[16\]](#page-47-3) are not based on kernelization algorithms.

Unfortunately, it is unlikely that all fixed-parameter tractable problems admit polynomial kernels. Bodlaender et al. [\[3,](#page-46-2) [4\]](#page-46-3) developed the first framework for proving kernel lower bounds and Fortnow and Santhanam [\[15\]](#page-47-5) showed a connection to the hypothesis $\mathsf{NP} \not\subset \mathsf{coNP/poly}$. Specifically, for several NP-hard problems, a kernel of polynomial size with respect to a parameter would imply that NP ⊂ coNP/poly, and thus an unlikely collapse of the polynomial hierarchy to its third level [\[24\]](#page-48-0). Driven by the practical benefits of kernelization algorithms, we explore the size bounds on kernels for most of the above-mentioned solution discovery problems in the token sliding model, particularly those identified as fixed-parameter tractable in the works of Fellows et al. [\[14\]](#page-47-2) and Grobler et al. [\[16\]](#page-47-3). **Overview of our results.** We focus on the kernelization complexity of solution discovery in the token sliding model for the following source problems: VERTEX COVER, INDEPENDENT SET, Dominating Set, Shortest Path, Matching, and Vertex Cut. For a base problem Π we write Π-D for the discovery version in the token sliding model.

[Figure 1](#page-3-0) summarizes our results. All graph classes and width parameters appearing in this introduction are defined in the preliminaries. Fellows et al. [\[14\]](#page-47-2) and Grobler et al. [\[16\]](#page-47-3) gave fixedparameter tractable algorithms with respect to the parameter *k* for IS-D on nowhere dense graphs, for VC-D, SP-D, MAT-D, and VCUT-D on general graphs and for DS-D on biclique-free graphs.

We show that IS-D, VC-D, DS-D, and Mat-D parameterized by *k* admit polynomial size kernels (on the aforementioned classes), while VCUT-D does not admit kernels of size polynomial in *k*. For SP-D, we show that the problem does not admit a kernel of polynomial size parameterized by $k + b$ unless $\mathsf{NP} \subseteq \mathsf{coNP/poly}.$

As NP-hardness provides strong evidence that a problem admits no polynomial-time algorithm, W[*t*]-hardness (for a positive integer *t*) with respect to a parameter *p* provides strong evidence that a problem admits no fixed-parameter tractable algorithm with respect to *p*. Fellows et al. [\[14\]](#page-47-2) proved that VC-D, IS-D, and DS-D are W[1]-hard with respect to parameter *b* on *d*-degenerate graphs but provided fixed-parameter tractable algorithms on nowhere dense graphs. They also showed that these problems are slicewise polynomial (XP) with respect to the parameter treewidth and left open the parameterized complexity of these problems with respect to the parameter treewidth alone. We show that these problems remain XNLP-hard (which implies W[*t*]-hardness for every positive integer *t*) for parameter pathwidth (even if given a path decomposition realising the pathwidth), which is greater than or equal to treewidth, and that they admit no polynomial kernels (even if given a path decomposition realising the pathwidth) with respect to the parameter $b + pw$, where *pw* is the pathwidth of the input graph, unless $NP \subseteq \text{coNP/poly}$.

Finally, we also consider the parameter feedback vertex set number (*fvs*), which is an upper bound on the treewidth of a graph, but is incomparable to pathwidth. We complement the parameterized complexity classification for the results of Fellows et al. [\[14\]](#page-47-2) by showing that IS-D, VC-D, and DS-D are W[1]-hard for the parameter *fvs*.

Several interesting questions remain open. For instance, while their parameterized complexity was determined, the kernelization complexity of Col-D and ECut-D remains unsettled. Similarly, the kernelization complexity of IS-D and DS-D with respect to parameter *k* is unknown on *d*-degenerate and semi-ladder-free graphs, respectively, where the problems are known to be fixed-parameter tractable. In addition, it remains open whether VCuT-D parameterized by $k + b$ admits a polynomial kernel or whether Mat-D parameterized by *b* admits polynomial kernels on restricted classes of graphs.

Organization of the paper. We introduce all relevant notation in [Section 2.](#page-2-0) In [Section 3,](#page-6-0) we provide fundamental graph gadgets that appear in many constructions presented in the paper and provide several lemmas describing useful properties of those gadgets. Afterwards, we present our results for VC-D in [Section 4,](#page-12-0) IS-D in [Section 5,](#page-21-0) DS-D in [Section 6,](#page-30-0) SP-D in [Section 7,](#page-40-0) Mat-D in [Section 8,](#page-41-0) and VCu_T-D in [Section 9.](#page-42-0)

2 Preliminaries

We use the symbol N for the set of non-negative integers (including 0), $\mathbb Z$ for the set of all integers. and \mathbb{Z}_+ for the set of positive non-zero integers. For $k \in \mathbb{N}$, we define $[k] = \{1, \ldots, k\}$ with the convention that $[0] = \emptyset$.

Figure 1: A classification of problems into three categories: (blue, alternatively grid) problems for which we obtain polynomial kernels, (white) those for which polynomial kernels are unlikely, and (red, alternatively lines) those for which fixed-parameter tractable algorithms are unlikely. Each entry in a category mentions a solution discovery problem, one or more parameters (in parentheses and followed by a dash), and the graph class with respect to which the problem falls into the category. A reference in the parentheses indicates that the fixed-parameter tractability of that problem was established in the cited work. *pw* denotes the pathwidth and *fvs* denotes the feedback vertex set number of the input graph.

Graphs. We consider finite and simple graphs only. We denote the vertex set and the edge set of a graph *G* by $V(G)$ and $E(G)$, respectively, and denote an undirected edge between vertices *u* and *v* by *uv* (or equivalently *vu*) and a directed edge from *u* to *v* by (u, v) . We use $N(v)$ to denote the set of all neighbors of *v* and $E(v)$ to denote the set of all edges incident with *v*. Furthermore, we define the closed neighborhood of *v* as $N[v] = N(v) \cup \{v\}$. For a set X of vertices we write $G[X]$ for the subgraph induced by *X*.

A sequence of edges $e_1 \ldots e_\ell$ for some $\ell \geq 1$ is a (simple) path of length ℓ if every two consecutive edges in the sequence share exactly one endpoint and each other pair of edges share no endpoints. For vertices *u* and *v*, we denote the length of a shortest path $e_1 \ldots e_\ell$ that connects *u* to *v* by $d(u, v)$, where $d(v, v) = 0$ for all $v \in V(G)$. For edges $e, e' \in E(G)$, we denote by $d(e, e')$ the length of a shortest path $e_1 \ldots e_\ell$ with e_1 being incident to e and $e' = e_\ell$. For a vertex $v \in V(G)$ and a non-negative integer *i*, we denote by $V(v, i) = \{u \in V(G) \mid d(u, v) = i\}$. For an edge $e \in E(G)$, we denote by $E(e, i) = \{e' \in E(G) \mid d(e, e') = i\}.$

The complete graph (clique) on *n* vertices is denoted by K_n and a complete bipartite graph (biclique) with parts of size *m* and *n*, respectively, by $K_{m,n}$. For an in-depth review of general graph theoretic definitions we refer the reader to the textbook by Diestel [\[9\]](#page-47-6).

Pathwidth and treewidth. A *tree decomposition* of a graph *G* is a pair $\mathcal{T} = (T, (X_i)_{i \in V(T)})$ where *T* is a tree and $X_i \subseteq V(G)$ for each $i \in V(T)$, such that

- i. $\bigcup_{i \in V(T)} X_i = V(G),$
- ii. for every edge $uv = e \in E(G)$, there is an $i \in V(T)$ such that $u, v \in X_i$, and
- iii. for every $v \in V(G)$, the subgraph T_v of *T* induced by $\{i \in V(T) \mid v \in X_i\}$ is connected, i.e., T_v is a tree.

We refer to the vertices of *T* as the *nodes* of *T*. For a node *i*, we say that the corresponding set X_i is the *bag* of *i*. The *width* of the tree decomposition $(T, (X_i)_{i \in V(T)})$ is $\max_{i \in V(T)} |X_i| - 1$. The *treewidth* of *G*, denoted *tw*(*G*), is the smallest width of any tree decomposition of *G*.

A *path decomposition* of a graph *G* is a tree decomposition $\mathcal{P} = (T, (X_i)_{i \in V(T)})$ in which *T* is a path. We represent a path decomposition $\mathcal P$ by the sequence of its bags only. The *pathwidth* of G , denoted *pw*(*G*), is the smallest width of any path decomposition of *G*. A *nice path decomposition* of *G* is one that begins and ends with nodes corresponding to empty bags and such that each other node in the decomposition corresponds to a bag that either *introduces* a vertex $v \in V(G)$ $(X_i = X_{i-1} \cup \{v\}$ for $v \notin X_i$) or *forgets* one $(X_i = X_{i-1} \setminus \{v\}$ for $v \in X_i$). Every path decomposition can be efficiently turned into a nice path decomposition of the same width [\[7\]](#page-46-4). Subdividing or deleting edges of a graph *G* preserves its path- or treewidth [\[23\]](#page-48-1). Additionally, the following holds.

Observation 2.1. Let *G* be a graph and $X \subseteq V(G)$. Then $pw(G) \leq pw(G - X) + |X|$ and $tw(G) \leq$ $tw(G - X) + |X|$.

Definition 2.1. A class $\mathscr C$ of graphs has bounded treewidth (bounded pathwidth) if there exists a constant *t* such that all $G \in \mathscr{C}$ have treewidth (pathwidth) at most *t*.

Feedback vertex set number (fvs). For a graph G , by $fvs(G)$ we mean the minimum size of a vertex set whose deletion leaves the graph acyclic.

Nowhere dense graphs. A graph *H* is a *minor* of a graph *G*, denoted $H \preceq G$, if there exists a mapping that associates each vertex v of H with a non-empty connected subgraph G_v of G such that G_u and G_v are disjoint for $u \neq v$ and whenever there is an edge between *u* and *v* in *H*, there is an edge between a vertex of G_u and a vertex of G_v . The subgraph G_v is referred to as the *branch set* of *v*. We call *H* a *depth-r minor* of *G*, denoted $H \leq_r G$, if each branch set of the mapping induces a graph of radius at most *r*.

Definition 2.2. A class C is *nowhere dense* if there exists a function $t : \mathbb{N} \to \mathbb{N}$ such that $K_{t(r)} \nleq r G$ for all $r \in \mathbb{N}$ and all $G \in \mathscr{C}$.

An *r-independent set* in a graph *G* is a set of vertices *I* such that the distance between any two vertices of *I* is at least $r + 1$. We make use of the fact that nowhere dense classes are uniform quasi-wide, as clarified by the following theorem.

Theorem 2.1 ([\[18,](#page-47-7) [22\]](#page-48-2)). Let $\mathscr C$ be a nowhere dense class of graphs. For all $r \in \mathbb N$, there is a polynomial $N_r : \mathbb{N} \to \mathbb{N}$ and a constant $x_r \in \mathbb{N}$ such that following holds. Let $G \in \mathscr{C}$ and let $A \subseteq V(G)$ be a vertex subset of size at least $N_r(m)$, for a given $m \in \mathbb{N}$. Then there exists a set $X \subseteq V(G)$ of size $|X| \leq x_r$ and a set $B \subseteq A \setminus X$ of size at least *m* that is *r*-independent in *G* − *X*. Moreover, given *G* and *A*, such sets *X* and *B* can be computed in time $\mathcal{O}(|A| \cdot |E(G)|)$.

Biclique-free graphs. A graph is said to be *d*-biclique-free it excludes the biclique $K_{d,d}$ as a subgraph.

Definition 2.3. A class \mathscr{C} of graphs is *biclique-free* if there exists a number *d* such that all $G \in \mathscr{C}$ are *d*-biclique-free.

An inclusion diagram of all presented graph classes is depicted in [Figure 2.](#page-5-0)

Solution discovery. A vertex (edge) subset problem Π is a problem defined on graphs such that a solution consists of a subset of vertices (edges) satisfying certain requirements. For a vertex (edge) subset problem Π on an instance with an input graph G , a *configuration* C on G is a subset of its vertices (edges). Alternatively, a configuration can be seen as the placement of tokens on a subset of vertices (edges) in G . In the *token sliding* model, a configuration C' can be obtained (in one step)

Figure 2: Graph classes considered in this paper. Arrows indicate inclusion.

from a configuration *C*, written $C \vdash C'$, if $C' = (C \setminus \{y\}) \cup \{x\}$ for elements $y \in C$ and $x \notin C$ such that *x* and *y* are neighbors in *G*, that is, if $x, y \in V(G)$, then $xy \in E(G)$; and if $x, y \in E(G)$, then they share an endpoint. Alternatively, when a token *slides* from a vertex to an adjacent one or from an edge to an incident one, we get $C \vdash C'$. A *discovery sequence* of length ℓ in G is a sequence of configurations $C_0C_1 \ldots C_\ell$ of *G* such that $C_i \vdash C_{i+1}$ for all $0 \leq i < \ell$.

The Π-Discovery problem is defined as follows. We are given a graph *G*, a configuration $S \subseteq V(G)$ (resp. $S \subseteq E(G)$) of size k (which at this point is not necessarily a solution for Π), and a budget *b* (a non-negative integer). We denote instances of Π -DISCOVERY by (G, S, b) . The goal is to decide whether there exists a discovery sequence $C_0C_1 \ldots C_\ell$ in *G* for some $\ell \leq b$ such that $S = C_0$ and C_{ℓ} is a solution for Π . When a path decomposition is given as part of the input, the instances are denoted by (G, \mathcal{P}_G, S, b) to highlight that the path decomposition \mathcal{P}_G of *G* is provided.

Parameterized complexity and kernelization. Downey and Fellows [\[10\]](#page-47-8) developed a framework for parameterized problems which include a parameter *p* in their input. A parameterized problem Π has inputs of the form (x, p) where $|x| = n$ and $p \in \mathbb{N}$. Fixed-parameter tractable problems belong to the complexity class FPT. The class XNLP consists of the parameterized problems that can be solved with a non-deterministic algorithm that uses $f(p) \cdot \log n$ space and $f(p) \cdot n^{\mathcal{O}(1)}$ time. The W-hierarchy is a collection of parameterized complexity classes FPT ⊆ W[1] ⊆ W[2] ⊆ ... ⊆ XNLP where inclusions are conjectured to be strict.

For parameterized problems Π and Π′ , an FPT*-reduction* from Π to Π′ is a reduction that given an instance (x, p) of Π produces (x', p') of Π' in time $f(p) \cdot |x|^{\mathcal{O}(1)}$ and such that $p' \leq g(p)$ where *f*, *g* are computable functions. A *pl-reduction* from Π to Π' is one that additionally computes (x', p') using $\mathcal{O}(h(p) + \log |x|)$ working space where h is a computable function. We write $\Pi \leq_{\text{FPT}} \Pi'$ (resp. Π ≤pl Π′) if there is an FPT-reduction (resp. pl-reduction) from Π to Π′ . If Π is W[*t*]-hard for a positive integer *t* and $\Pi \leq_{\text{FPT}} \Pi'$, then Π' is also W[*t*]-hard. If Π is XNLP-hard and $\Pi \leq_{\text{pl}} \Pi'$, then Π' is XNLP-hard and, in particular, $W[t]$ -hard for all $t \geq 1$.

Every problem that is in FPT admits a kernel, although it may be of exponential size or larger. Under the complexity-theoretic assumption that $NP \not\subseteq \text{coNP/poly}$, we can rule out the existence of a polynomial kernel for certain fixed-parameter tractable problems Π. The machinery for such kernel lower bounds heavily relies on composing instances that are equivalent according to a polynomial equivalence relation [\[7\]](#page-46-4).

Definition 2.4*.* An equivalence relation R on the set of instances of a problem Π is called a *polynomial equivalence relation* if the following two conditions hold.

- 1. There is an algorithm that given two instances *x* and *y* of Π decides whether *x* and *y* belong to the same equivalence class in time polynomial in $|x| + |y|$.
- 2. For any finite set *S* of instances of Π, the equivalence relation R partitions the elements of *S* into at most $(\max_{x \in S} |x|)^{O(1)}$ classes.

We can compose equivalent instances in more than one way. We focus here on or-crosscompositions.

Definition 2.5 ([\[4\]](#page-46-3)). Let Π' be a problem and let Π be a parameterized problem. We say that Π $or-cross-composes$ into Π' if there is a polynomial equivalence relation R on the set of instances of Π and an algorithm that, given *t* instances (where $t \in \mathbb{Z}_+$) x_1, x_2, \ldots, x_t belonging to the same equivalence class of \mathcal{R} , computes an instance (x^*, k^*) in time polynomial in $\Sigma_{i=1}^t |x_i|$ such that the following properties hold.

1. $(x^*, k^*) \in \Pi$ if and only if there exists at least one index *i* such that x_i is a yes-instance of Π' .

2. k^* is bounded above by a polynomial in $\max_{i=1}^t |x_i| + \log t$.

The inclusion $NP \subseteq \text{coNP}/\text{poly}$ holds if an NP-hard problem or-cross-composes into a parameterized problem Π having a polynomial kernel. As this inclusion is believed to be false, we will constantly make use of the following theorem to show that the existence of a polynomial kernel is unlikely.

Theorem 2.2 ([\[4\]](#page-46-3))*.* If a problem Π′ is NP-hard and Π′ or-cross-composes into the parameterized problem Π, then there is no polynomial kernel for Π unless NP ⊆ coNP*/*poly.

We refer the reader to textbooks [\[7,](#page-46-4) [11\]](#page-47-4) for more on parameterized complexity and kernelization.

3 An Auxiliary Problem and Foundational Gadgets

In this section, we describe foundational gadgets used in our reductions and compositions and explain how combining such gadgets preserves a bound on the pathwidth of the constructed graphs (assuming we start with graphs of bounded pathwidth). We show first that starting from a graph of bounded pathwidth *H*, we can construct new graphs G_H , \tilde{G}_H , G_t , and \hat{G}_t , using our gadgets such that G_H , \tilde{G}_H , G_t , and \hat{G}_t still have bounded pathwidth (in addition to other useful properties).

The following problem will be used in the reductions that establish the XNLP-hardness of IS-D, VC-D and DS-D with respect to parameter *pw* and subsequently in the or-cross-compositions that render it unlikely for any of these problems to have a polynomial kernel with respect to parameter $b + pw$. We denote by *orientation* of a graph *G* a mapping $\lambda : E(G) \to V(G) \times V(G)$ such that $\lambda(uv) \in \{(u, v), (v, u)\}.$

MINIMUM MAXIMUM OUTDEGREE (MMO):

Input: Undirected weighted graph *H*, a path decomposition \mathcal{P}_H of *H* of width *pw*, an edge weighting σ : $E(H) \rightarrow \mathbb{Z}_+$ and a positive integer *r* (all integers are given in unary).

Question: Is there an orientation of *H* such that for each $v \in V(H)$, the total weight of the edges directed away from *v* is at most *r*?

Bodlaender et al. [\[2\]](#page-46-5) showed that MMO is XNLP-complete with respect to pathwidth given a path decomposition realising the pathwidth. If all edge weights are identical, then MMO (on general graphs) can be solved in polynomial time using network flows [\[1\]](#page-46-6).

For an instance $(H, \mathcal{P}_H, \sigma, r)$ of MMO, we define $\sigma = \sum_{e \in E(H)} \sigma(e)$, $n = |V(H)|$ and $m = |E(H)|$. We construct for an instance $(H, \mathcal{P}_H, \sigma, r)$ of MMO, a graph G_H consisting of disjoint subgraphs G_e for each $e \in E(H)$ and G_v for each $v \in V(H)$. We refer to the edge-based and vertex-based subgraphs as *MMO-edge-gadgets* and *MMO-vertex-gadgets*, respectively. For an edge $e \in E(H)$ we refer to G_e as *MMO-edge-e*. Similarly, for a vertex $v \in V(H)$ we refer to G_v as *MMO-vertex-v*.

MMO-edge-e. For an edge $e = uv \in E(H)$, an MMO-edge- $e \ G_e$ contains $\sigma(e) + 1$ edges with endpoints a_e^i and b_e^i for $i \in [\sigma(e)+1]$, and an edge $e^u e^v$ such that $b_e^{\sigma(e)+1}$ is adjacent to each of e^u and e^v . We define $A_e = \bigcup_{i \in [\sigma(e)]} a_e^i$ and $B_e = \bigcup_{i \in [\sigma(e)]} b_e^i$ (see [Figure 3\)](#page-7-0). We refer to the connected component inside G_e (or any subdivision of G_e) containing e^u and e^v by G_e^{sel} .

Figure 3: An MMO-edge-*e* G_e for an edge $uv = e \in E(H)$ for a graph *H* and edge weight function σ of an MMO instance, with $\sigma(e) = 4$.

MMO-vertex-v. For a vertex *v* in $V(H)$, an MMO-vertex-*v* G_v contains a *representative vertex of v* denoted by w_v , adjacent to *r* target vertices of *v* denoted by $x_v^1, x_v^2, \ldots, x_v^r$ and one extra vertex x_v^{r+1} . Additionally, for each edge $e \in E(H)$ incident to *v*, the MMO-vertex-*v* contains $\sigma(e)$ edges with endpoints $y_e^{v(i)}$ and $z_e^{v(i)}$ for $i \in [\sigma(e)]$ such that $y_e^{v(i)}$ is adjacent to w_v , the representative vertex of v (see [Figure 4\)](#page-7-1). We define $X_v = \bigcup_{i \in [r]} x_v^i$, $Y_e^v = \bigcup_{i \in [\sigma(e)]} y_e^{v(i)}$, $Z_e^v = \bigcup_{i \in [\sigma(e)]} z_e^{v(i)}$, $Y^v = \bigcup_{e \in E(H)} Y^v_e$, and $Z^v = \bigcup_{e \in E(H)} Z^v_e$.

Figure 4: An MMO-vertex-*v* G_v for a vertex $v \in V(H)$ for a graph *H*, edge weight function σ , and integer *r* of an MMO instance. The vertex *v* is incident to edges $e_1, e_2 \in E(H)$, $\sigma(e_1) = 3$, $\sigma(e_2) = 2$, and $r = 4$.

The graph G_H **.** We let $A = \bigcup_{e \in E(H)} A_e$, $A^+ = \bigcup_{e \in E(H)} a_e^{\sigma(e)+1}$, $B = \bigcup_{e \in E(H)} B_e$, $B^+ =$ $\cup_{e \in E(H)} \quad b_e^{\sigma(e)+1}, X = \cup_{v \in V(H)} \quad X_v, X^+ = \cup_{v \in V(H)} \quad x_v^{r+1}, Y = \cup_{v \in V(H)} \quad Y^v, \text{ and } Z = \cup_{v \in V(H)} \quad Z^v.$ We form G_H by connecting its MMO-edge-gadget vertices to its MMO-vertex-gadget vertices as follows. For a vertex $v \in V(H)$ and edge $e \in E(H)$ incident to *v*, we connect each vertex of B_e to a corresponding distinct vertex in Z_e^v (in other words, each b_e^i to $z_e^{v(i)}$ for $i \in [\sigma(e)]$). Similarly, we connect e^v to each vertex of Y_e^v (see [Figure 5](#page-8-0) for an example).

Figure 5: Edges from one MMO-edge-*e*, for an edge $e = uv$ for a graph *H*, edge weight function σ , and integer *r* of an MMO instance, to the MMO-vertex- u and MMO-vertex- v subgraphs in G_H . Red is used for edges between vertices in *B* and *Z* and yellow is used for edges between vertices in $\{e^u, e^v\}$ and *Y*. $\sigma(e) = 2$ and $r = 4$.

The supplier gadget and the graph \tilde{G}_H . In some of our reductions, we add a new gadget to G_H and make one of its vertices the *supplier vertex* adjacent to various vertices within G_H . We denote the graph thus obtained by G_H and refer to the gadget containing the supplier vertex as the *supplier gadget*. We let G_s be the supplier gadget that we connect to G_H , and we let *s* denote the supplier vertex. In particular, G_s contains a supplier vertex *s* that is adjacent to *donor vertices* d_1^i of the *donor paths* $D^i = \{d_1^i, d_2^i, d_3^i\}$ for $i \in [rn - \sigma]$ as well as another vertex $d_1^{rn - \sigma + 1}$ (see [Figure 6\)](#page-8-1).

Figure 6: G_s for a graph *H*, edge weight function σ , and integer r, such that $r_n - \sigma = 3$.

Pathwidth of G_H **,** \tilde{G}_H **, and their subdivisions. Our reductions and compositions must use** at most $\mathcal{O}(h(pw) + \log |x|)$ working space, for an input instance of size |x| and parameter *pw*, and a computable function *h*. We show that our reductions/compositions can be performed on a log-space transducer and are pl-reductions. A log-space transducer is a type of Turing machine with a read-only input tape, a read/write work tape of logarithmic size and a write-only, write-once output tape.

Lemma 3.1. Let (H, \mathcal{P}_H, w, r) be an instance of MMO. Then, there exists a log-space transducer that transforms a path decomposition of *H* to one of G_H (resp. \tilde{G}_H , or any subdivision of G_H , or any subdivision of \tilde{G}_H) with width at most $pw(H) + 6$ (resp. $pw(H) + 7$, or $pw(H) + 6$, or $pw(H) + 7$. Thus, $pw(G_H) \leq pw(H) + 6$, and $pw(\tilde{G}_H) \leq pw(H) + 7$, and any subdivision of G_H or \tilde{G}_H results in a graph of bounded pathwidth.

Proof. The final statement of the lemma follows from the preceding statement. Thus, we build log-space transducers for the graphs G_H , \tilde{G}_H and their subdivisions and we start with G_H .

Given the path decomposition of *H*, we first ensure that it is nice (which can be done via a log-space transducer [\[17\]](#page-47-9)). Then, we pass through the bags from left to right. For a forget bag in the path decomposition of *H*, we output a bag containing the representative vertices (of the vertex gadgets) of the vertices in the forget bag. For a bag that introduces a vertex $v \in V(H)$, we output the following bags in order:

- 1. for $j \in [r+1]$, we output one bag that introduces the vertex x_v^j , followed by one that forgets the same vertex (these bags have a size larger than the pathwidth of *H* by only 1),
- 2. for each vertex *u* in the bag such that $u \neq v$ and $uv = e \in E(H)$:
	- (a) we output four bags that introduce the vertices e^u , e^v , $b_e^{\sigma(e)+1}$, and $a_e^{\sigma(e)+1}$, respectively, followed by two bags that forget the vertices $b_e^{\sigma(e)+1}$, and $a_e^{\sigma(e)+1}$, respectively (these bags have a size larger than the pathwidth of *H* by only 4),
	- (b) for $j \in [\sigma(e)]$, we output bags that introduce the vertices $a_e^j, b_e^j, z_e^{u(j)}, y_e^{u(j)}, z_e^{v(j)}$ and $y_e^{v(j)}$, followed by bags that forget all those vertices (these bags have a size larger than the pathwidth of *H* by only 6),
	- (c) then, we output two bags that forget the vertices e^u and e^v , respectively.

It is easy to verify that the result is a nice path decomposition of the graph *GH*. The width has increased by at most 6.

For the graph G_H , we change the log-space transducer for G_H to output at first a bag that introduces the supplier vertex. Additionally, we then let the same log-space transducer output for each $i \in [rn - \sigma]$, bags that represent the path decompositions of each of the donor paths (augmented by the supplier vertex). The log-space transducer then outputs a bag containing the supplier vertex and the vertex $d^{rn- $\sigma+1}$ followed by a bag that forgets $d^{rn- $\sigma+1}$. The log-space$$ transducer finally behaves similarly to that of *G^H* but augments each of the then outputted bags by the supplier vertex. It is easy to verify that the result is a nice path decomposition of the graph G_H . The width has increased by at most 7.

The following claim finalizes the proof of the lemma.

Claim 1*.* A log-space transducer that takes as input a nice path decomposition of a graph *G* and outputs a path decomposition of a graph *G*′ can be adapted to output a path decomposition of any subdivision of G' with width $pw(G')$.

Proof. Note that for any edge subdivision of edges uv_1, \ldots, uv_q incident to a vertex *u* in the graph *G*, that introduce vertices w_1, \ldots, w_q to the graph, the log-space transducer can be adapted to output directly before the bag that introduces v_i for $i \in [q]$, a bag that introduces w_i and before any bag that introduces a neighbor of v_i one bag that forgets the vertex w_i . If some vertices $v_i, \ldots, v_{i'}$ have no neighbors, the log-space transducer can be adapted to output bags that introduce $w_i, \ldots, w_{i'}$ just before the vertex *u* is forgotten and only output the bags that introduce the vertices $v_i, \ldots, v_{i'}$ after the vertex u is forgotten. \triangleleft

It is easy to see then that [Claim 1](#page-9-0) can be used to prove the existence of a log-space transducer that outputs a path decomposition of any subdivision of G_H (resp. \tilde{G}_H) of the same width of a path decomposition of G_H (resp. \tilde{G}_H). \Box

We note here that in the DS-D reduction and composition, we may augment subdivisions of *G^H* (resp. \tilde{G}_H), by an edge *dd'* (*d* and *d'* are new vertices, and we refer to *d* as the *dominator vertex*) where *d* is adjacent to various vertices in the subdivisions of G_H (resp. G_H). We denote the resulting graphs by *augmented subdivisions of* G_H (resp. G_H). By Observation [2.1,](#page-4-0) this modification can increase the pathwidth of those graphs by at most 2. A log-space transducer for such modified graphs can be built by adapting one of the log-space transducers from [Lemma 3.1](#page-8-2) to first output bags that introduce the vertices *d* and *d'* and only forget them at the end of the path decomposition.

Corollary 3.1. Let (H, \mathcal{P}_H, w, r) be an instance of MMO. Then, there exists a log-space transducer that transforms a path decomposition of *H* to one of an augmented subdivision of *G^H* (resp. G_H) with width at most $pw(H) + 8$ (resp. $pw(H) + 9$).

MMO-instance-selector. In our or-cross-compositions, we assume that we are given as input a family of *t* MMO instances $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$, where for each $j \in [t]$, H_j is a bounded-pathwidth graph with path decomposition \mathcal{P}_{H_j} , $|V(H_j)| = n$, $|E(H_j)| = m$, $\sigma_j : E(H_j) \to \mathbb{Z}_+$ such that $\sum_{e_j \in E(H_j)} \sigma_j(e_j) = \sigma$ and $r_j = r \in \mathbb{Z}_+$ (integers are given in unary). It is not hard to see that these instances belong to the same equivalence class of a polynomial equivalence relation $\mathcal R$ [\(Definition 2.4\)](#page-5-1) whose polynomial-time algorithm decides that two instances are equivalent if they have the same number of vertices, number of edges, and total weight on the edges. R also has at most $\max_{x \in S} |x|^{\mathcal{O}(1)}$ equivalence classes, where *S* is a set of MMO instances of the form $(H, \mathcal{P}_H, \sigma, r)$, where *H* is of bounded pathwidth. In particular it has at most $m \cdot n \cdot (\max_{x \in S} |x|)$ equivalence classes.

Some of our or-cross-compositions will encode, in a graph *G^t* , all *t* input instances of MMO in (y^*, k^*) [\(Definition 2.5\)](#page-6-1) using the multiple induced subgraphs G_{H_j} for $j \in [t]$. We must also encode the OR behavior. An *instance selector* is a gadget with *t* possible states, each corresponding to a distinct instance x_j for $j \in [t]$ and compelling us to select x_j so that (x^*, k^*) is solved. We form an instance selector by constructing a new gadget, called a *MMO-instance-selector*. In *G^t* , we make some of the MMO-instance-selector vertices adjacent to various vertices of G_{H_j} for $j \in [t]$.

An MMO-instance-selector contains, for each $j \in [t]$, an edge with endpoints SELECT_j and UNSELECT_j. It also contains edges $f^1g^1, f^2g^2, \ldots, f^{\sigma}g^{\sigma}$ and a *weights-hub vertex h* adjacent to each vertex f^i for $i \in [\sigma]$. It also comprises edges $o^1p^1, o^2p^2, \ldots, o^mp^m$ and an *orientations-quay vertex* q adjacent to each vertex o^i for $i \in [m]$.

Figure 7: An MMO-instance-selector for $t = 3$ MMO instances $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ with $|E(H_j)| = m = 4$, edge weight function σ_j such that $\sum_{e_j \in E(H_j)} \sigma_j(e_j) = \sigma = 5$, and integers $r_j = r \in \mathbb{Z}_+$.

In *G^t* , we will make the vertices *h* and *q* adjacent to different vertices in the *t* induced subgraphs G_{H_j} for $j \in [t]$. Additionally, the vertices SELECT_j or UNSELECT_j for $j \in [t]$ will also be adjacent to different vertices within their corresponding induced subgraph *GH^j* . For some source problems, we may additionally augment subdivisions of *G^t* by attaching to *h* and *q* a number of pendant vertices. We denote the resulting graphs by *augmented subdivisions of G^t* .

Lemma 3.2. There exists a log-space transducer that given *t* MMO instances $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$, where for each $j \in [t]$, $|V(H_j)| = n$, $|E(H_j)| = m$, $\sigma_j : E(H_j) \to \mathbb{Z}_{>0}$ is such that $\sum_{e_j \in E(H_j)} \sigma_j(e_j) = \sigma$, and $r_j = r \in \mathbb{Z}_+$ (integers are given in unary), outputs a path decomposition of the graph G_t (resp. any augmented subdivision of G_t) with width at most $\max_{i \in [t]} p w(H_i) + 10$. Thus, the graph G_t and any augmented subdivision of it are graphs of bounded pathwidth.

Proof. The last statement of the lemma follows from the preceding statement. Thus, we build log-space transducers for the graphs G_t and its augmented subdivisions and we start with a log-space transducer for (an augmented) G_t . An augmented G_t is G_t with a number of pendant vertices attached to *h* and *q*. We first ensure that the path decompositions of H_j for each $j \in [t]$ are nice (which can be done via a log-space transducer). Afterwards, the log-space transducer outputs bags that introduce the vertices *h* and *q*, introduce and forget the pendant vertices attached to *h* or *q* in the case of an augmented *G^t* one-by one, and then outputs bags that represent the path decompositions of the edges $f^1g^1, f^2g^2, \ldots, f^{\sigma}g^{\sigma}, o^1p^1, o^2p^2, \ldots, o^mp^m$, augmented by the vertices h and *q*. Next, the log-space transducer outputs for each $j \in t$, the bags in the path decomposition of the graph *GH^j* (i. e., behaves as the log-space transducer of [Lemma 3.1](#page-8-2) that outputs a path decomposition of the graph G_H) but augmented by the vertices h, q , SELECT_j and UNSELECT_j, followed by bags that forget the vertices SELECT_j and UNSELECT_j . It is easy to see that the result is a path decomposition of (an augmented) G_t with width max_{j∈[*t*]} $pw(H_j) + 10$ (as the path decomposition of G_{H_j} for any $j \in [t]$ has width at most $\max_{j \in [t]} pw(H_j) + 6$.

Using [Claim 1,](#page-9-0) we can build a log-space transducer for any augmented subdivision of G_t that outputs a path decomposition of the subdivision with width $\max_{i \in [t]} p w(H_i) + 10$. \Box

In the DS-D composition, we form the graph \hat{G}_t in a manner akin to a subdivision of G_t except, we encode each of the *t* input instances of MMO using the multiple induced subgraphs that are augmented subdivisions of G_{H_j} for $j \in [t]$. Using [Corollary 3.1](#page-10-0) instead of [Lemma 3.1](#page-8-2) in the proof of [Lemma 3.2,](#page-11-0) the log-space transducer can output for each $j \in [t]$, the bags in the path decomposition of an augmented subdivision of *GH^j* , and we get the following.

Corollary 3.2. There exists a log-space transducer that given *t* MMO instances $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$, where for each $j \in [t]$, $|V(H_j)| = n$, $|E(H_j)| = m$, $\sigma_j : E(H_j) \to \mathbb{Z}_+$ is such that $\sum_{e_j \in E(H_j)} \sigma_j(e_j) = \sigma$, and $r_j = r \in \mathbb{Z}_+$ (integers are given in unary), outputs a path decomposition of the graph \hat{G}_t (resp. any subdivision of \hat{G}_t) with width at most $\max_{j \in [t]} pw(H_j) + 12$. Thus, the graph \hat{G}_t and any subdivision of it are graphs of bounded pathwidth.

Corollary 3.3. Given an MMO instance $(H, \mathcal{P}_H, \sigma, r)$, one can build a log-space transducer that outputs a path decomposition of (any subdivision of) G_H , (resp. (any subdivision of) \tilde{G}_H , or an augmented subdivision of G_H , or an augmented subdivision of G_H) with width at most $pw(H) + 6$ (resp. $pw(H) + 7$, or $pw(H) + 8$, or $pw(H) + 9$), along with a representation of the graph, any subset of its vertices, and an integer with at most a polynomial (in the input size) number of bits.

Corollary 3.4. Given *t* MMO instances $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$, where for each $j \in [t]$, $|V(H_j)| = n$, $|E(H_j)| = m$, σ_j is such that $\sum_{e_j \in E(H_j)} \sigma_j(e_j) = \sigma$ and $r_j = r \in \mathbb{Z}_+$ (integers are given in unary), one can build a log-space transducer that outputs a path decomposition (of an augmented subdivision) of the graph G_t (resp. a path decomposition of the graph \hat{G}_t), with width at most $\max_{j \in [t]} p w(H_j) + 10$ (resp. $\max_{j \in [t]} p w(H_j) + 12$), along with a representation of the graph, any subset of its vertices, and an integer with at most a polynomial (in the input size) number of bits.

4 Vertex Cover Discovery

Fellows et al. [\[14\]](#page-47-2) showed that VC-D is in FPT with respect to parameter *k* on general graphs and in FPT with respect to parameter *b* on nowhere dense classes of graphs. We show in this section that the problem has a polynomial kernel with respect to parameter *k*. With respect to the parameter $b + pw$, where pw is the pathwidth of the input graph, we show that the problem does not have a polynomial kernel unless NP ⊆ coNP*/*poly.

Theorem 4.1. VC-D has a kernel of size $\mathcal{O}(k^2)$.

Proof. Let (G, S, b) be an instance of VC-D. Let G' be the graph obtained from G by deleting the vertices of degree greater than *k*. If *G'* has more than k^2 edges or more than $2k^2$ non-isolated vertices we can reject the instance. The vertices of degree greater than *k* must be in any vertex cover of size at most *k*. The remaining vertices of the vertex cover can cover at most *k* edges each, as we have at most k vertices for the vertex cover, there can be at most k^2 edges left. These have at most $2k^2$ endpoints.

We now construct the kernel (H, S, b) . We define *H* to be the graph obtained from *G* as follows: We keep all non-isolated vertices of *G'* as well as all vertices that contain a token. Furthermore, we keep all vertices of *G* with degree greater than *k* (but not all their neighbors). For all *u, v* with degree greater than *k* in *G*, if $N_G(u) \cap N_G(v)$ contains only isolated vertices in *G'*, then we keep one arbitrary vertex of this intersection and name it *xuv*. These vertices need to be kept to ensure that all discovery sequences survive in *H*. Finally, for every vertex *u* of degree greater than *k* in *G*, if *u* has degree $d < k + 1$ in *H*, we add arbitrary $k + 1 - d$ isolated neighbors to *u*.

We claim that (H, S, b) is equivalent to (G, S, b) and has at most $3k^2 + 2k$ vertices: at most k vertices with degree at least $k+1$ (yielding $k(k+1)$ vertices), at most $2k^2$ non-isolated vertices from *G*′ and at most *k* isolated vertices with tokens on them.

It remains to show that the instances are equivalent. Assume (G, S, b) is a yes-instance. Consider a shortest discovery sequence $S = C_0 \vdash C_1 \vdash \ldots \vdash C_\ell$ for $\ell \leq b$. We claim that there exists a discovery sequence $S = C_0 \vdash C'_1 \vdash \ldots \vdash C'_{\ell-1} \vdash C_{\ell}$ in *H* of the same length that ends in the same configuration C_{ℓ} and that also constitutes a vertex cover in *H*. First observe that because we consider a shortest discovery sequence all C_i do not contain isolated vertices of G' unless they belong to *S*, or to $N_G(u) \cap N_G(v)$ for vertices *u, v* with degree greater than *k* in *G*. Furthermore, C_{ℓ} contains no isolated vertices of *G*′ unless they belong to *S*. Now every slide along a vertex *x* of $N(u) \cap N(v)$ that does not belong to *H* can be replaced by the slide along x_{uv} , that is, either $C_i' = C_i$ or $C_i' = (C_i \setminus \{x\}) \cup \{x_{uv}\}\$. As C_{ℓ} is a vertex of G and H is a subgraph of G, also C_{ℓ} is a vertex cover of *H*.

Conversely, assume (*H, S, b*) is a yes-instance. As *H* is a subgraph of *G*, every discovery sequence is also a discovery sequence in *G*. It remains to show that every vertex cover of size *k* of *H* is also a vertex cover of *G*. This easily follows from the fact that every vertex of degree greater than *k* in *G* is also a vertex of degree greater than *k* in *H* and every vertex cover of *H* must contain all vertices of degree greater than *k*. This implies that all edges between high degree vertices and isolated vertices in G' are covered in G . All other edges appear also in H and are hence covered in H as well as in *G*. \Box

Theorem 4.2*.* VC-D is XNLP-hard parameterized by pathwidth.

As stated in [Section 3,](#page-6-0) we present a pl-reduction from MMO. Let $(H, \mathcal{P}_H, \sigma, r)$ be an instance of MMO where *H* is a bounded pathwidth graph, $|V(H)| = n$, $|E(H)| = m$, $\sigma : E(H) \to \mathbb{Z}_+$ such that $\sum_{e \in E(H)} \sigma(e) = \sigma$ and $r \in \mathbb{Z}_+$ (integers are given in unary). We construct an instance $(\tilde{G}_H, \mathcal{P}_{\tilde{G}_H}, S, b)$ of VC-D as follows. We form the graph \tilde{G}_H as outlined below (see [Figure 8\)](#page-14-0):

- (a) We subdivide each edge $a^i b^i$ for each $i \in [\sigma(e)]$ for each edge $e \in E(H)$, of a subgraph G_e (which is the MMO-edge-*e* described in [Section 3\)](#page-6-0), and add it to \tilde{G}_H . We denote the introduced vertex (from a subdivision of an edge $a^i b^i$) by c^i . We let $C_e = \bigcup_{i \in [w(e)]} c^i$, $C = \bigcup_{e \in E(H)} C_e$.
- (b) We subdivide each edge $w_v x^{v(i)}$ for $i \in [r]$, of a subgraph G_v (which is the MMO-vertex-*v* described in [Section 3\)](#page-6-0), for each vertex $v \in V(H)$, and add it to \tilde{G}_H . We denote the introduced vertex (from a subdivision of an edge $w_v x^{v(i)}$) by $c(x^{v(i)})$. We let $C(X_v) = \bigcup_{i \in [r]} c(x^{v(i)})$, $C(X) = \bigcup_{v \in V(H)} C(X_v).$
- (c) As described in [Section 3](#page-6-0) (under the graph G_H heading), we make each vertex b_e^i , for each edge $uv = e \in E(H)$, adjacent to the vertices in Z_e^v and Z_e^u , and each vertex e^v for each edge $uv = e \in E(H)$ adjacent to all vertices in Y_e^v .
- (d) We let the supplier gadget be G_s as described in [Section 3,](#page-6-0) add it to \tilde{G}_H , and make the vertex *s* adjacent to all vertices in *X*.

By [Lemma 3.1,](#page-8-2) \tilde{G}_H is of bounded pathwidth (it is a subdivision of the original graph \tilde{G}_H constructed in [Section 3\)](#page-6-0).

We set $S = C \cup B \cup Y \cup \bigcup_{uv=e \in E(H)} (e^u \cup e^v) \cup \bigcup_{v \in V(H)} w_v \cup s \cup \bigcup_{i \in [rn-\sigma]} (d_1^i \cup d_3^i)$ and $b = m + 3rn$. Given that all integers are given in unary, the construction of the graph G_H , or its path decomposition (as described in [Lemma 3.1\)](#page-8-2), and as a consequence the reduction, take time polynomial in the size of the input instance. Additionally, by [Corollary 3.3,](#page-11-1) this reduction is a pl-reduction. We claim that $(H, \mathcal{P}_H, \sigma, r)$ is a yes-instance of MMO if and only if $(\tilde{G}_H, \mathcal{P}_{\tilde{G}_H}, S, b)$ is a yes-instance of VC-D.

Lemma 4.1. If $(H, \mathcal{P}_H, \sigma, r)$ is a yes-instance of MMO, then $(\tilde{G}_H, \mathcal{P}_{\tilde{G}_H}, S, b)$ is a yes-instance of VC-D.

Proof. Let $\lambda : E(H) \to V(H) \times V(H)$ be an orientation of the graph *H* such that for each $v \in V(H)$, the total weight of the edges directed out of *v* is at most *r*. In \tilde{G}_H , the edges between $c(X)$ and X are not covered. The same applies for the edges between A^+ and B^+ . To fix that, for each edge $uv = e \in E(H)$ such that $\lambda(e) = (v, u)$:

- we move, for each $i \in [\sigma(e)]$, the token on $y_e^{v(i)}$ to any free vertex of $c(X_v)$ and the token on b_e^i to $z_e^{v(i)}$ (this consumes $3\sigma(e)$ slides),
- we slide the token on e^u to $b_e^{\sigma(e)+1}$, hence covering $a_e^{\sigma(e)+1}b_e^{\sigma(e)+1}$ (this consumes 1 slide).

Figure 8: Parts of the graph \tilde{G}_H constructed by the reduction of Theorem [4.2](#page-13-0) given an instance $(H, \mathcal{P}_H, \sigma, r)$, where *H* has three vertices *u, v,* and *w*, and two edges $e_1 = uv$ and $e_2 = uw$, and $r = 3$. Additionally, $\sigma(e_1) = 3$ and $\sigma(e_2) = 1$. For clarity, the edges between the vertices in B_{e_1} and $Z_{e_1}^u$ are missing. The same applies for the edges between e_1^v and the vertices of $Y_{e_1}^v$, the edges between e_1^u and the vertices of $Y_{e_1}^u$ as well as some of the edges between *s* and the vertices in *X*. Red, yellow, and blue edges are used to highlight the different types of edges used to connect the subgraphs $G_{e_1}, G_{e_2}, G_u, G_v, G_w$, and G_s of \tilde{G}_H , vertices in black are in *S* and those in white are not.

This constitutes $3\sigma + m$ slides. We cover the $rn - \sigma$ remaining uncovered edges between $c(X)$ and *X* using three slides per D^i path for $i \in [rn - \sigma]$ (by sliding the token on d_3^i to d_2^i , and moving the token on d_1^i to a token-free vertex in *X*). \Box

Lemma 4.2. If $(\tilde{G}_H, \mathcal{P}_{\tilde{G}_H}, S, b)$ is a yes-instance of VC-D, then $(H, \mathcal{P}_H, \sigma, r)$ is a yes-instance of MMO.

Proof. First, note that for an edge $a_e^{\sigma(e)+1}b_e^{\sigma(e)+1}$, where $uv = e \in E(H)$, to be covered with a minimal number of slides, the token on the vertex e^u or the token on the vertex e^v must move to $b_e^{\sigma(e)+1}$ (note that any other token on the vertices of the graph must pass through either e^u or e^v to get to $b_e^{\sigma(e)+1}$, thus we can safely assume that the token already on either of e^u or e^v is the token that slides to $b_e^{\sigma(e)+1}$). This consumes at least *m* slides, leaving 3*rn* slides.

No vertex cover formed with a minimal number of slides would need to make the token on the vertex *s* or the token on a vertex w_v for a vertex $v \in V(H)$ slide (as this token must always be replaced by another to cover the incident edges $sd^{rn-\sigma+1}$ or $w_v x^{r+1}$ for a vertex $v \in V(H)$, respectively, with a minimal number of slides, thus we can always assume that the token has not been moved). Thus, an edge between a pair of vertices in X_v and $C(X_v)$ can be covered by either moving the token on a vertex d_1^i for an integer $i \in [rn - \sigma]$ towards the vertex in X_v , or moving a token from a vertex $y_e^{v(i_1)}$, for an edge $uv = e \in E(H)$ and an integer $i_1 \in [\sigma(e)]$, towards the vertex in $C(X_v)$. If the token on d_1^i moves towards the vertex in X_v , the token on d_3^i must slide to d_2^i . If a token on $y_e^{v(i_1)}$ moves towards the vertex in $C(X_v)$, it must be the case that another token has moved to either the vertex $z_e^{v(i_1)}$ or to $y_e^{v(i_1)}$. This however requires at least one slide per such a token.

Thus, if an edge between a pair of vertices in *X* and *C*(*X*) is covered by moving a token on one vertex d_1^i for an integer $i \in [rn - \sigma]$ towards the vertex in *X*, it does not consume more slides than moving a token from a vertex in *Y* towards the vertex in $C(X)$. Given that at most $rn - \sigma$ edges can be covered using tokens from the donor paths (as $rn - \sigma + 1$ tokens are needed to cover G_s), each of the at least σ remaining uncovered edges must be covered by moving a token from a vertex in *Y* towards a vertex in $c(X)$. Additionally, each of the remaining uncovered edges between $c(X)$ and *X* will require at least one additional slide (besides the two slides needed to move a token from *Y*) and thus, tokens on distinct vertices in *Y* must be used to cover the edges, as the remaining at most σ slides do not allow to get any token not initially on a vertex in *Y* to a vertex in *Y*. This is true because, each $G_{e_1}^{sel}$ component for an edge $u_1v_1 = e_1 \in E(H)$ cannot have less than two tokens, thus if, w.l.o.g., we move a token from $e_1^{u_1}$ to Y^{u_1} , then we have to move another token onto the component. This also implies that if the token on $y_e^{v(i_1)}$ moves towards a vertex in $c(X_v)$, and consequently the token on the vertex e^v slides to $y_e^{v(i_1)}$, it will require at least one more slide as $e^u e^v$ will not be covered. Given that we have only σ remaining slides, and at least one slide for each of the remaining at least σ remaining uncovered edges is needed, the token on the vertex $b_e^{(i_1)}$ must slide to $z_e^{v(i_1)}$.

This totals *b* slides. Each vertex that is token-free in *Y* after the *b* slides are consumed must be adjacent to a vertex of the form $e_2^{u_2}$ with a token, for an edge $u_2v_2 = e_2 \in E(H)$ (so that the edges between $e_2^{u_2}$ and the vertices in \overline{Y} are covered). This implies that for each edge $u_2v_2 = e_2 \in E(H)$, at most $\sigma(e_2)$ tokens can move to $c(X)$ from tokens on the vertices of the sets $Y_{e_2}^{v_2}$ and $Y_{e_2}^{u_2}$, and from only one of those sets, as only one of $e_2^{u_2}$ and $e_2^{v_2}$ has a token. To cover the σ remaining uncovered edges, each edge $u_2v_2 = e_2 \in E(H)$ must allow $\sigma(e_2)$ tokens to move from either vertices in $Y_{e_2}^{v_2}$ and $Y_{e_2}^{u_2}$ and from at most one. This gives a feasible orientation for the instance $(H, \mathcal{P}_H, \sigma, r)$ as any of $c(X_u)$ or $c(X_v)$ can receive at most *r* tokens. \Box The proofs of Lemmas [4.1](#page-13-1) and [4.2](#page-15-0) complete the proof of Theorem [4.2.](#page-13-0)

Theorem 4.3*.* There exists an or-cross-composition from MMO into VC-D on bounded pathwidth graphs with respect to parameter *b*. Consequently, VC-D does not admit a polynomial kernel with respect to $b + pw$, where *pw* denotes the pathwidth of the input graphs, unless $NP \subseteq \text{coNP/poly}$.

Proof. As stated in [Section 3,](#page-6-0) we can assume that we are given a family of *t* MMO instances $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$, where H_j is a bounded pathwidth graph with path decomposition \mathcal{P}_{H_j} , $|V(H_j)| = n$, $|E(H_j)| = m, \sigma_j : E_j \to \mathbb{Z}_+$ is a weight function such that $\sum_{e_j \in E(H_j)} \sigma_j(e_j) = \sigma$ and $r_j = r \in \mathbb{Z}_+$ (integers are given in unary). The construction of the instance $(G_t, \mathcal{P}_{G_t}, S, b)$ of VC-D is twofold.

For each instance H_j for $j \in [t]$, we add to G_t the graph G_{H_j} formed as per the construction in [Theorem 4.2,](#page-13-0) but without the supplier gadget. We refer to the sets A, B, X, X^+, C, Y , and $c(X)$, subsets of vertices of a subgraph G_{H_j} of G_t , by A_j , B_j , X_j , X_j^+ , C_j , Y_j , and $c(X_j)$, respectively. Subsequently, we let $A = \bigcup_{j \in [t]} A_j$, $B = \bigcup_{j \in [t]} B_j$, $X = \bigcup_{j \in [t]} X_j$, and so on. We attach to each of the weights-hub vertex *h* and the orientations-quay vertex *q* of the MMO-instance-selector described in [Section 3,](#page-6-0) $2m + 5\sigma + 2$ pendant vertices. We add the MMO-instance selector and connect it to the rest of G_t as follows (see [Figure 9\)](#page-16-1). We make for each $j \in [t]$, the vertex SELECT_j adjacent to the vertices in $V(G_{H_j}) \cap S$, where *S* is as defined later. We make the vertex *h* adjacent to each vertex in *X* and the vertex *q* adjacent to each vertex of e^u and e^v for each edge $uv = e \in E(H_j)$ for each $j \in [t]$. By [Lemma 3.2,](#page-11-0) G_t is of bounded pathwidth (it is an augmented subdivision of the original graph G_t appearing in [Section 3\)](#page-6-0). Now, we set

$$
S = C \cup B \cup B^+ \cup Y \cup X \cup \bigcup_{\substack{j \in [t] \\ uv = e \in E(H_j)}} (e^u \cup e^v) \cup \bigcup_{\substack{j \in [t] \\ v \in V(H_j)}} w_v \cup \bigcup_{j \in [t]} \text{UNSELECT}_j \cup h \cup q
$$

and $b = 2m + 5\sigma + 1$.

Figure 9: Orange, pink, and green edges highlighting the different types of edges between an MMO-instance-selector of the composition in [Theorem 4.3](#page-16-0) and a subgraph G_{H_j} for a $j \in [t]$ of the same. H_j has 3 vertices u, v , and w , and two edges $e_1 = uv$ and $e_2 = uw$, and $r = 3$. Additionally, $\sigma_i(e_1) = 3$ and $\sigma_i(e_2) = 1$. For clarity, not all edges inside *G^H^j* are drawn, nor are all the pink edges depicted. Vertices in black are in *S* and those in white are not.

Given that all integers are given in unary, the construction of the graph G_t , or its path decomposition (as described in [Lemma 3.2\)](#page-11-0), and as a consequence the reduction take time polynomial in the size of the input instances. Additionally, by [Corollary 3.4,](#page-12-2) this composition is a pl-reduction. We claim that $(G_t, \mathcal{P}_{G_t}, S, b)$ is a yes-instance of VC-D if and only if for some $j \in [t]$, $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ is a yes-instance of MMO.

Claim 2. If for some $j \in [t]$, $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ is a yes-instance of MMO, then $(G_t, \mathcal{P}_{G_t}, S, b)$ is a yes-instance of VC-D.

Proof. Let $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ be a yes-instance of MMO and let λ be a feasible orientation of H_j such that for each $v \in V(H_j)$, the total weight of the edges directed out of *v* is at most *r*. In G_t , the edges $f^1g^1,\ldots,f^{\sigma}g^{\sigma},o^1p^1,\ldots,o^mp^m$ are not covered. First, we slide the token on UNSELECT_j to SELECT_j. Using 2*m* slides, we move for each edge $e \in E(H_j)$ the token on $e^u(e^v)$, if $\lambda(e) = (v, u)$ $(\lambda(e) = (u, v))$, towards a token-free vertex in o^1, \ldots, o^m . We additionally slide each token on a vertex b_e^i for $i \in [\sigma_j(e)]$ to the vertex $z_e^{v(i)}$, move the token on $y_e^{v(i)}$ towards a token-free vertex in $c(X_v)$ and consequently, move the token on the adjacent vertex in X_v towards a token-free vertex in f^1, \ldots, f^{σ} . The total number of slides performed is *b* and they achieve a configuration for the tokens that covers all of G_t . . And the contract of \mathcal{A}

Claim 3. If $(G_t, \mathcal{P}_{G_t}, S, b)$ is a yes-instance of VC-D, then there exists an integer $j \in [t]$, such that $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ is a yes-instance of MMO.

Proof. In any solution that uses the minimal number of slides, the tokens on the vertices h, q, w_v for each $v \in V(H_i)$ and integer $j \in [t]$, and on the vertices in C do not need to be moved (as these tokens must be replaced by others to cover the edges incident to the pendant vertices and *h*, or the pendant vertices and *q*, or to cover the edges $w_v x^{r+1}$, or the edges incident to the vertices in *A*, thus we can assume these tokens remain stationary). In the same solution, we can similarly assume that a token on one of UNSELECT_j and SELECT_j for each $j \in [t]$ remains on either one of those vertices. To cover the edges o^1p^1, \ldots, o^mp^m and $f^1g^1, \ldots, f^{\sigma}g^{\sigma}$, at least $2m + 2\sigma$ slides are needed to get tokens from one or more of the vertices in *X* onto the vertices f^1, \ldots, f^{σ} , and from one or more of the vertices of the form e^u for an edge $e \in E(H_j)$ incident to a vertex $u \in V(H_j)$ for an integer $j \in [t]$, onto the vertices o^1, \ldots, o^m . If a token is moved out of a subgraph G_{H_j} (for an integer $j \in [t]$ of G_t , which is bound to happen to get tokens onto the vertices $f^1, \ldots, f^{\sigma}, o^1, \ldots, o^m$, at least one slide is needed to cover the edge between now token-free vertices in G_{H_j} and $\text{SELET}j$ and exactly one slide can only be achieved by sliding the token on UNSELECT_j to SELECT_j (since otherwise a token has to move from one of the vertices of a subgraph $G_{H_{j'}}$ for $j' \neq j \in [t]$ into G_{H_j} , and this requires more than one slide).

W.l.o.g. assume a token on a vertex, denoted x_v^i , in X, for a vertex $v \in V(H_i)$, and integers $j \in [t]$ and $i \in [r]$, is moved to one of the vertices f^1, \ldots, f^{σ} , then at least 2 slides are needed to move a token into either x_v^i or $c(x_v^i)$ (since the tokens on w_v and *h* are assumed to be stationary). Since a token moving from any other vertex, except x_v^i , in *X* into x_v^i can replace the token on x_v^i in moving into one of the vertices f^1, \ldots, f^{σ} , in a solution that uses the minimal number of slides 2 slides can only be achieved by moving a token on a vertex, denoted $y_e^{v(i_1)}$, in Y^v , for some edge $e \in E(H_i)$ adjacent to *v* and some integer $i_1 \in [\sigma_i(e)]$, to $c(x_v^i)$. Additionally, 3 slides can only be achieved by moving a token on the same vertex to x_v^i . Since in a solution that uses the minimal

number of slides a token on one of UNSELECT; and SELECT; is assumed to remain on either of those vertices, and a token in *B* can slide at most one slide to a vertex in *Z*, if a token on $y_e^{v(i_1)}$ is moved to a vertex in $c(X)$ (or X), either a token has to move to the vertex $z_e^{v(i_1)}$, or a token has to slide from the vertex e^v to $y_e^{v(i_1)}$.

Given the budget and the fact that σ tokens in any solution must move from *X* onto the vertices f^1, \ldots, f^{σ} , tokens must move from distinct vertices in *X* onto the vertices f^1, \ldots, f^{σ} and from distinct vertices of the form e^u for an edge $e \in E(H_j)$ incident to a vertex $u \in V(H_j)$ for an integer $j \in [t]$, onto the vertices o^1, \ldots, o^m . Additionally, given the budget, tokens in the same solution must move onto f^1, \ldots, f^{σ} from only the vertices in X_j and onto o^1, \ldots, o^m from only the vertices of the form e_1^u , for an edge $uw = e_1 \in E(H_i)$ (note that one token sliding to SELECT_i will cover the edge between SELECT_j and e_1^u and the edge between SELECT_j and a vertex in X_j). In the same solution, if a token moves from the vertex e_1^u onto one of the vertices o^1, \ldots, o^m , the token on e_1^w remains stationary as the budget does not allow for another token to move into either one of the adjacent vertices e_1^u and e_1^w . To fill all of o^1, \ldots, o^m with tokens, exactly one token must move from $G_{e_2}^{sel}$ onto the vertices o^1, \ldots, o^m for each edge $e_2 \in E(H_i)$. The latter implies that the token on e^v does not move to $y_e^{v(i_1)}$ and given the budget that the token on $b_e^{i_1}$ slides to $z_e^{v(i_1)}$.

W.l.o.g. assume that the token on e^v does not move to one of o^1, \ldots, o^m , then at most the $\sigma(e)$ tokens on the vertices of Y_e^v can be sent to $c(X_v)$. This implies that for each edge in *H*, at most its weight in tokens can move to $c(X)$ from and to exactly one of the vertex gadgets corresponding to the vertices incident to that edge in *H*. Given that σ tokens are needed on the vertices of $c(X)$, it must be the case that for each edge, all its weight in tokens must move to $c(X)$. This gives a feasible orientation for $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$, since for each $v \in V(H_j)$, we have at most *r* vertices in $c(X_v)$. \triangleleft

This concludes the proof of the theorem.

 \Box

Next we consider the feedback vertex set number (*fvs*) parameterization of the VC-D problem. In Theorem [4.2,](#page-13-0) we proved that the VC-D problem is XNLP-hard for the parameter pathwidth of the input graph. The feedback vertex set number (*fvs*) and pathwidth are upper bounds of treewidth, but are incomparable. We will show that the VC-D problem is W[1]-hard for the parameter *fvs*.

Theorem 4.4*.* The VC-D problem is W[1]-hard when parameterized by the feedback vertex set number, i.e., *fvs*, of the input graph.

We present a parameterized reduction from the MULTI-COLORED CLIQUE problem. We utilize the reduction presented in Theorem [6.4,](#page-37-0) and apply some changes over the constructed graph to obtain a reduced instance of the VC-D problem. Consider the graph *H* constructed in the proof of Theorem [6.4.](#page-37-0) For each $i \in [\kappa]$, we add a neighbor \tilde{t}_i to t_i in the vertex-block H_i . For each $1 \leq i < j \leq \kappa$, we add a neighbor $\tilde{t}_{i,j}$ to $t_{i,j}$ in the edge-block $H_{i,j}$. For each $1 \leq i < j \leq \kappa$ and $l \in \{i, j\}$, we do the following changes in the connector $\mathcal{C}_{i,j}^l$:

- Add four new vertices $\tilde{s}^l_{i,j}, \tilde{s}^l_{i,j}, \tilde{r}^l_{i,j}$ and $\tilde{r}^l_{i,j}$.
- Connect $\tilde{s}^l_{i,j}$, $\hat{s}^l_{i,j}$ with $s^l_{i,j}$, and $\tilde{r}^l_{i,j}$, $\tilde{r}^l_{i,j}$ with $r^l_{i,j}$.
- For each neighboring vertex *v* of $s_{i,j}^l$ from the vertex-blocks, remove the edge $s_{i,j}^l v$ and add the edge $\tilde{s}^l_{i,j}v$.
- For each neighboring vertex *v* of $s_{i,j}^l$ from the edge-blocks, remove the edge $s_{i,j}^l v$ and add the edge $\hat{s}^l_{i,j}v$.

Figure 10: An illustration of the reduction of Theorem [4.4.](#page-18-0) For $1 \leq i \leq j \leq \kappa$, the vertex-block H_i and the edge-block $H_{i,j}$ are connected to the connector $\mathcal{C}_{i,j}^i$. The initial configuration is denoted by vertices with red circle.

- • For each neighboring vertex *v* of $r_{i,j}^l$ from the vertex-blocks, remove the edge $r_{i,j}^l v$ and add the edge $\tilde{r}^l_{i,j}v$.
- For each neighboring vertex *v* of $r_{i,j}^l$ from the vertex-blocks, remove the edge $r_{i,j}^l v$ and add the edge $\hat{r}_{i,j}^l v$.

An illustration of a connector connecting a vertex-block and an edge-block is given in Figure [10.](#page-19-0) This completes the construction of graph *H* for the VC-D instance. Next we describe the initial configuration *S* as follows:

$$
S=\bigcup_{i\in[\kappa],x\in[n]}Q_{i,x}\cup\bigcup_{e\in E}Q_e\cup\bigcup_{i\in[\kappa]} \{t_i,\tilde{t}_i\}\cup\bigcup_{1\leq i
$$

Finally, we set $b = (12n + 2)\binom{\kappa}{2} + 2\kappa$ and the reduced VC-D instance is (H, S, b) .

Lemma 4.3. The *fvs* of the graph *H* is at most $8\binom{\kappa}{2}$.

Proof. Let $F = \{\tilde{s}_{i,j}^l, \tilde{s}_{i,j}^l, \tilde{r}_{i,j}^l, \hat{r}_{i,j}^l \mid 1 \leq i < j \leq \kappa, l \in \{i, j\}\}\.$ The removal of F from H results in a forest. Therefore, the *fvs* of *H* is at most $|F| = 8\binom{\kappa}{2}$.

Next we prove the correctness of the reduction.

Lemma 4.4. If (G, κ) is a yes-instance of the MULTI-COLORED CLIQUE problem, then (H, S, b) is a yes-instance of the VC-D problem.

Proof. Let $C = \subseteq V(G)$ be a *κ*-clique in *G*. For each $i \in [\kappa]$, let u_{i,x_i} be the vertex in $C \cap V_i$ for some $x_i \in [n]$. For each $1 \leq i < j \leq \kappa$, let $e_{i,j} = u_{i,x_i} u_{j,x_j}$. For each $i \in [\kappa]$, we slide the token on \tilde{t}_i to p_{i,x_i} . Then, for each $j \neq i \in [\kappa]$, we slide x_i -tokens in Q_i^j i_{i,x_i} towards $\tilde{s}^i_{i,j}$ and $n - x_i$ -tokens in Q_i^j *i,xⁱ* towards $\tilde{r}^i_{i,j}$. For each $1 \leq i < j \leq \kappa$, we slide the token on $\tilde{t}_{i,j}$ to $p_{e_{i,j}}$. Then, we slide

- $n x_i$ tokens in $Q_{e_{i,j}}$ to $\hat{s}_{i,j}^i$,
- x_i tokens in $Q_{e_{i,j}}$ to $\hat{r}_{i,j}^i$,
- $n x_j$ tokens in $Q_{e_{i,j}}$ to $\hat{s}^j_{i,j}$, and
- x_j tokens in $Q_{e_{i,j}}$ to $\hat{r}_{i,j}^j$.

The tokens received at the vertices $\tilde{s}^*_{*,*}$ and $\hat{s}^*_{*,*}$ are pushed to $s^*_{*,*}$. Similarly, the tokens received at the vertices $\tilde{r}^*_{*,*}$ and $\hat{r}^*_{*,*}$ are pushed to $r^*_{*,*}$. For each $1 \leq i \leq j \leq \kappa$, and for each $l \in i, j, s^l_{i,j}$ receives x_l -tokens from H_l and $n-x_l$ -tokens from $H_{i,j}$. Similarly, $r_{i,j}^l$ receives $n-x_l$ -tokens from H_l and *x*_l-tokens from $H_{i,j}$. Further, we push the *n*-tokens received by $s_{i,j}^l$ to $A_{i,j}^l$ and *n*-tokens received by $r_{i,j}^l$ to $D_{i,j}^l$. The resulting configuration is a valid vertex cover. Finally, let $S' \subseteq V(H)$ be the solution obtained from the above token sliding steps. More precisely,

$$
S' = \bigcup_{i \in [\kappa]} \{ \{t_i, p_{i,x_i}\} \cup (Q_i \setminus Q_{i,x_i}) \} \cup \bigcup_{1 \leq i < j \leq \kappa} \{ \{t_{i,j}, p_{e_{i,j}}\} \cup (Q_{i,j} \setminus Q_{e_{i,j}}) \}
$$
\n
$$
\cup \bigcup_{1 \leq i < j \leq \kappa, l \in \{i,j\}} \{ \{\tilde{s}_{i,j}^l, \tilde{s}_{i,j}^l, \tilde{r}_{i,j}^l, \hat{r}_{i,j}^l\} \cup A_{i,j}^l \cup D_{i,j}^l \}.
$$

It is clear that the set S' is a vertex cover in H . Next we count the number of token steps used to obtain *S'* from *S*. In each vertex-block, we spend $2(\kappa - 1)n + 2$ steps to push tokens towards the connectors. Similarly, at each edge-block, we spend $(4n + 2)$ steps. At each connectors, we spend 2*n* steps. Therefore, we spend $\kappa \cdot (2(\kappa - 1)n + 2) + {k \choose 2} \cdot (4n + 2) + 2{k \choose 2} \cdot 2n = (12n + 2){k \choose 2} + 2\kappa = b$. Hence, (H, S, b) is a yes-instance of VC-D problem. \Box

Lemma 4.5. If (H, S, b) is a yes-instance of the VC-D problem, then (G, κ) is a yes-instance of the MULTI-COLORED CLIQUE problem.

Proof. Let S^* be a feasible solution for the instance (H, S, b) of the VC-D problem. At each connector $\mathcal{C}_{i,j}^l$ for $1 \leq i < j \leq \kappa$ and $l \in \{i,j\}$, at least 2*n* tokens need to be slid from either vertex-blocks or edge blocks. Because, each $H[C_{i,j}^l]$ contains a matching of size $2n + 4$, but it has only four tokens in the initial configuration. It is clear that every token must move at least 3 steps to reach the sets $A_{*,*}^*$ and $D_{*,*}^*$ in order to cover the uncovered edges. This saturates a budget of $4n \cdot 2\binom{\kappa}{2} = 12n\binom{\kappa}{2}$. Therefore, we left with exactly $2\kappa + 2\binom{\kappa}{2}$ budget to adjust the tokens on the vertex blocks and edge blocks. For any $1 \leq i < j \leq \kappa$, let $q_{i,x}^{j,z}$ for some integers $x, z \in [n]$ be a vertex that looses the token where the token is moved to some vertex in a connector. Since the edge $p_{i,x}q_{i,x}^{j,z}$ become uncovered, we need to slide a token to $q_{i,x}^{j,z}$ or $p_{i,x}$. This cost at least two token step. By construction of the vertex-block H_i , by sliding a token (for two steps) to the vertex $p_{i,x}$ for some $x \in [n]$, one can release at most $n(\kappa - 1)$ tokens from the neighboring set $Q_{i,x}$. Similarly, on a edge-block $H_{i,j}$ for some $1 \leq i < j \leq \kappa$, by sliding a token (for two steps) to the vertex p_e for some $e \in E_{i,j}$, one can release at most 2*n* tokens from the neighboring set Q_e . This implies that by

sliding at most 2κ tokens on the vertex-blocks, one can release at most $\kappa \cdot n(\kappa - 1) = 2n\binom{\kappa}{2}$ token from the vertex-blocks. Similarly, by sliding at most $2\binom{\kappa}{2}$ tokens on the edge-blocks, one can release at most $2n\binom{\kappa}{2}$ tokens from the edge-blocks. Therefore, we need to slide exactly one token (for two steps) in each vertex-block and each edge-block.

For each $i \in [\kappa]$, let p_{i,x_i} for some $x_i \in [n]$ be the vertex in H_i that gets token in S^* and releases all the tokens in Q_{i,x_i} . Similarly, for each $1 \leq i < j \leq \kappa$, let p_e for some $e = u_{i,z_i} u_{i,z_j} \in E_{i,j}$ with $z_i, z_j \in [n]$ be the vertex in $H_{i,j}$ that gets token in S^* and releases all tokens in Q_e . Consider the connector $\mathcal{C}_{i,j}^i$. The set Q_i^j *i*_{*i,x_i*} pushes *x_i* tokens to *s*^{*i*}_{*i,j*} and *n* − *x_i* tokens to *r*^{*i*}_{*i,j*}. The set *Q_{<i>e*} pushes z_i tokens to $r_{i,j}^i$ and $n-z_i$ tokens to $s_{i,j}^i$. The number of tokens passed through $s_{i,j}^i$ to $A_{i,j}^i$ is $x_i + (n - z_i)$. Since $A_{i,j}^i$ need *n* tokens, it is mandatory that $x_i = z_i$. This equality should hold for every *i*. Therefore, for each $1 \leq i < j \leq \kappa$, there exist an edge $u_{i,x_i}u_{j,x_j}$. Hence (G,κ) is an yes-instance of the MULTI-COLORED CLIQUE problem. \Box

The proofs of Lemmas [4.3,](#page-19-1) [4.4](#page-19-2) and [4.5](#page-20-0) complete the proof of Theorem [4.4.](#page-18-0)

5 Independent Set Discovery

Fellows et al. [\[14\]](#page-47-2) showed that IS-D is in FPT with respect to parameter $k + b$ on nowhere dense classes of graphs. We show in this section that IS-D has a polynomial kernel with respect to parameter *k* on nowhere dense classes of graphs and does not admit a polynomial kernel with respect to the parameter $b + pw$, where *pw* is the pathwidth of the input graph, unless $NP \subseteq \text{coNP/poly}$.

Definition 5.1. For any instance $\mathcal{I} = (G, S, b)$ of a Π -DISCOVERY problem for some vertex (resp. edge) selection problem Π , we call a vertex $v \in V(G) \setminus S$ (resp. $e \in E(G) \setminus S$) *irrelevant* with respect to $s \in S$ if there exists a configuration C_{ℓ} such that $\ell \leq b, C_{\ell}$ is a solution for Π , and the token on s is not on v (resp. e) in C_{ℓ} .

The kernelization algorithm for nowhere dense graphs uses [Theorem 2.1,](#page-4-1) along with other structural properties of the input graph, to form a "sunflower" and find an irrelevant vertex. It then removes from the graph some of the vertices that are irrelevant with respect to every token. A *sunflower* with *p petals* and a *core Y* is a family of sets F_1, \ldots, F_p such that $F_i \cap F_j = Y$ for all $i \neq j$; the sets $F_i \setminus Y$ are petals and we require none of them to be empty [\[12\]](#page-47-10).

Lemma 5.1. Let (G, S, b) be an instance of IS-D where $|S| = k$, and let G' be the subgraph of *G* induced by the vertices of $\bigcup_{s \in S, i \in [3k]} V(s, i) \cup S$. Then (G', S, b) is equivalent to (G, S, b) .

Proof. We show that in any solution to (G, S, b) , if a token on a vertex $s \in S$ moves to a vertex $u \in C_{\ell}$ such that $d(s, u) > 3k$, it can instead move towards a vertex $v \in V(H)$ such that $d(s, v) \leq 3k$, while keeping the rest of the solution unchanged. First, the vertices in $C_{\ell} \setminus \{u\}$ can appear in at most $k-1$ of the 3*k* sets $V(s, i)$ for $i \in [3k]$ and every such vertex that appears in a set $V(s, i)$ for a specific $i \in [3k]$ can be a neighbor of at most all the vertices in $V(s, i - 1)$ and $V(s, i + 1)$. This implies that the token on *s* cannot move towards any vertex of at most $3k-3$ of the 3*k* sets $V(s, i)$ for $i \in [3k]$ (as these contain tokens and thus might result in adjacent tokens) and thus there exists a vertex *v* which the token on *s* can move to while maintaining an independent set in $C_{\ell} \setminus \{u\} \cup \{v\}.$ \Box

Lemma 5.2. Let (G, S, b) be an instance of IS-D where $|S| = k$, and let $\mathcal{V} = \{v_1, v_2, \ldots, v_t\}$ be a set of vertices of $G \setminus S$ such that for a given token on a vertex $s \in S$, $d(s, v_i) = d(s, v_j)$ for $i \neq j \in [t]$. If $\mathcal{A} = \{N[v_1], \ldots, N[v_t]\}$ contains a sunflower with $k+1$ petals, then any vertex whose closed neighborhood corresponds to one of those petals is irrelevant with respect to *s*.

Proof. Let *vdel* be one such vertex whose closed neighborhood corresponds to one of the *k* + 1 petals, and consider a solution to (G, S, b) in which the token on *s* is on the vertex v_{del} in C_{ℓ} . First, note that no vertex of $C_{\ell} \setminus \{v_{del}\}\$ is in the core of the sunflower since that would contradict the fact that $v_{del} \in C_{\ell}$ as v_{del} is a neighbor of every vertex in the core. Second, since the sunflower has *k* remaining petals (besides the one corresponding to the closed neighborhood of *vdel*) and $|C_{\ell} \setminus \{v_{del}\}| = k - 1$, there must remain one vertex (denoted v_{rep}) whose closed neighborhood corresponds to one of the remaining *k* petals and such that *vrep* is not in the closed neighborhood of any of the vertices in $C_{\ell} \setminus \{v_{del}\}\$. Thus, $C_{\ell} \setminus \{v_{del}\} \cup \{v_{rep}\}\$ forms an independent set. Additionally, since $d(s, v_{del}) = d(s, v_{rep})$, the number of slides in the solution remains constant. As a result, v_{del} is irrelevant with respect to *s*. \Box

Theorem 5.1*.* IS-D has a polynomial kernel with respect to parameter *k* on nowhere dense graphs.

Proof. Let (G, S, b) be an instance of IS-D where *G* is nowhere dense. Without loss of generality, we assume the graph *G* to be connected. For each vertex $s \in S$ and integer $i \in [3k]$, we compute $V(s, i)$. We maintain the invariant that we remove from $V(s, i)$ for each $s \in S$ and $i \in [3k]$, irrelevant vertices with respect to *s* (note that a vertex can appear in multiple sets $V(s, i)$).

We remove an irrelevant vertex with respect to a vertex $s \in S$ from $V(s, i)$ for an integer $i \in [3k]$ as follows. If $|V(s,i)| > N_2(2^{x_2} \cdot (k+1))$, where N_2 and x_2 are as per [Theorem 2.1](#page-4-1) (here $V(s, i)$ plays the role of the set *A*), we can compute sets $X, B \subseteq V(s, i)$ such that $|X| \leq x_2$, $|B| \geq 2^{x_2} \cdot (k+1)$ and *B* is 2-independent in $G - X$. Let $\mathcal{B}' = \{B'_1, B'_2, \ldots\}$ be a family of sets that partitions the vertices in *B* such that for any two vertices $u, v \in B$, $u, v \in B'$ if and only if $N[u] \cap X = N[v] \cap X$. Since $|B| \geq 2^{x_2} \cdot (k+1)$ and $|X| \leq x_2$, at least one set $B_j \in \mathcal{B}$, for a specific j, contains at least $k+1$ vertices of *B*. All vertices in B_i have the same neighborhood in *X* and they are 2-independent *G* − *X* (i. e., no vertex from outside of *X* can be in the closed neighborhood of two vertices in B_i ; thus their closed neighborhoods form a sunflower with at least $k+1$ petals and a core that is contained in *X* [\(Figure 11\)](#page-23-1). By [Lemma 5.2,](#page-21-1) one vertex of B_j is irrelevant with respect to *s* and can be removed from $V(s, i)$. We can repeatedly apply [Theorem 2.1](#page-4-1) on the set $V(s, i)$ until $|V(s, i)| \leq N_2(2^{x_2} \cdot (k+1)).$

We form the kernel (G', S, b) of the original instance (G, S, b) as follows. We set $V(G') =$ $\bigcup_{s \in S, i \in [3k]} V(s, i)$ ∪ *S*. By [Lemma 5.1,](#page-21-2) any vertex $v \in V(G)$ such $d(s, v) > 3k$ for every $s \in S$ is irrelevant with respect to every $s \in S$ and not required in the kernel (G', S, b) . For each vertex $v \in V(s, i)$, for $s \in S$ and $i \in [3k]$, we add to $V(G')$ at most *i* vertices that are on the shortest path from *s* to *v*, if such vertices are not already present in $V(G')$. *G'* is the subgraph of *G* induced by the vertices in $V(G')$. By the end of this process, $|V(G')| \leq k + [9k^3 \cdot N_2(2^{x_2} \cdot (k+1))]$, as for each $s \in S$ and $i \in [3k]$, $V(s, i) \leq N_2(2^{x_2} \cdot (k+1))$ and for each vertex in the latter sets, we added to $V(G')$ at most $3k-1$ vertices that are on a shortest path from that vertex to the vertex *s*. (G', S, b) is a kernel as only vertices that are irrelevant with respect to every token in S might not be in *V* (*G*′) and all vertices needed to move tokens from vertices in *S* towards an independent set using only *b* slides are present in $V(G')$. \Box

Figure 11: An example of a sunflower (with pink, beige and blue petals) formed by the closed neighborhoods of the vertices in *B*_j of [Theorem 5.1.](#page-22-0) The vertices in *B*_j are 2-independent in $G - X$ and they have the same closed neighborhood in *X* (the blue colored vertices).

Theorem 5.2*.* IS-D is XNLP-hard with respect to parameter pathwidth.

As stated in [Section 3,](#page-6-0) we present an FPT-reduction from MMO. Let $(H, \mathcal{P}_H, \sigma, r)$ be an instance of MMO where *H* is a bounded pathwidth graph, $|V(H)| = n$, $|E(H)| = m$, $\sigma : E(H) \to \mathbb{Z}_+$ such that $\sum_{e \in E(H)} \sigma(e) = \sigma$ and $r \in \mathbb{Z}_+$ (integers are given in unary). We construct an instance $(G_H, \mathcal{P}_{G_H}, S, b)$ of IS-D where G_H is exactly as described in [Section 3](#page-6-0) (under the graph G_H heading). See [Figure 12.](#page-24-0) From [Lemma 3.1,](#page-8-2) G_H is of bounded pathwidth. We set $S = A \cup A^+ \cup B$ *B*⁺ ∪ *Y* ∪ *X*⁺ and *b* = *m* + 3 σ . Given that all integers are given in unary, the construction of the graph *GH*, or its path decomposition (as described in [Lemma 3.1\)](#page-8-2), and as a consequence the reduction, take time polynomial in the size of the input instance. Additionally, by [Corollary 3.3,](#page-11-1) this reduction is a pl-reduction. We claim that $(H, \mathcal{P}_H, \sigma, r)$ is a yes-instance of MMO if and only if $(G_H, \mathcal{P}_{G_H}, S, b)$ is a yes-instance of IS-D.

Lemma 5.3. If $(H, \mathcal{P}_H, \sigma, r)$ is a yes-instance of MMO, then $(G_H, \mathcal{P}_{G_H}, S, b)$ is a yes-instance of IS-D.

Proof. Let $\lambda : E(H) \to V(H) \times V(H)$ be an orientation of the graph *H* such that for each $v \in V(H)$, the total weight of the edges directed out of *v* is at most *r*. In $(H, \mathcal{P}_H, \sigma, r)$, the vertices in *A* and *B* contain tokens. The same applies for the vertices in A^+ and B^+ . To fix that, for each edge $e \in E(H)$ such that $\lambda(e) = (v, u)$:

- 1. we slide, for each $i \in [\sigma(e)]$, the token on b_e^i to $z_e^{v(i)}$ (this consumes $\sigma(e)$ slides),
- 2. we move, for each $i \in [\sigma(e)]$, the token on $y_e^{v(i)}$ to any free vertex of X_v (this consumes $2\sigma(e)$) slides),
- 3. we slide the token on $b_e^{\sigma(e)+1}$ to e^v (this consumes 1 slide).

This constitutes $m + 3\sigma$ slides and we get an independent set in G_H . Step 2 above is possible (i.e. a token-free vertex exists in X^v) since λ is an orientation of the graph *H* such that for each $v \in V(H)$, the total weight of the edges directed out of *v* is at most *r*. Step 3 is possible for each edge $e \in E(H)$ since in Step 2 all tokens were removed from the vertices in Y_e^v . \Box

Lemma 5.4. If $(G_H, \mathcal{P}_{G_H}, S, b)$ is a yes-instance of IS-D, then $(H, \mathcal{P}_H, \sigma, r)$ is a yes-instance of MMO.

Figure 12: Parts of the graph G_H constructed by the reduction of [Theorem 5.2](#page-23-0) given an instance $(H, \mathcal{P}_H, \sigma, r)$, where *H* has three vertices *u*, *v* and *w*, and two edges $e_1 = uv$ and $e_2 = uw$, and $r = 3$. Additionally, $\sigma(e_1) = 3$ and $\sigma(e_2) = 1$. For clarity, the edges between the vertices in B_{e_1} and $Z_{e_1}^u$ are missing. The same applies for the edges between e_1^v and the vertices of $Y_{e_1}^v$ and the edges between e_1^u and the vertices of $Y_{e_1}^u$. Red and yellow edges are used to highlight the different types of edges used to connect the subgraphs $G_{e_1}, G_{e_2}, G_u, G_v$ and G_w of G_H , vertices in black are in *S* and those in white are not.

Proof. The minimum number of slides used inside any induced subgraph G_e for an edge $uv =$ $e \in E(H)$ is one and it can only be achieved by sliding the token on $b_e^{\sigma(e)+1}$ to one of either e^u or e^v . Thus, at least *m* slides are required inside the MMO-edge-gadgets and the budget remaining is 3σ . Additionally, each token on a vertex b_e^i in B_e , for an edge $uv = e \in E(H)$ and an integer $i \in [\sigma(e)]$ must slide to either $z_e^{u(i)}$ or $z_e^{v(i)}$, consuming σ slides. Since a solution that moves the token on $a_e^{\sigma(e)+1}$ but not the token on $b_e^{\sigma(e)+1}$ is not minimal, we can safely assume that the described $m + \sigma$ slides are executed in any minimal solution.

In the same solutions, each token on a vertex $z_e^{u(i)}$ for an edge $uv = e \in E(H)$ and an integer $i \in [\sigma(e)]$ requires the token on $y_e^{u(i)}$ to slide to either e^u or w_u , utilizing as a result σ other slides. A token that slides from $y_e^{u(i)}$ to the vertex w_u must slide again at least once, since any independent set that is achieved through the minimal number of slides would never require the sliding of the tokens on the vertices in X^+ (the token that moves to the vertex w_u can be moved, using one less slide, to the vertex the token on x_i^{r+1} moves to). Since G_e^{sel} can contain at most 2 tokens, a token on $y_e^{u(i)}$ that slides to the vertex e^u must either slide again at least once to a vertex, denoted $y_e^{u(i_1)}$ (for an integer $i_1 \in [\sigma(e)]$) in Y_e^u , or require another token on a vertex in G_e^{sel} to slide at least once to either a vertex, denoted $y_e^{u(i_2)}$ (for an integer $i_2 \in [\sigma(e)]$) in Y_e^u , or a vertex, denoted $y_e^{v(i_2)}$ (for an integer $i_2 \in [\sigma(e)]$ in Y_e^v , while the token initially on $y_e^{u(i)}$ stays on e^u . Given that at most σ slides remain in any minimal solution, and that each of the σ tokens initially on vertices in Y that moved to either vertices of the form $e_1^{u_1}$ or w_{u_1} , for an edge $e_1 \in E(H)$ incident to a vertex $u_1 \in V(H)$,

uses or requires at least one additional slide, each one such token can use or require exactly one additional slide. If the token on $y_e^{u(i)}$ slides to w_u , then either in exactly one more slide it can move to a free vertex in X_u , or it can slide back to a vertex, denoted $y_{e_2}^{u(i_3)}$ (for an edge e_2 adjacent to u in H and an integer $i_3 \in [\sigma(e_1)]$ in Y^u . However, either $y_{e_2}^{u(i_3)}$ (resp. $y_e^{u(i_1)}, y_e^{u(i_2)},$ or $y_e^{v(i_2)}$) or its adjacent vertex, denoted $z_{e_2}^{u(i_3)}$ in Z^u (resp. $z_e^{u(i_1)}$ in Z_e^u , $z_e^{u(i_2)}$ in Z_e^u , or $z_e^{v(i_2)}$ in Z_e^v), contains a token, thus requiring at least one other additional slide, which is impossible. As a result, it can only be the case that a token on $y_e^{u(i)}$ slides to w_u and then in exactly one more slide it moves to a free vertex in X_u .

For any edge $uv = e \in E(H)$, if $e^v \in C_\ell$ (resp. $e^u \in C_\ell$), then no vertex of Y_e^v (resp. Y_e^u) appears in C_{ℓ} and the tokens on the vertices of Y_e^v (resp. Y_e^u) have been moved to some of the free vertices of X_v (resp. X_u). Given the latter, we produce an orientation λ to H , where $\lambda(e) = (v, u)$ (resp. $\lambda(e) = (u, v)$ if $e^v \in C_\ell$ (resp. $e^u \in C_\ell$). Since $|X_v| = |X_u| \leq r$, λ is such that the total weight directed out of any vertex $v \in V(H)$ is at most r. \Box

The proofs of Lemmas [5.3](#page-23-2) and [5.4](#page-23-3) complete the proof of Theorem [5.2.](#page-23-0)

By making some of the vertices of our MMO-instance-selector adjacent to some of the vertices in G_{H_1}, \ldots, G_{H_t} constructed following the reduction of [Theorem 5.2](#page-23-0) for *t* MMO input instances H_1, \ldots, H_t , we prove the following.

Theorem 5.3*.* There exists an or-cross-composition from MMO into IS-D on bounded pathwidth graphs with respect to *b*. Consequently, IS-D does not admit a polynomial kernel with respect to $b + pw$, where *pw* denotes the pathwidth of the input graphs, unless $NP \subseteq \text{coNP/poly}$.

Proof. As stated in [Section 3,](#page-6-0) we can assume that we are given a family of *t* MMO instances $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$, where H_j is a bounded pathwidth graph with path decomposition \mathcal{P}_{H_j} , $|V(H_j)| = n$, $|E(H_j)| = m, \sigma_j : E_j \to \mathbb{Z}_+$ is a weight function such that $\sum_{e_j \in E(H_j)} \sigma_j(e_j) = \sigma$ and $r_j = r \in \mathbb{Z}_+$ (integers are given in unary). The construction of the instance $(G_t, \mathcal{P}_{G_t}, S, b)$ of IS-D is twofold.

For each instance H_j for $j \in [t]$, we add to G_t the graph G_{H_j} as per the reduction in [Theorem 5.2.](#page-23-0) We refer to the sets \overline{A} , \overline{B} , \overline{X} , and \overline{X} ⁺, subsets of vertices of a subgraph G_{H_j} of G_t , by A_j , B_j , X_j , and X_j^+ , respectively. Subsequently, we let $A = \bigcup_{j \in [t]} A_j$, $B = \bigcup_{j \in [t]} B_j$, $X = \bigcup_{j \in [t]} X_j$, and $X^+ = \bigcup_{j \in [t]} X^+_j$. We add the MMO-instance-selector described in [Section 3](#page-6-0) (under the MMOinstance-selector heading) and connect it to the rest of G_t as follows (see [Figure 13\)](#page-26-0). We make for each $j \in [t]$, the vertex UNSELECT_j adjacent to the vertices in $V(G_{H_j}) \setminus S$, where S is as defined later. We make the vertex *h* adjacent to the vertices in *A* and the vertex *q* adjacent to the vertices in A^+ . The result is the original graph G_t appearing in [Section 3.](#page-6-0) By [Lemma 3.2,](#page-11-0) G_t is of bounded pathwidth. Now, we set

$$
S = B \cup B^+ \cup X^+ \cup Y \cup \bigcup_{j \in [t]} \text{UNSELECT}_j \cup \bigcup_{i \in [\sigma]} (f^i \cup g^i) \cup \bigcup_{i \in [m]} (o^i \cup p^i) \cup h \cup q
$$

and $b = 3m + 5\sigma + 1$. Given that all integers are given in unary, the construction of the graph G_t , or its path decomposition (as described in [Lemma 3.2\)](#page-11-0), and as a consequence the reduction take time polynomial in the size of the input instances. Additionally, by [Corollary 3.4,](#page-12-2) this composition is a pl-reduction. We claim that $(G_t, \mathcal{P}_{G_t}, S, b)$ is a yes-instance of IS-D if and only if for some integer $j \in [t]$, $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ is a yes-instance of MMO.

Claim 4. If for some $j \in [t]$, $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ is a yes-instance of MMO, then $(G_t, \mathcal{P}_{G_t}, S, b)$ is a yes-instance of IS-D.

Figure 13: Orange, pink, and green edges highlighting the different types of edges between an MMO-instance-selector of the composition in [Theorem 5.3](#page-25-0) and a subgraph G_{H_j} for a $j \in [t]$ of the same. H_j has three vertices u, v , and w and two edges $e_1 = uv$ and $e_2 = uw$, and $r = 3$. Additionally, $\sigma_j(e_1) = 3$ and $\sigma_j(e_2) = 1$. For clarity, not all edges inside *G^H^j* are drawn, nor are all the pink edges depicted. Vertices in black are in *S* and those in white are not.

Proof. Let $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ be a yes-instance of MMO and let λ be a feasible orientation of H_j such that for each $v \in V(H_j)$, the total weight of the edges directed out of *v* is at most *r*. In G_t , the tokens on f^i and g^i are adjacent for each $i \in \sigma$, and the tokens on o^i and p^i are adjacent for each $i \in [m]$. First, we slide the token on Unselect_j onto the vertex Select_j. Using $2\sigma + 2m$ slides, we move the token on the vertex f_i for each $i \in [\sigma]$ towards a token-free vertex in A_i and we move the token on the vertex o_i for each $i \in [m]$ towards a token-free vertex in A_j^+ . This achieves a configuration of the tokens on G_{H_j} that is similar to the starting configuration of the tokens on the graph *G^H* of the reduction of [Theorem 5.2.](#page-23-0) From [Lemma 5.3,](#page-23-2) given a feasible orientation of the MMO instance $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$, we can achieve a configuration of the tokens that constitutes an independent set in G_{H_j} in $m + 3\sigma$ slides. This totals *b* slides and achieves a configuration of the tokens that constitutes an independent set in G_t . . ◁

Claim 5. If $(G_t, \mathcal{P}_{G_t}, S, b)$ is a yes-instance of IS-D, then there exists an integer $j \in [t]$, such that $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ is a yes-instance of MMO.

Proof. In any solution that uses the minimal number of slides, at least $2m + 2\sigma$ slides are needed to get the tokens on f^1, \ldots, f^{σ} and o^1, \ldots, o^m to vertices in *A* and A^+ , respectively. Note that a solution that moves the token on g^i for some integer $i \in [\sigma]$ but not the token on f^i or that moves the token on p^i for some integer $i \in [m]$ but not the token on o^i is not minimal. When a token is moved from one of the vertices $f^1, \ldots, f^{\sigma}, o^1, \ldots, o^m$ to one of the vertices in $V(G_{H_j})$ for an integer $j \in [t]$, which is bound to happen, at least one slide is needed so that the token on UNSELECT_j is not adjacent to any other token and one slide can be achieved by sliding the token on UNSELECT_j to SELET_j . Note that a solution that uses the minimal number of slides and slides the token on UNSELECT_{*j*} for any $j \in [t]$ to any vertex $v \in V(G_t) \setminus \{\text{SELECT}_j\}$ (and possibly slides another token to SELECT_j can safely be replaced by a solution that performs the same number of slides and the same slides except that it slides the token on UNSELECT_j to SELECT_j (and possibly the other token to *v*). Thus, we consider minimal solutions that slide UNSELECT_j for any $j \in [t]$ only to SELECT_j.

Assume that for some integer $j \in [t]$, UNSELECT_j has moved to SELECT_j. In a solution that uses the minimal number of slides, if a token is the first to move from one of the vertices o^1, \ldots, o^m to a vertex $a_e^{\sigma_j(e)+1}$ for an edge $uv = e \in E(H_j)$, it will require the token on $b_e^{\sigma_j(e)+1}$ to slide to one of e^u or e^v . Each other token that moves from one of the vertices o^1, \ldots, o^m to $a_e^{\sigma(e)+1}$ will require in the same solution at least 3 additional slides as one token must exit the induced subgraph G_e^{sel} and the two remaining tokens must not be on adjacent vertices. Thus, if we assume that the *m* tokens on o^1, \ldots, o^m move to distinct vertices in A^+ , they require at least *m* additional slides.

Assume that for some integer $j_1 \in [t]$, UNSELECT_{j1} has moved to SELECT_{j1}. In a solution that uses the minimal number of slides, if a token is the first to move from one of the vertices f^1, \ldots, f^{σ} to a vertex $a_{e_1}^i$ for an edge $u_1v_1 = e_1 \in E(H_{j_1})$ and $i \in [\sigma_{j_1}(e_1)]$, it will require the token on $b_{e_1}^i$ to slide to one of $z_{e_1}^{u_1(i)}$, or $z_{e_1}^{v_1(i)}$. W.l.o.g., assume the token on $b_{e_1}^i$ slides to $z_{e_1}^{u_1(i)}$. In the same solution, the token on $z_{e_1}^{u_1(i)}$ will in turn require the token on $y_{e_1}^{u_1(i)}$ to slide to either w_{u_1} or $e_1^{u_1}$. Each other token that moves from one of the vertices f^1, \ldots, f^{σ} to $a_{e_1}^i$ will require in the same solution at least 4 additional slides to leave the path $a_{e_1}^i b_{e_1}^i z_{e_1}^{u_1(i)} y_{e_1}^{u_1(i)}$ which cannot accommodate more tokens. Given that the remaining budget is at most 3σ , a second token sliding to the vertex $a_{e_1}^i$ is only possible if for some token initially on a vertex in *Y* that moved to a vertex w_{u_2} or a vertex $e_2^{u_2}$, for a vertex $u_2 \in V(H_{j_2})$, edge $u_2v_2 = e_2 \in E(H_{j_2})$, and integer $j_2 \in [t]$, does not slide or require another token to slide. In any solution that uses the minimal number of slides, the tokens on the vertices in *X*⁺ do not need to be moved (since we can move any token that moves into the adjacent representative vertices to the vertices the tokens on the vertices of X^+ were being moved to). Thus, a token on w_{u_2} must slide again. Similarly, a token on $e_2^{u_2}$ must either slide again, or require another token (on the vertex in B^+) to slide. Thus, with a remaining budget of at most 3σ , no token can afford to move from f^1, \ldots, f^{σ} to $a_{e_1}^i$ once another token has already moved to the same vertex. In other words, given *b*, it must be the case that the σ tokens on f^1, \ldots, f^{σ} slide towards distinct vertices in *A*.

Additionally, each such token will require at least 3 slides. Consequently, the *m* tokens on $o¹, \ldots, o^m$ must also slide to distinct vertices in $A⁺$. Given that one slide remains for moving the token on one vertex UNSELECT_j to SELECT_j for an integer $j \in [t]$, it must be the case that the tokens on f^1, \ldots, f^{σ} (resp. o^1, \ldots, o^m) move to distinct vertices in A_j (resp. A_j^+). This achieves a configuration of the tokens on G_{H_j} that is similar to the starting configuration of the tokens inside G_H of the reduction of [Theorem 5.2.](#page-23-0) From [Lemma 5.4,](#page-23-3) with a remaining budget of $m + 3\sigma$, we get that $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ is a yes-instance of MMO.

This concludes the proof the theorem.

 \Box

Next we consider the *fvs* parameterization of the IS-D problem.

Theorem 5.4*.* The IS-D problem is W[1]-hard for the parameter *fvs* of the input graph.

We present a parameterized reduction from the MULTI-COLORED CLIQUE problem. We utilize the reduction given in Theorem [6.4,](#page-37-0) and apply some changes over the constructed graph to obtain reduced instance for the IS-D instance. Consider the graph *H* constructed in the proof of Theorem [6.4.](#page-37-0) For each $i \in [\kappa]$, we add a vertex \tilde{t}_i with $n(n-1)(\kappa-1)$ pendent neighbors (call the set as T_i) in the vertex-block H_i . For each vertex v in Q_i , we add a pendent neighbor $b(v)$. For any set $B \subseteq Q_i$, we used to refer $b(B)$ as the set of all pendent neighbors of the vertices in *B*. The vertex \tilde{t}_i is made adjacent to all the vertices in $b(Q_i)$. We add a pendent neighbor \hat{t}_i to t_i . For each $1 \leq i < j \leq \kappa$, we add a vertex $\tilde{t}_{i,j}$ with $2n|E_{i,j}|-2n$ pendent neighbors (call the set as $T_{i,j}$) in the edge-block $H_{i,j}$. For each vertex *v* in $Q_{i,j}$, we add a pendent neighbor $c(v)$. For any set $C \subseteq Q_{i,j}$, we used to refer $c(C)$ as the set of all pendent neighbors of the vertices in *C*. The vertex $\tilde{t}_{i,j}$ is made adjacent to all the

Figure 14: An illustration of the reduction of Theorem [5.4.](#page-27-0) For $1 \leq i \leq j \leq \kappa$, the vertex-block H_i and the edge-block $H_{i,j}$ are connected to the connector $C_{i,j}^i$. The initial configuration is denoted by vertices with red circle.

vertices in $c(Q_{i,j})$. We add a pendent neighbor $\hat{t}_{i,j}$ to $t_{i,j}$. For each $1 \leq i < j \leq \kappa$ and $l \in \{i, j\}$, remove the vertex subsets $B_{i,j}^l$ and $C_{i,j}^l$, and the edges incident on them in the connector $C_{i,j}^l$. We add a pendent neighbor $\tilde{s}^l_{i,j}$ to $s^l_{i,j}$ and $\tilde{r}^l_{i,j}$ to $r^l_{i,j}$. An illustration of a connector connecting a vertex-block and an edge-block is given in Figure [14.](#page-28-0) This completes the construction of graph *H* for the IS-D instance. Next we describe the initial configuration *S* as follows:

$$
S = \bigcup_{i \in [\kappa], x \in [n]} (Q_{i,x} \cup b(Q_{i,x}) \cup \bigcup_{e \in E} (Q_e \cup c(Q_e)) \cup \bigcup_{i \in [\kappa]} \{t_i, \hat{t}_i\} \cup \bigcup_{1 \leq i < j \leq \kappa} \{t_{i,j}, \hat{t}_{i,j}\}.
$$

Finally, we set $b = (4n^2 + 1)\binom{\kappa}{2} + 4nm + \kappa$ and the reduced IS-D instance is (H, S, b) .

Lemma 5.5. The *fvs* of the graph *H* is at most
$$
5\binom{\kappa}{2} + \kappa
$$
.

Proof. Let $F = \{s_{i,j}^l, r_{i,j}^l \mid 1 \leq i < j \leq \kappa, l \in \{i, j\}\} \cup \{\tilde{t}_{i,j} \mid 1 \leq i < j \leq \kappa\} \cup \{\tilde{t}_i \mid i \in [\kappa]\}.$ Removal of *F* from *H* results a forest. Therefore, the *fvs* of *H* is at most $|F| = 5{k \choose 2} + \kappa$.

Next we prove the correctness of the reduction.

Lemma 5.6. If (G, κ) is a yes-instance of the MULTI-COLORED CLIQUE problem, then (H, S, b) is a yes-instance of the IS-D problem.

Proof. Let $C = \subseteq V(G)$ be a *κ*-clique in *G*. For each $i \in [\kappa]$, let u_{i,x_i} be the vertex in $C \cap V_i$ for some $x_i \in [n]$. For each $1 \leq i < j \leq \kappa$, let $e_{i,j} = u_{i,x_i}u_{j,x_j}$. For each $i \in [\kappa]$, we slide the token on t_i to p_{i,x_i} .

For each $x \in [n]$,

- if $x = x_i$, then for each $j \neq i \in [\kappa]$, we slide x_i -tokens in Q_i^j i_{i,x_i} towards $s_{i,j}^i$ and $n - x_i$ -tokens in Q_i^j i_{i,x_i} towards $r_{i,j}^i$.
- if $x \neq x_i$, then we slide all $n(\kappa 1)$ tokens in $b(Q_{i,x})$ to \tilde{T}_i .

For each $1 \leq i \leq j \leq \kappa$, we slide the token on $t_{i,j}$ to $p_{e_{i,j}}$. For each $e \in E_{i,j}$, if $e = u_{i,x_i}u_{j,x_j}$, then we slide

- $n x_i$ tokens in $Q_{e_{i,j}}$ to $s_{i,j}^i$,
- x_i tokens in $Q_{e_{i,j}}$ to $r_{i,j}^i$,
- $n x_j$ tokens in $Q_{e_{i,j}}$ to $s_{i,j}^j$, and
- x_j tokens in $Q_{e_{i,j}}$ to $r_{i,j}^j$.

Otherwise, we slide all 2*n* tokens in $c(Q_e)$ to $\tilde{T}_{i,j}$. For each $1 \leq i \leq j \leq \kappa$, and for each $l \in i, j, s_{i,j}^l$ receives x_l -tokens from H_l and $n - x_l$ -tokens from $H_{i,j}$. Similarly, $r_{i,j}^l$ receives $n - x_l$ tokens from H_l and x_l -tokens from $H_{i,j}$. Further, we push the *n*-tokens received by $s_{i,j}^l$ to $A_{i,j}^l$ and *n*-tokens received by $r_{i,j}^l$ to $D_{i,j}^l$. The resulting configuration is a valid independent set. Finally, let $S' \subseteq V(H)$ be the solution obtained from the above token sliding steps. It is clear that the set S' is an independent set in H . Next we count the number of token steps used to obtain *S'* from *S*. In each vertex-block, we spend $2(\kappa - 1)n^2 + 1$ steps to push tokens towards the connectors and \tilde{T}_i . Similarly, at each edge-block, we spend $4n|E_{i,j}|+1$ steps. Therefore, we spend $\kappa \cdot (2(\kappa - 1)n^2 + 1) + 4nm + {k \choose 2} = (4n^2 + 1){k \choose 2} + 4nm + \kappa = b$. Hence, (H, S, b) is a yes-instance of IS-D problem. \Box

Lemma 5.7. If (H, S, b) is a yes-instance of the IS-D problem, then (G, κ) is a yes-instance of the MULTI-COLORED CLIQUE problem.

Proof. Let S^* be a feasible solution for the instance (H, S, b) of the IS-D problem. In each vertexblock H_i , we need to slide at least $n^2(\kappa - 1)$ tokens as the vertices in both sets Q_i and $b(Q_i)$ have tokens in the initial configuration. We can accommodate at most $n(n-1)(\kappa-1)$ tokens at the vertices in \tilde{T}_i . Therefore, at least $n(\kappa-1)$ token should be pushed towards connectors. Each such tokens must slide at least two steps to find a free vertex. Therefore, we need at least $2n^2(\kappa-1)$ token steps to settle the tokens on Q_i and $b(Q_i)$. Similarly, at each edge-block $H_{i,j}$, we need to slide at least $2n|E_{i,j}|$ tokens as the vertices in the sets $Q_{i,j}$ and $c(Q_{i,j})$ have tokens in the initial configuration. We can accommodate at most $2n(|E_{i,j}|-1)$ tokens at the vertices in $\tilde{T}_{i,j}$. Therefore, at least 2*n* tokens should be pushed towards connectors. Each such tokens must slide at least two steps to find a free vertex. Therefore, we need at least $4n|E_{i,j}|$ token steps to settle the tokens on $Q_{i,j}$ and $c(Q_{i,j})$. This saturates a budget of $2n^2(\kappa-1)\kappa+4nm = 4n^2\binom{\kappa}{2}+4nm$. We left with a budget of at most $\binom{\kappa}{2} + k$. In each vertex-block H_i , we still need to fix the tokens on t_i and \hat{t}_i . We can use at most one token step to fix this. Therefore, the token on t_i should move to a neighbor $p_{i,x}$ for some $x \in [n]$. Similarly, the token on $t_{i,j}$ for each $1 \leq i \leq j \leq \kappa$, should move to a neighbor p_e for some $e \in E_{i,j}$.

For each $i \in [\kappa]$, let p_{i,x_i} for some $x_i \in [n]$ be the vertex in H_i that gets token in S^* and releases all the tokens in Q_{i,x_i} . Similarly, for each $1 \leq i < j \leq \kappa$, let p_e for some $e = u_{i,z_i} u_{i,z_j} \in E_{i,j}$ with $z_i, z_j \in [n]$ be the vertex in $H_{i,j}$ that gets token in S^* and releases all tokens in Q_e . Consider the connector $\mathcal{C}_{i,j}^i$. The set Q_i^j *i*_{*i,x_i*} pushes *x_i* tokens to *s*^{*i*}_{*i,j*} and *n* − *x_i* tokens to *r*^{*i*}_{*i,j*}. The set *Q_{<i>e*} pushes

 z_i tokens to $r_{i,j}^i$ and $n-z_i$ tokens to $s_{i,j}^i$. The number of tokens passed through $s_{i,j}^i$ to $A_{i,j}^i$ is $x_i + (n - z_i)$. Since $A_{i,j}^i$ need *n* tokens, it is mandatory that $x_i = z_i$. This equality should hold for every *i*. Therefore, for each $1 \leq i < j \leq \kappa$, there exist an edge $u_{i,x_i}u_{j,x_j}$. Hence (G,κ) is an yes-instance of the MULTI-COLORED CLIQUE problem. \Box

The proofs of Lemmas [5.5,](#page-28-1) [5.6](#page-28-2) and [5.7](#page-29-0) complete the proof of Theorem [5.4.](#page-27-0)

6 Dominating Set Discovery

DS-D was shown to be W[1]-hard with respect to parameter $k + b$ on general graphs and with respect to parameter *b* on 2-degenerate graphs. On the positive side, however, it is in FPT for parameter *k* on biclique-free graphs as well as with respect to parameter *b* on nowhere dense classes of graphs [\[14\]](#page-47-2). We show in this section that the problem has polynomial kernels with respect to parameter *k* on biclique-free classes. Additionally, via a slight modification to the proofs of [Theorems 4.2](#page-13-0) and [4.3,](#page-16-0) we show that DS-D is XNLP-hard with respect to parameter *pw* and does not have a polynomial kernel with respect to the parameter $b + pw$ where *pw* is the pathwidth of the input graph unless NP ⊆ coNP*/*poly.

Theorem 6.1. Let $\mathscr C$ be a biclique-free class of graphs. Then DS-D has a polynomial kernel on $\mathscr C$ with respect to parameter k .

For the proof of [Theorem 6.1](#page-30-1) we use the concept of *k-domination cores*, which were introduced by Dawar and Kreutzer to approach domination type problems [\[8\]](#page-47-11).

Definition 6.1. Let *G* be a graph and $k \geq 1$. A set $C \subseteq V(G)$ is a *k*-domination core if every set of size at most *k* that dominates *C* also dominates *G*.

Bounded size domination cores do not exist for general graphs, however, they do exist for many important graph classes, see e.g. [\[18,](#page-47-7) [21\]](#page-47-12), most generally for semi-ladder free graphs [\[13\]](#page-47-13). For our construction of polynomial kernels it is important that biclique-free classes admit polynomial domination cores. For semi-ladder free graphs no polynomial cores are known and the proof of existence only yields an fpt and no polynomial-time algorithm. Note that the notion of cores does not appear explicitly in [\[21\]](#page-47-12), however, it is easily observed that the set of black vertices in the auxiliary RWB-dominating set problem considered in that work yields a *k*-domination core.

Lemma 6.1 (follows from [\[21\]](#page-47-12)). Let $\mathscr C$ be a biclique-free class of graphs. Then there exists a polynomial time algorithm that given $G \in \mathscr{C}$ and $k \in \mathbb{N}$ decides that *G* cannot be dominated by *k* vertices or computes a *k*-comination core $C \subseteq V(G)$ of size polynomial in *k*.

Proof of [Theorem 6.1.](#page-30-1) Let (G, S, b) be an instance of DS-D, where $G \in \mathscr{C}$ and $|S| = k$. We first compute a domination core $C \subseteq V(G)$ of size polynomial in k, which is possible by [Lemma 6.1.](#page-30-2) We then compute the projection classes of all vertices towards *C*, where we classify two vertices $u, v \in V(G)$ as equivalent if and only if $N(u) \cap C = N(v) \cap C$. The number of projection classes is polynomially bounded in $|C|$, as biclique-free classes have bounded VC-dimension. As $|C|$ is polynomially bounded we derive a polynomial bound also for the number of projection classes. For a set $M \subseteq V(G)$ and a vertex $v \in V(G)$ we define $d(v, M) = \min_{w \in M} d(v, w)$. For every projection class *X* we now fix a minimal set *R^X* of representative vertices such that for each token *t* on a vertex v_t the set R_X contains a vertex $v_{t,X}$ such that $d(v_t, v_{t,X}) = d(t,X)$. Note that R_X contains

at most *k* vertices and that such a set can be computed in polynomial time by simple breadth-first searches. We define $W \subseteq V(G)$ as the union of the vertices of *C*, the vertices of *S*, and the vertices of a shortest path between v_t and the vertex $v_{t,X}$ for each $v_t \in S$ and projection class X. We define the kernel as $(G[M], S, b)$.

First we prove that $(G[M], S, b)$ is an equivalent instance. First assume that (G, S, b) is a positive instance. Let $C_0 \vdash C_1 \vdash \ldots \vdash C_\ell$ for $\ell \leq C_b$ be a discovery sequence. We may assume that in each step a token moves on a shortest path to its final destination in C_b . As C_b is a dominating set, it dominates in particular the core C , say token t is moved to a vertex of projection class X_t . Then we obtain an equivalent discovery sequence where the token t is moved to $v_{t,X}$ instead. The same sequence exists in $G[M]$ and ends in a set of size at most k that dominates C. Hence, it also dominates $G[M]$, which shows that also $(G[M], S, b)$ is a positive instance. Conversely, a discovery sequence in $G[M]$ to a dominating set of $G[M]$ leads to a dominating set of *C* in $G[M]$, which exists exactly like this in *G*. By definition of a *k*-domination core, we also discover a dominating set in *G*.

Finally, it remains to show that *G*[*M*] has size bounded by a polynomial in *k*. As we argued already, we have a polynomial size core *C* and at most polynomially many projection classes. From each class we keep at most *k* representative vertices. It remains to show that *b* can be upper bounded by a polynomial in *k*. This is easily derived from the fact that a graph with a dominating set of size *k* can have diameter at most $3k+2$, as a shortest path with $3k+3$ vertices cannot be dominated by *k* vertices. Hence, every token arrives in its final position after at most $3k + 2$ steps and we can assume that $b \leq 3k^2 + 2k$. \Box

Theorem 6.2*.* DS-D is XNLP-hard with respect to parameter pathwidth.

As stated in [Section 3,](#page-6-0) we present a pl-reduction from MMO. Let $(H, \mathcal{P}_H, \sigma, r)$ be an instance of MMO where *H* is a bounded pathwidth graph with path decomposition \mathcal{P}_H , $|V(H)| = n$, $|E(H)| = m$, $\sigma : E(H) \to \mathbb{Z}_+$ such that $\sum_{e \in E(H)} \sigma(e) = \sigma$ and $r \in \mathbb{Z}_+$ (integers are given in unary). We construct an instance $(\tilde{G}_H, \mathcal{P}_{\tilde{G}_H}, S, b)$ of DS-D as follows (see [Figure 15\)](#page-33-0).

We form the graph \tilde{G}_H as outlined below:

- (a) We subdivide twice each edge $a_e^i b_e^i$ for each $i \in [\sigma(e)]$ for each edge $e \in E(H)$, and once each edge $a_e^{\sigma(e)+1}b_e^{\sigma(e)+1}$, of a subgraph G_e (which is the MMO-edge-*e* described in [Section 3\)](#page-6-0), and add it to \tilde{G}_H . We denote the introduced vertices between a_e^i and b_e^i by, in order, c_e^i and $c_e^{\prime i}$. We denote the introduced vertex from a subdivision of an edge $a_e^{\sigma(e)+1}b_e^{\sigma(e)+1}$ by $c_e^{\sigma(e)+1}$. We let $C_e = \bigcup_{i \in [\sigma(e)]} c_e^i$, $C = \bigcup_{e \in E(H)} C_e$, $C'_e = \bigcup_{i \in [\sigma(e)]} c_e^{i}$, $C' = \bigcup_{e \in E(H)} C'_e$, and $C^+ = \bigcup_{e \in E(H)} c_e^{\sigma(e)+1}.$
- (b) We subdivide each edge $w_v x^{v(i)}$ for $i \in [r+1]$ for each vertex $v \in V(H)$, and each edge $w_v y_e^{v(i)}$ for $uv = e \in E(H)$ and $i \in [\sigma(e)]$, of a subgraph G_v (which is the MMO-vertex*v* described in [Section 3\)](#page-6-0), and add it to \tilde{G}_H . We denote the introduced vertex from a subdivision of an edge $w_v x^{v(i)}$ by $c(x^{v(i)})$ and the introduced vertex from a subdivision of an edge $w_v y_e^{v(i)}$ by $c(y_e^{v(i)})$. We let $c(X_v) = \bigcup_{i \in [r]} c(x^{v(i)})$, $c(X) = \bigcup_{v \in V(H)} c(X_v)$, $c(X^+) = \cup_{v \in V(H)} c(x^{v(r+1)}), c(Y_e^v) = \cup_{i \in [\sigma(e)]} c(y_e^{v(i)}), c(Y^v) = \cup_{e \in E(H)} c(Y_e^v)$, and $c(Y) =$ $\cup_{v \in V(H)} c(Y_e^v)$.
- (c) We make each vertex b_e^i adjacent to the vertices $z_e^{v(i)}$ and $z_e^{u(i)}$, for each $uv = e \in E(H)$ and $i \in [\sigma(e)].$
- (d) We connect each vertex e^v and vertex in Y_e^v , for each edge $uv = e \in E(H)$, via paths of length 2. We denote the vertex between e^v and $y_e^{v(i)}$ for $i \in [\sigma(e)]$ by $c'(y_e^{v(i)})$. We let $c'(Y_e^v) = \bigcup_{i \in [\sigma(e)]} c'(y_e^{v(i)}), c'(Y^v) = \bigcup_{e \in E(H)} c'(Y_e^v),$ and $c'(Y) = \bigcup_{v \in V(H)} c'(Y^v).$
- (e) We subdivide the edges $d_1^i d_2^i$, and $d_2^i d_3^i$ for $i \in [rn \sigma]$ of the supplier gadget G_s (described under the supplier gadget and the graph \tilde{G}_H heading in [Section 3\)](#page-6-0) twice, and denote the introduced vertices by d_{1+}^i (for the vertex adjacent to d_1^i), d_{2-}^i (for the vertex adjacent to d_2^i) and d_{1+}^i), d_{2+}^i (for the other vertex adjacent to d_2^i), and d_{3-}^i (for the vertex adjacent to d_3^i). We denote the subgraph resulting from subdividing the edges of G_s by the *subdivision of* G_s .
- (f) We add the subdivision of G_s to \tilde{G}_H and make the vertex *s* adjacent to all vertices in X.
- (g) We add the edge dd' to \tilde{G}_H and make the dominator vertex *d* adjacent to all vertices in $c(Y)$.

By [Corollary 3.1,](#page-10-0) \tilde{G}_H has bounded pathwidth (as an augmented subdivision of the original graph \tilde{G}_H constructed in [Section 3\)](#page-6-0). We set $S = C \cup B \cup Y \cup c(X^+) \cup \bigcup_{uv=e \in E(H)} (e^u \cup e^v) \cup$ $\bigcup_{i\in [rn-\sigma]} (d_1^i \cup d_2^i \cup d_3^i) \cup s \cup d$ and $b = 2m + 4rn$. Given that all integers are given in unary, the construction of the graph \tilde{G}_H , or its path decomposition (as described in the discussion for [Corollary 3.1\)](#page-10-0), and as a consequence the reduction, take time polynomial in the size of the input instance. Additionally, by [Corollary 3.3,](#page-11-1) this reduction is a pl-reduction. We claim that (H, \mathcal{P}_H, w, r) is a yes-instance of MMO if and only if $(\tilde{G}_H, \mathcal{P}_{\tilde{G}_H}, S, b)$ is a yes-instance of DS-D.

Lemma 6.2. If $(H, \mathcal{P}_H, \sigma, r)$ is a yes-instance of MMO, then $(\tilde{G}_H, \mathcal{P}_{\tilde{G}_H}, S, b)$ is a yes-instance of DS-D.

Proof. Let $\lambda : E(H) \to V(H) \times V(H)$ be an orientation of the graph *H* such that for each $v \in V(H)$, the total weight of the edges directed out of *v* is at most *r*. In \tilde{G}_H , the vertices in $c(X)$, A^+ , and C^+ are not dominated. To fix that, for each edge $uv = e \in E(H)$ such that $\lambda(e) = (v, u)$:

- we move, for each $i \in [\sigma(e)]$, the token on $y_e^{v(i)}$ to any free vertex of $c(X_v)$ and the token on b_e^i to $z_e^{v(i)}$ (this consume $4\sigma(e)$ slides),
- we slide the token on e^u to $c_e^{\sigma(e)+1}$, hence dominating $a_e^{\sigma(e)+1}$ and $c_e^{\sigma(e)+1}$ (this consumes 2 slides).

This constitutes $4\sigma + 2m$ slides. We dominate the $rn - \sigma$ remaining non-dominated vertices in $c(X)$, using 4 slides per D^i path for $i \in [rn - \sigma]$ (by sliding the token on d_3^i to d_{3-}^i , the token on d_2^i to $d_{2^-}^i$ and moving the token on d_1^i to a token-free vertex in *X* that neighbors a non-dominated vertex in $c(X)$). \Box

Lemma 6.3. If $(\tilde{G}_H, \mathcal{P}_{\tilde{G}_H}, S, b)$ is a yes-instance of DS-D, then $(H, \mathcal{P}_H, \sigma, r)$ is a yes-instance of MMO.

Proof. First, note that for a vertex $a_e^{\sigma(e)+1}$, where $uv = e \in E(H)$ to be dominated with a minimal number of slides, the token on the vertex e^u or the token on the vertex e^v must move to $c_e^{\sigma(e)+1}$ (note that any other token on the vertices of the graph must pass through either e^u or e^v to get to $c_e^{\sigma(e)+1}$, thus we can safely assume that the token already on either of e^u or e^v is the token that slides to $c_e^{\sigma(e)+1}$). This consumes at least 2*m* slides, leaving 4*rn* slides.

No dominating set formed with a minimal number of slides would need to make the token on a vertex in $c(X^+)$ or the tokens on either of the vertices *s* or *d* slide (as this token must always be replaced by another to dominate the vertices in X^+ , or the vertex $d_1^{rn-\sigma+1}$, or the vertex d' , respectively, with a minimal number of slides, thus we can always assume that the token has not

Figure 15: Parts of the graph \tilde{G}_H constructed by the reduction of Theorem [6.2](#page-31-0) given an instance $(H, \mathcal{P}_H, \sigma, r)$, where *H* has three vertices *u, v,* and *w,* and two edges $e_1 = uv$ and $e_2 = uw$, and $r = 3$. Additionally, $\sigma(e_1) = 3$ and $\sigma(e_2) = 1$. For clarity, the edges between the vertices in B_{e_1} and $Z_{e_1}^u$ are missing. The same applies for the paths between e_1^v and the vertices of $Y_{e_1}^v$, the paths between e_1^u and the vertices of $Y_{e_1}^u$ as well as some of the edges between *s* and the vertices in *X*. Dotted lines incident to the vertices in *c*(*Y*) represent edges to the vertex *d* which is not shown in the figure. Red, yellow, and blue edges are used to highlight the different types of edges used to connect the subgraphs G_{e_1} , G_{e_2} , G_u , G_v , G_w and G_s of \tilde{G}_H , vertices in black are in S and those in white are not.

been moved). Thus, a pair of vertices in $c(X_v)$ and X_v for a vertex $v \in V(H)$ can be dominated by either moving the token on a vertex d_1^i for an integer $i \in [rn - \sigma]$ towards the vertex in X^v , or moving a token from a vertex $y_e^{v(i_1)}$ for an edge $uv = e \in E(H)$ and an integer $i_1 \in [\sigma(e)]$, towards the non-dominated vertex in $c(X_v)$. If the token on d_1^i moves towards the vertex in X_v , the token on d_2^i must slide to d_{2-}^i and, the token on d_3^i must slide to d_{3-}^i , so that d_{1+}^i is dominated. If a token on $y_e^{v(i_1)}$ moves towards the vertex in $c(X_v)$, it must be the case that another token has moved to either the vertex $z_e^{v(i_1)}$ or, the vertex $c(y_e^{v(i_1)})$ or, the vertex $c'(y_e^{v(i_1)})$ or, to $y_e^{v(i_1)}$ itself (to dominate $y_e^{v(i_1)}$). This however requires at least one slide per such a token (as no vertex that dominates more than one vertex in *Y* exists).

Thus, if a vertex in $c(X)$ is dominated by moving a token from one vertex d_1^i for an integer $i \in [rn - \sigma]$ towards the vertex in X, it does not consume more slides than moving a token from a vertex in *Y* towards the vertex in $c(X)$. Given that at most $rn - \sigma$ vertices can be dominated using tokens from the donor paths (as $rn - \sigma + 1$ tokens are needed to dominate the vertices in G_s), each of the at least σ remaining vertices in $c(X)$ must be dominated by moving a token from a vertex in *Y* towards a vertex in $c(X)$. Additionally, each of the remaining vertices in $c(X)$ will require at least one additional slide (besides the two slides needed to move a token from *Y*) and thus, tokens on distinct vertices in *Y* must be used to dominate the vertices in $c(X)$, as the remaining at most σ slides do not allow to get any token not initially on a vertex in *Y* to a vertex in *Y* . If the token on the vertex e^v , slides to $c'(y_e^{v(i_1)})$, it will require at least one more slide as e^u will not be dominated. Thus, the token on the vertex $b_e^{i_1}$ slides to $z_e^{v(i_1)}$ when the token on $y_e^{v(i_1)}$ moves towards a vertex in $c(X^v)$.

This totals *b* slides. For each vertex that is token-free in *Y* after the *b* slides are consumed, the adjacent vertices in $c'(Y)$ must be adjacent to a vertex of the form $e_2^{u_2}$ with a token, for an edge $u_2v_2 = e_2 \in E(H)$ (so that they are dominated). This implies that for each edge $u_2v_2 = e_2 \in E(H)$, at most $\sigma(e_2)$ tokens can move to $c(X)$ from tokens on the vertices of the sets $Y_{e_2}^{v_2}$ and $Y_{e_2}^{u_2}$, and from only one of those sets, as only one of $e_2^{u_2}$ and $e_2^{v_2}$ has a token. To dominate the σ remaining non-dominated vertices in $c(X)$, each edge $u_2v_2 = e_2 \in E(H)$ must allow $\sigma(e_2)$ tokens to move from either vertices in $Y_{e_2}^{v_2}$ and $Y_{e_2}^{u_2}$ and from at most one. This gives a feasible orientation for the instance $(H, \mathcal{P}_H, \sigma, r)$ as any of $c(X_u)$ or $c(X_v)$ can receive at most *r* tokens. \Box

The proofs of Lemmas [6.2](#page-32-0) and [6.3](#page-32-1) complete the proof of Theorem [6.2.](#page-31-0)

Theorem 6.3*.* There exists an or-cross-composition from MMO into DS-D on bounded pathwidth graphs and where the parameter is *b*. Consequently, DS-D does not admit a polynomial kernel with respect to $b + pw$, where *pw* denotes the pathwidth of the input graphs, unless NP ⊆ coNP*/*poly.

Proof. As stated in [Section 3,](#page-6-0) we can assume that we are given a family of *t* MMO instances $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$, where H_j is a bounded pathwidth graph with path decomposition \mathcal{P}_{H_j} , $|V(H_j)| = n$, $|E(H_j)| = m, \sigma_j : E_j \to \mathbb{Z}_+$ is a weight function such that $\sum_{e_j \in E(H_j)} \sigma_j(e_j) = \sigma$ and $r_j = r \in \mathbb{Z}_+$ (integers are given in unary). The construction of the instance $(\hat{G}_t, \mathcal{P}_{G_t}, S, b)$ of DS-D is twofold.

For each instance H_j for $j \in [t]$, we add to \hat{G}_t the graph G_{H_j} formed as per the construction in [Theorem 6.2,](#page-31-0) but without the supplier gadget. We refer to the sets $A, B, X, X^+, C, C', C^+, Y$, $c(X), c(X^+), c(Y)$, and $c'(Y)$, subsets of vertices of a subgraph G_{H_j} of \hat{G}_t , by A_j , B_j , X_j , X_j^+ , C_j , $C'_j, C^+_j, Y_j, c(X_j), c(X^+_j), c(Y_j)$, and $c'(Y_j)$, respectively. Similarly, we refer to the vertices d and d' of a subgraph G_{H_j} of G , by d_j and d'_j , respectively. Subsequently, we let $A = \cup_{j \in [t]} A_j$, $B = \cup_{j \in [t]} B_j$, $X = \bigcup_{j \in [t]} X_j$ and so on. We add the MMO-instance-selector (described in [Section 3\)](#page-6-0) and connect

it to the rest of \hat{G}_t as follows (see [Figure 16\)](#page-35-0). We connect, for each $j \in [t]$, the vertex SELET_j to the vertices in $V(G_{H_j}) \cap S$, where *S* is as defined later, via paths of length 2. We make the vertex *h* adjacent to each vertex in *X* and the vertex *q* adjacent to each vertex of e^u and e^v for each edge $uv = e \in E(H_j)$ for each $j \in [t]$. By [Corollary 3.2,](#page-11-2) \hat{G}_t is of bounded pathwidth. Now, we set

$$
S = C \cup B \cup A^+ \cup Y \cup X \cup c(X^+) \cup d \cup \bigcup_{j \in [t]} \text{UNSELECT}_j \cup \bigcup_{\substack{j \in [t] \\ uv = e \in E(H_j)}} (e^u \cup e^v)
$$

and $b = 2m + 6\sigma + 1$.

Figure 16: Orange, pink, and green edges highlighting the different types of edges between an MMO-instance-selector of the composition in [Theorem 6.3](#page-34-0) and a subgraph G_{H_j} for a $j \in [t]$ of the same. H_j has three vertices u, v , and w and two edges $e_1 = uv$ and $e_2 = uw$, and $r = 3$. Additionally, $\sigma_j(e_1) = 3$ and $\sigma_j(e_2) = 1$. For clarity, not all edges inside *G^H^j* are drawn, nor are all the pink edges depicted. Vertices in black are in *S* and those in white are not. Dotted lines incident to the vertices in $c(Y)$ represent edges to the vertex d_j which is not shown in the figure.

Given that all integers are given in unary, the construction of the graph \hat{G}_t or its path decomposition (as described in the discussion for [Corollary 3.2\)](#page-11-2), and as a consequence the reduction take time polynomial in the size of the input instances. Additionally, by [Corollary 3.4,](#page-12-2) this composition is a pl-reduction. We claim that $(\hat{G}_t, \mathcal{P}_{\hat{G}_t}, S, b)$ is a yes-instance of DS-D if and only if for some integer $j \in [t]$, $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ is a yes-instance of MMO.

Claim 6. If for some $j \in [t]$, $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ is a yes-instance of MMO, then $(\hat{G}_t, \mathcal{P}_{\hat{G}_t}, S, b)$ is a yes-instance of DS-D.

Proof. Let $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ be a yes-instance of MMO and let λ be a feasible orientation of H_j such that for each $v \in V(H_i)$, the total weight of the edges directed out of *v* is at most *r*. In \hat{G}_t , the vertices $f^1, \ldots, f^{\sigma}, o^1, \ldots, o^m$ and their neighbors are non-dominated. First, we slide the token on UNSELECT_j to SELECT_j. Using 2*m* slides, we move for each edge $e \in E(H_i)$ the token on e^u (resp. e^v) if $\lambda(e) = (v, u)$ (resp. $\lambda(e) = (v, u)$), towards a token-free vertex in o^1, \ldots, o^m . We additionally slide each token on a vertex b_e^i for $i \in [\sigma_j(e)]$ to the vertex $z_e^{v(i)}$ (resp. $z_e^{u(i)}$), move the token on $y_e^{v(i)}$ (resp. $y_e^{u(i)}$) towards a token-free vertex in $c(X_v)$ (resp. $c(X_u)$) and consequently, move the token on the adjacent vertex in X_v (resp. X_u) towards a token-free vertex in f^1, \ldots, f^{σ} . The total number of slides performed is *b* and they achieve a configuration for the tokens that dominates all of \hat{G}_t . \lhd

Claim 7. If $(\hat{G}_t, \mathcal{P}_{\hat{G}_t}, S, b)$ is a yes-instance of DS-D, then there exists an integer $j \in [t]$, such that $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$ is a yes-instance of MMO.

Proof. In any solution that uses the minimal number of slides, the tokens on the vertices d_j for each $j \in [t]$, and on the vertices in $c(X^+)$ do not need to be moved (as these tokens must be replaced by others to dominate the vertices d'_{j} for each $j \in [t]$, or the vertices in X^{+} , thus we can assume these tokens remain stationary). In the same solution, we can similarly assume that a token on one of UNSELECT_{*j*} and SELECT_{*j*} for each $j \in [t]$ remains on either one of those vertices. To dominate $g^1, \ldots, g^{\sigma}, p^1, \ldots, p^m$, at least $2m + 2\sigma$ slides are needed to get tokens from one or more of the vertices in *X* onto the vertices f^1, \ldots, f^{σ} , and from one of more of the vertices of the form e^u for an edge $e \in E(H_j)$ incident to a vertex $u \in V(H_j)$ for an integer $j \in [t]$, onto the vertices o^1, \ldots, o^m . If a token is moved out of a subgraph G_{H_j} (for an integer $j \in [t]$) of \hat{G}_t , which is bound to happen to get tokens onto the vertices $f^1, \ldots, f^{\sigma}, o^1, \ldots, o^m$, at least one slide is needed to dominate the vertex between now token-free vertices in G_{H_j} and SELECT_j and exactly one slide can only be achieved by sliding the token on UNSELECT_j to SELECT_j (since otherwise a token has to move from one of the vertices of a subgraph $G_{H_{j'}}$ for $j' \neq j \in [t]$ into G_{H_j} , and this requires more than one slide).

W.l.o.g. assume a token on a vertex, denoted x_v^i , in X, for a vertex $v \in V(H_i)$, and integers $j \in [t]$ and $i \in [r]$, is moved to one of the vertices f^1, \ldots, f^{σ} , then at least 3 slides are needed to move a token into either x_v^i or $c(x_v^i)$ (since the tokens on $c(X^+)$) are assumed to be stationary and a token moving from any other vertex, except x_v^i , in X into x_v^i can replace the token on x_v^i in moving into one of the vertices f^1, \ldots, f^{σ}). In a solution that uses the minimal number of slides, 3 slides can only be achieved by moving a token on a vertex, denoted $y_e^{v(i_1)}$, in Y^v , for some edge $e \in E(H_i)$ adjacent to *v* and some integer $i_1 \in [\sigma_j(e)]$, to $c(x_v^i)$. Additionally, 4 slides can only be achieved by moving a token on the same vertex to x_v^i . Since in a solution that uses the minimal number of slides a token on one of UNSELECT_j and SELECT_j is assumed to remain on either of those vertices, and a token in *B* can slide at most one slide to a vertex in *Z*, if a token on $y_e^{v(i_1)}$ is moved to a vertex in $c(X)$ (or X), either a token has to move to the vertex $z_e^{v(i_1)}$ (while a token has to be on the vertex e^v), or a token has to slide from the vertex e^v to $c'(y_e^{v(i_1)})$ or to $y_e^{v(i_1)}$ itself. Moving the token on e^v to $y_e^{v(i_1)}$ requires two slides.

Given the budget and the fact that σ tokens in any solution must move from X onto the vertices f^1, \ldots, f^{σ} , tokens must move from distinct vertices in *X* onto the vertices f^1, \ldots, f^{σ} and from distinct vertices of the form e^u for an edge $e \in E(H_j)$ incident to a vertex $u \in V(H_j)$ for an integer $j \in [t]$, onto the vertices o^1, \ldots, o^m . Additionally, given the budget, tokens in the same solution must move onto f^1, \ldots, f^{σ} from only the vertices in X_j and onto o^1, \ldots, o^m from only the vertices of the form e_1^u , for an edge $uw = e_1 \in E(H_i)$ (note that one token sliding to SELECT_j from UNSELECT_j will dominate all vertices on the paths between SELECT_j and $V(G_{H_j})$). In the same solution, if a token moves from the vertex e_1^u onto one of the vertices o^1, \ldots, o^m , the token on e_1^w remains stationary as the budget does not allow for another token to move into either one of the vertices e_1^u and e_1^w (to additionally dominate $b_{e_1}^{\sigma_j(e_1)+1}$). To fill all of o^1, \ldots, o^m with tokens, exactly one token must move from $G_{e_2}^{sel}$ onto the vertices o^1, \ldots, o^m for each edge $e_2 \in E(H_j)$. The latter implies that the token on e^v does not move to $c'(y_e^{v(i_1)})$ and given the budget that the token on $b_e^{i_1}$ slides to $z_e^{v(i_1)}$.

W.l.o.g. assume that the token on e^v does not move to one of o^1, \ldots, o^m , then at most the $\sigma(e)$ tokens on the vertices of Y_e^v can be sent to $c(X_v)$. This implies that for each edge in *H*, at most its weight in tokens can move to $c(X)$ from and to exactly one of the vertex gadgets corresponding to the vertices incident to that edge in *H*. Given that σ tokens are needed on the vertices of $c(X)$, it must be the case that for each edge, all its weight in tokens must move to $c(X)$. This gives a feasible orientation for $(H_j, \mathcal{P}_{H_j}, \sigma_j, r_j)$, since for each $v \in V(H_j)$, we have at most *r* vertices in $c(X_v)$. \triangleleft

This concludes the proof of the theorem.

Next, we consider the DS-D problem with respect to the parameter *fvs*.

Theorem 6.4*.* The DS-D problem is W[1]-hard for the parameter *fvs* of the input graph.

We present a parameterized reduction from the MULTI-COLORED CLIQUE problem, which is known to be W[1]-hard [\[7\]](#page-46-4) with respect to the solution size κ . In the MULTI-COLORED CLIQUE problem, we are given a graph *G*, and an integer κ , where $V(G)$ is partitioned into κ independent sets ${V_1, \ldots V_{\kappa}}$. The goal is to decide whether there exists a clique of size κ .

Let (G, κ) be an instance of the MULTI-COLORED CLIQUE problem. The edge set $E(G)$ can be partitioned into $\binom{\kappa}{2}$ sets $\{E_{i,j} = \{uv : u \in V_i, v \in V_j\} \mid 1 \leq i < j \leq \kappa\}$. Without loss of generality, we assume that for each $i \in [\kappa], |V_i| = n$. Otherwise, add isolated vertices in respective subsets. We usually use *n* to denote the number of vertices in the input graph. However, we use *n* to denote the number of vertices in each color class. For each $i \in [\kappa]$, let $V_i = \{u_{i,\ell} \mid \ell \in [n]\}.$

For an instance (G, κ) of the MULTI-COLORED CLIQUE problem, the reduction outputs an instance (H, S, b) of the DS-D problem. The graph *H* has an induced subgraph H_i for each $i \in [\kappa]$ and an induced subgraph $H_{i,j}$ for each $1 \leq i \leq j \leq \kappa$. We refer to these induced subgraphs as *edge-blocks* and *vertex-blocks*, respectively. Finally, the vertex-blocks and edge-blocks are connected by connectors.

Vertex-block. For each $i \in [\kappa]$, we construct a vertex-block H_i as follows. We start by adding a vertex t_i . For each $x \in [n]$, we add a star-tree rooted at $p_{i,x}$ with $n(\kappa - 1)$ leaves $\{q_{i,x}^{j,1}, \ldots, q_{i,x}^{j,n}\}$ $j \neq i$. Each vertex $p_{i,x}$ is connected with t_i by an edge. For each $x \in [n]$ and $j \neq i \in [k]$, let $Q_{i,x}^j = \{q_{i,x}^{j,\ell} \mid \ell \in [n]\}$. For each $x \in [n]$, $Q_{i,x} = \bigcup Q_{i,x}^j$. Further, for each $i \in [\kappa]$, let $j \neq i \in [\kappa]$

$$
Q_i = \bigcup_{x \in [n]} Q_{i,x}.
$$

Edge-block. For each $1 \leq i \leq j \leq \kappa$, we construct a edge-block $H_{i,j}$ as follows. We start by adding a vertex $t_{i,j}$. For each edge $e \in E_{i,j}$, we add a star-tree rooted at p_e with $2n$ leaves q_e^1, \ldots, q_e^{2n} . Each vertex p_e is connected with t_i by an edge. For each $e \in E_{i,j}$, let $Q_e = \{q_e^{\ell} | \ell \in [2n]\}$. Further, for each $1 \leq i < j \leq \kappa$, $Q_{i,j} = \bigcup$ *e*∈*Ei,j Qe*.

Connector. For each $1 \leq i < j \leq \kappa$ and for each $l \in \{i, j\}$, we construct a connector $\mathcal{C}_{i,j}^l$ as follows. Let $A_{i,j}^l = \{a_{i,j}^{l,1}, \ldots, a_{i,j}^{l,n}\}, B_{i,j}^l = \{b_{i,j}^{l,1}, \ldots, b_{i,j}^{l,n}\}, C_{i,j}^l = \{c_{i,j}^{l,1}, \ldots, c_{i,j}^{l,n}\}$ and $D_{i,j}^l = \{d_{i,j}^{l,1}, \ldots, d_{i,j}^{l,n}\}.$ We add $4n+2$ vertices $(\{s_{i,j}^l, r_{i,j}^l\} \cup A_{i,j}^l \cup B_{i,j}^l \cup C_{i,j}^l \cup D_{i,j}^l)$. For each $x \in [n]$, we add the edges $s_{i,j}^{l}a_{i,j}^{l,x}, a_{i,j}^{l,x}b_{i,j}^{l,x}, r_{i,j}^{l}c_{i,j}^{l,x}$ and $c_{i,j}^{l,x}d_{i,j}^{l,x}$.

For each $1 \leq i < j \leq \kappa$ and $l \in \{i, j\}$, the vertex-block H_l is connected with the connector $\mathcal{C}_{i,j}^l$ as follows. Let $l' \neq l \in \{i, j\}$. For each $x, z \in [n]$,

- if $z \leq x$, then add an edge $q_{l,x}^{l',z}s_{i,j}^{l}$, and
- if $z > x$, then add an edge $q_{l,x}^{l',z} r_{i,j}^{l}$.

For each $1 \leq i < j \leq \kappa$, the edge-block $H_{i,j}$ is connected with the connectors $\mathcal{C}_{i,j}^i$ and $\mathcal{C}_{i,j}^j$ as follows. For each $e = u_{i,x}u_{j,y} \in E_{i,j}$ for some $x, y \in [n]$, and for each $z, w \in [n]$,

- if $z \leq x$, then add an edge $q_e^z r_{i,j}^i$,
- if $z > x$, then add an edge $q_e^z s_{i,j}^i$,

Figure 17: An illustration of the reduction of Theorem [6.4.](#page-37-0) For $1 \leq i \leq j \leq \kappa$, the vertex-block H_i and the edge-block $H_{i,j}$ are connected to the connector $\mathcal{C}_{i,j}^i$. The initial configuration is denoted by vertices with red circle.

- • if $w \leq y$, then add an edge $q_w^{n+w} r_{i,j}^j$, and
- if $w > y$, then add an edge $q_{l,x}^{n+w} s_{i,j}^j$.

For a pair (i, j) with $1 \leq i < j \leq \kappa$, an illustration of a connector $\mathcal{C}_{i,j}^i$ that connects V_{H_i} and $H_{i,j}$ is given in Figure [17.](#page-38-0) This completes the construction of the graph *H*. Further, we set $b = (8n+1)\binom{\kappa}{2} + \kappa$, and we define the initial configuration *S* as follows:

$$
S = \bigcup_{i \in [\kappa], x \in [n]} Q_{i,x} \cup \bigcup_{e \in E} Q_e \cup \{t_i \mid i \in [\kappa] \} \cup \{t_{i,j} \mid 1 \le i < j \le \kappa\}.
$$

Lemma 6.4. The *fvs* of the graph *H* is at most $4\binom{\kappa}{2}$.

Proof. Let $F = \{s_{i,j}^i, r_{i,j}^i, s_{i,j}^j, r_{i,j}^j \mid 1 \leq i < j \leq \kappa\}$. Removal of F from H results a forest. Therefore, the *fvs* of *H* is at most $|F| = 4{k \choose 2}$.

Lemma 6.5. If (G, κ) is a yes-instance of the MULTI-COLORED CLIQUE problem, then (H, S, b) is a yes-instance of the DS-D problem.

Proof. Let $C = \subseteq V(G)$ be a *κ*-clique in *G*. For each $i \in [\kappa]$, let u_{i,x_i} be the vertex in $C \cap V_i$ for some $x_i \in [n]$. For each $1 \leq i < j \leq \kappa$, let $e_{i,j} = u_{i,x_i}u_{j,x_j}$. For each $i \in [\kappa]$, we slide the token on t_i to p_{i,x_i} . Then, for each $j \neq i \in [\kappa]$, we slide x_i -tokens in Q_i^j i_{i,x_i} towards $s_{i,j}^i$ and $n - x_i$ -tokens in Q_i^j *i,xⁱ* towards $r_{i,j}^i$. For each $1 \leq i < j \leq \kappa$, we slide the token on $t_{i,j}$ to $p_{e_{i,j}}$.

Then, we slide

- $n x_i$ tokens in $Q_{e_{i,j}}$ to $s_{i,j}^i$,
- x_i tokens in $Q_{e_{i,j}}$ to $r_{i,j}^i$,
- $n x_j$ tokens in $Q_{e_{i,j}}$ to $s_{i,j}^j$, and
- x_j tokens in $Q_{e_{i,j}}$ to $r_{i,j}^j$.

For each $1 \leq i < j \leq \kappa$, and for each $l \in i, j$, $s_{i,j}^l$ receives x_l -tokens from H_l and $n - x_l$ -tokens from $H_{i,j}$. Similarly, $r_{i,j}^l$ receives $n - x_l$ -tokens from H_l and x_l -tokens from $H_{i,j}$. Further, we push the *n*-tokens received by $s_{i,j}^l$ to $A_{i,j}^l$ and *n*-tokens received by $r_{i,j}^l$ to $D_{i,j}^l$. The above token slides result the following. For each $i \in [\kappa]$,

- t_i is dominated by p_{i,x_i} ,
- for each $j \neq i \in [\kappa]$, the vertices in Q_i^j \sum_{i,x_i}^{j} are dominated by p_{i,x_i} , and
- for each $\ell \neq x_i \in [n]$, $p_{i,\ell}$ is dominated by $Q_{i,\ell}^j$ for any $j \neq i$.

for each $1 \leq i < j \leq \kappa$,

- $t_{i,j}$ is dominated by $p_{e_{i,j}}$,
- the vertices in $Q_{e_{i,j}}$ are dominated by $p_{e_{i,j}}$, and
- for each $e \neq e_{i,j} \in E_{i,j}$, p_e is dominated by the vertices in Q_e .

Finally, let $S' \subseteq V(H)$ be the solution obtained from the above token sliding steps. More precisely,

$$
S' = \bigcup_{i \in [\kappa]} \{ \{p_{i,x_i}\} \cup (Q_i \setminus Q_{i,x_i})\} \cup \bigcup_{1 \leq i < j \leq \kappa} \{ \{p_{e_{i,j}}\} \cup (Q_{i,j} \setminus Q_{e_{i,j}})\} \cup \bigcup_{1 \leq i < j \leq \kappa, l \in \{i,j\}} (A_{i,j}^l \cup D_{i,j}^l).
$$

It is clear that the set S' is a dominating set in H . Next we count the number of token steps used to obtain *S'* from *S*. In each vertex-block, we spend $(\kappa - 1)n + 1$ steps to push tokens towards the connectors. Similarly, at each edge-block, we spend $(2n+1)$ steps. At each connectors, we spend 2*n* steps. Therefore, we spend $\kappa \cdot ((\kappa - 1)n + 1) + {\kappa \choose 2} \cdot (2n + 1) + 2{\kappa \choose 2} \cdot 2n = (8n + 1){\kappa \choose 2} + \kappa = b$. Hence, (H, S, b) is a yes-instance of DS-D problem. \Box

Lemma 6.6. If (H, S, b) is a yes-instance of the DS-D problem, then (G, κ) is a yes-instance of the MULTI-COLORED CLIQUE problem.

Proof. Let S^* be a feasible solution for the instance (H, S, b) of the DS-D problem. At each connector $\mathcal{C}_{i,j}^l$ for $1 \leq i < j \leq \kappa$ and $l \in \{i,j\}$, at least 2*n* tokens need to be slid from either vertex-blocks or edge blocks. It is clear that every token must move at least 2 steps to reach the sets $A^*_{*,*}$ and $D^*_{*,*}$ in order to dominate the vertices in the set $B^*_{*,*}$ and $C^*_{*,*}$, respectively. This saturates a budget of $4n \cdot 2{k \choose 2} = 8n{k \choose 2}$. Therefore, we left with exactly $\kappa + {k \choose 2}$ budget to adjust the tokens on the vertex blocks and edge blocks. For any $1 \leq i < j \leq \kappa$, let $q_{i,x}^{j,z}$ for some integers $x, z \in [n]$ be a vertex that looses the token where the token is moved to some vertex in a connector. Since none of its neighbors have token, we need to slide a token to the vertex or to it's neighbors. This cost at least one token step. By construction of the vertex-block H_i , by sliding a token to the vertex $p_{i,x}$ for some $x \in [n]$, one can release at most $n(\kappa - 1)$ tokens from the neighboring set $Q_{i,x}$. Similarly, on an edge-block $H_{i,j}$ for some $1 \leq i \leq j \leq \kappa$, by sliding a token to the vertex p_e for some $e \in E_{i,j}$, one can release at most 2*n* tokens from the neighboring set Q_e . This implies that by sliding at most κ tokens on the vertex-blocks, one can release at most $\kappa \cdot n(\kappa - 1) = 2n\binom{\kappa}{2}$ token from the vertex-blocks. Similarly, by sliding at most $\binom{\kappa}{2}$ tokens on the edge-blocks, one can release at most $2n\binom{\kappa}{2}$ tokens from the edge-blocks. Therefore, we need to slide exactly one token in each vertex-block and each edge-block.

For each $i \in [\kappa]$, let p_{i,x_i} for some $x_i \in [n]$ be the vertex in H_i that gets token in S^* and releases all the tokens in Q_{i,x_i} . Similarly, for each $1 \leq i < j \leq \kappa$, let p_e for some $e = u_{i,z_i} u_{i,z_j} \in E_{i,j}$ with $z_i, z_j \in [n]$ be the vertex in $H_{i,j}$ that gets token in S^* and releases all tokens in Q_e . Consider the connector $\mathcal{C}_{i,j}^i$. The set Q_i^j *i*_{*i,x_i*} pushes *x_i* tokens to *s*^{*i*}_{*i,j*} and *n* − *x_i* tokens to *r*^{*i*}_{*i,j*}. The set *Q_{<i>e*} pushes z_i tokens to $r_{i,j}^i$ and $n-z_i$ tokens to $s_{i,j}^i$. The number of tokens passed through $s_{i,j}^i$ to $A_{i,j}^i$ is $x_i + (n - z_i)$. Since $A_{i,j}^i$ need *n* tokens, it is mandatory that $x_i = z_i$. This equality should hold for every *i*. Therefore, for each $1 \leq i < j \leq \kappa$, there exist an edge $u_{i,x_i}u_{j,x_j}$. Hence (G,κ) is an yes-instance of the MULTI-COLORED CLIQUE problem. \Box

The proofs of Lemmas [6.4,](#page-38-1) [6.5](#page-38-2) and [6.6](#page-39-0) complete the proof of Theorem [6.4.](#page-37-0)

7 Shortest Path Discovery

Finally, we show that SP-D does not admit a polynomial kernel unless NP ⊆ coNP*/*poly. The employed or-cross-composition is similar to the construction in the hardness proof of SP-D presented in [\[16,](#page-47-3) Theorem 4.2]. We denote an instance of SP-D by (G, S, b, a, b) to emphasize that the solution must be a shortest path between the vertices a and b in $V(G)$ (for consistency with the previous sections we do not speak of *s*-*t*-connectivity but use *t* for the number of instances in the cross composition).

Theorem 7.1. There exists an or-cross-composition from HAMILTONIAN PATH into SP-D, parameterized by $k + b$. Consequently, SP-D does not admit a polynomial kernel with respect to $k + b$, unless $NP \subseteq coNP/poly$.

Proof. Let \mathcal{R} be the polynomial equivalence relation whose equivalence classes are defined by graphs with the same number of vertices, that is, two graphs G and H are equivalent with respect to $\mathcal R$ if and only if $|V(G)| = |V(H)|$. Let G_1, \ldots, G_t be a sequence of instances of HAMILTONIAN PATH, where every G_j , $j \leq t$, is an *n*-vertex graph, say $V(G_j) = \{1, \ldots, n\}$. For every G_j we create a new graph H_j that consists of n^2 vertices, say (x, y) for $x, y \leq n$. For every $x < n$ and $y, y' \leq n$, we connect the vertex (x, y) with the vertex $(x + 1, y')$ if and only if $yy' \in E(G_j)$.

We construct the following graph *G*. First, *G* consists of a disjoint union of all H_j , $j \leq t$. Furthermore, we add two fresh vertices *a* and *b*, as well as *n* fresh vertices (we simply call them $\{1, \ldots, n\}$, too) to the vertex set of *G*. For every $y \leq n$ we connect the vertex *a* with every vertex $(1, y)$ in every H_j . Also, for every $y \leq n$ we connect every vertex (n, y) in every H_j with *b*. Finally, for every $x \leq n$ we connect the vertex x in G with every vertex (x, y) in every H_j for all $y \leq n$ with a path of length *n*. This finishes the construction of *G*. Let $S = \{a, b, 1, \ldots, n\}$, hence $k = n + 2$ and $b = n^2$. Observe that the size of every G_j is (given a suitable encoding) bounded by n^2 . Hence, the parameter $k + b = n^2 + n + 2$ is bounded by a polynomial in $\max_{j=1}^{t} |G_j| + \log t$. We claim that (G, S, b, a, b) is a yes-instance of SP-D if and only if at least one G_j admits a Hamiltonian path.

We begin with the backward direction, that is let G_j be a Hamiltonian graph with Hamiltonian path $i_1 \ldots i_n$. Then we can move the token on vertex *x* in *G* to (x, i_x) in H_j using *n* slides for each token. This forms a shortest *a*-*b*-path in *G* which is discovered with the budget $b = n^2$.

For the other direction assume that (G, S, b, a, b) is a yes-instance of SHORTEST PATH DISCOVERY and observe that every shortest $a-b$ -path in G (which is of length $n+1$ and hence uses n internal vertices) uses internal vertices from one H_j only. By the choice of the budget and the connections between vertices *x* and (*x, y*), every solution can only move the token from vertex *x* to a vertex of the form (x, y) for some $y \leq n$ in H_i . Let $a(1, y_1)(2, y_2) \ldots (n, y_n)t$ be the discovered *a*-*b*-path in *G*. By construction, we have $y_i \neq y_{i'}$ for $i \neq i'$. Hence $y_1 \ldots y_n$ is a Hamiltonian path in G_j . \Box

8 Matching Discovery

Grobler et al. [\[16\]](#page-47-3) show that MAT-D is $W[1]$ -hard with respect to the parameter *b* on 3-degenerate graphs, yet it is in FPT with respect to parameter *k* on general graphs. We show that, similarly to VC-D, Mat-D admits a polynomial kernel with respect to the parameter *k*.

In a manner akin to [Theorem 5.1,](#page-22-0) our kernelization algorithm for Mat-D with respect to the parameter *k* will remove from the graph vertices that are irrelevant for every token. Here however, to find irrelevant vertices or edges, we will make use of a classical result of Erdős and Rado [\[12\]](#page-47-10) known in the literature as the *sunflower lemma*.

Theorem 8.1 ([\[12\]](#page-47-10)). Let A be a family of sets (without duplicates) over a universe U , such that each set in A has cardinality at most *d*. If $|\mathcal{A}| > d!(p-1)^d$, then A contains a sunflower with *p* petals and such a sunflower can be computed in time polynomial in $|A|, |U|$, and p.

Theorem 8.2. MAT-D admits a kernel of size $\mathcal{O}(k^5)$.

Proof. Let (G, S, b) be an instance of MAT-D. Without loss of generality, we assume the graph *G* to be connected. For each vertex $s \in S$, and integer $i \in [3k]$, we compute $E(s, i)$. We maintain the invariant that we remove from $E(s, i)$ for each $s \in S$ and $i \in [3k]$, irrelevant vertices with respect to *s*.

We remove an irrelevant edge with respect to a vertex $s \in S$ from $E(s, i)$ for an integer $i \in [3k]$ as follows. From the sunflower lemma [\(Theorem 8.1\)](#page-41-2), if $|E(s, i)| > 8k^2$, then it has a sunflower with 2*k* + 1 petals that can be computed in polynomial time in *k*. We arbitrarily choose one edge *e* corresponding to one petal of the sunflower and remove it from $E(s, i)$. To see why *e* is irrelevant with respect to *s*, assume that the token on *s* slides to $e \in C_{\ell}$, where C_{ℓ} is a matching in *G*. The 2*k* − 2 vertices of $C_{\ell} \setminus \{e\}$ can be incident to at most 2*k* − 2 of the edges corresponding to the petals of the sunflower, leaving at least one petal with an edge e_1 that can replace e in the matching C_{ℓ} in *G*. Since also all edges in $E(s, i)$ are at the same distance *i* from *s*, replacing *e* by e_1 will not increase the number of slides needed to achieve $C_{\ell} \setminus \{e\} \cup \{e_1\}.$

We form the kernel (G', S, b) of the original instance (G, S, b) as follows. First, note that for a token $s \in S$ and an edge $e \in E(H) \cap C_{\ell}$ such that $d(s, e) > 3k$, the edges in $C_{\ell} \setminus \{e\}$ can appear in at most $k-1$ of the 3*k* sets of edges $E(s, i)$ for $i \in [3k]$ and every such edge that appears in a set *E*(*s*, i) for a specific $i \in [3k]$ can be incident to at most all the edges in $E(s, i - 1)$ and $E(s, i + 1)$. This implies that the token on *s* cannot move towards any edge of at most $3k-3$ of the 3*k* sets $E(s, i)$ for $i \in [3k]$ (as these contain tokens and thus might result in incident tokens) and thus there exists an edge e_1 which the token on *s* can move to while maintaining a matching in $C_\ell \setminus \{e\} \cup \{e_1\}$. Thus, in any solution to (G, S, b) , if a token on an edge $s \in S$ moves to an edge $e \in C_{\ell}$ such that $d(s, e) > 3k$, it can instead move towards an edge $e_1 \in E(H)$ such that $d(s, e_1) \leq 3k$, while keeping the rest of the solution unchanged. Consequently, we set $E(G') = \bigcup_{s \in S, i \in [3k]} E(s, i) \cup S$ and for each edge $e \in E(s, i)$, for $s \in S$ and $i \in [3k]$, we add to $E(G')$ at most i edges that are on the shortest path from *s* to *e* (if such edges are not already in $E(G')$). G' is the subgraph of G induced

by the edges in $E(G')$. By the end of this process, $|E(G')| \leq k + 9k^3 \cdot 8k^2$, as for each $s \in S$ and $i \in [3k]$, $E(s, i) \leq 8k^2$ and for each edge of the latter $3k^2$ sets of edges, we added to $E(G')$ at most $3k - 1$ edges that are on a shortest path from that edge to the edge *s*. (G', S, b) is a kernel as only edges that are irrelevant with respect to every token in *S* might not be in *E*(*G*′) and all edges needed to move tokens from edges in S towards a matching using only b slides are present in $E(G')$. \Box

9 Vertex Cut Discovery

Grobler et al. [\[16\]](#page-47-3) showed that VCUT-D is $W[1]$ -hard with respect to parameter *b* on 2-degenerate bipartite graphs but is in FPT with respect to the parameter *k* on general graphs. We show that the problem admits no polynomial kernels unless NP ⊆ coNP/poly. We denote an instance of VCuT-D by (G, S, b, a_1, b_1) to emphasize that the solution must be a vertex cut between a_1 and b_1 in $V(G)$.

Given a graph *H* and an edge coloring $\varphi : E(H) \to [c]$, we say φ is proper if, for all distinct edges $e, e_1 \in E(H), \varphi(e) \neq \varphi(e_1)$ whenever *e* and e_1 share a vertex. We form our or-cross-composition from the RAINBOW MATCHING problem, which is NP-complete even on properly colored 2-regular graphs and where every $i \in [c]$ is used exactly twice in the coloring [\[19\]](#page-47-1):

RAINBOW MATCHING:

Input: Graph *H*, a proper edge coloring φ and an integer κ .

Question: Does *H* have a rainbow matching, i.e., a matching whose edges have distinct colors, with at least κ edges?

Theorem 9.1. There exists an or-cross-composition from RAINBOW MATCHING into VCUT-D where the parameter is the number of tokens, k . Consequently, VCUT-D does not admit a polynomial kernel with respect to k , unless $\mathsf{NP} \subseteq \mathsf{coNP/poly}$.

Proof. By choosing an appropriate polynomial equivalence relation \mathcal{R} , we may assume that we are given a family of *t* RAINBOW MATCHING instances $(H_r, \varphi_r, \kappa_r)$, where H_r is a 2-regular graph, $|V(H_r)| = n$, $|E(H_r)| = m$, $\kappa_r = \kappa \in \mathbb{N}$, and $\varphi_r : E(H_r) \to [c]$ is a mapping that properly colors H_r and in which every $i \in [c]$ is used exactly twice. We may duplicate some input instances so that $t = 2^s$ for some integer *s*. Note that this step at most doubles the number of input instances. The construction of the instance (G, S, b, a_1, b_1) of VCu_T-D is twofold.

For each instance $(H_r, \varphi_r, \kappa_r)$, we create G_r , formed of two vertices, s_r and t_r , as well as $\kappa - 1$ sets $\{E_r^1, \ldots, E_r^{\kappa-1}\}\$ of $2m+2$ vertices each. A set E_r^p for $p \in [\kappa-1]$ contains $2m$ vertices, denoted *edge-vertices*, that represent the edges in H_r twice and two other vertices which are denoted by s_r^p and t_r^p (see [Figure 18\)](#page-44-0). We denote the edge-vertices in a set E_r^p as $v_{e_h}^{p,r}(1)$ $(v_{e_h}^{p,r}(2))$ to refer to the first (second) vertex representing the same edge e_h of $E(H_r)$ in E_r^p . We denote by $E_r^p(1)$ the set of all vertices $v_{e_h}^{p,r}(1)$, and by $E_r^p(2)$ the set of all vertices $v_{e_h}^{p,r}(2)$. In G_r , we connect:

- through paths of length $m^3 + \log t$, s_r to each of s_r^p for $p \in [\kappa 1]$ and t_r to each of t_r^p for $p \in [\kappa - 1],$
- through paths of length $m^3 + \log t$, s_r^p to all vertices $v_{e_h}^{p,r}(1)$ and t_r^p to all vertices $v_{e_h}^{p,r}(2)$ for each $e_h \in E(H_r)$ and each $p \in [\kappa - 1]$,
- through paths of length $m^3 + \log t$, all vertices $v_{e_h}^{p,r}(1)$ and $v_{e_g}^{q,r}(2)$ such that $\varphi_r(e_h) = \varphi_r(e_g)$ for each $p \le q \in [\kappa - 1],$
- through paths of length $m^3 + \log t$, $v_{e_h}^{p,r}(1)$ and $v_{e_g}^{q,r}(2)$, for each $p \le q \in [\kappa 1]$, whenever e_h and e_q are incident in H_r ,

• through paths of length $m^3 + \log t$, $v_{e_h}^{p,r}(2)$ and $v_{e_g}^{q,r}(1)$, for each $p \in [\kappa - 2]$, $q = p + 1$, whenever $e_h \neq e_q$.

We form *G* of all G_r for $r \in [t]$ as follows (see [Figure 19\)](#page-45-0). We create two global vertices a_1 and b_1 such that b_1 is connected through paths of length $m^3 + \log t$ to t_r for $r \in [t]$. Additionally, we create a binary tree $\mathcal T$ rooted at a_1 , with $\log t + 1$ levels, and whose leaves constitute s_r for $r \in [t]$. For each depth *d* of \mathcal{T} for $d \in \{1, \ldots, \log t\}$, we create a vertex v^d that contains a token and is connected through a single edge to each vertex of $\mathcal T$ that is at depth *d*. The edges of $\mathcal T$ are all replaced by paths of length $m^3 + \log t$. Finally, we create $2(\kappa - 1)$ sets $\{M_1, \ldots, M_{2(\kappa-1)}\}\)$, of *m* − 1 edges each. We connect each edge $e^{(i,j)} \in M_i$ for $i \in [2(\kappa-1)]$ and $j \in [m-1]$, from one of its endpoints, denoted $u^{(i,j)}$, to each vertex $v_{e_h}^{[i/2],r}(1)$ for each $r \in [t]$ if *i* is odd, and to each vertex $v_{e_h}^{[i/2],r}(2)$ for each $r \in [t]$ if *i* is even. Additionally, we connect through paths of length $m^3 + \log t$, each s_r and t_r for $r \in [t]$ to all of $u^{(i,j)}$ for $i \in [2(\kappa-1)]$ and $j \in [m-1]$. All vertices in the sets ${M_1, \ldots, M_{2(\kappa-1)}}$ contain tokens. Setting $b = \log t + 2(2\kappa - 2) \cdot (m-1)$ finalizes the construction of (G, S, b, a_1, b_1) . Since we perform only a polynomial number of operations per instance as well as some polynomial in t other operations while creating the tree $\mathcal T$ and connecting some vertices, the reduction is polynomial in $\Sigma_{i=1}^t |x_i|$. Additionally, *k* is $O(m^2 + \log t)$ since $\kappa \leq m$.

Claim 8. If for some $\mathfrak{r} \in [t]$, $(H_{\mathfrak{r}}, \varphi_{\mathfrak{r}}, \kappa_{\mathfrak{r}})$ is a yes-instance of RAINBOW MATCHING, then the constructed instance (G, S, b, a_1, b_1) is a yes-instance of VCu_T-D.

Proof. Let \mathcal{M}_r be a solution to the instance $(H_r, \varphi_r, \kappa_r)$. $\mathcal{M}_r \subseteq E(H_r)$ forms a matching in H_r such that $\varphi_{\mathfrak{r}}(e_h) \neq \varphi_{\mathfrak{r}}(e_g)$, for all $e_h, e_g \in \mathcal{M}_{\mathfrak{r}}$. We apply the following slides in (G, S, b, a_1, b_1) to disconnect a_1 from b_1 . First, we choose one edge e_h of \mathcal{M}_r and using $m-1$ slides, we slide the tokens on $u^{(1,j)}$ for $j \in [m-1]$ onto all vertices in $E^1_{\mathfrak{r}}(1)$ except $v^{1,\mathfrak{r}}_{e_h}(1)$. Then, using $(2\kappa-3) \cdot (m-1)$ slides, for each $i \in [\kappa - 1]$, we choose one other edge $e_s \in \mathcal{M}_r$ and slide the tokens on $u^{(2i,j)}$ and $u^{(2i+1,j)}$ (when applicable) for $j \in [m-1]$ onto all vertices in $E_{\mathfrak{r}}^{i}(2)$ and $E_{\mathfrak{r}}^{i+1}(1)$ except $v_{e_s}^{i,\mathfrak{r}}(2)$ and $v_{e_s}^{i+1,\mathfrak{r}}(1)$, respectively. We slide onto $u^{(i,j)}$ for all $i \in [2(\kappa-1)]$ and $j \in [m-1]$ the tokens adjacent to the latter vertices, on the edges in $\{M_1, \ldots, M_{2(\kappa-1)}\}$, using $(2\kappa - 2) \cdot (m - 1)$ slides. Finally, in \mathcal{T} , we use the tokens on the vertices v^d for $d \in \{1, \ldots, \log t\}$, to disconnect all paths from the root a_1 to all of s_r for $r \in [t] - \{\tau\}$, using one slide per token. This ensures that, through at most log *t* slides, all paths from *a*¹ to *b*¹ go through only both *s*^r and *t*^r . Following the described steps, we have executed a total of *b* slides. To see that *a*¹ and *b*¹ are now disconnected, note that after the slides of the tokens on u^d for $d \in \{1, \ldots, \log t\}$ are performed, all paths from a_1 to b_1 in *G* go through s_t and t_t . Thus it suffices to argue that the remaining $2(2\kappa - 2) \cdot (m - 1)$ slides disconnect s_t and t_t . First, if this is not the case, then no path between s_t and t_t goes through any $u^{(i,j)}$ for all $i \in [2(\kappa-1)]$ and $j \in [m-1]$ since the tokens that left those vertices have been replaced. Also, the last four vertices on any path between s_t and t_t must be $v_{e_h}^{p,\mathfrak{r}}(1)$ for some $p \in [\kappa - 1]$ and some $e_h \in E(H_{\mathfrak{r}})$, $v_{e_g}^{q,\mathfrak{r}}(2)$ for some $q \in \{p, \ldots, \kappa - 1\}$ and some $e_q \in E(H_{\mathfrak{r}})$, $t_{\mathfrak{r}}^q$ and $t_{\mathfrak{r}}$. However, by construction, there exists no paths between all vertices $v_{e_h}^{p,\mathfrak{r}}(1)$ and $v_{e_g}^{q,\mathfrak{r}}(2)$ for each $p \leq q \in [\kappa-1]$, such that $\varphi_{\mathfrak{r}}(e_h) \neq \varphi_{\mathfrak{r}}(e_g)$ and e_h and e_g are non-adjacent. Thus, given our choice of the free vertices remaining in $E_{\rm t}^p(.)$ for all $p \in [\kappa - 1]$, no path exists between s_t from t_t and therefore between a_1 and b_1 .

Claim 9. If (G, S, b, a_1, b_1) is a yes-instance of VCu_T-D, then there exists an integer $\mathfrak{r} \in [t]$ for which $(H_{\mathfrak{r}}, \varphi_{\mathfrak{r}}, \kappa_{\mathfrak{r}})$ is a yes-instance of RAINBOW MATCHING.

Figure 18: An illustration of $E_1^1, E_1^2, s_1^1, t_1^1, s_1^2$, and t_1^2 of G_1 of the or-cross-composition of Theorem [9.1.](#page-42-1) In H_1 , the vertices are *a*, *b*, *c*, *d*, *e*, *f*, *g*, *h*, *i*, and *j*. For simplification purposes, the figure illustrates the types of edges but does not contain all edges between the illustrated vertices. Length $m^3 + \log t$ paths are represented by the edges (regular or dotted). Vertices in red brackets are in $E_1^1(1)$ and those in beige brackets are in $E_1^1(2)$. Blue edges are between vertices representing edges of the same color in H^1 and dotted ones between all $v_{e_h}^{p,r}(2)$ and $v_{e_g}^{q,r}(1)$ for $q = p + 1$, whenever $e_h \neq e_g$. Finally, orange edges show that the edges, represented by the adjacent edge-vertices, are adjacent in H_1 . In G_1 , length $m^3 + \log t$ paths exist between s_1 and both of s_1^1 and s_1^2 and between t_1 and both of t_1^1 and t_1^2 . No vertex in this figure contains a token (colored vertices display the colors of the edges in the instance (H_1, φ_1, r_1)).

Figure 19: An illustration of the graph *G* formed as per the composition of [Theorem 9.1](#page-42-1) given input instances $(H_r, \varphi_r, \kappa_r)$ for $r \in [8]$, where $\kappa_r = \kappa \geq 3$. For clarity, the graphs G_r for $r \in [8]$ were replaced by rectangles with blue borders incident to two blue vertices s_r and t_r of G_r . Pink edges are used to illustrate how the vertices v^d for $d \in [3]$ connect to the vertices of $\mathcal T$. Dotted lines represent paths of length $m^3 + \log t$ between the vertices and thick edges are used to represent that a vertex is adjacent to all vertices in a set of vertices. The yellow, pink, and blue rectangular areas on the left provide a zoomed-in view of some of the content of *G*1, *G*2, and *G*3, respectively. Particularly, they show the sets of vertices $E_1^1(1)$, $E_1^1(2)$, $E_2^1(1)$, $E_2^1(1)$, $E_2^1(2)$, $E_2^2(1)$, $E_3^1(1)$, $E_3^1(2)$, and $E_3^2(1)$. For clarity, not all edges between vertices of the form $u(i, j)$ for $i \in [2(\kappa - 1)]$ and $j \in [m - 1]$, and both vertices s_r and t_r for $r \in [8]$ are shown.

Proof. Assume C_{ℓ} for $\ell \leq b$, is a solution to (G, S, b, a_1, b_1) that is reached with only $2(2\kappa - 2)$. $(m-1) + \log t$ slides and disconnects a_1 from b_1 , then any token that slides in *G* slides at most once, given that everything except:

- for $d \in \{1, \ldots, \log t\}$, the vertex v^d and each vertex of $\mathcal T$ that is at level d ,
- $u^{(i,j)}$ for $i \in [2(\kappa-1)]$ and $j \in [m-1]$, to each vertex $v_{e_h}^{[i/2],r}(1)$ for each $r \in [t]$ if *i* is odd, and to each vertex $v_{e_h}^{[i/2],r}(2)$ for each $r \in [t]$ if *i* is even,
- the endpoints of each edge $e^{(i,j)} \in M_i$ for $i \in [2(\kappa-1)]$ and $j \in [m-1]$,

is connected by paths of length $(m^3 + \log t) > b$. Thus, we know that the tokens on the vertices v^d for $d \in \{1, \ldots, \log t\}$ will have to leave some paths that go from a_1 to b_1 at least through one pair of vertices s_t and t_t for some $\mathfrak{r} \in [t]$ and can use at most log *t* slides. We know that in $G \setminus C_{\ell}$, no path exists between s_t and t_t . Since no token can reach s_t and t_t in the allocated budget, the remaining slides can only disconnect s_t from t_t . Note also that $u^{(i,j)} \in C_{\ell}$, for $i \in [2(\kappa-1)]$ and $j \in [m-1]$ as otherwise, a path from a_1 to b_1 that goes through s_t , $u^{(i,j)}$ and t_t will remain tokens-free. This implies that at most $m-1$ tokens can be slid into any one level $\{E^1_{\mathfrak{r}}(\cdot), \ldots, E^{\kappa-1}_{\mathfrak{r}}(\cdot)\}$. We show via an inductive argument that the set of edges in $H_{\mathfrak{r}}$ represented by the vertices in $\{E_{\mathfrak{r}}^1(\cdot), \ldots, E_{\mathfrak{r}}^{\kappa-1}(\cdot)\}$ but not in C_{ℓ} must form a matching $\mathcal{M}_{\mathfrak{r}}$ in $H_{\mathfrak{r}}$ of size $\kappa_{\mathfrak{r}} = \kappa$, such that for $e_h, e_g \in \mathcal{M}_{\mathfrak{r}}, \varphi_{\mathfrak{r}}(e_h) \neq \varphi_{\mathfrak{r}}(e_g)$ and the claim follows. Let $P(q)$ be the proposition that the set \mathcal{E}_q of edges represented by vertices in ${E_{\mathfrak{r}}^1(\cdot), \ldots, E_{\mathfrak{r}}^q(\cdot)}$ but not in C_{ℓ} form a matching such that for $e_h, e_g \in \mathcal{E}_q$, $\varphi_{\mathfrak{r}}(e_h) \neq \varphi_{\mathfrak{r}}(e_g)$ and that vertices that remain free in $E_{\mathfrak{r}}^{q+1}(1)$ for $q < \kappa - 1$ represent the same edges as the vertices that remain free in $E_{\mathfrak{r}}^q(2)$. We show that $P(q)$ holds by induction on the levels $q = \{1, \ldots, \kappa - 1\}$.

We prove the base case by contradiction and assume that a vertex $v_{e_g}^{1,\mathfrak{r}}(2)$ that remains free in $E^1_{\mathfrak{r}}(2)$ either represents an edge e_g that is incident to an edge e_h represented by a vertex $v_{e_h}^{1,\mathfrak{r}}(1)$ that remains free in $E^1_t(1)$ or it holds that $\varphi_t(e_g) = \varphi_t(e_h)$. This implies that there exists a path between $s_{\mathfrak{r}}$ and $t_{\mathfrak{r}}$ that goes from $s_{\mathfrak{r}}$ to $s_{\mathfrak{r}}^1$, to $v_{e_h}^{1,\mathfrak{r}}(1)$, $v_{e_g}^{1,\mathfrak{r}}(2)$, $t_{\mathfrak{r}}^1$ and to $t_{\mathfrak{r}}$ and thus C_{ℓ} is not a

solution to (G, S, b, a_1, b_1) . As for the second part of the statement, assume that a vertex $v_{e_h}^{1,\mathfrak{r}}(2)$ that remains free in $E^1_{\mathfrak{r}}(2)$ does not represent the same edge as any of the vertices that remain free in $E^2_{\mathfrak{r}}(1)$, then there exists a path between $s_{\mathfrak{r}}$ and $t_{\mathfrak{r}}$ that goes through, $s_{\mathfrak{r}}^2$, then any of the latter vertices, followed by $v_{e_h}^{1,\mathfrak{r}}(2)$ and $t_{\mathfrak{r}}^1$ and thus C_{ℓ} is not a solution to (G, S, b, a_1, b_1) . Note that the same arguments used in the base case apply for the inductive step.

In other words, given the second part of the statement, we may assume (for contradiction purposes) that a vertex $v_{e_g}^{i,\mathfrak{r}}(2)$ for $i \leq q$ (that remains free in $E_{\mathfrak{r}}^{i}(2)$) either represents an edge e_g that is incident to an edge e_h represented by a vertex $v_{e_h}^{i',\mathfrak{r}}(1)$ for $i' \leq i$ (that remains free in $E_{\mathfrak{r}}^{i'}(1)$) or it holds that $\varphi_r(e_g) = \varphi_r(e_h)$. By construction, this implies that there exists a path from s_r and t_r that goes from $s_{\mathfrak{r}}$ to $s_{\mathfrak{r}}^{i'}, v_{e_h}^{i', \mathfrak{r}}(1), v_{e_g}^{i, \mathfrak{r}}(2), t_{\mathfrak{r}}^i$, and to $t_{\mathfrak{r}}$ and thus C_{ℓ} is not a solution to (G, S, b, a_1, b_1) . As for the second part of the statement, assume that a vertex $v_{e_h}^{q,\mathfrak{r}}(2)$ (that remains free in $E_{\mathfrak{r}}^q(2)$) does not represent the same edge as any of the vertices that remain free in $E_{\mathfrak{r}}^{q+1}(1)$, then there exists a path between s_r and t_r that goes through, s_r^{q+1} , then any of the latter vertices, followed by $v_{e_h}^{q,\mathfrak{r}}(2)$ and $t_{\mathfrak{r}}^q$ and thus C_{ℓ} is not a solution to (G, S, b, a_1, b_1) .

Thus, $P(\kappa - 1)$ holds and the set $\mathcal{E}_{\kappa-1}$ of edges represented by vertices in $\{E^1_{\mathfrak{r}}(\cdot), \ldots, E^{\kappa-1}_{\mathfrak{r}}(\cdot)\}\$ but not C_{ℓ} form a matching of size κ such that for e_h , $e_g \in \mathcal{E}_{\kappa-1}$, $\varphi_{\mathfrak{r}}(e_h) \neq \varphi_{\mathfrak{r}}(e_g)$.

 \Box

This concludes the proof of the theorem.

References

- [1] Yuichi Asahiro, Eiji Miyano, and Hirotaka Ono. Graph classes and the complexity of the graph orientation minimizing the maximum weighted outdegree. *Discrete Applied Mathematics*, 159(7):498–508, 2011.
- [2] Hans L. Bodlaender, Gunther Cornelissen, and Marieke van der Wegen. Problems hard for treewidth but easy for stable gonality. In *In proceedings of the 48th International Workshop on Graph-Theoretic Concepts in Computer Science, WG 2022, Tübingen, Germany, June 22-24, 2022*, pages 84–97. Springer, 2022.
- [3] Hans L. Bodlaender, Rodney G. Downey, Michael R. Fellows, and Danny Hermelin. On problems without polynomial kernels. *Journal of Computer and System Sciences*, 75(8):423–434, 2009.
- [4] Hans L. Bodlaender, Bart M.P. Jansen, and Stefan Kratsch. Kernelization lower bounds by cross-composition. *SIAM Journal on Discrete Mathematics*, 28(1):277–305, 2014.
- [5] Nicolas Bousquet, Amer E. Mouawad, Naomi Nishimura, and Sebastian Siebertz. A survey on the parameterized complexity of the independent set and (connected) dominating set reconfiguration problems. *arXiv preprint arXiv:2204.10526*, 2022.
- [6] Liming Cai, Jianer Chen, Rodney G. Downey, and Michael R. Fellows. Advice classes of parameterized tractability. *Annals of Pure and Applied Logic*, 84(1):119–138, 1997.
- [7] Marek Cygan, Fedor V. Fomin, Lukasz Kowalik, Daniel Lokshtanov, Daniel Marx, Marcin Pilipczuk, Michal Pilipczuk, and Saket Saurabh. *Parameterized Algorithms*. Springer Publishing Company, Incorporated, 1st edition, 2015.
- [8] Anuj Dawar and Stephan Kreutzer. Domination problems in nowhere-dense classes. In Ravi Kannan and K. Narayan Kumar, editors, *Proceedings of the 29th international conference on the Foundations of Software Technology and Theoretical Computer Science, FSTTCS 2009, IIT Kanpur, India, December 15-17, 2009*, volume 4 of *LIPIcs*, pages 157–168. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2009.
- [9] Reinhard Diestel. *Graph Theory*. Electronic Library of Mathematics. Springer, 2005.
- [10] Rodney G. Downey and Michael R. Fellows. *Parameterized Complexity*. Springer Science & Business Media, 2012.
- [11] Rodney G. Downey and Michael R. Fellows. *Fundamentals of Parameterized Complexity*, volume 4. Springer, 2013.
- [12] Paul Erdös and Richard Rado. Intersection theorems for systems of sets. *Journal of the London Mathematical Society*, 1(1):85–90, 1960.
- [13] Grzegorz Fabianski, Michal Pilipczuk, Sebastian Siebertz, and Szymon Torunczyk. Progressive algorithms for domination and independence. In Rolf Niedermeier and Christophe Paul, editors, *Proceedings of the 36th International Symposium on Theoretical Aspects of Computer Science, STACS 2019, Berlin, Germany, March 13-16, 2019*, volume 126 of *LIPIcs*, pages 27:1–27:16. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2019.
- [14] Michael R. Fellows, Mario Grobler, Nicole Megow, Amer E. Mouawad, Vijayaragunathan Ramamoorthi, Frances A. Rosamond, Daniel Schmand, and Sebastian Siebertz. On Solution Discovery via Reconfiguration. In Kobi Gal, Ann Nowé, Grzegorz J. Nalepa, Roy Fairstein, and Roxana Rădulescu, editors, *Proceedings of the 26th European Conference on Artificial Intelligence, Kraków, Poland, September 30 - October 4, 2023*, volume 372 of *FAIA*, pages 700–707, 2023.
- [15] Lance Fortnow and Rahul Santhanam. Infeasibility of instance compression and succinct pcps for np. In *Proceedings of the Fortieth Annual ACM Symposium on the Theory of computing, Victoria, British Columbia, Canada, May 17-20, 2008*, pages 133–142, 2008.
- [16] Mario Grobler, Stephanie Maaz, Nicole Megow, Amer E. Mouawad, Vijayaragunathan Ramamoorthi, Daniel Schmand, and Sebastian Siebertz. Solution discovery via reconfiguration for problems in P. *arXiv preprint arXiv:2311.13478*, 2023.
- [17] Shiva Kintali and Sinziana Munteanu. Computing bounded path decompositions in logspace. *Electronic Colloquim on Computational Complexity (ECCC)*, 2012.
- [18] Stephan Kreutzer, Roman Rabinovich, and Sebastian Siebertz. Polynomial kernels and wideness properties of nowhere dense graph classes. *ACM Transactions on Algorithms (TALG)*, 15(2):1– 19, 2018.
- [19] Van Bang Le and Florian Pfender. Complexity results for rainbow matchings. *Theoretical Computer Science*, 524(C):27–33, 2014.
- [20] Naomi Nishimura. Introduction to reconfiguration. *Algorithms*, 11(4):52, 2018.
- [21] Geevarghese Philip, Venkatesh Raman, and Somnath Sikdar. Solving dominating set in larger classes of graphs: Fpt algorithms and polynomial kernels. In *Proceedings of the 17th Annual European Symposium on Algorithms, ESA, Copenhagen, Denmark, September 7-9, 2009.*, pages 694–705. Springer, 2009.
- [22] Michał Pilipczuk, Sebastian Siebertz, and Szymon Toruńczyk. On the number of types in sparse graphs. In *Proceedings of the 33rd Annual ACM/IEEE Symposium on Logic in Computer Science, Oxford, United Kingdom, July 9-12, 2018*, pages 799–808, 2018.
- [23] Neil Robertson and Paul D. Seymour. Graph minors. II. algorithmic aspects of tree-width. *Journal of Algorithms*, 7(3):309–322, 1986.
- [24] Chee K Yap. Some consequences of non-uniform conditions on uniform classes. *Theoretical Computer Science*, 26(3):287–300, 1983.