arXiv:2410.00528v1 [eess.AS] 1 Oct 2024

End-to-End Speech Recognition with Pre-trained Masked Language Model

Yosuke Higuchi, Student Member, IEEE, Tetsuji Ogawa, Member, IEEE, Tetsunori Kobayashi, Member, IEEE, and Shinji Watanabe, Fellow, IEEE,

Abstract—We present a novel approach to end-to-end automatic speech recognition (ASR) that utilizes pre-trained masked language models (LMs) to facilitate the extraction of linguistic information. The proposed models, BERT-CTC and BECTRA, are specifically designed to effectively integrate pre-trained LMs (e.g., BERT) into end-to-end ASR models. BERT-CTC adapts BERT for connectionist temporal classification (CTC) by addressing the constraint of the conditional independence assumption between output tokens. This enables explicit conditioning of BERT's contextualized embeddings in the ASR process. seamlessly merging audio and linguistic information through an iterative refinement algorithm. BECTRA extends BERT-CTC to the transducer framework and trains the decoder network using a vocabulary suitable for ASR training. This aims to bridge the gap between the text processed in end-to-end ASR and BERT, as these models have distinct vocabularies with varying text formats and styles, such as the presence of punctuation. Experimental results on various ASR tasks demonstrate that the proposed models improve over both the CTC and transducer-based baselines, owing to the incorporation of BERT knowledge. Moreover, our in-depth analysis and investigation verify the effectiveness of the proposed formulations and architectural designs.

Index Terms—BERT, masked language model, connectionist temporal classification, transducer, end-to-end speech recognition

I. INTRODUCTION

I N the field of natural language processing (NLP), pretraining of language models (LMs) has emerged as the predominant paradigm. This approach involves training largescale LMs on a large quantity of text-only data using welldesigned self-supervised objectives [1], [2], thereby enabling the acquisition of versatile linguistic knowledge [3]. Such pre-trained models provide sophisticated representations that enhance the performance of downstream NLP tasks, while also mitigating the need for extensive supervised training data. In light of their remarkable success in NLP, pre-trained LMs have been actively adopted for a variety of end-toend speech processing tasks [4]–[10], including end-to-end automatic speech recognition (ASR).

End-to-end ASR aims to model direct speech-to-text conversion using a single deep neural network (DNN) [11]–[13]. One of the challenges in end-to-end ASR lies in the notable discrepancy between the characteristics of input and output sequences. Specifically, the input sequence is a continuous acoustic signal that contains fine-grained patterns with local dependencies, while the output sequence comprises discrete linguistic symbols (e.g., subwords or words), exhibiting long-range dependencies. Such difference in modalities poses a significant effort for end-to-end ASR models in extracting semantic and morphosyntax information from speech, which is essential for generating accurate textual output. Hence, the use of pre-trained LMs holds promising potential in aiding the extraction of linguistic information for end-to-end ASR.

Several attempts have been made to indirectly employ pretrained LMs to improve end-to-end ASR models, such as knowledge distillation [14]-[17] and N-best hypothesis rescoring [4], [18]-[21]. Although these approaches are straightforward and do not interfere with the original end-to-end ASR structures, they can only benefit from the powerful linguistic knowledge of the LMs either during training or inference. More recently, there have been efforts to integrate pre-trained LMs directly into end-to-end ASR models, accomplished by fine-tuning the LMs in conjunction with a speech processing network [5], [22]-[25]. This enables explicit adaptation of pre-trained LMs to ASR, while allowing models to exploit the linguistic knowledge during both training and inference. However, these approaches require a complex mechanism to summarize the speech input into a sequence of appropriate output length before it can be fed into the LMs. Moreover, to effectively optimize the unified model, the fine-tuning process entails precise calibration and scheduling of hyperparameters.

In this paper, we present a novel approach for integrating a pre-trained masked LM (e.g., BERT [1]) into end-to-end ASR. To achieve this, we propose two models, BERT-CTC and **BECTRA**, specifically designed to overcome the challenges associated with the integration. BERT-CTC facilitates the combination of audio and linguistic features, based on the formulation of connectionist temporal classification (CTC) [26]. More precisely, BERT embeddings are used to explicitly condition CTC on context-aware linguistic information, thereby mitigating the conditional independence in outputs. BERT-CTC exploits the capabilities of BERT without requiring finetuning, while enabling end-to-end training and inference using BERT knowledge and retaining the advantages of the efficient CTC framework. BERT-CTC-Transducer (BECTRA) is an extension of BERT-CTC developed to address the discrepancy between text formats and styles employed in end-to-end ASR and BERT. BECTRA expands BERT-CTC to the transducerbased model [27] and trains the decoder (i.e., prediction/joint networks) using a vocabulary tailored to the target ASR task. This distinct decoder allows for more accurate text generation

Y. Higuchi, T. Ogawa, and T. Kobayashi are with Department of Communications and Computer Engineering, Waseda University, Tokyo 162-0042, Japan (e-mail: {higuchi, ogawa}@pcl.cs.waseda.ac.jp, koba@waseda.jp).

S. Watanabe is with Language Technologies Institute, Carnegie Mellon University, Pittsburgh, PA 15213-3891, USA (e-mail: shinjiw@ieee.org).

by alleviating a crucial limitation in BERT-CTC, wherein the model training is constrained on a word-level and domainmismatched vocabulary used in BERT.

The key contributions of this work are summarized as

- We introduce BERT-CTC, which efficiently incorporates linguistic knowledge from a pre-trained masked LM into the end-to-end ASR process.
- We propose BECTRA, an extension of BERT-CTC that effectively closes the gap between the text formats utilized in an end-to-end ASR model and pre-trained LM.
- We present probabilistic formulations of our proposed approaches and elucidate their close relationship to the conventional CTC and transducer-based models.
- We evaluate our models across various ASR tasks, which demonstrates the effectiveness irrespective of differences in the amount of training data, speaking styles, and languages. The codes and recipes have been made publicly available at https://github.com/YosukeHiguchi/ espnet/tree/bectra.
- We perform thorough analyses to validate the efficacy of our models and propose several techniques to maximize their advantages for further improving ASR performance.

This paper builds upon our previous studies [28], [29] by expanding on our findings in the following ways: we present precise formulations of conventional end-to-end ASR approaches (Section II); we provide a consistent description of the proposed BERT-CTC [28] and BECTRA [29], along with a comprehensive comparison of their formulations to the conventional approaches (Section III); we provide detailed explanations of the relationship between our work and prior research (Section IV); we conduct experiments on various ASR tasks, including additional experiments on low-resource and punctuation-preserved settings; to enhance the effectiveness of our approach, we explore the use of different pretrained masked LMs and the combination with shallow fusion (Sections V and VI); and we further provide more in-depth analysis and investigation to show the effectiveness of the proposed formulations and architectural designs (Section VII).

II. BACKGROUND: END-TO-END ASR

To understand how the proposed approach utilizes a pretrained masked LM (e.g., BERT [1]), we start with a brief overview of the probabilistic formulations of conventional endto-end ASR approaches, focusing on CTC [11], [26] and the transducer [27], [30].

A. Definition of End-to-End ASR

Let $O = (\mathbf{o}_t \in \mathbb{R}^F | t = 1, \dots, T')$ be an input sequence of length T', and $W = (w_n \in \mathcal{V} | n = 1, \dots, N)$ be the corresponding output sequence of length N, where \mathbf{o}_t is an F-dimensional acoustic feature at frame t, w_n is an output token at position n, and \mathcal{V} is a vocabulary. In general, the output length is much shorter than the input length (i.e., $N \ll$ T'). The goal of ASR is to identify the most probable output sequence \hat{W} that matches the input sequence O:

$$\hat{W} = \operatorname*{argmax}_{W \in \mathcal{V}^*} p(W|O), \tag{1}$$

where \mathcal{V}^* is a set of all possible token sequences. End-to-end ASR aims to realize direct speech-to-text mapping $(O \mapsto W)$ by modeling the posterior distribution p(W|O) using a single DNN.

B. Conformer Encoder

For the DNN architecture, we adopt a Conformer-based model [31] consisting of a stack of I identical encoder blocks. The input audio sequence O is embedded into a discriminative latent space as

$$H = \text{ConformerEncoder}(O), \tag{2}$$

where $H = (\mathbf{h}_t \in \mathbb{R}^{d_{\text{model}}} | t = 1, \cdots, T)$ is a sequence of d_{model} -dimensional hidden vectors with length T (< T'). The *i*-th encoder block takes input as a previous sequence $H^{(i-1)} \in \mathbb{R}^{T \times d_{\text{model}}}$ and outputs $H^{(i)} \in \mathbb{R}^{T \times d_{\text{model}}}$ as

$$\bar{H}^{(i)} = H^{(i-1)} + \text{SelfAtten}(H^{(i-1)}),$$
 (3)

$$H^{(i)} = \bar{H}^{(i)} + \text{Conv}(\bar{H}^{(i)}),$$
 (4)

where $i \in \{1, \dots, I\}$, and SelfAtten(\cdot) and Conv(\cdot) indicate the multi-head self-attention and depthwise separable convolution modules, respectively. $H^{(0)}$ is obtained by applying convolution down-sampling [32] and positional encoding [33] to O. We denote H in Eq. (2) as the final output of the blocks $(H = H^{(I)})$. Note that in Eqs (3) and (4), we omit layer normalization applied before each module and the macaronstyle feed-forward module for simplicity.

C. Connectionist Temporal Classification

CTC [26] formulates end-to-end ASR by evaluating all possible alignments between an input sequence O and the corresponding output sequence W. To align the sequences at the frame level, W is augmented by permitting repeated occurrences of the same token and inserting a blank symbol ϵ for representing "no output token" (e.g., silence). Let $A = (a_t \in \mathcal{V} \cup \{\epsilon\} | t = 1, \cdots, T)$ be an augmented sequence, which we refer to as an *alignment* between O and W.

With the introduction of the frame-level alignment, CTC factorizes the posterior distribution of p(W|O) as

$$p_{\mathsf{ctc}}(W|O) \approx \sum_{A \in \mathcal{B}_{\mathsf{ctc}}^{-1}(W)} p(W|A, \mathscr{O}) p(A|O)$$
(5)

$$\approx \sum_{A \in \mathcal{B}_{\mathsf{ctc}}^{-1}(W)} p(A|O), \tag{6}$$

where $\mathcal{B}_{ctc} : A \mapsto W$ is the collapsing function that removes repeated tokens and blank symbols in A, and $\mathcal{B}_{ctc}^{-1}(W)$ is a set of all possible alignments that are compatible with W. In Eq. (5), CTC assumes a conditional independence of O, which is indicated by the slash sign. Furthermore, to obtain Eq. (6), p(W|A) = 1 is assumed, as W can be determined uniquely by the collapsing function. The joint probability p(A|O) in Eq. (6) is further factorized by the probabilistic chain rule as

$$p(A|O) \approx \prod_{t=1}^{T} p(a_t | \underline{a_1, \cdots, a_{t-1}}, O).$$
 (7)

3



Fig. 1. Schematic comparisons between different model architectures for end-to-end ASR. All the models are described in relation to the CTC-based model (a). The transducer introduces a prediction network to capture causal dependencies between the outputs (b). BERT-CTC conditions CTC on contextualized linguistic representations that are obtained from BERT (c). BECTRA is an extension of BERT-CTC that incorporates a prediction network, leveraging the benefits of both the transducer framework and the usage of BERT (d).

In Eq. (7), CTC makes a conditional independence assumption between output tokens, where p(A|O) is approximated as the product of token emission probabilities at each time frame.

The token emission probability $p(a_t|O)$ in Eq. (7) is computed using the embedded sequence H from Eq. (2) as

$$p(a_t|O) = \sigma(\mathbf{h}_t) \in [0,1]^{|\mathcal{V}|+1},\tag{8}$$

where $\sigma(\cdot)$ is a softmax layer.

1) Inference: Substituting Eq. (6) into Eq. (1), CTC estimates \hat{W} using the best path decoding algorithm [26]. The most probable alignment \hat{A} is first obtained by concatenating the most active tokens at the each time frame in H: $\hat{a}_t = \operatorname{argmax}_{a_t} p(a_t|H)$. \hat{W} is then derived by applying the collapsing function to \hat{A} as $\hat{W} = \mathcal{B}_{ctc}(\hat{A})$. Although not necessarily guaranteed to identify the most probable tokens, this greedy algorithm has been empirically demonstrated to deliver satisfactory results, particularly when the model is trained with the recent advanced modeling techniques [34].

2) **Training:** The objective function of CTC is defined as the negative log-likelihood of Eq. (6), which is further expanded using Eq. (7) as

$$\mathcal{L}_{\mathsf{ctc}} \triangleq -\log \sum_{A \in \mathcal{B}_{\mathsf{ctc}}^{-1}(W)} \prod_{t=1}^{T} p(a_t|O).$$
(9)

While Eq. (9) requires consideration of all possible *A*, CTC efficiently computes it through dynamic programming (i.e., forward-backward algorithm).

D. Transducer

CTC estimates the distribution over alignments solely based on the speech input (i.e., Eq. (7)), leading to an inaccurate capture of the conditional dependence of output tokens, often referred to as the *multimodality* problem [35]. The transducer [27] addresses this problem by making each token prediction explicitly conditioned on the previous output tokens (w_1, \dots, w_{n-1}) . Let $Z = (z_u \in \mathcal{V} \cup \{\epsilon\} | u = 1, \dots, T + N)$ be an alignment defined by the transducer, which is slightly different from A defined by CTC in that Z takes into account the combined input and output states. Similarly to Eq. (6), the transducer marginalizes the posterior distribution of p(W|O) over all possible alignments as

$$p_{\text{tra}}(W|O) \approx \sum_{Z \in \mathcal{B}_{\text{tra}}^{-1}(W)} p(Z|O),$$
(10)

where $\mathcal{B}_{tra} : Z \mapsto W$ is the collapsing function. The joint probability p(Z|O) in Eq. (10) is further factorized without the conditional independence assumption (cf. Eq. (7)) as

$$p(Z|O) = \prod_{\substack{u=1\\T+N}}^{T+N} p(z_u|z_1, \cdots, z_{u-1}, O)$$
(11)

$$\approx \prod_{u=1}^{T+N} p(z_u | \underbrace{w_1, \cdots, w_{n_u-1}}_{=\mathcal{B}_{\text{tra}}(z_1, \cdots, z_{u-1})}, O), \qquad (12)$$

where n_u is the number of non-blank tokens predicted up to an output index of u. From Eq. (11) to Eq. (12), the transducer approximates $(z_1, \dots, z_{u-1}) \approx (w_1, \dots, w_{n_u-1})$, which is reasonable because W can be determined uniquely from Zusing the collapsing function. The token emission probability $p(z_u|w_1, \dots, w_{n_u-1}, O)$ in Eq. (12) is computed using the embedded sequence H from Eq. (2) as

$$p(z_u|w_1, \cdots, w_{n_u-1}, O)$$

$$= \sigma(\text{JointNet}(\mathbf{h}_t, \mathbf{q}_{n_u})) \in [0, 1]^{|\mathcal{V}|+1}, \quad (13)$$

$$\mathbf{q}_{n_u} = \operatorname{PredictionNet}(w_1, \cdots, w_{n_u-1}) \in \mathbb{R}^{d_{\operatorname{model}}}.$$
 (14)

In Eq. (13), JointNet(\cdot) is a joint network that combines the audio and token representations, \mathbf{h}_t and \mathbf{q}_{n_u} , using a linear projection layer. In Eq. (14), PredictionNet(\cdot) is a prediction network that encodes the previous non-blank output tokens to a hidden vector \mathbf{q}_{n_u} . The introduction of the prediction network is the primary difference from CTC (Fig. 1(a) vs. 1(b)), which allows for explicit capture of causal dependencies in the outputs.

1) Inference: Based on Eqs. (1) and (10), the transducer identifies the most probable token sequence \hat{W} using the beam search algorithm [27]. The algorithm operates by searching through the possible hypotheses, keeping the *B*-best hypotheses at each step based on their probability scores measured by Eq. (13). We follow the implementation in [36], with a minor modification in skipping the initial prefix search part.

2) *Training*: The transducer loss is defined by the negative log-likelihood of Eq. (10), extended by Eq. (12) as

$$\mathcal{L}_{\mathsf{tra}} \triangleq -\log \sum_{Z \in \mathcal{B}_{\mathsf{tra}}^{-1}(W)} \prod_{u=1}^{T+N} p(z_u | w_{< n_u}, O).$$
(15)

Similarly to the calculation of the CTC objective in Eq. (9), the summation over alignments is efficiently implemented using dynamic programming.

III. INTEGRATING PRE-TRAINED MASKED LANGUAGE MODELS INTO END-TO-END ASR

We propose a novel approach to end-to-end ASR that utilizes a pre-trained masked LM in its formulation, focusing on BERT [1] as a case in point. Our proposed approach is designed to address the following key points: *How to make* end-to-end ASR conditioned on BERT information, and how to bridge the gap between text processed in end-to-end ASR and BERT. The former is solved via **BERT-CTC**, which adapts BERT representations to explicitly condition CTC on linguistic contexts (Section III-A). The latter is tackled by **BERT-CTC-T**ransducer (**BECTRA**) by extending BERT-CTC to the transducer framework. While the BERT-CTC formulation is restricted to the vocabulary used in BERT, BECTRA overcomes this limitation by enabling the handling of different text formats and styles (Section III-B).

To provide a precise explanation of the proposed formulation, we define output sequences that are tokenized using two varying vocabularies: $W^{a} = (w_{l}^{a} \in \mathcal{V}^{a} | l = 1, \dots, L)$ and $W^{b} = (w_{m}^{b} \in \mathcal{V}^{b} | m = 1, \dots, M)$, where \mathcal{V}^{a} is a vocabulary constructed from ASR training text, and \mathcal{V}^{b} is a vocabulary of BERT, with the superscripts a and b indicating ASR and BERT, respectively. Typically, \mathcal{V}^{b} consists of almost wordlevel tokens with a large subword vocabulary size, while \mathcal{V}^{a} comprises smaller subword units (i.e., $|\mathcal{V}^{b}| \gg |\mathcal{V}^{a}|$). Moreover, \mathcal{V}^{b} may contain written symbols, including punctuation and casing, whereas they are often disregarded in \mathcal{V}^{a} .

A. BERT-CTC

Overview: In Fig. 1, we compare BERT-CTC to the conventional CTC and transducer-based models (described in Sections II-C and II-D). BERT-CTC leverages powerful contextualized representations from BERT to make CTC's training and inference explicitly conditioned on linguistic information (Fig. 1(a) vs. 1(c)). BERT-CTC can be similar to the transducer in that it fuses audio and token representations to estimate the distribution over alignments (Fig. 1(b) vs. 1(c)). However, by employing a concatenation network that attends to the full contexts of the input and output sequences, BERT-CTC permits learning inner and inter-dependencies within and between the sequences, facilitating the integration of information from the different modalities [37].

BERT-CTC formulates end-to-end ASR by introducing a partially masked (\Leftrightarrow partially observed) sequence $\tilde{W}^{b} = (\tilde{w}_{m}^{b} \in \mathcal{V}^{b} | m = 1, \cdots, M)$, which is obtained by replacing some tokens in an output sequence W^{b} with a special mask

token [MASK]. Note that [MASK] is included in the BERT vocabulary \mathcal{V}^{b} . An example pair of W^{b} and \tilde{W}^{b} can be

$$W^{b} = ($$
"Tokyo", "is", "the", "capital", "of", "Japan", "."),
 $\tilde{W}^{b} = ($ "Tokyo", [MASK], "the", [MASK], "of", "Japan", ".").

We obtain this masked sequence by applying masks to a ground-truth sequence during training or a hypothesized sequence during inference.

Taking account of all possible masked sequences, the posterior distribution of ASR, $p(W^b|O)$, is factorized as

$$p_{\mathsf{bertctc}}(W^{\mathsf{b}}|O) = \sum_{\tilde{W}^{\mathsf{b}} \in \mathcal{M}(W^{\mathsf{b}})} p(W^{\mathsf{b}}, \tilde{W}^{\mathsf{b}}|O)$$
(16)

$$= \sum_{\tilde{W}^{\mathsf{b}} \in \mathcal{M}(W^{\mathsf{b}})} p(W^{\mathsf{b}} | \tilde{W}^{\mathsf{b}}, O) p(\tilde{W}^{\mathsf{b}} | O), \quad (17)$$

where $\mathcal{M}(W^{\mathrm{b}})$ covers W^{b} with all possible masking patterns. In Eq. (17), we interpret $p(\tilde{W}^{\mathrm{b}}|O)$ as a distribution of sequences that consist of unmasked (observed) tokens, which are readily recognizable from the speech input alone. The other masked tokens, in contrast, are difficult to determine (e.g., homophones) and require context from observed tokens, which is modeled by $p(W^{\mathrm{b}}|\tilde{W}^{\mathrm{b}},O)$. We provide a more intuitive explanation of this interpretation in the inference section (Section III-A1).

Similarly to Eq. (5), $p(W^b|\tilde{W}^b, O)$ in Eq. (17) is further factorized by introducing CTC alignments as

$$p(W^{\mathsf{b}}|\tilde{W}^{\mathsf{b}}, O) = \sum_{A^{\mathsf{b}} \in \mathcal{B}_{\mathsf{ctc}}^{-1}(W^{\mathsf{b}})} p(W^{\mathsf{b}}, A^{\mathsf{b}}|\tilde{W}^{\mathsf{b}}, O)$$
(18)

$$\approx \sum_{A^{\mathbf{b}} \in \mathcal{B}_{\mathsf{ctc}}^{-1}(W^{\mathbf{b}})} p(A^{\mathbf{b}} | W^{\mathbf{b}}, \tilde{\mathcal{W}}^{\mathbf{b}}, O) p(W^{\mathbf{b}} | \tilde{W}^{\mathbf{b}}, \mathscr{O}), \quad (19)$$

where $A^{b} = (a_{t}^{b} \in \mathcal{V}^{b} \cup \{\epsilon\} | t = 1, \cdots, T)$ is an alignment corresponding to W^{b} with the BERT vocabulary. In Eq. (19), we make two conditional independence assumptions. The first is that given W^{b} and O, \tilde{W}^{b} is not required to determine A^{b} . This is reasonable because W^{b} already contains observed tokens in \tilde{W}^{b} and is helpful in avoiding the combination of all possible masked sequences and alignments (i.e., the Cartesian product of $\mathcal{M} \times \mathcal{B}_{ctc}^{-1}$). The second is that given \tilde{W}^{b} , O is not required to determine W^{b} . We consider $p(W^{b}|\tilde{W}^{b})$ as a strong prior distribution modeled by a pre-trained masked LM, e.g., BERT, which can be achieved without the observation from O. We empirically show that this assumption holds in Section VII-C.

The joint probability $p(A^{b}|W^{b}, O)$ in Eq. (19) is factorized using the probabilistic chain rule as

$$p(A^{\mathbf{b}}|W^{\mathbf{b}}, O) \approx \prod_{t=1}^{T} p(a_t^{\mathbf{b}}|\underline{a_1^{\mathbf{b}}, \dots, a_{t-1}^{\mathbf{b}}, W^{\mathbf{b}}, O).$$
(20)

In Eq. (20), we make the same conditional independence assumption as in CTC. However, compared to Eq. (7), Eq. (20) is conditioned on an output sequence W^{b} , which enables explicit use of linguistic information to estimate the distribution over alignments. This is somewhat similar to the transducer

Algorithm 1 Decoding algorithm of BERT-CTC

function DECODEBERTCTC(H, K) 1. Initialize a masked sequence $\tilde{W}^{\prime b}$ with all mask tokens

for k = 1 to K do

- 2. Forward BERT($\tilde{W}^{\prime b}$) and update E with Eq. (23)
- 3. Forward ConcatNet(HE) and compute token emission probabilities with Eq. (22)
- 4. Generate a hypothesis \hat{W}^{b} via best path decoding 5. Compute $N_{mask} = \lfloor |\hat{W}^{b}| \cdot \frac{K-k}{K} \rfloor$
- 6. Update \tilde{W}'^{b} by masking N_{mask} tokens in \hat{W}^{b}
- with the lowest probability scores from Step 3
- return \hat{W}^{b}, E

formulation in Eq. (12), but is different in that BERT-CTC attends to the whole context $(w_1^{\mathsf{b}}, \cdots, w_M^{\mathsf{b}})$.

Substituting Eq. (20) into Eq. (19), we model the product of $p(a_t^b|W^b, O)$ and $p(W^b|\tilde{W}^b)$ as

Eq. (19)
$$\triangleq \sum_{A^{\mathbf{b}} \in \mathcal{B}_{\mathsf{ctc}}^{-1}(W^{\mathbf{b}})} \prod_{t=1}^{T} p(a_t^{\mathbf{b}} | \mathsf{BERT}(\tilde{W}^{\mathbf{b}}), O),$$
 (21)

where BERT(·) indicates the final hidden states of BERT or any pre-trained masked LM, representing the distribution of target sequences.¹ Eq. (21) can be realized with a single differentiable model, enabling the whole network to be trained end-to-end while being conditioned on BERT knowledge. In Eq. (21), The token emission probability at each time frame is computed using the audio sequence $H \in \mathbb{R}^{T \times d_{model}}$ from Eq. (2) as

$$p(a_t^{\mathsf{b}}|\mathsf{BERT}(\tilde{W}^{\mathsf{b}}), O)$$

= $\sigma(\mathsf{ConcatNet}_t((H, E))) \in [0, 1]^{|\mathcal{V}^{\mathsf{b}}|+1},$ (22)

$$E = \text{Linear}(\text{BERT}(\tilde{W}^{\mathsf{b}})) \in \mathbb{R}^{M \times d_{\text{model}}}.$$
 (23)

In Eq. (23), Linear(\cdot) maps the BERT outputs into a sequence of d_{model} -dimensional vectors E. In Eq. (22), ConcatNet_t(\cdot) represents the t-th output of a concatenation network that consists of a stack of Transformer self-attention layers [33]. Processing the concatenated sequence (H, E) through this self-attention mechanism, the model is capable of capturing dependencies within and between the audio and token sequences, H and E, which we analyze in Section VII-B.

1) **Inference**: The most probable token sequence is estimated by solving Eq. (1) for Eq. (17) as

$$\hat{W}^{\mathsf{b}} = \operatorname*{argmax}_{W^{\mathsf{b}}} \sum_{\tilde{W}^{\mathsf{b}} \in \mathcal{M}(W^{\mathsf{b}})} p(W^{\mathsf{b}} | \tilde{W}^{\mathsf{b}}, O) p(\tilde{W}^{\mathsf{b}} | O)$$
(24)

$$\approx \underset{W^{\mathsf{b}}}{\operatorname{argmax}} p(W^{\mathsf{b}} | \tilde{W}'^{\mathsf{b}}, O), \tag{25}$$

where
$$\tilde{W}^{\prime b} = \operatorname*{argmax}_{\tilde{W}^{b}} p(\tilde{W}^{b}|O).$$
 (26)

¹As our formulation assumes $p(W^{b}|\tilde{W}^{b})$ to be a strong prior distribution of a masked LM, we use BERT as a feature extractor for an output sequence without fine-tuning, which has been reported to still be effective for several NLP tasks [38]–[40]. In Section VII-C, we provide empirical evidence that fine-tuning is not necessary for our proposed approach. To obtain Eq. (25), we apply the Viterbi approximation to Eq. (24) in order to handle the intractable summation over all possible masked sequences.

The inference formulation with Eqs. (25) and (26) can be viewed as the process of human speech recognition, which involves "top-down" and "bottom-up" processing [41], [42]. Determining $\tilde{W}^{\prime b}$ in Eq. (26) is analogous to bottom-up processing, where the model analyzes the individual low-level sounds that make up words. However, certain words, particularly those with homophones, are difficult to identify solely from their sounds, requiring higher-level linguistic information for accurate recognition. This is solved via top-down processing in Eq. (25), where the conditioning from $\tilde{W}^{\prime b}$ enables the model to leverage linguistic knowledge, context, and anticipations for identifying words from low-level sounds.

To solve Eqs. (25) and (26), we design a fill-mask-style decoding algorithm based on mask-predict [43] and CTC inference, which is based on [44]-[46]. Algorithm 1, consisting of Steps 1 to 6, describes the proposed algorithm. At the beginning of decoding, a masked sequence $\tilde{W}^{\prime b}$ is initialized by replacing all token positions with the mask token [MASK] (Step 1).² The algorithm then proceeds to generate a hypothesis by gradually filling in the masked tokens over K iterations. At each iteration $k \in \{1, \dots, K\}$, the current masked sequence $\tilde{W}^{\prime b}$ is fed into BERT to obtain contextual embeddings E, as defined by Eq. (23) (Step 2). The encoder output H from Eq. (2) and E are concatenated and input into the concatenation network, which computes the framewise probability $p(a_t^{\mathsf{b}}|\mathsf{BERT}(\tilde{W}'^{\mathsf{b}}), O)$ as in Eq. (22) (Step 3). Using the probabilities computed at each frame, a hypothesis \hat{W}^{b} is generated through best path decoding, in the same manner as in Section II-C1 (Step 4). The number of tokens that will be masked N_{mask} is determined by a linear decay function as $N_{\text{mask}} = \lfloor |\hat{W}^{\text{b}}| \cdot \frac{K-k}{K} \rfloor$ (Step 5), e.g., if K is set to five, N_{mask} decreases by 20% at each iteration. The masked sequence $\tilde{W}^{\prime b}$ is updated by replacing N_{mask} tokens in the hypothesis \hat{W}^{b} with the mask token [MASK] (Step 6). Here, tokens are selected for masking according to their confidence scores, which are measured by calculating the output probability of each token. Using the framewise probabilities from Step 3, the output probability for a token $\hat{w}_n^{\mathsf{b}} \in \hat{W}^{\mathsf{b}}$ is derived as

$$p(w_n^{\mathsf{b}} = \hat{w}_n^{\mathsf{b}} | \text{BERT}(\tilde{W}'^{\mathsf{b}}), O)$$

= max $\left(\left\{ p(a_t^{\mathsf{b}} = \hat{w}_n^{\mathsf{b}} | \text{BERT}(\tilde{W}'^{\mathsf{b}}), O) | t \in \mathcal{T}_n \right\} \right), \quad (27)$

where \mathcal{T}_n is a set of frame indices that correspond to the *n*-th token \hat{w}_n^{b} after applying the collapsing function. With Eq. (27), N_{mask} tokens with the lowest probability scores are masked.

In the first iteration (i.e., k = 1), the model generates a hypothesis solely based on the speech input, without any linguistic cues from the output tokens, which are all masked. This can be aligned with the concept of bottom-up processing as formulated by Eq. (26). As the iterations proceed (i.e., $1 < k \le K$), the output tokens become gradually observable, providing additional linguistic information for generating a

²This requires predicting the target length beforehand [35], which we obtain from intermediate predictions from the encoder (see Section V-D for details).

more precise hypothesis. This can be interpreted as top-down processing as formulated by Eq. (25).

2) *Training*: The BERT-CTC objective is defined by the negative log-likelihood of Eq. (17):

$$-\log \sum_{\tilde{W}^{\mathsf{b}} \in \mathcal{M}(W^{\mathsf{b}})} p(W^{\mathsf{b}} | \tilde{W}^{\mathsf{b}}, O) p(\tilde{W}^{\mathsf{b}} | O),$$
(28)

which is further expanded using Eqs. (19) and (20) as

$$= -\log \sum_{\substack{\tilde{W}^{\mathsf{b}} \in \mathcal{M}(W^{\mathsf{b}})\\A^{\mathsf{b}} \in \mathcal{B}_{\mathsf{ctc}}^{-1}(W^{\mathsf{b}})}} p(A^{\mathsf{b}}|W^{\mathsf{b}}, O)p(W^{\mathsf{b}}|\tilde{W}^{\mathsf{b}})p(\tilde{W}^{\mathsf{b}}|O) \quad (29)$$

$$\approx -\log \mathbb{E}_{\tilde{W}^{\mathsf{b}} \sim \mathcal{M}'(W^{\mathsf{b}})} \left[\sum_{A^{\mathsf{b}} \in \mathcal{B}_{\mathsf{ctc}}^{-1}(W^{\mathsf{b}})} p(A^{\mathsf{b}}|W^{\mathsf{b}}, O)p(W^{\mathsf{b}}|\tilde{W}^{\mathsf{b}}) \right]. \quad (30)$$

To obtain Eq. (30), we approximate the intractable marginalization over \tilde{W}^{b} as expectation with respect to the sampling distribution $\mathcal{M}'(W^{b})$, which is calculated on the probability distribution of $p(\tilde{W}^{b}|O)$. The upper bound of Eq. (30) can be derived by applying Jensen's inequality as

$$\approx -\mathbb{E}_{\tilde{W}^{\mathsf{b}}\sim\mathcal{M}'(W^{\mathsf{b}})}\left[\log\sum_{A^{\mathsf{b}}\in\mathcal{B}_{\mathsf{ctc}}^{-1}(W^{\mathsf{b}})}p(A^{\mathsf{b}}|W^{\mathsf{b}},O)p(W^{\mathsf{b}}|\tilde{W}^{\mathsf{b}})\right].$$
(31)

Substituting Eqs. (20) and (21) into Eq. (31), the loss for BERT-CTC training is defined as

$$\mathcal{L}_{\mathsf{bertctc}} \triangleq -\mathbb{E}_{\tilde{W}^{\mathsf{b}} \sim \mathcal{M}'(W^{\mathsf{b}})} \left[\log \sum_{A^{\mathsf{b}} \in \mathcal{B}_{\mathsf{ctc}}^{-1}(W^{\mathsf{b}})} \prod_{t=1}^{T} p(a_{t}^{\mathsf{b}} | \mathsf{BERT}(\tilde{W}^{\mathsf{b}}), O) \right].$$
(32)

In comparison to the CTC objective described in Eq. (9), each token prediction in Eq. (32) is explicitly conditioned on the contextualized embeddings from BERT. This allows an explicit consideration of the contextual dependencies among token predictions while retaining the efficient optimization strategy as in CTC.

For the sampling process of \tilde{W}^{b} in Eq. (32), we use random sampling from a uniform distribution to approximate the probability distribution of $\mathcal{M}'(W^{b})$, for the sake of simplicity. We adopt a strategy similar to the one employed in [43]. We first sample a random number N_{mask} from a uniform distribution ranging between one and the target sequence length M, i.e., $N_{\text{mask}} \sim \text{Uniform}(1, M)$. Then, we randomly select N_{mask} tokens from a ground-truth sequence and replace them with [MASK].

B. BERT-CTC-Transducer (BECTRA)

BERT-CTC progressively conditions CTC on contextual linguistic information by gradually predicting tokens and updating BERT embeddings correspondingly. This BERT-based refinement requires the model to work with the BERT's text format, which has the vocabulary \mathcal{V}^{b} that can be too large for ASR training, and could lead to a mismatch against the target ASR domain. BERT-CTC-Transducer (BECTRA) is designed to extend BERT-CTC for handling such mismatches while still utilizing BERT knowledge to enhance ASR performance.

Overview: Figure 1 presents a comparison between BEC-TRA, the conventional transducer-based model (described in Section II-D), and BERT-CTC (introduced in Section III-A). BECTRA formulates end-to-end ASR based on BERT-CTC, using the output of the concatenation network for calculating the transducer loss (Fig. 1(c) vs. 1(d)). Here, the joint and prediction networks are trained with an ASR-specific vocabulary \mathcal{V}^a , which allows for more suitable end-to-end ASR training without being limited by the BERT vocabulary \mathcal{V}^b . Hence, unlike $p_{\text{bertctc}}(W^b|O)$ in Eq. (16), BECTRA utilizes W^a tokenized by \mathcal{V}^a as its target sequence.

Similarly to Eq. (17), BECTRA formulates E2E-ASR by marginalizing the posterior distribution of $p(W^a|O)$ over all possible masked sequences as

$$p_{\mathsf{bectra}}(W^{\mathsf{a}}|O) = \sum_{\tilde{W}^{\mathsf{b}} \in \mathcal{M}(W^{\mathsf{b}})} p(W^{\mathsf{a}}|\tilde{W}^{\mathsf{b}}, O) p(\tilde{W}^{\mathsf{b}}|O).$$
(33)

In Eq. (33), \tilde{W}^{b} is obtained by masking a sequence in the BERT unit W^{b} ($\neq W^{a}$). Similarly to Eq. (10), $p(W^{a}|\tilde{W}^{b}, O)$ in Eq. (33) is factorized by considering all possible alignments of the transducer as

$$p(W^{\mathsf{a}}|\tilde{W}^{\mathsf{b}}, O) = \sum_{Z^{\mathsf{a}} \in \mathcal{B}_{\text{tra}}^{-1}(W^{\mathsf{a}})} p(W^{\mathsf{a}}, Z^{\mathsf{a}}|\tilde{W}^{\mathsf{b}}, O)$$
(34)

$$\approx \sum_{Z^{\mathsf{a}} \in \mathcal{B}_{\mathsf{tra}}^{-1}(W^{\mathsf{a}})} p(Z^{\mathsf{a}}|W^{\mathsf{a}}, \tilde{\mathcal{W}}^{\mathsf{b}}, O) p(W^{\mathsf{a}}|\tilde{W}^{\mathsf{b}}, \mathscr{O}), \quad (35)$$

where $Z^{a} = (z_{u}^{a} \in \mathcal{V}^{a} \cup \{\epsilon\}|u = 1, \dots, T + L)$ is an alignment corresponding to W^{a} with the ASR vocabulary, as defined by the transducer (see Eq. (10)). In Eq. (35), we use the same approximations employed in Eq. (19). The joint probability $p(Z^{a}|W^{a}, O)$ in Eq. (35) is further factorized by the probabilistic chain rule without a conditional independence assumption (cf. Eq. (20)) as

$$p(Z^{a}|W^{a}, O) = \sum_{Z^{a} \in \mathcal{B}_{\text{tra}}^{-1}(W^{a})} \prod_{u=1}^{T+L} p(z_{u}^{a}|z_{1}^{a}, \cdots, z_{u-1}^{a}, W^{a}, O), \quad (36)$$

$$\approx \sum_{Z^{a} \in \mathcal{B}_{\text{tra}}^{-1}(W^{a})} \prod_{u=1}^{T+L} p(z_{u}^{a}| \underbrace{w_{1}^{a}, \cdots, w_{l_{u}-1}^{a}}_{=\mathcal{B}_{\text{tra}}(z_{1}^{a}, \cdots, z_{u-1}^{a})}, W^{a}, O), \quad (37)$$

where l_u is the number of non-blank tokens predicted up to an index of u. Eq. (37) assumes $(z_1^a, \dots, z_{u-1}^a) \approx$ $(w_1^a, \dots, w_{l_u-1}^a)$, using the same approximation as the transducer in Eq. (12). Similarly to the BERT-CTC formulation in Eq. (21), BECTRA models Eq. (35) using Eq. (37) as

Eq. (35)
$$\triangleq \sum_{Z^{\mathfrak{a}} \in \mathcal{B}_{\mathsf{tra}}^{-1}(W^{\mathfrak{a}})} \prod_{u=1}^{T+L} p(z_{u}^{\mathfrak{a}} | w_{< l_{u}}^{\mathfrak{a}}, \mathsf{BERT}(\tilde{W}^{\mathfrak{b}}), O),$$
(38)

where we employ BERT to model $p(W^{a}|\tilde{W}^{b})$. This is a reasonable approximation because both W^{b} and W^{a} represent

Algorithm 2 Decoding algorithm of BECTRA

function DECODEBECTRA(H, K, B)
1. Perform DECODEBERTCTC(H, K) and obtain E
2. Generate a hypothesis \hat{W}^a via beam search decoding
with a beam size of B , using output probabilities
computed with Eqs. (39) and (40)
return \hat{W}^{a}

the same target sentence. Thus, W^a can be derived easily by first converting W^b into a word sequence and then tokenizing it using \mathcal{V}^a . The token emission probability in Eq. (38) is computed using the audio sequence H from Eq. (2) and BERT output E similar to Eq. (22) as

$$p(z_{u}^{\mathsf{a}}|w_{$$

$$\mathbf{q}_{l_u}^{\mathsf{a}} = \operatorname{PredictionNet}(w_1^{\mathsf{a}}, \cdots, w_{l_u-1}^{\mathsf{a}}) \in \mathbb{R}^{d_{\mathsf{model}}}.$$
 (40)

The network architecture is almost identical to the transducer presented in Eqs. (13) and (14) but it differs in that the joint network takes the output of the concatenation network as its input. This enables the integration of BERT knowledge into the transducer-based model. By adopting the prediction network, BECTRA can explicitly capture the causal dependencies between output tokens, leading to better sequence modeling. This is another key advantage of BECTRA compared to BERT-CTC, beyond the use of ASR-specific vocabulary, which we discuss in Section VII-D.

1) Inference: Algorithm 2 shows the inference algorithm of BECTRA, which includes Steps 1 and 2. The algorithm is implemented with BERT-CTC decoding (see Section III-A1) followed by beam-search decoding of the transducer (see Section II-D1). BERT-CTC decoding provides the model with a fully contextualized BERT output E, which is obtained from the final hypothesis estimated by the iterative refinement (Step 1). To find the optimal sequence with the highest sequence-level generation probability, beam-search decoding is performed using the token emission probabilities computed from Eq. (39) (Step 2). With this combined inference algorithm, BECTRA can leverage the BERT's ability to capture bidirectional context in an output sequence, providing the benefit of non-autoregressive decoding. Furthermore, transducerbased decoding enables the model to refine a sequence in an autoregressive manner, utilizing a more appropriate output unit for performing ASR.

2) *Training*: The transducer loss of BECTRA is defined by substituting Eq. (38) into Eq. (33) and following the same derivation process as Eq. (32), resulting in

$$\mathcal{L}_{\mathsf{bectra}}^{\prime} \triangleq \\ - \mathbb{E}_{\tilde{W}^{\mathsf{b}} \sim \mathcal{M}(W^{\mathsf{b}})} \Bigg[\log \sum_{Z^{\mathsf{a}} \in \mathcal{B}_{\mathsf{tra}}^{-1}(W^{\mathsf{a}})} \prod_{u=1}^{T+L} p(z_{u}^{\mathsf{a}} | w_{< l_{u}}^{\mathsf{a}}, \mathsf{BERT}(\tilde{W}^{\mathsf{b}}), O) \Bigg],$$

$$\tag{41}$$

where the summation over Z^a can be efficiently computed using the same approach as in transducer training (see Section II-D2). The sampling strategy for \tilde{W}^b is described in BERT-CTC training (see Section III-A2). The objective

TABLE I Comparisons between end-to-end ASR formulations for modeling distribution over alignments

Model	Formulation
СТС	$\sum_{A \in \mathcal{B}_{ctc}^{-1}(W)} \prod_{t=1}^{T} p(a_t O)$
Transducer	$\sum_{Z \in \mathcal{B}_{\text{tra}}^{-1}(W)} \prod_{u=1}^{T+N} p(z_u w_{< n_u}, O)$
BERT-CTC	$\sum_{A \in \mathcal{B}_{ctc}^{-1}(W)} \prod_{t=1}^{T} p(a_t BERT(\tilde{W}), O)$
BECTRA	$\sum_{Z \in \mathcal{B}_{\text{tra}}^{-1}(W)} \prod_{u=1}^{T+N} p(z_u w_{< n_u}, \text{BERT}(\tilde{W}), O)$

function of BECTRA is defined by combining $\mathcal{L}_{bertctc}$ from Eq. (32) and \mathcal{L}'_{bectra} from Eq. (41) as

$$\mathcal{L}_{\text{bectra}} = (1 - \lambda)\mathcal{L}_{\text{bertctc}} + \lambda \mathcal{L}'_{\text{bectra}}, \qquad (42)$$

where $\lambda \in (0, 1)$ is a tunable parameter.

C. Overall Comparison of End-to-End ASR Formulations

As summarized in Table I, the key difference between the end-to-end ASR formulations discussed thus far lies in how the distribution over alignments is calculated. CTC estimates the distribution based solely on the speech input O, assuming that the output tokens are independent of one another. The transducer conditions each token prediction explicitly on the preceding non-blank tokens $w_{< n_u}$, introducing the prediction and joint networks. BERT-CTC achieves similar conditioning using BERT's contextualized embeddings $\text{BERT}(\tilde{W})$ through the concatenation network. BECTRA is conditioned on both $w_{< n_u}$ and $\text{BERT}(\tilde{W})$, enabling a model to benefit from the information provided by both sources.

IV. ADDITIONAL RELATED WORK

In this section, we further clarify the position of our research in relation to other relevant topics in end-to-end ASR, focusing on masked LM-based modeling and external LM integration.

A. End-to-End ASR and Masked Language Modeling

Conditional masked LM (CMLM) [43], one of the successful approaches in non-autoregressive neural machine translation, has been introduced to solve end-to-end ASR. CMLM utilizes an encoder-decoder structure, wherein its decoder is trained with the masked LM objective [1] while being conditioned on the encoder outputs through the cross-attention mechanism. Audio-CMLM [47] employs CMLM to enable non-autoregressive end-to-end ASR by conditioning the decoder on audio information to learn the fill-mask process. By combining CMLM-based modeling with CTC, Imputer [44] and Mask-CTC [45], [46] extend the mask-predict algorithm to refine either a frame-level or token-level sequence predicted

Dataset	Hours	Language	Speech Style	Text Style
LibriSpeech [58]	100 960	English English	Read Read	Normalized Normalized
Libri-Light [59]	10	English	Read	Normalized
TED-LIUM2 [60]	210	English	Spontaneous	Normalized
AISHELL-1 [61]	170	Mandarin	Read	Normalized
CoVoST2 [62]	430	English	Read	Punct./Casing

TABLE II DATASET DESCRIPTIONS

in the CTC framework. Several studies have trained CMLM as an error-correction model for predictions generated by an end-to-end ASR system [48], [49].

Our approach of incorporating masked language modeling with the CTC and transducer frameworks is relevant to the above studies. However, it differs in that we aim to leverage the pre-existing knowledge acquired by a pre-trained masked LM to enhance end-to-end ASR performance.

B. Language Model Integration for End-to-End ASR

There is a line of previous studies that have explored the integration of an LM, e.g., recurrent neural network (RNN)-LM, into end-to-end ASR systems. In this context, the LM is trained on external in-domain text data that pertains to a specific ASR task. Shallow fusion has been the predominant method [50]– [53], which linearly interpolates the output probabilities from an end-to-end ASR model and external LM. Deep fusion [51] is a more structured approach, where an end-to-end ASR model is jointly trained with an external LM to learn the optimal combination of audio and linguistic information. Cold fusion [54] and component fusion [55] have improved deep fusion by incorporating a gating mechanism that enables a more sophisticated combination of the two models.

Our approach shares similarities with cold fusion by combining an end-to-end ASR model and pre-trained masked LM using the self-attention mechanism to selectively merge audio and linguistic representations. However, we focus on exploring how the versatile linguistic knowledge acquired from large-scale pre-trained LMs (i.e., BERT) can be utilized to improve end-to-end ASR. Additionally, we demonstrate that the conventional LM fusion technique is applicable to our approach, allowing for the incorporation of a domain-specific RNN-LM to further enhance performance.

V. EXPERIMENTAL SETTING

We used the ESPnet toolkit [56], [57] for conducting the experiments. All the codes and recipes used in our experiments are made publicly available.³

A. Data

We used the corpora listed in Table II, which comprised different quantities of data, languages, and speech and text styles. LibriSpeech [58] consists of utterances derived from read English audiobooks. In addition to the full 960-hour training set (LS-960), we trained models on the *train-clean-100* subset (LS-100) for conducting additional investigations and analyses. We also used the 10-hour training set provided by Libri-Light [59] (LL-10), which is a low-resource subset extracted from LS-960. TED-LIUM2 (TED2) [60] contains utterances from English TED Talks. AISHELL-1 (AS1) [61] is a multi-domain Mandarin corpus that covers a range of common applications, such as prompts for smart speakers. CoVoST2 (CV2) [62] is a corpus for speech translation tasks, which is based on the Common Voice project [63]. We used CV2 for an English ASR task by exclusively using source speech-text data from the "En \rightarrow X" task. For each corpus, we used the standard development and test sets for tuning hyper-parameters and evaluating performance, respectively.

Notice that all corpora except CV2 only provide normalized transcriptions in which punctuation is removed and casing is standardized to upper or lower case. This potentially limits the capabilities of BERT, which is often trained on written-form text with punctuation and casing preserved. In contrast, CV2 provides unnormalized transcriptions with a decent amount of ASR training data, which makes it an ideal resource for evaluating the effectiveness of the proposed approach.

We used SentencePiece [64] to construct subword vocabularies from ASR transcriptions in order to obtain the ASR vocabulary \mathcal{V}^a . The vocabulary sizes were set to 300, 5k, 100, 500, and 500 for LS-100, LS-960, LL-10, TED2, and CV2, respectively. For AS1, we used character-level tokenization with 4231 Chinese characters. It should be noted that before extracting subwords or characters, the ASR transcriptions were normalized regardless of the corpus.

B. Model and Network Architecture

We evaluated end-to-end ASR models illustrated in Fig. 1. **CTC** and **Transducer** are the baseline models trained based on \mathcal{L}_{ctc} and \mathcal{L}_{tra} , as defined by Eqs. (9) and (15), respectively. **BERT-CTC** and **BECTRA** are the proposed models trained based on $\mathcal{L}_{bertctc}$ and \mathcal{L}_{bectra} , as defined by Eqs. (32) and (42), respectively.

The Conformer encoder in Eq. (2) consisted of two convolutional neural network (CNN) layers followed by a stack of I = 12 encoder blocks. The CNN layers had 256 channels, a kernel size of 3×3 , and a stride size of 2, which resulted in down-sampling the input length by a factor of 4 (i.e., T = T'/4). For the self-attention module in Eq. (3), the number of heads $d_{\rm h}$, dimension of a self-attention layer $d_{\rm model}$, and dimension of a feed-forward network $d_{\rm ff}$, were set to 4, 256, and 1024, respectively. For the depthwise separable convolution module in Eq. (4), we used a kernel size of 31.

For the transducer-based models, including Transducer and BECTRA, the prediction network was a single long short-term memory (LSTM) layer with 256 hidden units. The joint network consisted of a single linear layer with 256 hidden units, followed by a hyperbolic tangent activation function.

Regarding the BERT-based models, including BERT-CTC and BECTRA, the concatenation network was the Transformer encoder [33] with 6 blocks, where d_h , d_{model} , and d_{ff} were

³https://github.com/YosukeHiguchi/espnet/tree/bectra

configured to 4, 256, and 2048, respectively. We applied two CNN layers to the encoder output before passing it through the concatenation network, using the same configuration as that of the down-sampling layer in the Conformer encoder. Unless stated otherwise, we used a BERT_{BASE} (uncased) model trained for each language from the HuggingFace Transformers library [65]: English [66] (with $|\mathcal{V}^{b}| = 30522$) and Mandarin [67] (with $|\mathcal{V}^{b}| = 21128$).

C. Training Configuration

For each dataset, we mostly adhered to the configurations provided by the ESPnet2 recipe. We trained the models for 100 epochs on LS-100, LL-10, and AS1; 70 epochs on TED2 and LS-960; and 50 epochs on CV2. We used the Adam optimizer [68] for weight updates with the beta coefficients (β_1, β_2) , epsilon parameter, and weight decay rate of (0.9, 0.999), 10^{-8} , and 10^{-6} , respectively. We used Noam learning rate scheduling [33], where the number of warmup steps was set to 15k, and a peak learning rate was tuned from $\{1.0, 2.0\} \times 10^{-3}$. We set the batch size to 256, except for LL-10, which was set to 32. We augmented speech data using speed perturbation [69] with a factor of 3 and SpecAugment [70], [71]. For the hyperparameters in SpecAugment, we set the number of frequency and time masks to 2 and 5, and the size of frequency and time masks to 27 and 0.05T'. For BECTRA, we set λ in Eq. (42) to 0.5.

For all of the models, we applied the intermediate CTC regularization technique [72], [73] to the Conformer encoder, which has been demonstrated to enhance ASR performance. Similarly to the CTC loss in Eq. (9), an auxiliary CTC loss was calculated using the output of the 6-th encoder block $H^{(i=6)}$. The intermediate CTC loss was based on a target sequence W^a tokenized by the ASR vocabulary \mathcal{V}^a . This is especially effective for model training with the large BERT vocabulary \mathcal{V}^b , facilitating the prediction of sparse word-level tokens in a hierarchical multi-tasking manner [74]–[77].

D. Decoding Configuration

A final model was obtained for evaluation by averaging model parameters over 10 checkpoints with the best validation performance. For the number of iterations in BERT-CTC decoding (in Algorithm 1), we set K to 20 for BERT-CTC and 10 for BECTRA. We performed the beam search decoding with a beam size of 10 for Transducer and 5 for BECTRA.

During the initialization process of a masked sequence in BERT-CTC decoding (Algorithm 1 Step 1), the output length was determined based on intermediate predictions. To be more specific, we utilized the intermediate encoder states, where the auxiliary CTC loss was applied, to perform best path decoding. This allowed us to generate a sequence tokenized based on the ASR vocabulary \mathcal{V}^a , which was then retokenized using the BERT vocabulary \mathcal{V}^b to estimate the initial length.

VI. RESULTS

A. Effectiveness of BERT-CTC

We first investigate the effectiveness of BERT-CTC, which is designed to enhance ASR performance by integrating audio



Fig. 2. WER or CER [%] (\downarrow) of BERT-CTC evaluated on development sets, using varying numbers of decoding iterations. When K = 1, the model relies solely on audio information to predict output tokens. When K > 1, the model incorporates linguistic information from BERT to refine its outputs.

TABLE III
WER [%] (\downarrow) of CTC and Transducer baselines compared to our
PROPOSED BERT-CTC, EVALUATED ON LIBRISPEECH-100H. CTC AND
Transducer were trained using either the ASR vocabulary \mathcal{V}^{a}
or the BERT vocabulary $\mathcal{V}^{b}.$

	Output	Vocab.	Dev	WER	Test WER			
Model	\mathcal{V}^{a}	\mathcal{V}^{b}	clean	other	clean	other		
CTC	\checkmark		6.9	20.1	7.0	20.2		
CIC		\checkmark	11.2	21.4	11.4	22.0		
T	\checkmark		5.9	17.7	6.0	17.6		
Transducer		\checkmark	9.7	21.5	9.8	22.3		
BERT-CTC		\checkmark	7.0	16.4	7.1	16.5		

information with linguistic knowledge from BERT. Figure 2 depicts the relationship between the number of decoding iterations (K in Algorithm 1) and the BERT-CTC results, as evaluated by the word error rate (WER) for LS-100 and TED2, and the character error rate (CER) for AS-1. Note that WERs for LS-100 are calculated as an average of the scores on the *dev*-{*clean, other*} sets. During decoding with K = 1, the model only relies on the speech input, as all output tokens are masked, and the model does not have access to any linguistic cues (cf. Eq. (26)). By increasing the number of iterations with K > 1, the model successfully utilized the knowledge from BERT to refine the output tokens (cf. Eq. (25)), leading to more beneficial outcomes across all tasks.

B. Difficulty of Training ASR with BERT Vocabulary

In Table III, we compare WERs obtained by training CTC and Transducer models on LS-100 using either the ASR or BERT vocabulary (\mathcal{V}^{a} vs. \mathcal{V}^{b}). It is apparent that CTC and Transducer produced notably higher WERs when trained with the BERT vocabulary, indicating that employing word-level BERT units was not an optimal choice for ASR training [78]. Moreover, we also mention that the BERT vocabulary is not precisely aligned with the intended domain of the LibriSpeech task (e.g., Wikipedia vs. audiobook). As a result, there was a potential domain mismatch between the ASR training text and BERT vocabulary.

In contrast, despite using the same BERT vocabulary, our proposed BERT-CTC model significantly outperformed both the conventional CTC and Transducer models. The gain from

]	LibriSpe	ech-100ł	1]	LibriSpe	ech-960h	1	TED-I	LIUM2	AISH	ELL-1
	Output	Vocab.	Dev WER		Test WER		Dev WER		Test WER		WER		CI	ER
Model	\mathcal{V}^{a}	\mathcal{V}^{b}	clean	other	clean	other	clean	other	clean	other	Dev	Test	Dev	Test
Transducer BERT-CTC BECTRA	√ √	\checkmark	5.9 7.0 5.1	17.7 16.4 15.4	6.0 7.1 5.4	17.6 16.5 15.5	2.5 3.1 2.6	6.8 7.1 6.7	2.8 3.2 2.9	6.8 7.1 6.7	7.8 8.3 7.3	7.4 7.6 6.9	4.9 3.9 3.7	5.3 4.0 3.9

CTC demonstrates the effectiveness of leveraging BERT's contextualized linguistic embeddings for relaxing the conditional independence assumption (cf. Table I). BERT-CTC improved over Transducer by modeling output dependencies using BERT, allowing the model to consider bi-directional context in the target sequence (cf. Table I). BERT-CTC addressed the domain-mismatch issue through the effective use of powerful representations obtained from BERT. However, the effectiveness of BERT-CTC diminishes when compared to CTC and Transducer models trained on the ASR vocabulary, thereby reducing the advantage gained from using BERT.

C. Main Results

Table IV lists results on the major ASR tasks, including LS-100, LS-960, TED2, and AS1, evaluated in terms of the WER or CER. We compare our proposed models, BERT-CTC and BECTRA, with Transducer trained on the ASR vocabulary, which was the best performing baseline from Table III. As discussed in Section VI-B, BERT-CTC underperformed compared to Transducer in several tasks, which we attribute to the vocabulary discrepancy. Overall, BECTRA achieved the highest performance compared to all other models, taking the advantages of both BERT-CTC and Transducer (cf. Section III-C). BECTRA effectively utilized BERT knowledge by adopting BERT-CTC-based feature extraction, and incorporated the transducer framework to enable more suitable and flexible token generation using the ASR vocabulary. In Section VII-A, we present the specific errors that BECTRA succeeded in recovering, as compared to BERT-CTC.

Another notable observation was that with more training data in LS-960, the performance gap between Transducer and BECTRA narrowed, and the impact of BERT became less pronounced. This finding led us to explore two further directions for investigation, which we discuss in the following two subsections.

D. Results on Low-Resource Setting

The proposed models, BERT-CTC and BECTRA, were less significant in the LS-960 task, likely due to the fact that the dataset already contained a sufficient amount of text data. Consequently, the ASR models were capable of acquiring rich linguistic information specific to the LibriSpeech domain, without relying on BERT knowledge. This can be consistent with the recent results on LibriSpeech, which indicate an LM (for shallow fusion) has a limited effect on performance with a well-trained ASR model [79].

TABLE V WER [%] (\downarrow) comparison on low-resource Libri-Light-10h

	Output	Vocab.	Dev	WER	Test WER			
Model	\mathcal{V}^{a}	\mathcal{V}^{b}	clean	other	clean	other		
CTC Transducer BERT-CTC		√ √ √	36.2 34.9 27.2	46.9 45.9 39.2	36.8 35.6 28.3	47.7 46.8 40.4		
CTC Transducer BECTRA			24.8 21.7 19.9	43.2 38.8 36.1	25.8 22.3 20.3	44.4 39.7 37.2		

TABLE VI
WER [%] (\downarrow) comparison on CoVoST2 with and without
CONSIDERING PUNCTUATION OR CASING. CTC AND TRANSDUCER WERE
TRAINED ON THE ASR VOCABULARY. † INDICATES A "CASED" MODEL.

		Text	Style	WER			
Model	Masked LM	Punct.	Casing	Dev	Test		
CTC	_	_	-	18.7	23.2		
Transducer	-	-	-	15.2	18.8		
	BERT _{BASE}	X	X	14.4	17.6		
	BERTBASE	\checkmark	X	14.0	17.2		
	$\text{BERT}_{\text{BASE}}^{\dagger}$	\checkmark	\checkmark	14.0	17.1		
	$RoBERTa^{\dagger}_{BASE}$	\checkmark	\checkmark	14.1	17.1		
BECTRA	BERTLARGE	✓	× –	13.4	16.4		
	$\mathrm{BERT}^{\dagger}_{\mathrm{LARGE}}$	\checkmark	\checkmark	13.8	16.7		
	DistilBERT _{BASE}	\checkmark	<u>×</u>	14.3	17.6		
	$\text{DistilBERT}_{\text{BASE}}^{\dagger}$	\checkmark	\checkmark	14.9	17.9		
	ALBERT _{BASE}	\checkmark	×	14.6	17.7		

We, thus, examine the other end of the spectrum, evaluating the proposed models on LL-10, an extremely low-resource condition with only 10 hours of training data. Table V lists WERs obtained by training the models using either the ASR or BERT vocabulary (\mathcal{V}^a vs. \mathcal{V}^b). The overall trend was in line with what was observed in the previous results in Tables III and IV, highlighting the ability of the BERT-based approaches to compensate for the limited availability of training text data.

E. Results on Preserving Punctuation and Casing

The experimental setups used to obtain results in Table IV could potentially limit the full capabilities of BERT since the training text data was normalized for ASR training (see Section V-A). Pre-trained LMs are typically trained on written-style text, preserving punctuation and casing as a standard practice. Therefore, it appears that the prior experimental

condition may have caused a discrepancy regarding the text format used as input into BERT.

To verify the above consideration, we conducted experiments on CV2 while explicitly controlling the preservation of punctuation and casing. Table VI presents the results of BECTRA in comparison to CTC and Transducer trained on the ASR vocabulary. Note that punctuation and casing only affect the BERT-CTC processing (i.e., Algorithm 2 Step 1) with the BERT vocabulary \mathcal{V}^{b} , and the WER is calculated using the normalized text, which is obtained from a hypothesis tokenized by the ASR vocabulary \mathcal{V}^a . For training with casing preserved, we used the "cased" model⁴. Looking at the BECTRA results based on BERT_{BASE}, BECTRA outperformed the baseline models even without considering punctuation and casing, which is consistent with the outcome in Table IV. The addition of punctuation provided further improvement, whereas the impact of adding casing was less significant. This suggests the importance of matching the input text format used for BERT with that used for input during pre-training.

BECTRA is capable of processing two distinct types of text with different vocabularies, thanks to the BERT-CTC's ability to handle BERT information and the transducer decoder's capacity to generate tokens in a desired text style. This is accomplished through an end-to-end framework, eliminating the need for a retokenization process in the output sequence.

F. Application of BERT Variants

In Table VI, we compare the BECTRA results obtained from using various pre-trained masked LMs other than $BERT_{BASE}$. RoBERTa_{BASE}⁵ is an extension of BERT that is constructed with an improved pre-training procedure [80]. However, there was little improvement over the results using vanilla BERT_{BASE}. BECTRA greatly benefited from increasing the capacity of a pre-trained LM, with BERT_{LARGE}⁶ achieving the best overall performance.

BECTRA incurs a high computational cost, especially during inference, primarily due to the multiple forward passes in BERT (i.e., K = 10 times) with the $O(N^2)$ computational and memory complexities in self-attention layers. To mitigate this drawback, we explored lightweight variants, including DistilBERT_{BASE}⁷ and ALBERT_{BASE}⁸. DistilBERT distills BERT's knowledge into a more compact model [81], while ALBERT reduces model size by sharing common parameters across layers [82]. Both lightweight models achieved superior results compared to the baseline models, with only minor performance degradation compared to BERT_{BASE}.

In alignment with the observation in Section VI-E, the BERT variants gave more importance to considering punctuation than casing.

G. Combination with Shallow Fusion

We examined the feasibility of utilizing an in-domain LM during BECTRA inference. BECTRA can adopt the commonly

TABLE VII WER [%] (↓) COMPARISON ON LIBRISPEECH-100H WITH AND WITHOUT PERFORMING SHALLOW FUSION DURING INFERENCE

	w/	o Shall	ow Fusi	on	w/ Shallow Fusion					
	Dev	WER	Test	WER	Dev	WER	Test WER			
Model	clean	other	clean	other	clean	other	clean	other		
Transducer BECTRA	5.9 5.1	17.7 15.4	6.0 5.4	17.6 15.5	5.1 4.5	15.0 14.2	5.1 4.9	15.1 14.2		

used shallow fusion technique, as its inference process relies on the original transducer framework (Algorithm 2 Step 2). We used the external text data provided by LibriSpeech to train an RNN-LM, which consisted of 4 LSTM layers with 2048 units. The LM weight and beam size for shallow fusion were configured to 0.5 and 20, respectively.

In Table VII, we compare the WER between the Transducer and BECTRA models, which were trained on LS-100 and decoded with or without the RNN-LM. Through the incorporation of linguistic knowledge from RNN-LM via shallow fusion, Transducer significantly improved the performance, resulting in lower WERs compared to BECTRA, which by default employs BERT in its formulation. Similarly, the performance of BECTRA was further improved by utilizing shallow fusion. This indicates that BECTRA effectively integrated general knowledge from BERT and domain-specific knowledge from the RNN-LM, thereby enhancing its ability to consider linguistic information.

VII. ANALYSIS

A. Example Decoding Process of BECTRA

Table VIII provides an example of the BECTRA inference process, which was obtained by decoding an utterance in the CoVoST2 test set. We used the model trained with $BERT_{BASE}$ from Table VI, which only preserved punctuation during BERT-CTC decoding. During the first iteration of BERT-CTC inference (k = 1), the model produced erroneous predictions that are phonetically similar to the actual tokens (e.g., "car" vs. "carr", "mc cly" vs. "mcclenny"). The model was solely conditioned on acoustic information during the first iteration, which led to difficulties in accurately determining the target tokens. As the iteration progressed $(k = \{5, 10\})$, the model was able to correct some of the errors by considering the output dependencies extracted from BERT. However, the model still struggled with recognizing rare words such as the place name "mcclenny". In addition, the model mistakenly identified the technical term "turpentine" as "carpenter", despite the two words sounding dissimilar. This error is likely due to the contextual information being influenced by the BERT knowledge. The transducer decoding in BECTRA effectively recovered these errors by accurately predicting the rare words. The autoregressive token generation facilitated more flexible estimation of tokens using a vocabulary suited for ASR in the CoVoST2 domain.

⁴https://huggingface.co/bert-base-cased

⁵https://huggingface.co/roberta-base

⁶https://huggingface.co/bert-large-{cased,uncased}

⁷https://huggingface.co/distilbert-base-{cased,uncased}

⁸https://huggingface.co/albert-base-v2

TABLE VIII

EXAMPLE INFERENCE PROCESS OF BECTRA (ALGORITHM 2), DECODING AN UTTERANCE FROM COVOST2 TEST SET. DURING BERT-CTC INFERENCE (ALGORITHM 2 STEP 1), THE HIGHLIGHTED TOKENS WERE REPLACED WITH THE MASK TOKEN AND SUBSEQUENTLY RE-PREDICTED IN THE FOLLOWING ITERATION. THE TRANSDUCER DECODING WITH BEAM SEARCH FURTHER REFINED THE BERT-CTC RESULT (ALGORITHM 2 STEP 2). THE CORRECTED TOKENS ARE COLORED IN BLUE, WHILE THE INCORRECT ONES ARE IN RED. PUNCTUATION IS ONLY CONSIDERED DURING BERT-CTC DECODING.

	BERT-CTC $(k=1)$	car	,	s	business	in	mc	cly	was	in	sawmill	mills	,	tutine	,	lumber ,	and	land .
îne	BERT-CTC $(k=5)$	carr	,	s	business	in	mc	lean	was	in	sawmill	mills	,	tu ,	lun	nber and	land	
Ref	BERT-CTC $(k=10)$	carr	,	s	business	in	mc	lean	was	in	sawmills	s, car	pe	enter,	lu	mber and	lanc	Ι.
_ ↓	BECTRA $(B=5)$		_&	ap	os s bus	sines	s ir	n_m	clenn	y	was_in	sawmill	s	turpen	tine	lumber	and	land
	Reference	carr	8	ap	os s bus	sines	s ir	n me	cclenn	y y	was in	sawmill	s	turpen	tine	lumber	and	land



Fig. 3. Visualization of self-attention weights learned in the concatenation network. White lines indicate the boundaries of audio and token sequences, H and E, which are concatenated and processed by self-attention in Eq. (22).

B. Attention Visualization

In Fig. 3, we present example attention weight matrices that were obtained from the second self-attention layer of the concatenation network in BERT-CTC. We identified two major attention patterns: weights aligning audio and token sequences by capturing their inter-dependencies (Fig. 3 left) and weights attending to the inner-dependencies within each sequence (Fig. 3 right). These attention weights support the effectiveness of our proposed architectural design for BERT-CTC, indicating audio and linguistic information are merged by considering their inter end inner-dependencies.

C. Conditional Independence of $p(W^{\mathsf{b}}|\tilde{W}^{\mathsf{b}}, \mathscr{O})$

We empirically validate the conditional independence assumption made in Eq. (19), where the output sequence W^b depends solely on its masked sequence \tilde{W}^b without audio information O. To this end, we incorporated trainable crossattention layers into the BERT module, which is similar to the technique proposed in Adapter-BERT Networks [83]. These additional layers enable each BERT layer to attend to the audio encoder output H, thereby allowing BERT-CTC to achieve $p(W^b|\tilde{W}^b, O)$. After training the modieifed BERT-CTC on LS-100, we observed inferior WERs compared to the original BERT-CTC presented in Table IV, with 7.2%/17.9% and 7.3%/18.0% on the development and test sets, respectively.

The finding above suggests that BERT is capable of capturing sophisticated linguistic information without relying on audio input conditioning. Furthermore, this implies that our proposed formulation does not require any adaptation or finetuning of BERT.

D. BECTRA with BERT Vocabulary

To further examine the advantages of BECTRA compared to BERT-CTC, we utilized the BERT vocabulary to train the transducer decoder of BECTRA. Under the same experimental conditions using LS-100, BECTRA with the BERT vocabulary achieved 7.1%/16.6% on the LibriSpeech test sets, while BERT-CTC resulted in slightly worse scores of 7.3%/16.9%. This improvement over BERT-CTC can be attributed to the transducer-based formulation in BECTRA, which does not rely on the conditional independence assumption between outputs (Eq. (20) vs. Eq.(35)). Nevertheless, using the ASR vocabulary appeared to be the superior choice.

Different from the results reported in Table IV, the above results were obtained by reducing the number of training epochs $(100 \rightarrow 50)$. Training a transducer-based model with a large vocabulary size leads to a substantial increase in memory consumption [84], resulting in a significant extension of the training time. Therefore, employing the ASR vocabulary is the optimal approach for constructing the BECTRA model, as it also facilitates faster training and inference.

VIII. CONCLUSION AND FUTURE WORKS

We proposed novel end-to-end ASR models that effectively incorporate a pre-trained masked LM in their formulations. BERT-CTC adapts BERT for CTC to alleviate the conditional independence assumption between output tokens, while integrating both audio and linguistic information through an iterative refinement algorithm. BECTRA extends BERT-CTC by adopting the transducer framework, which enables the management of different vocabularies that contain varying text formats and styles. The experimental results conducted on diverse datasets demonstrated that the advantages of the proposed models outperform the conventional approaches. Furthermore, our comprehensive analyses confirmed the effectiveness of the proposed formulations and architectural designs.

To further expand the scope of this study, future work should consider the implementation of the proposed models in streaming scenarios. The possible solutions include the adoption of the two-pass modeling [85] or blockwise-attention mechanism [86]. In addition, we plan to extend our approaches to incorporate autoregressive pre-trained LMs, such as GPT-3 [2] and LLaMA [87].

REFERENCES

J. Devlin *et al.*, "BERT: Pre-training of deep bidirectional Transformers for language understanding," in *Proc. NAACL-HLT*, 2019, pp. 4171– 4186.

- [2] T. Brown et al., "Language models are few-shot learners," in Proc. NeurIPS, 2020, pp. 1877–1901.
- [3] I. Tenney et al., "BERT rediscovers the classical NLP pipeline," in Proc. ACL, 2019, pp. 4593–4601.
- [4] J. Shin *et al.*, "Effective sentence scoring method using BERT for speech recognition," in *Proc. ACML*, 2019, pp. 1081–1093.
- [5] W.-C. Huang et al., "Speech recognition by simply fine-tuning BERT," in Proc. ICASSP, 2021, pp. 7343–7347.
- [6] Y.-S. Chuang *et al.*, "SpeechBERT: An audio-and-text jointly learned language model for end-to-end spoken question answering," in *Proc. Interspeech*, 2020, pp. 4168–4172.
- [7] Y.-A. Chung *et al.*, "SPLAT: Speech-language joint pre-training for spoken language understanding," in *Proc. NAACL-HLT*, 2021, pp. 1897– 1907.
- [8] T. Hayashi et al., "Pre-trained text embeddings for enhanced text-tospeech synthesis," in Proc. Interspeech, 2019, pp. 4430–4434.
- [9] T. Kenter *et al.*, "Improving the prosody of RNN-based english text-tospeech synthesis by incorporating a BERT model," in *Proc. Interspeech*, 2020, pp. 4412–4416.
- [10] J.-U. Bang *et al.*, "Improving end-to-end speech translation model with BERT-based contextual information," in *Proc. ICASSP*, 2022, pp. 6227– 6231.
- [11] A. Graves and N. Jaitly, "Towards end-to-end speech recognition with recurrent neural networks," in *Proc. ICML*, 2014, pp. 1764–1772.
- [12] J. K. Chorowski et al., "Attention-based models for speech recognition," in Proc. NeurIPS, 2015, pp. 577–585.
- [13] W. Chan *et al.*, "Listen, attend and spell: A neural network for large vocabulary conversational speech recognition," in *Proc. ICASSP*, 2016, pp. 4960–4964.
- [14] H. Futami *et al.*, "Distilling the knowledge of BERT for sequence-tosequence ASR," in *Proc. Interspeech*, 2020, pp. 3635–3639.
- [15] Y. Bai et al., "Fast end-to-end speech recognition via nonautoregressive models and cross-modal knowledge transferring from BERT," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 29, pp. 1897–1911, 2021.
- [16] Y. Kubo *et al.*, "Knowledge transfer from large-scale pretrained language models to end-to-end speech recognizers," in *Proc. ICASSP*, 2022, pp. 8512–8516.
- [17] K.-H. Lu and K.-Y. Chen, "A context-aware knowledge transferring strategy for CTC-based ASR," in *Proc. SLT*, 2022, pp. 60–67.
- [18] J. Salazar et al., "Masked language model scoring," in Proc. ACL, 2020, pp. 2699–2712.
- [19] S.-H. Chiu and B. Chen, "Innovative BERT-based reranking language models for speech recognition," in *Proc. SLT*, 2021, pp. 266–271.
- [20] H. Futami *et al.*, "ASR rescoring and confidence estimation with ELECTRA," in *Proc. ASRU*, 2021, pp. 380–387.
- [21] T. Udagawa *et al.*, "Effect and analysis of large-scale language model rescoring on competitive ASR systems," in *Proc. Interspeech*, 2022, pp. 3919–3923.
- [22] C. Yi et al., "Efficiently fusing pretrained acoustic and linguistic encoders for low-resource speech recognition," *IEEE Signal Processing Letters*, vol. 28, pp. 788–792, 2021.
- [23] G. Zheng et al., "Wav-BERT: Cooperative acoustic and linguistic representation learning for low-resource speech recognition," in Proc. Findings of EMNLP, 2021, pp. 2765–2777.
- [24] K. Deng *et al.*, "Improving hybrid CTC/attention end-to-end speech recognition with pretrained acoustic and language models," in *Proc. ASRU*, 2021, pp. 76–82.
- [25] F.-H. Yu et al., "Non-autoregressive ASR modeling using pre-trained language models for Chinese speech recognition," *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, vol. 30, pp. 1474– 1482, 2022.
- [26] A. Graves *et al.*, "Connectionist temporal classification: Labelling unsegmented sequence data with recurrent neural networks," in *Proc. ICML*, 2006, pp. 369–376.
- [27] A. Graves, "Sequence transduction with recurrent neural networks," in Proc. ICML Representation Learning Workshop, 2012.
- [28] Y. Higuchi *et al.*, "BERT meets CTC: New formulation of end-to-end speech recognition with pre-trained masked language model," in *Proc. Findings of EMNLP*, 2022, pp. 5486–5503.
- [29] —, "BECTRA: Transducer-based end-to-end ASR with BERTenhanced encoder," in *Proc. ICASSP*, 2023.
- [30] A. Graves *et al.*, "Speech recognition with deep recurrent neural networks," in *Proc. ICASSP*, 2013, pp. 6645–6649.
- [31] A. Gulati et al., "Conformer: Convolution-augmented Transformer for speech recognition," in Proc. Interspeech, 2020, pp. 5036–5040.

- [32] T. Hori *et al.*, "Advances in joint CTC-attention based end-to-end speech recognition with a deep CNN encoder and RNN-LM," in *Proc. Interspeech*, 2017, pp. 949–953.
- [33] A. Vaswani *et al.*, "Attention is all you need," in *Proc. NeurIPS*, 2017, pp. 5998–6008.
- [34] Y. Higuchi *et al.*, "A comparative study on non-autoregressive modelings for speech-to-text generation," in *Proc. ASRU*, 2021, pp. 47–54.
- [35] J. Gu et al., "Non-autoregressive neural machine translation," in Proc. ICLR, 2018.
- [36] F. Boyer *et al.*, "A study of Transducer based end-to-end ASR with ESPnet: Architecture, auxiliary loss and decoding strategies," in *Proc. ASRU*, 2021, pp. 16–23.
- [37] Y. Fujita *et al.*, "Insertion-based modeling for end-to-end automatic speech recognition," in *Proc. Interspeech*, 2020, pp. 3660–3664.
- [38] M. E. Peters *et al.*, "To tune or not to tune? adapting pretrained representations to diverse tasks," in *Proc. RepLANLP*, 2019, pp. 7–14.
- [39] J. Zhu et al., "Incorporating BERT into neural machine translation," in Proc. ICLR, 2020.
- [40] L. Stappen *et al.*, "Cross-lingual zero-and few-shot hate speech detection utilising frozen transformer language models and AXEL," *arXiv preprint* arXiv:2004.13850, 2020.
- [41] J. L. McClelland and J. L. Elman, "The TRACE model of speech perception," *Cognitive psychology*, vol. 18, no. 1, pp. 1–86, 1986.
- [42] D. Norris, "Shortlist: A connectionist model of continuous speech recognition," *Cognition*, vol. 52, no. 3, pp. 189–234, 1994.
- [43] M. Ghazvininejad *et al.*, "Mask-predict: Parallel decoding of conditional masked language models," in *Proc. EMNLP-IJCNLP*, 2019, p. 6112–6121.
- [44] W. Chan et al., "Imputer: Sequence modelling via imputation and dynamic programming," in Proc. ICML, 2020, pp. 1403–1413.
- [45] Y. Higuchi *et al.*, "Mask CTC: Non-autoregressive end-to-end ASR with CTC and mask predict," in *Proc. Interspeech*, 2020, pp. 3655–3659.
- [46] —, "Improved mask-CTC for non-autoregressive end-to-end ASR," in *Proc. ICASSP*, 2021, pp. 8363–8367.
- [47] N. Chen et al., "Non-autoregressive transformer for speech recognition," IEEE Signal Processing Letters, vol. 28, pp. 121–125, 2021.
- [48] H. Futami *et al.*, "Non-autoregressive error correction for CTC-based ASR with phone-conditioned masked LM," in *Proc. Interspeech*, 2022, pp. 3889–3893.
- [49] R. Fan et al., "Acoustic-aware non-autoregressive spell correction with mask sample decoding," arXiv preprint arXiv:2210.08665, 2022.
- [50] A. Hannun *et al.*, "Deep speech: Scaling up end-to-end speech recognition," *arXiv preprint arXiv:1412.5567*, 2014.
- [51] C. Gulcehre et al., "On using monolingual corpora in neural machine translation," arXiv preprint arXiv:1503.03535, 2015.
- [52] J. Chorowski and N. Jaitly, "Towards better decoding and language model integration in sequence to sequence models," in *Proc. Interspeech*, 2017, pp. 523–527.
- [53] A. Kannan *et al.*, "An analysis of incorporating an external language model into a sequence-to-sequence model," in *Proc. ICASSP*, 2018, pp. 5824–5828.
- [54] A. Sriram et al., "Cold fusion: Training seq2seq models together with language models," in Proc. Interspeech, 2018, pp. 387–391.
- [55] C. Shan *et al.*, "Component fusion: Learning replaceable language model component for end-to-end speech recognition system," in *Proc. ICASSP*, 2019, pp. 5361–5635.
- [56] S. Watanabe *et al.*, "ESPnet: End-to-end speech processing toolkit," in *Proc. Interspeech*, 2018, pp. 2207–2211.
- [57] —, "The 2020 ESPnet update: New features, broadened applications, performance improvements, and future plans," in *Proc. DSLW*, 2021, pp. 1–6.
- [58] V. Panayotov et al., "Librispeech: An ASR corpus based on public domain audio books," in Proc. ICASSP, 2015, pp. 5206–5210.
- [59] J. Kahn et al., "Libri-Light: A benchmark for ASR with limited or no supervision," in Proc. ICASSP, 2020, pp. 7669–7673.
- [60] A. Rousseau *et al.*, "Enhancing the TED-LIUM corpus with selected data for language modeling and more TED talks," in *Proc. LREC*, 2014, pp. 3935–3939.
- [61] H. Bu *et al.*, "AISHELL-1: An open-source Mandarin speech corpus and a speech recognition baseline," in *Proc. O-COCOSDA*, 2017, pp. 1–5.
- [62] C. Wang et al., "CoVoST 2 and massively multilingual speech translation," in Proc. Interspeech, 2021, pp. 2247–2251.
- [63] R. Ardila *et al.*, "Common voice: A massively-multilingual speech corpus," in *Proc. LREC*, 2020, pp. 4218–4222.

- [64] T. Kudo, "Subword regularization: Improving neural network translation models with multiple subword candidates," in *Proc. ACL*, 2018, pp. 66– 75.
- [65] T. Wolf et al., "Transformers: State-of-the-art natural language processing," in Proc. EMNLP: System Demonstrations, 2020, pp. 38–45.
- [66] "bert-base-uncased," https://huggingface.co/bert-base-uncased, [Online; Accessed on March-23-2023].
- [67] "bert-base-chinese," https://huggingface.co/bert-base-chinese, [Online; Accessed on March-23-2023].
- [68] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," in *Proc. ICLR*, 2015.
- [69] T. Ko et al., "Audio augmentation for speech recognition," in Proc. Interspeech, 2015, pp. 3586–3589.
- [70] D. S. Park *et al.*, "SpecAugment: A simple data augmentation method for automatic speech recognition," in *Proc. Interspeech*, 2019, pp. 2613– 2617.
- [71] —, "SpecAugment on large scale datasets," in *Proc. ICASSP*, 2020, pp. 6879–6883.
- [72] A. Tjandra *et al.*, "DEJA-VU: Double feature presentation and iterated loss in deep Transformer networks," in *Proc. ICASSP*, 2020, pp. 6899– 6903.
- [73] J. Lee and S. Watanabe, "Intermediate loss regularization for CTC-based speech recognition," in *Proc. ICASSP*, 2021, pp. 6224–6228.
- [74] S. Fernández *et al.*, "Sequence labelling in structured domains with hierarchical recurrent neural networks," in *Proc. IJCAI*, 2007, pp. 774– 779.
- [75] R. Sanabria and F. Metze, "Hierarchical multitask learning with CTC," in *Proc. SLT*, 2018, pp. 485–490.
- [76] K. Krishna *et al.*, "Hierarchical multitask learning for CTC-based speech recognition," *arXiv preprint arXiv:1807.06234*, 2018.
- [77] Y. Higuchi *et al.*, "Hierarchical conditional end-to-end ASR with CTC and multi-granular subword units," in *Proc. ICASSP*, 2022, pp. 7797– 7801.
- [78] H. Soltau *et al.*, "Neural speech recognizer: Acoustic-to-word LSTM model for large vocabulary speech recognition," *arXiv preprint arXiv:1610.09975*, 2016.
- [79] Y. Zhang et al., "Pushing the limits of semi-supervised learning for automatic speech recognition," arXiv preprint arXiv:2010.10504, 2020.
- [80] Y. Liu *et al.*, "RoBERTa: A robustly optimized BERT pretraining approach," *arXiv preprint arXiv:1907.11692*, 2019.
- [81] V. Sanh et al., "DistilBERT, a distilled version of BERT: smaller, faster, cheaper and lighter," in Proc. NeurIPS Workshop on Energy Efficient Machine Learning and Cognitive Computing, 2019.
- [82] Z. Lan et al., "ALBERT: A lite BERT for self-supervised learning of language representations," in Proc. ICLR, 2020.
- [83] J. Guo et al., "Incorporating BERT into parallel sequence decoding with adapters," in Proc. NeurIPS, 2020, pp. 10843–10854.
- [84] J. Lee et al., "Memory-efficient training of RNN-Transducer with sampled softmax," in Proc. Interspeech, 2022, pp. 4441–4445.
- [85] T. N. Sainath et al., "Two-pass end-to-end speech recognition," in Proc. Interspeech, 2019, pp. 2773–2777.
- [86] T. Wang et al., "Streaming end-to-end ASR based on blockwise nonautoregressive models," in Proc. Interspeech, 2021, pp. 3755–3759.
- [87] H. Touvron et al., "LLaMA: Open and efficient foundation language models," arXiv preprint arXiv:2302.13971, 2023.