# A simple geometric construction of an ODE with undecidable blow-ups

Manh Khang Huynh

October 3, 2024

#### Abstract

We present a simple construction of an ODE on  $\mathbb{R}^n$  where the vector field is smooth, and finite-time blow-up is equivalent to the halting problem for a universal Turing machine.

### 1 Introduction

The classical ODE problem

$$\dot{x}(t) = F(x(t)) \tag{1.1}$$
$$x(0) = x_0$$

where  $F : \mathbb{R}^n \to \mathbb{R}^n$  is smooth, admits a unique smooth solution x(t) which lives on a maximal time interval of existence  $(t_{\min}, t_{\max})$ . In particular if  $t_{\max} < \infty$  then we must have finite-time blow-up [Tes12], i.e.  $\lim_{t\uparrow t_{\max}} |x(t)| = \infty$ . Given F and  $x_0$ , determining the value of  $t_{\max}$ , or simply whether it is finite, is an unsolved problem. In certain scenarios, we can use numerical methods to rigorously verify that the ODE solution will blow up in some specific direction [Tak+17].

In [Tao16], Terence Tao constructed a solution to an averaged version of 3D Navier-Stokes which exhibits finite-time blow-up. The ideas behind the "logic gates" used in the construction led to [Tao17], in which the author used Nash embedding to embed any vector-field flows with an "adapted 1-form", including a smooth model of a universal Turing machine, into a potential well system (which is an ODE on the cotangent bundle of  $\mathbb{R}^n$ ). In particular, it also implied the halting problem was equivalent to the trajectory entering some bounded open set, with the initial position corresponding to the input tape for the Turing machine (see also [Moo90; Moo91] for the theory of generalized shifts). Similar Turing completeness results were then proved for steady Euler flows, and we refer to [Car+23; Car+21; CMP22] for more details.

Terence Tao speculated in [Tao17] that by Turing completeness, one could possibly "program" a solution towards blow-up. In this paper we present such an ODE, where the aforementioned open set becomes "infinity".

**Theorem 1.1** (Main theorem). We can find  $n \in \mathbb{N}$  and a smooth function  $F : \mathbb{R}^n \to \mathbb{R}^n$ , with an associated universal Turing machine TM, and a set of initial positions  $X_0$ , such that for any  $x_0 \in X_0$  (corresponding to some input tape  $s_0$ ), the solution in (1.1) exhibits (finite-time) blow-up <sup>1</sup> if and only if the Turing machine TM halts when given the input tape  $s_0$ .

*Remark* 1.2. The undecidability of ODE blow-up seems natural and expected, given the possible complexity of ODE dynamics. In particular, it was proven in [GBC08]; [GZB09] for analytic vector fields, using computability theory techniques to robustly simulate a Turing machine with small error bounds. Our construction was independently obtained via a short and simple geometric embedding scheme, with an exact simulation of a Turing machine.

#### Acknowledgements

The author would like to thank Jean-Philippe Lessard and Alex Blumenthal for interesting discussions about the theory of rigorous numerical verification.

## 2 Preliminaries

We first recall the definition of a Turing machine.

**Definition 2.1.** A Turing machine  $(Q, \text{START}, \text{HALT}, \Sigma, \delta)$  consists of

- A finite set of states Q, where {START, HALT}  $\subseteq Q$ .
- A finite alphabet set  $\Sigma$  with at least 2 elements.
- A transition function  $\delta: Q \setminus \{\text{HALT}\} \times \Sigma \to Q \times \Sigma \times \{-1, 0, 1\}$

We denote q as the current state and  $t = (t_n)_{n \in \mathbb{Z}} \in \Sigma^{\mathbb{Z}}$  as the current tape. The machine works by following a simple algorithm:

- 1. Set q to START and t to the input tape.
- 2. If q is HALT, halt and return t as output. Otherwise compute  $(q', t'_0, \epsilon) = \delta(q, t_0)$ .
- 3. Replace q with q' and  $t_0$  with  $t'_0$ .

<sup>&</sup>lt;sup>1</sup>an ODE solution could "grow up", i.e. tend to infinity at infinite time, for instance in [Tak+17], but such a scenario is ruled out in our construction.

4. Replace the tape with its  $\epsilon$ -shifted version (with  $\epsilon = 1$  being left-shift, 0 being no shift, and -1 being right-shift). Then return to step 2.

Then for any  $q \in Q \setminus \{\text{HALT}\}$  and  $t \in \Sigma^{\mathbb{Z}}$ , we have an auxiliary map  $\Delta : (q, t) \mapsto (q', t')$  giving the next state q' and the next input tape t'.

From this point on, we fix TM to be a *universal* Turing machine [AB16], which can be used to model any other Turing machine.

We recall the standard torus model for TM as constructed in [Tao17, Section 4].

**Lemma 2.2.** Let  $M = \mathbb{T}^2 \times \mathbb{T}^2$  be the 4-dimensional torus. Each state  $q \in Q$  corresponds to an open square  $B_q \subseteq \mathbb{T}^2$  (with the closed squares  $(\overline{B_q})_{q \in Q}$  being disjoint), while each string  $s \in \Sigma^{\mathbb{Z}}$  corresponds to a unique point  $f_s \in \mathbb{T}^2$ , and there is a diffeomorphism  $\Phi : M \to M$  such that  $\Phi(\overline{B_q} \times \{f_s\}) \subseteq B_{q'} \times \{f_{s'}\}$  for any (q, t) where  $\Delta(q, t) = (q', t')$ .

#### Halting region $U_0$

With the torus model constructed above, we now define  $x_{\text{START}}$  as the center of  $B_{\text{START}}$ , and the open set  $U_0 \subseteq M$  as a small neighborhood of  $\overline{B}_{\text{HALT}} \times \mathbb{T}^2$ , such that  $\overline{U}_0$  is disjoint from any  $\overline{B}_q \times \mathbb{T}^2$  where  $q \neq \text{HALT}$ . Then given a starting point  $(x_{\text{START}}, f_s)$ , the trajectory  $\Phi^{\mathbb{N}}(x_{\text{START}}, f_s)$  enters  $\overline{B}_{\text{HALT}} \times \mathbb{T}^2$  at some time if and only if the Turing machine TM halts when given input tape s. A similar statement holds for the trajectory entering  $U_0$ . We could also modify  $U_0$  to specify some output tape digits.  $U_0$  can also be chosen to be connected with smooth boundary, and we can either shrink or grow  $U_0$  without changing the conclusion.

#### Continuous-time model

To turn discrete-time dynamics into continuous-time dynamics, we consider  $M_I$  which is  $M \times [0,1] / \sim$  where each (p,1) is identified with  $(\Phi(p), 0)$ . We parametrize  $M_I$  by variables (p,t), and consider the one-parameter group, or flow,  $(\Phi_Y^t)_{t \in \mathbb{R}}$  generated by the vector field  $Y = \partial_t$ . Then there is no stationary point (equilibrium). Now we let  $U_1$  be a small neighborhood containing  $U_0 \times \{0\}$  (disjoint from any  $(\overline{B_q} \times \mathbb{T}^2) \times [0,1]$  for  $q \neq$  HALT). Obviously  $U_1$  can be chosen to be connected with smooth boundary.

Consequently, given the starting point  $(x_{\text{START}}, f_s, 0) \in M_I$ , the trajectory along Y enters  $U_1$  at some time if and only if the Turing machine TM halts when given the input tape s.

## 3 Geometric embedding



Figure 3.1: Geometric embedding scheme

We can use Whitney embedding (or Nash embedding) to smoothly embed the manifold  $M_I$  constructed above into a compact region of  $\mathbb{R}^d$  (where d could be chosen to be 10, for instance). Let  $\mathcal{E}$  be this embedding.

### Height function

There is a smooth function h on  $M_I$  such that  $0 \le h \le 1$  and  $\overline{U_1} = h^{-1}(\{1\})$ . We can therefore define the embedding

$$\mathcal{E}_{h}: M_{I} \to \mathbb{R}^{d+1}$$
$$p \mapsto \left(\mathcal{E}\left(p\right), h\left(p\right)\right)$$

Let  $M_h$  be the image of  $\mathcal{E}_h$ . Then  $\mathcal{E}_h(\overline{U_1}) = \{x_{d+1} = 1\} \cap M_h$ . The pushforward  $(\mathcal{E}_h)_* Y$  of Y can be smoothly extended to a vector field  $Y_h$  on  $\mathbb{R}^{d+1}$  with support near  $M_h$ . Consequently, reaching  $\{x_{d+1} = 1\}$  via the flows of  $Y_h$  is equivalent to the halting problem.

### Spherical embedding

As  $M_h$  is compact and bounded, there is a compact manifold B with smooth boundary such that

- 1.  $M_h \subseteq B \subseteq \mathbb{R}^{d+1}$ .
- 2.  $M_h \cap \partial B = \{x_{d+1} = 1\} \cap M_h = \mathcal{E}_h(\overline{U_1}).$
- 3. There is a diffeomorphism  $\psi : \mathbb{R}^{d+1} \to \mathbb{R}^{d+1}$  such that  $\psi(B) = \overline{\mathbb{D}^{d+1}}$  (the closed unit ball of  $\mathbb{R}^{d+1}$ ).

Then

$$\psi \circ \mathcal{E}_h\left(\overline{U_1}\right) = \mathbb{S}^d \cap \psi\left(M_h\right),$$

so reaching the sphere via the flows of  $\psi_* Y_h$  is equivalent to the halting problem.

### Poincaré radial compactification

Finally, there is a diffeomorphism

$$T: \mathbb{D}^{d+1} \to \mathbb{R}^{d+1}$$
$$x \mapsto \frac{x}{\sqrt{1-|x|^2}}$$

between the open unit ball and the whole space, which leads to the Poincaré radial compactification of  $\mathbb{R}^{d+1}$ , by essentially "mapping" the sphere  $\mathbb{S}^d$  to  $\partial \mathbb{R}^{d+1}$ .

We are done. Given the starting point  $T \circ \psi \circ \mathcal{E}_h(x_{\text{START}}, f_s, 0)$ , the trajectory via the flow of  $(T \circ \psi)_* Y_h$  blows up in finite time if and only if the Turing machine TM halts when given the input tape s. Thus Theorem 1.1 is proven.  $\Box$ 

*Remark* 3.1. Since a universal Turing machine could model a halting Turing machine, there exist initial conditions that lead to finite-time blow-ups. Similarly, there are initial conditions that would not lead to blow-ups. We have essentially geometrically "programmed" a solution towards blow-up.

*Remark* 3.2. In [Tak+17], Poincaré radial compactification was used to regularize ODE blow-ups for rigorous numerical verification. See also [LMT21; LMT23] for similar geometric techniques related to blow-ups. Our construction is flexible and could be further simplified by condensing multiple steps into a single embedding, but the connection to numerical verification and Poincaré radial compactification deserves to be made explicit.

### 4 Open questions

Following [Tao17], it is natural to ask whether we can find a potential well system or a nonlinear wave system where blow-up is undecidable, using geometric methods.

In yet another direction, we look towards other PDEs such as those in fluid mechanics. Instead of encoding the Turing-complete dynamical complexity into the nonlinearity F as in (1.1), we can encode the complexity into the initial velocity field, such as the steady Euler flows constructed in [Car+21; Car+23; CMP22]. See also [Tao18] for a discussion of the universality of non-steady Euler flows on manifolds.

## References

- [AB16] Sanjeev Arora and Boaz Barak. Computational Complexity: A Modern Approach. ISBN: 978-0-521-42426-4. 2016.
- [Car+21] Robert Cardona et al. "Constructing Turing Complete Euler Flows in Dimension 3". Proceedings of the National Academy of Sciences. URL: https://www.pnas.org/doi/abs/10.1073/pnas.2026818118. May 11, 2021.
- [Car+23] Robert Cardona et al. "Universality of Euler Flows and Flexibility of Reeb Embeddings". Advances in Mathematics. URL: https://www. sciencedirect.com/science/article/pii/S0001870823002852. Sept. 1, 2023.
- [CMP22] Robert Cardona, Eva Miranda, and Daniel Peralta-Salas. "Turing Universality of the Incompressible Euler Equations and a Conjecture of Moore". International Mathematics Research Notices. URL: https://doi.org/10.1093/imrn/rnab233. Nov. 22, 2022.
- [GBC08] Daniel S. Graça, Jorge Buescu, and Manuel L. Campagnolo. "Boundedness of the Domain of Definition Is Undecidable for Polynomial ODEs". *Electronic Notes in Theoretical Computer Science*. URL: https: //www.sciencedirect.com/science/article/pii/S1571066108001126. Mar. 21, 2008.
- [GZB09] D.S. Graça, N. Zhong, and J. Buescu. "Computability, Noncomputability and Undecidability of Maximal Intervals of IVPs". Transactions of the American Mathematical Society. URL: https://www. ams.org/tran/2009-361-06/S0002-9947-09-04929-0/. Jan. 22, 2009.
- [LMT21] Jean-Philippe Lessard, Kaname Matsue, and Akitoshi Takayasu. A Geometric Characterization of Unstable Blow-up Solutions with Computer-Assisted Proof. Mar. 23, 2021.
- [LMT23] Jean-Philippe Lessard, Kaname Matsue, and Akitoshi Takayasu. "Saddle-Type Blow-Up Solutions with Computer-Assisted Proofs: Validation and Extraction of Global Nature". Journal of Nonlinear Science. URL: https://doi.org/10.1007/s00332-023-09900-6. Mar. 17, 2023.

- [Moo90] Cristopher Moore. "Unpredictability and Undecidability in Dynamical Systems". *Physical Review Letters*. URL: https://link.aps. org/doi/10.1103/PhysRevLett.64.2354. May 14, 1990.
- [Moo91] C. Moore. "Generalized Shifts: Unpredictability and Undecidability in Dynamical Systems". Nonlinearity. URL: https://dx.doi.org/ 10.1088/0951-7715/4/2/002. May 1991.
- [Tak+17] Akitoshi Takayasu et al. "Numerical Validation of Blow-up Solutions of Ordinary Differential Equations". Journal of Computational and Applied Mathematics. URL: https://www.sciencedirect.com/ science/article/pii/S0377042716305027. Apr. 1, 2017.
- [Tao16] Terence Tao. "Finite Time Blowup for an Averaged Three-Dimensional Navier-Stokes Equation". Journal of the American Mathematical Society. URL: https://www.ams.org/jams/2016-29-03/S0894-0347-2015-00838-4/. 2016.
- [Tao17] Terence Tao. "On the Universality of Potential Well Dynamics". Dynamics of Partial Differential Equations. URL: https://www. intlpress.com/site/pub/pages/journals/items/dpde/content/ vols/0014/0003/a001/abstract.php. Sept. 2017.
- [Tao18] Terence Tao. "On the Universality of the Incompressible Euler Equation on Compact Manifolds". Discrete & Continuous Dynamical Systems - A. URL: https://www.aimsciences.org/article/doi/10. 3934/dcds.2018064. 2018.
- [Tes12] Gerald Teschl. Ordinary Differential Equations and Dynamical Systems. ISBN: 978-0-8218-8328-0. 2012.