Bias-Variance Trade-off in Kalman Filter-Based Disturbance **Observers**

Shilei Li^a, Dawei Shi^a, Xiaoxu Lyu^b, Jiawei Tang^b, Ling Shi^b

^aSchool of Automation, Beijing Institute of Technology, Beijing 100081, China

^bDepartment of Electronic and Computer Engineering, Hong Kong University of Science and Technology, Hong Kong SAR

Abstract

The performance of disturbance observers is strongly influenced by the level of prior knowledge about the disturbance model. The simultaneous input and state estimation (SISE) algorithm is widely recognized for providing unbiased minimum-variance estimates under arbitrary disturbance models. In contrast, the Kalman filter-based disturbance observer (KF-DOB) achieves minimum mean-square error estimation when the disturbance model is fully specified. However, practical scenarios often fall between these extremes, where only partial knowledge of the disturbance model is available. This paper investigates the inherent bias-variance trade-off in KF-DOB when the disturbance model is incomplete. We further show that SISE can be interpreted as a special case of KF-DOB, where the disturbance noise covariance tends to infinity. To address this trade-off, we propose two novel estimators: the multi-kernel correntropy Kalman filter-based disturbance observer (MKCKF-DOB) and the interacting multiple models Kalman filter-based disturbance observer (IMMKF-DOB). Simulations verify the effectiveness of the proposed methods.

Key words: simultaneous input and state estimator, Kalman filter-based disturbance observer, multi-kernel correntropy, interacting multiple models

1 Introduction

Disturbances are pervasive across various domains, including cyber-physical systems [\(Yu et al.,](#page-14-0) [2024\)](#page-14-0), robotics [\(Yan et al.,](#page-14-1) [2023;](#page-14-1) [Kim and Chung,](#page-14-2) [2015;](#page-14-2) [Chen](#page-13-0) [et al.,](#page-13-0) [2015a\)](#page-13-0), and physiological systems [\(De Nicolao](#page-13-1) [et al.,](#page-13-1) [1997\)](#page-13-1). In control systems, disturbances degrade system performance and can even lead to instability [\(Chen et al.,](#page-13-2) [2015b\)](#page-13-2). In estimation systems, disturbances diminish estimation accuracy and may cause filter divergence [\(Perea et al.,](#page-14-3) [2007\)](#page-14-3). Therefore, accurately estimating the disturbance is crucial for a wide range of applications.

A promising approach to estimate disturbance is disturbance observers (DOBs). DOBs can be roughly divided into two categories: frequency domain-based methods and time domain-based methods. The frequency domain-based approach was initially developed

by [Ohishi et al.](#page-14-4) [\(1987\)](#page-14-4) where the inverse of the nominal model $G(s)$ accompanied by a low-pass filter $Q(s)$ was utilized to estimate the disturbance. To improve the convergence rate with periodic disturbances, [Elka](#page-13-3)[yam et al.](#page-13-3) [\(2018\)](#page-13-3) enhanced the conventional frequencydomain disturbance observer by mixing it with a series of multi-resonant terms. The time domain-based DOBs are much more pervasive than the frequencybased approaches, e.g., nonlinear disturbance observer (NDOB) [\(Chen et al.,](#page-13-4) [2000\)](#page-13-4), higher-order NDOB [\(Kim](#page-14-5) [et al.,](#page-14-5) [2010\)](#page-14-5), extended state-observer (ESO) [\(Han,](#page-14-6) [2009\)](#page-14-6), unknown input observer (UIO) [\(Johnson,](#page-14-7) [1970\)](#page-14-7), simultaneous input and state estimation (SISE) [\(Yong](#page-14-8) [et al.,](#page-14-8) [2016;](#page-14-8) [Gillijns and De Moor,](#page-13-5) [2007\)](#page-13-5), Kalman filterbased disturbance observer (KF-DOB) [\(Phuong et al.,](#page-14-9) [2018\)](#page-14-9), to name only a few. [Chen et al.](#page-13-4) [\(2000\)](#page-13-4) designed an NDOB to offset the friction torque in manipulators with guaranteed stability. [Kim et al.](#page-14-5) [\(2010\)](#page-14-5) proposed a generalized form of NDOB by considering higher-order disturbances. Different from NDOB, [Han](#page-14-6) [\(2009\)](#page-14-6) designed ESO by utilizing the relative degree of the system information and estimating the lumped disturbance and state simultaneously. This method is widely used in active disturbance rejection control (ADRC). Opposite to the above estimators that do not require an explicit

Email addresses: shileili@bit.edu.cn (Shilei Li), daweishi@bit.edu.cn (Dawei Shi), eelyuxiaoxu@ust.hk (Xiaoxu Lyu), jtangas@connect.ust.hk (Jiawei Tang), eesling@ust.hk (Ling Shi).

disturbance model, UIO assumes that the disturbance is generated by an exogenous system with a known differential equation. Then, the state and disturbance can be jointly estimated [\(Johnson,](#page-14-7) [1970\)](#page-14-7). It is worth mentioning that NDOB, ESO, and UIO do not consider measurement and process noise explicitly. However, in some applications, the noise cannot be ignored. In such a scenario, KF and its variants are preferable.

The state estimation of linear systems with unknown disturbance (or input) and stochastic measurements has attracted many research efforts since its inception. Initially, [Kitanidis](#page-14-10) [\(1987\)](#page-14-10) formulated an unbiased minimum-variance estimator for robust state estimation under arbitrary disturbances. Afterward, [Darouach and](#page-13-6) [Zasadzinski](#page-13-6) [\(1997\)](#page-13-6) developed an alternative unbiased minimum variance estimator and provided the corre-sponding convergence analysis. Subsequently, [Gillijns](#page-13-5) [and De Moor](#page-13-5) [\(2007\)](#page-13-5) refined the results of [Kitanidis](#page-14-10) [\(1987\)](#page-14-10) and constructed the SISE estimator which provided an unbiased minimum-variance estimation for both the state and disturbance. Recently, [Bitmead et al.](#page-13-7) [\(2019\)](#page-13-7) interpreted SISE as a special KF with a specific disturbance model and [Song and Zheng](#page-14-11) [\(2024\)](#page-14-11) further extended this result to the direct feedthrough case. It is worth noting that although the above estimators are theoretically attractive due to the unbiased minimum variance property, they are rarely utilized in practical control engineering since their outputs usually contain a high uncertainty (in other words, the outputs are noisy). The noisy estimate is destructive to robots' control stability and energy consumption. On the contrary, the result of KF-DOB is much more smooth (although it may be biased) and is favored by many engineers [\(Phuong](#page-14-9) [et al.,](#page-14-9) [2018;](#page-14-9) [Li et al.,](#page-14-12) [2020,](#page-14-12) [2015\)](#page-14-13).

Intuitively, the disturbance estimation is idealistic if the result is both unbiased and smooth. However, in the presence of incomplete disturbance models and stochastic measurements, achieving these two objectives is inherently conflicting. We refer to this effect as disturbance estimation bias-variance dilemma. This phenomenon has been frequently observed by many researchers. For instance, in KF-DOB, reducing the disturbance noise covariance Q_d results in smoother output but compromises tracking speed. Although the trade-off between tracking speed and estimation smoothness is well understood empirically, an in-depth analysis of this trade-off within the KF framework, along with effective countermeasures, remains unexplored, which motivates this work.

This paper uncovers the inherent bias-variance trade-off in KF-DOB and proposes corresponding solutions. First, we demonstrate the existence of this trade-off in KF-DOB under inaccurate disturbance models and stochastic noise. We then establish the equivalence between SISE and KF-DOB when the disturbance noise covariance is infinite, highlighting the critical role of disturbance noise covariance in balancing the bias-variance effect. Note that the primary connection between SISE and KF was built in [Bitmead et al.](#page-13-7) [\(2019\)](#page-13-7). In this work, we extend the result of [Bitmead et al.](#page-13-7) [\(2019\)](#page-13-7) to the scenario of knowing nominal disturbance models, which are extensively utilized in the robotic community [\(Phuong](#page-14-9) [et al.,](#page-14-9) [2018;](#page-14-9) [Li et al.,](#page-14-12) [2020,](#page-14-12) [2015\)](#page-14-13). On this basis, we propose two remedies to mitigate the bias-variance dilemma in KF-DOB, i.e., MKCKF-DOB and IMMKF-DOB. The main contributions of this work are outlined as follows.

- We establish the existence of a bias-variance tradeoff in KF-DOB, as formalized in Theorem 3. Additionally, we prove that KF-DOB is equivalent to SISE when the disturbance noise covariance tends to infinity, as demonstrated in Theorem 5 and Corollary 3.
- We develop two remedies to alleviate the biasvariance trade-off in KF-DOB, i.e., MKCKF-DOB and IMMKF-DOB in Algorithms 1 and 2 .
- The bias-variance effects of different estimator are visualized in simulations. The results confirm that the proposed methods offer superior performance compared to existing estimators.

The remainder of this paper is arranged as follows. In Section II, we provide some preliminaries. In Section III, we demonstrate the intrinsic trade-off in KF-DOB. In Section IV, we prove that KF-DOB is identical to SISE when applying infinite disturbance noise covariance and develop two remedies. In Section V, we give some simulations to validate the proposed approaches. In Section VI, we draw a conclusion.

Notations: The transpose of a matrix A is denoted by A^T . The symbol $X \succ 0$ $(X \succ 0)$ denotes X is a positive definite (semi-positive definite) matrix. The Gaussian distribution with mean μ and covariance Σ is denoted by $\mathcal{N}(\mu, \Sigma)$. The expectation of a random variable X is denoted by $E(X)$. The notation $A \to \infty$ denotes that all eigenvalues of A tend to infinity, which implies that $A^{-1} \to 0$. The symbol $||x||_A^2$ denotes $x^T A x$.

2 Preliminaries

We begin by revisiting the SISE estimator and KF-DOB. Next, we present the multi-kernel correntropy Kalman filter (MKCKF) and the interacting multiple model Kalman filter (IMMKF). Finally, we summarize the distinct characteristics of each estimator and provide a problem description

2.1 SISE Algorithm

We consider the following linear system:

$$
x_k = F_k x_{k-1} + G_k d_{k-1} + w_k \n y_k = H_k x_k + v_k
$$
\n(1)

where $x_k \in \mathbb{R}^n$ is the state, $y_k \in \mathbb{R}^m$ is the measurements, $d_k \in \mathbb{R}^p$ is the unknown input, $w_k \sim \mathcal{N}(0, Q_k)$, and $v_k \sim \mathcal{N}(0, R_k)$. The SISE algorithm [\(Gillijns and](#page-13-5) [De Moor,](#page-13-5) [2007\)](#page-13-5) is summarized as follows:

1) time update

$$
x_{k|k-1} = F_k x_{k-1|k-1}
$$

\n
$$
P_{k|k-1} = F_k P_{k-1|k-1} F_k^T + Q_k.
$$
\n(2)

2) unknown input estimation

$$
\tilde{R}_k = H_k P_{k|k-1} H_k^T + R_k
$$
\n
$$
M_k^* = \left(G_k^T H_k^T \tilde{R}_k^{-1} H_k G_k \right)^{-1} G_k^T H_k^T \tilde{R}_k^{-1} \qquad (3)
$$
\n
$$
d_{k-1} = M_k^* \left(y_k - H_k x_{k|k-1} \right).
$$

3) measurement update

$$
x_{k|k}^{*} = x_{k|k-1} + G_{k}d_{k-1}
$$

\n
$$
K_{k}^{*} = P_{k|k-1}H_{k}^{T}\tilde{R}_{k}^{-1}
$$

\n
$$
\hat{x}_{k|k} = x_{k|k}^{*} + K_{k}^{*} (y_{k} - H_{k}x_{k|k}^{*})
$$

\n
$$
P_{k|k} = (I - K_{k}^{*}H_{k}) [(I - G_{k}M_{k}H_{k}) P_{k|k-1} (I - G_{k}M_{k}H_{k})^{T}
$$

\n
$$
+ G_{k}M_{k}R_{k}M_{k}^{T}G_{k}^{T}] + K_{k}^{*}R_{k}M_{k}^{T}G_{k}^{T}
$$

\n
$$
P_{k|k}^{dd} = (G_{k}^{T}H_{k}^{T}\tilde{R}_{k}^{-1}H_{k}G_{k})^{-1}
$$
\n(4)

Lemma 1 [\(Gillijns and De Moor,](#page-13-5) [2007\)](#page-13-5) $M_k^* H_k G_k = I_p$ where I_p is an identity matrix of dimension p.

Lemma 2 [\(Gillijns and De Moor,](#page-13-5) [2007\)](#page-13-5) SISE algorithm is an unbiased minimum variance estimator under arbitrary disturbance signals.

2.2 Kalman Filter-Based Disturbance Observer

In many practical applications, one can augment the disturbance as a new state and construct the KF-DOB as follows:

$$
x_k = \Phi_k x_{k-1} + w_k
$$

\n
$$
y_k = H_k x_k + v_k
$$
\n(5)

where

$$
\mathbf{x}_k = \begin{bmatrix} d_k \\ x_k \end{bmatrix}, \Phi_k = \begin{bmatrix} I & 0 \\ G_k & F_k \end{bmatrix}, \mathbf{H}_k = \begin{bmatrix} 0 & H_k \end{bmatrix}, \mathbf{y}_k = y_k.
$$

Moreover, the augmented process noise is assumed to follow $\mathbf{w}_k \triangleq [w_{d,k}^T, w_{x,k}^T]^T \sim \mathcal{N}(0, \mathbf{Q}_k)$ and $\mathbf{v}_k \triangleq v_k \sim$ $\mathcal{N}(0, R_k)$. Correspondingly, the KF-DOB can be executed as

$$
\hat{\mathbf{x}}_{k|k-1} = \Phi_k \hat{\mathbf{x}}_{k-1|k-1} \n\hat{\mathbf{x}}_{k|k} = \hat{\mathbf{x}}_{k|k-1} + \mathbf{K}_k (\mathbf{y}_k - \mathbf{H}_k \mathbf{x}_{k|k-1}) \n= (\mathbf{I} - \mathbf{K}_k \mathbf{H}_k) \Phi_k \hat{\mathbf{x}}_{k-1|k-1} + \mathbf{K}_k \mathbf{y}_k \n\mathbf{P}_{k|k-1} = \Phi_k \mathbf{P}_{k-1|k-1} \Phi_k^T + \mathbf{Q}_k \n\mathbf{K}_k = \mathbf{P}_{k|k-1} \mathbf{H}_k^T (\mathbf{H}_k \mathbf{P}_{k|k-1} \mathbf{H}_k^T + \mathbf{R}_k)^{-1} \n\mathbf{P}_{k|k} = (\mathbf{I} - \mathbf{K}_k \mathbf{H}_k) \mathbf{P}_{k|k-1} (\mathbf{I} - \mathbf{K}_k \mathbf{H}_k)^T + \mathbf{K}_k \mathbf{R}_k \mathbf{K}_k^T.
$$
\n(6)

The information form posterior error covariance update [\(Zhao and Huang,](#page-14-14) [2020\)](#page-14-14) has

$$
P_{k|k}^{-1} = P_{k|k-1}^{-1} + H_k^T R_k^{-1} H_k.
$$
 (7)

Note that the difference between the SISE and KF-DOB is that a nominal dynamic model $d_k = d_{k-1} + w_{d,k}$ is utilized in KF-DOB, but is avoided in SISE. It is worth mentioning that although we use the constant disturbance model in this paper for ease of analysis, it can be replaced by other models that reflect our prior knowledge of the disturbance.

2.3 Multi-kernel Correntropy Kalman filter

The MKC [\(Li et al.,](#page-14-15) [2021,](#page-14-15) [2023\)](#page-14-16) is a similarity measure of two random vectors $\mathscr{X}, \mathscr{Y} \in \mathbb{R}^l$:

$$
V(\mathcal{X}, \mathcal{Y}) = \sum_{i=1}^{l} \sigma_i^2 E[\kappa_{\sigma_i}(\mathcal{X}_i, \mathcal{Y}_i)]
$$
 (8)

where $E[\kappa_{\sigma_i}(\mathscr{X}_i, \mathscr{Y}_i)] = \int \kappa_{\sigma_i}(x_i, y_i) dF_{\mathscr{X}_i \mathscr{Y}_i}(x_i, y_i),$ $\kappa_{\sigma_i}(x_i, y_i) = G_{\sigma_i}(x_i, y_i) = \exp(-\frac{e_i^2}{2\sigma_i^2}), \sigma_i$ is the kernel bandwidth, $e_i = x_i - y_i$ is the realization error, and $F_{\mathscr{X}_i \mathscr{Y}_i}(\cdot, \cdot)$ is the joint distribution. In some applications, only finite samples x_k and y_k can be obtained. Then, MKC can be estimated as

$$
\hat{V}(\mathcal{X}, \mathcal{Y}) = \sum_{i=1}^{l} \sigma_i^2 \hat{V}_i(\mathcal{X}_i, \mathcal{Y}_i)
$$
(9)

where $\hat{V}_i(\mathscr{X}_i, \mathscr{Y}_i) = \frac{1}{N} \sum_{k=1}^N G_{\sigma_i}(x_{i,k}, y_{i,k})$ and $x_{i,k}$ and $y_{i,k}$ denote *i*-th elements of x_k and y_k . The MKC loss (MKCL) is defined as

$$
J_{MKCL} = \sum_{i=1}^{l} \sigma_i^2 (1 - \hat{V}_i) = \frac{1}{N} \sum_{k=1}^{N} \sum_{i=1}^{l} \sigma_i^2 \left(1 - G_{\sigma_i}(e_{i,k}) \right)
$$
\n(10)

where $e_k = [e_{1,k}, e_{2,k}, \dots, e_{l,k}]^T$ and $e_{i,k} = x_{i,k} - y_{i,k}$. By replacing the MSE loss with MKCL, one can derive the MKCKF which is robust to heavy-tailed process or measurement noises. Readers can refer to [\(Li et al.,](#page-14-15) [2021,](#page-14-15) [2023\)](#page-14-16) for details.

2.4 Interacting Multiple Models Kalman Filter

We consider a state estimation problem with q Markov jump linear models. For model j ($j = 1, 2, \ldots, q$), we have

$$
x_k = A_j x_{k-1} + w_{j,k}
$$

\n
$$
y_k = C_j x_k + v_{j,k}
$$
\n(11)

where $x_k \in \mathbb{R}^n$ is the state, $y_k \in \mathbb{R}^m$ is the measurement, and $w_{j,k}$ and $v_{j,k}$ are Gaussian noises for j-th model with covariance matrices Q_j and R_j , respectively. The Markov transition probability matrix has $\mathcal{P} = [\mathcal{P}_{i,j}]$ where $\mathcal{P}_{i,j}$ is the transition probability from model i to model j . Then, the IMM-KF can be summarized as follows [\(Fan et al.,](#page-13-8) [2021\)](#page-13-8):

Table 1 Characteristics of different estimators.

Estimators	Noise assumption	Features		
SISE	Gaussian	unbiased minimum variance estimator under <i>arbitrary disturbance models</i>		
KF-DOB	Gaussian	optimal under <i>accurate disturbance models</i>		
MKCKF	heavy-tailed	robust to heavy-tailed noise		
IMMKF	Gaussian	capable of handling Markov jump systems		

1) Input interaction: obtain the transition probability from model i to model j at time step $k - 1$:

$$
\mu_{ij,k-1|k-1} = \mathcal{P}_{ij}\mu_{i,k-1}/\bar{c}_j \tag{12}
$$

where $\mu_{i,k-1}$ is the probability for model i obtained at time step $k-1$ and $\bar{c}_j = \sum_{i=1}^q \mathcal{P}_{ij} \mu_{i,k-1}$.

2) Obtain the initial state and covariance estimate of model j:

$$
\hat{x}_{j,k-1|k-1}^{init} = \sum_{i=1}^{q} \hat{x}_{i,k-1|k-1} \mu_{ij,k-1|k-1}
$$
\n
$$
P_{j,k-1|k-1}^{init} = \sum_{i=1}^{q} \mu_{ij,k-1|k-1} \left(P_{i,k-1|k-1} + \left(\hat{x}_{i,k-1|k-1} - \hat{x}_{i,k-1|k-1}^{init} \right) \right)
$$
\n
$$
- \hat{x}_{i,k-1|k-1}^{init} \left(\hat{x}_{i,k-1|k-1} - \hat{x}_{i,k-1|k-1}^{init} \right)^{T} \right).
$$
\n(13)

3) State and covariance estimation for model j :

$$
\hat{x}_{j,k|k} = \hat{x}_{j,k|k-1} + K_{j,k}e_{j,k}
$$
\n
$$
P_{j,k|k} = (I - K_{j,k}C_j)P_{j,k|k-1}
$$
\n(14)

with

$$
\begin{cases}\n\hat{x}_{j,k|k-1} = A_j \hat{x}_{j,k-1|k-1}^{init} \\
P_{j,k|k-1} = A_j P_{j,k-1|k-1}^{init} A_j^T + Q_j \\
e_{j,k} = y_k - A_j \hat{x}_{k|k-1} \\
S_{j,k} = C_j P_{j,k|k-1} C_j^T + R_j \\
K_{j,k} = P_{j,k|k-1} C_j^T S_{j,k}^{-1}\n\end{cases} (15)
$$

4) Update the model probability for model j:

$$
\mu_{j,k} = \frac{\Lambda_{j,k}\bar{c}_j}{c} \tag{16}
$$

where
$$
\Lambda_{j,k} = \frac{1}{\sqrt{2\pi|S_{j,k}|}} \exp\left(-\frac{1}{2}e_{j,k}^T S_{j,k}^{-1} e_{j,k}\right)
$$
 and $c = \sum_{j=1}^q \Lambda_{j,k} \bar{c}_j$.

5) State and error covariance interaction:

$$
\hat{x}_{k|k} = \sum_{j=1}^{q} \mu_{j,k} \hat{x}_{j,k|k}
$$
\n
$$
P_{k|k} = \sum_{j=1}^{q} \mu_{j,k} \left(P_{j,k|k} + (\hat{x}_{j,k|k} - \hat{x}_{k|k}) (\hat{x}_{j,k|k} - \hat{x}_{k|k})^T \right).
$$
\n(17)

2.5 Problem Description

We summarize the characteristics of the above four estimators in Table 1. We find that SISE is unbiased under arbitrary disturbance models and KF-DOB is optimal under accurate disturbance models. In many practical applications, we only have an inaccurate disturbance model. In such cases, SISE is under-confident since it ignores the disturbance model, and KF-DOB is overconfident since it regards the disturbance model as an accurate one. Since unmodeled disturbance dynamics can be regarded as heavy-tailed noise [\(Li et al.,](#page-14-16) [2023\)](#page-14-16) and a linear combination of multiple models can better approximate inaccurate disturbance models, MKCKF and IMMKF have the potential of outperforming SISE and KF-DOB in terms of disturbance estimation.

In this paper, we answer the following questions: What is the role of the disturbance model in simultaneous state and disturbance estimation? Can we build a connection between KF-DOB and SISE? How can we provide a better estimator when the disturbance model is inaccurate? The answers would facilitate our understanding of state estimation with inaccurate disturbance models and guide the practical usage of disturbance observers.

3 Bias-Variance Trade-off in KF-DOB

This section investigates the fundamental trade-off between the disturbance tracking speed and estimation variance in KF-DOB.

3.1 Bias-Variance Trade-off with Incorrect Initialization in KF

Directly investigating the bias-variance effect in KF-DOB is difficult. To simplify the problem, we initially investigate the effects of the process covariance selection with an improper initial guess in KF, which would pave the way for the subsequent analysis.

3.1.1 Effects of ∆Q on Convergence Speed

We consider the linear time-invariant system as shown in (5). By denoting the used process covariance Q_k^u as

$$
Q_k^u = Q_k + \Delta Q \tag{18}
$$

where Q_k denotes the real process noise covariance and ΔQ is the covariance mismatch. Subsequently, we instigate the effects of ΔQ on the convergence speed and estimation accuracy with incorrect initial guess in KF.

By aggregating the state and measurement from time step 1 to k as $X_{1,k} = [x_1^T, x_2^T, \cdots, x_k^T]^T$ and $Y_{1,k} =$

 $[y_1^T, y_2^T, \cdots, y_k^T]^T$, the extended state-space model of (5) has

$$
X_{1,k} = \Phi_{1,k}X_0 + G_{1,k}W_{1,k}
$$

\n
$$
Y_{1,k} = H_{1,k}X_0 + D_{1,k}W_{1,k} + V_{1,k}
$$
\n(19)

where x_0 denotes the initial state, $W_{1,k} = [w_1^T, \ldots, w_k^T]^T$, $V_{1,k} = [v_1^T, \dots, v_k^T]^T$, and

$$
\Phi_{1,k} = [\Phi_1^T, (\Phi_2 \Phi_1)^T, \dots, (\phi_{k-1}^1)^T, (\phi_k^1)^T]^T
$$

$$
G_{1,k} = \begin{bmatrix} I & 0 & \cdots & 0 & 0 \\ \Phi_2 & I & \cdots & 0 & 0 \\ \vdots & \vdots & \ddots & \vdots & \vdots \\ \phi_{k-1}^2 & \phi_{k-1}^3 & \cdots & I & 0 \\ \phi_k^2 & \phi_k^3 & \cdots & \Phi_k & I \end{bmatrix}
$$

$$
H_{1,k} = \bar{H}_{1,k} \Phi_{1,k}
$$

where $\phi_j^i = \Phi_i \Phi_{i+1} \dots \Phi_j$ with $i < j$, $\bar{H}_{1,k}$ = diag(H_1, H_2, \ldots, H_k), and $D_{1,k} = \overline{H}_{1,k} G_{1,k}$. According to (19), we can specify x_k as the last row vector $X_{1,k}$:

$$
\mathbf{x}_k = \phi_k^1 \mathbf{x}_0 + \mathbf{G}_{1,k}^{rk} \mathbf{W}_{1,k} \tag{20}
$$

where $G_{1,k}^{rk}$ denote k-th row of $G_{1,k}$.

Given the initial value x_0 and the measurement set $Y_{1,k}$, the batch Kalman estimate appears in the convolution-based form [\(Barfoot,](#page-13-9) [2024\)](#page-13-9) at time step k as

$$
\hat{x}_k = \mathcal{H}_{1,k}^h Y_{1,k} + \mathcal{H}_{1,k}^s x_0 \tag{21}
$$

where gains $\mathcal{H}_{1,k}^h$ and $\mathcal{H}_{1,k}^s$ minimize the MSE for inputs $Y_{1,k}$ and x_0 . According to the unbiasedness constraint and orthogonality principle between the state estimate and the measurement set, one obtains

 $\hat{x}_k = \hat{x}_k^h + \hat{x}_k^s = \mathcal{H}_{1,k}^h Y_{1,k} + (\phi_k^1 - \mathcal{H}_{1,k}^h H_{1,k}) x_0$ (22) where

 $\mathcal{H}_{1,k}^{h} = \mathrm{G}_{1,k}^{rk} \mathrm{Q}_{1,k} \mathrm{D}_{1,k}^{T} (\mathrm{D}_{1,k} \mathrm{Q}_{1,k} \mathrm{D}_{1,k}^{T} + \mathrm{R}_{1,k})^{-1}$. (23) The detailed derivation is in Appendix 7.1. Since both (21) and the KF in (6) are optimal in the minimum mean squared error sense, we have the following lemma.

Lemma 3 [\(Zhao and Huang,](#page-14-14) [2020\)](#page-14-14) Given system dynamics as shown in (5) with exactly known initial value x_0 (i.e., the uncertainty about x_0 is zero), the optimal state estimate x_k at time instant k can be obtained either by recursively running conventional KF with $\hat{x}_0 = x_0$ and $P_0 = 0$ given in (6), or by the batch estimator specified in (22).

According to (22), one can decompose \hat{x}_k as response to measurement $\hat{\mathbf{x}}_k^h$ and response to initial value $\hat{\mathbf{x}}_k^s$. Considering Lemma 3, we have the following proposition.

Proposition 1 The response to measurements \hat{x}_k^h has

$$
\hat{\mathbf{x}}_k^h = (\mathbf{I} - \mathbf{K}_k \mathbf{H}_k) \Phi_k \hat{\mathbf{x}}_{k-1}^h + \mathbf{K}_k \mathbf{y}_k \tag{24}
$$

with initial value $\hat{x}_0^h = 0$ and $P_0 = 0$, and K_k is the Kalman gain. Furthermore, the response to initial value $\hat{\mathbf{x}}_k^s$ has

$$
\hat{\mathbf{x}}_k^s = (\mathbf{I} - \mathbf{K}_k \mathbf{H}_k) \Phi_k \hat{\mathbf{x}}_{k-1}^s
$$
\n
$$
a \text{ from } \hat{\mathbf{x}}_k^s = \mathbf{x}_0
$$
\n(25)

starting from $\hat{\mathbf{x}}_0^s = \mathbf{x}_0$.

The proof is available in Appendix 7.2.

Corollary 1 Denote $\bar{\Phi}_k \triangleq (I - K_k H_k) \Phi_k$ which is inferred as the one-step predictor. If KF is stable, all eigenvalues of $\bar{\Phi}_k$ are strictly within the unit circle. Consequently,

$$
\lim_{k \to \infty} \hat{\mathbf{x}}_k^s = 0 \tag{26}
$$

meaning that the response of the Kalman estimates to x_0 decreases to zero gradually where the convergence speed is governed by $\bar{\Phi}_k$.

We then consider a much more general case, i.e., x_0 is not exactly known but follows $\mathcal{N}(\bar{x}_0, \bar{P}_0)$. In this scenario, the batch estimator (21) is modified as

$$
\hat{x}_k = \bar{\mathcal{H}}_{1,k}^h Y_{1,k} + \bar{\mathcal{H}}_{1,k}^s \bar{x}_0 \tag{27}
$$

where $\bar{\mathcal{H}}_{1,k}^h$ and $\bar{\mathcal{H}}_{1,k}^s$ are gains to be determined. According to the unbiasedness constraint and orthogonal principle, by analogy with the obtainment of (22), one has

$$
\hat{\mathbf{x}}_k = \hat{\mathbf{x}}_k^{\bar{h}} + \hat{\mathbf{x}}_k^{\bar{s}} = \bar{\mathcal{H}}_{1,k}^h \mathbf{Y}_{1,k} + (\phi_k^1 - \bar{\mathcal{H}}_{1,k}^h \mathbf{H}_{1,k}) \bar{\mathbf{x}}_0 \tag{28}
$$

where

$$
\bar{\mathcal{H}}_{1,k}^{h} = (\phi_k^1 \mathbf{P}_0 \mathbf{H}_{1,k}^T + \mathbf{G}_{1,k}^{rk} \mathbf{Q}_{1,k} \mathbf{D}_{1,k}^T) (\mathbf{H}_{1,k} \mathbf{P}_0 \mathbf{H}_{1,k}^T + \mathbf{D}_{1,k} \mathbf{Q}_{1,k} \mathbf{D}_{1,k}^T + \mathbf{R}_{1,k})^{-1}.
$$
\n(29)

The derivation is available in Appendix 7.3.

Lemma 4 [\(Zhao and Huang,](#page-14-14) [2020\)](#page-14-14) Given a linear Gaussian state-space model (5) with known initial distribution $\mathcal{N}(\bar{x}_0, P_0)$, the optimal state estimate x_k at time instant k can be obtained either by recursively running conventional KF with $\hat{x}_0 = \bar{x}_0$ and $P_{0|0} = P_0$ as shown in (6) , or through the batch estimator specified in (28) .

Proposition 2 The response to measurements $\hat{\mathrm{x}}_k^{\bar{k}}$ has $\hat{x}_{k}^{\bar{h}} = (I - K_{k}H_{k})\Phi_{k}\hat{x}_{k-1}^{\bar{h}} + K_{k}y_{k}$ (30) with initial value $\hat{x}_0^{\bar{h}} = 0$ and $P_{0|0} = P_0$. The symbol K_k

is the Kalman gain. The response to initial value $\hat{\mathbf{x}}_k^{\bar{\mathbf{s}}}$ has $\hat{\mathbf{x}}_k^{\bar{s}} = (\mathbf{I} - \mathbf{K}_k \mathbf{H}_k) \Phi_k \hat{\mathbf{x}}_{k-1}^{\bar{s}}$ (31)

starting from $\hat{\mathbf{x}}_0^s = \bar{\mathbf{x}}_0$.

The proof of this proposition is similar to that of Proposition 1 and hence is omitted.

Corollary 2 If KF is stable, one has

$$
\lim_{k \to \infty} \hat{\mathbf{x}}_k^{\bar{s}} = \prod_{i=1}^k \bar{\Phi}_k \bar{\mathbf{x}}_0^{\bar{s}} = 0
$$
\n(32)

where $\bar{\Phi}_k = (\mathbf{I} - \mathbf{K}_k \mathbf{H}_k) \Phi_k$ and $\bar{\mathbf{x}}_0^{\bar{s}} = \bar{\mathbf{x}}_0$.

In the case that an incorrect initial mean $\bar{\mathbf{x}}^u_0$ is used (with correct P_0 , according to (31) , the corresponding response to initial value has $\hat{x}_k^{\bar{s}_u} = \overline{\Phi}_k \hat{x}_{k-1}^{\bar{s}_u}$ with $\hat{x}_0^{\bar{s}_u} =$ \bar{x}_0^u . Subsequently, the estimation bias can be quantified by

$$
\hat{\mathbf{x}}_k^b = \bar{\Phi}_k \hat{\mathbf{x}}_{k-1}^b.
$$
\n(33)

where $\hat{x}_k^b = \hat{x}_k^{\bar{s}} - \hat{x}_k^{\bar{s}_u}$ and $\bar{x}_0^b = \bar{x}_0 - \bar{x}_0^u$.

Remark 1 Proposition 2 allows us to investigate the estimation bias and estimation uncertainty (i.e., variance) by analyzing (33) and (30) separately. It is worth mentioning the incorrect initial value can be generalized to the state estimation with sudden state jumps, which can be found in many applications, e.g., target tracking with impulsive disturbances, position tracking of robots with suddenly added loads, etc.

Lemma 5 For the Kalman filter shown in (6) , by denoting $M_k = I - K_k H_k$, one has

$$
M_k = (I + P_{k|k-1}H_k^T R_k^{-1}H_k)^{-1}.
$$
 (34)

The proof of this lemma is available in Appendix 7.4.

We formulate the following convergence performance measure

$$
C_{\gamma,k} = \|\hat{\mathbf{x}}_k^b\|_2^2 = (\hat{\mathbf{x}}_{k-1}^b)^T \bar{\Phi}_k^T \bar{\Phi}_k \hat{\mathbf{x}}_{k-1}^b
$$

= $(\hat{\mathbf{x}}_{k-1}^b)^T \Phi_k^T \mathbf{M}_k^T \mathbf{M}_k \Phi_k \hat{\mathbf{x}}_{k-1}^b.$ (35)

To investigate effects of ΔQ on $C_{\gamma,k}$, we denote $C_{\gamma,k}^o$ and $C_{\gamma,k}^u$ as the results of applying Q_k and Q_k^u . Furthermore, we denote

$$
P_{k|k-1}^o = \Phi_k P_{k-1|k-1}^o \Phi_k^T + Q_k
$$

$$
P_{k|k-1}^u = \Phi_k P_{k-1|k-1}^u \Phi_k^T + Q_k^u
$$

and define

$$
X_k \triangleq I + P_{k|k-1}^o H_k^T R_k^{-1} H_k,
$$

\n
$$
Y_k \triangleq \left(P_{k|k-1}^u - P_{k|k-1}^o \right) H_k^T R_k^{-1} H_k.
$$
\n(36)

Assumption 1 We assume that $X_k Y_k^T + Y_k X_k^T +$ $Y_k Y_k^T \succeq 0$ for any $\Delta Q \succeq Q_{\epsilon+} \succeq 0$ where $Q_{\epsilon+}$ is a certain positive semi-definite (PSD) matrix . Moreover, $X_k Y_k^T + Y_k X_k^T + Y_k Y_k^T \preceq 0$ for any $\Delta Q \prec Q_{\epsilon-} \prec 0$ where $Q_{\epsilon-}$ is a certain negative semi-definite (NSD) matrix.

Note that certain $Q_{\epsilon+}$ and $Q_{\epsilon-}$ always exist of fulfilling Assumption 1. Then, we have the following theorem.

Theorem 1 Under Assumption 1, if $\Delta Q \succeq Q_{\epsilon+}$, $C_{\gamma,k}^o \geq C_{\gamma,k}^u$. Otherwise if $\Delta Q \preceq Q_{\epsilon-}, \ C_{\gamma,k}^o \leq C_{\gamma,k}^u$.

The proof is available in Appendix 7.5.

Remark 2 Theorem 1 indicates that the convergence of improper initial guess would be accelerated when applying

 $\Delta Q \succeq Q_{\epsilon+}$ and decelerated when applying $\Delta Q \preceq Q_{\epsilon-}$ (under the premise that KF is stable).

To tighten the bounds $Q_{\epsilon+}$ and $Q_{\epsilon-}$, we make the following assumption.

Assumption 2 The terms X_k and Y_k in (36) are symmetric.

Remark 3 Note that this assumption is not very restrictive since in many applications, e.g., target tracking [\(Zhu](#page-14-17) [et al.,](#page-14-17) [2021;](#page-14-17) [Chen et al.,](#page-13-10) [2017\)](#page-13-10), X_k and Y_k are approximately symmetric.

Proposition 3 Under Assumption 2, $Q_{\epsilon+}$ and $Q_{\epsilon-}$ in Theorem 1 will degenerate to zero matrices, i.e., $Q_{\epsilon+} =$ $Q_{\epsilon-} = 0$. In this scenario, if $\Delta Q \succeq 0$, $C_{\gamma,k}^o \geq C_{\gamma,k}^u$. Otherwise if $\Delta Q \preceq 0$, $C^o_{\gamma,k} \leq C^u_{\gamma,k}$.

The proof is available at Appendix 7.6.

Proposition 4 (Infinite Convergence Rate) In the case that the eigenvalues of ΔQ tends to infinity, i.e., $\Delta Q \rightarrow \infty$ and $\tilde{H}_k^T R_k^{-1} H_k$ is a positive definite (PD) matrix, \hat{x}_k^b converges to zero with infinite convergence rate, *i.e.*, $\hat{\mathbf{x}}_1^b = 0$ for arbitrary \bar{x}_0^b .

The proof is available in Appendix 7.7.

3.1.2 Effects of ∆Q on Steady-state Error Covariance

we investigate effects of ∆Q on the steady-state error covariance in KF by analyzing the relations of the following three performance indices: ideal error covariance $P_{k|k}$, filter calculated error covariance $P_{k|k}^f$, and true error covariance $P_{k|k}^t$. Note that $P_{k|k}^f$ does not provide a true measure of estimation accuracy when $\Delta Q \neq 0$.

Assumption 3 We assume that $P_{k-1|k-1} = P_{k-1|k-1}^f =$ $P_{k-1|k-1}^t$ at time step $k-1$.

The above assumption follows [Ge et al.](#page-13-11) [\(2016\)](#page-13-11). Accordingly, $P_{k|k}$ can be obtained by the ideal KF as shown in (6). Under Assumption 3, $P_{k|k}^f$ can be calculated by

$$
\hat{\mathbf{x}}_{k|k}^{f} = \hat{\mathbf{x}}_{k|k-1}^{f} + \mathbf{K}_{k}^{f}(\mathbf{y}_{k} - \mathbf{H}_{k}\hat{\mathbf{x}}_{k|k-1}^{f})
$$
\n
$$
\mathbf{P}_{k|k}^{f} = (\mathbf{I} - \mathbf{K}_{k}\mathbf{H}_{k})\mathbf{P}_{k|k-1}^{f}(\mathbf{I} - \mathbf{K}_{k}\mathbf{H}_{k})^{T} + \mathbf{K}_{k}^{f}\mathbf{R}_{k}(\mathbf{K}_{k}^{f})^{T}
$$
\n
$$
\hat{\mathbf{x}}_{k|k-1}^{f} = \Phi_{k}\hat{\mathbf{x}}_{k-1|k-1}
$$
\n
$$
\mathbf{P}_{k|k-1}^{f} = \Phi_{k}\mathbf{P}_{k-1|k-1}\Phi_{k}^{T} + \mathbf{Q}_{k}^{u}
$$
\n
$$
\mathbf{K}_{k}^{f} = \mathbf{P}_{k|k-1}^{f}\mathbf{H}_{k}^{T}(\mathbf{H}_{k}\mathbf{P}_{k|k-1}^{f}\mathbf{H}_{k}^{T} + \mathbf{R}_{k})^{-1}.
$$
\n(37)

The information form of $P_{k|k}^f$ has

$$
(\mathbf{P}_{k|k}^f)^{-1} = (\mathbf{P}_{k|k-1}^f)^{-1} + \mathbf{H}_k^T \mathbf{R}_k^{-1} \mathbf{H}_k. \tag{38}
$$

Note that $P_{k|k}^f$ does not provide a true measure of the estimation accuracy at time step k . Since

$$
\tilde{\mathbf{x}}_{k|k}^f = \mathbf{x}_k - \hat{\mathbf{x}}_{k|k}^f
$$

= $(\mathbf{I} - \mathbf{K}_k^f \mathbf{H}_k) \Phi_k \tilde{\mathbf{x}}_{k-1|k-1} + (\mathbf{I} - \mathbf{K}_k^f \mathbf{H}_k) \mathbf{w}_k - \mathbf{K}_k^f \mathbf{v}_k,$

it follows that the true error covariance $P_{k|k}^t = cov(\tilde{x}_{k|k}^f)$ has

$$
P_{k|k}^{t} = (I - K_k^f H_k) P_{k|k-1} (I - K_k^f H_k)^T + K_k^f R_k K_k^T.
$$
 (39)
Then we have the following theorem

Then, we have the following theorem.

Lemma 6 [\(Ge et al.,](#page-13-11) [2016\)](#page-13-11) Under Assumption 3, if $\Delta Q \geq 0, P_{k|k}^f \geq P_{k|k} \geq P_{k|k}$. Otherwise, if $-Q_k \preceq$ $\Delta \mathrm{Q} \preceq 0, \mathrm{P}^t_{k|k} \succeq \mathrm{P}_{k|k} \succeq \mathrm{P}^f_{k}$ $_{k|k}^{\scriptscriptstyle J}$.

Remark 4 Lemma 6 reveals that the true error covariance is always bigger than the ideal error covariance $P_{k|k}$ as long as $\Delta Q \neq 0$.

Theorem 2 Under Assumption 3, if $0 \leq \Delta Q_1 \leq \Delta Q_2$, one has $P_{k|k} \preceq P_{k|k}^{f_1} \preceq P_{k|l}^{f_2}$ one has $P_{k|k} \preceq P_{k|k}^{f1} \preceq P_{k|k}^{f2}$ and $P_{k|k} \preceq P_{k|k}^{t1} \preceq P_{k|k}^{t2}$
where superscripts 1 and 2 denote corresponding results of applying ΔQ_1 and ΔQ_2 . On the contrary, if $0 \succeq$ $\Delta Q_1 \succeq \Delta Q_2 \succeq -Q_k$, one has $P_{k|k} \succeq P_{k|k}^{f2} \succeq P_{k|k}^{f2}$ $\frac{J^2}{k|k|}$ and $\mathrm{P}_{k|k} \preceq \mathrm{P}^{t1}_{k|k} \preceq \mathrm{P}^{t2}_{k|k}.$

The proof is available in Appendix 7.8.

Remark 5 According to Theorems 1 and 2, one observes that the two targets, bias convergence rate and ground truth error covariance, are conflicting. A bigger process covariance would lead to a faster bias convergence speed, at the cost of enlarged steady-state error covariance.

3.2 Bias-Variance Trade-off in KF-DOB

As indicated in Remark 1, the incorrect initial guess in KF can be generalized to intermittent state jump in KF-DOB under step-like disturbance (note that the disturbance itself is a state in KF-DOB). Before proceeding, we give the following assumptions.

Assumption 4 The disturbance in (5) is the summation of a step signal plus a white noise term, i.e.,

$$
d_k = \mathbf{1} \sum_{i=0}^{n} \alpha_i \chi_{A_i}(k) + w_{d,k} \tag{40}
$$

.

where 1 denotes a vector with elements 1 of proper dimension, $w_{d,k} \sim \mathcal{N}(0, Q_d)$, α_i are real numbers, A_i are intervals with $A_i \cap A_j = \emptyset$ and $\bigcup_{i=0}^n A_i = \mathbb{R}, \chi_{A_i}(k)$ is a indicator function of k:

$$
\chi_{A_i}(k) = \begin{cases} 1, & \text{if } k \in A_i \\ 0, & \text{if } k \notin A_i \end{cases}
$$

Assumption 5 The KF-DOB convergences to its steady state before the next disturbance jump comes.

Remark 6 As one can see, the problem KF-DOB with step-like disturbance is identical to the problem of KF with incorrect initial mean, except for the state jump happening intermittently in KF-DOB but only happening at $k = 0$ for KF with improper initial mean.

We assume that there is no cross-correlation between the state and disturbance, i.e., $Q_k = diag(Q_d, Q_x)$ for (5). Since the state jump only occurs on the disturbance part, we use the following process covariance

$$
Q_k^u = \begin{bmatrix} Q_d + \Delta Q_d & 0 \\ 0 & Q_x \end{bmatrix} . \tag{41}
$$

Subsequently, we investigate the influence of ΔQ_d on the bias-variance effects of KF-DOB. To simplify the analysis, we assume that the disturbance switched from $1\alpha_1$ to $1\alpha_2$ at time step $j+1$, i.e., $d_j = 1\alpha_1 + w_{d_j}$ while $d_{j+1} = \mathbf{1}\alpha_2 + w_{d_{j+1}}$. Correspondingly, at time step $j+1$, the "initialization error" becomes

$$
\overline{\mathbf{x}}_{j}^{\text{b,dob}} = [(d_j^{\text{b, dob}})^T, (x_j^{\text{b, dob}})^T] \n= [(\alpha_2 - \alpha_1) \mathbf{1}^T, \mathbf{0}^T]^T.
$$
\n(42)

This error would converges to zero as $j \to \infty$ if KF-DOB is stable. Consequently, we denote the true steady-state error covariance as $P_{\infty}^{t, dob}$.

Theorem 3 There is an intrinsic bias-variance tradeoff in KF-DOB regarding $\Delta Q_d \succeq 0$. Under assumption 2, when using $\Delta Q_d = 0$, $P_{\infty}^{t, dob}$ is minimized and equal to the ideal error covariance, but the bias $\bar{x}^{\text{b},\text{dob}}_j$ converges to zero at the slowest speed. On the contrary, when applying $\Delta\mathrm{Q}_d\to\infty$, $\bar{x}^{\mathrm{b},\mathrm{dob}}_j$ converges to zero at its quickest speed, but its steady-state covariance $P_{\infty}^{t, dob}$ is maximized.

The proof of this theorem is available in Appendix 7.9.

Theorem 4 Consider a more general process mismatch covariance $\Delta Q = \begin{bmatrix} \Delta Q_d & 0 \end{bmatrix}$ 0 $\Delta\mathrm{Q}_x$ 1 (*i.e.*, existing both ΔQ_d

and ΔQ_x). In this scenario, KF-DOB is an unbiased minimum variance estimator if and only if $\Delta Q_d \rightarrow \infty$ and $Q_x = 0$.

The proof of this theorem is available at Appendix 7.10.

4 Remedies

In this section, we build a connection between SISE and conventional KF-DOB. We prove that these estimators are identical when selecting infinite disturbance noise covariance. Moreover, we demonstrate that KF-DOB is insufficient for complex disturbance scenarios. To handle

this issue, we provide two remedies, i.e., MKCKF-DOB and IMMKF-DOB.

4.1 Native Kalman Filter-based Disturbance Observer

We consider the following NKF-DOB as follows:

$$
\begin{bmatrix} d_{k-1} \\ x_k \end{bmatrix} = \begin{bmatrix} 0 & 0 \\ G_k & F_k \end{bmatrix} \begin{bmatrix} d_{k-1} \\ x_{k-1} \end{bmatrix} + \begin{bmatrix} w_{d,k-1} \\ w_{x,k} \end{bmatrix}
$$

$$
y_k = \begin{bmatrix} 0 & H_k \end{bmatrix} \begin{bmatrix} d_{k-1} \\ x_k \end{bmatrix} + v_k.
$$
 (43)

where $w_{d,k-1} \sim \mathcal{N}(0, D_k)$. The cross covariance has $E[(x_k - E(x_k))(d_{k-1} - E(d_{k-1}))^T] = E[(G_k d_{k-1} +$ $F_k x_{k-1} + w_{x,k} - \bar{x}_k (w_{d,k-1} - \bar{d}_{k-1}) = G_k D_k$. Analogicaly, one obtains

$$
E\begin{pmatrix} w_{d,k-1} \\ w_{x,k} \end{pmatrix} \begin{bmatrix} w_{d,k-1} \\ w_{x,k} \end{bmatrix}^T = \begin{bmatrix} D_k & D_k G_k^T \\ G_k D_k & Q_k \end{bmatrix}.
$$

Assumption 6 The initial state x_0 is independent of $w_{x,k}$ and $w_{d,k-1}$ with a known mean $x_{0|0}$ and covariance $matrix P_{0|0}^x$. Moreover, rank $H_kG_k = rank G_k = p$ where p is the dimension of d_k .

Under Assumption 6 and applying standard Gaussian conditional density formula, one arrives [\(Bitmead et al.,](#page-13-7) [2019\)](#page-13-7)

$$
P_{k|k-1} = G_k D_k G_k^T + F_k P_{k-1|k-1} F_k^T + Q_k
$$

\n
$$
K_k = P_{k|k-1} H_k^T (H_k P_{k|k-1} H_k^T + R_k)^{-1}
$$

\n
$$
M_k = D_k G_k^T H_k^T (H_k P_{k|k-1} H_k^T + R_k)^{-1}
$$

\n
$$
P_{k|k} = cov(x_k | \{y_k\}) = (I - K_k H_k) P_{k|k-1}
$$

\n
$$
P_{k-1|k}^d = cov(d_{k-1} | \{y_k\}) = (I - M_k H_k G_k) D_k
$$

\n
$$
x_{k|k} = F_k x_{k-1|k-1} + K_k (y_k - H_k F_k x_{k-1|k-1})
$$

\n
$$
d_{k-1|k} = M_k (y_k - H_k F_k x_{k-1|k-1})
$$

\nwhere d_k denotes the estimate of d_k of time at the

where $d_{k-1|k}$ denotes the estimate of d_{k-1} at time step k.

Lemma 7 [\(Bitmead et al.,](#page-13-7) [2019\)](#page-13-7) The NKFDOB in (44) is identical to SISE as shown in (2)-(4) when $D_k \to \infty$.

Lemma 8 (Identify 9 of [Bitmead et al.](#page-13-7) [\(2019\)](#page-13-7)) $M_k \rightarrow$ M_k^* and $K_k \to G_k \tilde{M}_k^* + K_k^*(I - H_k G_k M_k^*)$ as $\tilde{D_k} \to \infty$.

4.2 Kalman filter-based Disturbance Observer

We consider the KFDOB as shown in (5). The disturbance noise is assumed to follow $w_{d,k-1} \sim \mathcal{N}(0, D_k)$. Note that the only different between (43) and (5) is that a nominal model $d_k = d_{k-1}$ is used in (5) but ignored in

(43). Denote
$$
P_{k-1|k-1} = \begin{bmatrix} P^{dd} & P^{dx} \\ P^{xd} & P^{xx} \end{bmatrix}, \tilde{Q}_k = \begin{bmatrix} D_k & 0 \\ 0 & Q_k \end{bmatrix},
$$

and applying standard KF, one has

$$
P_{k|k-1}^{dd} = P^{dd} + D_k, P_{k|k-1}^{dx} = P^{dd}G_k^T + P^{dx}F_k^T
$$

\n
$$
P_{k|k-1}^{xx} = G_k P^{dd}G_k^T + F_k P^{xd}G_k^T + G_k P^{dx}F_k^T + F_k P^{xx}F_k^T + Q_k
$$

\n
$$
K_k^x = P_{k|k-1}^{xx} H_k^T (H_k P_{k|k-1}^{xx} H_k^T + R_k)^{-1}
$$

\n
$$
M_k^d = P_{k|k-1}^{dx} H_k^T (H_k P_{k|k-1}^{xx} H_k^T + R_k)^{-1}
$$

\n
$$
P_{k|k}^{xx} = cov(x_k | \{y_k\}) = (I - K_k H_k) P_{k|k-1}^{xx}
$$

\n
$$
P_{k|k}^{dd} = cov(d_{k-1} | \{y_k\}) = P_{k|k-1}^{dd} - P_{k|k-1}^{dx} H_k^T
$$

\n
$$
\times (H_k P_{k|k-1}^{xx} H_k^T + R_k)^{-1} H_k P_{k|k-1}^{xd}
$$

\n
$$
P_{k|k}^{dx} = P_{k|k-1}^{dx} - P_{k|k-1}^{dx} H_k^T (H_k P_{k|k-1}^{xx} H_k^T + R)^{-1} H_k P_{k|k-1}^{xx}
$$

\n
$$
x_{k|k} = F_k x_{k-1|k-1} + G_k d_{k-1|k-1} + K_k^x (y_k
$$

\n
$$
- H_k F_k x_{k-1|k-1} - H_k G_k d_{k-1|k-1} - H_k G_k d_{k-1|k-1}
$$

\n
$$
d_{k|k} = d_{k-1|k-1} + M_k (y_k - H_k F_k x_{k-1|k-1} - H_k G_k d_{k-1|k-1})
$$

\n(45)

Theorem 5 The KFDOB in (45) is identical to NKF-DOB in (44) as $D_k \to \infty$.

The proof of this theorem is available at Appendix 7.11.

Corollary 3 According to Lemma 7 and Theorem 5, KFDOB is identical to the SISE estimator as $D_k \to \infty$.

Remark 7 Corollary 3 coincides with Theorem 4 which states that KF-DOB becomes an unbiased minimum variance estimator as $D_k \to \infty$ under arbitrary disturbance models.

According to Corollary 3, as $D_k \to \infty$, NKF-DOB, KF-DOB, and SISE coincide. As pointed out by [\(Gillijns](#page-13-5) [and De Moor,](#page-13-5) [2007\)](#page-13-5), SISE is an unbiased minimum variance estimator under an arbitrary disturbance model. Meanwhile, KF-DOB is an optimal estimator when the disturbance model is exactly known. In many practical applications, the disturbance model is complex and cannot be modeled accurately. In this case, based on Theorem 3, there is an intrinsic bias-variance trade-off in KF-DOB. To alleviate this issue, we give two remedies: MKCKF-DOB and IMMKF-DOB. The former alleviates this trade-off through a robust loss, i.e., MKCL, while the latter uses a switching disturbance covariance to balance the disturbance tracking speed and tracking uncertainty.

4.3 Multi-Kernel Correntropy Kalman Filter-Based Disturbance Observer

One can rewrite (5) as

$$
\mathbf{T}_k = \mathbf{W}_k \mathbf{x}_k + \mathbf{B}_k^{-1} \nu_k \tag{46}
$$

where

$$
\mathbf{T}_k = \mathbf{B}_k^{-1} \begin{bmatrix} \hat{\mathbf{x}}_{k|k-1} \\ \mathbf{y}_k \end{bmatrix}, \mathbf{W}_k = \mathbf{B}_k^{-1} \begin{bmatrix} \mathbf{I} \\ \mathbf{H}_k \end{bmatrix}, \nu_k = \begin{bmatrix} \hat{\mathbf{x}}_{k|k-1} - \mathbf{x}_k \\ \mathbf{v}_k \end{bmatrix}
$$

Algorithm 1 MKMCKF-DOB

1: Step 1: Initialization

- 2: Choose the bandwidth vector σ_d and a threshold ε .
- 3: Step 2: State Prediction
- 4: $\hat{x}_{k|k-1} = \Phi_k \hat{x}_{k-1|k-1}$
- 5: $P_{k|k-1} = \Phi_k P_{k-1|k-1} \Phi_k^T + Q_k$
- 6: Obtain B_p and B_r by Cholesky decomposition.
- 7: Step 3: State Update 8: $\hat{x}_{k|k,0} = \hat{x}_{k|k-1}$
- $\displaystyle 9{:}~~\textbf{while}~~\frac{\left\|\hat{\mathrm{x}}_{k\left|k,t-\hat{\mathrm{x}}_{k\left|k,t\right|}\right\|}}{\left\|\hat{\mathrm{x}}_{k\left|k,t\right|\right|}}>\varepsilon~\textbf{do}$
- 10: $\hat{x}_{k|k,t} = \hat{x}_{k|k-1} + \tilde{K}_{k,t}(y_k H_k\hat{x}_{k|k-1})$
- 11: $\tilde{\mathbf{K}}_{k,t} = \tilde{\mathbf{P}}_{k|k-1} \mathbf{H}_{k}^{T} (\mathbf{H}_{k} \tilde{\mathbf{P}}_{k|k-1} \mathbf{H}_{k}^{T} + \tilde{\mathbf{R}}_{k})^{-1}$
- 12: $\tilde{P}_{k|k-1} = B_p \tilde{M}_p^{-1} B_p^T$, $\tilde{R}_k = B_r \tilde{M}_r^{-1} B_r^T$
- 13: $\tilde{M}_p = diag(G_{\sigma_p}(e_{p,k}))$, $\tilde{M}_r = diag(G_{\sigma_r}(e_{r,k}))$
- 14: $e_{p,k} = B_p^{-1} \hat{x}_{k|k-1} B_p^{-1} \hat{x}_{k|k,t-1}$
- 15: $e_{r,k} = B_r^{-1}y_k B_r^{-1}H\hat{x}_{k|k,t-1}$
- 16: $t = t + 1$
-
- 17: end while

18: $\mathrm{P}_{k|k} = (\mathrm{I} \tilde{\mathrm{K}}_k \mathrm{H}_k) \mathrm{P}_{k|k-1} (\mathrm{I} \tilde{\mathrm{K}}_k \mathrm{H}_k)^T + \tilde{\mathrm{K}}_k \mathrm{R}_k \tilde{\mathrm{K}}_k^T$

and B_k is obtained by Cholesky decomposition with

$$
E(\nu_k \nu_k^T) = \begin{bmatrix} \mathbf{P}_{k|k-1} & 0 \\ 0 & \mathbf{R}_{k} \end{bmatrix} = \begin{bmatrix} \mathbf{B}_p \mathbf{B}_p^T & 0 \\ 0 & \mathbf{B}_r \mathbf{B}_r^T \end{bmatrix} = \mathbf{B}_k \mathbf{B}_k^T.
$$

MKCKF is obtained by minimizing the following MKCL [\(Li et al.,](#page-14-16) [2023\)](#page-14-16):

$$
\min_{\mathbf{x}_k} J_{MKCKF} = \sum_{i=1}^l \sigma_i^2 (1 - G_{\sigma_i}(e_{i,k})) \qquad (47)
$$

where l denotes the dimensions of T_k , $e_{i,k}$ denotes the *i*-th element of e_k with $e_k = [e_{p,k}^T, e_{r,k}^T]^T = T_k - W_k x_k$, and σ_i are kernel bandwidths.

As a comparison, the KF can be derived by the following objective function [\(Simon,](#page-14-18) [2006\)](#page-14-18):

$$
\min_{\mathbf{x}_k} J_{KF} = \frac{1}{2} ||\mathbf{y}_k - \mathbf{H}_k \mathbf{x}_k||_{\mathbf{R}_k^{-1}}^2 + \frac{1}{2} ||\mathbf{x}_k - \Phi_k \mathbf{x}_{k-1}||_{\mathbf{P}_{k|k-1}^{-1}}^2.
$$
\n(48)

Lemma 9 [\(Li et al.,](#page-14-16) [2023\)](#page-14-16) The loss function (48) is *identical to* (47) when $\sigma_i \rightarrow \infty$ for $i = 1, 2, \ldots, l$.

We denote the process kernel bandwidth vector as $\sigma_p =$ $[\sigma_d^T, \sigma_x^T]^T$ where σ_d and σ_x are bandwidth vectors for the disturbance and state. Furthermore, we denote σ_r as the kernel bandwidth vector for the measurement. Since the nominal disturbance model $d_k = d_{k-1}$ may deviate from the ground truth disturbance model in MKCKF-DOB, we apply $\sigma_x \to \infty$ and $\sigma_r \to \infty$ vectors with infinite kernel bandwidth, and use σ_d as a positive vector with relatively small values according to [\(Li et al.,](#page-14-16) [2023\)](#page-14-16). Then, the MKCKF-DOB is summarized in Algorithm 1.

Remark 8 Since Gaussian kernel function $G_{\sigma}(e_k) \leq 1$ always holds, one has $\tilde{P}_{k|k-1} \succeq P_{k|k-1}$ and $\tilde{R}_k \succeq R_k$

Algorithm 2 IMMKF-DOB

- 1: Step 1: Initialization
- 2: Select disturbance noise covariance $Q_{dj,k}$ for model j
- 3: Step 2: Mixing
- 4: Obtain initial conditions of model j through (12) and (13)
- 5: Step 2: Filtering
- 6: Obtain the estimate of model j through (14)
- 7: Step 3: Mode update
- 8: Update the model probability for model j through (16)
- 9: Step 4: Output
- 10: Calculate posterior state and error covariance through (17)

in Algorithm 1. In MKCKF-DOB, we apply $\sigma_x \to \infty$ and $\sigma_r \to \infty$, which indicate that $\tilde{R}_k = R_k$ and only the submatrix of $P_{k|k-1}$ associated with the disturbance is inflated where the inflation level is determined by the process error $e_{p,k}$. This mechanism can be understood as applying an "adaptive" disturbance process covariance matrix so that it matches the practical process error under certain information metrics. Benefiting from the fixedpoint iteration in Line 9-17 of Algorithm 1, MKCKF-DOB alleviates the bias-variance dilemma compared with the conventional KF-DOB.

4.4 Interacting Multiple Model Kalman Filter-based Disturbance Observer

As demonstrated in Theorem 3, there is an intrinsic biasvariance trade-off in KF-DOB regarding the disturbance noise covariance selection. This dilemma can be mitigated by designing a switching disturbance process covariance mechanism so that the disturbance tracking is timely and smooth. To achieve this purpose, we design an IMMKF-DOB that has a similar structure to the conventional IMMKF summarized in Section 2.4, whereas a unified dynamic model accompanied with different process covariance is utilized in IMMKF-DOB. Specifically, in IMMKF-DOB, model j has

$$
x_k = \Phi_k x_{k-1} + w_{j,k}
$$

\n
$$
y_k = H_k x_k + v_k
$$
\n(49)

where
$$
w_{j,k} \sim \mathcal{N}\left(0, \begin{bmatrix} Q_{dj,k} & 0 \\ 0 & Q_{x,k} \end{bmatrix}\right)
$$
 and $Q_{dj,k}$ is the

disturbance noise covariance for model j . By selecting multiple $Q_{dj,k}$, IMMKF-DOB can achieve a timely and smoothing disturbance tracking through the fusion of multiple models (i.e., multiple disturbance covariances). The detailed IMMKF-DOB algorithm is similar to IMMKF shown in equations (12) to (17) and is summarized in Algorithm 2.

5 Simulations

We consider the following tracking problem:

$$
x_k = F_k x_{k-1} + G_k d_{k-1} + w_k
$$

\n
$$
y_k = H_k x_k + v_k
$$
\n(50)

where $F_k =$ $\begin{bmatrix} 1 & T \\ 0 & 1 \end{bmatrix}$ $, G_k =$ $\lceil \frac{T^2}{2} \rceil$ 2 \mathcal{I} 1 , $H_k =$ $\begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$, $x_k =$

 $[p_k, v_k]^T$ which contains the position and velocity, $T =$ 0.1s is the sampling time, and d_k is step-like disturbance as shown in (40) .

5.1 Trade-off Property

We denote the nominal disturbance covariance as D^* . Then, we compare the performance of NKF-DOB and KF-DOB with $D = \eta D^*$ where η ranging from exp(0) to exp(20). The results are shown in Fig. 1. One can observe that when η is finite and the disturbance is a step-like function, NKF-DOB and KF-DOB are biased but their estimate is relatively smooth. On the contrary, when η tends to infinity, the estimators are unbiased at the price of a non-smooth estimate.

Fig. 1. The performances of different estimators. (a) The disturbance estimate of NKF-DOB with different η . (b) The state estimate error of NKF-DOB with different η . (c) The disturbance estimate of KF-DOB with different η . (d) The state estimate error of KF-DOB with different $\eta.$

To highlight the bias-variance trade-off in KF-DOB,

we conduct 100 Monte Carlo runs to compare the bias and standard deviation of the disturbance estimate at each time step with different η . It is worth mentioning that the average disturbance bias is obtained by $b_{d,k} = \frac{1}{K} \sum_{i=1}^{K} (d_k - \hat{d}_k)$ and the standard deviation is obtained by $\sigma_{d,k} = \sqrt{\frac{1}{K} \sum_{i=1}^{K} (d_k - \hat{d}_k - b_{d,k})^2}$, where d_k is the ground truth disturbance, d_k is the estimated disturbance, and K is the Monte Carlo counts. The results are shown in Fig. 2(a). We observe that the $3\sigma_{d,k}$ region of $\eta = \exp(0)$ is substantially tighter than that of $\eta = \exp(20)$, at the cost of increased bias when a step-like disturbance comes. Meanwhile, when η is sufficiently large, the $3\sigma_{d,k}$ region becomes wider but the bias effects disappear gradually. We further summarize the average square of bias $\overline{b}_d^2 = \frac{1}{m_2 - m_1 + 1} \sum_{k=m_1}^{m_2} b_{d,k}$ and average variance $\bar{\sigma}^2 = \frac{1}{m_2 - m_1 + 1} \sum_{k=m_1}^{m_2} \sigma_k^2$ within the time interval $t = [126, 132]$ (i.e., $m_1 = 1260$ and m_2 = 1320. This region contains both the constant disturbance region and disturbance jump region). The corresponding result is shown in Fig. 2(b), where one can observe an obvious bias-variance trade-off with the increment of η (i.e., the disturbance noise covariance).

Fig. 2. The visualization of bias-variance trade-off in KF– DOB with different η .

5.2 Identity Property

We apply a sufficiently large D (e.g., $D = \exp(20)D^*$) for NKF-DOB and KF-DOB, and compare them with the SISE estimator. The results are shown in Fig. 3. One can observe that these estimators are identical which coincides with Theorem 5 and Corollary 3.

5.3 Two Remedies

In MKCKF-DOB, we use $\boldsymbol{\sigma}_p = [\varsigma_d, 10^8, 10^8]^T$ and $\boldsymbol{\sigma}_r =$ $[10^8, 10^8]$ with $\varsigma_d = 3$ according to Remark 8. Moreover, we apply $D = D^*$ which is the same with the KF-DOB setting. As for IMMKF-DOB, we use $D_1 = D^*$ for Model 1 and $D_2 = \exp(5)D^*$ for Model 2. The Markov

Table 2 Root-mean-square-error and and Time Consumption of Different Estimators.

Algorithm	$d - \hat{d}$ (mean \pm std)	$x_1 - \hat{x}_1$ (mean \pm std)	$x_2 - \hat{x}_2$ (mean \pm std)	time cost (mean \pm std)
KF-DOB $\eta = \exp(1)$	$2.2274 + 0.0125$	$0.0674 + 0.004537$	$0.1743 + 0.0024$	$0.0078 + 0.0019$
KF-DOB $\eta = \exp(1)$	$1.7857 + 0.0137$	$0.0673 + 0.004548$	$0.1434 + 0.0022$	0.0076 ± 0.0010
KF-DOB $\eta = \exp(2)$	$1.5008 + 0.0158$	$0.0672 + 0.004552$	$0.1327 + 0.0019$	$0.0076 + 0.0017$
KF-DOB $\eta = \exp(3)$	1.4497 ± 0.0190	$0.0672 + 0.004552$	$0.1325 + 0.0017$	$0.0076 + 0.0017$
KF-DOB $\eta = \exp(20)$	$2.0025 + 0.0311$	$0.0672 + 0.0045493$	$0.1417 + 0.0016$	0.0077 ± 0.0016
MKCKF-DOB	0.7500 ± 0.0105	$0.0672 + 0.004560$	$0.1102 + 0.0016$	0.0188 ± 0.0039
IMMKF-DOB	$0.9412 + 0.0183$	$0.0671 + 0.004556$	$0.1176 + 0.0016$	0.0296 ± 0.0027

Fig. 3. Identity property of SISE, NKF-DOB, and KF-DOB. (a) The disturbance estimate of different estimators. (d) Error covariance of different estimators.

transition matrix has $P =$ $\begin{bmatrix} 0.98 & 0.02 \end{bmatrix}$ 0.5 0.5 1

. The correspond-

ing disturbance error performances of SISE, KF-DOB, MKCKF-DOB, and IMMKF-DOB are shown in Fig. 4. One can observe that MKCKF-DOB and IMMKF-DOB have a smaller bias at the disturbance jump moments compared with the KF-DOB, but have a similar performance with the KF-DOB at the constant disturbance moments, which indicates that these two remedies have a better bias-variance trade-off compared with conventional KF-DOB.

Fig. 4. The disturbance estimate of SISE, KF-DOB, MKCK-F-DOB, and IMMKF-DOB.

To visualize the bias-variance effects of the above two remedies, we conduct 100 Monte Carlo runs and visualize the corresponding results in Fig. $5(a)$. We observe that $3\sigma_{d,k}$ region of the MKCKF and IMMKF are similar to that of the KF-DOB, but the bias effect is significantly mitigated. Furthermore, by denoting performance loss as the summation of the square of bias and variance, i.e., $\bar{b}_d^2 + \bar{\sigma}^2$, within the time interval $t \in [126, 132]$, we give the corresponding performance loss of different estimators in Fig. 5(b). The results verify the effectiveness of the proposed remedies.

Fig. 5. (a) The bias-variance visualization of KF-DOB, MKCKF-DOB, and IMMKF-DOB with 100 Monte Carlo runs. (b) Performance loss of different estimators with different η . Note that in MKCKF-DOB, the kernel bandwidth for the disturbance channel is set as $\varsigma_d = 3 + \log(\eta)$. In IMMK-F-DOB, we use $D_1 = D^*$ and $D_2 = \exp(\eta) \tilde{D}^*$.

We summarize the root-mean-square-error performance of different estimators by conducting 100 Monte Carlo simulations in Table 2. The program is executed in MAT-LAB on a laptop (Core(TM) i7-1360P, 2.2-GHz CPU, 16-GB RAM) and the time consumption of different algorithms is shown in the last column of Table 2. We observe that the overall performances of MKCKF-DOB and IMMKF-DOB are better than KF-DOB. We also see that the algorithm complexities of MKCKF-DOB and IMMKF-DOB are slightly higher than KF-DOB but are acceptable.

6 Conclusion

In the paper, we systematically investigate the biasvariance effects in KF-DOB and reveal that it is identical to the SISE estimator when applying infinite disturbance covariance. To meet the requirement of both timely and smooth disturbance estimates in many practical applications, we propose two remedies: MKCKF-DOB and IMMKF-DOB. The superiority of the proposed methods is explained from the perspective of "adaptive" or "switched" disturbance covariance and is verified in extensive simulations and experiments. It is worth noting that although MKCKF-DOB and IMMKF-DOB have better performances compared with the existing approaches, MKCKF-DOB needs to tune the kernel bandwidths and IMMKF-DOB needs to empirically design the Markov transition probability matrix. In the future, we will devote ourselves to developing adaptive mechanisms to avoid these time-consuming procedures.

7 Appendix

Derivation of Equation (22)

Based on the unbiasedness constraint, one has

$$
E(\hat{\mathbf{x}}_k) = E(\mathbf{x}_k). \tag{51}
$$

Applying (20) and (21) into (51) with $Y_{1,k}$ specified in (19), on arrives

$$
\mathcal{H}_{1,k}^s = \phi_k^1 - \mathcal{H}_{1,k}^h \mathbf{H}_{1,k}.
$$
 (52)

According to orthogonality principle, the estimator is optimal if $e_k \triangleq x_k - \hat{x}_k$ is orthogonal to $Y_{1,k}$ and x_0 , i.e.,

$$
E((\mathbf{x}_k - \mathcal{H}_{1,k}^h \mathbf{Y}_{1,k} - \mathcal{H}_{1,k}^s \mathbf{x}_0) \mathbf{Y}_{1,k}^T) = 0. \qquad (53)
$$

Substituting the expression of $Y_{1,k}$ as shown (19) and concerning that x_0 , $W_{1,k}$, and $V_{1,k}$ are mutually independent, (53) can be rewritten as

$$
\mathcal{B}_{1,k}\bar{P}_0\mathbf{H}_{1,k}^T + \mathcal{W}_{1,k}\mathbf{Q}_{1,k}\mathbf{D}_{1,k}^T + \mathcal{V}_{1,k}\mathbf{R}_{1,k} = 0 \quad (54)
$$

where

$$
\mathcal{B}_{1,k} = \phi_k^1 - \mathcal{H}_{1,k}^h \mathbf{H}_{1,k} - \mathcal{H}_{1,k}^s
$$

$$
\mathcal{W}_{1,k} = \mathbf{G}_{1,k}^{rk} - \mathcal{H}_{1,k}^h \mathbf{D}_{1,k}, \ \mathcal{V}_{1,k} = \mathcal{H}_{1,k}^h
$$
 (55)

and $\bar{P}_0 = E(x_0x_0^T), Q_{1,k} = E(W_{1,k}W_{1,k}^T), R_{1,k}$ $E(\mathbf{V}_{1,k}\mathbf{V}_{1,k}^T)$. Since \mathbf{x}_0 is known, the expectation operator in \overline{P}_0 can be removed, i.e., $\overline{P}_0 = E(\mathbf{x}_0 \mathbf{x}_0^T) = 0$. By collecting the terms in (54), one obtains the expression of $\mathcal{H}_{1,k}^h$ as shown in (23). Finally, according to (21) and (52), one arrives (22).

7.2 Proof of Proposition 1

One can regard the results of \hat{x} as the superposition of two components: one part is $x_0 = 0$ with normal y_k and another part is $x_0 \neq 0$ but $y_k = 0$ for all k. For the first part, (22) degenerates to $\hat{\mathbf{x}}_k = \hat{\mathbf{x}}_k^h$. According to Lemma

3, batch estimator (22) is identical to recursive estimator (6). It follows that $\hat{\mathbf{x}}_k^h$ can be written as (24) with initial value $\hat{x}_0^h = 0$ and $P_0 = 0$. For the second part, according to Lemma 3, one can derive (25) starting from $\hat{x}_0^s = x_0$. By superimposing (24) and (25), one can recover the KF as shown in (6) with known x_0 , which completes the proof.

7.3 Derivation of Equation (28)

According to the unbiasedness condition $E(\mathbf{x}_k) = E(\hat{\mathbf{x}}_k)$ where \hat{x}_k is shown in (27) and x_k is shown in (20) with $Y_{1,k}$ specified in (19), one obtains

$$
\bar{\mathcal{H}}_{1,k}^{s} = \phi_k^1 - \bar{\mathcal{H}}_{1,k}^{h} \mathbf{H}_{1,k}.
$$
 (56)

According to the orthogonality principle, one has $E[(\mathbf{x}_k - \hat{\mathbf{x}}_k)\mathbf{Y}_{1,k}^T] = 0.$ In a similar manner with the obtainment of (23), one can obtain (29). Finally, substituting the expression of (56) into (28) completes the proof.

7.4 Proof of Lemma 5

According to the posterior error covariance update equation and its corresponding information form update formula as shown in (7), one has

$$
P_{k|k} = (I - K_k H_k) P_{k|k-1}
$$

= $(P_{k|k-1}^{-1} + H_k^T R_k^{-1} H_k)^{-1}$
= $(P_{k|k-1}^{-1} + P_{k|k-1}^{-1} P_{k|k-1} H_k^T R_k^{-1} H_k)^{-1}$ (57)
= $(P_{k|k-1}^{-1} (I + P_{k|k-1} H_k^T R_k^{-1} H_k))^{-1}$
= $(I + P_{k|k-1} H_k^T R_k^{-1} H_k)^{-1} P_{k|k-1}$

Then, according to the first and final line of (57), one obtains (34). This completes the proof.

7.5 Proof of Theorem 1

Denote the discrete-time algebraic Riccati equation as $g(X) = \Phi_k X \Phi_k^T + \mathbf{Q}_k - \Phi_k X \mathbf{H}_k^T (\mathbf{H}_k X \mathbf{H}_k^T + \mathbf{R}_k)^{-1} \mathbf{H}_k X \Phi_k^T.$ It follows that $P_{k+1|k} = g(P_{k|k-1})$. According to [Bit](#page-13-12)mead et al. (1985), $g(X) \succeq g(Y)$ if $X \succeq Y$ and $Q_k^X \succeq Q_k^Y$ where Q_k^X and Q_k^Y are the corresponding process covariance matrices. At time step $k = 1$, $P_{1|0}^o = \Phi_1 P_{0|0} \Phi_1^T + Q_1$ and $P_{1|0}^u = \Phi_1 P_{0|0} \Phi_1^T + Q_1^u$, which indicate that $P_{1|0}^o \preceq$ $P_{1|0}^u$ if $\Delta Q \succeq 0$ and $P_{1|0}^o \succeq P_{1|0}^u$ if $\Delta Q \preceq 0$ (note that $\Delta Q = Q_k^u - Q_k$). Accordingly, it follows that $P_{k|k-1}^o \preceq$ $P_{k|k-1}^u$ for $\Delta Q \succeq 0$ and $P_{k|k-1}^o \succeq P_{k|k-1}^u$ for $\Delta Q \preceq 0$ for $k \geq 1$. Based on Lemma 5, it follows that

$$
M_k^o = (I + P_{k|k-1}^o H_k^T R_k^{-1} H_k)^{-1}
$$

$$
M_k^u = (I + P_{k|k-1}^u H_k^T R_k^{-1} H_k)^{-1}
$$
 (58)

Based on (36), one has

$$
\left((M_k^u)^T M_k^u\right)^{-1} = (X_k + Y_k)(X_k + Y_k)^T = \left((M_k^o)^T M_k^o\right)^{-1} + X_k Y_k^T + Y_k X_k^T + Y_k Y_k^T
$$
(59)

According to Assumption 1, it follows that $(M_k^u)^T M_k^u \leq$ $(M_k^o)^T M_k^o$ if $\Delta Q \succeq Q_{\epsilon+}$ and $(M_k^u)^T M_k^u \succeq (M_k^o)^T M_k^o$ if $\Delta Q \preceq Q_{\epsilon-}$. Subsequently, by denoting $z \triangleq \Phi_k \hat{x}_{k-1}^b$, it follows that $C_{\gamma,k}^o = z^T (\mathbf{M}_k^o)^T \mathbf{M}_k^o z \geq z^T (\mathbf{M}_k^u)^T \mathbf{M}_k^u z =$ $C^u_{\gamma,k}$ if $\Delta Q \geq Q_{\epsilon+}$ and $C^o_{\gamma,k} = z^T (M_k^o)^T M_k^o z \leq$ $z^T (\mathbf{M}_k^u)^T \mathbf{M}_k^u z = C_{\gamma,k}^u$ if $\Delta \mathbf{Q} \preceq \mathbf{Q}_{\epsilon-}$. This completes the proof.

7.6 Proof of Proposition 3

According to [Meenakshi and Rajian](#page-14-19) [\(1999\)](#page-14-19), the product of two positive PSD matrices is still a PSD matrix if and only if the product is symmetric. This implies that X_k and Y_k are PSD matrices if X_k and Y_k are symmetric and $\Delta Q \succeq 0$ (note that $P_{k|k-1}^o$, $P_{k|k-1}^u$, and $\tilde{H}_k^T R_k^{-1} H_k$ are PSD matrices). It follows that $(M_k^o)^{-1} = X_k$ and $(M_k^u)^{-1} = X_k + Y_k$ are PSD matrices. Subsequently, one has $M_k^o \succeq M_k^u$ if $\Delta Q \succeq 0$. By denoting $z \triangleq \Phi_k \hat{x}_{k-1}^b$, one obtains $C_{\gamma,k}^o = z^T (M_k^o)^T M_k^o z \geq z^T (M_k^u)^T M_k^u z = C_{\gamma,k}^u$ if $\Delta Q \succeq 0$. In a similar, one has $C_{\gamma,k}^o \leq C_{\gamma,k}^u$ if $\Delta Q \preceq 0$. This completes the proof.

7.7 Proof of Proposition 4

According to (18), it is clear that $Q_k^u \to \infty$ when $\Delta Q \to$ ∞ . Then, one obtains $M_k^u \to 0$ according to (34) under the premise that $H_k^T R_k^{-1} H_k$ is a PD matrix. Consequently, one arrives

$$
\lim_{\Delta Q \to \infty} C_{\gamma,1}^u = (\hat{\mathbf{x}}_0^b)^T \Phi_1^T (\mathbf{M}_k^u)^T \mathbf{M}_k^u \Phi_1 \hat{\mathbf{x}}_0^b \to 0 \tag{60}
$$

which implies that the estimation bias $\hat{\mathbf{x}}_k^b$ convergences to zero after receiving a single measurement if $\Delta Q \rightarrow \infty$.

7.8 Proof of Theorem 2

According to (7) and (38), one obtains

$$
(\mathbf{P}_{k|k}^{f})^{-1} - (\mathbf{P}_{k|k})^{-1} = (\Phi_k \mathbf{P}_{k-1|k-1} \Phi_k^T + \mathbf{Q}_k^u)^{-1}
$$

$$
- (\Phi_k \mathbf{P}_{k-1|k-1} \Phi_k^T + \mathbf{Q}_k)^{-1}.
$$
 (61)

It follows that $P_{k|k} \preceq P_{k|k}^{f_1} \preceq P_{k|k}^{f_2}$ $\Delta^{I2}_{k|k}$ if $0 \preceq \Delta Q_1 \preceq \Delta Q_2$ and $P_{k|k} \succeq P_{k|k}^{f1} \succeq P_{k|k}^{f2}$ $\bigcup_{k|k}^{J^2}$ if $\mathbf{0} \succeq \Delta Q_1 \succeq \Delta Q_2 \succeq -Q_k$.

Then, we compare $P_{k|k}^{t1}$ and $P_{k|k}^{t2}$. According to (6) and (39), one has

$$
P_{k|k}^{t} - P_{k|k} = C_{k}R_{k} \times (A_{k} + A_{k}B_{k}^{-1}A_{k})^{-1}
$$

$$
\times A_{k} ((A_{k} + A_{k}B_{k}^{-1}A_{k})^{-1})^{T} (R_{k})^{T} C_{k}^{T}
$$
(62)

where

$$
A_{k} = H_{k}P_{k|k-1}H_{k}^{T} + R_{k}
$$

\n
$$
B_{k} = H_{k}\Delta QH_{k}^{T}, C_{k} = H_{k}^{T} (H_{k}H_{k}^{T})^{-1}.
$$
 (63)

The above equation indicates that $P_{k|k}^t \succeq P_{k|k}$ always holds due to its quadratic form. Since ∆Q only appears in B_k , one has $P_{k|k} \preceq P_{k|k}^{t1} \preceq P_{k|k}^{t2}$ if $0 \preceq \Delta Q_1 \preceq \Delta Q_2$ and $P_{k|k} \preceq P_{k|k}^{t1} \preceq P_{k|k}^{t2}$ if $\mathbf{0} \succeq \Delta Q_1 \succeq \Delta Q_2 \succeq -Q_k$. This completes the proof.

7.9 Proof of Theorem 3

Since KF is optimal at its steady state in the minimum mean-square-error sense when applying the correct process and measurement covariance matrices, we conclude that $P_{\infty}^{t, dob}$ is minimized when applying $\Delta Q = 0$. At the same time, according to Proposition 3, one can deduce that $\Delta Q = 0$ yields the slowest bias convergence with disturbance jump under Assumption 2 for any $\Delta Q_d \succeq 0$. Meanwhile, according to Proposition 3 and Theorem 2, one can conclude that the true error covariance is maximized but the bias convergence rate is fastest (i.e., infinite convergence rate) by applying $\Delta Q_d \to \infty$.

7.10 Proof of Theorem 4

We first show that KF-DOB is unbiased if and only if $\Delta Q_d \rightarrow \infty$. According to Assumption 5, we know that KF-DOB is unbiased at time step j before its next disturbance jump, i.e., $E(\mathbf{x}_i) = \hat{\mathbf{x}}_i$. According to partitioned matrix inversion lemma [\(Bernstein,](#page-13-13) [2009\)](#page-13-13), if matrices A and D are invertible, one has

$$
\begin{bmatrix} A & B \\ C & D \end{bmatrix}^{-1} = \begin{bmatrix} A^{-1} + A^{-1} BECA^{-1} & -A^{-1} BE \\ - ECA^{-1} & E \end{bmatrix} \tag{64}
$$

where $E = (D - CA^{-1}B)^{-1}$. Based on the bias propagation equation (33) and the "initialization error" shown in (42), one obtains

$$
\bar{\mathbf{x}}_{j+1}^{\mathrm{b, dob}} = \bar{\Phi}_k \bar{\mathbf{x}}_j^{\mathrm{b, dob}} \tag{65}
$$

where
$$
\bar{\Phi}_k = \Phi_k M_k^u
$$
 and $M_k^u = (I + P_{k|k-1}^u H_k^T R_k^{-1} H_k)^{-1}$
(see Lemma 5). Denote $(M_k^u)^{-1} = S = \begin{bmatrix} S_{11} & S_{12} \\ S_{12} & S_{22} \end{bmatrix}$

 $|S_{21} S_{22}|$ where S_{11} and S_{22} are square matrices with the same dimension of ΔQ_d and ΔQ_x . As $\Delta Q_d \rightarrow \infty$, according to the error covariance prediction formula

$$
P_{k|k-1}^{u} = \Phi_k P_{k-1|k-1}^{u} \Phi_k^T + Q_k + \begin{bmatrix} \Delta Q_d & 0\\ 0 & \Delta Q_x \end{bmatrix}
$$
, one has

 $S_{11} \rightarrow \infty$ and hence $S_{11}^{-1} \rightarrow 0$. It follows that

$$
\mathbf{M}_k^u = \begin{bmatrix} 0 & 0\\ 0 & S_{22}^{-1} \end{bmatrix} \tag{66}
$$

according to (64). Subsequently, one has $\bar{x}_{j+1}^{b, \text{dob}} = 0$ by substituting the expressions of \mathbf{M}_{k}^{u} in (66) and $\bar{\mathbf{x}}_{j}^{\text{b,dob}}$ in (42) into (65). It indicates that $E(\mathbf{x}_{j+1}) = (\hat{\mathbf{x}}_{j+1})$ and KF-DOB is unbiased since the bias term is eliminated. On the contrary, KF-DOB is always biased since $\bar{x}_{j+1}^{\text{b,dob}} \neq 0$ if $\Delta Q_d \nrightarrow \infty$. These facts reveal that KF-DOB is unbiased if and only if $Q_d \to \infty$.

We then prove that $\Delta Q_x = 0$ gives the minimum variance estimator among all unbiased estimators. According to Lemma 6 and Theorem 2, one can observe that any additional perturbation on the process covariance will inflate the true error covariance. Hence, one can infer that $\Delta Q_x = 0$ gives a minimum variance estimator among all ΔQ_x . This completes the proof.

7.11 Proof of Theorem 5

To proceed, we first make the following assumptions: $P_{k-1|k-1}^{dd} \rightarrow D_k$ and $P_{k-1|k-1}^{dx}$ is negligible compared with $D_k G_k^T$ as $D_k \to \infty$. Under these assumptions, according to the standard Kalman filter equation, it follows that

$$
P_{k|k-1}^{dd} \to 2D, P_{k|k-1}^{dx} \to DG_{k}^{T}
$$

\n
$$
P_{k|k-1}^{xx} \to G_{k}D_{k}G_{k}^{T} + F_{k}P^{xx}F_{k}^{T} + Q_{k}
$$

\n
$$
K_{k}^{x} = P_{k|k-1}^{xx}H_{k}^{T}(H_{k}P_{k|k-1}^{xx}H_{k}^{T} + R_{k})^{-1}
$$

\n
$$
M_{k}^{d} \to D_{k}G_{k}^{T}H_{k}^{T}(H_{k}P_{k|k-1}^{xx}H_{k}^{T} + R_{k})^{-1}
$$

\n
$$
P_{k|k}^{xx} = (I - K_{k}H_{k})P_{k|k-1}^{xx}
$$

\n
$$
P_{k|k}^{dd} \to 2D_{k} - D_{k}G_{k}^{T}H_{k}^{T}(H_{k}P_{k|k-1}^{xx}H_{k}^{T} + R_{k})^{-1}
$$

\n
$$
\times H_{k}G_{k}D_{k} \to D_{k}
$$

\n
$$
x_{k|k} = F_{k}x_{k-1|k-1} + G_{k}d_{k-1|k-1} + K_{k}^{x}
$$

\n
$$
(y_{k} - H_{k}F_{k}x_{k-1|k-1} - H_{k}G_{k}d_{k-1|k-1})
$$

\n
$$
d_{k|k} = d_{k-1|k-1} + M_{k}^{d}(y_{k} - H_{k}F_{k}x_{k-1|k-1} - H_{k}G_{k}d_{k-1|k-1})
$$
\n(67)

One can observe that a necessary condition for the identity of the above equation with estimator (44) is that the following equations hold as $D_k \to \infty$,

$$
d_{k-1|k-1} - M_k^d H_k G_k d_{k-1|k-1} \to 0 \tag{68a}
$$

$$
G_k d_{k-1|k-1} - K_k^x H_k G_k d_{k-1|k-1} \to 0 \tag{68b}
$$

By observation, one obtains $M_k^d \to M_k$ and $K_k^x \to K_k$ as $D_k \to \infty$ by comparing (67) and (44). Then, according to Lemma 8, it follows that $M_k H_k G_k = M_k^d H_k G_k =$ I and hence (68a) holds. Similarly, based on Lemma 8, as $D_k \to \infty$, one obtains $K_k^x H_k G_k = K_k H_k G_k =$ $G_k M_k^* H_k G_k + K_k^* (H_k G_k - H_k G_k M_k^* H_k G_k) = G_k$, hence (68b) holds. A remaining issue is to prove $P_{k-1|k-1}^{dd} \rightarrow$ D_k and $P_{k-1|k-1}^{dx} \ll D_k G^T$ as $D_k \to \infty$. Without loss of generality, one can set the initial covariance as $P_{0|0} =$ 1

 $\begin{bmatrix} D_k & 0 \end{bmatrix}$ $0 \t P_{0|0}^x$. As $D_k \to \infty$, according to the propagation of

 $P_{k-1|k-1}^{dd}$ and $P_{k-1|k-1}^{dx}$ as shown in (45), one can deduce

that $P_{k-1|k-1}^{dd} \rightarrow D_k$ and $P_{k-1|k-1}^{dx}$ is negligible compared with $D_k G_k^T$ for $k \geq 2$. This completes the proof.

References

- Timothy D Barfoot. State estimation for robotics. Cambridge University Press, 2024.
- Dennis S Bernstein. Matrix mathematics: theory, facts, and formulas. Princeton university press, 2009.
- Robert R Bitmead, Michel R Gevers, Ian R Petersen, and R John Kaye. Monotonicity and stabilizabilityproperties of solutions of the riccati difference equation: Propositions, lemmas, theorems, fallacious conjectures and counterexamples. Systems Control Letters, 5(5):309–315, 1985.
- Robert R Bitmead, Morten Hovd, and Mohammad Ali Abooshahab. A Kalman-filtering derivation of simultaneous input and state estimation. Automatica, 108: 108478, 2019.
- Badong Chen, Xi Liu, Haiquan Zhao, and Jose C Principe. Maximum correntropy Kalman filter. Automatica, 76:70–77, 2017.
- Mou Chen, Peng Shi, and Cheng-Chew Lim. Robust constrained control for mimo nonlinear systems based on disturbance observer. IEEE Transactions on Automatic Control, 60(12):3281–3286, 2015a.
- Wen-Hua Chen, Donald J Ballance, Peter J Gawthrop, and John O'Reilly. A nonlinear disturbance observer for robotic manipulators. IEEE Transactions on Industrial Electronics, 47(4):932–938, 2000.
- Wen-Hua Chen, Jun Yang, Lei Guo, and Shihua Li. Disturbance-observer-based control and related methods—an overview. IEEE Transactions on Industrial Electronics, 63(2):1083–1095, 2015b.
- Mohamed Darouach and Michel Zasadzinski. Unbiased minimum variance estimation for systems with unknown exogenous inputs. Automatica, 33(4):717–719, 1997.
- Giuseppe De Nicolao, Giovanni Sparacino, and Claudio Cobelli. Nonparametric input estimation in physiological systems: Problems, methods, and case studies. Automatica, 33(5):851–870, 1997. ISSN 0005-1098.
- Moria Elkayam, Sergei Kolesnik, and Alon Kuperman. Guidelines to classical frequency-domain disturbance observer redesign for enhanced rejection of periodic uncertainties and disturbances. IEEE Transactions on Power Electronics, 34(4):3986–3995, 2018.
- Xuxiang Fan, Gang Wang, Jiachen Han, and Yinghui Wang. Interacting multiple model based on maximum correntropy Kalman filter. IEEE Transactions on Circuits and Systems II: Express Briefs, 68(8):3017–3021, 2021.
- Quanbo Ge, Teng Shao, Zhansheng Duan, and Chenglin Wen. Performance analysis of the Kalman filter with mismatched noise covariances. IEEE Transactions on Automatic Control, 61(12):4014–4019, 2016.
- Steven Gillijns and Bart De Moor. Unbiased minimum-

variance input and state estimation for linear discretetime systems. Automatica, 43(1):111–116, 2007.

- Jingqing Han. From PID to active disturbance rejection control. IEEE Transactions on Industrial Electronics, 56(3):900–906, 2009.
- C Johnson. Further study of the linear regulator with disturbances–the case of vector disturbances satisfying a linear differential equation. IEEE Transactions on Automatic Control, 15(2):222–228, 1970.
- Kyung-Soo Kim, Keun-Ho Rew, and Soohyun Kim. Disturbance observer for estimating higher order disturbances in time series expansion. IEEE Transactions on Automatic Control, 55(8):1905–1911, 2010.
- Min Jun Kim and Wan Kyun Chung. Disturbanceobserver-based PD control of flexible joint robots for asymptotic convergence. IEEE Transactions on Robotics, 31(6):1508–1516, 2015.
- Peter K Kitanidis. Unbiased minimum-variance linear state estimation. Automatica, 23(6):775–778, 1987.
- Li Li, Tianqi Wang, Yuanqing Xia, and Ning Zhou. Trajectory tracking control for wheeled mobile robots based on nonlinear disturbance observer with extended Kalman filter. Journal of the Franklin Institute, 357(13):8491–8507, 2020.
- Shilei Li, Dawei Shi, Wulin Zou, and Ling Shi. Multikernel maximum correntropy Kalman filter. IEEE Control Systems Letters, 6:1490–1495, 2021.
- Shilei Li, Dawei Shi, Yunjiang Lou, Wulin Zou, and Ling Shi. Generalized multi-kernel maximum correntropy Kalman filter for disturbance estimation. IEEE Transactions on Automatic Control, 2023.
- Zhijun Li, Chun-Yi Su, Liangyong Wang, Ziting Chen, and Tianyou Chai. Nonlinear disturbance observerbased control design for a robotic exoskeleton incorporating fuzzy approximation. IEEE Transactions on Industrial Electronics, 62(9):5763–5775, 2015.
- AR Meenakshi and C Rajian. On a product of positive semidefinite matrices. Linear Algebra and Its Applications, 295(1-3):3–6, 1999.
- Kiyoshi Ohishi, Masato Nakao, Kouhei Ohnishi, and Kunio Miyachi. Microprocessor-controlled dc motor for load-insensitive position servo system. IEEE Transactions on Industrial Electronics, (1):44–49, 1987.
- Laura Perea, Jonathan How, Louis Breger, and Pedro Elosegui. Nonlinearity in sensor fusion: divergence issues in ekf, modified truncated gsf, and ukf. In AIAA Guidance, Navigation and Control Conference and Exhibit, pages 6514–6529, 2007.
- Thao Tran Phuong, Kiyoshi Ohishi, Chowarit Mitsantisuk, Yuki Yokokura, Kouhei Ohnishi, Roberto Oboe, and Asif Sabanovic. Disturbance observer and Kalman filter based motion control realization. IEEJ Journal of Industry Applications, 7(1):1–14, 2018.
- Dan Simon. Optimal state estimation: Kalman, H infinity, and nonlinear approaches. John Wiley & Sons, 2006.
- Xinmin Song and Wei Xing Zheng. A Kalman-filtering derivation of input and state estimation for linear discrete-time systems with direct feedthrough. Auto-

matica, 161:111453, 2024.

- Yunda Yan, Xue-Fang Wang, Benjamin James Marshall, Cunjia Liu, Jun Yang, and Wen-Hua Chen. Surviving disturbances: A predictive control framework with guaranteed safety. Automatica, 158:111238, 2023.
- Sze Zheng Yong, Minghui Zhu, and Emilio Frazzoli. A unified filter for simultaneous input and state estimation of linear discrete-time stochastic systems. Automatica, 63:321–329, 2016.
- Dongdong Yu, Yuanqing Xia, Di-Hua Zhai, and Yufeng Zhan. Distributed simultaneous state-input estimation over sensor networks under quantized communication. Automatica, 163:111552, 2024.
- Shunyi Zhao and Biao Huang. Trial-and-error or avoiding a guess? Initialization of the Kalman filter. Automatica, 121:109184, 2020.
- Hao Zhu, Guorui Zhang, Yongfu Li, and Henry Leung. A novel robust Kalman filter with unknown non-stationary heavy-tailed noise. Automatica, 127: 109511, 2021.