Stochastic MPC for Finite Gaussian Mixture Disturbances with Guarantees

M. H. W. Engelaar¹, M. P. P. Swaanen¹, M. Lazar¹, and S. Haesaert¹

Abstract—This paper presents a stochastic model predictive control (SMPC) algorithm for linear systems subject to additive Gaussian mixture disturbances, with the goal of satisfying chance constraints. To synthesize a control strategy, the stochastic control problem is reformulated into an MPC problem. The reformulation begins by decoupling the mixture distribution and decomposing the system dynamics. Using stochastic simulation relations, we then redefine the stochastic control problem onto the resultant abstract system. Next, constraint tightening forms an MPC problem subject to finite disturbances. A branching control is introduced to solve the MPC problem. Finally, a controller refinement procedure determines a valid control strategy. Our contribution is an extension of the SMPC literature to accommodate Gaussian mixture disturbances while retaining recursive feasibility and closed-loop guarantees. We illustrate the retention of guarantees with a case study of vehicle control on an ill-maintained road.

I. INTRODUCTION

Control theory, a fundamental discipline in engineering and applied mathematics, offers a broad spectrum of techniques, ranging from simple, intuitive methods to highly sophisticated and computationally intensive approaches [1]. Within this spectrum, stochastic model predictive control (SMPC) is a robust method for effectively managing chance constraints—set constraints that must be met with a specified probability—while addressing uncertainties within dynamical systems, often described by probability distributions [2]. SMPC has been effectively utilized in various applications, including vehicle path planning, air traffic control, building climate control, and operations research and finance [2].

SMPC approaches are typically classified into two broad categories: randomized and analytic approximation methods [3]. Randomized methods rely on generating realizations of disturbances, while analytic approximation methods generally seek to convert the stochastic control problem into a deterministic one, all while proving essential properties, including recursive feasibility. The literature on SMPC covers scenarios ranging from complete knowledge of system disturbances [4] to cases where only partial information is available [5]. Some approaches consider discrete distributions [6], while others handle continuous distributions [7].

For the subclass of convex unimodal continuous distributions, researchers have successfully reformulated stochastic control synthesis problems into deterministic ones [8]–[11]. However, their approaches struggle when confronted with more complex distributions. Specifically, the assumption of convex unimodality is crucial for ensuring the closed-loop guarantees, though this assumption often fails in real-world scenarios. A more realistic model for such applications involves Gaussian mixtures, which can approximate any continuous distribution with arbitrary precision [12], [13].

Approximating distributions in the context of predictive control have been considered in [14] in which distributional robust data-enabled predictive control was used. Herein, a ball is constructed in the space of probability distributions centred around the uniform distribution of the sample set, which contains the actual distribution with a predefined probability [15]. The control strategy is developed under the assumption of the worst-case distribution scenario. Similarly, Gaussian mixtures in the context of predictive control have been considered in [16], which assumed non-linear dynamics subject to additive disturbances. Nevertheless, tractable implementation, deriving closed-loop guarantees, and establishing recursive feasibility remain open research problems.

This paper aims to develop a control strategy for linear systems subject to additive Gaussian mixture disturbances with the purpose of satisfying chance constraints. The primary contribution of this paper is the extension of SMPC methods to handle additive Gaussian mixture distributions while preserving key properties such as recursive feasibility and closed-loop guarantees. To achieve this, we consider the approach depicted in Fig. 1. Herein, we reformulate the stochastic control synthesis problem into an MPC problem. To this aim, firstly, we fragment the system dynamics by employing disturbance decoupling, separating the mixture into discrete and continuous distribution components, and system decomposition, separating the dynamics into nominal and error parts. Next, the stochastic control problem is redefined onto the resultant abstract system through stochastic simulation relations. Afterwards, constraint tightening is utilized to obtain an MPC problem subject to finite disturbances. To solve the MPC problem, a branching control strategy is synthesized. Finally, by utilizing controller refinement, a valid control strategy on the original system can be obtained.



Fig. 1. An illustration of the stochastic MPC synthesis approach. The steps are given by: (1) redefine the control problem, (2) reformulate the control problem, (3) solve the MPC problem, and (4) refine the control strategy.

This work is supported by the Dutch NWO Veni project CODEC under grant number 18244 and the European project SymAware under grant number 101070802. ¹Department of Electrical Engineering (Control Systems Group), Eindhoven University of Technology, The Netherlands. Emails:{m.h.w.engelaar, m.p.p.swaanen, m.lazar, s.haesaert}@tue.nl.

The remainder of this paper is organized as follows. In Section II, the preliminaries and the problem statement are introduced. In Section III, the stochastic control synthesis problem is redefined onto the abstract system. In Section IV, the redefined control problem is reformulated into an MPC problem. In Section V, control implementation, recursive feasibility and closed-loop guarantees are established. Finally, Section VI considers a one-dimensional example of a vehicle maintaining position on an ill-maintained road.

II. PRELIMINARIES & PROBLEM STATEMENT

For a given probability measure \mathbb{P} defined over Borel measurable space $(\mathbb{X}, \mathcal{B}(\mathbb{X}))$, we denote the probability of an event $\mathcal{A} \in \mathcal{B}(\mathbb{X})$ as $\mathbb{P}(\mathcal{A})$. We denote the set of all probability measures over $(\mathbb{X}, \mathcal{B}(\mathbb{X}))$ by $\mathscr{P}(\mathbb{X})$. In this paper, we will work with Polish spaces and Borel measurability. Further details on measurability are omitted, and we refer the interested reader to [17]. The vector of all elements one or zero is denoted, respectively, by $\mathbf{1}_n, \mathbf{0}_n \in \mathbb{R}^n$, and 1 or **0** if the context is clear. The Minkowski set difference and sum of $\mathcal{A}, \mathcal{B} \subseteq \mathbb{R}^n$ are, respectively, given by $\mathcal{A} \ominus \mathcal{B} := \{a \mid a+b \in \mathcal{A}, \forall b \in \mathcal{B}\}$ and $\mathcal{A} \oplus \mathcal{B} = \{a+b \mid \forall a \in \mathcal{A}, \forall b \in \mathcal{B}\}$.

A. Stochastic System Dynamics

We consider linear dynamics with additive noise, given by

$$x(k+1) = Ax(k) + Bu(k) + w(k),$$
 (1)

where (A, B) is stabilizable, $x \in \mathbb{R}^n$ is the state of the system, $x(0) \in \mathbb{R}^n$ is an initial state, $u \in \mathbb{R}^m$ is the input of the system and $w \in \mathbb{R}^n$ is an independent, identically distributed noise disturbance with distribution \mathcal{Q}_w , i.e., $w(k) \sim \mathcal{Q}_w$. We will assume that the distribution \mathcal{Q}_w is a mixture of Gaussians denoted by $\mathcal{M}(\mu, \pi, \Sigma)$ with $\mu = \{\mu_1, \dots, \mu_p\}$, $\mu_i \in \mathbb{R}^n, \pi = \{\pi_1, \dots, \pi_p\}, \pi_i \in [0, 1]$ and $\Sigma \in \mathbb{R}^{n \times n}$ a strictly positive definite matrix. The probability density function of $\mathcal{M}(\mu, \pi, \Sigma)$ is defined as

$$g(x; \boldsymbol{\mu}, \boldsymbol{\pi}, \boldsymbol{\Sigma}) := \sum_{i=1}^{p} \pi_{i} g(x; \mu_{i}, \boldsymbol{\Sigma}), \qquad (2)$$

where $\sum_{i=1}^{p} \pi_i = 1$, and $g(x; \mu_i, \Sigma)$ is the probability density function of a multivariate Gaussian distribution. All multivariate Gaussian distribution components within the mixture have different means but share the same variance.

To control the system, we define a sequence of policies

$$\boldsymbol{f} := \{f_0, f_1, \dots\},\$$

such that $f_k : \mathbb{H}_k \to \mathbb{R}^m$ maps history to inputs. The history is defined as $\mathbb{H}_k := (\mathbb{R}^n \times \mathbb{R}^m)^k \times \mathbb{R}^n$, with elements $\eta(k) :=$ $(x(0), u(0), \dots, u(k-1), x(k))$, representing the previous states and inputs. By implementing control strategy f upon system (1), we obtain its controlled form for which the control input satisfies the feedback law $u(k) = f_k(\eta(k))$ with $\eta(k) \in \mathbb{H}_k$. We indicate the input sequence of system (1) by $u := \{u(0), u(1), \dots\}$ and define its executions as sequences of states $x := \{x(0), x(1), \dots\}$, referred to as signals. We define the suffix of any signal x by $x_k = \{x(k), x(k + 1), \dots\}$. Any signal x can be interpreted as a realization of the probability distribution induced by implementing control strategy f upon the system (1), denoted by $x \sim \mathbb{P}_f$.

B. Chance Constraints

In this paper, the objective is to synthesize a control strategy f such that, if implemented, satisfaction is guaranteed for a given specification. This paper defines the specifications as set constraints on the state and input of system (1), where satisfaction is to be guaranteed with predefined probability at each time instance. The following chance constraints describe such a specification.

$$\mathbb{P}_{\boldsymbol{f}}(\boldsymbol{x}(k) \in \mathcal{X} \mid \boldsymbol{x}(0)) \ge p_x, \ k \in \mathbb{N} - \{0\},$$
(3a)

$$\mathbb{P}_{\boldsymbol{f}}(u(k) \in \mathcal{U} \mid x(0)) \ge p_u, \ k \in \mathbb{N},\tag{3b}$$

where \mathcal{X} and \mathcal{U} are convex sets, and p_x and p_u represent the *target lower bounds*, i.e., the minimal predefined probability targets of the set constraints. It is assumed that the convex sets \mathcal{X} and \mathcal{U} contain the origin within their interior. The chance constraints are defined with respect to the initial state, i.e., conditioned based on the initial state x(0).

C. Problem Formulation

This paper aims to synthesize a control strategy f, using model predictive control, such that stochastic linear system (1) satisfies the chance constraints (3). As a secondary objective, we want to update the control strategy as new measurements become available. More formally, we want to develop a model predictive control synthesis method for updating, at each time instance k, suffix f_k such that, if the control strategy f is implemented, the system (1) will satisfy chance constraints (3). Note that due to the Gaussian mixture representation of the disturbance, which is much more realistic than the single Gaussian, the stochastic MPC synthesis problem becomes more challenging. To address this, we aim to decouple the mixture disturbance into discrete and continuous components (see Fig. 2) and utilize branching control to obtain a valid control strategy.



Fig. 2. An illustration of the decoupling of a Gaussian mixture (Left: Purple) into a continuous (Gaussian) distribution (Right: Purple) and a discrete distribution (Right: Stems). The dashed lines represent the Gaussian components of the mixture. Each stem corresponds to a component.

III. REDEFINING THE STOCHASTIC CONTROL PROBLEM

To synthesize a control strategy, we draw inspiration from the work [8], which suggests reformulating the stochastic control problem into an MPC problem. As a first step, in this section, we redefine the stochastic control problem onto an abstract system. This abstract system is obtained via system decomposition, separating the nominal and error dynamics, and mixture decoupling, separating the discrete and continuous components. We prove that any valid control strategy developed on the abstract system will give rise to a valid control strategy on the original system via stochastic simulation relations and controller refinement.

A. Abstract System Design

To obtain the abstract system, we first decouple the mixture into a discrete and continuous distribution, obtaining the dynamical system given by

$$x(k+1) = Ax(k) + Bu(k) + w_x(k) + w_e(k), \quad (4)$$

where $w_x(k) \sim Q_w^x$ is a discrete distribution with probability mass function

$$g(w_x; \boldsymbol{\mu}, \boldsymbol{\pi}) = \begin{cases} \pi_i & \text{if } w_x = \mu_i, \\ 0 & \text{otherwise,} \end{cases}$$
(5)

and $w_e(k) \sim Q_w^e := \mathcal{N}(\mathbf{0}, \Sigma)$. Next, we decompose dynamics (4) into a nominal and an error part similar to [8], i.e., x(k) = z(k) + e(k). The nominal dynamics, denoted as z, contain stochasticity with finite support, and the error dynamics, denoted as e, are autonomous and contain stochasticity with infinite support. The abstract system is then given by the stochastic linear system

$$z(k+1) = Az(k) + Bv(k) + w_x(k),$$
 (6a)

$$e(k+1) = A_K e(k) + w_e(k),$$
 (6b)

where v(k) is the nominal input, $A_K = A + BK$ and K is a stabilizing feedback gain meant to keep the error e small, i.e., A_K has eigenvalues strictly inside the unit circle. We note that the dynamical systems (4) and (6), for the same disturbance $w_x(k)$ and $w_e(k)$, satisfy x(k) = z(k) + e(k) if

$$v(k) = u(k) - Ke(k).$$
(7)

B. Stochastic Simulation Relation

To redefine the stochastic control problem onto the abstract system, we first employ stochastic simulation relations to show that the original system simulates the abstract system. To define stochastic simulation relations, the notion of Markov decision process and lifting are required [18].

Definition 1 (Markov Decision Process): The tuple $\mathbf{M} = (\mathbb{X}, \mathbb{T}, \mathbb{U}, h, \mathbb{Y})$ defines a Markov decision process (MDP). A MDP is characterized by 1) Polish sets \mathbb{X} and \mathbb{U} ; by 2) \mathbb{T} , a Borel measurable stochastic transition kernel that assigns to each state $x \in \mathbb{X}$ and input $u \in \mathbb{U}$, a probability measure $\mathbb{T}(\cdot|x, u) \in \mathscr{P}(\mathbb{X})$; and by 3) $h : \mathbb{X} \to \mathbb{Y}$, a measurable output map that assigns to each state $x \in \mathbb{X}$ an output $y \in \mathbb{Y}$.

The MDP representation is non-unique for both systems (1) and (6). In this paper, we consider the following MDP representations, respectively, for original system M and abstract system \hat{M} . We exclude the time indexes for brevity and note that each (signal) element *s* has index *k*, and each differential *ds* has index k + 1.

$$\mathbf{M} := \begin{cases}
\mathbb{X} := \mathbb{R}^n \times \mathbb{R}^m, \ \mathbb{Y} := \mathbb{R}^n \times \mathbb{R}^m, \ \mathbb{U} := \mathbb{R}^m, \\
h(x, x_i) := (x, x_i), \ \mathbb{T}(dx \times dx_i \mid x, u) \\
:= \sum_{i=1}^p \pi_i \mathcal{N}(dx; Ax + Bu + \mu_i, \Sigma) \delta(dx_i - u).
\end{cases}$$

$$\hat{\mathbf{M}} := \begin{cases}
\hat{\mathbb{X}} := \mathbb{R}^n \times \mathbb{R}^n \times \mathbb{R}^m, \ \hat{\mathbb{Y}} := \mathbb{R}^n \times \mathbb{R}^m, \ \hat{\mathbb{U}} := \mathbb{R}^m, \\
\hat{h}(z, e, \hat{x}_i) := (z + e, \hat{x}_i), \ \mathbb{T}(dz \times de \times d\hat{x}_i \mid z, e, v) \\
:= \sum_i^p \pi_i \delta(dz - Az - Bv - \mu_i) \mathcal{N}(de; A_K e, \Sigma) \\
\delta(d\hat{x}_i - v - K e).
\end{cases}$$

For MDP M and \hat{M} , the transition kernels depict, respectively, the system dynamics of (1) and (6), with an additional intermediate state element $x_i(k)$, $\hat{x}_i(k)$ representing, respectively, the input u(k-1) and the input relation v(k-1) + Ke(k-1). Both of these are also our secondary outputs together with the primary outputs of the state x(k)for M and the state relation z(k) + e(k) for \hat{M} . The sequel will show that the output pairs x(k) and z(k) + e(k), and u(k) and v(k) + Ke(k) have similar probability when the control strategies of both systems satisfy certain relations.

Definition 2 (Lifting): Consider two measurable spaces $(\mathbb{X}, \mathcal{B}(\mathbb{X}))$ and $(\hat{\mathbb{X}}, \mathcal{B}(\hat{\mathbb{X}}))$, and a relation $\mathcal{R} \subseteq \mathbb{X} \times \hat{\mathbb{X}}$ with $\mathcal{R} \in \mathcal{B}(\mathbb{X} \times \hat{\mathbb{X}})$. Pairs of probability measure $(\mathbb{P}_1, \mathbb{P}_2) \in \mathscr{P}(\mathbb{X}) \times \mathscr{P}(\hat{\mathbb{X}})$ belong to the lifted relation $\overline{\mathcal{R}}$ if there exists a probability measure \mathbb{W} , referred to as a lifting, over a measurable space $(\mathbb{X} \times \hat{\mathbb{X}}, \mathcal{B}(\mathbb{X} \times \hat{\mathbb{X}}))$ such that

I. $\mathbb{W}(A_1 \times \hat{\mathbb{X}}) = \mathbb{P}_1(A_1)$ for all $A_1 \in \mathcal{B}(\mathbb{X})$; II. $\mathbb{W}(\mathbb{X} \times A_2) = \mathbb{P}_2(A_2)$ for all $A_2 \in \mathcal{B}(\hat{\mathbb{X}})$; III. $\mathbb{W}(\mathcal{R}) = 1$.

The interpretation of the lifting \mathbb{W} is a relation between realizations of probability measures within the confine of a relation \mathcal{R} . Lifting also generalizes the notion of coupling as explained in [18]. Utilizing the previous definitions, we obtain a definition for stochastic simulation relations [18].

Definition 3 (Stochastic Simulation Relation): The MDP $\hat{\mathbf{M}} = (\hat{\mathbb{X}}, \hat{\mathbb{T}}, \hat{\mathbb{U}}, \hat{h}, \hat{\mathbb{Y}})$ is simulated by MDP $\mathbf{M} = (\mathbb{X}, \mathbb{T}, \mathbb{U}, h, \mathbb{Y})$ if there exists a Borel measurable interface function $\nu : \hat{\mathbb{U}} \times \hat{\mathbb{X}} \times \mathbb{X} \to \mathbb{U}$ and a relation $\mathcal{R} \subseteq \hat{\mathbb{X}} \times \mathbb{X}$ with $\mathcal{R} \in \mathcal{B}(\hat{\mathbb{X}} \times \mathbb{X})$ for which there exists a Borel measurable stochastic kernel $\mathbb{W}(\cdot | \hat{u}, \hat{x}, x)$ on $\hat{\mathbb{X}} \times \mathbb{X}$ given values in $\hat{\mathbb{U}} \times \hat{\mathbb{X}} \times \mathbb{X}$, such that

- 1) $\forall (\hat{x}, x) \in \mathcal{R}, \ \hat{h}(\hat{x}) = h(x);$
- ∀(x̂, x) ∈ R, ∀û ∈ Û, (Î(·|x̂, û), T(·|x, ν(û, x̂, x)) ∈
 R̄ with lifted probability measure W(· | û, x̂, x).

The interpretation of the above conditions is that 1) state components in the relation behave similarly and 2) that for any element in the relation and any input on the simulated system, any realization of subsequent states, connected via the lifting and interface, will be contained in the relation, making the relation invariant over the transition kernels. Utilizing the above definition, it is proven that the original system simulates the abstract system.

Theorem 4: System $\hat{\mathbf{M}}$ is simulated by \mathbf{M} via relation $\mathcal{R} = \{(z, e, \hat{x}_i, x, x_i) \mid x = z + e, x_i = \hat{x}_i\}$ and interface function $\nu(e, v) = v + Ke$.

Proof: First, we consider a relation between the disturbances w, w_x and w_e , given by $\mathcal{R}_1 := \{(w, w_x, w_e) \mid w = w_x + w_e\}$. We claim that distributions \mathcal{Q}_w and $\mathcal{Q}_w^x \otimes \mathcal{Q}_w^e$ belong to the lifted relation. To prove this claim, we consider the potential lifting given by

$$\mathbb{W}_{1}(w, w_{x}, w_{e}; \boldsymbol{\mu}, \boldsymbol{\pi}, \boldsymbol{\Sigma}) = \mathcal{M}(w; \boldsymbol{\mu}, \boldsymbol{\pi}, \boldsymbol{\Sigma}) \cdot \\
\sum_{i} \left[\delta(w_{x} - \mu_{i}) \frac{\pi_{i} \mathcal{N}(w; \mu_{i}, \boldsymbol{\Sigma})}{\mathcal{N}(w; \boldsymbol{\mu}, \boldsymbol{\pi}, \boldsymbol{\Sigma})} \right] \cdot \delta(w_{e} - w + w_{x}), \quad (8)$$

where δ denotes the Dirac delta distribution. To ascertain the validity of the lifting, we consider Def. 2. First, we note that

 $\mathbb{W}_1(\mathcal{R}_1) = 1$ due to the second Dirac delta. Regarding the requirements I and II, we consider two integrals given by

$$\iint_{w_x,w_e} \mathbb{W}_1(w,w_x,w_e;\boldsymbol{\mu},\boldsymbol{\pi},\boldsymbol{\Sigma}) dw_x dw_e, \\ \int_{w} \mathbb{W}_1(w,w_x,w_e;\boldsymbol{\mu},\boldsymbol{\pi},\boldsymbol{\Sigma}) dw.$$

Solving the former, the result is given by

$$\iint_{w_x,w_e} \mathbb{W}_1(w,w_x,w_e;\boldsymbol{\mu},\boldsymbol{\pi},\boldsymbol{\Sigma}) dw_x dw_e = \mathcal{M}(w;\boldsymbol{\mu},\boldsymbol{\pi},\boldsymbol{\Sigma})$$

while the latter will result in

$$\int_{w} \mathbb{W}_{1}(w, w_{x}, w_{e}; \boldsymbol{\mu}, \boldsymbol{\pi}, \boldsymbol{\Sigma}) dw = \int_{w} \mathcal{M}(w; \boldsymbol{\mu}, \boldsymbol{\pi}, \boldsymbol{\Sigma}) \cdot \\\sum_{i} \left[\delta(w_{x} - \mu_{i}) \frac{\pi_{i} \mathcal{N}(w; \mu_{i}, \boldsymbol{\Sigma})}{\mathcal{N}(w; \boldsymbol{\mu}, \boldsymbol{\pi}, \boldsymbol{\Sigma})} \right] \cdot \delta(w_{e} - w + w_{x}) dw = \\\int_{w} \sum_{i} \left[\delta(w_{x} - \mu_{i}) \pi_{i} \mathcal{N}(w; \mu_{i}, \boldsymbol{\Sigma}) \right] \delta(w_{e} - w + w_{x}) dw = \\\sum_{i} \pi_{i} \delta(w_{x} - \mu_{i}) \mathcal{N}(w_{e}; \mu_{i} - w_{x}, \boldsymbol{\Sigma}) = \\\sum_{i} \pi_{i} \delta(w_{x} - \mu_{i}) \mathcal{N}(w_{e}; \mathbf{0}, \boldsymbol{\Sigma}).$$

Both integral solutions explain that the marginalization leads to the distributions of Q_w and $Q_w^x \otimes Q_w^e$, proving our claim.

With the preliminaries established, we claim system $\hat{\mathbf{M}}$ is simulated by system \mathbf{M} . To prove this claim, we consider a relation between x, x_i, z, e and \hat{x}_i given by $\mathcal{R}_2 :=$ $\{(z, e, \hat{x}_i, x, x_i) \mid x = z + e, x_i = \hat{x}_i\}$; establish an interface function $\nu(e, v) = v + Ke$; and derive a stochastic kernel $\mathbb{W}_2(\cdot | x, x_i, z, e, \hat{x}_i, v)$ from the lifting \mathbb{W}_1 . Since x, z, e, \hat{x}_i of relation \mathcal{R}_2 are each directly related to an element in relation \mathcal{R}_1 , and x_i is directly determined from the interface function, any result in regards to Def. 2 on \mathbb{W}_1 can be extended towards \mathbb{W}_2 . Consequently, the satisfaction of the second requirement of Def. 3 follows from the fact that the stochastic kernel \mathbb{W}_2 can be derived from the lifting \mathbb{W}_1 and shares the same results as \mathbb{W}_1 in regards to Def. 2, only now extended towards the transition kernels. Since the first requirement is trivially satisfied, our claim is proven.

C. Stochastic Control Problem on Abstract System

We now redefine the stochastic control problem towards the abstract system. First, we consider the following proposition obtained from [18, Thm. 2].

Proposition 5: If \mathbf{M}_1 is simulated by \mathbf{M}_2 then for all control strategies f_1 there exists a control strategy f_2 such that, for all measurable events $\mathcal{A} \in \mathcal{B}(\mathbb{Y}^{N+1})$,

$$\mathbb{P}_{f_1 \times \mathbf{M}_1}(\{h_1(x_1)\}_{[0,N]} \in \mathcal{A}) = \mathbb{P}_{f_2 \times \mathbf{M}_2}(\{h_2(x_2)\}_{[0,N]} \in \mathcal{A}),$$
where $\{h_1(x_1)\}_{[0,N]} \in \mathcal{A}$ is the formula $\{h_2(x_2)\}_{[0,N]} \in \mathcal{A}$.

where $\{h_j(x_j)\}_{[0,N]} := \{h_j(x_j(0)), \cdots, h_j(x_j(N))\}.$

Since Thm. 4 establishes that the original system simulates the abstract system, the above proposition ensures that for any control strategy synthesized on the abstract system, there exists a control strategy on the original system, such that the output pairs x(k) and z(k)+e(k), and u(k) and v(k)+Ke(k)have similar probability. Accordingly, we can redefine the stochastic control problem into the following.

Redefined Stochastic Control Problem: Synthesize a control strategy f for abstract system (6), with the objective of satisfying the chance constraints

$$\mathbb{P}_{\boldsymbol{f}}(z(k) + e(k) \in \mathcal{X} \mid x(0)) \ge p_x, \ k \in \mathbb{N} - \{0\}, \quad (9a)$$

$$\mathbb{P}_{\boldsymbol{f}}(\boldsymbol{v}(k) + K\boldsymbol{e}(k) \in \mathcal{U} \mid \boldsymbol{x}(0)) \ge p_u, \ k \in \mathbb{N}.$$
(9b)

D. Controller Refinement Procedure

Based on Thm. 4, for any realization $w \sim Q_w$ of the disturbance on the original system, there exists a conditional probability measure given by

$$\mathbb{W}(w_x, w_e \mid w) := \mathbb{W}_1(w_x, w_e \mid w; \boldsymbol{\mu}, \boldsymbol{\pi}, \boldsymbol{\Sigma}) = \sum_i \left[\delta(w_x - \mu_i) \frac{\pi_i \mathcal{N}(w; \mu_i, \boldsymbol{\Sigma})}{\mathcal{N}(w; \boldsymbol{\mu}, \boldsymbol{\pi}, \boldsymbol{\Sigma})} \right] \delta(w_e - w + w_x), \quad (10)$$

such that any element in the support of (10) will ensure both the original and abstract system have the same output if u(k) = v(k) + Ke(k). Accordingly, if a valid control strategy is synthesized on the abstract system, the interface function and conditional probability measure (10) establish a valid control strategy on the original system. Fig. 3 illustrates this so-called controller refinement procedure.



Fig. 3. An illustration of the controller refinement procedure. The original system is denoted by \mathbf{M} , the abstract system by $\hat{\mathbf{M}}$, the abstract control strategy by $\hat{\mathbf{C}}$ and the original control strategy by \mathbf{C} .

IV. CONTROL SYNTHESIS FOR THE ABSTRACT SYSTEM

This section defines an MPC reformulation of the redefined stochastic control problem. This is accomplished by defining probabilistic reachable sets and utilizing these to tighten the chance constraints (9), producing deterministic set constraints on the nominal dynamics while eliminating the error dynamics. The remaining stochasticity within the nominal dynamics is handled by branching the control strategy for each realization of the nominal disturbance.

A. Bounding the Error Dynamics

As is common, we bound the effect of the error dynamics e(k) in (6). Afterwards, we tighten the constraints on the nominal dynamics z(k). To accomplish both, we define probabilistic reachable sets over the error dynamics (6b).

Definition 6 (Probabilistic Reachable Sets [8]): A probabilistic reachable set (PRS) of probability level $p \in [0, 1]$ for error dynamics (6b), denoted by \mathcal{R}^p , is a set that satisfies

$$e(0) = \mathbf{0} \Rightarrow \mathbb{P}(e(k) \in \mathcal{R}^p) \ge p, \ \forall k \ge 0.$$
(11)

The above definition states that a PRS of probability level p will contain at any time instance k the accumulating error e(k) with at least probability p, if the initial error satisfies e(0) = 0. Multiple approaches exist to obtaining an explicit form for any given PRS; see [5], [8]. As in [5], we consider the ellipsoidal explicit representation based on the multivariate Chebyshev inequality;

$$\mathcal{R}^p = \{ x \in \mathbb{R}^n \mid x^T \Sigma_{\infty}^{-1} x \le \tilde{p} \},$$
(12)

where Σ_{∞} solves the Lyapunov equation $A_K \Sigma_{\infty} A_K^T + \operatorname{var}(\mathcal{Q}_w) = \Sigma_{\infty}$ and $\tilde{p} = \chi_n^2(p)$ where $\chi_n^2(\cdot)$ is the inverse cumulative distribution function of the chi-squared distribution with *n* degrees of freedom. Since the variance of \mathcal{Q}_w is strictly positive definite and A_K is stable, Lyapunov theory states a strictly positive definite Σ_{∞} exists [19].

B. Tightening the Chance Constraints

Based on the probabilistic reachable sets \mathcal{R}^p , we can decompose and tighten the chance constraints (9a) on z(k) + e(k) into a constraint for the error dynamics e(k) and a constraint for the nominal state z(k), since

$$\mathbb{P}(z(k)+e(k)\in\mathcal{X})\geq\mathbb{P}(z(k)\in\mathcal{X}\oplus\mathcal{R}_x\wedge e(k)\in\mathcal{R}_x)\geq p_x,$$

if $\mathcal{R}_x := \mathcal{R}^{p_x}$ (c.f. (12)) and $\mathbb{P}(z(k) \in \mathcal{X} \ominus \mathcal{R}_x) = 1$. The result is the deterministic constraint $z(k) \in \mathcal{X} \ominus \mathcal{R}_x$ on the nominal state. Similarly, we can decompose and tighten the chance constraint (9b) on v(k) + Ke(k) into a deterministic constraint on v(k). All in all, the chance constraints can be replaced by the deterministic constraints

$$z(k) \in \mathcal{Z} := \mathcal{X} \ominus \mathcal{R}_x, \ \mathcal{R}_x = \mathcal{R}^{p_x},$$
(13a)

$$v(k) \in \mathcal{V} := \mathcal{U} \ominus K\mathcal{R}_u, \ \mathcal{R}_u = \mathcal{R}^{p_u}.$$
 (13b)

Note that we can replace PRS $K\mathcal{R}_u$ with the set $\mathcal{R}_u^K = \{x \in \mathbb{R}^n \mid x^T K^T \Sigma_{\infty}^{-1} K x \leq \tilde{p}_u\}$, with $\tilde{p}_u = \chi_n^2(p_u)$. We note that set \mathcal{R}_u^K satisfies $Ke(0) = \mathbf{0} \implies \mathbb{P}(Ke(k) \in \mathcal{R}_u^K) \geq p_u, \forall k \geq 0$ and is therefore a valid alternative to PRS $K\mathcal{R}_u$. Details can be found in [5].

In the sequel, we will compute with (13a) as though $\mathbb{P}(z(k) \in \mathcal{Z}) = p_z = 1$. However, we would like to remark that probability p_z can be relaxed if $\mathcal{R}_x = \mathcal{R}^{p_e}$ with $p_e p_z \ge p_x$. The same holds for the nominal input v(k).

C. Branching Control of the Nominal Dynamics

With tightening ensuring that the error dynamics (6b) and chance constraints (9) can be converted into deterministic constraints (13), all that remains is the discrete distribution present in the nominal dynamics (6a). To handle this, we consider branching the control strategy for each realization of the nominal disturbance and ensuring that each control strategy branch is suitable. To synthesize a control strategy for each branch, we consider a tube-based MPC framework.

Under the assumption of a finite time horizon N and a finite set of nominal disturbances given by $\mathbb{W} :=$ $\{\mu_1, \dots, \mu_p\}$, we design a finite tree of p^N branches, where each branch represents a potential control strategy. Each strategy corresponds to a unique sequence $\{\mu_{i_1}, \dots, \mu_{i_N}\}$, $i_j \in \{1, \dots, p\}$, capturing all nominal disturbance behaviour of length N. A visualization of the tree is given in Fig. 4.

We denote for any vector or scalar of sequences s(k), the corresponding predicted value of s(k+i) by $s_i(k)$. Regarding the branch superscript, we follow the pattern illustrated in Fig. 4. To synthesize a control strategy for each branch, we define the following tube-based MPC problem.

$$\min_{\bar{z}(k), \bar{v}(k), \xi(k)} \quad J(\bar{z}(k), \bar{v}(k)) + \epsilon \xi(k)^2$$
(14a)



Fig. 4. An illustration of the branching approach. Each branch is a potential control strategy, corresponding to a realization of $Q_w^x \otimes \cdots \otimes Q_w^x$.

s.t.
$$z_{i+1}^{(j-1)p+d}(k) = A z_i^j(k) + B v_i^j(k) + \mu_d,$$
 (14b)

$$z_i^j(k) \in \mathcal{Z}, \ v_i^j(k) \in \mathcal{V}, \ z_N^l(k) \in \mathcal{Z}_f,$$
 (14c)

$$z_0^1(k) = (1 - \xi(k))x(k) + \xi(k)z_1^c(k-1),$$
(14d)

$$\xi(k) \in \{0, 1\}, \ \forall i \in \{0, \dots, N-1\},$$
(14e)

$$\forall d \in \{1, \dots, p\}, \forall j \in \{1, \dots, p^i\}, \forall l \in \{1, \dots, p^N\},$$

where $\bar{z}(k) := \{z_0^1(k), z_1^1(k), \cdots, z_N^{p^N}(k)\}$ and $\bar{v}(k) := \{v_0^1(k), v_1^1(k), \cdots, v_{N-1}^{p^{N-1}}(k)\}$ are sequences of nominal states and inputs, as observed in Fig. 4; $z_1^c(k-1)$ is the previously computed nominal state and $z_1^c(-1) = x(0)$; J is a linear or quadratic function; and \mathcal{Z}_F is the terminal set.

The terminal set, with respect to input v(k) = Kz(k), must satisfy $(A + BK)\mathcal{Z}_F \oplus \mathbb{W} \subseteq \mathcal{Z}_F \subseteq \mathcal{Z}$ and $K\mathcal{Z}_F \subseteq \mathcal{V}$ to ensure recursive feasibility. Should set \mathcal{Z} and \mathcal{V} be (underapproximated by) polyhedral sets, a terminal set \mathcal{Z}_F can be obtained from [6, Thm. 3.1]. A more general algorithm to compute the terminal set is given by [20, Alg. 10.4]. The choice of initial state $z_0^1(k)$ comes from the idea put forward in [8]. Therein, both the real measurement x(k) and the previously computed nominal state $z_1^c(k-1)$ can become the current initial state, again to ensure recursive feasibility.

Remark 1: The number of optimization variables in MPC problem (14) grows exponentially with the number of mixture components and the time horizon. In future work, we opt to reduce the complexity. To accomplish this, we consider the work by [21], wherein the growth can be reduced to (potentially) quadratic under the assumption of polyhedral nominal set constraints. However, only a single control strategy will be synthesized for all branches, leading to a conservative control strategy. An alternative second approach considers the mixed logic dynamical framework described in [22]. This framework, too, can potentially reduce the complexity at the cost of solving a mixed integer quadratic programming problem. A third approach considers scenario MPC, which fixes the disturbance after a specified time [23], reducing the number of branches. In addition to the previously mentioned approaches, we might also consider removing branches, thereby reducing the probability of $\mathbb{P}(z(k) + \mathcal{R}_x \subseteq \mathcal{X})$ and $\mathbb{P}(v(k) + K\mathcal{R}_x \subseteq \mathcal{U})$. To ensure the satisfaction of (9), the trade-off implies tighter constraints (13).

V. IMPLEMENTATION & CLOSED-LOOP GUARANTEES

In this section, we determine a recursive model predictive control synthesis algorithm for the original system via controller refinement and a control strategy synthesized on the abstract system. Additionally, we establish that the closedloop original system will satisfy the chance constraints (3).

We first consider the following theorem regarding the recursive feasibility of the tube-based MPC problem (14).

Theorem 7 (Recursive Feasibility): The tube-based MPC problem (14) has a solution for all time $k \in \mathbb{N}$, assuming that a solution exists at time k = 0.

Proof: Considering proof by induction, we assume

$$\bar{z}(k) = \{z_0^1(k), z_1^1(k), \cdots z_N^{p^N}(k)\},\$$

$$\bar{v}(k) = \{v_0^1(k), v_1^1(k), \cdots v_{N-1}^{p^{N-1}}(k)\},\$$

is a solution of (14) at time k, and, without loss of generality, that $z_1^c(k) = z_1^j(k)$. We take $\xi(k+1) = 1$, and $\overline{z}(k+1)$ and $\overline{v}(k+1)$ to be defined by the following set of relations.

$$z_0^1(k+1) = z_1^j(k), (15a)$$

$$z_i^{(l-1)p+d}(k+1) = z_{i+1}^{(j-1)p^i + (l-1)p+d}(k),$$
(15b)

$$z_N^{(l-1)p+d}(k+1) = A_K z_{N-1}^l(k+1) + \mu_d, \ i = N, \ (15c)$$

$$v_0^1(k+1) = v_1^j(k),$$
 (15d)

$$v_{i}^{(l-1)p+d}(k+1) = v_{i+1}^{(j-1)p^{+}+(l-1)p+d}(k),$$
(15e)

$$v_{N-1}^{t}(k+1) = K z_{N-1}^{t}(k+1), \ i = N,$$
 (15f)

for $l \in \{1, \dots, p^{i-1}\}$, $i \in \{1, \dots, N-1\}$ and $d \in \{1, \dots, p\}$. When considering the tree at time k, prefixes (15b) and (15e) represent, respectively, the nominal state and input corresponding to the sub-tree with origin $z_1^j(k)$.

We note that $\bar{z}(k + 1)$, $\bar{v}(k + 1)$ and $\xi(k + 1)$ satisfy conditions (14b), (14d) and (14e) trivially at time k + 1. Similarly, condition (14c) is trivially satisfied for all $i \in$ $\{0, \dots, N-2\}$. Regarding i = N - 1 and the terminal set constraint, satisfaction is a result of the conditions $(A + BK)\mathcal{Z}_F \oplus \mathbb{W} \subseteq \mathcal{Z}_F \subseteq \mathcal{Z}$ and $K\mathcal{Z}_F \subseteq \mathcal{V}$, and the observation that $z_{N-1}^l(k+1) \in \mathcal{Z}_F$ for all $l \in \{1, \dots, p^{N-1}\}$. Thus, a solution for MPC problem (14) exists at time k + 1if a solution exists at time k. This finishes the proof.

An algorithm displaying the control implementation on the original system is given below. Herein, it is explained how to recursively control the original system (1) via controller refinement and control synthesis on the abstract system (6).

Algorithm	1	Implementation	Algorithm
		1	0

- 1: Given: Dynamics (1), x(0), \mathcal{X} , \mathcal{U} , p_x , p_u , $J(\cdot)$, and ϵ
- 2: Construct \mathcal{R}_x and \mathcal{R}_u and compute \mathcal{Z}, \mathcal{V} and \mathcal{Z}_F
- 3: for each time instance $k \in \mathbb{N}$ do
- 4: Solve (14) to obtain $z_0^1(k)$ and $v_0^1(k)$
- 5: Compute e(k) from (6b) and u(k) from (7)
- 6: Obtain x(k+1) and compute w(k) from (1)
- 7: Draw $\mu_i = w_x$ from (10) and set $z_1^c(k) = z_1^j(k)$
- 8: end for

The following proposition establishes satisfaction of the chance constraints (9) for the closed-loop abstract system.

Proposition 8 (PRS for closed-loop error): Let \mathcal{R} be a convex symmetric set. For system (6) under the control input $v(k) = v_0^1(k)$ resulting from Alg. 1, we have that

$$\mathbb{P}(e_0(k) \in \mathcal{R}) \ge \mathbb{P}(e_k(0) \in \mathcal{R}), \quad \forall k \ge 0.$$
 (16)

The proof of Prop. 8 can be found in [8, Thm. 3]. Though [8] does not consider a branching control strategy, the result of [8, Thm. 3] remains valid within the current framework as its proof remains accurate regardless of which control strategy branch is implemented at each time instance. This is because the proof regards only the error dynamics, which remain consistent with [8] within this paper. The proposition implies that $\mathbb{P}(e(k) \in \mathcal{R}_x) \ge p_x$ and $\mathbb{P}(Ke(k) \in \mathcal{R}_u) \ge p_u$, $\forall k \in \mathbb{N}$. Hence, the abstract system under the control input $v(k) = v_0^1(k)$ resulting from Alg. 1 satisfies chance constraints (9). Consequently, we have the following corollary, the proof of which follows from Prop. 5.

Corollary 9: System (1) under the control law resulting from Alg. 1 will satisfy the chance constraints (3).

VI. CASE STUDY

To illustrate that our control synthesis algorithm allows for the satisfaction of the chance constraints, we consider a vehicle control case study in which the vehicle must maintain its position on an ill-maintained road. The vehicle's position on the road is defined by a one-dimensional disturbed integrator dynamical system given by x(k+1) =x(k) + u(k) + w(k) where $w(k) \sim \mathcal{M}(\boldsymbol{\mu}, \boldsymbol{\pi}, \boldsymbol{\Sigma})$ represents the vehicle's deviation as a result of the road's condition. We assume that $\mu = \{-1.5, 0, 1.5\}, \pi = \{0.2, 0, 3, 0.5\}$ and $\Sigma = 0.25$. The road is split into an inner and outer part, each of which the vehicle must remain within with a certain probability. The inner road is defined by a convex set $\mathcal{X}_{Inn} = \{x \mid -2 \leq x \leq 2\}$ and the target lower bound $p_{Inn} = 0.6$. The outer road is defined by a convex set $\mathcal{X}_{Out} = \{x \mid -3 \leq x \leq 3\}$ and the target lower bound $p_{Out} = 0.99$. Additionally, the velocity of the vehicle is also restricted. This restriction is represented on the input space via the convex set $\mathcal{U} = \{u \mid -2 \leq u \leq 2\}$ and the target lower bound $p_u = 0.65$.



Fig. 5. A line graph showing a few trajectories of the vehicle. Each trajectory corresponds to different realizations of the Gaussian mixture.



Fig. 6. A bar graph of the percentage of constraint violations after 1000 simulations. The lines indicate the upper bounds of the road and velocity violations in accordance with the target lower bounds.

We consider a total horizon of 10 steps and an MPC horizon of 5 steps. After simulating 1000 control strategies for differing realizations of the Gaussian mixture disturbance, we obtain the above graphs regarding the vehicle's behaviour and the number of constraint violations. As can be extrapolated from the graphs, the vehicle satisfies the inner road, outer road and velocity constraints with at least probability equal to the target lower bounds. Moreover, it can be inferred that the control strategies are conservative as all chance constraints are easily met. Based on the data, the inner road chance constraint would be satisfied with probability 0.86, the outer road with probability 0.99 and the velocity with probability 0.89.

VII. CONCLUSION

In conclusion, we addressed the control synthesis problem for linear systems subject to additive Gaussian mixture disturbances to satisfy chance constraints while preserving key properties such as recursive feasibility and closed-loop guarantees. This was achieved by formulating an abstract system, redefining the stochastic control problem onto the abstract system, and reformulating the redefined stochastic control problem into a tube-based MPC framework. A branching control strategy was employed to solve the resulting MPC problem. Our main contribution is the extension of the SMPC methods towards Gaussian mixtures. While our method does contain conservativeness, we want to emphasise that this is partially inhered from the MPC reformulation of the redefined stochastic control problem. Future research may enhance the framework by considering or developing more computationally efficient methods to solve the MPC problem.

REFERENCES

- X. Guo, S. Hou, P. Niu, and D. Zhao, "A review of control methods for quadrotor UAVs," in 5th International Conference on Electronics and Electrical Engineering Technology, 2022, pp. 132–138.
- [2] A. Mesbah, "Stochastic model predictive control: An overview and perspectives for future research," *IEEE Control Systems Magazine*, vol. 36, no. 6, pp. 30–44, 2016.
- [3] M. Farina, L. Giulioni, and R. Scattolini, "Stochastic linear model predictive control with chance constraints-a review," *Journal of Process Control*, vol. 44, pp. 53–67, 2016.
- [4] A. Mesbah, "Stochastic model predictive control with active uncertainty learning: A survey on dual control," *Annual Reviews in Control*, vol. 45, pp. 107–117, 2018.

- [5] L. Hewing, K. P. Wabersich, and M. N. Zeilinger, "Recursively feasible stochastic model predictive control using indirect feedback," *Automatica*, vol. 119, p. 109095, 2020.
- [6] B. Kouvaritakis and M. Cannon, *Model Predictive Control.* Springer International Publishing, 2016.
- [7] T. A. N. Heirung, J. A. Paulson, J. O'Leary, and A. Mesbah, "Stochastic model predictive control—how does it work?" *Computers & Chemical Engineering*, vol. 114, pp. 158–170, 2018.
- [8] L. Hewing and M. N. Zeilinger, "Stochastic model predictive control for linear systems using probabilistic reachable sets," in *IEEE Conference on Decision and Control*, 2018, pp. 5182–5188.
- [9] C. Mark and S. Liu, "Distributed stochastic model predictive control for dynamically coupled linear systems using probabilistic reachable sets," in 18th European Control Conference, 2019, pp. 1362–1367.
- [10] H. Schlüter and F. Allgöwer, "Stochastic model predictive control using initial state optimization," *IFAC-PapersOnLine*, vol. 55, no. 30, pp. 454–459, 2022.
- [11] M. H. W. Engelaar, S. Haesaert, and M. Lazar, "Stochastic model predictive control with dynamic chance constraints," in 27th International Conference on System Theory, Control and Computing, 2023, pp. 356–361.
- [12] I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*. MIT Press, 2016.
- [13] V. Maz'ya and G. Schmidt, "On approximate approximations using gaussian kernels," *IMA Journal of Numerical Analysis*, vol. 16, no. 1, pp. 13–29, 1996.
- [14] J. Coulson, J. Lygeros, and F. Dörfler, "Distributionally robust chance constrained data-enabled predictive control," *IEEE Transactions on Automatic Control*, vol. 67, no. 7, pp. 3289–3304, 2021.
- [15] P. Mohajerin Esfahani and D. Kuhn, "Data-driven distributionally robust optimization using the wasserstein metric: Performance guarantees and tractable reformulations," *Mathematical Programming*, vol. 171, no. 1, pp. 115–166, 2018.
- [16] F. Weissel, M. F. Huber, and U. D. Hanebeck, "Stochastic nonlinear model predictive control based on gaussian mixture approximations," in *Informatics in Control, Automation and Robotics: Selected Papers* from the International Conference on Informatics in Control, Automation and Robotics 2007, 2009, pp. 239–252.
- [17] D. Bertsekas and S. E. Shreve, Stochastic optimal control: the discretetime case. Athena Scientific, 1996, vol. 5.
- [18] S. Haesaert, S. E. Zadeh Soudjani, and A. Abate, "Verification of general markov decision processes by approximate similarity relations and policy refinement," *SIAM Journal on Control and Optimization*, vol. 55, no. 4, pp. 2333–2367, 2017.
- [19] B. Datta, *Numerical methods for linear control systems*. Elsevier, 2004.
- [20] F. Borrelli, A. Bemporad, and M. Morari, *Predictive control for linear and hybrid systems*. Cambridge University Press, 2017.
- [21] P. J. Goulart, E. C. Kerrigan, and J. M. Maciejowski, "Optimization over state feedback policies for robust control with constraints," *Automatica*, vol. 42, no. 4, pp. 523–533, 2006.
- [22] A. Bemporad and M. Morari, "Predictive control of constrained hybrid systems," in *Nonlinear model predictive control*. Springer, 2000, pp. 71–98.
- [23] S. Lucia, T. Finkler, and S. Engell, "Multi-stage nonlinear model predictive control applied to a semi-batch polymerization reactor under uncertainty," *Journal of process control*, vol. 23, no. 9, pp. 1306–1319, 2013.