Oblique Bayesian additive regression trees

Paul-Hieu V. Nguyen^{*}

Ryan Yee[†]

Sameer K. Deshpande[‡]

November 14, 2024

Abstract

Current implementations of Bayesian Additive Regression Trees (BART) are based on axisaligned decision rules that recursively partition the feature space using a single feature at a time. Several authors have demonstrated that oblique trees, whose decision rules are based on linear combinations of features, can sometimes yield better predictions than axis-aligned trees and exhibit excellent theoretical properties. We develop an oblique version of BART that leverages a data-adaptive decision rule prior that recursively partitions the feature space along random hyperplanes. Using several synthetic and real-world benchmark datasets, we systematically compared our oblique BART implementation to axis-aligned BART and other tree ensemble methods, finding that oblique BART was competitive with — and sometimes much better than — those methods.

1 Introduction

1.1 Motivation

Tree-based methods like CART (Breiman et al., 1984), random forests (RF; Breiman, 2001), and gradient boosted trees (GBT; Friedman, 2001) are widely used and extremely effective machine learning algorithms. These methods are simple to train and tune and typically deliver very accurate predictions (Hastie and Friedman, 2005, §9.2).

Compared to these models, the Bayesian Additive Regression Trees (BART; Chipman et al., 2010) model is used much less frequently in the wider machine learning community. Like RF and GBT, BART approximates unknown functions using regression tree ensembles. But unlike RF and GBT, BART is based on a fully generative probabilistic model, which facilitates natural uncertainty quantification (via the posterior) and allows it to be embedded within more complex statistical models. For instance, BART has been extended to models for survival (Sparapani et al., 2016; Linero et al., 2022) and semi-continuous (Linero et al., 2020) outcomes; conditional density regression (Orlandi et al., 2021; Li et al., 2023b); non-homogeneous point process data (Lamprinakou et al., 2023); regression with heteroskedastic errors (Pratola et al., 2020); and integrating predictions from multiple models (Yannotty et al., 2024a,b). BART and its extensions typically return accurate predictions and well-calibrated uncertainty intervals without requiring users to specify the functional form of

^{*}Department of Statistics, University of Wisconsin-Madison. pvnguyen5@wisc.edu

[†]Department of Statistics, University of Wisconsin-Madison. ryee2@wisc.edu

[‡]Department of Statistics, University of Wisconsin-Madison. sameer.deshpande@wisc.edu

the unknown function and without hyperparameter tuning. Its ease-of-use and generally excellent performance make BART an attractive "off-the-shelf" modeling tool, especially for estimating heterogeneous causal effects (Hill, 2011; Dorie et al., 2019; Hahn et al., 2020).

Virtually every implementation of RF, GBT, and BART utilizes axis-aligned regression trees, which partition the underlying predictor space into rectangular boxes (Figure 1a) and correspond to piecewise constant step functions. Although step functions (i.e., regression trees) are universal function approximators, several authors have proposed modifications to make regression trees even more expressive and flexible. One broad class of modifications replaces the constant output in each leaf node with simple parametric models (e.g., Quinlan, 1992; Landwehr et al., 2005; Chan and Loh, 2004; Künzel et al., 2022) or nonparametric models (e.g., Gramacy and Lee, 2008; Starling et al., 2020; Maia et al., 2024). Another broad class involves the use of "oblique" decision rules, which allow trees to partition the predictor space along arbitrary hyperplanes (see, e.g., Figure 1b). As we detail in Section 2.1, several authors have found that oblique trees and ensembles thereof often outperform their axis-aligned counterparts in terms of prediction accuracy. For instance, Bertsimas and Dunn (2017) reported oblique decision trees can outperform CART by 7% while Breiman (2001) noted that an oblique version of RF can improve performance by up to 8.5%. Beyond these empirical results, Cattaneo et al. (2024) recently demonstrated that oblique decision trees and their ensembles can sometimes obtain the same convergence rates as neural networks. To the best of our knowledge, however, there has been no systematic exploration of oblique trees in the Bayesian setting.



Figure 1: Example of step functions defined over $[-1,1]^2$ and their corresponding axis-aligned (a) and oblique (b) regression tree representations.

1.2 Our contributions

In this work, we introduce obliqueBART and systematically compare its predictive ability to the original BART model and several other tree-based methods. As a preview of the promise of oblique-BART, consider the functions in Figures 2a and 2d. Although these functions are extremely simple, outputting only two values, their discontinuities are not closely aligned with the coordinate axes. Although axis-aligned BART captures the general shape of the decision boundaries, it requires very deep trees to do so and inappropriately smoothes over the functions' sharp discontinuities (Figures 2b and 2e). obliqueBART, in sharp contrast, recovers the boundaries much more precisely and with shallower trees (Figures 2c and 2f). We will return to these examples in Section 4.1.



Figure 2: True function (a,d), axis-aligned BART estimate (b,e), and obliqueBART estimate (c,f).

The rest of the paper is organized as follows. In Section 2, we review the literature on oblique trees in the frequentist setting and briefly review the basic axis-aligned BART model. In Section 3, we introduce our prior on oblique decision rules and discuss our implementation of obliqueBART. We compare the performance of obliqueBART to axis-aligned BART and several popular tree-based machine learning models across a range of synthetic and benchmark datasets in Section 4. We discuss potential extensions and further refinements in Section 5.

2 Background

Before reviewing existing oblique tree models (Section 2.1) and BART (Section 2.2), we introduce some notation and briefly review existing methods like RF and GBT. For simplicity, we focus on the standard nonparametric regression problem with continuous predictors: given *n* observations $(\boldsymbol{x}_1, y_1), \ldots, (\boldsymbol{x}_n, y_n)$ with $\boldsymbol{x}_i \in [-1, 1]^p$ from the model $\boldsymbol{y} \sim \mathcal{N}(f(\boldsymbol{x}), \sigma^2)$, we wish to recover the unknown function *f* and residual variance σ^2 . A *decision tree* over $[-1, 1]^p$ is a pair $(\mathcal{T}, \mathcal{D})$ containing (i) a binary tree \mathcal{T} that contains several terminal or *leaf* nodes and several non-terminal or *decision* nodes and (ii) a collection of decision rules \mathcal{D} , one for each decision node in \mathcal{T} . Axisaligned decision rules take the form $\{X_j < c\}$ while oblique decision rules take the form $\{\phi^{\top}\boldsymbol{x} < c\}$ where $\phi \in \mathbb{R}^p$. Notice that axis-aligned rules form a subset of all oblique rules. Given a decision tree $(\mathcal{T}, \mathcal{D})$, for each point $\boldsymbol{x} \in [-1, 1]^p$, we can trace a path from the root to a unique leaf as follows. For axis-aligned trees (resp. oblique trees), starting from the root, whenever the path reaches a node with decision rule $\{X_j < c\}$ (resp. $\{\phi^\top \boldsymbol{x} < c\}$), the path proceeds to the left if $x_j < c$ (resp. $\phi^\top \boldsymbol{x} < c$) and to the right otherwise. We let $\ell(\boldsymbol{x}; \mathcal{T}, \mathcal{D})$ denote the leaf reached by \boldsymbol{x} 's decision-following path. By associating a scalar μ_ℓ to each leaf in \mathcal{T} , the regression tree $(\mathcal{T}, \mathcal{D}, \mathcal{M})$ represents a piecewise constant step function over $[-1, 1]^p$. Given a regression tree $(\mathcal{T}, \mathcal{D}, \mathcal{M})$, we denote the evaluation function that returns the scalar associated to the leaf reached by \boldsymbol{x} as $g(\boldsymbol{x}; \mathcal{T}, \mathcal{D}, \mathcal{M}) = \mu_{\ell(\boldsymbol{x}; \mathcal{T}, \mathcal{D})}$.

In the nonparametric regression problem, CART estimates a single regression tree such that $f(\boldsymbol{x}) \approx g(\boldsymbol{x}; \mathcal{T}, \mathcal{D}, \mathcal{M})$ using an iterative approach. After initializing \mathcal{T} as the root node, CART visits every current leaf node, finds an optimal decision rule for that leaf, and attaches two children to the leaf, turning it into a decision node. This process continues until each leaf contains a single observation. Typically CART trees are pruned back according to a cross-validation criterion. At each step, CART exhaustively searches for the optimal decision rule using a variance reduction criteria. See Hastie and Friedman (2005, §9.2) for an overview of the CART algorithm.

RF, GBT, and BART instead learn a collection (or *ensemble*) of M regression trees $\mathcal{E} = \{(\mathcal{T}_m, \mathcal{D}_m, \mathcal{M}_m)\}$ such that $f(\boldsymbol{x}) \approx \sum_{m=1}^{M} g(\boldsymbol{x}; \mathcal{T}_m, \mathcal{D}_m, \mathcal{M}_m)$. These methods differ significantly in how they learn the ensemble \mathcal{E} .

RF estimates each tree in \mathcal{E} using independent bootstrap sub-samples of the training data. Each tree in an RF ensemble is trained using an iterative procedure similar to CART. However, instead of exhaustively searching over p features, at each iteration, RF identifies the optimal rule over a random subset of features. When the number of training observations n is very large, each treegrowing iteration of RF can be slow, as it involves searching over all possible cutpoints for the randomly selected features. The Extremely Randomized Trees (ERT) procedure of Geurts et al. (2006) overcomes this limitation by randomizing both the splitting variable and cutpoint. That is, in each iteration, ERT draws a small collection of splitting variable and cutpoint pairs and then finds the optimal rule among this small collection. ERT also differs from RF in that each tree is trained using the whole sample, rather than independent bootstrap re-samples. Typically, the trees in an RF or ERT ensemble are un-pruned.

GBT, on the other hand, trains the trees sequentially, with each tree trained to predict the residuals based on all preceding trees. Specifically for each m, GBT trains $(\mathcal{T}_m, \mathcal{D}_m, \mathcal{M}_m)$ to predict the residuals $y_i - \sum_{m'=1}^{m-1} g(\mathbf{x}_i; \mathcal{T}_{m'}, \mathcal{D}_{m'}, \mathcal{M}_{m'})$. Unlike CART, RF, and ERT, trees in a GBT ensemble are constrained to have a fixed depth, typically three or less. Although BART shares some algorithmic similarities with ERT and GBT, there are crucial differences, which we will exploit when developing obliqueBART.

2.1 Inducing oblique trees

Conceptually, extending CART to use oblique rules seems straightforward: one need only find an optimal direction ϕ and cutpoint c that most decreases the variance of the observed responses that reach a given node. Unfortunately, the resulting optimization problem is extremely challenging; in the case of classification, the problem is NP-complete (Heath et al., 1993, Theorem 2.1). Consequently, researchers rely on heuristics to build oblique trees and ensembles thereof. These heuristics fall into three broad classes. The first class of heuristics are model-based: at each decision node,

one selects ϕ after fitting an intermediate statistical model and then finds an optimal cutpoint for the feature $\phi^{\top} x$. For instance, Menze et al. (2011) set ϕ to be the parameter estimated by fitting a ridge regression at each decision node. Zhang and Suganthan (2014) and Rainforth and Wood (2015) instead performed linear discriminant, principal component, and canonical correlation analyses at each decision node to determine ϕ . Compared to the axis-aligned random forests, ensembles of these model-based oblique trees respectively improved prediction accuracy by 20%, 2.9%, and 28.7%.

The second class of heuristics involve randomization: instead of searching over all possible directions ϕ , one draws a collection of D random directions ϕ_1, \ldots, ϕ_D ; computes D new features $\phi_1^{\top} \boldsymbol{x}, \ldots, \phi_D^{\top} \boldsymbol{x}$; and then identifies the optimal axis-aligned rule among these new features. Notable examples of randomization-based approaches are Breiman (2001), Blaser and Fryzlewicz (2016), Tomita et al. (2020), and Li et al. (2023a), which differ primarily in the distribution used to draw the candidate directions ϕ_1, \ldots, ϕ_D . Breiman (2001), for instance, restricted the ϕ_d 's to have k non-zero elements drawn uniformly from [-1, 1]. The resulting random combination forests algorithm had out-of-sample errors 3% to 8.5% lower than the errors of axis-aligned random forests. By allowing a variable number of non-zero entries in ϕ_d but restricting those entries to ± 1 , Tomita et al. (2020) obtained similar performance gains.

Methods based on the first two classes of heuristics estimate or propose new oblique rules in each iteration of the tree growing procedure. An alternative strategy involves pre-computing a large number of feature rotations or projections and then training a standard model using the newly-constructed features. Rodriguez et al. (2006), for instance, combine a PCA pre-processing step with the standard random forest algorithm. Blaser and Fryzlewicz (2016) instead generate a large number of randomly rotated features before building a random forest ensemble. Their random rotation random forest method outperformed axis-aligned methods in about two-third of their experiments.

Before proceeding, it is worth mentioning Bertsimas et al. (2021) does not utilize model- or randomization-based heuristics to grow oblique trees. They instead find optimal oblique decision rules using mixed-integer programming. Their procedure, however, restricts the depth and structure of the tree \mathcal{T} a priori, is generally not scalable beyond depth three, and led to small increases in the predictive \mathbb{R}^2 .

2.2 Review of BART

Like RF, ERT, and GBT, BART expresses the unknown regression function $f(\boldsymbol{x})$ with an ensemble of trees $\mathcal{E} = \{(\mathcal{T}_m, \mathcal{D}_m, \mathcal{M}_m)\}$. Unlike these methods, which learn only a single ensemble, BART computes an entire posterior distribution over tree ensembles. Since the posterior is analytically intractable, BART uses Markov chain Monte Carlo (MCMC) to simulate posterior samples.

The BART prior. Key to BART's empirical success is its regularizing prior over the regression tree ensemble. BART models each tree $(\mathcal{T}_m, \mathcal{D}_m, \mathcal{M}_m)$ as a priori independent and identically distributed. We can describe the regression tree prior compositionally by explaining how to sample from it. First, we draw the tree structure \mathcal{T} by simulating a branching process. Starting from the root node, which is initially treated as a terminal node at depth 0, whenever a terminal node at depth d is created, the process attaches two child nodes to it with probability $\alpha(1+d)^{-\beta}$. Then, at each decision node, decision rules of the form $\{X_i < c\}$ are drawn conditionally on the rules at the nodes' ancestors. Drawing a decision rule involves (i) uniformly selecting the splitting axis j; (ii) computing the interval of valid values of X_j at the current tree node; and (iii) drawing the cutpoint c uniformly from this interval. The set of valid X_j values at any node is determined by the rules at the node's ancestors in \mathcal{T} . For instance in Figure 1a, if we were to draw a decision rule at node 5, [-1, 0.4] is the set of valid X_1 values and [0.2, 1] is the set of valid X_2 values. Finally, conditionally on \mathcal{T} , the leaf outputs in \mathcal{M} are drawn independently from a $\mathcal{N}(0, \tau^2/\mathcal{M})$ distribution.

Chipman et al. (2010) completed their prior by specifying $\sigma^2 \sim \text{Inv. Gamma}(3/2, 3\lambda/2)$. They further recommended default values for each prior hyperparameter. They suggested setting $\alpha =$ 0.95 and $\beta = 2$, so that the branching process prior concentrates considerable prior probability on trees of depth less than 5. For any \boldsymbol{x} , the marginal prior for $f(\boldsymbol{x})$ is $\mathcal{N}(0, \tau^2)$. Chipman et al. (2010) recommended setting τ so that this marginal prior places 95% probability over the range of the observed data. They similarly recommended setting λ so that there was 90% prior probability on the event that σ was less than the standard deviation of the observed outcome. Finally, they recommended setting M = 200. Although some of these choices are somewhat *ad hoc* and datadependent, they have proven tremendously effective across a range of datasets.

Posterior sampling. To simulate draws from the tree ensemble posterior, Chipman et al. (2010) introduced a Metropolis-within-Gibbs sampler. In each iteration, the sampler sweeps over the entire ensemble and sequentially updates each regression tree $(\mathcal{T}_m, \mathcal{D}_m, \mathcal{M}_m)$ conditionally fixing the remaining M - 1 trees. Each regression tree update consists of two steps. First, a new decision tree $(\mathcal{T}, \mathcal{D})$ is drawn from its conditional distribution given the data, σ , and all other regression trees in the ensemble. Then, new leaf outputs \mathcal{M} are drawn conditionally given the new decision tree, the data, σ , and the remaining regression trees. In the standard nonparametric regression setting, the leaf outputs are conditionally independent given the tree structure, which allows us to draw \mathcal{M} with standard normal-normal conjugate updates. Most implementations of BART update the decision tree $(\mathcal{T}, \mathcal{D})$ by first drawing a new decision tree from a proposal distribution and accepting that proposal with a Metropolis-Hastings step. The simplest proposal distribution involves randomly growing or pruning $(\mathcal{T}, \mathcal{D})$ with equal probability.

In each MCMC iteration, BART updates each regression tree *conditionally* fixing the other trees in the ensemble \mathcal{E} . Consequently, each individual regression tree in a BART ensemble does not attempt to estimate the true regression function well. Instead, like GBT, each tree is trained to fit a *partial residual* based on the fits of other tres. However, unlike GBT, which trains trees sequentially, each tree in the BART ensemble is dependent on every other tree *a posteriori*. This is in sharp contrast to RF and ERT, which independently train each tree to predict the outcome using a bootstrap sample (RF) or full training data (ERT).

BART is, nevertheless, similar to ERT, insofar as both methods grow trees using *random* decision rules. Recall that at each iteration, ERT grows a tree by selecting the best decision rule among a small collection of random proposals. BART, on the other hand, uses a Metropolis-Hastings step to accept or reject a single random proposal. As a result, BART can sometimes grow a tree with a rule that does not significantly improve overall fit to data or remove a split that does. Thus, unlike CART, RF, ERT, and GBT, we cannot regard the decision rules appearing in a BART ensemble as optimal in any sense.

3 BART with oblique decision rules

We are now ready to describe our proposed obliqueBART. For ease of exposition, we describe obliqueBART for regression. For binary classification, we follow Chipman et al. (2010) and use the standard Albert and Chib (1993) data augmentation for probit regression.

Suppose that we observe *n* pairs $(\boldsymbol{x}_1, y_1), \ldots, (\boldsymbol{x}_n, y_n)$ of *p*-dimensional vectors of predictors \boldsymbol{x} and scalar outcomes *y* from the model $y \sim \mathcal{N}(f(\boldsymbol{x}), \sigma^2)$. Further suppose that we have p_{cont} continuous predictors and $p_{\text{cat}} = p - p_{\text{cont}}$ categorical predictors. Without loss of generality, we will arrange continuous predictors first; assume that all continuous predictors lie in interval $[-1, 1]^{p_{\text{cont}}}$; and that the *j*-th categorical predictor lies in a discrete set \mathcal{K}_j . That is, we assume that all predictor vectors $\boldsymbol{x} = (\boldsymbol{x}_{\text{cont}}^{\top}, \boldsymbol{x}_{\text{cat}}^{\top})^{\top}$ lie in the product space $[-1, 1]^{p_{\text{cont}}} \times \mathcal{K}_1 \times \cdots \times \mathcal{K}_{p_{\text{cat}}}$.

Oblique BART expresses the unknown regression function $f(\mathbf{x})$ with an ensemble of M regression trees $\mathcal{E} = \{(\mathcal{T}_1, \mathcal{D}_1, \mathcal{M}_1), \dots, (\mathcal{T}_M, \mathcal{D}_M, \mathcal{M}_M)\}$ whose decision rules take the form $\{\phi^{\top}\mathbf{x}_{cont} < c\}$ or $\{X_{p_{cont}+j} \in \mathcal{C}\}$ where $j \in \{1, \dots, p_{cat}\}$ and $\mathcal{C} \subseteq \mathcal{K}_j$. Formally, this involves specifying a prior and computing a posterior over \mathcal{E} , from which we can approximately sample using MCMC. Like in the original BART model, we model the individual trees $(\mathcal{T}_m, \mathcal{D}_m, \mathcal{M}_m)$ as a priori i.i.d.. Similarly, we simulate posterior samples using a Metropolis-within-Gibbs sampler that updates each regression tree one-at-a-time while fixing the others. The main differences between obliqueBART and the original, axis-aligned BART are the decision rule prior and the conditional regression tree updates.

3.1 The obliqueBART prior

For obliqueBART, we adopt exactly the same priors for \mathcal{T} and \mathcal{M} as Chipman et al. (2010). That is, we specify the same branching process prior for \mathcal{T} and independent normal priors for outputs in \mathcal{M} with the same default hyperparameters described in Section 2.2. We specify the obliqueBART decision rule prior implicitly, by describing how to draw a rule at a non-terminal node in a tree \mathcal{T} . To this end, suppose we are at internal node nx in \mathcal{T} and that we have drawn rules at all of nx's ancestors. With probability p_{cat}/p , we draw a categorical decision rule of the form $\{X_{p_{\text{cat}}+j} \in \mathcal{C}\}$ where $\mathcal{C} \subset \mathcal{K}_j$ and $j \in \{1, \ldots, p_{\text{cat}}\}$ and with probability p_{cont}/p , we draw a continuous decision rule of the form $\{\phi^{\top} x_{\text{cont}} < c\}$.

Drawing a categorical decision rule involves (i) selecting the splitting variable index j; (ii) computing the set \mathcal{A} of valid values of the j-th categorical predictor $X_{p_{\text{cont}+j}}$; and (iii) forming a subset $\mathcal{C} \subset \mathcal{A}$ by randomly assigning each element of \mathcal{A} to \mathcal{C} with probability 1/2. The set \mathcal{A} is determined by the decision rules of \mathbf{nx} 's ancestors in the tree. Although Chipman et al. (1998) initially used such categorical decision rules in their Bayesian CART procedure, most implementations of BART do not use this prior and instead one-hot encode categorical features. A notable exception is Deshpande (2024), who demonstrated these categorical decision rules often produced more accurate predictions than one-hot encoding.

Drawing a continuous decision rule involves (i) drawing a random vector ϕ ; (ii) computing the interval of valid values of $\phi^{\top} \boldsymbol{x}_{\text{cont}}$ at \mathbf{nx} ; and (iii) drawing the cutpoint *c* uniformly from that interval. Both Breiman (2001) and Tomita et al. (2020) recommend the use of sparse ϕ 's when inducing oblique decision trees. While Breiman (2001) fixed the number of non-zero elements of ϕ , Tomita et al. (2020) demonstrated that allowing the number of non-zero entries to vary across decision rules improved prediction. Motivated by their findings, we specify a hierarchical spike-

and-slab prior for ϕ , which encourages sparsity and also allows the number of non-zero entries of ϕ to vary adaptively with the data.

Formally, we introduce a parameter $\theta \in [0, 1]$ that controls the overall sparsity of ϕ . Conditionally on θ , we draw p binary indicators $\gamma_1, \ldots, \gamma_p | \theta \stackrel{\text{i.i.d.}}{\sim}$ Bernoulli (θ). Then, for each $j = 1, \ldots, p_{\text{cont}}$, we draw $\phi_j \sim \mathcal{N}(0, 1)$ if $\gamma_j = 1$ and $\phi_j = 0$ otherwise. Finally, we re-scale ϕ to have unit norm. By specifying a further prior on θ , we allow oblique BART to learn an appropriate level of sparsity of ϕ from the data. For simplicity, we specify a conjugate Beta (a_{θ}, b_{θ}) prior with fixed $a_{\theta}, b_{\theta} > 0$.

Once we draw ϕ , we draw c uniformly from the range of valid values of $\phi^{\top} \boldsymbol{x}_{\text{cont}}$ available at nx. This range is determined by the continuous decision rules used at the ancestors of nx in the tree and can be computed by solving two linear programs maximizing and minimizing $\phi^{\top} \boldsymbol{x}_{\text{cont}}$ over the linear polytope corresponding to nx.

obliqueBART depends on several hyperparameters: the number of trees M, the hyperparameters $a_{\theta}, b_{\theta} > 0$ for θ , and ν and λ for the prior on σ^2 . Following Chipman et al. (2010), we recommend setting $M = 200, \nu = 3$, and tuning λ so that there is 90% prior probability on the event that σ^2 is less than the observed variance of Y. For the spike-and-slab prior, we recommend fixing $a_{\theta} = M$ and setting b_{θ} so that the prior mean of θ is $1/p_{\text{cont}}$.

3.2 Posterior computation

To simulate draws from the obliqueBART posterior, we deploy a Metropolis-within-Gibbs sampler that is almost identical to the original BART sampler described in Section 2.2. In each Gibbs sampler iteration, we update each of \mathcal{E}, θ , and σ^2 conditionally on the other two. Simple conjugate updates are available for θ and σ^2 . Like Chipman et al. (2010), we update the trees in \mathcal{E} oneat-a-time in two steps: a marginal decision tree update followed by a conditional update for the leaf outputs. We further utilize grow and prune proposals to update each decision tree. The only difference between our obliqueBART sampler and the original BART sampler lies in the generation of grow proposals.

Regression tree updates. To describe the update of the *m*-th regression tree $(\mathcal{T}_m, \mathcal{D}_m, \mathcal{M}_m)$, let \mathcal{E}^- denote the collection of the remaining M - 1 regression trees in the ensemble. For every node \mathbf{nx} in \mathcal{T} , let $\mathcal{I}(\mathbf{nx})$ denote the set of indices of the observations \mathbf{x}_i whose decision-following paths visit the node \mathbf{nx} . Further let $n_{\mathbf{nx}} = |\mathcal{I}(\mathbf{nx})|$ count the number of observations which visit \mathbf{nx} . The full conditional posterior density of the *m*-th regression tree factorizes over the leafs of \mathcal{T} :

$$p(\mathcal{T}, \mathcal{D}, \mathcal{M} | \boldsymbol{y}, \mathcal{E}^{-}, \sigma^{2}, \theta) \propto p(\mathcal{T}, \mathcal{D} | \theta) \times \prod_{\substack{\text{leafs}\\\ell}} \left[\tau^{-1} \exp\left\{ -\frac{1}{2} \left[\sigma^{-2} \sum_{i \in \mathcal{I}(\ell)} (r_{i} - \mu_{\ell})^{2} + \tau^{-2} \mu_{\ell}^{2} \right] \right\} \right], \quad (1)$$

where r_i is the i-th partial residual based on the trees in \mathcal{E}^- given by $r_i = y_i - \sum_{m' \neq m} g(\boldsymbol{x}_i; \mathcal{T}_{m'}, \mathcal{D}_{m'}, \mathcal{M}_{m'})$.

From Equation (1), we compute

$$p(\mathcal{T}, \mathcal{D} | \boldsymbol{y}, \mathcal{E}^{-}, \sigma^{2}, \theta) \propto p(\mathcal{T}, \mathcal{D} | \theta) \times \prod_{\substack{\text{leafs}\\\ell}} \left[\tau^{-1} P_{\ell}^{-\frac{1}{2}} \exp\left\{\frac{\Theta_{\ell}^{2}}{2P_{\ell}}\right\} \right]$$
(2)

$$p(\mathcal{M}|\mathcal{T}, \mathcal{D}, \mathcal{E}^{-}, \boldsymbol{y}, \sigma^{2}) \propto \prod_{\substack{\text{leafs}\\\ell}} P_{\ell}^{\frac{1}{2}} \exp\left\{-\frac{P_{\ell}(\mu_{\ell} - P_{\ell}^{-1}\Theta_{\ell})^{2}}{2}\right\}$$
(3)

where, for any node nx in \mathcal{T} , $P_{nx} = n_{nx}\sigma^{-2} + \tau^{-2}$ and $\Theta_{nx} = \sigma^{-2}\sum_{i\in\mathcal{I}(nx)}r_i$. We see immediately from Equation (3) that, given the decision tree structure, the leaf outputs are conditionally independent and normally distributed. Specifically, in leaf ℓ , we have $\mu_{\ell} \sim \mathcal{N}\left(P_{\ell}^{-1}\Theta_{\ell}, P_{\ell}^{-1}\right)$ conditionally on $\mathcal{T}, \boldsymbol{y}, \mathcal{E}^{(-)}$, and σ^2 . This means that when n_{ℓ} is large, μ_{ℓ} 's conditional posterior is sharply concentrated near the average of the *partial residuals* in the leaf. This is in marked contrast to CART, RF, and ERT where the leaf outputs are exactly the average of the outcomes in the leaf.

Efficient decision tree updates. It remains to describe how to sample a new decision tree from the distribution in Equation (2). Although its density is available in closed form, this distribution does not readily admit an exact sampling procedure. Instead, assuming that currently $(\mathcal{T}_m, \mathcal{D}_m) = (\mathcal{T}, \mathcal{D})$, we use a single Metropolis-Hastings (MH) step in which we first propose a random perturbation $(\mathcal{T}^*, \mathcal{D}^*)$ of the $(\mathcal{T}, \mathcal{D})$ and then set $(\mathcal{T}_m, \mathcal{D}_m) = (\mathcal{T}^*, \mathcal{D}^*)$ with probability

$$\alpha(\mathcal{T}, \mathcal{D} \to \mathcal{T}^{\star}, \mathcal{D}^{\star}) = \min\left\{1, \frac{q(\mathcal{T}, \mathcal{D}|\mathcal{T}^{\star}, \mathcal{D}^{\star})}{q(\mathcal{T}^{\star}, \mathcal{D}^{\star}|\mathcal{T}, \mathcal{D})} \times \frac{p(\mathcal{T}^{\star}, \mathcal{D}^{\star}|\boldsymbol{y}\mathcal{E}^{-}, \sigma^{2}, \theta)}{p(\mathcal{T}, \mathcal{D}|\boldsymbol{y}, \mathcal{E}^{-}, \sigma^{2}, \theta)}\right\},\tag{4}$$

where $q(\cdot|\cdot)$ is a to-be-specified proposal kernel.

In obliqueBART, we use a simple proposal mechanism that randomly grows or prunes the tree, each with probability 1/2. To generate a grow proposal, we (i) attach two child nodes to a leaf node selected uniformly at random; (ii) draw a new decision rule to associate with the selected node; and (iii) leave the rest of the tree and the other decision rules unchanged. To generate a prune proposal, we (i) delete two leafs with a common parent and their incident edges in \mathcal{T} ; (ii) delete the decision rule associated with the parent of the deleted leafs; and (iii) leave the rest of the tree and the other decision rules unchanged. See Figure 3 for a cartoon illustration.



Figure 3: Cartoon illustration of a grow and prune move with oblique, continuous decision rules

The local nature of grow and prune proposals — they change at most two leaves — and the fact that the conditional posterior density of $(\mathcal{T}, \mathcal{D})$ factorizes over leafs (Equation (2)) yields considerable cancelation in the acceptance probability in Equation (4); see Appendix B.

During a grow move, we must draw a decision rule to associate to the newly created decision node from some proposal distribution; in Figure 3, this rule is highlighted in dark green. In principal, we can use any distribution over decision rules for the proposal. But for simplicity, we choose to propose decision rules in grow moves from the prior described in Section 3.1. That is, we first randomly decide whether to draw a categorical or continuous decision rule. If we draw a categorical rule, we select the splitting variable and form a random subset of the available levels of that variable. If we decide to draw continuous decision rule, then, conditionally on θ , we draw the entries of ϕ independently from the spike-and-slab prior.

Note that there is positive probability that the proposed ϕ contains all zeros. When this occurs, we set c = 1 so that the decision rule $\{\mathbf{0}^{\top} \boldsymbol{x} < 1\}$ sends all observations to the left child and none to the right child in the proposed decision tree $(\mathcal{T}^{\star}, \mathcal{D}^{\star})$. Such proposals provide exactly the same fit to the data as the original tree but receives less prior support due to their increased complexity. Consequently, these proposal tends to be rejected in the MH step. When ϕ contains at least one non-zero element, we solve two linear programs to compute the maximum and minimum values of $\phi^{\top} \boldsymbol{x}_{\text{cont}}$ over the linear polytope corresponding to the node nx. In our implementation, we solve these programs using the numerical optimization library ALGLIB 4.01.0 (Bochkanov, 2023).

At first glance, it may seem counter-intuitive to propose rules completely at random and independently of the data. One might anticipate that completely random rules would lead to very low MH acceptance probabilities. One might further expect that proposing new rules in a data-dependent fashion, for instance using the model-based heuristics of Menze et al. (2011), Zhang and Suganthan (2014), or Rainforth and Wood (2015), could lead to larger acceptance probabilities and more efficient MCMC exploration. In fact, drawing overly-informed proposals can result in even *slower* MCMC exploration than drawing proposals from the prior.

To develop some intuition for this phenomenon, we note that the MH acceptance probability can be decomposed into the product of two terms (Equation (B1)). The first balances tree complexity against data fit while the other is the ratio between the prior and proposal probabilities of the new rule. Although informed proposals might increase the first term by improving the data fit, they generally make the second term extremely small, deflating the acceptance probability. The resulting Markov chain tends to get stuck and explore the posterior very slowly. See Deshpande (2024, §2.2 and Appendix B) for more discussion about this phenomenon.

To summarize, in each Gibbs sampler iteration, while keeping σ^2 and θ fixed, we first sweep over the trees in \mathcal{E} , updating each one conditionally on all the others. Each regression tree update involves (i) sampling a new decision tree from Equation (2) with a MH step and grow/prune mechanism and then (ii), conditionally on the new decision tree, drawing leaf ℓ 's output from a $\mathcal{N}\left(P_{\ell}^{-1}\Theta_{\ell}, P_{\ell}^{-1}\right)$ distribution. When generating grow proposals, we draw new decision rules from the prior described in Section 3.1.

Updating θ and σ^2 . Once we update each tree in \mathcal{E} , we draw σ^2 and θ from their full conditional

posterior distributions, which are both conjugate. We compute

$$\sigma^{2}|\boldsymbol{y}, \mathcal{E}, \boldsymbol{\theta} \sim \text{Inv. Gamma}\left(\frac{\nu+n}{2}, \frac{\nu\lambda}{2} + \frac{1}{2}\sum_{i=1}^{n}\left(y_{i} - \sum_{m=1}^{M}g(\boldsymbol{x}_{i}; \mathcal{T}_{m}, \mathcal{D}_{m}, \mathcal{M}_{m})\right)^{2}\right)$$
$$\boldsymbol{\theta}|\boldsymbol{y}, \mathcal{E}, \sigma^{2} \sim \text{Beta}\left(a_{\boldsymbol{\theta}} + n_{\boldsymbol{\phi}}, b_{\boldsymbol{\theta}} + z_{\boldsymbol{\phi}}\right),$$

where n_{ϕ} (resp. z_{ϕ}) counts the number of non-zero (resp. zero) entries in the ϕ 's appearing in \mathcal{E} . An R package implementating of obliqueBART is available at https://github.com/paulhnguyen/

4 Experiments

obliqueBART.

We compared the performance of obliqueBART to other tree models using several synthetic and benchmark datasets. In Section 4.1, we use the synthetic data from Figure 2 to compare oblique-BART to axis-aligned BART with the original features and several randomly rotated versions of the features. Then, in Section 4.2, we compare obliqueBART to other axis-aligned tree ensemble methods fit, respectively, with the original features and randomly pre-rotated features on benchmark datasets for both regression and classification problems. Generally speaking, obliqueBART performed very well on regression tasks and was competitive with the other methods on classification tasks. We further found that randomly pre-rotating features before fitting axis-aligned RF, ERT, or GBT models tended to yield worse results than simply fitting obliqueBART.

We performed all of our experiments on a shared high-throughput computing cluster (Center for High Throughput Computing, 2006). For obliqueBART and BART, we compute posterior means of f(x) (for regression) and $\mathbb{P}(y = 1|x)$ (for classification) based on 1000 samples obtained by simulating a single Markov chain for 2000 iterations and discarding the first 1000 as "burn-in." We fit BART, RF, ERT, and XGBoost models using implementations available in **BART** (Sparapani et al., 2021), randomForest (Liaw and Wiener, 2002), ranger (Wright and Ziegler, 2017), and **xgboost** (Chen et al., 2024). We used package default settings for all experiments and did not manually tune any hyperparameters.

4.1 Synthetic data experiments

We compared obliqueBART to axis-aligned BART with data from the two simple functions in Figure 2. Since obliqueBART partitions the feature space along randomly selected directions, we additionally compared it with a hybrid procedure that first computes R random rotations of the feature space and then trains an axis-aligned BART model using the rotated features. This random rotation BART model is a direct analog of the random rotation ensemble methods studied in Blaser and Fryzlewicz (2016).

For these experiments, we sampled *n* covariate vectors $\mathbf{x}_i \sim \text{Uniform}([0,1]^2)$ and generated $y_i \sim \mathcal{N}(f(\mathbf{x}_i;\theta,\Delta),1)$, where the function $f(\mathbf{x};\theta,\Delta)$ takes on two values $\pm\Delta$ and depends on a parameter θ . We considered two such functions, the rotated axes function (Figure 2a) and the sinusoid function (Figure 2a).

Rotated axes. Given any $\theta \in [0, \pi/4]$, let $\boldsymbol{u}(\boldsymbol{x})$ be the point obtained by rotating $\boldsymbol{x} \ \theta$ radians counter-clockwise around the origin. The value of rotated axes function is determined by the quadrant in which \boldsymbol{u} lies. Specifically, for rotation angle $\theta \in \{0, \pi/36, \ldots, \pi/4\}$ and jump $\Delta \in \{0.5, 1, 2, 4\}$, we set $f(\boldsymbol{x}; \theta, \Delta) = \Delta \times (2 \times \mathbb{1} (u_1 u_2 > 0) - 1)$.

Sinusoid. The value of $f(\boldsymbol{x}; \theta, \Delta)$ depends on which side of a particular sinusoid the point \boldsymbol{x} lies. Specifically, for a given amplitude $\theta \in \{0, 0.1, \ldots, 1\}$ and jump $\Delta \in \{0.5, 1, 2, 4\}$, we set $f(\boldsymbol{x}; \theta, \Delta) = \Delta \times (2 \times \mathbb{1} (x_2 > \theta \sin (10x_1)) - 1)$.

For each combination of $n \in \{100, 1000, 10000\}$, function f, jump Δ , and parameter θ , we generated 20 datasets of size n. Figure 4a shows how axis-aligned BART and random rotation BART's outof-sample RMSE (averaged over 20 replications) relative to oblique BART changes as the decision boundaries becomes less and less axis-aligned (i.e., as θ increases) with $\Delta = 4$.



Figure 4: Performance of axis-aligned BART (AA) and axis-aligned BART with random rotations relative to obliqueBART in terms of out-of-sample predictive error in the (a) rotated axes partition and (b) sinusoidal partition.

As we might expect, obliqueBART substantially outperformed axis-aligned BART on the rotated axes problem. Interestingly, we see that obliqueBART even out-performs axis-aligned BART when $\theta = 0$ and the true decision boundary is axis-aligned. When $\theta = 0$, the obliqueBART ensemble used, on average, axis-aligned rules 70.2% of the time compared to 52.9% of the time when $\theta = \pi/4$. This suggests that obliqueBART, through the hierarchical spike-and-slab prior for ϕ , can adaptively adjust the number of axis-aligned or oblique rules. obliqueBART further outperformed axis-aligned BART on the sinusoid problem, even though the decision boundary was highly non-linear (see Figure 4b).

Although obliqueBART also outperformed random rotation BART with a small number of random rotations, the gap between the methods diminished as the number of rotations R increased. For these data, random rotation BART run with at least 50 rotations performed as well as — and, at times, slightly outperformed — obliqueBART. As we discuss in Section 4.2, matching oblique BART's performance with a random rotation ensemble is much harder when the number of continuous predictors $p_{\rm cont}$ is large.

4.2 Results on benchmark datasets

We next compared obliqueBART's performance to that of RF, ERT, XGB, BART, and rotated versions of these methods with R = 200 random rotations on 18 regression and 22 classification benchmark datasets. The regression datasets contain between 96 and 53,940 observations and between 4 and 31 predictors and the classification datasets contain between 61 and 4601 observations and between 4 and 72 predictors. We obtained most of these datasets from UCI Machine Learning Repository (https://archive.ics.uci.edu); the Journal of Applied Econometrics data archive (http://qed.econ.queensu.ca/jae/); and from several R packages. See Table A1 for the dimensions of and links to these datasets.

We created 20 random 75%-25% training-testing splits of each dataset. For regression tasks, we computed each methods' standardized out-of-sample mean square error (SMSE), which is defined as the ratio between the the mean square errors of a model, $n_{\text{test}}^{-1} \sum_{i=1}^{n_{\text{test}}} (Y_{\text{test},i} - \hat{Y}_i)^2$ and the mean of the training data $n_{\text{test}}^{-1} \sum_{i=1}^{n_{\text{test}}} (Y_{\text{test},i} - \overline{Y}_{\text{train}})^2$. For classification problems, we formed predictions by truncating the outputted class probability at 50% and computed out-of-sample accuracy. We performed one-sided paired t-tests to determine whether oblique BART's error were significantly less than the competing methods' errors.

Comparison to axis-aligned methods. Figure 5 compares obliqueBART's SMSE and accuracy to those of the axis-aligned methods across every fold and dataset. We defer dataset-by-dataset tabulations of these error metrics to Tables A2 and A3 in Appendix A.



Figure 5: obliqueBART's SMSE (a) and accuracy (b) across all splits and datasets, compared to XGB, ERT, RF, and BART. Models with lower SMSE's and higher accuracies are preferred.

Although no single method performed the best across all regression datasets, obliqueBART had the the smallest overall average SMSE (0.296). For comparison, the SMSEs for the axis-aligned methods were 0.316 (BART), 0.330 (RF), 0.332 (ERT), and 0.342 (XGB). obliqueBART's SMSE was also statistically significantly lower (at the 5% level) than BART's on nine datasets, RF's on nine datasets, ERT's on 12 datasets, and XGB's on nine datasets.

obliqueBART had the smallest classification accuracy (0.846) averaged across all folds and datasets while ERT had the highest (0.866). ERT had the largest accuracy on nine datasets while oblique-BART was the best-performing method for five datasets. Generally speaking, however, oblique-BART was still competitive with the other methods for classification. The difference in accuracy between obliqueBART and ERT was less than 2% in 15 of the 22 datasets. Similarly, the difference in accuracy between obliqueBART and BART was less than 1.7% in 14 of the datasets.

Because BART and obliqueBART generate many samples of the regression tree ensemble, we would expect them to be slower than RF, ERT, and XGB, which only generate a single ensemble. Further, because obliqueBART involves solving two linear programs when proposing new decision rules, we would expect it to be slower than BART. This was generally the case in our experiments: for most datasets, obliqueBART was about twice as slow as BART and slower than RF, ERT, and XGB. Surprisingly, however, obliqueBART was much faster on the **diamons** dataset.

Comparison with random rotation ensembles. Next, we compared oblique BART's performance to randomly rotated versions of BART, RF, ERT, and XGB with $R \in \{1, 4, 16, 50, 100, 200\}$ random rotations. We report dataset-by-dataset SMSEs and accuracies in Tables A4 and A5. We additionally determined how many random rotations were needed for each of these methods to match obliqueBART's performance (Tables A6 and A7). Figure 6 shows the SMSEs and accuracies of oblique BART and the random rotation ensembles with R = 200 for all datasets and folds.



Figure 6: oblique BART's SMSE and accuracy (resp. left and right) across all splits and datasets, compared to XGB, ERT, RF, and BART with 200 random rotations. Models with lower SMSE's and higher accuracies are preferred.

Somewhat surprisingly, the randomly rotated random forests (rotRF) performed markedly worse than the other methods. For regression, obliqueBART and the rotated version of BART (rotBART) had the smallest average SMSEs (0.297 and 0.296, resp.). obliqueBART was also competitive with the rotERT and rotXGB for classification; it's average accuracy was 0.846 while the best performing method, rotERT, had an average accuracy of 0.859. We additionally observed that obliqueBART was, on average, 20 times faster than rotRF and twice as fast as rotBART run with R = 200random rotations.

Interestingly, there was substantial variation in the minimum number of rotations needed for rot-BART, rotRF, rotERT, and rotXGB to match obliqueBART's performance. For instance, rotBART was unable to match obliqueBART's performance on 19 datasets even with 200 rotations and required only one rotation for 17 datasets; four rotations for two datasets; 16 rotations for one dataset; and 50 rotations for one dataset. rotXGB, on the other hand, was unable to match obliqueBART's performance on 24 datasets using 200 rotations and required one rotation for nine datasets; four rotations for four datasets; 16 rotations for one dataset; 50 rotations for one dataset; and 100 rotations for one dataset. These results suggest that running obliqueBART is often more effective and faster than tuning the number of random pre-rotations used to train a random rotation ensemble.

5 Discussion

We introduced obliqueBART, which extends the expressivity of the BART model by building regression trees that partition the predictor space based on random hyperplanes. Unlike oblique versions of CART or RF, obliqueBART does not search for optimal decision rules and instead grows trees by randomly accepting (via a Metropolis-Hastings step) completely *random* decision rules. Although obliqueBART does not uniformly outperform BART across the 40 benchmark datasets we considered, its performance is generally not significantly worse than BART's and can sometimes be substantially better. On this view, we would not advocate for a wholesale replacement axis-aligned BART in favor of our obliqueBART implementation. It is possible, for instance, that alternative priors for ϕ may yield somewhat larger improvements.

While we have focused primarily on the tabular data setting, we anticipate that our obliqueBART implementation can be fruitfully extended to accommodate structured input like images. Li et al. (2023a) demonstrated that oblique tree ensembles can close the performance gap between non-neural network methods and convolutional deep networks for image classification. Their manifold oblique random forests (MORF) procedure recursively partitions images based on the average pixel value within random rectangular sub-regions of an image. Developing a BART analog of MORF would involve modifying the decision rule prior to ensure that the non-zero elements of ϕ correspond to a connected sub-region of an image. We leave this and similar extensions for other types of structured inputs (e.g., tensors, functional data) to future work.

References

- Albert, J. H. and Chib, S. (1993). Bayesian analysis of binary and polychotomous response data. Journal of the American Statistical Association, 88(422):669–679.
- Bertsimas, D. and Dunn, J. (2017). Optimal classification trees. *Machine Learning*, 106(7):1039–1082.
- Bertsimas, D., Dunn, J., and Wang, Y. (2021). Near-optimal nonlinear regression trees. *Operations Research Letters*, 49(2):201–206.
- Blaser, R. and Fryzlewicz, P. (2016). Random rotation ensembles. Journal of Machine Learning Research, 17(1):126–151.
- Bochkanov, S. (2023). ALGLIB. www.alglib.net.
- Breiman, L. (2001). Random forests. Machine Learning, 45:5–32.
- Breiman, L., Friedman, J. H., Olshen, R. A., and Stone, C. J. (1984). Classification and Regression Trees. Routledge.
- Cattaneo, M. D., Chandak, R., and Klusowski, J. M. (2024). Convergence rates of oblique regression trees for flexible function libraries. Annals of Statistics, 52(2):466–490.

Center for High Throughput Computing (2006). Center for High Throughput Computing.

- Chan, K.-Y. and Loh, W.-Y. (2004). Lotus: An algorithm for building accurate and comprehensible logistic regression trees. *Journal of Computational and Graphical Statistics*, 13(4):826–852.
- Chen, T., He, T., Benesty, M., Khotilovich, V., Tang, Y., Cho, H., Chen, K., Mitchell, R., Cano, I., Zhou, T., Li, M., Xie, J., Lin, M., Geng, Y., Li, Y., and Yuan, J. (2024). *xgboost: Extreme Gradient Boosting.* R package version 1.7.8.1.
- Chipman, H. A., George, E. I., and McCulloch, R. E. (1998). Bayesian CART model search. Journal of the American Statistical Association, 93(443):935–948.
- Chipman, H. A., George, E. I., and McCulloch, R. E. (2010). BART: Bayesian additive regression trees. Annals of Applied Statistics, 4(1):266–298.
- Deshpande, S. K. (2024). flexBART: Flexible Bayesian regression trees with categorical predictors. arXiv:2211.04459.
- Dorie, V., Hill, J., Shalit, U., Scott, M., and Cervone, D. (2019). Automated versus do-it-yourself methods for causal inference: Lessons learned from a data analysis competition. *Statistical Science*, 34(1):43–68.
- Friedman, J. H. (2001). Greedy function approximation: A gradient boosting machine. Annals of Statistics, 29(5):1189–1232.
- Geurts, P., Ernst, D., and Wehenkel, L. (2006). Extremely randomized trees. *Machine Learning*, 63:3–42.
- Gramacy, R. B. and Lee, H. K. (2008). Bayesian treed Gaussian process models with an application to computer modeling. *Journal of the American Statistical Association*, 103(483):1119–1130.
- Hahn, P. R., Murray, J. S., and Carvalho, C. M. (2020). Bayesian regression models for causal inference: Regularization, confounding, and heterogeneous effects. *Bayesian Analysis*, 15(3):965– 1056.
- Hastie, T. and Friedman, R. T. J. (2005). The Elements of Statistical Learning: Data Mining, Inference, and Prediction. Springer.
- Heath, D. G., Kasif, S., and Salzberg, S. L. (1993). Induction of oblique decision trees. In International Joint Conference on Artificial Intelligence.
- Hill, J. L. (2011). Bayesian nonparametric modeling for causal inference. Journal of Computational and Graphical Statistics, 20(1):217–240.
- Künzel, S. R., Saarinen, T. F., Liu, E. W., and Sekhon, J. S. (2022). Linear aggregation in treebased estimators. Journal of Computational and Graphical Statistics, 31(3):917–934.
- Lamprinakou, S., Barahona, M., Flaxman, S., Filippi, S., Gandy, A., and McCoy, E. J. (2023). BART-based inference for poisson processes. *Computational Statistics & Data Anal*ysis, 180:107658.

Landwehr, N., Hall, M., and Frank, E. (2005). Logistic model trees. Machine Learning, 59:161–205.

- Li, A., Perry, R., Huynh, C., Tomita, T. M., Mehta, R., Arroyo, J., Patsolic, J., Falk, B., Sarma, S., and Vogelstein, J. (2023a). Manifold oblique random forests: Towards closing the gap on convolutional deep networks. SIAM Journal on Mathematics of Data Science, 5(1):77–96.
- Li, Y., Linero, A. R., and Murray, J. (2023b). Adaptive conditional distribution estimation with Bayesian decision tree ensembles. *Journal of the American Statistical Association*, 118(543):2129– 2142.
- Liaw, A. and Wiener, M. (2002). Classification and regression by randomForest. *R News*, 2(3):18–22.
- Linero, A. R., Basak, P., Li, Y., and Sinha, D. (2022). Bayesian survival tree ensembles with submodal shrinkage. *Bayesian Analysis*, 17(3):997–1020.
- Linero, A. R., Sinha, D., and Lipsitz, S. R. (2020). Semiparametric mixed-scale models using shared Bayesian forests. *Biometrics*, 76(1):131–144.
- Maia, M., Murphy, K., and Parnell, A. C. (2024). GP-BART: A novel Bayesian additive regression trees approach using gaussian processes. *Computational Statistics & Data Analysis*, 190:107858.
- Menze, B. H., Kelm, B. M., Splitthoff, D. N., Koethe, U., and Hamprecht, F. A. (2011). On oblique random forests. In *Machine Learning and Knowledge Discovery in Databases*.
- Orlandi, V., Murray, J., Linero, A. R., and Volfovsky, A. (2021). Density regression with Bayesian additive regression trees. arXiv:2112.12259.
- Pratola, M. T., Chipman, H. A., George, E. I., and McCulloch, R. E. (2020). Heteroscedastic BART using multiplicative regression trees. *Journal of Computational and Graphical Statistics*, 29(2):405–417.
- Quinlan, J. R. (1992). Learning with continuous classes. In 5th Australian Joint Conference on Artificial Intelligence.
- Rainforth, T. and Wood, F. (2015). Canonical correlation forests. arXiv:1507.05444.
- Rodriguez, J., Kuncheva, L., and Alonso, C. (2006). Rotation forest: A new classifier ensemble method. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 28(10):1619–1630.
- Sparapani, R., Logan, B. R., McCulloch, R. E., and Laud, P. W. (2016). Nonparametric survival analysis using Bayesian Additive Regression Trees. *Statistics in Medicine*, 35(16):2741–2753.
- Sparapani, R., Spanbauer, C., and McCulloch, R. (2021). Nonparametric machine learning and efficient computation with Bayesian additive regression trees: The BART R package. *Journal of Statistical Software*, 97(1):1–66.
- Starling, J. E., Murray, J. S., Carvalho, C. M., Bukowski, R. K., and Scott, J. G. (2020). BART with targeted smoothing: An analysis of patient-specific stillbirth risk. *Annals of Applied Statistics*, 14(1):28–50.

- Tomita, T. M., Browne, J., Shen, C., Chung, J., Patsolic, J. L., Falk, B., Priebe, C. E., Yim, J., Burns, R., Maggioni, M., and Vogelstein, J. T. (2020). Sparse projection oblique randomer forests. *Journal of Machine Learning Research*, 21(104):1–39.
- Wright, M. N. and Ziegler, A. (2017). ranger: A fast implementation of random forests for high dimensional data in C++ and R. Journal of Statistical Software, 77(1):1–17.
- Yannotty, J. C., Santner, T. J., Furnstahl, R. J., and Pratola, M. T. (2024a). Model mixing using Bayesian additive regression trees. *Technometrics*, 66(2):196–207.
- Yannotty, J. C., Santner, T. J., Li, B., and Pratola, M. T. (2024b). Combining climate models using Bayesian regression trees and random paths. arXiv 2407.13169.
- Zhang, L. and Suganthan, P. N. (2014). Random forests with ensemble of feature spaces. Pattern Recognition, 47(10):3429–3437.

A Additional benchmarking details and results

Table A1 lists the dimensions and sources of each benchmark dataset. Most datasets are from the UCI data repository, though some are from individual R packages (bolded), the Journal of Applied Econometrics data archive, and the CMU Statlib data repository.

Regression Data				Classification Data				
Data (Source)	n	p	p_{cont}	Data	n	p	p_{cont}	
abalone (UCI)	4177	8	7	$\texttt{banknote}(ext{UCI})$	1372	4	4	
ais (\mathbf{DAAG})	202	12	10	blood transfusion $\left(\mathrm{UCI} ight)$	748	4	4	
$ ext{ammenity} (ext{JAE})$	3044	25	20	breast cancer diag (UCI)	569	30	30	
$ extsf{attend} (extsf{JSE})$	838	9	6	breast cancer $\left(\mathrm{UCI} ight)$	683	9	9	
$\mathtt{baseball}(\mathbf{ISLR})$	263	19	16	breast cancer prog. $\left(\mathrm{UCI} ight)$	194	32	32	
$ ext{basketball} (ext{SMIS})$	96	4	3	climate crashes $\left(\mathrm{UCI} ight)$	540	18	18	
$\texttt{boston}~(\mathbf{MASS})$	506	4	3	$ ext{connectionist sonar}\left(ext{UCI} ight)$	208	60	60	
t budget (JAE)	1729	10	10	$ ext{credit}$ approval $(ext{UCI})$	653	15	6	
cane (OzDASL)	3775	31	25	echocardiogram (UCI)	579	10	9	
cpu (<mark>UCI</mark>)	209	7	6	fertility $({f UCI})$	100	9	3	
diabetes $(lars)$	442	10	9	$ ext{german}$ credit $(ext{UCI})$	1000	20	7	
diamonds $(\mathbf{ggplot2})$	53940	9	6	heptatitis (UCI)	80	19	7	
edu (<mark>JAE</mark>)	2338	6	5	ILPD (UCI)	579	10	9	
labor (\mathbf{Ecdat})	5320	6	4	$ t ionosphere \ ({ m UCI})$	351	34	34	
mpg (UCI)	392	8	7	ozone1 (<mark>UCI</mark>)	1848	72	72	
$ extsf{rice} (extsf{JAE})$	1026	18	14	ozone8 (UCI)	1847	72	72	
$ extsf{servo} (extsf{UCI})$	167	4	2	$ extsf{parkinsons} (extsf{UCI})$	195	22	22	
$\mathtt{strikes} \ ({f Statlib})$	625	6	5	planning relax (UCI)	182	12	12	
				qsar bio. $\left(\mathrm{UCI} ight)$	1055	41	38	
				seismic bumps $\left(\mathrm{UCI} ight)$	2584	18	14	
				spambase (UCI) 4601			57	
				spectf heart (UCI)	267	44	44	

Table A1: Dimensions and hyperlinked sources of benchmark datasets

Tables A2 and A3, respectively, show the out-of-sample standardized mean square and accuracy of obliqueBART, RF, ERT, BART, and XGB for each benchmark dataset, averaged over 20 training-testing splits. We marked entries in these tables with asterisks whenever obliqueBART achieved statistically significantly lower SMSE or higher accuracy than the competing method. Throughout, we assessed significance using a paired t-test and a 5% threshold. We report analogous results from comparison obliqueBART to rotated versions of RF, ERT, BART, and XGB run with 200 random rotations in Tables A4 and A5.

Table A2: Standardized mean square errors on regression benchmark datasets, averaged across 20 training-testing splits, for obliqueBART and axis-aligned methods. Best performing method is bolded and errors that are statistically significantly larger than obliqueBART's are marked with an asterisk.

data	ERT	obliqueBART	RF	BART	XGB
abalone	0.454*	0.44	0.448*	0.449*	0.467^{*}
ais	0.137^{*}	0.122	0.113	0.133^{*}	0.147^{*}
amenity	0.315^{*}	0.283	0.279	0.278	0.283
attend	0.420^{*}	0.246	0.433^{*}	0.302^{*}	0.252
baseball	0.410^{*}	0.390	0.418^{*}	0.399^{*}	0.48^{*}
basketball	0.642	0.762	0.708	0.669	0.735
boston	0.587	0.778	0.662	0.6	0.637
budget	0.010^{*}	0.003	0.007^{*}	0.003	0.003
cane	0.350^{*}	0.183	0.185	0.193^{*}	0.174
cpu	0.155^{*}	0.139	0.162	0.272^{*}	0.151
diabetes	0.517^{*}	0.495	0.538^{*}	0.500^{*}	0.666^{*}
diamonds	0.018	0.020	0.019	0.019	0.025^{*}
edu	0.020	0.020	0.020^{*}	0.020	0.022^{*}
labor	0.719^{*}	0.221	0.630^{*}	0.693^{*}	0.506^{*}
mpg	0.141	0.135	0.136	0.125	0.146^{*}
rice	0.055^{*}	0.015	0.037^{*}	0.027^{*}	0.012
servo	0.193^{*}	0.167	0.302^{*}	0.149	0.076
strikes	0.837	0.926	0.843	0.863	1.290^{*}

Table A3: Accuracies on each classification benchmark datasets, averaged across 20 training-testing splits for obliqueBART and axis-aligned methods. Best performing method is bolded and errors that are statistically significantly larger than obliqueBART's are marked with an asterisk.

data	ERT	obliqueBART	BART	\mathbf{RF}	XGB
banknote	0.999	0.999	0.997^{*}	0.992^{*}	0.991^{*}
blood transfusion	0.776	0.768	0.795	0.768	0.798
breast cancer diag.	0.965	0.922	0.966	0.961	0.967
breast cancer	0.975	0.974	0.973	0.975	0.964^{*}
breast cancer prog.	0.754	0.758	0.760	0.756	0.733^{*}
climate crashes	0.919	0.917	0.944	0.926	0.951
connectionist sonar	0.871	0.796	0.824	0.835	0.832
credit approval	0.874	0.866	0.87	0.876	0.872
echocardiogram	0.733	0.714	0.712	0.707	0.692^{*}
fertility	0.846^{*}	0.86	0.860	0.842^{*}	0.846
german credit	0.765	0.751	0.76	0.763	0.745
hepatitis	0.858	0.84	0.865	0.868	0.855
ILPD	0.725	0.714	0.71	0.706	0.692^{*}
ionosphere	0.936	0.902	0.926	0.928	0.924
ozone1	0.969^{*}	0.970	0.97	0.969^{*}	0.970
ozone8	0.940	0.933	0.938	0.939	0.938
parkinsons	0.910	0.866	0.861	0.899	0.880
planning relax	0.697^{*}	0.717	0.708^{*}	0.686^{*}	0.621^{*}
qsar bio.	0.868	0.826	0.845	0.862	0.855
seismic bumps	0.930^{*}	0.935	0.935	0.933^{*}	0.934^{*}
spambase	0.956	0.765	0.932	0.953	0.945
spectf heart	0.802	0.799	0.813	0.814	0.796

Table A4: Standardized mean square errors on regression benchmark datasets, averaged across 20 training-testing splits, for obliqueBART and rotated versions of axis-aligned methods with 200 random rotations. Best performing method is bolded and errors that are statistically significantly larger than obliqueBART's are marked with an asterisk. NA indicates that the method could not be run with 200 random rotations.

data	obliqueBART	rotERT	rotRF	rotBART	rotXGB
abalone	0.44	0.45^{*}	1.08*	0.448^{*}	0.47^{*}
ais	0.122	0.151^{*}	1.33^{*}	0.129	0.167^{*}
amenity	0.283	0.349^{*}	1.07^{*}	0.281	0.357^{*}
attend	0.246	0.304^{*}	1.06^{*}	0.297^{*}	0.305^{*}
baseball	0.39	0.446^{*}	1.07^{*}	0.406^{*}	0.544^{*}
basketball	0.762	0.68	1.06^{*}	0.691	0.767^{*}
boston	0.778	0.833	22.6^{*}	0.577	0.853
budget	0.003	0.010^{*}	1.200^{*}	0.003	0.019^{*}
cane	0.183	0.315^{*}	1.580^{*}	0.191	0.294^{*}
cpu	0.139	0.201^{*}	1.480^{*}	0.313^{*}	0.249^{*}
diabetes	0.495	0.520^{*}	0.967^{*}	0.499	0.606^{*}
diamonds	0.020	NA	NA	0.020	NA
edu	0.020	0.022^{*}	1.150^{*}	0.020	0.024^{*}
labor	0.221	NA	NA	NA	NA
mpg	0.135	0.14	1.09^{*}	0.138	0.16^{*}
rice	0.015	0.204^{*}	1.670^{*}	0.026^{*}	0.234^{*}
servo	0.167	0.25^{*}	2.24^{*}	0.196^{*}	0.225^{*}
strikes	0.926	0.915	36.2^{*}	0.805	1.31

Table A5: Accuracies on classification datasets, averaged across 20 training-testing splits, for obliqueBART and rotated versions of axis-aligned methods with 200 random rotations. Best performing method is bolded and accuracies that are statistically significantly smaller than oblique-BART's are marked with an asterisk.

data	obliqueBART	rotERT	rotBART	rotRF	rotXGB
banknote	0.999	1	0.999	0.451	0.998
blood transfusion	0.768	0.734^{*}	0.793	0.748	0.789
breast cancer diag.	0.922	0.977	0.973	0.635^{*}	0.97
breast cancer	0.974	0.973	0.975	0.647	0.972
breast cancer prog.	0.758	0.751	0.759	0.303	0.733
climate crashes	0.917	0.926	0.932	0.56	0.952
connectionist sonar	0.796	0.849	0.801	0.474^{*}	0.824
credit approval	0.866	0.87	0.859	0.453	0.871
echocardiogram	0.714	0.712	0.708	0.343	0.695
fertility	0.86	0.848	0.86	0.726	0.84
german credit	0.751	0.757	0.74	0.3^{*}	0.743
hepatitis	0.84	0.858	0.858	0.725	0.842
ILPD	0.714	0.711	0.7	0.336	0.708
ionosphere	0.902	0.93	0.881	0.361	0.892
ozone1	0.97	0.968*	0.97	0.0314^{*}	0.969
ozone8	0.933	0.939	0.941	0.0695^{*}	0.939
parkinsons	0.866	0.911	0.859	0.265	0.894
planning relax	0.717	0.653^{*}	0.711	0.283^{*}	0.63^{*}
qsar bio.	0.826	0.851	0.847	0.568*	0.857
seismic bumps	0.935	0.919^{*}	0.934	0.0648^{*}	0.929
spambase	0.765	0.951	0.936	0.413^{*}	0.945
spectf heart	0.799	0.813	0.817	0.799	0.791

data	rotBART	rotXGB	rotERT	rotRF
abalone	-	-	-	-
ais	1	-	-	-
amenity	1	-	-	-
attend	-	-	-	-
baseball	-	-	-	-
basketball	-	1	-	-
boston	-	1	1	1
budget	1	-	-	-
cane	50	-	-	-
cpu	-	-	-	-
diabetes	1	-	-	-
diamonds	-	-	-	-
edu	1	-	-	-
labor	-	-	-	-
mpg	1	-	16	-
rice	-	-	-	-
servo	-	100	-	-
strikes	-	-	4	1

Table A6: Number of random rotations of the data for difference between obliqueBART's and rotated method's MSE to be statistically insignificant. Model and data combinations with "-" had MSE's that were larger than obliqueBART, even with 200 random data rotations.

Table A7: Number of random rotations of the data for difference between obliqueBART's and rotated method's accuracies to be statistically insignificant. Model and data combinations with "-" had smaller accuracies than obliqueBART, even with 200 random data rotations.

data	rotERT	rotBART	rotXGB	rotRF
banknote	1	4	4	-
blood transfusion	-	-	-	4
breast cancer diag.	-	-	-	-
breast cancer	1	1	4	1
breast cancer prog.	1	1	1	1
climate crashes	1	-	-	4
connectionist sonar	-	1	1	-
credit approval	1	4	1	1
echocardiogram	1	1	16	1
fertility	4	1	16	4
german credit	4	1	4	-
hepatitis	16	-	1	4
ILPD	1	1	4	1
ionosphere	-	-	50	1
ozone1	-	1	1	-
ozone8	-	-	-	-
parkinsons	-	1	1	-
planning relax	-	16	-	-
qsar bio.	-	-	-	-
seismic bumps	-	1	1	-
spambase	-	-	-	-
spectf heart	4	1	1	4

B Metropolis-Hastings acceptance probabilities

Grow move. Suppose we are updating the *m*-th decision tree $(\mathcal{T}_m, \mathcal{D}_m) = (\mathcal{T}, \mathcal{D})$. Further suppose that we formed the proposal $(\mathcal{T}^*, \mathcal{D}^*)$ by growing $(\mathcal{T}, \mathcal{D})$ from an existing leaf nx at depth d(nx) and then drawing a new rule rule to associate with nx in $(\mathcal{T}^*, \mathcal{D}^*)$. Let $q(\text{rule}|\mathcal{T}, \mathcal{D})$ denote the proposal probability of drawing rule at nx. Additionally, let $nleaf(\cdot)$ and $nnog(\cdot)$ count the number of leaf nodes and decision nodes with no grandchildren in a tree. The acceptance probability of a grow move decomposes the product of three terms.

$$\begin{aligned} \alpha(\mathcal{T}, \mathcal{D} \to \mathcal{T}^{\star}, \mathcal{D}^{\star}) &= \frac{\alpha(1 + d(\mathbf{nx}))^{-\beta} \left[1 - \alpha(2 + d(\mathbf{nx}))^{-\beta}\right]^2}{1 - \alpha(1 + d(\mathbf{nx}))^{-\beta}} \times \frac{\mathbf{nleaf}(\mathcal{T})}{\mathbf{nnog}(\mathcal{T}^{\star})} \\ &\times \tau^{-1} \times \left(\frac{P_{\mathbf{nxl}}P_{\mathbf{nxr}}}{P_{\mathbf{nx}}}\right)^{-\frac{1}{2}} \times \exp\left\{\frac{\Theta_{\mathbf{nxl}}^2}{2P_{\mathbf{nxl}}} + \frac{\Theta_{\mathbf{nxr}}^2}{2P_{\mathbf{nxr}}} - \frac{\Theta_{\mathbf{nx}}}{2P_{\mathbf{nx}}}\right\} \end{aligned}$$
(B1)
$$&\times \frac{p(\mathbf{rule}|\mathcal{T}^{\star})}{q(\mathbf{rule}|\mathcal{T})}. \end{aligned}$$

The terms in the first two lines of Equation (B1) respectively compare the complexity (i.e., depth) and overall fit to the partial residual \mathbf{R} of $(\mathcal{T}^*, \mathcal{D}^*)$ and $(\mathcal{T}, \mathcal{D})$. More specifically, the term in second line tends to be larger than one whenever splitting the tree at \mathbf{nx} along \mathbf{rule} yields a better fit to the current partial residual than not splitting the tree at \mathbf{nx} . The term in the final is the ratio between the prior and proposal probability of drawing the rule \mathbf{rule} . When we draw \mathbf{rule} from the prior, the MH acceptance probability depends only on terms that compare the fit and complexity of the two trees. However, if the proposal distribution is much more sharply concentrated around \mathbf{rule} than the prior, this term will artificially deflate the acceptance probability.

Prune move. Suppose instead that we form $(\mathcal{T}^*, \mathcal{D}^*)$ by removing leafs nxl and nxr and turning their common parent nx into a leaf. Let **rule** denote the rule associated with nx in $(\mathcal{T}, \mathcal{D})$. The acceptance probability of a prune move is

$$\begin{aligned} \alpha(\mathcal{T}, \mathcal{D} \to \mathcal{T}^{\star}, \mathcal{D}^{\star}) &= \frac{1 - \alpha(1 + d(\mathbf{nx}))^{-\beta}]}{\alpha(1 + d(\mathbf{nx}))^{-\beta} \left[1 - \alpha(2 + d(\mathbf{nx}))^{-\beta}\right]^2} \times \frac{\mathbf{nnog}(\mathcal{T})}{\mathbf{nleaf}(\mathcal{T}^{\star})} \\ &\times \tau \times \left(\frac{P_{\mathbf{nx}}}{P_{\mathbf{nx}\mathbf{l}}P_{\mathbf{nx}\mathbf{r}}}\right)^{-\frac{1}{2}} \times \exp\left\{\frac{\Theta_{\mathbf{nx}}^2}{2P_{\mathbf{nx}}} - \frac{\Theta_{\mathbf{nx}\mathbf{l}}^2}{2P_{\mathbf{nx}\mathbf{l}}} - \frac{\Theta_{\mathbf{nx}\mathbf{r}}^2}{2P_{\mathbf{nx}\mathbf{r}}}\right\} \\ &\times \frac{q(\mathbf{rule}|\mathcal{T}^{\star}, \mathcal{D}^{\star})}{p(\mathbf{rule}|\mathcal{T}^{\star}, \mathcal{D}^{\star})}. \end{aligned}$$
(B2)