

# The Cost of Replicability in Active Learning

Rupkatha Hira\*  
rupkatha@upenn.edu

Dominik Kau\*  
dominikk@upenn.edu

Jessica Sorrell†  
jess@jhu.edu.

## Abstract

Active learning aims to reduce the required number of labeled data for machine learning algorithms by selectively querying the labels of initially unlabeled data points. Ensuring the replicability of results, where an algorithm consistently produces the same outcome across different runs, is essential for the reliability of machine learning models but often increases sample complexity. This report investigates the cost of replicability in active learning using the CAL algorithm, a classical disagreement-based active learning method. By integrating replicable statistical query subroutines and random thresholding techniques, we propose two versions of a replicable CAL algorithm. Our theoretical analysis demonstrates that while replicability does increase label complexity, the CAL algorithm can still achieve significant savings in label complexity even with the replicability constraint. These findings offer valuable insights into balancing efficiency and robustness in machine learning models.

## 1 Introduction

Modern machine learning techniques have demonstrated an impressive ability to improve model performance by training on increasing amounts of data. While unlabeled training data is abundant for many applications (e.g., text and image data sourced from the internet), obtaining large quantities of labeled data, required for classification and prediction tasks, can be prohibitively costly. For example, accurately labeling diagnostic imaging data requires medical expertise, so curating datasets for training medical risk predictors requires a great deal of clinician time and effort.

In response to these challenges, active learning has emerged as a powerful approach to reduce the number of labeled samples required to learn a good model [Angluin \[1988\]](#), [Cohn et al. \[1994b\]](#). Active learning algorithms selectively query the labels of the data points that are most informative, while also leveraging unlabeled data to learn.

A key challenge in active learning, as with any learning framework, is ensuring the stability of results, which is crucial for the robustness and reliability of machine learning models. Stability, in the context of machine learning, refers to the insensitivity of an algorithm to perturbations in its training data. Informally, stability ensures that models do not overfit their training data, and a variety of stability notions have been studied for the purposes of guaranteeing generalization to unseen data and privacy-preservation of training data.

In this work we consider the strong stability notion of *replicability*, introduced in [Impagliazzo et al. \[2022\]](#). Replicability requires that running a learning algorithm twice, on two datasets drawn i.i.d. from the same distribution and with shared internal randomness across both runs, yields identical models with high probability (over the samples and internal randomness). Replicable learning algorithms not only generalize well under adaptive data analysis [Impagliazzo et al. \[2022\]](#), but they also enable verification of experiments in machine

---

\*Department of Computer and Information Sciences, University of Pennsylvania.

†Department of Computer Science, Johns Hopkins University. A substantial portion of the work for this project was completed while the author was at the University of Pennsylvania.

learning. By publishing the randomness used to train a model, another team of researchers can obtain the same model, using their own data, removing ambiguity in whether or not a replication effort has been successful. These properties come at the cost of increased sample complexity, however. In the case of PAC learning, it is known that the sample complexity of replicable learners depends on Littlestone dimension, as opposed to VC dimension as in non-replicable PAC-learning [Impagliazzo et al. \[2022\]](#), [Ghazi et al. \[2021b\]](#).

Since active learning aims to reduce the labeled sample complexity and replicability tends to increase it, we aim to investigate the cost of replicability in active learning. Our goal is to demonstrate that active learning can still lead to savings in label complexity even with the additional requirement of replicability.

## 1.1 Our Results

We give the first replicable algorithms for active learning of finite hypothesis classes, in both the realizable and agnostic setting. The sample complexity bounds for our replicable algorithms show an improvement in sample complexity over passive learning analogous to known improvements from active learning for non-replicable algorithms. More precisely, for target error rate  $\varepsilon$ , the sample bounds for our realizable algorithm has only logarithmic dependence on  $1/\varepsilon$ . For replicable passive learning, this dependence is linear, and so this represents a significant improvement in accuracy dependence. In the agnostic setting, our replicable active learning algorithm instead has a sample complexity dependence on  $(\nu/\varepsilon)^2$ , where  $\nu$  is the error of the optimal hypothesis in the class  $C$ . While the dependence on  $1/\varepsilon$  is technically still quadratic for our algorithm, as it is for the replicable passive agnostic learning algorithm of [Bun et al. \[2023\]](#), we note that when the optimal error  $\nu$  is quite close to the target error  $\varepsilon$ , this still represents a significant improvement in accuracy dependence, and therefore we do still improve over passive replicable learning in both realizable and agnostic cases.

Similarly to [Cohn et al. \[1994a\]](#), [Balcan et al. \[2006\]](#), [Hanneke \[2007\]](#), we instead obtain a sample complexity dependence on the *disagreement coefficient*  $\Theta$  of a hypothesis class  $C$  for distribution  $D$ . We formally define the disagreement coefficient in Section 2, but informally, the disagreement coefficient is a measure of the probability of disagreement among hypotheses in a class  $C$  that are within some error ball centered on the optimal hypothesis in  $C$ . A small disagreement coefficient means that relatively few labeled samples are needed to rule out hypothesis that are far from optimal, with the caveat that these samples should be points on which hypotheses in  $C$  disagree. Active learning allows us to selectively query such points, and therefore obtain sample complexities dependent on  $\Theta$  and only logarithmically on  $1/\varepsilon$  (or quadratically on  $\nu/\varepsilon$  in the agnostic case). The sample complexity dependence on  $\Theta$  we obtain for our replicable active learning algorithms is analogous to those in [Cohn et al. \[1994a\]](#), [Balcan et al. \[2006\]](#), [Hanneke \[2007\]](#): linear dependence in the realizable case, and quadratic in the agnostic.

## 1.2 Related Work

As mentioned before, our work is primarily based on concepts introduced in [Cohn et al. \[1994a\]](#), [Impagliazzo et al. \[2022\]](#) and [Bun et al. \[2023\]](#). It is to be noted that the CAL algorithm given in [Cohn et al. \[1994a\]](#) was formalized with theoretical bounds and extended by several researchers, notably in [Balcan \[2015\]](#), [Dasgupta et al. \[2007\]](#) and [Hanneke et al. \[2014\]](#).

[Castro and Nowak \[2008\]](#) formalized the achievable limits in active learning using minimax analysis techniques. The CAL algorithm was originally proposed for the realizable setting. [Dasgupta et al. \[2007\]](#) extended the CAL algorithm to be applicable in the agnostic setting, and showed that with certain assumptions their extension of the CAL algorithm achieved asymptotic label complexity improvements. Other active learning techniques have since

been proposed for the agnostic setting, notably, the  $A^2$  algorithm introduced in [Balcan et al. \[2006\]](#), which was the first active learning algorithm to achieve  $\varepsilon$ -optimal performance where the underlying distribution has arbitrary noise.

In the context of replicability, it is worth noting that a closely related term is used in literature for differential privacy, called “stability”. This has been studied extensively on its own in [Bun et al. \[2020\]](#), [Ghazi et al. \[2021a\]](#), [Ghazi et al. \[2021b\]](#), etc., as well as in relation to replicability in [Chase et al. \[2023\]](#). In [Bun et al. \[2020\]](#), the notion of “global stability” was introduced and its equivalence to differential privacy was proved. In general, global stability is a stricter requirement than replicability, since it does not allow the assumption of shared internal randomness, unlike replicability. Hence it is not immediately clear that our techniques can be directly extended to satisfy the definition of stability. We leave this as an interesting open question.

While replicability for active learning specifically is a novel work to the best of our knowledge, there has been some work done to achieve differential privacy in active learning ([Balcan and Feldman \[2013\]](#), [Bittner et al. \[2020\]](#), [Ghassemi et al. \[2016\]](#)). The connection between privacy and replicability was studied in [Bun et al. \[2023\]](#), but the equivalence between the two was established only for statistical tasks in the batch setting. Hence, it is not immediately clear how to leverage this equivalence to obtain replicable learning algorithms from private ones in the active learning context.

Moreover, the transformation of a private algorithm to a replicable one is not necessarily computationally efficient. Our work gives algorithms that are efficient for finite hypothesis classes, and hence give a more practical result than what would follow from the known connections between privacy and replicability, even if those connections held in the active learning setting.

### 1.3 Organization

The structure of this paper is as follows. In [Section 2](#), we introduce the theory of active learning, followed by the concept of replicability in machine learning. In [Section 3](#), we propose an algorithm for replicable active learning in the realizable setting and analyze its convergence. In [Section 4](#), we adapt the algorithm of [Section 3](#) to the agnostic setting and provide an analysis. Finally, we conclude with suggestions for future work.

## 2 Background

### 2.1 Active Learning Theory

We work in the PAC learning framework of [Valiant \[1984\]](#). Fix a domain  $X$ , a binary label space  $Y = \{0, 1\}$ , a concept class  $C$  of hypotheses  $h : X \rightarrow Y$  and define the ground truth or target function as  $c \in C$ . Algorithm  $\mathcal{A}$  is said to be a PAC learner for  $C$  if there exists a function  $n(\varepsilon, \delta)$ , polynomial in  $\frac{1}{\varepsilon}, \frac{1}{\delta}$ , such that for every distribution  $D$  over  $X$  and every  $\varepsilon$  and  $\delta > 0$ , given  $n(\varepsilon, \delta)$  samples  $x \in X$  drawn i. i. d. from  $D$  and labels  $y = c(x) \in Y$ ,  $\mathcal{A}$  outputs a hypothesis  $h \in C$  such that  $\text{err}_D(h) = \Pr_{x \sim D} [h(x) \neq y] < \varepsilon$ , except with probability  $\delta$  over the choice of samples.

In the agnostic setting, the ground truth is not a hypothesis in  $C$ . The learning algorithm  $\mathcal{A}$  will return a hypothesis  $h$  whose error does not exceed the error rate  $\nu$  by more than  $\varepsilon$ . Here,  $\nu$  — sometimes labeled as the noise rate — is the error rate of the best hypothesis  $h^* = \text{argmin}_{h \in C} \text{err}(h)$ .

Active learning is the field of machine learning that deals with algorithms that can ask questions or queries. The aim of these algorithms is to improve the sample – and especially label – complexity of a learner over their passive equivalent. This is especially useful for tasks

where the unlabeled sample points are easily accessible but the labeling requires additional (e. g. computational or manual) effort. Examples of this are image classification and speech recognition.

The field of active learning can be further subdivided based on how queries are contrived and how points are sampled. Algorithms that select queries via the query by disagreement principle base their queries on the disagreement of all hypotheses that are still considered. Stream-based selective sampling encompasses algorithms that receive one sample point at a time and determine for each point if they want to request a label or not. [Settles \[2012\]](#)

### 2.1.1 Disagreement Coefficient

The set of  $x \in X$  on which at least two hypotheses  $h$  from a version space  $V \subseteq C$  disagree is defined as

$$DIS(V) = \{x \in X \mid \exists h_1, h_2 \in V \text{ s. t. } h_1(x) \neq h_2(x)\}.$$

In the following, this set is referred to as the disagreement region or set. The respective probability of sampling an  $x$  in the disagreement region is

$$\Delta_D(V) = \Pr_{x \sim D} [x \in DIS(V)]$$

with probability distribution  $D$ . The distance metric for two hypotheses  $h_1, h_2$

$$d_D(h_1, h_2) = \Pr_{x \sim D} [h_1(x) \neq h_2(x)]$$

is used to define a ball around a hypothesis

$$B_D(h, \varepsilon) = \{h' \in C \mid d_D(h, h') \leq \varepsilon\}.$$

The ball  $B_D(c, \varepsilon)$  where  $c$  is the target function includes all hypotheses with an error rate of at most  $\varepsilon$ . Then,  $\Delta_D(B_D(c, \varepsilon))$  is the probability of sampling a point from distribution  $D$  on which at least two hypotheses with an error rate of at most  $\varepsilon$  disagree. The disagreement coefficient is defined as

$$\Theta_D = \sup_{\varepsilon > 0} \frac{\Delta_D(B_D(c, \varepsilon))}{\varepsilon}$$

and describes the maximum aforementioned probability normalized by  $\varepsilon$ . Intuitively, this is a measure of how many points have to be sampled to improve upon a set of hypotheses with an error rate of at most  $\varepsilon$ .

This becomes clear when considering the worst case round of the CAL algorithm, which will be explained in the next section. It is clear that the worst case occurs when all points in the current disagreement region have to be sampled to remove all hypotheses with an error rate greater than  $\varepsilon$ . Thus, consider the case where the target function and  $n$  additional hypotheses remain in the version space. Each of the  $n$  hypotheses makes a mistake only on a single point that is sampled with a probability of  $\frac{1}{n}$ . Then, the disagreement region has a probability mass of  $n \cdot \frac{1}{n} = 1$ , and the disagreement coefficient for the critical error rate  $\frac{1}{n}$  is  $n$  – the number of points that have to be sampled.

In the following the subscript  $D$  will be omitted from the introduced variables for succinctness if the respective probability distribution is clear from context.

### 2.1.2 CAL Algorithm

The CAL algorithm, which was first proposed by and named after [Cohn et al. \[1994a\]](#) is based on the concept of query by disagreement and is used for learning in the realizable case. The algorithm is given in [algorithm 1](#) as pseudo-code. Despite the pooling of points in each round  $r$ , the algorithm is categorized as a stream-based selective sampling algorithm.

The choice over requesting a label depends on whether a given point is in the disagreement region. This is equivalent to sampling from an alternate probability distribution  $D_r$  that is obtained by conditioning on the inclusion in the disagreement region. In this round-based formulation the probability mass of the disagreement region is at least halved in each round. The exit condition of the loop ensures that all hypotheses in the final version space will have an error rate smaller than  $\varepsilon$ . This results from the fact that the target function  $c$  is never eliminated and no hypothesis may deviate more than  $\varepsilon$  from the ground truth. Furthermore, it follows that the number of rounds is  $\mathcal{O}(\log 1/\varepsilon)$ .

A detailed label complexity analysis of such a disagreement region based algorithm in terms of the disagreement coefficient  $\Theta$  was first derived in [Balcan et al. \[2006\]](#). The label complexity for a finite hypothesis class as given by [Hsu \[2010\]](#) is

$$\mathcal{O}\left(\log \frac{1}{\varepsilon} \cdot \Theta \log \frac{|C| \log \frac{1}{\varepsilon}}{\delta}\right). \quad (1)$$

Here, the first factor accounts for the number of rounds that the CAL algorithm will run for and the second factor is the number of points  $k$  that are sampled in each round. Compared to the sample complexity of a passive learner [Kearns and Vazirani \[1994\]](#)

$$\mathcal{O}\left(\frac{1}{\varepsilon} \log \frac{|C|}{\delta}\right), \quad (2)$$

the CAL algorithm yields an exponential improvement in label complexity with respect to the dependence on  $\varepsilon$ , assuming that the disagreement coefficient is finite.

---

**Algorithm 1** CAL algorithm

---

**input:**  $\delta, \varepsilon$

- 1: Set sample size  $k = \mathcal{O}\left(\Theta \log \frac{|C| \log \frac{1}{\varepsilon}}{\delta}\right)$
  - 2: Initialize version space  $V = C$
  - 3: **while**  $\Delta(V) > \varepsilon$  **do**
  - 4:   Sample  $k$  points  $x_1, \dots, x_k$  from  $DIS(V)$
  - 5:   Query labels  $y_1, \dots, y_k$  for sampled points
  - 6:   Update  $V \leftarrow \{h \in V : \forall i \in [k] : h(x_i) = y_i\}$
  - 7: **end while**
  - 8: **return** Any  $h \in V$
- 

### 2.1.3 $A^2$ Algorithm

The  $A^2$  algorithm was first proposed by [Balcan et al. \[2006\]](#), as the first agnostic active learning algorithm. It can be thought of as a robust version of the CAL algorithm that allows for noise. It is a disagreement-based active learning algorithm that was shown to work in an agnostic setting with no assumptions about the mechanism producing noise. All it needs access to is a stream of examples drawn i.i.d. from some fixed distribution.

The algorithm is given in [algorithm 2](#) as pseudo-code. This pseudocode is chosen from [Balcan \[2015\]](#), over other flavors of the algorithm as depicted in [Balcan et al. \[2006\]](#) and ..., for the sake of simplicity.

To work in the Agnostic setting, the  $A^2$  algorithm must be more conservative than the CAL algorithm. The rejection of bad hypotheses based on disagreement over a single example can no longer be a valid step, since it would risk rejecting the best hypothesis with a non-zero noise rate. Instead, in each round it estimates the distributional lower and upper bounds, and eliminates all hypotheses from the disagreement region whose lower bound is greater than the minimum estimated upper bound. Similar to the CAL algorithm, the probability mass of the disagreement region is at least halved in each round. Since exit condition of the

loop is relatively weaker, the algorithm concludes with one last step where a certain number of points are all labelled and the hypothesis from the remaining version space which has the lowest estimated error is finally chosen. The error of the final hypothesis is provably smaller than  $\nu + \varepsilon$  where  $\nu$  is the noise rate, or the true error of the ground truth.

It follows from the exit condition that the number of rounds in the loop is  $\mathcal{O}(\log 1/\Theta\nu)$ .

The label complexity for a finite hypothesis class as given by [Hanneke \[2007\]](#) is

$$\mathcal{O}\left(\Theta^2 \log \frac{1}{\Theta\nu} \left(\frac{\nu^2}{\varepsilon^2} + 1\right) \left(\log |C| + \log \frac{1}{\delta}\right)\right). \quad (3)$$

Compared to the sample complexity of a passive agnostic (PAC) learner in [Kearns and Vazirani \[1994\]](#)

$$\mathcal{O}\left(\frac{1}{\varepsilon^2} \left(\log |C| + \frac{1}{\delta}\right)\right), \quad (4)$$

the CAL algorithm yields an exponential improvement in label complexity with respect to the dependence on  $\varepsilon$ , assuming that the disagreement coefficient is finite, and the noise rate is small enough.

---

### Algorithm 2 $A^2$ algorithm

---

**input:**  $\nu, \delta, \varepsilon$

- 1: Initialize  $V_i = C$ ,  $k = \tilde{O}(\Theta^2 d)$ ,  $k' = \tilde{O}(\Theta^2 d \nu^2 / \varepsilon^2)$ ,  $\delta' = \delta / (1 + \lceil \log(\frac{1}{8\Theta\nu}) \rceil)$ .
  - 2: **while**  $\Delta(V_i) \geq 8\Theta\nu$  **do**
    - (a) Let  $D_i$  be the conditional distribution  $D$  given that  $x \in DIS(V_i)$ .
    - (b) Sample  $k$  iid labeled examples from  $D_i$ . Denote this set by  $S_i$ .
    - (c) Update  $V_{i+1} = \{h \in V_i : LB(S_i, h, \delta') \leq \min_{h' \in H} UB(S_i, h', \delta')\}$ .
  - 3: **end while**
  - 4: Sample  $S$  of  $k'$  points from  $D_i$ .
  - 5: **return**  $\arg \min_{h \in V_i} \text{err}_S(h)$
- 

## 2.2 Replicability in Learning

The notion of replicability we use in our work was introduced by [Impagliazzo et al. \[2022\]](#), to define randomized learning algorithms that are stable with high probability over different samples from the same underlying distribution. Following is the definition of replicability introduced by [Impagliazzo et al. \[2022\]](#), that we will be going by in our paper.

A randomized algorithm  $\mathcal{A}(S; b)$  is replicable if there exists a function  $m_0 : \mathbb{R} \rightarrow \mathbb{N}$  such that for all  $\rho > 0$ , and any  $m > m_0(\rho)$

$$\Pr_{S_1, S_2, b} [\mathcal{A}(S_1; b) = \mathcal{A}(S_2; b)] \geq 1 - \rho,$$

where  $S_1$  and  $S_2$  denote samples of size  $m$  drawn i. i. d. from  $D$ , and  $b$  denotes a random binary string representing the internal randomness used by  $\mathcal{A}$ . We will call learning algorithms that are simultaneously replicable and PAC learners *replicable learning algorithms*.

**Replicable Statistical Query** We have used the rSTAT subroutine developed in the paper to design our Naive-ReplicAL algorithm. rSTAT is a replicable simulation of a statistical query oracle.

Statistical Query was defined by [Kearns \[1998\]](#) using the query function  $\phi = X \rightarrow [0, 1]$ , such that with probability  $1 - \delta$  a mechanism  $M$  answers  $\phi$  with tolerance  $\tau \in (0, 1)$  over distribution  $D$  over  $X$  if  $a \leftarrow M$  satisfies  $a \in [\mathbb{E}_{x \sim D}[\phi(x)] \pm \tau]$ . Such estimation of  $\phi$  by  $M$  is hereafter referred to as  $\tau$ -estimation.

$\text{rSTAT}_{\rho,\tau,\phi}(S)$  is such a mechanism that takes in parameters  $\rho$  (replicability parameter),  $\tau$  (tolerance parameter) and  $\phi$  (the query), and  $\rho$ -replicably gives a  $\tau$ -estimation of the query  $\phi$  over sample  $S$  with high probability  $1 - \delta$ .

The sample complexity of a single query to  $\text{rSTAT}$  is shown to be

$$k_{\text{rSTAT}} = \mathcal{O}\left(\frac{\log \frac{1}{\delta}}{\tau^2(\rho - 2\delta)^2}\right) \quad (5)$$

We have used the  $\text{rSTAT}$  subroutine as a blackbox, replicably estimating the error of a hypothesis on sample  $S$ .

**Replicable Learner for Finite Classes** To develop our efficient RepliCAL algorithm, we have drawn from the random thresholding trick used to develop a replicable learner for finite hypothesis classes in [Bun et al. \[2023\]](#). The idea is to estimate the risk of each hypothesis in the class  $C$  by standard uniform convergence bounds, choose a random error threshold  $v \in [OPT, OPT + \alpha]$ , and finally output a random  $h \in C$  with empirical error  $\text{err}_S(h) = \frac{1}{|S|} \sum_{(x,y) \in S} \mathbf{1}[h(x) \neq y]$  guaranteed to be at most  $v$ . It was shown in the paper that such random thresholding achieves replicability with high probability when the hypothesis class is finite.

In the realizable case, the required sample complexity for this learner was shown to be

$$\mathcal{O}\left(\frac{\log^2 |C| \log \frac{1}{\rho} + \rho^4 \log\left(\frac{1}{\delta}\right)}{\varepsilon \rho^4}\right) \quad (6)$$

This result was further improved upon with regards to the replicability parameter  $\rho$  by a boosting procedure. Then, the resulting sample complexity for the realizable case is

$$\mathcal{O}\left(\log^3 \frac{1}{\rho} \cdot \frac{\log^2 |C| + \log\left(\frac{1}{\rho\beta}\right)}{\varepsilon \rho^2}\right) \quad (7)$$

In our work we have extended the random thresholding concept to the active learning setting and proved that it leads to replicable learning.

In the last section, we propose an agnostic replicable learner for finite classes, with a label complexity of

$$\tilde{\mathcal{O}}\left(\Theta^2 \left(\log \frac{1}{\Theta\nu} + \frac{\nu^2}{\varepsilon^2}\right) \left(\log \frac{|C|}{\delta} + \frac{\log^2 |C| \log \frac{1}{\rho} \log^4 \frac{1}{\Theta\nu}}{\rho^4}\right)\right). \quad (8)$$

The dependence on  $\rho$  can be brought down by boosting, and the resulting label complexity would be

$$\tilde{\mathcal{O}}\left(\Theta^2 \log^3 \frac{1}{\rho} \left(\log \frac{1}{\Theta\nu} + \frac{\nu^2}{\varepsilon^2}\right) \left(\log \frac{|C|}{\rho\delta} + \frac{\log^2 |C| \log^4 \frac{1}{\Theta\nu}}{\rho^2}\right)\right) \quad (9)$$

## 3 Replicable Active Realizable Learning

### 3.1 Algorithm

Our approach is based on the replicable learning algorithm for finite hypothesis classes given by [Bun et al. \[2023\]](#). In each loop of the RepliCAL algorithm, the version space is updated by thresholding the empirical, conditional error rate based on a fixed, random threshold which is selected at the start. The samples are chosen from the disagreement region equivalently to the original CAL algorithm. After exiting the loop, all hypotheses in the final version space will be randomly reordered. Then, the first hypothesis is returned.

Replicability is achieved by ensuring that for two different runs of the algorithm the final sets of hypotheses are similar and that therefore the same hypothesis will be returned with high probability.

---

**Algorithm 3** RepliCAL algorithm

---

**input:**  $\delta, \varepsilon, \rho$

- 1: Set interval size  $\tau = \mathcal{O}\left(\frac{\rho^2}{\Theta \log |C|}\right)$
  - 2: Set unlabeled sample size  $|T| = \mathcal{O}\left(\frac{\log^2(1/\varepsilon) \log(\log(1/\varepsilon)/\delta)}{\varepsilon^2 \rho^2}\right) = \tilde{\mathcal{O}}\left(\frac{\log(1/\delta)}{\varepsilon^2 \rho^2}\right)$
  - 3: Set sample size  $k = \mathcal{O}\left(\Theta \cdot \frac{\log^2(|C|/\delta) \log \frac{\log \frac{1}{\rho}}{\rho} \log^4 \frac{1}{\varepsilon} + \rho^4 \log \frac{|C| \log \frac{1}{\varepsilon}}{\delta}}{\rho^4}\right)$
  - 4: Initialize version space  $V = C$
  - 5: Select random threshold start value  $v_{\text{init}} \leftarrow_b \left[0, \frac{1}{4\Theta}\right]$
  - 6: Select random threshold  $v \leftarrow \left\{v_{\text{init}} + \frac{3}{2}\tau, v_{\text{init}} + \frac{5}{2}\tau, \dots, v_{\text{init}} + \frac{1}{8\Theta} - \frac{\tau}{2}\right\}$
  - 7: Sample  $|T|$  unlabeled points and define  $T = \{x_1, \dots, x_{|T|}\}$
  - 8: Approximate disagreement region  $\hat{\Delta}(V) = \text{rSTAT}_{\frac{\rho}{2N}, \frac{\varepsilon}{2}, \psi}(T)$
  - 9: **while**  $\hat{\Delta}(V) \geq \frac{\varepsilon}{2}$  **do**
  - 10:   Sample  $k$  points  $x_1, \dots, x_k$  from  $DIS(V)$
  - 11:   Query labels  $y_1, \dots, y_k$  for sampled points
  - 12:   Define set  $S_r = \{(x_1, y_1), \dots, (x_k, y_k)\}$
  - 13:   Estimate conditional error  $\text{err}_{S_r}^{D_r}(h)$  for every  $h \in V$
  - 14:    $V \leftarrow \{h \in V : \text{err}_{S_r}^{D_r}(h) \leq v\}$
  - 15:   Sample  $|T|$  unlabeled points and define  $T = \{x_1, \dots, x_{|T|}\}$
  - 16:   Approximate disagreement region  $\hat{\Delta}(V) = \text{rSTAT}_{\frac{\rho}{2N}, \frac{\varepsilon}{2}, \psi}(T)$
  - 17: **end while**
  - 18: Randomly order all  $h \in V$
  - 19: **return** The first hypothesis in  $V$
- 

### 3.2 Theoretical Analysis

**Theorem 1.** *Let  $C$  be any finite concept class. In the realizable setting, RepliCAL is a replicable active learning algorithm for  $C$  with label complexity:*

$$\mathcal{O}\left(\Theta \log \frac{1}{\varepsilon} \cdot \frac{\log^2 |C| \log \frac{\log \frac{1}{\rho}}{\rho} \log^4 \frac{1}{\varepsilon} + \rho^4 \log \frac{|C| \log \frac{1}{\varepsilon}}{\delta}}{\rho^4}\right). \quad (10)$$

**Lemma 1.** *The RepliCAL algorithm outputs a hypothesis with error  $\leq \varepsilon$  with probability  $1 - \delta$ , and it stops after  $\mathcal{O}(\log \frac{1}{\varepsilon})$  rounds.*

Proof of lemma 1 runs analogous to Balcan [2015]. Letting  $V_r$  denote the hypothesis space at round  $r$ , we will first argue convergence by showing that the distributional size of the disagreement region  $\Delta(V_r)$  will be at least halved with each successive round, i.e.,  $\Delta(V_{r+1}) \leq \Delta(V_r)/2$  with high probability. Let  $V_r^\ominus$  be the set of hypotheses in  $V_r$  with large error

$$V_r^\ominus = \left\{h \in V_r : \text{err}(h) = d(h, c) \geq \frac{\Delta(V_r)}{2\Theta}\right\}.$$

If all hypotheses in this set are removed, the distributional size of the disagreement region will indeed be halved

$$\Delta(V_{r+1}) \leq \Delta\left(B\left(c, \frac{\Delta(V_r)}{2\Theta}\right)\right) \leq \Theta \frac{\Delta(V_r)}{2\Theta} = \frac{\Delta(V_r)}{2}$$



where the definition of the disagreement coefficient was used.

So as long as all high-error hypotheses are removed in each round, the size of the disagreement region is halved, and Algorithm 3 converges in at most  $\mathcal{O}(\log \frac{1}{\varepsilon})$  steps, because the algorithm terminates when  $\Delta(V_r) \leq \varepsilon$ .

We now argue that with high probability, all high-error hypotheses are removed at each round. Note that because we are in the realizable setting,  $\text{err}(h) = \Delta(V_r)\text{err}^{D_r}$  for every  $h$ , and so it follows that if  $\Delta(V_r)\text{err}^{D_r} \geq \frac{\Delta(V_r)}{2\Theta}$ , then we can lower-bound the conditional error  $\text{err}^{D_r} \geq \frac{1}{2\Theta}$ . It therefore suffices to remove all hypotheses with at least this conditional error on the disagreement region.

From algorithm 3 it is clear that since the hypotheses in each round are chosen to fall under a random threshold that is upper-bounded by  $\frac{3}{8\Theta} - \frac{\tau}{2}$ , this upper-bounds the conditional empirical error of the algorithm in each round. By applying Chernoff-Hoeffding bounds for the realizable case, we can bound the probability that any hypothesis with conditional error rate  $\frac{1}{2\Theta}$  has empirical error rate less than  $\frac{3}{8\Theta} - \frac{\tau}{2}$ , for any of the  $N \in \mathcal{O}(\log(1/\varepsilon))$  rounds of the algorithm. We see that the number of labeled points needed in each round to ensure good error estimates for all hypotheses with probability at least  $1 - \frac{\delta}{2N}$  is :

$$\mathcal{O}\left(\Theta \log \frac{|C|N}{\delta}\right). \quad (11)$$

We take the sample for our empirical estimate of conditional error to be greater than this quantity, and so except with probability  $\delta$ , all high-error hypotheses are removed at every round. This guarantees convergence within  $\mathcal{O}(\log(1/\varepsilon))$  rounds, and so in total

$$\mathcal{O}\left(\Theta \log(1/\varepsilon) \log\left(\frac{|C| \log(1/\varepsilon)}{\delta}\right)\right)$$

labeled samples are required for convergence.

It remains to argue accuracy of the final hypothesis. The stop condition  $\Delta(V) \leq \varepsilon$  guarantees that all  $h \in V_N$  have error rate below  $\varepsilon$ . This follows from the fact that in the realizable case, the ground truth  $c$  will never be removed from the hypothesis space because the estimated error rate of the ground truth cannot exceed 0. Since the ground truth  $c$  is never removed, if all hypotheses agree on a point, all of them must classify this point correctly. The size of the disagreement region is approximated with accuracy  $\frac{\varepsilon}{2}$  using a replicable statistical query that succeeds with probability  $1 - \frac{\delta}{2N}$  and replicability parameter  $1 - \frac{\rho}{2N}$  in every round on unlabeled data. The (unlabeled) sample complexity for this query is then

$$\mathcal{O}\left(\frac{N^2 \log \frac{\log 1/\varepsilon}{\delta}}{\varepsilon^2(\rho - 2\delta)^2}\right) = \mathcal{O}\left(\frac{\log^2(1/\varepsilon) \log \frac{\log 1/\varepsilon}{\delta}}{\varepsilon^2(\rho - 2\delta)^2}\right) \quad (12)$$

A union bound over the failure probabilities of the empirical error rate estimation in each round yields an overall failure probability of  $\mathcal{O}(\delta)$ .

**Lemma 2.** *Let the RepliCAL algorithm be run on two different sets of samples  $S^1 = \{S_1^1, \dots, S_N^1\}$  and  $S^2 = \{S_1^2, \dots, S_N^2\}$  drawn from the respective distributions  $\{D_1^1, \dots, D_N^1\}$  and  $\{D_1^2, \dots, D_N^2\}$ , which are obtained by conditioning the distribution  $D$  on the disagreement region of the corresponding round  $(1, \dots, N)$ .*

*Randomly select a threshold start value  $v_{\text{init}} \leftarrow_b [0, \frac{1}{4\Theta}]$  and interval width  $\tau \leq \mathcal{O}\left(\frac{\rho^2}{\Theta \log |C|}\right)$  which should divide  $\frac{1}{8\Theta}$ . Define  $I_i$  to be intervals corresponding to the conditional error rate*

in the last round

$$\begin{aligned}
I_0 &= [v_{\text{init}}, v_{\text{init}} + \tau) \\
I_1 &= [v_{\text{init}} + \tau, v_{\text{init}} + 2\tau) \\
&\vdots \\
I_{\frac{1}{8\Theta\tau}} &= \left[ v_{\text{init}} + \frac{1}{8\Theta} - \tau, v_{\text{init}} + \frac{1}{8\Theta} \right)
\end{aligned}$$

and  $v_i = v_{\text{init}} + \frac{2i+1}{2} \cdot \tau$  be the respective thresholds.

Let

$$\begin{aligned}
H_1^{(i)} &= \{h \in C : \text{err}_{S_1^1}^{D_1^1}(h) \leq v_i \wedge \dots \wedge \text{err}_{S_N^1}^{D_N^1}(h) \leq v_i\} \\
H_2^{(i)} &= \{h \in C : \text{err}_{S_1^2}^{D_1^2}(h) \leq v_i \wedge \dots \wedge \text{err}_{S_N^2}^{D_N^2}(h) \leq v_i\}
\end{aligned}$$

denote the hypotheses with conditional empirical error at most  $v_i$  across the two independent sets of samples  $S^1$  and  $S^2$ , i.e., the ones remaining after the last round.

Then with probability at least  $1 - \frac{\rho}{8}$ , for  $S^1$  and  $S^2$  containing samples of size  $k' = \mathcal{O}\left(\frac{\log \frac{1}{\rho}}{\Theta\tau^2}\right)$  we have:

$$\frac{|H_1^{(i)} \Delta H_2^{(i)}|}{|H_1^{(i)} \cup H_2^{(i)}|} \leq \frac{\rho}{4}.$$

To prove [lemma 2](#), we – analogous to [Bun et al. \[2023\]](#), call a threshold  $v_i$  “bad” if any of the following conditions hold:

1. The  $i$ th interval has too many elements:

$$|I_i| > \frac{\rho}{30} |I_{[i-1]}|.$$

2. The number of elements beyond  $I_i$  increases too quickly:

$$\exists j \geq 1 : |I_{i+j}| \geq e^j |I_{[i-1]}|.$$

and “good” otherwise.

Here,  $|I_i|$  denotes the number of hypotheses whose true risk lies in interval  $I_i$ , and  $|I_{[i]}|$  the number of hypotheses in intervals up through  $I_i$ .

We will be proving the following:

1. If  $v_i$  is a good threshold, then  $H_1^{(i)}$  and  $H_2^{(i)}$  are probably close

$$\Pr_{S_1, S_2} \left[ \frac{|H_1^{(i)} \Delta H_2^{(i)}|}{|H_1^{(i)} \cup H_2^{(i)}|} \leq \frac{\rho}{4} \right] \geq 1 - \frac{\rho}{8}.$$

2. At most a  $\frac{\rho}{8}$  fraction of thresholds are bad.

**Part 1** To prove the first part, we consider three cases in which mistakes can occur.

1. A “bad” hypothesis in the last round with  $\text{err}^{D_N}(h) \in I_{i+j}$  was accepted in every round, i. e., with empirical error smaller than the threshold  $v_i$ .
2. A “good” hypothesis in the last round with  $\text{err}^{D_N}(h) \in I_{i-j}$  was rejected in any round, i. e., with empirical error larger than the threshold  $v_i$ .
3. For any hypothesis in the last round with  $\text{err}^{D_N}(h) \in I_i$ , the empirical error is on the wrong side of the threshold  $v_i$ .

By a Chernoff bound, the probability of a hypothesis with true error rate  $\text{err}^{D_N}(h) \in I_{i+j}, j > 0$  having a conditional empirical error rate less than  $v_i$  in any round  $r$  is at most

$$\Pr \left[ \text{err}_{S_r}^{D_r}(h) \leq v_i \right] \leq e^{-\Omega\left(\frac{j^2 \tau |S_r|}{i+j}\right)} \leq e^{-\Omega(j^2 \tau^2 \Theta k')}$$

where  $k' = |S_r|$ . The probability of the first case occurring is upper bounded by this Chernoff bound for the last round  $r = N$ . We introduce the random variable  $x_i$  that counts the number of hypotheses with  $\text{err}^{D_N}(h) \in I_{i+j}, j > 0$  which cross the threshold  $v_i$  in the last round. Then, the expected value can be bounded by – assuming that the chosen threshold is good

$$\begin{aligned} \mathbb{E}[x_i] &\leq \sum_{j>0} |I_{i+j}| e^{-\Omega(j^2 \tau^2 \Theta k')} \\ &\leq |I_{i-1}| \sum_{j>0} e^{-\Omega(j^2 \log 1/\rho - j)} \leq |I_{i-1}| \sum_{j>0} \rho^{\mathcal{O}(j^2)} \\ &\leq \frac{\rho^2}{30 \cdot 64} |I_{i-1}|. \end{aligned}$$

Here, the second condition for good thresholds and size of the samples  $k$  was used. The last step follows from an asymptotic consideration that holds for small enough constants. Using Markov’s theorem, we conclude that

$$\Pr \left[ x_i \geq \frac{\rho}{30} |I_{i-1}| \right] \leq \frac{\rho}{64}.$$

For the second case, the probability of one good hypothesis – measured by the last round – crossing the threshold in any round is given by a union bound over all rounds. The chance of incorrectly rejecting a good hypothesis is highest in the last round. Therefore, the probability can be upper bounded by

$$\Pr \left[ \text{err}_{S_N}^{D_N}(h) \leq v_i \right] \leq N e^{-\Omega(j^2 \tau^2 \Theta k')}$$

and the expectation of the equivalent to  $x_i$  defined as  $y_i$  is upper bounded by

$$\begin{aligned} \mathbb{E}[y_i] &\leq N \sum_{j>0} |I_{i-j}| e^{-\Omega(j^2 \tau^2 \Theta k')} \\ &\leq |I_{i-1}| N e^{-\Omega(\tau^2 \Theta k')} \leq |I_{i-1}| N \rho^{\mathcal{O}(j^2)}. \end{aligned}$$

Again, we conclude that with probability at least  $1 - \frac{\rho}{64}$  only a fraction of  $\frac{\rho}{30}$  hypotheses will have made a mistake according to case 2.

In the third case, by definition of the first condition of bad thresholds, we directly see that in the worst case the number of hypotheses is upper bounded by the number of hypotheses in the interval

$$|I_i| \leq \frac{\rho}{30} |I_{i-1}|.$$

Thus, in total there will be no more than  $\frac{\rho}{10} |I_{i-1}|$  mistakes made with high probability  $1 - \frac{\rho}{32}$ . Considering two different runs of the algorithm, the symmetric difference of the final

hypothesis sets will be less than  $\frac{\rho}{5}|I_{[i-1]}|$  with high probability at least  $1 - \frac{\rho}{16}$ . Furthermore, the union of the sets is guaranteed to be at least  $(1 - \frac{\rho}{15})|I_{[i-1]}|$  with a failure probability of at most  $1 - \frac{\rho}{32}$  as seen in the analysis of the second case.

Finally, a union bound yields the desired result

$$\Pr_{S^1, S^2} \left[ \frac{|H_1^{(i)} \Delta H_2^{(i)}|}{|H_1^{(i)} \cup H_2^{(i)}|} \leq \frac{\rho}{4} \right] \geq 1 - \frac{\rho}{8}.$$

**Part 2** Now, let us prove that almost all thresholds are good. The structure of the proof is based on lower-bounding the number of hypotheses “contributed” by each of the “bad” intervals, which in turn upper bounds the number of “bad” intervals, since the total number of hypotheses is fixed by the size of the concept class,  $|C|$ .

Let the “bad” intervals be present in  $\ell$  clusters (longest consecutive “bad” intervals bounded by “good” interval(s)), with the  $j^{\text{th}}$  “bad” cluster containing  $t_j$  continuous “bad” intervals. Thus, the total number of “bad” intervals is  $\sum_{j=1}^{\ell} t_j$

First, let’s say the intervals are “bad” by condition 1 of “badness”. Then, by the definition of 1, the  $j^{\text{th}}$  bad cluster increases the number of hypotheses from  $I_{[i_j]}$  by at least  $(1 + \frac{\rho}{30})^{t_j}$

If the intervals are bad by condition 2 of “badness”, the  $j^{\text{th}}$  cluster increases the number of hypotheses (corresponding to the future interval(s) causing them to be “bad” by condition 2), by at least  $e^{t_j}$ . Since  $e > (1 + \frac{\rho}{30})$ , the statement that the  $j^{\text{th}}$  cluster increases the number of hypotheses by “at least”  $(1 + \frac{\rho}{30})^{t_j}$  still holds, for both conditions of “badness”. Since  $|I_0| > 1$ , we can write:

$$|C| \geq \left(1 + \frac{\rho}{30}\right)^{\sum_{j=1}^{\ell} t_j} \tag{13}$$

It follows that the number of “bad” intervals:

$$\sum_{j=1}^{\ell} t_j \leq \mathcal{O}\left(\frac{\log |C|}{\rho}\right) \tag{14}$$

Since  $\tau$  has been chosen such that the total number of intervals is at least  $\mathcal{O}\left(\frac{\log |C|}{\rho^2}\right)$ , the fraction of intervals that are “bad” is  $\mathcal{O}(\rho)$

This is true for each round of our algorithm. If we want to bound the probability of choosing a bad interval in “any” round, we have to take a Union-bound of the probability of bad intervals in each round. By choosing  $\rho' = \frac{\rho}{N}$  where  $\rho$  is the replicability-factor of the parent algorithm, and using an appropriate constant, we can union bound over  $N$  rounds to have the probability over all rounds to be  $\frac{\rho}{8}$ . This requirement of having to choose a smaller  $\rho$  will be accounted for while calculating the label complexity.

Three events can break replicability of the proposed algorithm: A bad interval is randomly selected, the sets  $H_1^{(i)}$  and  $H_2^{(i)}$  are not close or two different random hypotheses are chosen even though the final sets are close. The probabilities of these bad events occurring are  $\frac{\rho}{8}$ ,  $\frac{\rho}{8}$  and  $\frac{\rho}{4}$  respectively. Thus, a union bound yields a failure probability of at most  $\frac{\rho}{2}$ , satisfying  $\rho$ -replicability as required.

**Label Complexity** Finally, bounding the label complexity of the algorithm would conclude the proof of [theorem 1](#). From the proof of [lemma 1](#), we have bounds on the number of samples required for [Algorithm 3](#) to get an error rate of at most  $\varepsilon$  with high probability  $1 - \delta$ , and converge within  $O(\log(1/\varepsilon))$  rounds.

Furthermore, in [lemma 2](#), we have seen the worst case sample complexity for the thresholding to be  $\rho$ -replicable is  $k' = \mathcal{O}\left(\frac{\log \frac{1}{\rho}}{\Theta \tau^2}\right)$ . Since  $\tau \leq \mathcal{O}\left(\frac{\rho^2}{\Theta \log |C|}\right)$ , we can replace  $\tau$  to get sample size as:

$$k' = \mathcal{O}\left(\frac{\Theta \log^2 |C| \log \frac{1}{\rho}}{\rho^4}\right). \quad (15)$$

This is the label complexity required in each round. Hence, the total label complexity required for  $\rho$ -replicability after  $N$  rounds is

$$\mathcal{O}\left(N \cdot \frac{\Theta \log^2 |C| \log \frac{1}{\rho}}{\rho^4}\right).$$

While proving [lemma 2](#), we stated that in order for the algorithm to be  $\rho$ -replicable, the thresholding subroutine has to be run with a lower replicability parameter:  $\frac{\rho}{N}$ , where  $N$  is the number of rounds. Hence, the corresponding label complexity should be corrected to:

$$\mathcal{O}\left(N \cdot \frac{\Theta \log^2 |C| \log \frac{N}{\rho} N^4}{\rho^4}\right).$$

[Lemma 1](#) states that the number of rounds required for convergence is  $\mathcal{O}\left(\log \frac{1}{\varepsilon}\right)$ . Hence, the label complexity is

$$\mathcal{O}\left(\Theta \log \frac{1}{\varepsilon} \cdot \frac{\log^2 |C| \log \frac{\log \frac{1}{\varepsilon}}{\rho} \log^4 \frac{1}{\varepsilon}}{\rho^4}\right). \quad (16)$$

The label complexity required to ensure bounded error as well as replicability can be found by combining ?? and [equation 16](#). The overall complexity thus derived is:

$$\mathcal{O}\left(\Theta \log \frac{1}{\varepsilon} \cdot \frac{\log^2 |C| \log \frac{\log \frac{1}{\varepsilon}}{\rho} \log^4 \frac{1}{\varepsilon}}{\rho^4} + \Theta \log \frac{1}{\varepsilon} \left[\log \frac{|C| \log \frac{1}{\varepsilon}}{\delta}\right]\right). \quad (17)$$

This gives us the required label complexity

$$\mathcal{O}\left(\Theta \log \frac{1}{\varepsilon} \cdot \frac{\log^2 |C| \log \frac{\log \frac{1}{\varepsilon}}{\rho} \log^4 \frac{1}{\varepsilon} + \rho^4 \log \frac{|C| \log \frac{1}{\varepsilon}}{\delta}}{\rho^4}\right), \quad (18)$$

as stated in [theorem 1](#), and concludes the proof.

It can be argued that  $\log \log \frac{1}{\varepsilon}$  is trivial w.r.t. the other terms, and the label complexity thus reduces to

$$\tilde{\mathcal{O}}\left(\Theta \log \frac{1}{\varepsilon} \cdot \frac{\log^2 |C| \log \frac{1}{\rho} \log^4 \frac{1}{\varepsilon} + \rho^4 \log \frac{|C|}{\delta}}{\rho^4}\right). \quad (19)$$

### 3.3 Boosting

The label complexity can be boosted via the procedure proposed in [Impagliazzo et al. \[2022\]](#) and modified in [Bun et al. \[2023\]](#) to improve the dependence on  $\rho$ . The boosting procedure is based on the idea of running the replicable learning algorithm on  $\mathcal{O}\left(\log \frac{1}{\rho}\right)$  different random strings with a constant replicability parameter  $\rho' = 0.01$ . Different sets of samples induce a distribution of hypotheses for each random string. Because of the constant replicability parameter, with high probability at least one of these distributions will have a  $\Omega(1)$  heavy-hitter, i.e. an element that is drawn with extremely high probability. The rHeavy-Hitters algorithm given in [Impagliazzo et al. \[2022\]](#) is used to replicably find a heavy-hitter

hypothesis for which it requires  $\mathcal{O}\left(\frac{\log^3(1/\rho)}{\rho^2}\right)$  samples that are shared between the multiple runs on different random strings.

Setting the failure probability during the repeated running of the replicable learning algorithm to  $\delta' = \delta \cdot \frac{\rho^2}{\log^3(1/\rho)} \approx \mathcal{O}(\delta \cdot \text{poly}(\rho))$  ensures that – by a union bound over all samples – the hypotheses will be good with probability  $1 - \delta$ . Therefore, the  $\log \frac{1}{\delta}$  term of the non-boosted version is changed to  $\log \frac{1}{\rho\delta}$ .

This results in a label complexity of

$$\mathcal{O}\left(\Theta \log \frac{1}{\varepsilon} \log^3 \frac{1}{\rho} \cdot \frac{\log^2 |C| \log \log \frac{1}{\varepsilon} \log^4 \frac{1}{\varepsilon} + \log \frac{|C| \log \frac{1}{\varepsilon}}{\delta \rho}}{\rho^2}\right).$$

Analogous to [equation 19](#), this can be approximated as

$$\tilde{\mathcal{O}}\left(\Theta \log \frac{1}{\varepsilon} \log^3 \frac{1}{\rho} \cdot \frac{\log^2 |C| \log^4 \frac{1}{\varepsilon} + \log \frac{|C|}{\delta \rho}}{\rho^2}\right).$$

### 3.4 Comparison to Replicability in Passive Learning

A direct comparison of the label complexity we got in [equation 19](#) to the one in passive replicable learning by [Bun et al. \[2023\]](#) as stated in [equation 6](#), shows us a clear improvement in the sample complexity, given the hypothesis class and underlying distribution are suitable for active learning in the first place, as signified by a low enough disagreement coefficient  $\Theta$ .

Since  $\frac{1}{\varepsilon}$  asymptotically dominates  $\log^5 \frac{1}{\varepsilon}$ , we see a clear improvement in the part of the complexity corresponding to the cost of replicability. The added complexity because of the cost of the CAL algorithm is independent of  $\rho$ , and was already proven to be an improvement over passive learning complexity in [Balcan \[2015\]](#).

Thus, the overall complexity is a definite improvement over the passive case, proving the intuition that active learning could be a viable solution for the high sample complexity that replicability demands.

## 4 Replicable Active Agnostic Learning

In this section, we introduce the  $\text{Replica}^2$  algorithm ([Algorithm 4](#)) for replicable active learning in the agnostic setting. [Algorithm 4](#) adapts the approach of [Algorithm 3](#) to the agnostic setting, by removing the implicit assumption that there always exists a perfectly consistent hypothesis within the version space  $V$ .

## 4.1 Algorithm

---

**Algorithm 4** *ReplicA<sup>2</sup>* algorithm

---

**input:**  $\delta, \varepsilon, \rho, b$

- 1: Set interval size  $\tau = \mathcal{O}\left(\frac{\rho^2}{\Theta \log |C|}\right)$ ,  $\tau' = \mathcal{O}\left(\frac{\varepsilon \rho^2}{\Theta \nu \log |C|}\right)$
  - 2: Set unlabeled sample size  $|T| = \mathcal{O}\left(\frac{\log^2(1/(\Theta \nu)) \log(\log(1/(\Theta \nu))/\delta)}{\Theta^2 \nu^2 \rho^2}\right) = \tilde{O}\left(\frac{\log(1/\delta)}{\Theta^2 \nu^2 \rho^2}\right)$
  - 3: Set labeled sample size  $k = \mathcal{O}\left(\Theta^2 \log \frac{1}{\Theta \nu} \left(\log \frac{|C| \log \frac{1}{\Theta \nu}}{\delta} + \frac{\log^2 |C| \log \frac{\log \frac{1}{\Theta \nu}}{\rho} \log^4 \frac{1}{\Theta \nu}}{\rho^4}\right)\right)$ ,  
 $k' = \mathcal{O}\left(\Theta^2 \frac{\nu^2}{\varepsilon^2} \left(\log \frac{|C|}{\delta} + \frac{\log^2 |C| \log \frac{\log \frac{1}{\Theta \nu}}{\rho} \log^4 \frac{1}{\Theta \nu}}{\rho^4}\right)\right)$
  - 4: Define query  $\psi(x) = \begin{cases} 1, & x \in \Delta(V) \\ 0, & \text{otherwise} \end{cases}$
  - 5: Initialize version space  $V = C$
  - 6: Select random threshold start value  $v_{\text{init}} \leftarrow_b \left[0, \frac{1}{16\Theta}\right]$
  - 7: Select random threshold  $v \leftarrow_b \left\{v_{\text{init}} + \frac{3}{2}\tau, v_{\text{init}} + \frac{5}{2}\tau, \dots, v_{\text{init}} + \frac{1}{32\Theta} - \frac{\tau}{2}\right\}$
  - 8: Sample  $|T|$  unlabeled points and define  $T = \{x_1, \dots, x_{|T|}\}$
  - 9: Approximate disagreement region  $\hat{\Delta}(V) = \text{rSTAT}_{\frac{\rho}{2(N+1)}, 8\Theta \nu, \psi}(T)$
  - 10: **while**  $\hat{\Delta}(V) \geq 16\Theta \nu$  **do**
  - 11:     Define  $\sigma_r = \frac{2\nu}{\hat{\Delta}(V)} + \frac{1}{16\Theta}$
  - 12:     Sample  $k$  points  $x_1, \dots, x_k$  from  $DIS(V)$
  - 13:     Query labels  $y_1, \dots, y_k$  for sampled points
  - 14:     Define set  $S_r = \{(x_1, y_1), \dots, (x_k, y_k)\}$
  - 15:     Estimate conditional error  $\text{err}_{S_r}^{D_r}(h)$  for every  $h \in V$
  - 16:      $V \leftarrow \{h \in V : \text{err}_{S_r}^{D_r}(h) \leq v + \sigma_r\}$
  - 17:     Sample  $|T|$  unlabeled points and define  $T = \{x_1, \dots, x_{|T|}\}$
  - 18:     Approximate disagreement region  $\hat{\Delta}(V) = \text{rSTAT}_{\frac{\rho}{2(N+1)}, 8\Theta \nu, \psi}(T)$
  - 19: **end while**
  - 20: Select random threshold start value  $v_{\text{init}} \leftarrow_b \left[0, \frac{\varepsilon}{32\Theta \nu}\right]$
  - 21: Select threshold  $v$  in  $\left\{v_{\text{init}} + \frac{3}{2}\tau', v_{\text{init}} + \frac{5}{2}\tau', \dots, v_{\text{init}} + \frac{\varepsilon}{64\Theta \nu} - \frac{\tau'}{2}\right\}$  with the same interval index as before
  - 22: Sample  $|T|$  unlabeled points and define  $T = \{x_1, \dots, x_{|T|}\}$
  - 23: Approximate disagreement region  $\hat{\Delta}(V) = \text{rSTAT}_{\frac{\rho}{2(N+1)}, \frac{\varepsilon}{2}, \psi}(T)$
  - 24: Define  $\sigma' = \frac{2\nu}{\hat{\Delta}(V_r)} + \frac{\varepsilon}{16\Theta \nu}$
  - 25: Sample  $k'$  points  $x_1, \dots, x_{k'}$  from  $DIS(V)$
  - 26: Query labels  $y_1, \dots, y_{k'}$  for sampled points
  - 27: Define set  $S_{N+1} = \{(x_1, y_1), \dots, (x_{k'}, y_{k'})\}$
  - 28: Estimate conditional error  $\text{err}_{S_{N+1}}^{D_{N+1}}(h)$  for every  $h \in V$
  - 29:  $V \leftarrow \{h \in V : \text{err}_{S_{N+1}}^{D_{N+1}}(h) \leq v + \sigma'\}$
  - 30: Randomly order all  $h \in V$
  - 31: **return** The first hypothesis in  $V$
-

## 4.2 Theoretical Analysis

**Theorem 2.** *Let  $C$  be any finite concept class. In the agnostic setting,  $\text{Replica}^2$  is a replicable active learning algorithm for  $C$  with label complexity:*

$$\tilde{\mathcal{O}} \left( \Theta^2 \left( \log \frac{1}{\Theta\nu} + \frac{\nu^2}{\varepsilon^2} \right) \left( \log \frac{|C|}{\delta} + \frac{\log^2 |C| \log \frac{1}{\rho} \log^4 \frac{1}{\Theta\nu}}{\rho^4} \right) \right). \quad (20)$$

**Lemma 3.** *Let  $\nu$  denote the error of the optimal hypothesis in  $C$ . The  $\text{Replica}^2$  algorithm outputs a hypothesis with error  $\leq \nu + \varepsilon$  with probability  $1 - \delta$ , and it stops after  $\mathcal{O}(\log \frac{1}{\Theta\nu})$  rounds.*

Proof of lemma 3 runs analogous to Balcan [2015]. Let  $V_r$  denote the hypothesis space at round  $r$ . The distributional size of the disagreement region  $\Delta(V_r)$  will be at least halved with each successive round  $\Delta(V_{r+1}) \leq \Delta(V_r)/2$  with high probability. Let  $V_r^\Theta$  be the set of hypotheses in  $V_r$  with large error

$$V_r^\Theta = \left\{ h \in V_r : d(h, h^*) \geq \frac{\Delta(V_r)}{2\Theta} \right\}.$$

If all hypotheses in this set are removed, the distributional size of the disagreement region will indeed be halved

$$\Delta(V_{r+1}) \leq \Delta \left( B \left( c, \frac{\Delta(V_r)}{2\Theta} \right) \right) \leq \Theta \frac{\Delta(V_r)}{2\Theta} = \frac{\Delta(V_r)}{2}$$

where the definition of the disagreement coefficient was used.

Since the size of the disagreement region is halved in each round with high probability, and the loop stops when  $\hat{\Delta}(V_r) \leq 16\Theta\nu$ , the convergence would take at most  $\mathcal{O}(\log \frac{1}{\Theta\nu})$  steps, since  $\hat{\Delta}(V_r)$  is an estimate of  $\Delta(V_r)$  with tolerance  $8\Theta\nu$ . The exit condition is again checked by a statistical query on unlabeled data that approximates the size of the disagreement region with an accuracy of  $8\Theta\nu$ . The replicability parameter is  $\frac{\rho}{2(N+1)}$  and the failure probability  $\frac{\delta}{2(N+1)}$  in every round. Thus, the number of unlabeled data points for this estimation is

$$|T| = \mathcal{O} \left( \frac{N^2 \log \frac{\log 1/(\Theta\nu)}{\delta}}{\Theta^2 \nu^2 \rho^2} \right), \quad (21)$$

under the benign assumption that  $2\delta < \rho/2$ .

First, we show that in the round based portion of the algorithm, hypotheses in the set  $V_r^\Theta$  will be removed with high probability. By definition of the loops exit condition we have  $\hat{\Delta}(V_r) \geq 16\Theta\nu$ . We have estimated

From the definition of the distance metric we get

$$\begin{aligned} d(h, h^*) &= \Delta(V_r) \Pr_{x \sim D_r} [h(x) \neq h^*(x)] \\ &\leq \Delta(V_r) [\text{err}^{D_r}(h) + \text{err}^{D_r}(h^*)] \\ &\leq \Delta(V_r) \text{err}^{D_r}(h) + \nu. \end{aligned}$$

Assuming that  $h \in V_r^\Theta$  we get

$$\begin{aligned} \Delta(V_r) \text{err}^{D_r}(h) &\geq d(h, h^*) - \nu \\ \Rightarrow \text{err}^{D_r}(h) &\geq \frac{1}{2\Theta} - \frac{\nu}{\Delta(V_r)} \\ &\geq \frac{1}{2\Theta} - \frac{1}{8\Theta} = \frac{3}{8\Theta} \end{aligned}$$



using  $\frac{1}{\Delta(V_r)} \leq \frac{1}{8\Theta\nu}$ . This in turn implies that the empirical conditional error, which is estimated to within tolerance  $\frac{1}{16\Theta}$ , must be greater than  $\frac{5}{16\Theta}$ .

Recall that the largest value the threshold  $v + \sigma_r$  can take is

$$\frac{2\nu}{\widehat{\Delta}(V_r)} + \frac{3}{32\Theta} - \frac{\tau}{2} < \frac{2\nu}{\widehat{\Delta}(V_r)} + \frac{1}{8\Theta} < \frac{1}{4\Theta}.$$

Therefore

$$\text{err}_{S_r}^{D_r}(h) \geq \text{err}^{D_r}(h) - \frac{1}{16\Theta} \geq \frac{5}{16\Theta} \geq \frac{1}{4\Theta} \geq v + \sigma_r$$

and therefore we will remove  $h$  with high probability  $1 - \frac{\delta}{2(N+1)}$ . The necessary tolerances for the empirical estimates are achieved by sampling

$$\mathcal{O}\left(\Theta^2 \log \frac{|C|N}{\delta}\right)$$

points, yielding estimates within a tolerance of  $\frac{1}{16\Theta}$ . Thus, the total sample complexity for all  $N$  rounds is

$$k = \mathcal{O}\left(N\Theta^2 \log \frac{|C|N}{\delta}\right) \quad (22)$$

The best hypothesis  $h^*$  is never removed from the version space  $V$  with high probability, due to the chosen removal condition threshold of  $\frac{\nu}{\Delta(V_r)} + \frac{1}{8\Theta}$  and accuracy of error estimation  $\frac{1}{8\Theta}$ .

Now we assume that  $\Delta(V_r) \leq 8\Theta\nu$

$$\begin{aligned} \text{err}(h) - \text{err}(h^*) &\leq \Delta(V_r) [\text{err}^{D_r}(h) - \text{err}^{D_r}(h^*)] \\ \varepsilon &\geq 8\Theta\nu [\text{err}^{D_r}(h) - \text{err}^{D_r}(h^*)] \\ &\geq 8\Theta\nu \left[ \text{err}^{D_r}(h) - \frac{\nu}{\Delta(V_r)} \right] \end{aligned}$$

Therefore, it suffices to find hypotheses with  $\text{err}_{S_r}^{D_r}(h) \leq \frac{\nu}{\Delta(V_r)} + \frac{\varepsilon}{16\Theta\nu}$  to find a hypothesis with  $\text{err}(h) \leq \text{err}(h^*) + \varepsilon$ . Estimating the conditional error with an accuracy of  $\frac{\varepsilon}{16\Theta\nu}$  and failure probability of  $\rho/4$  requires a sample set size of

$$\mathcal{O}\left(\Theta^2 \frac{\nu^2}{\varepsilon^2} \log \frac{|C|}{\delta}\right) \quad (23)$$

So overall, combining [equation 22](#) and [equation 23](#) and substituting  $N$  we get that

$$\mathcal{O}\left(\Theta^2 \left( \log \frac{1}{\Theta\nu} \log \frac{|C| \log \frac{1}{\Theta\nu}}{\delta} + \frac{\nu^2}{\varepsilon^2} \log \frac{|C|}{\delta} \right)\right) \quad (24)$$

many labeled samples are required for convergence to a good hypothesis.

**Lemma 4.** *Let the ReplicA<sup>2</sup> algorithm be run on two different sets of samples  $S^1 = \{S_1^1, \dots, S_{N+1}^1\}$  and  $S^2 = \{S_1^2, \dots, S_{N+1}^2\}$  drawn from the respective distributions  $\{D_1^1, \dots, D_{N+1}^1\}$  and  $\{D_1^2, \dots, D_{N+1}^2\}$ , which are obtained by conditioning the distribution  $D$  on the disagreement region  $V_i$  of the corresponding round  $(1, \dots, N+1)$ .*

*Randomly select a threshold start value  $v_{\text{init}} \leftarrow_b [0, \frac{1}{16\Theta}]$  (and again  $v_{\text{init}} \leftarrow_b [0, \frac{\varepsilon}{32\Theta\nu}]$  for the final round  $N+1$ ) and interval width  $\tau \leq \mathcal{O}\left(\frac{\rho^2}{\Theta \log |C|}\right)$  which should divide  $\frac{1}{32\Theta}$  (For the final round the interval width  $\tau' \leq \mathcal{O}\left(\frac{\varepsilon \rho^2}{\Theta \nu \log |C|}\right)$ , which should divide  $\frac{\varepsilon}{64\Theta\nu}$ ). Define  $I_i$  to be*

intervals corresponding to the conditional error rate in the last round

$$\begin{aligned} I_0 &= [v_{\text{init}}, v_{\text{init}} + \tau') \\ I_1 &= [v_{\text{init}} + \tau', v_{\text{init}} + 2\tau') \\ &\vdots \\ I_{\frac{\varepsilon}{64\Theta\nu\tau'}} &= \left[ v_{\text{init}} + \frac{\varepsilon}{64\Theta\nu} - \tau', v_{\text{init}} + \frac{\varepsilon}{64\Theta\nu} \right) \end{aligned}$$

and  $v_i = v_{\text{init}} + \frac{2i+1}{2} \cdot \tau'$  be the respective thresholds.

Let

$$\begin{aligned} H_1^{(i)} &= \left\{ h \in C : \text{err}_{S_1^1}^{D_1^1}(h) \leq v_i + \sigma_1 \wedge \cdots \wedge \text{err}_{S_N^1}^{D_N^1}(h) \leq v_i + \sigma_N \wedge \text{err}_{S_{N+1}^1}^{D_{N+1}^1}(h) \leq v_i + \sigma' \right\} \\ H_2^{(i)} &= \left\{ h \in C : \text{err}_{S_1^2}^{D_1^2}(h) \leq v_i + \sigma_1 \wedge \cdots \wedge \text{err}_{S_N^2}^{D_N^2}(h) \leq v_i + \sigma_N \wedge \text{err}_{S_{N+1}^2}^{D_{N+1}^2}(h) \leq v_i + \sigma' \right\} \end{aligned}$$

denote the hypotheses with conditional empirical error at most  $v_i$  across the two independent sets of samples  $S^1$  and  $S^2$ , i.e., the ones remaining after the last round.

Then with probability at least  $1 - \frac{\rho}{8}$ , for  $S^1$  and  $S^2$  drawn i.i.d. from  $D_r$  and containing samples of size  $\mathcal{O}\left(\frac{\Theta^2 \log^2 |C| \log \frac{1}{\rho} \log^4 \frac{1}{\Theta\nu}}{\rho^4} \left(\frac{1}{\Theta\nu} + \frac{\nu^2}{\varepsilon^2}\right)\right)$  we have:

$$\frac{|H_1^{(i)} \Delta H_2^{(i)}|}{|H_1^{(i)} \cup H_2^{(i)}|} \leq \frac{\rho}{4}.$$

To prove [lemma 4](#), we – analogous to [Bun et al. \[2023\]](#), call a threshold  $v_i$  “bad” if any of the following conditions hold:

1. The  $i$ th interval has too many elements:

$$|I_i| > \frac{\rho}{30} |I_{[i-1]}|.$$

2. The number of elements beyond  $I_i$  increases too quickly:

$$\exists j \geq 1 : |I_{i+j}| \geq e^j |I_{[i-1]}|.$$

and “good” otherwise.

Here,  $|I_i|$  denotes the number of hypotheses whose true risk lies in interval  $I_i$ , and  $|I_{[i]}|$  the number of hypotheses in intervals up through  $I_i$ .

We will be proving the following:

1. If  $v_i$  is a good threshold, then  $H_1^{(i)}$  and  $H_2^{(i)}$  are probably close

$$\Pr_{S_1, S_2} \left[ \frac{|H_1^{(i)} \Delta H_2^{(i)}|}{|H_1^{(i)} \cup H_2^{(i)}|} \leq \frac{\rho}{4} \right] \geq 1 - \frac{\rho}{8}.$$

2. At most a  $\frac{\rho}{8}$  fraction of thresholds are bad.

**Part 1** To prove the first part, we consider three cases in which mistakes can occur.

1. A “bad” hypothesis in the last round with  $\text{err}^{D_{N+1}}(h) - \sigma' \in I_{i+j}$  was accepted in every round, i. e., with empirical error smaller than the threshold  $v_i$ .
2. A “good” hypothesis in the last round with  $\text{err}^{D_{N+1}}(h) - \sigma' \in I_{i-j}$  was rejected in any round, i. e., with empirical error larger than the threshold  $v_i$ .
3. For any hypothesis in the last round with  $\text{err}^{D_{N+1}}(h) - \sigma' \in I_i$ , the empirical error is on the wrong side of the threshold  $v_i$ .

By a Chernoff bound, the probability of a hypothesis with true error rate  $\text{err}^{D_r}(h) - \sigma_r \in I_{i+j}, j > 0$  having a conditional empirical error rate less than  $v_i$  in any round  $r$  is at most

$$\Pr \left[ \text{err}_{S_r}^{D_r}(h) \leq v_i + \sigma_r \right] \leq e^{-\Omega(j^2 \tau^2 |S_r|)} = e^{-\Omega(j^2 \tau^2 k_{rep})}$$

where  $k_{rep} = |S_r|$ . From one round to the next, it gets easier to accept any hypothesis. Hence, the probability of the first case occurring is upper bounded by this Chernoff bound for the last round  $r = N + 1$ . We introduce the random variable  $x_i$  that counts the number of hypotheses with  $\text{err}^{D_{N+1}}(h) - \sigma' \in I_{i+j}, j > 0$  which cross the threshold  $v_i$  in the last round. Then, the expected value can be bounded by – assuming that the chosen threshold is good

$$\begin{aligned} \mathbb{E}[x_i] &\leq \sum_{j>0} |I_{i+j}| e^{-\Omega(j^2 \tau^2 k_{rep})} \\ &\leq |I_{[i-1]}| \sum_{j>0} e^{-\Omega(j^2 \log 1/\rho - j)} \leq |I_{[i-1]}| \sum_{j>0} \rho^{\mathcal{O}(j^2)} \\ &\leq \frac{\rho^2}{30 \cdot 64} |I_{[i-1]}|. \end{aligned}$$

Here, the second condition for good thresholds and size of the samples  $k$  was used. The last step follows from an asymptotic consideration that holds for small enough constants. Using Markov’s theorem, we conclude that

$$\Pr \left[ x_i \geq \frac{\rho}{30} |I_{[i-1]}| \right] \leq \frac{\rho}{64}.$$

For the second case, the probability of one good hypothesis – measured by the last round – crossing the threshold in any round is given by a union bound over all rounds. The chance of incorrectly rejecting a good hypothesis is highest in the first round. Therefore, the probability can be upper bounded by

$$\Pr \left[ \text{err}_{S_{N+1}}^{D_{N+1}}(h) \leq v_i + \sigma' \right] \leq N e^{-\Omega(j^2 \tau^2 k_{rep})}$$

and the expectation of the random variable analogous to  $x_i$  defined as  $y_i$  is upper bounded by

$$\begin{aligned} \mathbb{E}[y_i] &\leq N \sum_{j>0} |I_{i-j}| e^{-\Omega(j^2 \tau^2 k_{rep})} \\ &\leq |I_{[i-1]}| N e^{-\Omega(\tau^2 \Theta k_{rep})} \leq |I_{[i-1]}| N \rho^{\mathcal{O}(j^2)}. \end{aligned}$$

Again, we conclude that with probability at least  $1 - \frac{\rho}{64}$  only a fraction of  $\frac{\rho}{30}$  hypotheses will have made a mistake according to case 2.

In the third case, by definition of the first condition of bad thresholds, we directly see that in the worst case the number of hypotheses is upper bounded by the number of hypotheses in the interval

$$|I_i| \leq \frac{\rho}{30} |I_{[i-1]}|.$$

Thus, in total, there will be no more than  $\frac{\rho}{10}|I_{[i-1]}|$  mistakes made with high probability  $1 - \frac{\rho}{32}$ . Considering two different runs of the algorithm, the symmetric difference of the final hypothesis sets will be less than  $\frac{\rho}{5}|I_{[i-1]}|$  with high probability at least  $1 - \frac{\rho}{16}$ .

Furthermore, the union of the sets is guaranteed to be at least  $(1 - \frac{\rho}{15})|I_{[i-1]}|$  with a failure probability of at most  $1 - \frac{\rho}{32}$  as seen in the analysis of the second case.

Finally, a union bound yields the desired result

$$\Pr_{S^1, S^2} \left[ \frac{|H_1^{(i)} \Delta H_2^{(i)}|}{|H_1^{(i)} \cup H_2^{(i)}|} \leq \frac{\rho}{4} \right] \geq 1 - \frac{\rho}{8}.$$

**Part 2** Proving that almost all thresholds are “good” follows the same argument as in the realizable setting, and we can conclude that the fraction of intervals that are “bad” is  $\mathcal{O}(\rho)$

This is true for each round  $n = 1, 2, \dots, N + 1$  of our algorithm. By choosing  $\rho' = \frac{\rho}{2(N+1)}$  where  $\rho$  is the replicability-factor of the parent algorithm, and using an appropriate constant, we can union bound over  $N$  rounds to have the probability over all rounds to be  $\frac{\rho}{8}$ . Union bounding over the “bad” events gives us a total failure probability of  $\frac{\rho}{2}$ , as in the realizable setting, hence proving  $\rho$ -replicability as required.

**Label Complexity** Finally, bounding the label complexity of the algorithm would conclude the proof of [theorem 2](#). [??](#) gives us the worst-case sample complexity of our algorithm required to get an error rate of at most  $\nu + \varepsilon$  with high probability  $1 - \delta$ .

Furthermore, in [lemma 4](#), we have seen the worst case sample complexity for the thresholding to be  $\rho$ -replicable is  $k_{rep} = \mathcal{O}\left(\frac{\log \frac{1}{\rho}}{\tau^2}\right)$ . Since  $\tau \leq \mathcal{O}\left(\frac{\rho^2}{\Theta \log |C|}\right)$ , we can replace  $\tau$  to get sample size as:

$$k_{rep} = \mathcal{O}\left(\frac{\Theta^2 \log^2 |C| \log \frac{1}{\rho}}{\rho^4}\right). \quad (25)$$

This is the label complexity required in each round. Hence, the total label complexity required for  $\rho$ -replicability after  $N$  rounds is

$$\mathcal{O}\left(N \cdot \frac{\Theta^2 \log^2 |C| \log \frac{1}{\rho}}{\rho^4}\right).$$

While proving [lemma 4](#), we stated that in order for the algorithm to be  $\rho$ -replicable, the thresholding subroutine has to be run with a lower replicability parameter of the order of  $\frac{\rho}{N}$ . Hence, the corresponding label complexity should be corrected to:

$$\mathcal{O}\left(N \cdot \frac{\Theta^2 \log^2 |C| \log \frac{N}{\rho} N^4}{\rho^4}\right).$$

[Lemma 1](#) states that the number of rounds required for convergence is  $\mathcal{O}\left(\log \frac{1}{\Theta \nu}\right)$ . Hence, the label complexity is

$$k_{rep} = \mathcal{O}\left(\Theta^2 \log \frac{1}{\Theta \nu} \cdot \frac{\log^2 |C| \log \frac{\log \frac{1}{\Theta \nu}}{\rho} \log^4 \frac{1}{\Theta \nu}}{\rho^4}\right). \quad (26)$$

To ensure  $\rho$ -replicability in the last round we need  $k'_{rep} = \mathcal{O}\left(\frac{\log \frac{1}{\rho}}{\tau'^2}\right)$  labels. To ensure the same number of intervals, the replicability-constant should be the same as the one before,

$\frac{\rho}{N}$ . Since  $\tau' \leq \mathcal{O}\left(\frac{\epsilon \rho^2}{\Theta \nu \log |C|}\right)$ , we have the label complexity in the last round as

$$k'_{rep} = \mathcal{O}\left(\frac{\Theta^2 \nu^2 \log^2 |C| \log \frac{N}{\rho} N^4}{\epsilon^2 \rho^4}\right) \quad (27)$$

The label complexity required to ensure bounded error as well as replicability can be found by combining [equation 24](#), [equation 26](#) [equation 27](#). The overall complexity thus derived is:

$$\mathcal{O}\left(\Theta^2 \left(\log \frac{1}{\Theta \nu} \log \frac{|C| \log \frac{1}{\Theta \nu}}{\delta} + \frac{\nu^2}{\epsilon^2} \log \frac{|C|}{\delta} + \frac{\log^2 |C| \log \frac{\log \frac{1}{\Theta \nu}}{\rho} \log^4 \frac{1}{\Theta \nu}}{\rho^4} \left(\log \frac{1}{\Theta \nu} + \frac{\nu^2}{\epsilon^2}\right)\right)\right) \quad (28)$$

Or

$$\tilde{\mathcal{O}}\left(\Theta^2 \left(\log \frac{1}{\Theta \nu} + \frac{\nu^2}{\epsilon^2}\right) \left(\log \frac{|C|}{\delta} + \frac{\log^2 |C| \log \frac{1}{\rho} \log^4 \frac{1}{\Theta \nu}}{\rho^4}\right)\right) \quad (29)$$

Applying Boosting to the algorithms using the same setup as in [section 3.3](#), we can reduce this complexity to

$$\tilde{\mathcal{O}}\left(\Theta^2 \log^3 \frac{1}{\rho} \left(\log \frac{1}{\Theta \nu} + \frac{\nu^2}{\epsilon^2}\right) \left(\log \frac{|C|}{\rho \delta} + \frac{\log^2 |C| \log^4 \frac{1}{\Theta \nu}}{\rho^2}\right)\right) \quad (30)$$

It effectively improves the label complexity by having a multiplicative factor of  $\Theta^2$  (for the first  $N$  rounds) and  $\frac{\nu^2}{\epsilon^2}$  (for the last round) instead of the  $\frac{1}{\epsilon^2}$  factor in passive agnostic learning. For distributions which are suitable for active learning (characterized by a low value of  $\Theta$ ), and for problems with a reasonably low noise rate, both these values are much lower than  $\frac{1}{\epsilon^2}$ .

## 5 Conclusions and Future Work

In this work, we presented the first replicable adaptations of two classical active learning algorithms- CAL for the realizable setting and  $A^2$  for the agnostic setting- yielding the RepliCAL and ReplicA<sup>2</sup> algorithms. By integrating replicability through random thresholding and replicable statistical query subroutines, we demonstrated that one can maintain the core label complexity advantages of active learning under the strong stability requirement of replicability.

In the realizable setting for finite hypothesis classes with suitable disagreement coefficients, RepliCAL matches the known dependence on  $\Theta \log 1/\epsilon$  from CAL while introducing only a mild overhead due to replicability. In the agnostic setting, ReplicA<sup>2</sup> leverages the framework of  $A^2$  to handle noise and still achieves notable improvements over naive passive bounds. These results confirm that even under stringent stability notions, leveraging adaptive queries can yield substantial label complexity savings.

Future works could aim at establishing lower bounds on replicable active learning to determine whether the obtained improvements are optimal. Investigating a broader class of active learning algorithms, including those applicable to infinite hypothesis classes or structured prediction tasks, would be valuable. Additionally, studying connections between replicability and other notions of stability, such as differential privacy, and examining the robustness of these algorithms under more complex data distributions are natural directions. Empirical studies will be essential to evaluate these methods in practical scenarios, providing further insights into their reliability and performance in real-world applications.

## References

- Dana Angluin. Queries and concept learning. *Machine learning*, 2:319–342, 1988.
- Maria-Florina Balcan. 10-806 foundations of machine learning and data science, 2015. URL <https://www.cs.cmu.edu/~ninamf/courses/806/lect1116-18.pdf>.
- Maria-Florina Balcan, Alina Beygelzimer, and John Langford. Agnostic active learning. In *Proceedings of the 23rd international conference on Machine learning*, pages 65–72, 2006.
- Maria-Florina F Balcan and Vitaly Feldman. Statistical active learning algorithms. *Advances in neural information processing systems*, 26, 2013.
- Daniel M Bittner, Alejandro E Brito, Mohsen Ghassemi, Shantanu Rane, Anand D Sarwate, and Rebecca N Wright. Understanding privacy-utility tradeoffs in differentially private online active learning. *Journal of Privacy and Confidentiality*, 10(2), 2020.
- Mark Bun, Roi Livni, and Shay Moran. An equivalence between private classification and online prediction. In *2020 IEEE 61st Annual Symposium on Foundations of Computer Science (FOCS)*, pages 389–402. IEEE, 2020.
- Mark Bun, Marco Gaboardi, Max Hopkins, Russell Impagliazzo, Rex Lei, Toniann Pitassi, Satchit Sivakumar, and Jessica Sorrell. Stability is stable: Connections between replicability, privacy, and adaptive generalization. In *Proceedings of the 55th Annual ACM Symposium on Theory of Computing*, pages 520–527, 2023.
- Rui M. Castro and Robert D. Nowak. Minimax bounds for active learning. *IEEE Transactions on Information Theory*, 54(5):2339–2353, 2008. doi: 10.1109/TIT.2008.920189.
- Zachary Chase, Shay Moran, and Amir Yehudayoff. Replicability and stability in learning. *arXiv preprint arXiv:2304.03757*, 2023.
- David Cohn, Les Atlas, and Richard Ladner. Improving generalization with active learning. *Machine learning*, 15:201–221, 1994a.
- David Cohn, Les Atlas, and Richard Ladner. Improving generalization with active learning. *Machine learning*, 15:201–221, 1994b.
- Sanjoy Dasgupta, Daniel J Hsu, and Claire Monteleoni. A general agnostic active learning algorithm. In J. Platt, D. Koller, Y. Singer, and S. Roweis, editors, *Advances in Neural Information Processing Systems*, volume 20. Curran Associates, Inc., 2007. URL [https://proceedings.neurips.cc/paper\\_files/paper/2007/file/8f85517967795eeef66c225f7883bdcb-Pa](https://proceedings.neurips.cc/paper_files/paper/2007/file/8f85517967795eeef66c225f7883bdcb-Pa)
- Mohsen Ghassemi, Anand D Sarwate, and Rebecca N Wright. Differentially private online active learning with applications to anomaly detection. In *Proceedings of the 2016 ACM Workshop on Artificial Intelligence and Security*, pages 117–128, 2016.
- Badih Ghazi, Noah Golowich, Ravi Kumar, and Pasin Manurangsi. Sample-efficient proper pac learning with approximate differential privacy. In *Proceedings of the 53rd Annual ACM SIGACT Symposium on Theory of Computing*, pages 183–196, 2021a.
- Badih Ghazi, Ravi Kumar, and Pasin Manurangsi. User-level differentially private learning via correlated sampling. *Advances in Neural Information Processing Systems*, 34:20172–20184, 2021b.
- Steve Hanneke. A bound on the label complexity of agnostic active learning. In *Proceedings of the 24th international conference on Machine learning*, pages 353–360, 2007.
- Steve Hanneke et al. Theory of disagreement-based active learning. *Foundations and Trends® in Machine Learning*, 7(2-3):131–309, 2014.

- Daniel Joseph Hsu. *Algorithms for active learning*. PhD thesis, UC San Diego, USA, 2010.
- Russell Impagliazzo, Rex Lei, Toniann Pitassi, and Jessica Sorrell. Reproducibility in learning. *CoRR*, 2022.
- Michael Kearns. Efficient noise-tolerant learning from statistical queries. *J. ACM*, 45(6): 983–1006, 11 1998. ISSN 0004-5411. doi: 10.1145/293347.293351.
- Michael J. Kearns and Umesh Vazirani. *An Introduction to Computational Learning Theory*. The MIT Press, 08 1994. ISBN 9780262276863. doi: 10.7551/mitpress/3897.001.0001. URL <https://doi.org/10.7551/mitpress/3897.001.0001>.
- Burr Settles. *Active Learning*. Synthesis Lectures on Artificial Intelligence and Machine Learning. Springer Cham, 1 edition, 2012. ISBN 978-3-031-00432-2. doi: 10.1007/978-3-031-01560-1.
- Leslie G Valiant. A theory of the learnable. *Communications of the ACM*, 27(11):1134–1142, 1984.