

Leveraging Multimodal Methods and Spontaneous Speech for Alzheimer’s Disease Identification

Yifan Gao[†], Long Guo[†], Hong Liu*

College of Computer Science

National Key Laboratory of Fundamental Science on Synthetic Vision

Sichuan University

Chengdu, China

Abstract—Cognitive impairment detection through spontaneous speech offers potential for early diagnosis of Alzheimer’s disease (AD) and mild cognitive impairment (MCI). The PROCESS Grand Challenge, part of ICASSP 2025, focuses on advancing this field with innovative solutions for classification and regression tasks.

In this work, we integrate interpretable features with temporal features extracted from pre-trained models through a multimodal fusion strategy. For the classification task, our model achieved an F1-score of 0.649 in predicting cognitive states (healthy, MCI, dementia). For the regression task, which involves MMSE score prediction, we obtained a root-mean-square error (RMSE) of 2.628. These results led to our team securing the top overall ranking in the competition.

Index Terms—Multimodal, Interpretable Features, Temporal Features

I. INTRODUCTION

Alzheimer’s disease (AD) is a progressive neurodegenerative disorder marked by cognitive impairments in language, speech, and memory. Although incurable, early detection and intervention are essential to slow progression and improve quality of life [1]. Speech-based AD detection methods typically extract audio, semantic, and manually defined features from spontaneous speech, using classifiers for diagnosis [2].

The PROCESS Grand Challenge at ICASSP 2025 focuses on detecting cognitive impairment through speech, targeting early diagnosis of mild cognitive impairment (MCI) and Alzheimer’s disease (AD). It includes a classification task (predicting cognitive states: healthy, MCI, dementia) and a regression task (predicting MMSE scores). PROCESS introduces new tasks evaluating semantic and phonetic fluency alongside the traditional “Cookie Theft” description to improve early detection.

This paper presents our submission to the PROCESS Grand Challenge, combining interpretable semantic and temporal audio features via multimodal fusion. Our method achieved an F1-score of 0.649 and RMSE of 2.628, outperforming the baseline (F1-score 0.550, RMSE 2.985) and securing the top overall ranking.

[†]These authors contributed equally to this work.

*Corresponding author

II. METHODOLOGY

A. Datasets

The PROCESS dataset supports early-stage dementia detection, with each sample consisting of three types of audio tasks: Semantic Fluency Task (SFT), Phonemic Fluency Task (PFT), and Cookie Theft Description (CTD). SFT involves naming as many animals as possible within one minute, while PFT requires participants to generate as many words as possible starting with the letter ‘P’ within one minute. CTD captures a spoken description of the Cookie Theft picture [3]. Each sample includes diagnostic labels, gender, age, and, for some, MMSE scores. The dataset consists of 82 healthy controls (HC), 59 mild cognitive impairment (MCI) cases, and 16 dementia cases, offering a robust foundation for classification and prediction tasks.

B. Preprocessing

For dataset preprocessing, we first completed the MMSE scores by filling missing values with the mean of samples from the same category and further refining them using a generative model. Next, the Whisper-large model was employed to transcribe audio from the test set into text via automatic speech recognition (ASR). Finally, all audio data underwent two steps of processing: Koala’s denoising model was applied for speech enhancement and noise suppression, generating the suppression version ¹; the Falcon model was used for speaker identification to extract and concatenate the audio of the longest speaker ², creating the subtracted version.

C. Features extraction and fusion

1) *Acoustic Features*: Acoustic features are made up of two parts: whisper embeddings and times whisper embeddings.

Whisper Embedding: The Whisper-large model uses a Transformer-based encoder to encode input audio signals into high-dimensional contextual feature vectors, capturing diverse characteristics [4]. In this study, audio was divided into 30-second segments, and features were extracted from each segment using the encoder. The segment-level features were then

¹Koala is available at: <https://picovoice.ai/docs/api/koala-web/>

²Falcon is available at: <https://picovoice.ai/platform/falcon/>

averaged to represent the entire audio, which was subsequently used for classification.

Times Whisper Embedding: Dividing audio into 30-second segments captures only global features, thereby neglecting finer temporal information. To address this, we split the audio into 16 smaller chunks based on the 16,000 Hz sampling rate. Whisper embeddings from each chunk were concatenated to create a time-series-aware representation, referred to as Times Whisper Embedding, minimizing the impact of padding.

2) *Linguistic Features:* Language features are made up of three parts: general features, verbal fluency features, and pause features.

General Features: The data were extracted using the Linguistic Feature Toolkit³, a commonly used Python package in computational linguistics, which calculates 129 features. These features are used to measure the lexical richness and syntactic complexity of the text.

Verbal Fluency Features: For the PFT task, the number of correctly described words starting with the letter "P" is counted. For the SFT task, the number of correctly described animals is counted.

Pause Features: Pause features include duration-related descriptors extracted using a Voice Activity Detection (VAD) [5] algorithm based on energy. It includes 16 descriptors used to describe the lengths of pauses and speech intervals.

3) *Multimodal fusion:* For classification tasks, we use a majority voting approach. Initially, each individual model is evaluated on its respective task using the validation set. Subsequently, we select the top-performing models and perform majority voting to determine the optimal combination based on validation set performance. In contrast, for regression tasks, we utilize an averaging voting method.

III. EXPERIMENTS AND RESULTS

TABLE I Experiment Results of AD Detection

Feature	Task	Model	Val	Test
Baseline	CTD	SVC	0.390	0.550
Whisper Embedding	PFT	A_1 .Logistic	0.492	-
	SFT	A_2 .RF	0.467	-
Times Whisper Embedding	CTD	A_3 .MLP-CA	0.455	-
	SFT	A_4 .MLP-CA	0.513	-
Interpretable Linguistic Feature	CTD	A_5 .RF	0.464	-
	PFT	A_6 .RF	0.512	-
$MV_1(A_1, A_2, A_5, A_6)$			0.607	0.603
$MV_2(A_1, A_2, A_4, A_5, A_6)$			0.618	0.633
$MV_3(A_1, A_2, A_3, A_4, A_5, A_6)$			0.627	0.649

A. Experiment setup

The machine learning models use the default configurations of the classifiers. For the MLP method, 10 random seeds are generated. Each model is trained with a batch size of 32 for a total of 65 epochs, and the best model is recorded and saved.

³LFTK is available at: <https://github.com/brucewlee/lftk>

TABLE II Experiment Results of MMSE Regression

Feature	Task	Model	Val	Test
Baseline	CTD,PFT,SFT	RoBERTa	3.110	2.985
Whisper Embedding	PFT	M_1 .Logistic	2.951	-
	SFT	M_2 .RF	3.196	-
Times Whisper Embedding	PFT	M_3 .MLP-CA	3.257	-
	CTD	M_4 .MLP-CA	3.165	-
Interpretable Linguistic Feature	PFT	M_5 .RF	2.973	-
	CTD	M_6 .RF	2.886	4.655
$AV_1(M_1, M_2, M_3)$			2.585	2.628
$AV_2(M_1, M_2, M_3, M_5)$			2.706	2.723

The validation of our experiments followed a bootstrapping strategy (75% training, 25% validation), where the process was repeated 100 times to ensure variability in the different sets.

B. Experiment results

Tables 1 and 2 show the results of AD detection and MMSE score prediction tasks respectively. The Whisper model and linguistic features performed well in different tasks. This demonstrates that both acoustic models and linguistic models can accurately distinguish between Alzheimer's patients and normal individuals.

After applying voting method, the model's performance improved significantly. The best model achieved 0.649 F1 score in AD detection and an RMSE of 2.628 in MMSE prediction.

IV. CONCLUSION

In this paper, we present our submission for the PROCESS challenge. Our approach outperforms all other models in overall performance and maintains consistent performance across different dataset splits. The innovation in our work lies in the seamless integration of acoustic features and interpretable linguistic features, enhancing the efficacy of Alzheimer's disease detection.

V. ACKNOWLEDGEMENT

This work is partly supported by the National Natural Science Foundation of China under grant U20A20161 and the Fundamental Research Funds for Central Universities under grants SCU2024D055 and SCU2024D059.

REFERENCES

- [1] V. G. Yadav, "The hunt for a cure for alzheimer's disease receives a timely boost," *Science Translational Medicine*, vol. 11, no. 509, p. eaaz0311, 2019.
- [2] K. C. Fraser, J. A. Meltzer, and F. Rudzicz, "Linguistic features identify alzheimer's disease in narrative speech," *Journal of Alzheimer's Disease*, vol. 49, no. 2, pp. 407–422, 2016.
- [3] J. Becker, F. Boller, O. Lopez, J. Saxton, and K. McGonigle, "The natural history of alzheimer's disease: Description of study cohort and accuracy of diagnosis," *Archives of Neurology*, vol. 51, no. 6, pp. 585–594, 1994.
- [4] A. Radford, J. W. Kim, T. Xu, G. Brockman, C. McLeavey, and I. Sutskever, "Robust speech recognition via large-scale weak supervision," 2022, accessed: 2024-12-10. [Online]. Available: <https://cdn.openai.com/papers/whisper.pdf>
- [5] P. A. Pérez-Toro, T. Arias-Vergara, P. Klumpp, T. Weise, M. Schuster, E. Noeth, J. R. Orozco-Arroyave, and A. Maier, "Multilingual speech and language analysis for the assessment of mild cognitive impairment: Outcomes from the taukadi challenge," in *Proc. Interspeech 2024*, 2024, pp. 982–986.